



AD743932

HEMISPHERIC SCAN COVERAGE STUDY

by
Quirino Balzano

RAYTHEON CO. MISSILE SYSTEMS DIVISION
BEDFORD LABORATORIES
Hartwell Road, Bedford, Massachusetts 01730

CONTRACT NO. F19628-70-C-0226
PROJECT NO. 4600
TASK NO. 460010
WORK UNIT NO. 46001001



FINAL REPORT
JANUARY 1970 - DECEMBER 1971
Approved for public release; distribution unlimited.

CONTRACT MONITOR: Allan C. Schell
Microwave Physics Laboratory

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
U S Department of Commerce
Springfield VA 22151

Prepared for

AIR FORCE CAMBRIDGE RESEARCH LABORATORIES
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
Bedford, Massachusetts 01730

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Raytheon Company Missile Systems Division Bedford, Massachusetts 01730		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b. GROUP	
3. REPORT TITLE HEMISPHERIC SCAN COVERAGE STUDY			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Final Scientific January 1970 - December 1971		Approved: 13 March 1972	
5. AUTHOR(S) (Last name, first name, initial) Quirino Balzano			
6. REPORT DATE February 1972		7a. TOTAL NO. OF PAGES 10	7b. NO. OF REFS 8
8a. CONTRACT OR GRANT NO. F19628-70-C-0226		9a. ORIGINATOR'S REPORT NUMBER(S) BR-6862	
b. PROJECT NO. Task, Work Unit Nos. 4600-10-01		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) AFCRL-72-0127	
c. DoD Element 62702F			
d. DoD Subelement 674600			
10. AVAILABILITY/LIMITATION NOTICES A-Approved for public release; distribution unlimited.			
11. SUPPLEMENTARY NOTES TECH, OTHER		12. SPONSORING MILITARY ACTIVITY Air Force Cambridge Research Laboratories (LZ) L. G. Hanscom Field, Bedford, Mass. 01730	
13. ABSTRACT The present report briefly summarizes the studies performed under AFCRL Contract No. F19628-70-C-0226. The objective of the contract is to investigate techniques for achieving hemispheric scan coverage by means of a phased array of elements flush mounted on a cylindrical surface. The studies included a theoretical investigation and an experimental program, the latter having the purpose of verifying the results of the analysis. The theoretical investigation has brought general methods of analyzing infinite periodic and finite cylindrical arrays. The experimental program has proved that the analytical methods give results in close agreement with experimental measurements.			

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Conformal Arrays Cylindrical Arrays						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification

HEMISPHERIC SCAN COVERAGE STUDY

by
Quirino Balzano

RAYTHEON CO. MISSILE SYSTEMS DIVISION
BEDFORD LABORATORIES
Hartwell Road, Bedford, Massachusetts 01730

CONTRACT NO. F19628-70-C-0226
PROJECT NO. 4600
TASK NO. 460010
WORK UNIT NO. 46001001

FINAL REPORT
JANUARY 1970 - DECEMBER 1971
Approved for public release; distribution unlimited.

CONTRACT MONITOR: Allan C. Schell
Microwave Physics Laboratory

Prepared for

AIR FORCE CAMBRIDGE RESEARCH LABORATORIES
AIR FORCE SYSTEMS COMMAND
UNITED STATES AIR FORCE
Bedford, Massachusetts 01730

UNCLASSIFIED

ABSTRACT

The present report briefly summarizes the studies performed under AFCRL Contract No. F19628-70-C-0226.

The objective of the contract is to investigate techniques for achieving hemispheric scan coverage by means of a phased array of elements flush mounted on a cylindrical surface. The studies included a theoretical investigation and an experimental program, the latter having the purpose of verifying the results of the analysis.

The theoretical investigation has brought general methods of analyzing infinite periodic and finite cylindrical arrays. The experimental program has proved that the analytical methods give results in close agreement with experimental measurements.

Preceding page blank

UNCLASSIFIED

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	iii
1. INTRODUCTION AND SUMMARY	1
2. THEORETICAL INVESTIGATION	3
2.1 General Considerations	3
2.2 Infinite Array Studies	3
2.3 Finite Array Studies	4
3. EXPERIMENTAL INVESTIGATION	6
4. CONCLUSIONS	7
REFERENCES	8

Preceding page blank

UNCLASSIFIED

1. INTRODUCTION AND SUMMARY

AA-7-197

The present report briefly summarizes the studies performed under AFCRL Contract No. F19628-70-C-0226, during the years 1970 and 1971. Detailed accounts of the studies can be found in Scientific Reports No. 1 (AFCRL No. 70-0682), No. 2 (AFCRL-71-0322) and No. 3 (AFCRL No. 72-0232). The objective of the contract is to investigate techniques applicable to the problem of achieving wide angle scan coverage by a phased array of elements flush mounted on a cylindrical surface and to establish relevant engineering design guidelines. Ultimate goal of the investigation is to establish the feasibility of a cylindrical array having a maximum gain fluctuation or dropoff versus scan angle no more than 6 dB on a hemispheric sector. The studies included a theoretical investigation and an experimental program, the latter having the purpose of verifying the results of the analysis. The theoretical investigation has been articulated in distinct phases.

Phase I) Infinite Cylindrical Arrays

The study has lead to effective techniques for the analysis of infinite cylindrical arrays. A finite size array is represented by an excited portion of the infinite periodic structure. This analysis gives reliable results in the coverage region around the array broadside. The infinite periodical model, of course, totally fails to predict the array performance in regions close to endfire.

Phase II) Finite Cylindrical Arrays

The analysis has been extended beyond the level of Phase I to include the edge effects due to the finite size of practical arrays. The antenna models developed during this phase are shown to predict endfire gain of arrays with accuracy good for all practical purposes.

UNCLASSIFIED

During the experimental investigation, a cylindrical array of 284 elements was built and tested. The cylinder radius is 16 in. and the array extends over a sector of about 50 deg. The array elements are circular waveguides load terminated. The tests consisted of feeding one element at a time and taking its gain pattern in the array environment. The information on the radiative properties of these array elements collected experimentally is in excellent agreement with the results from the analytical studies, thus proving that the methods developed to predict cylindrical array performance are indeed reliable.

UNCLASSIFIED

2. THEORETICAL INVESTIGATION

2.1 General Considerations

In order to investigate techniques to achieve hemispheric scan coverage by means of a cylindrical array, it is necessary to establish effective methods to predict array performance. This way techniques can be devised and their effects on array coverage quickly evaluated.

The theoretical studies performed under this AFCRL contract have been directed toward advancing cylindrical array analysis, taking into account mutual coupling among elements. In a first approach to cylindrical array analysis, the structures investigated were infinite periodic in the axial direction. A similar approach (infinite periodic model) was used by several authors⁽¹⁾⁽²⁾⁽³⁾ in the analysis of plane phased arrays.

The infinite array model was refined in a subsequent phase of the theoretical studies so as to include edge effects due to finite array dimensions. During this phase of the investigation the endfire coverage obtainable by a cylindrical array was carefully analyzed. In both phases of the theoretical studies the main technique considered for achieving hemispheric coverage was off-broadside matching. Results show that indeed a considerable improvement of array coverage can be obtained this way.

2.2 Infinite Array Studies

The approach used during this study consists in modelling the array as the finite excited portion of an infinite periodic structure. The array consists of flush mounted elements arranged in a triangular lattice. The method of analysis is based on a systematic exploitation of the translational and rotational symmetry of the infinite periodic array. Every "free" array excitation⁽⁴⁾ is decomposed in a set of elementary excitations matching the symmetry of the structure (eigenexcitations). The analysis of the array radiation for the eigenexcitations is much simpler than the general case,

UNCLASSIFIED

which can be obtained from the eigenexcitations by simple superposition. The analysis has been conducted rigorously, using several waveguide modes in matching the boundary conditions at the cylinder surface. The usefulness of the method of analysis introduced has been illustrated by a number of numerical examples⁽⁵⁾. Radiation from cylinders with radii ranging from 10λ to 100λ has been analyzed. The effects of different matching conditions on wide angle scan performance have been investigated. It has been shown that, by off-broadside matching, element patterns can be obtained, which have a gain fall of less than 6 dB up to 80 deg from broadside. It has also been checked that these desirable wide angle characteristics are preserved over a band of ± 5 percent around center frequency. For several cylinders the coverage of two arrays having broadside gains of approximately 20 and 30 dB has been calculated. The effectiveness of the off-broadside matching techniques in improving coverage is shown for both arrays. A result from this investigation is a method of shaping the array element pattern by means of a suitable matching network. The array models developed during this phase of the theoretical studies fail to give the correct gain of the array in the endfire direction. However, the infinite periodic array approach has helped considerably in gaining insight into the physical phenomena taking place in cylindrical structures.

2.3 Finite Array Studies

The analysis of plane and cylindrical arrays is usually based on the infinite array model⁽⁶⁾. This way the difficult problems related to the "edge effects" are avoided. However, the infinite array approach has the serious handicap of failing to give correct gain values in the regions close to endfire. To include edge effects in the array model, the finite array was taken into account, by applying a perturbation technique⁽⁷⁾, in which the results of the infinite array are used as zero order approximations of the solution. This technique avoids the inversion of the large matrices usually involved in finite array analysis. The voltages of the array elements are obtained by a Neuman series, which converges faster as the array size is increased. However, even small arrays (20 dB gain) can be analyzed by this method.

UNCLASSIFIED

The finite array analysis has brought two interesting results. It has shown that arrays radiate substantially in the endfire direction. This radiation could not be evaluated by means of the infinite array approach. Another interesting effect is that a long "spatial transient"⁽⁸⁾ is present in the array illumination when scanning at extreme angles. The aperture reflection coefficients vary along the array tending to the short condition typical of infinite arrays. By applying the finite array model, an analysis of the coverage obtainable by a cylindrical array of about 30 dB gain was performed. Computations have shown that, if the array is matched at broadside, a loss of about 7 dB is present when scanning to endfire in the plane of the polarization. If the array is matched for radiation at 80 deg from broadside in the plane of polarization, a scan loss of about 4 dB is present in the endfire direction of the same plane. The smaller scan loss is paid for by a lower broadside gain. If the polarization loss of 3 dB⁽⁵⁾ is added to the 4 dB minimum scan loss obtainable, it can be seen that hemispheric scan coverage (6 dB maximum loss) cannot be obtained from a 30 dB array by off-broadside matching techniques. On the other hand, computations show that the desired hemispheric coverage can be obtained by 20 dB gain arrays on large cylinders, since they appear to have a scan loss of less than 3 dB over the scan region. These results, along with the methods of analyzing cylindrical arrays, can be considered as the major output of the studies.

UNCLASSIFIED

3. EXPERIMENTAL INVESTIGATION

The experimental investigation has been aimed at checking the correctness of the analytical evaluations of the element patterns in the array environment. In particular, experimental evidence was sought of the widening of the element patterns (indication of increased coverage) due to a suitable matching network inside the element waveguide. The check on the element pattern predictions gives proof of the correctness of the computations for the array coverage.

The structure used for the tests is a hemicylindrical metal surface of 16-in. radius and 18-in. height. The array has 284 circular elements of 0.3-in. radius, disposed on a triangular lattice with 0.8-in. spacing. The array has an angular extent of about 50 deg and is square shaped. The elements are loaded with rexolite ($\epsilon_r = 2.54$) and are match terminated with the exception of one element which is fed and its patterns monitored.

Three different matching networks for the element pattern shaping were implemented by suitably changing the penetration and the distance from the radiating aperture of two copper-plated tabs. The tests consisted simply of taking the gain patterns of the excited element. To detect edge effects, the active element was positioned in different locations within the array. The frequency of operation was 8.3 GHz. The experimental results have been in close agreement with the theoretical predictions of the element patterns. A great amount of experimental data was collected and a detailed account of the results can be found in Scientific Report No. 3 (AFCRL No. 77-0232).

UNCLASSIFIED

4. CONCLUSIONS

The hemispheric scan coverage study has produced the following concrete end results:

- 1) It has advanced the methods of analysis of infinite cylindrical arrays to a state of refinement equal to the well-established methods for plane arrays.
- 2) It has introduced new methods for the analysis of planar and cylindrical arrays taking into account edge effects.
- 3) It has established the limits (about 30 dB) on the gain of arrays which can perform hemispheric scan coverage, if only conventional off-broadside matching techniques are applied.
- 4) It has checked the accuracy of the analytical methods developed in 1) and 2) by an extensive experimental investigation.

The information collected during the study period forms a solid basis for any future cylindrical array program.

UNCLASSIFIED

REFERENCES

- 1) Borgiotti, G. V., "Modal Analysis of Periodic Planar Phased Arrays of Apertures", Proceedings of IEEE, Vol. 56, No. 11, November 1968.
- 2) Amitav, N., and Galindo, V., "Analysis of Circular Waveguide Phased Arrays", Proceedings URSI Spring Meeting, Washington, D. C., 1968.
- 3) Borgiotti, G. V., and Balzano, Q., "Analysis of Periodic Phased Arrays of Circular Apertures", IEEE Transaction on Antennas and Propagation, Vol. AP-1, No. 2, March 1969.
- 4) Hansen, R. C., "Microwave Scanning Antennas", Academic Press, New York, Chapter 3, 1966.
- 5) Borgiotti, G. V., and Balzano, Q., "Analysis and Element Pattern Design of Periodic Arrays of Circular Apertures on Conducting Cylinders", Scientific Report No. 1, November 1970, AFCRL-70-0682.
- 6) Sureau, J. C., and Hessel, A., "Realized Gain Function for a Cylindrical Array of Open Ended Waveguides", 1970 Phased Array Antenna Symposium, Polytechnic Institute of Brooklyn, June 2-5, 1970.
- 7) Borgiotti, G. V., "Edge Effects In Finite Arrays of Uniform Slits on a Ground Plane", accepted for publication in IEEE Transaction on Antennas and Propagation.
- 8) Borgiotti, G. V., and Balzano, Q., "End-Fire Radiation from Planar and Large Cylindrical Array", Scientific Report No. 2, May 1971, AFCRL-71-0322.