AD-751 891

HAZARDS ASSOCIATED WITH THE OPERATION OF MICROWAVE OVENS

James D. Wallace

Environmental Health Laboratory McClellan Air Force Base, California

March 1969

DISTRIBUTED BY:

National Technical Information Service U. S. DEPARTMENT OF COMMERCE

5285 Port Royal Road, Springfield Va. 22151



DOCUMENT CO	NTROL DATA - R & D
1. ORIGINATING ACTIVITY (Corporate author)	28. REPORT SECURITY CLASSIFICATION
	Unclassified
USAF ENVIRONMENTAL HEALTH LABORATORY	26. GROUP
LCCLELLAN AFB, CA. 95652	i
3. REPORT TITLE	
HAZARDS ASSOCIATED WITH THE OP	ERATION OF MICROWAVE OVENS
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)	
FINAL	
5. AUTHOR(S) (First name, middle initial, last name)	
JAMES D. WALLACE	
6. REPORT DATE	78. TOTAL NO. OF PAGES 75. NO. OF REFS
March 1969	31 24
88. CONTRACT OR GRANT NO.	98. ORIGINATOR'S REPORT NUMBERIS)
b. PROJECT NO.	
	69M-6
с.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned
	και στοροτε)
d.	
10. DISTRIBUTION STATEMENT	
Rotaila at illustrations in	
Details of illustrations in this document may be better studied on microfiche	USAF Environmental Health Lab McClellan AFB, CA \$5652
Details of illustrations in this document may be better studied on microfiche ^{13. ABSTRACT} A review of the literature of "Haza Microwave Ovens" was undertaken alon being operated at USAF bases. The ope have been "jumped" (overridden) or hav represents the most serious hazard to a evaluation of this situation was perform ies was to appropriate survey procedur interpretation of survey results. It was concluded that there is very operation of these ovens, even though s these ovens are necessary to determine 'jumped" (overridden), and if significan are made for survey procedures and eq radiation leakage which require correct	USAF Environmental Health Lab McGlellan AFB, CA \$55652 rds associated with the Operation of g with a physical survey of microwave ovens eration of an oven with (1) interlocks that we failed (2) door partially or fully open operating personnel of these ovens, an need in the laboratory. Purpose of these stud- es and equipment, and provide guidance for little hazard associated with the normal ome leakage may occur. Periodic surveys if interlocks have failed or have been at leakage is occuring. Recommendations uipment to be used. Levels of microwave tive action are presented.
Details of illustrations in this document may be better studied on microfiche ^{13. ABSTRACT} A review of the literature of "Haza Microwave Ovens" was undertaken alon being operated at USAF bases. The ope have been "jumped" (overridden) or hav represents the most serious hazard to a evaluation of this situation was perform ies was to appropriate survey procedur interpretation of survey results. It was concluded that there is very operation of these ovens, even though s these ovens are necessary to determine "jumped" (overridden), and if significan are made for survey procedures and eq radiation leakage which require correct	USAF Environmental Haalth Lab McGlellan AFB, CA \$5652 ards associated with the Operation of g with a physical survey of microwave ovens eration of an oven with (1) interlocks that we failed (2) door partially or fully open operating personnel of these ovens, an ned in the laboratory. Purpose of these stud es and equipment, and provide guidance for little hazard associated with the normal ome leakage may occur. Periodic surveys if interlocks have failed or have been at leakage is occuring. Recommendations uipment to be used. Levels of microwave tive action are presented.

ł

うち、うちいう、どう、これにもいいというないか

MICROWAVE OVENS HAZARDS MICROWAVE SURVEYS RADIATION
MICROWAVE OVENS HAZARDS MICROWAVE SURVEYS RADIATION
ib

1

્રિન્

and the second second

and the state of the state of the state of the

A DESCRIPTION OF

ANTINIA STREET

2

.

USAF ENVIRONMENTAL HEALTH LABORATORY McClellan Air Force Base, California

HAZARDS ASSOCIATED WITH THE OPERATION OF MICROWAVE OVENS

Report No. 69M-6 (Project No. E68-57)

March 1969

ic

Prepared by:

سه يمز نه

JAMES D. WALLACE Captain, USAF, BSC Chief, Special Projects Division

Approved by:

FRANCIS S. SMITH Colonel, USAF, BSC Commander

ABSTRACT

بدأ خامعورا ولاعتدا والكوس اللامرومية

「「「「「「「」」」」

A review of the literature of "Hazards Associated with the Operation of Microwave Ovens" was undertaken along with a physical survey of microwave ovens being operated at USAF bases. The operation of an oven with (1) interlocks that have been "jumped" (overridden) or have failed (2) door partially or full open represents the most serious hazard to operating personnel of these ovens, an evaluation of this situation was performed in the laboratory. Purpose of these studies was to evaluate the magnitude of the hazard involved, recommend appropriate survey procedures and equipment, and provide guidance for interpretation of survey results.

It was concluded that there is very little hazard associated with the normal operation of these ovens, even though some leakage may occur. Periodic surveys of these ovens are necessary to determine if interlocks have failed or have been "jumped" (overridden), and if significant leakage is occurring. Recommendations are made for survey procedures and equipment to be used. Levels of microwave radiation leakage which require corrective action are presented.

していいいろうちょうとうないないないろうで

DISTRIBUTION LIST

Hq USAF (AFMSPAP)	2
SAC (SUP)	2
ADC (ADCSGM)	. 40
ATC (STSGPA)	10
AFSC (SCBP)	10
TAC (SGPS)	25
MAC (MAASGD)	10
AFLC (MCDDF)	10
	10
	6
CINCIPACAF (SGP)	25
A DGG	15
AFCS	2
AU	2
USAFSO	2
Hq COMD USAF	2
CAC	2
USAFA	2
USAFSS	2
1002 IGGP	٤
AFROND	2
Phoenixville DA	2

TABLE OF CONTENTS

SECTION		PAGE
I	Introduction and Purpose	1
п	Review of Literature and Discussion	1
III	Scope of Survey	13
IV	Survey Results	13
v	Discussions of Results and Conclusions	16
VI	Recommendations	17
Bibliograph	1 V	19

LIST OF TABLES

TABLE

and and the state of the state

Sec. 33

Ia	Summary of Released Microwave Intensities	6
Ib	Summary of Released Intensities - All Units Monitored	6
11	Summary of Released Microwave Intensities Denver Area	7
111	Summary of Released Microwave Intensities	7
IVa	Microwave Intensities Emitted from Closed Ovens	8
IVb	Summary of Released Radiation Intensities of Monitored Ovens	9
V	Microwave Leakages Associated with the Operation of Various Microwave Ovens	10
VI	Summary of Surveys by US Army	D
VII	Summary of Results of Surveys at AF Installations	14

TABLE OF CONTENTS (CONT'D)

VIII	Microwave Field From an Oven, Door Open	14
FIGURE I	Location of Survey Points	15

APPENDICES

APPENDIX

t

I	Ltr, Hq USAF (AFSPAP) to All Commands, 13 July 68, Subject: Microwave Ovens
II	Ltr, Hq AFLC (MCDPE) to All AFLC Bases, 16 July 68, Subject: Microwave Ovens
III	Survey Equipment and Description
	Empire Power Density Meter, Model NF-157
	Probes, Model NF-157, Power Density Meter
	Ramcor Power Density Meter
	Microlite (Probe) 287
	Fluorescent Bulb
IV	Survey Procedures

のいまたで、そうことにないいかがら

INTRODUCTION AND PURPOSE

In letter from Hq USAF (AFMSPAP) to all commands, dated 11 July 1968, subject; "Microwave Ovens" (See Appendix I), it was pointed out that certain reports have indicated that excessive amounts of microwave radiation may be emitted from microwave ovens. These reports indicate that this situation is brought about by malfunctioning interlock switches, poorly installed seals, or misaligned doors.

Commands were requested to forward consolidated listings of bases not having the capability to survey these ovens to Hq AFLC (MCDPE). AFLC then was to arrange for the survey of these ovens (See Appendix II).

Field guidance is needed as to appropriate survey equipment, procedures, and periodicity of surveys. The magnitude of the hazard associated with the operation of microwave ovens at USAF bases needs to be defined so the above guidance could be given. It is the purpose of this study to fulfill these requirements.

SECTION II

REVIEW OF LITERATURE AND DISCUSSION

A. Near and far-field Regions: Microwave radiations fall within the spectrum of electromagnetic radiation. Generally they encompass the range of frequencies of from 300 to 3×10^{5} megahertz (MH_z), wavelengths of 1.0 meter and 0.1 cm respectively. The UHF, SHF, and EHF bands of the Hertzian or radio frequencies are contained in this range. These frequencies include radio, television, and commercial and military radar bands. Also, frequencies designated for medical diathermy treatment and those used in microwave ovens are in this range.

1. Near-field: In close proximity to the radiator or source of radiation such as an area of leakage from a microwave oven, a near field region exists which is similar to fresnel region (See T.O. 31Z-10-4 for description, Ref 1). In a paper entitled "Near Field Radiated Emission Characteristics" the following observation was made:

"The near-field and far-field regions for an antenna or radiating element are difficult to define because there are no discrete dividing lines between the regions. The definition is further complicated by the fact that different criteria are used to define the dividing line between the regions. In one case, the dividing line is based on the ratio between

1

「「「「「「「「」」」」というないで、「「」」」

"induction" or "reactive" energy and propagated energy, in another case the dividing line is based on the degree of phase shift in the wave front, and in still another case, the dividing line is based on the degree of amplitude variation in the wave front. While each of these criteria has some significance in terms of measurement accuracy, the criteria do not, in the general case, establish a unique dividing line between the near-field and the far-field regions of an electromagnetic radiator" (Ref 20).

An example of this is the difference between the guidelines for defining these regions as presented in the above paper and in T.O. 31Z-10-4, "Electromagnetic Radiation Hazards", dated 1 August 1966, and are respectively:

	Near-field	Fresnel Region	Far-field
(1)	$0 \le D \le \frac{\lambda}{2\pi}$	$0 \ge D \ge 5 \Gamma_{s}^{P}$	$D \ge \frac{5}{5} \frac{\Gamma_{B}^{3}}{\Gamma_{B}^{3}}$
123	0 < 0 < 13	0 - 0 - 13	$D > T^3$

Where: D= the distance from the antenna in feet.

 $L_a =$ the antenna aperture, in feet.

 L_b = the largest linear dimension of the source or test antenna aperture, whichever is larger.

 λ = wavelength in feet.

In the near-field region description (1) above or in the very near field description (2) also above, a substantial part of the energy is in the form of "inductive" or "reactive" energy (Ref 20). These electrostatic and magnetic energies oscillate back and forth between the radiator and the surrounding space (Ref 20). The intensity of the electrostatic field varies as the inverse of D^3 where the magnetic field varies as the inverse of D^3 . For a short dipole source the field strength changes at a rate of 18dB per octave of distance. For this source, for distances greater than $\lambda/2\pi$ the field changes at a rate of 6dB per octave of distance (Ref 20). Therefore at distances less than $\lambda/2\pi$ the fields are predominately reactive or inductive, and at distances greater than $\lambda/2\pi$, the fields will be predominately propagated (Ref 20). When some element such as a horn or a human appendage is placed in these regions any one of a number of situations may arise, some of which have been described by Crapuchehas (Ref 21):

and the second solution in the second solution in the second solution is the second solution of the second s

1. The element may act as a tuning element causing the slot or leakage area to transmit in ways it does not transmit in the absence of the element.

2. The element may act as a reactance in space and the field is "coupled" to the element.

3. The element and the horn being reflectors may become boundaries for a resonator system or resonant cavity.

the set with the set with the standard and the set of the set

It has been postulated that the effects of these errors to measurement may be a factor of \pm 10 in the power density measured (Ref 21).

Horns for use in far-field are characteristically tightly coupled to the field, i. e., they intercept the greater percentage of the energy of the field in which they are inserted. This is necessary to give high sensitivity for in the far field the energy is low. The opposite is true in the near field. The horn or device used to intercept these fields would have to be a "point" probe that would not perturb the field devices but some of the mathematics for such a device have been developed (Ref 21).

In the Fresnel region, description # (1), or the latter portions of the near or fresnel region, description #(?) the criterion is based on the phase characteristics of the incident wave front. In this region the wave front will be a portion of a spherical surface having some finite curvature. As the wave front is received at the center of the antenna, the outermost portions are still some distance from the aperture, i.e., the signal received at the end of the antenna will have a phase lag relative to the signal received at the center of the antenna. For most applications the magnitude of this error is considered to be acceptable if this phase variation is 22.5 degrees or less across the aperture of an antenna. This results in a gain error of approximately less than 0.1dB and a negligible change in pattern shape. This occurs when D is $\geq 2 L^2 / \lambda$, description # (1). Therefore, in this region the gain, effective aperture, and pattern of an antenna are functions of the distance from the source. All antenna parameters are specified in terms of a uniform plane wave, one having exactly the same phase and exactly the same magnitude (Ref 21). The energy from complex waves cannot be specified in any limple way.

2. Far-field: In the far-field regions there are no contributions from the "reactive" fields surrounding the source and no significant phase variation in the wave front. Therefore, in this region the gain, effective aperture, and pattern of the test antenna are independent of the

distance from the source. It is within this region, at distances greater than 2 L^2/λ from the source, that the inverse square law implies in free space. In areas where the propagated wave may be reflected off surfaces, not in free space, the field intensity may be inhanced or diminished. This reflection is associated with dimensional resonance phenomena where the field amplitude build up because the dimensions are such that suscessive reflections from walls or boundaries just overlay one another properly in space and time. This may occur in the near or Fresnel region or in the far-field. For the Ramcor 1200 with S band horn the far field would begin at approximately 6" from the oven surface. Because the dimensions of the areas of leakage are small, the greatest dimension of the effective horn aperture were used to determine where the far-field region begins.

and the first of the second of the second

- Marana in

B. Criteria: The criteria for evaluation of exposures to far-field microwave radiation is set forth in AFM 161-7, "Control of Hazards to Health from Microwave Radiation", dated December 1965. According to field strength (power density, mw/cm²), three conditions may exist:

Condition	Field Strei	ngth (mw/sm ²)	Area Designation
safe	5	10.0	continuous occupancy
potentially hazardous	>	10 ≦ 100	limited occupancy
hazardous	>	100	denied occupancy

ì.

The "Maximum Permissible Power Density" for continuous exposure is then defined as 10 mw/cm². For "limited occupancy areas", accessible areas in which the incident power density is in excess of 10 mw/ cm² but less than or equal to 100 mw/cm² (Ref. 7), the following equation may be used to determine the permissible exposure time T_p (units are minutes/hour in any one-hour period) irrespective of the frequency involved:

$$T_p = \frac{6000}{W^2}$$

Where: W = power density in exposure area expressed in mw/cm³. This equation is applicable when power density $is > 10 mw/cm³ \le 100$. Therefore, any realistic evaluation of hazards associated with operation of microwave ovens must include the incident power and the exposure period.

C. Test Equipment: Several basic types of test equipment are being used to astect and quantitate microwave radiations in the far-field. A few of these are calibrated wave meters (frequency meters), power meters,

field strength meters, test antennas, and test lights. For a basic discussion of these instruments, see Appendix III.

D. Biological Effects: Biological effects of exposure to microwave radiation in the far-field have been described elsewhere (Ref. 3, 4, 5, 6, 7, and 23). The primary response is an overall rise in temperature of the exposed tissue or organ. Microwave ovens utilize this biological response of energy absorption and conversion to thermal energy in the preparation of foodstuffs. Microwave ovens for cooking foodstuffs operate at 2450 MH_z; for thawing food, they operate at 915 MH_z. The eyes are most susceptible to the 3000 MH_z frequency (Ref. 8). Between 1000 and 3000 MH_z, absorption in the deeper body tissues tend to diminish, depending on skin thickness, the total mass of body, thickness of fatty layer, and the frequency of the energy (Ref. 9). Little information is available as to the biological effect of exposure to the near-field radiations.

E. Results of Other Surveys:

いたので、「「「「「「」」」」

1. Results: Results of surveys of leakage radiation from microwave ovens are shown in the following, Tables I-VI, to show the leakages that have been found by others (Ref. 8, 9, 14, 15, 16 & 17). The extent of these leakages should indicate the magnitude of the hazard involved in operating these ovens.

TABLE Ia

· · · · · · · · · · · · · · · · · · ·	Hinged Door	Vertical Sliding Door
Number of ovens monitored	58	18
Number leaking	48	6
Percent emitting $< 1 \text{ mw/cm}^2$	17%	67%
Percent emitting 1-10 mw/cm ²	40%	33 <i>m</i>
Percent emitting > 10 mw/cm ²	· 43%	0%

SUMMARY OF RELEASED MICROWAVE INTENSITIES

Rentos, P. G.; "Microwave Oven Survey - A Composite Report," Public Health Service Occupational Health Program, Occupational Health Field Station, Salt Lake City, Utah, 1968.

TABLE Ib

SUMMARY OF RELEASED INTENSITIES - ALL UNITS MONITORED

ł		, , ,
1	Hinged Door	Vertical Sliding Door
Number of ovens monitored	93	25
Number emitting $> 10 \text{ mw/cm}^2$	27	1
Percent emitting > 10 mw/cm^2	29%	4%

(Amendment to Report by Rentos, 1968)

TABLE II

SUMMARY	OF	RELEASED	MICROWAVE	INTENSITIES
DENVER AREA				

	Hinged Door	Vertical Sliding Door
Number of ovens monitored	17	2
Number leaking	12	1
Percent emitting < 1 mw/cm^2	29%	50%
Percent emitting 1-10 mw/cm ²	29%	50%
Percent emitting > 10 mw/cm^2	41%	0

Personal correspondence, Lt McElwey, Lowry AFB, Colorado

TABLE III

SUMMARY OF RELEASED MICROWAVE INTENSITIES

	Numbe r Units
Number monitored	42
Number leaking = 10 mw/cm ² (maximum distance 12")	15

Personal correspondence, Captain Conrad, Patrick AFB.

ALT LA MULTIN

TABLE IVa

	Location of Measurements			
Oven Description	Face of Door	Face of Door Periphery of		y of Door
		Left Side	Тор	Right Side
Bottom-hinged door	2	2	0	2
open grill front	8	4	0	4
mechanical lcck	2	12	0	4
generating tube	3	9	0	0
	0	2	0	2
	0	2	0	2
	1	0	0	1
Bottom-hinged door	0	10	0	0
open grill, mechanical	0	6	10	5
lock, 2 generating	3	0	0	0
tubes	2	4	0	2
	3	10	2	0
	1	0	0	3
Vertical sliding	0	0	0	0
door, open grill	0	0	0	0
l generating tube	0	0	0	0
0 0	2	0	0	0
	0	6	0	4
	1	0	0	0
Vertical suiding		1	1	
door, open grill	0	0	0	0
2 generating tubes]	
Side-hinged solid	0	2	0	
panel door, mechanical	6	0	6	2
lock. 1 generating	1	2	4	4
tube				
Bottom-hinged door	0	0	0	0
lock				

MICROWAVE INTENSITIES EMITTED FROM CLOSED OVENS (Milliwatts/sq. cm)

Suroviec, H. J., "Microwave Oven Radiation Hazards in Food-Vending Establishments," Archives Environmental Health (March 1967), Vol. 14

ren uten en ar anstalle gebruidenten en Scheduler en fetre en sterken ten sen fen ten sterken bilteriet

TABLE IVb

	Bottom-Hinged Door	Vertical Sliding Door	Side-Hinged Door
Maximum level detected (milliwatts/sq cm)	12	6	Ó
Average levels detected (milliwatts/sq cm)	2.4	6.5	2.3
f emitting 10 or more milliwatts/sq c	28 m	0	0
% emitting l or more milliwatts/s3 cn	93	43	100

SUMMARY OF RELEASED RADIATION INTENSITIES OF MONITORED OVENS

Suroviec, H. J., "Microwave Oven Radiation Hazards in Food-Vending Establishments, "Archives Environmental Health, Vol. 14, March 1967.

TABLE V

MICROWAVE	LEALAGES ASSOCIATED WITH THE OPERATION	
	OF VARIOUS MICROWAVE OVENS	

and and a state and a second and a

*** *** * ****

.

and the second states and the second states

0	• <i>•</i>		Power Density#	
Oven	Location of		Milliwatts Per Square	
Number	Leakages	Load	Centimeter (mw/cm ^e)	Remarks
1	Front	Dummy	5.0	
	Side	Jummy	5.0	
2	Right Front	Dummy	10.0	
3	None	Dummy	0.0	
4	Front	Dummy	0.5	Only one magnetron functioning.
5	Front	Jummy	5.0 20.0	Door shims worn. Can crack door open without unit shutting off. With power switch on, warning light on at all times. Light becomes brighter when cooking commences.
6.	Front	Duromur	5.0	
U	I TOIL Sido	Dummer	2.0	
	Side	Dunny	(
7	None	Dummy	0.0	
8	Front	Roast	1.0	
-	Side	Roast	0.25	
9	Front Side/Door Ajar	Sandwich	5.0	Worn door shims prevented immediate activation of safety shut off.

Breysse, P. A. "Microwave Cookers", Occupational Health Bulletin, Vol. 21, No. 10, 1966.

Survey	Number	Number	Number Leaking	
Number	Ovens Surveyed	Leaking	≧ 10	≩ 20
1	28	22	ύ	2
2	32	25	ó	4

SUMMARY OF SURVEYS BY US ARMY

Survey No. 1 Taylor, 68. Survey No. 2 Taylor, 67.

the of her spectra and the second second second second second second her and the second second second second se

2. Critque of Results: The percentage of ovens with leakage (Tables Ia and b, II and IV) was: vertical sliding about 12 percent; hinged door, 29.6 percent. The majority of ovens shown in Tables I-V were not new and were located in public facilities receiving high usage. Therefore, oven construction is a critical factor as to leakage; and for ovens with higher usage, a greater probability exists that leakages would occur. The age of these ovens and their high usage tends to explain the high percentage of ovens that had leakages. Maintenance of these ovens was on contract basis. Rose, et al, (Ref 13) measured energy levels at a distance of 18 inches from the magnetron (high power tube) of a n-icrowave oven, averaging 22 mw/cm² at his abdomen. They concluded that "Data available do not confirm the probability but do prove that adequate protection can be afforded the worker by use of a simple, inexpensive device to intercept and absorb the microwave energy. The device is a wooden frame covered with copper mesh screening which is placed on the oven to shield the worker from the microwave energy to levels less than 5 mw/cm²."

For surveys, Tables II, III, and V, the oven to survey instrument distance was not shown. This distance was from 2-3 inches for survey, Table IVa and b, and at the surface of the oven for Tables Ia, Ib, and VI. In surveys, Tables II, IV, V, and VI, dummy loads were used simulating operating conditions. This was not established for surveys, Tables Ia and b, and II. Survey instrument esed in Tables Ia and b, and Table VI was the Rameor 1200, and in Table V the Empire NF 157. Instrument used was not established for Tables II and III. As previously discussed, the distance from the oven at which leakage (power densities) are measured affects the reliability of the measurements; this distance should be at least 6 inches if the measurements are to be reliable.

It can be concluded from the proceeding tables that leakages from microwave ovens do occur. As previously presented (See Section I, this report), the causes for these leakages are varied. In general, the authors (Ref. 8, 9, 14, 16-18) did conclude that these ovens represent a potential hazard. and a second second

SECTION III

SCOPE OF SURVEY

Surveys of 19 microwave ovens being operated at 12 Air Force installations were accomplished. The amount of microwave radiation leakage from these ovens and physical cause of leakage, when possible, along with the condition of the interlocks was determined. Survey procedures for these determinations were those shown in Appendix IV. Survey instruments were the Empire instruments, Models 157, Serial Nos. 181 and 195, calibrated 12 July 1968 and microlite (Probe) 287.

Determinations of the magnitude of hazard of operating these ovens when interlocks malfunction were also made. For these determinations, an oven of the sliding door type was brought into the laboratory and operated with interlocks "jumped", door opended, and dummy load inside the oven. The size of the beam and the power densities of the microwave field at various positions around the oven were determined. Ionization radiation was measured with a RF shielded Victoreen 440, survey instrument, Serial No. 306, calibrated 26 September 1968.

SECTION IV

SURVEY RESULTS

The results of field surveys of microwave ovens are shown in Table VII. Results of investigations in laboratory are shown in Table VIII. The locations of measurement are seen in Figure 1. a sheeting sheeting and sheeting a second

นั้น ค.ศ.ศ. ระดีนที่สะสานทางเราสะเหล่ามการสานสายสายสายสาย เราะสะสะสานที่ไปสายสายสายสายสายสายสายสาย ก

a second real of

In the field surveys, Table VII, the energy escaping was found to be directional giving a narrow beam, usually parallel to the plane of the door for ovens with hinged doors.

In the laboratory investigation with the oven door open, the energy escaping is directional, but the beam is extensive, extending to all sides of the oven, 180° from center front of oven. With the oven door closed and no dummy load in the oven, only one area of leakage was detected; 1/4 inch length of tube glow with the microlite, and 0.2 mw/cm^2 with the Empire 157. With dummy load, glass half full of water only a needle deflection was seen, using the Empire 157 survey instrument. No response was registered by the microlite 287. The operating procedure for these ovens is to place food inside the oven which is normally located on counters. The oven is activated for a pre-set period of time, and during this operation the operator can be in another area. The

TABLE VII

1.1.1

200

SUMMARY OF RESULTS OF SURVEYS AT AIR FORCE INSTALLATIONS

	Side Hinged Door	Vertical Sliding Door
Number of ovens monitored	9	10
Number leaking	6	3
Percent emitting > 1 mw/cm ²	0%	0 <i>°;</i> 0
Percent with malfunctioning interlocks	0%e	0°/0

TABLE VIII

MICROWAVE FIELD FROM AN OVEN, DOOR OPEN

Location	Microlite	Empire 157	Ramcor 1200	D'stance
1	full glow	150 mw/cm ²	*	ربان ربانه 8''
2	fulì glow	50 mw/cm ²	*	0'-2''
3	full glow	10 mw/cm^2	2 mw/cm^3	51-1
4	flashing glow	2 mw/cm ²	*	14'-0''

* Limit of instrument, 20.0 mw/cm³



operation time period is for several seconds to a few minutes and operation is by more than one person or on self-service basis. These short operating periods and intermittant operation by any one operator result in short individual exposure. It is possible for the operator to place his face or other parts of his body in close proximity of the oven. Probes have not been developed to measure the radiation within these near or Fresnel regions. Neither are there any guidance or criteria with which to evaluate this potential hazard and until such guidance is available and instruments are developed to measure these radiations, these exposures should be minimized (Ref 22). To the most probably susceptable organs, the eyes and gonards, these exposurers should be prohibited.

Surface readings of ionizing radiation at the air intake and outlet of oven, front and back respectively, showed 0.1 mr/hr.

SECTION V

DISCUSSIONS OF RESULTS & CONCLUSIONS

Two types of ovens are being operated on USAF installations. These are the hinged or the vertical sliding door, both operating at 2450 MHz. All models were relatively new. Measured leakage, consisted of narrow directional beams, always less than 1.0 mw/cm² at the surface of the ovens, using the NF 157 survey meter. Leakage was not detected six inches from the surface of the ovens. Note, that in using the NF 157 or Ramcor power density meters to measure leakage from slots or small areas the intensity of beam has been integrated, averaged, over the effective aperture of the antenna. Therefore, these instruments are not ideally suited for measuring the power density of beams of smaller cross sectional area than the effective aperture of their horn. But a conservative estimate of the actual power density within these small areas would be the measured power density times the ratio of the effective aperture of the horn to the cross sectional area of the leakage. Since no measurement was recorded at more than six inches from the oven surface this would not effect the results of our measurements. Therefore, the probability of a hazardous exposure to microwave radiation occurring during the normal operation (operation of ovens with interlocks not "jumped" and not damaged) of microwave ovens is remote. Likewise, there is no hazard from ionizating radiation.

The microlite-287 has proven adequate as a survey instrument for microwave ovens. Microwave energy can be detected and field pattern can be explored, using this probe. The response of this probe at other frequencies is being investigated and will be reported later, but the probe does seem to have application for detecting microwave energies المعالمة المعالمة المحالية المحالية

from other sources. It is inexpensive, quick, and responsive. Length of glow of microlite tube is proportional to field density.

Linkine .

いちょうかん ちょう

ļ,

Whether an oven leaks or the amount it leaks, in the absence of some element to perturb the radiation fields, is a function of such items as oven construction, age of oven, or usage oven has received, type or manufacturer of oven, etc. Therefore, the periodicity of survey for leakage will have to be determined locally for each set of circumstances. None of the ovens checked (See Table VII, this report) had malfunctioning interlocks, but they still require checking due to the magnitude of hazard their malfunction presents.

Equipment for measuring and criteria for evaluating the radiations within the near-field of leakage from microwave ovens are not a silable, but the energy levels within these regions may be significant (Ref 22). Until such time that the tools to evaluate this situation are available, these exposures should be precluded. The most common exposure to nearfield radiations occurs when the cooking operation is viewed through the perforated panel, door screen.

In the laboratory investigation, Table VIII, the maximum credible accident that could occur was shown in measurement location No. 1. This measurement and measurement, location No. 2, were probably within the near-field and therefore must be considered ambiguous. Solem, et al (Ref 19) made similar evaluations of various ovens operated in an anechoic chamber, a chamber designed to approximate freespace incorporating suitable attenuation of reflected waves. At 12 inches from the center of the face of the oven, they measured power densities ranging from approximately 160 to 700 mw/cm². They used a Ramcor 1200 B with S Band Horn and appropriate attenua ors. They concluded that "Although far field conditions are expected at distances beyond 30 cm from the open oven doors, the observed radiation power density decreases less rapidly than would be predicted from inverse square law determinations. Part of this effect may be caused by reflections from the floor" (Ref 19). We conclude a most serious condition would occur if an oven were operated with interlocks defeated and the area in which the hazard would exist would be normally occupied.

- このに、このないということである ないたちの

A SAME AND A SAME AND A SAME AND A SAME AND A

u such des sond such and the set of the state of the such as the second such as the second such as the second s

SECTION VI

RECOMMENDATIONS

1. All ovens should be surveyed by Base Bio-Environmental Engineer

or Preventive Medicine T__nnician initially and periodically with microlite-287 test lite.* This survey should include both a physical inspection of the integrity of the oven, test to determine whether interlocks are functioning and measurement of leakage radiation. Survey procedures for these tests are shown in Appendix IV.

2. If leakage at 6 inches away from the face of the oven causes microlite to glow full length of tube, the oven should be taken out of service for repair, which will usually be done on contract basis. After repair and before oven is put back into service, it should be resurveyed.

3. If interlocks are not working, the oven should be taken out of service for repair. Before it is again placed in service, the interlocks should be rechecked.

4. To minimize the potential hazard from exposures to near and far-field radiations of leakages from these ovens, viewing of these operations or other actions which would result in the possible exposure to the near-field radiations should not be condoned.

*Six of these lights are available from each of the USAF Environmental Health Laboratories.

18

いいろうちょう ひたくち !!

. ALOURAND A DESTRICTION OF DESTRICTION OF DESTRICTION AND A DESTRICTION OF DESTRICTION AND A DESTRICTION AND A

BIBLIOGRAPHY

- 1. T.O. 31Z-10-4, Electromagnetic Radiation Hazards, dated 1 August 1966.
- 2. Code of Federal Reg., Title 47, Part 18: Industrial Scientific and Medical Equipment that may Interfere with Radio Communications, Government Printing Office, Washington, D.C. 20401.
- 3. Weiss, M. W. and Munford, W. W., "Microwave Radiation Hazards," Health Physics (June 1961), Vol. 5, pp 160-168.

これになるときたち げんだ

- Deichmann, Wm. B., Ph.D. and Stephens, Frank H., "Microwave Radiation of 10 mw/cm², "<u>Industrial Medicine and Surgery</u> (June 1961), Vol. 30, No. 6.
- 5. McLaughlin, John T., M.D., "Health Hazards from Microwave Radiation," Western Medicine (April 1962), Vol. III, No. 4.
- 6. Seth, H. S., M. F. B.S. and Michaleson, D. J. M., "Microwave Hazards Evaluation," <u>Aerospace Medicine</u> (August 1964), pp 734-739.
- "Control of Hazards to Health from Microwave Radiation," USAF Manual 161-7 (December 1955), pp 3-4.
- 8. Breysse, P. A., "Microwave Cookers," <u>Occupational Health</u> Bulletin (1966), Vol. 21, No. 10.
- 9. Suroviec, Henry J., "Microwave Oven Radiation Hazards in Food-Vending Establishments," <u>Archives Environmental Health</u> (March 1967), Vol. 14.
- Instruction Manual, Empire Broadband Power Density Meter, Model NF-157, The Singer Company, Metrics Division, 915 Pembroke Street, Bridgeport, Connecticut.
- Handbook of Operation and Maintenance for Densiometer, Model 1200, T.O. Ne 33A-1#-12-284-1, Radar Measurements Corp., 190 Duffy Avenue, Hicksville, New York.
- 12. <u>Advertisement Flier</u>, International Crystal Mfg. Co., Inc., 10 North Lee, Oklahoma City, Oklahoma 73102.

- Rose, V. E.; Gellin, G. A.; Powell, C. H.; and Bourne, H. G., "Evaluation and Control of Exposures in Repairing Microwave Ovens," an unpublished report.
- 14. Conrad, Captain Ronald G., Personal Correspondence (September 1968), Patrick AFB, Florida.

- 15. McEiwey, Lt David W., Personal Correspondence (October 1968), Lowry AFB, Colorado.
- Taylor, J. R., "Microwave Survey No. 42-38-68", Food Service Division, Walter Reed General Hospital (WRGH), Washington, D.C., 28-29 March 1968.
- Taylor, J. R., "Microwave Survey No. 42-13-68, Walter Reed Army Medical Center (WRAMC), Washington, D.C., 7 September 1967.
- Rentos, P. G., "Microwave Oven Survey," Public Health Service, Occupational Health Program, Occupational Health Field Station, Salt Lake City, Utah, April 1968.
- Solem, D. L. et al, "Report of Preliminary Measurements of Electromagnetic Radiation Fields Near Microwave Ovens" TBS NO 5, Technical Services Branch, Consumer Protection and Environmental Health Service, National Center For Radiological Health, Rockville Maryland 20852, Dec. 1968.
- 20. Near Field Radiated Emission Characteristics, Handout, "Short Course Microwave Systems and Spurious Electromagnetic Radiation", Electronics Division, Engineering Experiment Station, Georgia Institute of Technology Atlanta GA 24 - 28 Feb 1969
- 21. Proceedings of a Meeting To Discuss Technical Considerations in the Measurement and Evaluation of Radiation Emission From Microwave Ovens U.S. Department of Health, Education, and Welfare, Fublic Health Service, Environmental Control Administration, National Center For Radiological Health, Rockville, Maryland 20852, July 31, 1968.
- Staff, "Personal Conversations", Electronics Division, Engineering Experiment Station, Georgia Institute of Technology Atlanta, GA, 27 - 28 Feb 1969.

「日本の日本のないないないないないない」

- 23. Moore, W. Jr., "Biological Aspects of Microwave Radiation", TSB4, U.S. Department of Health, Education and Welfare, Public Health Service National Center for Radiological Health July 1968.
- 24. TO 33 A1 7 69 1, Broad Band Power Density Meter, Model NF 157, dated 15 August 1962

and the second second

;

all and the second

APPENDIX 1

DEPARTMENT OF THE AIR FORCE HEADQUARTERS UNITED STATES AIR FORCE WASHINGTON D.C. 20333

ATTN OF AFMSPAP

SUBJECT Microwave Crens

11 July 1968

ro AAC ATC ADC AU AFCS USAN AFLC HQ (AFSC CAC

AU USAFSO HQ. COND USAF CAC USAFSS 1002 IG GP Norton AFB CA

CINCUSAFE

AFMFO Phoenixville PA

and the second second

And the state of the

(Surgeon)

1. Microwave ovens are being used with increasing frequency in the USAF. Food service facilities using these devices include hospitals, EX concessions, dining halls, officer, NCO, and service clubs. It has been reported that these ovens can emit excessive amounts of microwave radiation because of malfunctioning interlock switches, poorly installed seals, or misaligned doors.

2. It is requested that you identify the bases within your command using microwave ovens and survey each oven to insure that individuals are not receiving excess exposure. If trained personnel and calibrated equipment are not available within your command, a consolidated list of those bases requiring microwave oven surveys should be forwarded to Headquarters, AFIC (MCDPE), with an information copy to this Headquarters (AFMSPAP).

3. The provisions of this letter will expire 1 July 1969.

MAC

SAC

TAC

USAFA

CINCPACAF

FOR THE CHIEF OF STAFF

Down

H. C. DORRIS, Brig General, USAF, MC Director of Professional Services Office of the Surgeon General

APPENDIX II

DEPARTMENT OF THE AIR FORCE MADOUARTERS AND FORCE LOGIST & COMMANT MARIGHT PATTERSON AIR FORCE BASK MID 45433

MCDPE/76231

16 July 1968

Microwaye Ovens (Lir, Hq-USAF [AFMSPAP], 11 Jul 68)

2789 USAF Disp, Brookley AFB AL 36615 2845 USAF Hosp, Griffiss AFB NY 13440 2791 USAF Hosp, Hill AFB UT 84401 2794 USAF Disp, Kelly AFB TX 78241 2793 USAF Hosp, McCiellan AFB CA 95652 2795 USAF Hosp, Robins AFB GA 31093 2792 USAF Hosp, Tinker AFB OK 73145 USAF Hosp, WPAFB OH 45433 SMAMA (LSGHM), McClellan AFB CA 95652

1. The attached letter from Hq USAF is forwarded for your information and action.

2. Request you provide the following information to this office not later than 26 July 1968.

a. Make, model and location of all m . wave ovens at your base.

b. Date of last microwave survey for each oven.

c. Availability of trained personnel and calibrated microwave radiation measuring equipment at your base. If trained personnel and calibrated equipment are not available at your base, request you notify this Headquarters (MCDPE).

FOR THE COMMANDER

H. G. WALLACE, Colonel, USAF, MC Surgeon

1 Atch Cy subj ltr

23



APPENDIX III

EQUIPMENT DESCRIPTION

Empire Broad Band Power Density Meter Model NF-157:

This instrument is designed to measure average power densities from 1.0 milliwatt per square centimeter (mw/cm^2) midscale to 2,000 mw/cm². Frequency range is from 200 MHz to 10,000 MHz for either cw or pulse modulated signals. Components of unit are seen on pages 26 and 27 of this appendix.

The unit can be used for probing of high density RF fields and for detection of hot spots or leakage from antennas and other high power $c_{0\mu\nu\rho\sigma}$ ats. Probe selection is function of frequency of energy to be measured. Position of sensing element in the probe is commensurate with the specific energy to be measured. Read-out of power level being detected is directly in mw/cm². Scale is divided into forty divisions, each division representing 0.5 mw/cm². Step attenuator is provided which permits a choice from five coaxial sections ODB (XI) to 30 DB (X1000), 0-2000 mw/cm².

NOTE: See T.O. 31Z-10-4 and 33A1-7-69-1 for more detailed description.

Ramcor Model 1200 (Ref 11):

This instrument is used for detecting and measuring VHF, UHF and microwave energy radiating from high power transmitters and related equipment. The scale is a direct reading decibel scale, midscale "O" db mark is 10 mw/cm². Range is -10 db to +3 db scale read-.ngs or 1 to 20 mw/cm². Conversion from db to mw/cm² is by chart. Five antennas are supplied with the instruments and cover the following bands:

- VHF (200 225 MHz)
- UHF (400 450 MHz)
- L (1120 1700 MHz)
- S (2600 3300 MHz)

C (5000 - 5900 MHz)

A Minder Street & Barry to and

X (8500 - 10,000 MHz)

24

รู้ได้ผู้ผู้ผู้ผู้ผู้หรือ และเป็นหรือ พระเดิมหรือ (การสำนัก (การสำนัก) (การสาวสาวสาวสาวสาวสาวสาวสาวสาวสาวสาวสาว

The response of each horn is not flat for range of frequencies it covers. Therefore, for a given horn and enclosed attenuator, a calibration curve must be provided.

Instrument calibration is with a signal generator and antenna capable of producing a field of 10 mw/cm^2 . Field density should be within $\pm 1 \text{ db.}$

Microlite - 287:

This survey instrument consists of a preignited neon lamp designed to indicate a field intensity of 10 mw/cm^2 at 2450 MH_z. Length of glow along tube is a function of field strength, e.g., 1/4 tube length indicates 2 mw/cm², full length 10 mw/cm² or greater. For any other frequency the microlite probe can be expected to respond differently.

Fluorescent Bulb:

The bulb is used as an indicator of presence of microwaves. Energy required to fluoresce bulb being a function of frequency, geometry of bulb, and field strength. Example: 8 watt bulb, see page30, this appendix, glows steadily if field strength is 18 - 20 mw/cm², and flickers in field of δ to 8 mw/cm² (Ref. 13).

If fluorescent bulb is placed at surface of an oven, it may fluoresce when subsequent readings with power density meter show that power density at 6 inches is insignificant. The fluorescent bulb is not a good survey tool to quantitate leakages but does have its use when checking interlocks.





1

A States in

27

í







SURVEY PROCEDURES

Survey of microwave ovens is done in three parts: (1) physica inspection of oven, (2) survey for leakage radiation, and (3) check of interlocks.

In the physical inspection, the surveyor should check to see if: door shuts tight, all screws, doors screens, and other parts are in place, etc. For, areas where parts are missing can be sources of leakage. A strip of paper 1" wide and approximately 6" long can be used to check door seal. These are arbitrary demensions. With the door open place the strip of paper at different positions along the periphery of the door. Each time, closing the door and removing the strip of paper. If there is considerable resistance to the removal of the paper the door seals can be considered tight. This is also a good check before placing an oven back into service that has been found to leak around the periphery of the door seals but should not take the place of the other procedures discussed in the following paragraphs:

Prior to making leakage measurements, determine from manufacturer's plaque, or by other means, the frequency at which the oven operates. If it operates at 2450, the microlite probe can be used to accomplish this part of the survey. If the oven operates at some other frequency, a broad band power density meter can be used for this part of the survey. These instruments can be borrowed from the USAF Environmental Health Laboratories. 'The ovens surveyed to date have operated at 2450 MHz. To locate the areas of leakage, operate the oven empty (without dummy load), so that the least energy will be absorbed; therefore, the leakage is maximized. These operating periods should be limited to prevent excessive energy absorption by magnetron tube and subsequent damage of the tube (Ref. 16, 17, and 18). Make surface measurements along the periphery of the door and screen (viewing window). Also, at any other site where an area of leakage may be suspected (see preceding paragraphs). Now place a standard 150 ml beaker containing 100 ml of water in the center of the oven cavity to simulate operating conditions, resurvey the previously identified areas of leakage. Survey distance should be 6 inches from surface of oven (outside the fresnel area, assuring good survey instrument response).

In checking the interlocks, place a fluorescent bulb (1-40 watts) in the oven cavity along with a dummy load. Operate oven and with varying amounts of pressure, open the door. If interlocks are functioning properly, the fluorescent bulb will discontinue fluorescing as the door opens. If bulb continues to fluoresce, the interlocks are either malfunctioning or have been jumped.