AD-778 358

CHEMICAL LASER SYSTEMS

Milton J. Linevsky, et al

General Electric Company

Prepared for:

Army Missile Command Advanced Research Projects Agency

28 February 1974

DISTRIBUTED BY:

National Technical Information Service U. S. DEPARTMENT OF COMMERCE 5285 Port Royal Road, Springfield Va. 22151

(Security classification of title, body of abstract and ind	ONTRAL STATE	Thu	-118.00
OBIGINA TANG A STATE OF	UNTROL DATA - R & D	I when the	
General Electric Corporate euthor)	2a. R	EPORT SE	CURITY CLASSIFICATION
Space Division	U	nclassi	fied
Space Sciences Laboratory	2 <i>b</i> . G	ROUP	
REPORT TITLE	N,	/A	
CHEMICAL LASER SYSTEMS			
OESCRIPTIVE NOTES (Type of report and inclusive datas) Interim Technical Report			
AUTHOR(S) (First name, middle initial, last name)			
Milton J. Linevsky Ralph A. Carabetta			
REPORT DATE	78. TOTAL NO. OF PAGE	ES	76. NO. OF PEER
1 September 1973 - 28 February 1974	34		9
THE TOTOL OF THE TOTOL	98. ORIGINATOR'S REPO	RTNUMB	ER(5)
PROJECT NO.	74		
ARPA Order No. 1180	/4		
PROGRAM Code No. 2F20	96. OTHER REPORT NO	S) (Any oth	et numbere that may be seed
	this report)		unar unar unay ba assiĝna
OISTRIBUTION STATEMENT			
	Rep	NATION	TTOINIGH
		NEORMA	TION SERVICE
the second se			
		U S Depart Springt	ment of Commerce
SUPPLEMENTARY NOTES	12. SPONSORING MILITAN	S Depart Springf	ment of Commerce field VA 22*51
SUPPLEMENTARY NOTES	12. SPONSORING MILITAL Defense Advanc	ed Rese	earch Projects Agen
SUPPLEMENTARY NOTES	Defense Advanc U.S. Army Miss Bedstone Amson	ed Rese	earch Projects Agen
ABSTRACT	12. SPONSORING MILITAT Defense Advanc U.S. Army Miss Redstone Arsen	ed Rese ile Cor al, Ala	earch Projects Agen mand abama
ABSTRACT A number of chemical reactions leading to the formather mploying a diagnostic technique developed during the earlier of s the exchange reaction: $(1 + HI + HCI^{\ddagger} + 1)$ hlorine atoms were produced by microwave discharge in chlorine pressure of approximately 3 torr. Under these conditions, 3 ibrational-rotational transitions in HCL Spectroscopic measu- hat, assuming no chaining, i.e., one HCL molecule produced per ociated to CL atoms in the microwave discharge. Based on the of hemical efficiency has been found to be ca. 15%. Under these of een observed. An infrared interferometric technique has been employed time) measurement of the spontaneous HCL [‡] emission as a function eporting period, a fairly extensive effort has been made to imp ata. Full implementation of this technique will considerably study of other lasing molecules as well, e.g., UF, HF, etc. During the course of the studies on the CL + HI reaction ion which has been observed to accompany that from HCL. Becaus surce of this emission in the CL + HI reaction and in the [0(³ P) A number of other HCL producing reactions have also he is not yet complete, the results will not be included in this re Finally, a small effort to investigate means for efficient is these experiments, Cu metal atoms were electrically excited bo gon. In a separate set of experiments, the CuCl/Ar mixture wa	12. SPONSORING MILITAI Defense Advanc U.S. Army Miss Redstone Arsen out of vibrationally excited HCI ourse of this program. To date All = -32 kcal/mole -helium mixtures and rapidly min watts (cw) of laser power have rements of the total HCI populat Conditions, lasing lines from be conditions, lasing lines from be been to develop a diagnostic proce on of lucation along the flow ax prove the quality of the interfer simplify the diagnostis of HCI la con, measurements were made of t is of the interest in iodine as (C) (14, 32)] + HI reaction have rements of a spectroscopic exa (C)(14, 32)] + HI reaction have port but will he discussed thor iently producing metal atoms by y means of a pulsed electric di s reacted with Xa, viz.	Ave been the most y all, Ala have been the most y all, Ala have been the most y all, Ala have been the most y all, Ala been obtain tion produc ow, approxi- flow rate of oth IIC1 iso bedure which cis of the rememerical isers and s he atomic a lasing s the heat of the a lasing the chemical isonary of the most y the	studied spectroscopically promising system examined (1) studied spectroscopically promising system examined (1) in a fast-flow reactor at ned in a number of P-hranch ed by the reaction indicate mately 20% of the 12 is dis- "C1 atoms, the estimated trepes (IIC135 and IIC137) have makes possible the spatial reactor tube. During this ly derived line intensity hould be applicable to the iodine $({}^{2}P_{1/2}) + ({}^{2}\Gamma_{3/2})$ emis- pecies, a hrief study of the ried out. f the SO + N2O reaction to pro- out. However, since this work the Final Report. reaction has been initiated. rough CuCl vapor diluted with
ABSTRACT A number of chemical reactions leading to the formather mploying a diagnostic technique developed during the earlier est s the exchange reaction: $(1 + HI + HCI^{\frac{1}{2}} + 1)$ hlorine atoms were produced by microwave discharge in chlorines pressure of approximately 3 torr. Under these conditions, 3 ibrational-rotational transitions in HCL. Spectroscopic measures hat, assuming no chaining, i.e., one HCL molecule produced per ociated to CL atoms in the microwave discharge. Based on the of hemical efficiency has been found to be ca. 15%. Under these of een observed. An infrared interferometric technique has been employed time) measurement of the spontaneous HCL* emission as a function eporting period, a fairly extensive effort has been made to imp ata. Full implementation of this technique will considerably s tudy of other lasing molecules as well, e.g., UF, HF, etc. During the course of the studies on the CL + HI reaction ion which has been observed to accompany that from HCL. Because source of this emission in the CL + HI reaction and in the [0(2P) A number of other HCL producing reactions have also her is so yet complete, the results will not be included in this re- Finally, a small effort to investigate means for effici these experiments, Cu metal atoms were electrically excited by gon. In a separate set of experiments, the CuCl/Ar mixture wa Na + CuCl + ectroscopic measurements of the copper 3248Å and 5105Å emissio e 3248Å resonance transition suggesting that reaction (2) subs	12. SPONSORING MILITAL Defense Advanc U.S. Army Miss Redstone Arsen on of vibrationally excited HCI ourse of this program. To date All = -32 kcal/mole -helium mixtures and rapidly mix watts (cW) of laser power have rements of the total HCI populat Cl atom introduced into the floc energy released by (1) and the floc conditions, lasing lines from be able to develop a diagnostic proce on of lucation along the flow ax prove the quality of the interfe simplify the diagnosis of HCI Ia on, measurements were made of t the of the interest in iodine as ($C_2/N_2O/O_2$ flame laser has be port but will he discussed thor iently producing metal atoms by y means of a pulsed electric di s reacted with Na, viz., Cu + NaCI n lines showed that the additio tantially increases the Cu atom	ed Rese ile Cor al, Ala have been the most y xed with III been obtai tion produc flow rate o oth IIC1 isc edure which isers and s he atomic a lasing s re heen car mination o chemical scharge th:	studied spectroscopically rearch Projects Agen mand abama studied spectroscopically promising system examined (1) in a fast-flow reactor at ned in a number of P-hranch ed by the reaction indicate mately 20% of th. 212 is dis- "C1 atoms, the estimated tepes (IIC135 and IIC137) have makes possible the spatial reactor tube. During this ly derived line intensity hould he applicable to the iodine $({}^{2}P_{1/2}) + ({}^{2}\Gamma_{3/2})$ emis- pecies, a hrief study of the ried out. f the S0 + N20 reaction to pro- out. However, since this work the Final Report. revetion has been initiated, rough CuCl vapor diluted with (2) hances radiation trapping in tion in the discharge gases.
ABJERACT A number of chemical reactions leading to the formation mploying a diagnostic technique developed during the earlier es- s the exchange reaction: C1 + H1 + HCl [‡] + 1 hlorine atoms were produced by microwave discharge in chlorine pressure of approximately 3 torr. Under these conditions, 3 ibrational-rotational transitions in HCL. Spectroscopic measur- det to C1 atoms in the microwave discharge. Based on the of- themical efficiency has been found to be ca. 15%. Under these of time) measurement of the spontaneous HCl [®] emission as a function porting period, a fairly extensive effort has been made to imp- ata. Full implementation of this technique will considerably se- tudy of other lasing molecules as well, e.g., DF, HF, etc. During the course of the studies on the C1 - HI reaction ion which has been observed to accompany that from HCL. Becaus- burce 502(381) has heen initiated and some additional work on the is not yet complete, the results will not be included in this re- Finally, a small effort to investigate means for effic these experiments, Cu metal atoms were electrically excited has gon. In a separate set of experiments, the CuCl/Ar mixture wa Na + CuCl - Na	12. SPONSORING MILITAL Defense Advanc U.S. Army Miss Redstone Arsen out of vibrationally excited HCI ourse of this program. To date All = -32 kcal/mole -helium mixtures and rapidly mit watts (cw) of laser power have rements of the total BCI populat Cl atom introduced into the flo- energy released by (1) and the flo- conditions, lasing lines from be ent to develop a diagnostic proce on of lucation along the flow as prove the quality of the interfe simplify the diagnosis of HCI la on, measurements were made of t the of the interest in iodine as $(52/N_0/O_2$ flame laser has bee port but will he discussed thor iently producing metal atoms by y means of a pulsed electric di s reacted with Na, viz., Cu + NaCl n lines showed that the addition tantially increases the Cu atom	Ave been the most of the most	studied spectroscopically promising system examined (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)

1

Ù

personana a

1

Provincia da la

-

1

Π

And the second s

Landa Landa

France - -----

- supprised

KEY WORDS	LIN	K A	LINK		LINK C
	ROLE	WT	ROLE	NT R	OLE WT
HCl Lasers HCl Spectroscopy					
I ₂ Laser					
Metal Vaporization					
		1.51			
		±.			
				1.5	_
		S			
	1.00				
	and Street			561	-
				_	

INTERIM TECHNICAL REPORT 1 SEPTEMBER 1973 - 28 FEBRUARY 1974

CHEMICAL LASER SYSTEMS

MILTON J. LINEVSKY and RALPH A. CARABETTA

GENERAL ELECTRIC COMPANY SPACE DIVISION SPACE SCIENCES LABORATORY P.O. BOX 8555 PHILADELPHIA, PA. 19101

PROJECT SCIENTIST - MILTON J. LINEVSKY (215) 962-3495/3180

DAAHU1-73-2-0653

ARPA ORDER NO. 1180 PROGRAM CODE NO. 2E20 AMOUNT OF CONTRACT: \$255,787

Transfer a

Partners of

A REAL PROPERTY OF

A ALARMAN A

CONTRACT NO. DAH01-73-C-0653 DATE OF CONTRACT: 1 March 1973 EXPIRATION DATE: 1 August 1974

The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Defense Advanced Research Projects Agency or the U.S. Government.

> MONITORED BY THE U. S. ARMY MISSILE COMMAND REDSTONE ARSENAL, ALABAMA

> > iv

Approved for public relevant

TABLE OF CONTENTS

a start and the start of the start start of

[]

State of the

			Page
	SUMMA	RY	. 1
1.0	INTRO	DUCTION	. 3
2.0	HC1 S	TUDIES	. 5
	2.1	BACKGROUND	. 5
	2.2	FLOW REACTOR STUDIES	. 7
		2.2.1 Flow Reactor and Optical Set-Up	. 7
		2.2.2 C1 + HI Reaction	10
		2.2.2.1 Measurements of Lasing Power	. 10
		2.2.2.2 Spectroscopy	. 13
		2.2.2.3 Electronically Excited Iodine Population.	. 21
		2.2.2.4 Related Work	. 23
3.0	VISIB	LE CHEMICAL LASERS	. 24
	3.1	BACKGROUND	. 24
	3.2	ALKALI METAL/METAL HALIDE STUDIES	. 26
	REFER	ENCES	. 30

FIGURES

Figure	1.	Flow Reactor Schematic					
	2.	HC1 Lasing Line Spectrum	14				
	3.	HC1 Spontaneous Emission Spectra	16				
	4.	Isotopic Ratio vs Gain	20				
	5.	Metal Vapor Generator	28				

TABLES

Table	Ι.	Fundament	al Measure	ements	on	Some H	HC1 Pr	oducing	Reactions	6
	II.	Isotopic	Intensity	Ratio	for	Lines	s Show	ing Gair	1	19

SUMMARY

A number of chemical reactions leading to the formation of vibrationally excited HCl have been studied spectroscopically employing a diagnostic technique developed during the earlier course of this program. To date the most promising system examined is the exchange reaction:

$$C1 + HI \rightarrow HC1^{\ddagger} + I \qquad \Delta H = -32 \text{ kcal/mole}$$
(1)

Chlorine atoms were produced by microwave discharge in chlorine-helium mixtures and rapidly mixed with HI in a fast-flow reactor at a pressure of approximately 3 torr. Under these conditions, 3 watts (cw) of laser power have been obtained in a number of P-branch vibrational-rotational transitions in HC1. Spectroscopic measurements of the total HC1 population produced by the reaction indicate that, assuming no chaining, i.e., one HC1 molecule produced per C1 atom introduced into the flow, approximately 20% of the C1₂ is dissociated to C1 atoms in the microwave discharge. Based on the energy released by (1) and the flow rate of C1 atoms, the estimated chemical efficiency has been found to be <u>ca</u>. 15%. Under these conditions, lasing lines from both HC1 isotopes (HC1³⁵ and HC1³⁷) have been observed.

As has already been described in Ref. (1), an infrared interferometric technique has been employed to develop a diagnostic procedure which makes possible the spatial (time) measurement of the spontaneous HC1[‡] emission as a function of location along the flow axis of the reactor tube. During this reporting period, a fairly extensive effort has been made to improve the quality of the interferometrically derived line intensity data. Full implementation of this technique will considerably simplify the diag-

1

A Contractor L'Administra - -----Transformer 1

nosis of HCl lasers and should be applicable to the study of other lasing molecules as well, e.g., DF, HF, etc.

During the course of the studies on the Cl + HI reaction, measurements were made of the atomic iodine $({}^{2}P_{1/2}) \rightarrow ({}^{2}P_{3/2})$ emission which has been observed to accompany that from HCl. Because of the interest in iodine as a lasing species, a brief study of the source of this emission in the Cl + HI reaction and in the $[O({}^{3}P), O_{2}({}^{1}\Delta, {}^{3}\Sigma)]$ + HI reaction have been carried out.

A number of other HCl producing reactions have also been studied; a spectroscopic examination of the SO + N_2O reaction to produce $SO_2({}^{3}B_1)$ has been initiated and some additional work on the $CS_2/N_2O/O_2$ flame laser has been carried out. However, since this work is not yet complete, the results will not be included in this report but will be discussed thoroughly in the Final Report.

Finally, a small effort to investigate means for efficiently producing metal atoms by chemical reaction has been initiated. In these experiments, Cu metal atoms were electrically excited by means of a pulsed electric discharge through CuCl vapor diluted with Argon. In a separate set of experiments, the CuCl/Ar mixture was reacted with Na, viz.,

$$Na + CuCl \rightarrow Cu + NaCl$$
 (2)

Spectroscopic measurements of the copper 3248Å and 5105Å emission lines showed that the addition of Na enhances radiation trapping in the 3248Å resonance transition suggesting that reaction (2) substantially increases the Cu atom concentration in the discharge gases.

1.0 INTRODUCTION

Part of the work performed under the present contract represents a continuation of last year's program. In that effort, a large number of combustion systems were examined spectroscopically to determine whether, under certain conditions, population inversions are produced in reaction products. The systems were examined in two separate experimental facilities: a conventional variable pressure flame apparatus; and a fast-flow reactor constructed during the course of the program. As a result of this work it was found that several carbon containing fuels, namely, cyanogen, acetylene, and carbon bisulfide, led to the production of highly vibrationally excited CO when reacted with atomic and/or molecular oxygen at reduced pressures (1-100 torr).

On the basis of these results it was proposed that studies of the $CS_2/O_2/N_2O$ system be extended. In addition to the continuing effort on CO, a screening program to investigate HCl producing reactions was proposed. In this work, a number of combustion systems which can potentially lead to vibrationally excited HCl were to be examined both in the flow reactor and in the low pressure flame facility. Also proposed for investigation under the current contract was the possibility of obtaining visible chemical lasing from species such as metal oxides. Specifically, metals derived from metal carbonyls or alkyls were to be interacted with atomic/molecular oxygen, or in some cases with N_2O .

Some phases of the above work have been carried out and reported on in the Scmi-Annual Technical Report on Chemical Laser Systems (Ref. 1) which describes the work performed on the present contract during the time period March 1, 1973 to September 1, 1973. This Interim Report describes

the work carried out in the time period September 1, 1973 to February 28, 1974, and details of the earlier work will not be repeated herein.

During this reporting period, the bulk of the effort was spent on studying the Cl + HI reaction which has been found to be quite efficient in its production of HCl^{\ddagger} . A small effort has also been directed to the excitation of atomic iodine formed in the Cl + HI and in the $O/O_2(^{3}\Sigma, ^{1}\Delta)/HI$ reactions.

Finally, a relatively modest effort was to be devoted to the study of "chemical/electrical hybrid lasers". Included for investigation in this category were means for chemically producing species in which population inversion could be induced electrically. The work to be reported on the copper vapor generator represents a preliminary effort toward this objective.

2.0 HC1 STUDIES

2.1 BACKGROUND

10

and and

- Strands

Constant of

The practical incentive for the study of $HC1^{\ddagger}$ producing reactions stems from the need to produce an efficient high power laser system operating at wavelengths lying within an atmospheric window. The HCl molecule with vibrational-rotational transitions in the wavelength region $3.7-4.0\mu$ seems especially actractive in this regard. For example, Wang (Ref. 2) has recently computed the atmospheric transmission for a number of $v = 3 \rightarrow 2$ and $v = 2 \rightarrow 1$ P-branch transitions of HCl³⁵ and HCl³⁷. Included in the model were atmospheric attenuation by H_20 , N_20 , CO_2 , and CH_4 as well as extinction by aerosols. The results show that the vertical transmittance through t' entire atmosphere for the J = 8 \rightarrow 4 lines are about 90% or greater; the horizontal transmittance of these lines for a l0km path length at sea level are about 70% or greater.

Although HCl was the first molecule in which chemical pumping was observed, it seems that until recently relatively little effort has been directed toward the development of a chemical laser based on this molecule.

Much of the fundamental work on HCl[‡] producing reactions has been carried out by Polanyi and his colleagues (Refs. 3-5) over the past six years. In these experiments, measurements of the spontaneous emission from HCl[‡] at very low pressure have permitted a determination of the relative rates at which a given chemical reaction populates the individual levels of the product molecule. A compilation of some pertinent reactions for which such information is available is given in Table I. The table lists the frac-

TABLE I

FUNDAMENTAL MEASUREMENTS ON SOME HCL PRODUCING REACTIONS

EXOTHER- MICITY $f_T = f_V = f_R = k_0 = k_1 = k_2 = k_3 = k_4 = k_5 = k_6$.	C1 46.5 0.49 .43 .08 \sim 0 0.2 0.7 1.0 0.1	I 32.0 0.16 0.71 0.13 ∿ 0 0.2 0.3 1.0 0.7	I 32.0 0.16 0.71 0.13 0 0.12 0.35 0.73 1.0 0.05	I 46.5 0.49 0.40 0.10 0.1 0.33 1.0 0.86 0.25 0.06	SC1 46.0 0.43 0.53 0.72 1.0 0.83 0.25	F 34.5 0.27 0.66 0.07 ∿ 0 0.7 1.0 0.7	n of Energy in Translation, Vibration, Rotation.
XOTHER- XICITY from from from from from from from from	46.5 0.49 .43 .08	32.0 0.16 0.71 0.13	32.0 0.16 0.71 0.13	46.5 0.49 0.40 0.10	46.0 0.43	34.5 0.27 0.66 0.07	ergy in Translation, Vibrati
REACTION REACTION	$H + C1_2 \rightarrow HC1 + C1$	C1 + HI + HC1 + I	$CI + DI \rightarrow DCI + I$	$D + C1_2 + DC1 + I$	H + SC1 ₂ → HC1 + SC1	$F + D_2 \rightarrow DF + F$	$f_{T,V,R} = Fraction of Entry V_{r,R}$

.

[]

Ī

and the second s

tion of the exothermicity that appears in the three degrees of freedom of the product, and the relative rates at which the vibrational levels are populated. For all of the reactions listed, the vibrational levels of the products are populated up to the limit determined by the exothermicity of the reaction. Data for DF has been included for comparison because, as for HCl, DF vibrational-rotational transitions lie in a very favorable wavelength region.

The data in Table 1 show, for example, that the Cl + HI reaction compares favorably with $F + D_2$ with respect to both the energy released and the mode in which the reaction partitions energy into accessible vibrational levels. In the evaluation of this reaction as a pumping source for a high power laser, the absolute values of the rate constants for HCl[‡] formation and quenching must be taken into account, as well as other practical considerations such as the high atomic weight of iodine which may increase system weight and make diffusive mixing of Cl with HI difficult. However, proper injector design and the possibility of recycling the iodine to make HI may minimize these problems and should be the subjects of investigation in future work.

2.2 FLOW REACTOR STUDIES

2.2.1 Flow Reactor and Optical Set-Up

A schematic of the flow reactor employed in these studies is shown in Figure 1. The device was constructed in sections to permit disassembly for cleaning or for modification. Diluent gas, He, Ar, etc., is admitted into the first section, allowed to expand, and is then injected downstream through a perforated plate to obtain uniform flow throughout the reactor



Figure 1. Flow Reactor Schematic

1

and the second se

cross-section. Discharge products are admitted into the second section via a 0.5" diameter quartz tube which traverses the 6" reactor width. The gases are injected downstream through a number of holes drilled along the length of the tube. Half of the total discharge flow enters through each end of the quartz tube; two microwave (2450 MHz) power supplies, each rated at 125 watts are used as power sources, and energy is coupled into the gases in nitrogen-cooled Evanson cavities. The reactor sections through which the discharges flow are lined with teflon tape to minimize surface recombination of atoms.

Fuels are injected into the laser section, in a direction perpendicular to the main gas flow, through a total of approximately 15 holes drilled into the injector tubes (see section "A", Figure 1). The 7" long laser section is fitted with rectangular Brewster salt windows so that optical measurements can be made in the volume of gas extending from the injector tubes to a point 4" downstream. A small flow of inert gas is uniformly distributed over the window surface to help keep them clean. Cavity mirrors are mounted on an optical bench and can be translated along the direction of gas flow. Gases from the laser section exit through an expansion section into a plenum chamber and are exhausted with a 1200 cfm Roots blower.

Measurements of spontaneous emission were made along the length of the flow reactor. For this purpose, a light gatherer consisting of a number of mirrors and stops was employed to obtain a spatial resolution of approximately 2 mm along the direction of gas flow. For typical flow conditions, this corresponds to a time resolution of \sim 15 microseconds. Spectroscopic measurements of the lasing lines and of the spontaneous HCl emission were made with a Digilab FTS-14 scanning interferometer using LN₂ cooled Hg:Cd:Te

or PbS detectors.

2.2.2 C1 + HI Reaction

2.2.2.1 Measurements of Lasing Power

As discussed in the Semi-Annual Report (Ref. 1) the primary objective of the work on this reaction was to develop an optical diagnostic technique to facilitate the study of reaction systems which may lead to efficient HCl lasing. It was felt that through a detailed analysis of the spontaneous HCl emission, the performance of a number of HCl[‡] producing reactions could be rapidly evoluated. The Cl + HI reaction was chosen as the basis for this study as a matter of convenience because this system was found to produce HCl lasing quite easily, i.e., lasing action could be observed over a broad range of pressure and stoichiometry. As time went on, however, and as experience was gained with other HCl producing systems, it was soon realized that the Cl/HI reaction was more promising than originally anticipated. As a result, a substantial effort has been expended on the study of this system.

To date approximately 3.2 watts of lasing power has been obtained from a $Cl_2/HI/He$ mixture having a molar ratio of 1/1.66/125 at a total pressure of 3.7 torr; the same power level was obtained from a $Cl_2/HI/Ar$ mixture having a molar ratio of 1/1.66/31 at 1 torr. In both experiments, the flow of Cl_2 was 0.44 millimoles per second, the average gas velocity was about 140 meters per second, and the output was coupled from the cavity through a 3% transmitting dielectrically coated mirror. The total output obtained using two 3% mirrors, one on each end of the cavity, was virtually identical (1.55 watts/mirror) to that obtained using a single mirror; on this basis, optimum coupling is estimated to be between 3 and 6%. With a 3% coupling

mirror and a KBr flat placed intracavity to introduce an approximately 6% scattering loss, lasing was quenched. It is therefore estimated that neglecting absorptive and mirror (2%?) losses, the small-signal-gain in the system lies between 6 and 9% per round trip (\sim 30 cm) pass.

1

In the experiments described, the HI flow rate was about 0.75 millimoles per second. If it is assumed that laser output is limited by the HI flow, then, based on the exothermicity of Reaction (1) and the flow rate of HI, the maximum cw power level which can be achieved is <u>ca</u>. 98 watts. On this basis, the observed power level of 3.2 watts implies a minimum value of about 3.3% for the chemical efficiency.

In the preceeding calculation of efficiency, it has been tacitly assumed that approximately 83% or more of the Cl_2 flow is converted to Cl atoms, viz., 0.44 millimoles/sec x 0.83 x 2 = 0.73 millimoles/sec = HI flow rate. As has already been discussed in the Semi-Annual Report (Ref. 1), based on spectroscopic measurements of the total HCl concentration, a maximum of about 20% of the total Cl_2 flow is converted to Cl atoms which ultimately form HCl via Reaction (1). On this basis, the laser output is limited by the Cl atoms produced in the flow; the maximum power levels which can be achieved is about 23 watts and the observed output represents a chemical efficiency of 14%.

The dissociation of approximately 20% of the total Cl₂ flow by microwave discharge seems anomalously high; however, such percentages have been reported in the literature (Ref. 6). An alternative explanation for the relatively high HCl yields is that additional Cl atoms are produced in the reactive flow. One possibility is the simple chain:

 $C1 + HI \rightarrow HC1 + I$ $\Delta H \approx -20$ Kcal/mole

followed by

 $I + C1_2 \rightarrow IC1 + C1 \qquad \Delta H \approx 7 \text{ kcal/mole}$

At the relatively low temperatures associated with the gas flow, the endothermic Cl producing reaction would be expected to be negligibly slow. Nevertheless, the possibility exists that part of the Cl_2 emerging from the discharge is vibrationally excited and as a result the reaction of I with Cl_2 , cannot positively be precluded at this time. No attempt has been made to spectroscopically measure ICl using either absorption or resonance fluorescence techniques.

Attempts have also been made to employ a variety of chlorine containing substances to produce Cl atoms in the electric discharge. The substitution of nitrosyl chloride (ONCL) for Cl_2 , for example, was found to be reasonably effective. Approximately 1.1 watts of lasing power was obtained from an ONC1/HI/He mixture having the overall molar composition 1/3.5/260 at a total pressure of 3.6 torr. Based on the 0.21 millimole per second flow rate of ONCl, i.e., assuming 100% dissociation of ONCl to NO and Cl, the chemical efficiency is 4%. If it is assumed that 30% or so of the ONCl is dissociated in the discharge (the ON-Cl bond dissociation energy is approximately 38 kcal/mole <u>vs</u> 59 kcal/mole for Cl_2), the chemical efficiency is about 13% - comparable to that obtained using the Cl_2 discharge. Increasing the ONCl above the optimum value resulted in a decrease in power, suggesting quenching of HCl[‡] by excess ONCl or a decrease in the Cl atom concentration by a reaction such as

 $ONC1 + C1 \rightarrow NO + C1_2 \qquad \Delta H \approx -20 \text{ kcal/mole}$

or chain inhibition by the reaction

 $ONC1 + I \rightarrow NO + IC1$ $\Delta H \approx -12 \text{ kcal/mole}$

To date, the most suitable starting material for the production of Cl atoms in the microwave discharge has been found to be Cl_2 .

The effect of several additives on the laser output power was also briefly investigated. The addition of Ar, H₂, O₂, N₂, NO, CH₄, and SF₆: in quantities at least as large is the Cl₂ flow rate, did not appreciably alter the power levels obtained with the Cl₂/HI/He = 1/1.66/125, Cl₂ = 0.44 millimoles/sec, mixture which was used as a baseline flow. It was, in fact, possible to maintain the same peak power level of 3.2 watts when Ar, SF₆, or N₂ were substituted for He. In general, with the use of Ar, SF₆, or N₂, the peak power level was achieved with substantially lower diluent addition and at much reduced total pressures. With all diluents, the peak power conditions were found *G escur at approximately the same flow velocity and for the same Cl₂ (Cr HCl) concentration.

The addition of small quantities of either N_2^0 or $CO_2^{}$ was found to produce rather large decreases in the peak laser output level. This is, however, expected since it is well known that these molecules readily exchange vibrational energy with HCl[‡]. No attempt has been made to obtain lasing action from either $CO_2^{}$ or $N_2^{}O$.

2.2.2.2 Spectroscopy

Shown in Figure 2 is a typical set of lasing lines obtained by reflecting a very small fraction of a 3.2 watt beam into the entrance aperture of the interferometer. In this experiment the diluent used was He and the pressure was 3.7 torr; however, the results obtained using Ar diluent at



at lower pressure are similar. Note that in the nomenclature used to identify a transition, vP(J) or vR(J), v refers to the upper vibrational level while J refers to the lower rotational level of the transition. The isotopic abundance ratio Cl^{35}/Cl^{37} is approximately 3.08; therefore, assuming that the vibrational population distributions and the rotational temperature of $\mathrm{HC1}^{35}$ and $\mathrm{HC1}^{37}$ are identical, the gain in a given $\mathrm{HC1}^{35}$ transition should be about three times greater than that for a corresponding $HC1^{37}$ transition. Under conditions of low gain the only lasing lines observed are those of the most abundant isotope. For the conditions shown in Figure 2, lasing transitions are observed for both isotopes. A peculiarity of these data is that for the $HC1^{35}$ isotope, the strongest lasing transitions originate from the J = 6 and 5 rotational levels of the upper vibrational levels, whereas for $HC1^{37}$ the strongest transitions originate from the J = 4 and 3 levels. Indeed, for the most intense HCl³⁷ transition, 2P(5), the corresponding transition for HCl³⁵ is not observed. Since, for a given vibrational level, the line of maximum gain is determined by the vibrational population ratio between the upper and lower levels and the effective rotational temperature, these data suggest significantly different population distributions and/or rotational temperatures for the two isotopes. Whether this effect is the result of cascading among the vibrational levels of the $HC1^{35}$ isotope during lasing or vibrational exchange between $HC1^{35}$ and $HC1^{37}$ is uncertain.

0

Detailed, spatially resolved measurements of the HCl spontaneous emission have been carried out using a $Cl_2/HI/Ar = 1/2.6/140$ mixture at a total pressure of 3 torr. The total flow of Cl_2 in this experiment was about 0.12 millimoles per second. Typical spectra of the HCl spontaneous emission are shown in Figure 3. The data shown represent 20 co-added spectra of the



]

3

HCl fundamental taken with 0.5 cm⁻¹ spectral resolution. Associated with each transition are two peaks, the stronger from the HCl³⁵ and the weaker from the HCl³⁷ isotope. For a given transition in an optically thin gas, the I^{35}/I^{37} intensity ratio is 3.08 (Ref. 7).

As has already been discussed in Ref (1), the optically thin transitions could be employed directly to measure the rotational temperatures of the gas and to determine the vibrational population distribution of HCl relative to that in v = 1 as a function of location in the flow reactor. In addition, it was found possible to employ those transitions which exhibit self-absorption ($I^{35}/I^{37} < 3.08$), to measure the HCl concentration in the v = 0 and v = 1 vibrational levels. These data together with the relative population data permitted a total inventory of the HCl present at any location along the flow. From the results, it was possible to measure the smallsignal-gain for several transitions which were observed to lase.

The spectroscopic data can also, in principle, be employed directly to identify transitions which have gain. Entirely analogous to the more generally encountered case in which emission lines are self-absorbed by the emitting medium, the intensity of a line originating from a transition between levels in which a population inversion exists will be augmented by stimulation emission. For HCl, optical gain can be identified for a given transition by inspection of the I_{HC135}/I_{HC137} isotopic intensity ratio. In this case, the small-signal-gain (negative absorption) of the more abundant isotope will always be greater than that for the less abundant isotope, and the resulting isotopic intensity ratio will exceed 3.08.

1

The use of isotopic intensity ratios for the measurement of gain is useful for several reasons. In the Cl + HI reaction, for example, the

rate constant for the production of HCl in the v = 0 level is approximately zero (see Table I). Therefore, before appreciable quenching has occurred, the self-absorption of the $v = 1 \rightarrow 0$ transitions will not be of sufficient magnitude to permit a determination of the HCl concentration in the v = 0level. Under these circumstances, the isotopic intensity ratios of the v = $1 \rightarrow 0$ transition provide a most convenient measure of gain. The method is also especially suited for use with the HCl^{35/37} isotopes because, for a given transition, the isotopic line separation is less than 2 wavenumbers and corrections for system response with wavelengths are minimal. Also the formation kinetics and transition probabilities for the two isotopes can be considered to be identical.

As an example, examination of the data shown in Figure 3 shows that for several transitions, which are compiled in Table II, the observed isotopic intensity ratio exceeds 3.08. The lines for which this effect is observed are all P-branch transitions from rotational levels which are either the same or very close to those for which lasing action is observed. Under lasing conditions, the transitions having greatest gain are not necessarily identical to those which have the largest small-signal-gain because of cascading and other effects.

A plot of the expected variation of the isotopic ratios with the product $\alpha_0 \ell$, where α_0 is the small-signal-gain and ℓ is the path length, is shown in Figure 4. The calculation was carried out using the classical "line-absorption" method of Ladenburg and Reike (Ref. 8) assuming Doppler broadened profiles for the HCl lines. A comparison of the isotopic ratio data given in Table II with the corresponding values of $\alpha_0 \ell$ from Figure 4 shows that for most lines, especially the 2P(7) and the 1P(8) transitions,

TABLE	Ι	I
-------	---	---

e

[]

 \Box

 $\left[\right]$

ISOTOPIC INTENSITY RATIO FOR LINES SHOWING GAIN

TRANSITION	RATIO	TRANSITION	RATIO	
3P(6)	3.13	1P(8)	3.5	
3P(5)	3.15	1P(7)	3.2	
2P(7)	3.41	1P(6)	3.15	
2P(5)	3.19			



20

-

the values for gain obtained using this technique are unrealistically high. In fact, the principal limitation of this method seems to be the accuracy to which the line intensities could be measured.

A fairly extensive effort has been directed toward improving the accuracy of the intensity data provided by the infrared interferometer. A variety of techniques recommended by the manufacturer (Digilab) have been tried but to date intensity data reliable to better than about 10% have not been obtained and probably cannot be achieved employing the software package currently in the machine. However, a new software package which utilizes double-precision computational techniques has recently been made available and is scheduled for delivery in the very near future. It is felt that with this modification the accuracy of the interferometer will be much improved. Should this still not prove adequate, isotopic intensity ratios will be measured using a standard grating instrument with a suitable high sensitivity detector. Since, in this latter approach, the light collection efficiency of the interferometric method will be lost, it is felt that the small additional effort to be expended using the new computer software is warranted.

2.2.2.3 Electronically Excited Iodine Production

Throughout the course of the Cl + HI studies in the flow reactor it has been observed that chemiluminescent iodine $({}^{2}P_{1/2}) \rightarrow ({}^{2}P_{3/2})$ emission accompanies the reaction. The emission commences at the Cl/HI mixing region and persists throughout the entire 10 cm length of the flow reactor.

There are two obvious mechanisms which can lead to hot iodine production. The first is the direct formation of I^* by:

 $C1 + HI \rightarrow HC1 + I^*$

which is sufficiently exothermic to excite iodine; the second is vibrational transfer between ground state iodine and vibrationally excited HC1, viz.:

HC1 (v = 3) + I(
$${}^{2}P_{3/2}$$
) \rightarrow HC1 (v = 0) + I(${}^{2}P_{1/2}$)

To help distinguish between those two mechanisms a series of experiments were carried out. It was found that very small flows of CO_2 and N_2O were sufficient to quench not only HCl[‡] (as expected) but also I^{*} emission. In a related set of experiments, a flow of molecular oxygen and He was passed through the microwave cavities, and the mixture of atomic and molecular (ground state and ${}^{1}\Delta_{g}$) oxygen produced was subsequently reacted with HI. In this experiment, it was found that for the same flow of HI as was used in the Cl + HI case, the I^{*} emission was approximately two orders of magnitude more intense. Furthermore, the addition of large quantities of CO_2 or N_2O did not effect the intensity of the I^{*} emission.

Finally, atomic oxygen was produced by N atom titration with NO (i.e., little or no $O_2({}^{1}\Delta)$), and interacted with HI. In these experiments it was found that I^{*} emission intensity was comparable to that obtained in the Cl + HI reaction.

On the basis of these experiments, it has been tentatively concluded that in the Cl + HI reaction, I^* is excited by transfer with HCl in vibrational levels v > 3, and that a similar transfer mechanism, perhaps

$$OH^* + I \rightarrow OH + I^*$$

gives rise to I^{*} in the 0 + HI reaction. The very strong emission observed in the $0/0_2$ reaction with HI is very likely produced primarily by energy exchange of I with $0_2(^{1}\Delta)$, i.e.:

$$I({}^{2}P_{3/2}) + O_{2}({}^{1}\Delta_{g}) \rightarrow I({}^{2}P_{1/2}) + O_{2}({}^{3}\Sigma_{g})$$

2.2.2.4 Related Work

Within the last month of the reporting period several modifications have been made to the flow reactor and to the associated microwave discharge section. A new laser section has been constructed; similar in design to that shown in Figure 1, the new section incorporates a flat rectangular transparent lexan window in its upper surface. With this port, the flow within the reactor can be visualized at a variety of flow conditions (illumination provided by chemiluminescent reactions) to ensure proper mixing of fuel and oxidizer, etc. Plans are also being made to install a row of pin electrodes into the lexan top so that species formed by chemical reaction can be excited electrically. With regard to the discharge section, a 1000 watt, 2450 MHz, microwave power supply has been installed for discharging O₂, Cl₂, etc.

3.0 VISIBLE CHEMICAL LASERS

3.1 BACKGROUND

The second secon

Concerning of

a succession in

A STATE OF A STATE

1

Π

AND ADDRESS OF A

Chemiluminescent reactions which produce electronically excited species have received considerable attention as possible sources for pumping visible chemical lasers. Of special interest are metal oxide species which can be relatively easily formed in electronically excited states by chemical reaction, and for which, in some instances, favorable Franck-Condon factors exist for transitions from low vibrational levels of the excited state to high (non-thermally populated) vibrational levels of the lower electronic state. It has recently been reported (Ref. 8), for example, that in the reaction

$$Ba + N_2^0 \rightarrow Ba0^* + N_2$$

electronically excited BaO $({}^{1}\Sigma^{+})$ is produced with an efficiency of approximately 10% (Ref. 9).

To obtain visible lasing between electronic transitions, a number of demanding criteria must be met. Depopulation of the upper laser levels by spontaneous emission, which can be almost ignored for infrared vibrational-rotational transitions, is an important loss mechanism in the visible region because of the large transition probabilities associated with electronic transitions. This loss, together with the fact that the pumping reaction will distribute its products among a number of rotational-vibrational levels in the upper state, imposes severe requirements for the pumping rate which must be achieved in order to produce threshold gain. Thus it has been estimated (Ref 9) that to obtain visible chemical laser action in a diatomic molecule, excitation rates of the order of $10^{19}-10^{21}$ molecules/cm³ sec are required. For excitation via a two-body reaction, for example, if it is assumed that the effective rate constant for pumping is <u>ca</u>. 10^{-12} cm³/molecule second (i.e., ~1% efficiency for a gas kinetic reaction), then the product of the metal atom and oxidizer concentration which must be sustained for cw lasing must be quite high, of the order of $10^{18}-10^{22}$ molecule²/cm⁶. This result implies that to achieve chemical visible lasing, methods must be found to produce high flow rates of metals, and that the most promising reactions will involve oxidizers which can be supplied easily in relatively high concentrations, e.g., N₂0, O₂, etc.

In the work which has already been reported on in the Semi-Annual Report (Ref. 1), a number of chemical reactions have been investigated for their potential to produce electronically excited species, such as metal oxides, which may be of interest with regard to visible lasing. The approach taken was to spectroscopically survey the visible chemiluminescent emission produced by the interaction of metal or metal containing species with mixtures of atomic and molecular oxygen or with N_2O . Following this survey, absolute intensity measurements of the band systems and continua were carried out and production rates for some excited species estimated. Although a number of reactions have been investigated in this manner, e.g., trimethylaluminum + O, BCl₃ + O, Ni (heated $N_1(CO)_5$) + N_2O , Fe (heated Fe(CO)₅) + N_2O , the results obtained to date have not been encouraging in that, in all instances, only a very small fraction of fuel, <u>ca</u>. 10⁻⁴, could be converted to electronically excited oxide. Similar results have been obtained in a parallel study (Ref. 9) in which encapsulated metals were reacted with F₂, N_2O ,

or 0_2 . On this basis, alternative methods were sought for easily producing metal atoms for either electrical excitation or for further reaction with an oxidizer to produce electronically excited diatomic metal compounds.

3.2 ALKALI METAL/METAL HALIDE STUDIES

A review of the physical properties of a number of metals and their compounds reveals that in several cases, the halides of relatively involatile metals can have appreciably high vapor pressures at just moderately elevated temperatures. Since in many cases the reaction of these halides with alkali metals, which are themselves relatively volatile, are exothermic and therefore conceivably fast, a small effort was initiated to determine whether the reduction of metal halides by, for example, Na, would be a favorable route for free metal production. The choice of the CuCl/Na system as the starting point for these studies was based on several factors. First, copper metal atoms are of inherent interest to the laser community; electrically pumped copper vapor lasers can potentially be quite efficient. Second, lasing action in Cu has been observed in electrically discharged CuCl vapor/diluent mixtures - the presence of CuCl does not therefore have a deleterious effect on the performance of the Cu laser. Finally, CuCl and Na are compatible in terms of temperature. For example, at 600°K the equilibrium concentration of Na (gas) over liquid sodium is \sim 6.4 x $10^{14}/{
m cm}^3$ while the equilibrium concentration of (CuCl)_z over CuCl (solid) is \sim 8.8 x 10^{13} /cm³. Therefore, at this relatively low temperature, both Na and Cu can be produced in roughly stoichiometric proportions and at sufficiently high number density to permit threshold conditions to be achieved for a reasonably small copper atom path length (note that to obtain \sim 2 x 10^{14} /cm³ Cu (gas) over Cu (solid), T eq

1600°K).

A schematic of the experimental apparatus is shown in Figure 5. The device consists, basically, of an instrumented quartz tube, resistively heated to temperatures of approximately 600-700°K. Electrical excitation was carried out by means of 5 kv, 1 KHz, pulses having risetimes of approximately 150 nanoseconds; the pulse width at half height was approximately 175 nanoseconds. When the experiments were initiated, a separately heated reservoir was used for vaporizing CuCl prior to its introduction into the tube. It was found, however, that CuCl could more easily and uniformly be distributed in the gas phase by simply allowing CuCl (solid), which was vacuum deposited on the walls of the quartz tube before the experiment, to vaporize as the tube was heated to its final temperature.

Measurements of the emission intensities of the Cu 5105Å green line and the 3248Å resonance line were carried out using a 1/2-meter JACO monochromator. In all experiments, Cu emission could only be observed while the discharge was turned on, i.e., no chemiluminescence could be observed in the reaction of (CuCl)₃ with Na.

At very low, temperatures, i.e., low concentrations of $(CuCl)_3$ in the vapor phase, and with no sodium present, the intensity ratio, $I_{3248\text{\AA}}/I_{5105\text{\AA}}$, was approximately 100/1. As the temperature and therefore the concentration of $(CuCl)_3$ increased, radiation trapping of the resonance transition was observed; at T = 600°K, $I_{3248\text{\AA}}/I_{5105\text{\AA}}$ was reduced to about 1/2.4. The introduction of Na into the tube under these conditions resulted in a five-fold increase in the intensity of the 5105\text{\AA} line and a four-fold increase in the intensity of the resonance transition; the resulting $I_{3248\text{\AA}}/I_{5105\text{\AA}}$ $I_{5105\text{\AA}}$ ratio therefore decreased to about 1/3. On the basis of these mea-



surements, it was estimated that the copper atom concentration produced by the reaction of Na and $(CuCl)_3$ was $\geq 5 \times 10^{12}/cm^3$. Several other observations also indicate relatively rapid reaction of Na with the halide. For example, the relatively strong CuCl banded emission which is observed in the discharge through $(CuCl)_3/Ar$ mixture is very markedly reduced when Na is admitted into the system. Similarly, the sodium D-line emission which is observed in the discharge through $(CuCl)_3/Na/Ar$ mixtures, is observed to increase in intensity when all of the CuCl deposited on the wall is completely used up.

Although the effort expended to date on this task has been a modest one, the results appear to be rather encouraging. On the basis of the experiments described, it is felt that the production of metal vapor by chemical reaction is feasible and that these studies should be continued, not only with CuCl, but with other metal halides as well.

REFERENCES

- M. J. Linevsky and R. A. Carabetta, Chemical Laser Systems, Semi-Annual Technical Report, 1 March - 1 September 1973. GE Doc. No. 73SD4278.
- 2. J. Y. Wang, Applied Optics, 13, 56 (1974).

- 3. K. G. Anlauf, Ph.D. Thesis, University of Toronto (1968).
- 4. D. G. Maylotte, Ph.D. Thesis, University of Toronto (1968).
- 5. K. B. Woodall, Ph.D. Thesis, University of Toronto (1968).
- 6. See for example, N. V. Sidwick, <u>The Chemical Elements and Their</u> Compounds, Oxford (1950).
- 7. J. R. Airey, F. D. Findlay, and J. C. Polanyi, Can. Jour. Chem., 42, 2193 (1964).
- 8. Ladenburg, R., and Reiche, F., Ann. d. Phys. <u>42</u>, 181 (1913). See also, A.C.G. Mitchell and M. W. Zemansky, <u>Resonance Radiation</u> and Excited Atoms, Cambridge University Press (1961).
- 9. D. J. Eckstrom, S. A. Edelstein, S. W. Benson, A. Black, and M. Luria, Study of New Chemical Laser Systems, Technical Report RK-CR-73-6 (SRI MP #73-15), Stanford Research Institute.