

## TECHNICAL REPORT NO. 74-62

### EMERGENCY DISTRESS SIGNALLING DEVICE

COUNTED IN

20081001 201

IML TR-74 c. 2

62

C. L. Paxton Communications & Electronics

by

F

April 1974 Final Report TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

# U.S. ARMY LAND WARFARE LABORATORY

Aberdeen Proving Ground, Maryland 21005

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

ECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)	
REPORT DOCUMENTATION PAGE	
REFORT DOCUMENTATION FACE	READ INSTRUCTIONS BEFORE COMPLETING FORM
. REPORT NUMBER 2. GOVT ACCESSION NO	3. RECIPIENT'S CATALOG NUMBER
TECHNICAL REPORT NO. 74-62	
TITLE (and Subtitie)	5. TYPE OF REPORT & PERIOD COVERED
	Final Popart
EMERGENCY DISTRESS SIGNALLING DEVICE	Final Report
	6. PERFORMING ORG. REPORT NUMBER
AUTHOR(e)	8. CONTRACT OR GRANT NUMBER(s)
C. L. Paxton	
Communications & Electronics Branch	×
	10. PROGRAM ELEMENT, PROJECT, TASK
PERFORMING ORGANIZATION NAME AND ADDRESS	AREA & WORK UNIT NUMBERS
US Army Land Warfare Laboratory	Task No. 03-E-72
Aberdeen Proving Ground, MD 21005	
1. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
	May 1974
	17
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)	15. SECURITY CLASS. (of this report)
	SCHEDULE
6. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimit	ted
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimit 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different f	ted
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimit 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different f 18. SUPPLEMENTARY NOTES	ted rom Report) TECHNICAL LIBRARY BLDG. 305
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimit 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different f 18. SUPPLEMENTARY NOTES	TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL
<ul> <li>16. DISTRIBUTION STATEMENT (of this Report)</li> <li>Approved for public release; distribution unlimited in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement is second statement in the second statement in the second statement in the second statement is second statement in the second statement in the second statement in the second statement in the second statement is second statement in the s</li></ul>	TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL
<ul> <li>16. DISTRIBUTION STATEMENT (of this Report)</li> <li>Approved for public release; distribution unlimit</li> <li>17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, 11 different f</li> <li>18. SUPPLEMENTARY NOTES</li> <li>19. KEY WORDS (Continue on reverse side if necessary and identify by block number radio transmitter radio alarm emergency beacon arctic commemergency radio</li> </ul>	TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL.
<ul> <li>16. DISTRIBUTION STATEMENT (of this Report)</li> <li>Approved for public release; distribution unlimit</li> <li>17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different f</li> <li>18. SUPPLEMENTARY NOTES</li> <li>19. KEY WORDS (Continue on reverse side if necessary and identify by block number radio transmitter radio alarm emergency beacon arctic commemergency radio</li> </ul>	ted TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL "") unications ignalling
<ul> <li>16. DISTRIBUTION STATEMENT (of this Report)</li> <li>Approved for public release; distribution unlimit</li> <li>17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different f</li> <li>18. SUPPLEMENTARY NOTES</li> <li>19. KEY WORDS (Continue on reverse side if necessary and identify by block number radio transmitter radio alarm emergency beacon arctic commemergency radio emergency s</li> <li>20. ABSTRACT (Continue on reverse side if necessary and identify by block number of the state of the sector of the</li></ul>	TECHNICAL LIBRARY BLDG. 305 ABERDEEN PROVING GROUND, MD. STEAP-TL '') unications ignalling

# TABLE OF CONTENTS

· · · . .

AD-780744

:

	Page
REPORT DOCUMENTATION PAGE (DD FORM 1473)	iii
INTRODUCTION	2
DEVELOPMENT	3
DESCRIPTION	4
TESTING	8
CONCLUSIONS AND RECOMMENDATIONS	13
DISTRIBUTION LIST	14

#### INTRODUCTION

In early 1971 a need was identified by the Commanding General, US Army, Alaska (USARAL) for an emergency signalling system to enable small isolated patrols to alert their parent unit of an emergency situation or condition from distances as remote as 50 to 100 miles. Operational limitations caused by terrain and environmental conditions of the Arctic severely limit the radio range of the AN/PRC-77 tactical radio system normally employed by the patrol unit.

The LWL approach is based upon the use of a narrow-band, tone coded, frequency modulation system. This narrow bandwidth design provides a high signal-to-noise ratio, and therefore, high receiver sensitivity. To obtain good signal-to-noise ratios at line-of-sight ranges in excess of the required 50 miles, a rocket system is used to elevate the transmitter package to a height of 7000 feet. Balloons as well as rockets were initially considered as elevation systems. The balloon concept was dropped because of the restrictions imposed by the weight of the heavy inflation system required and adverse effects caused by the weather conditions of the Arctic.

#### DEVELOPMENT

The Thiokol Chemical Corporation, Elkton, MD performed the basic design engineering and development testing of the Emergency Distress Signalling Device under the direction of the US Army Land Warfare Laboratory (USALWL).

The rocket portion of this emergency signalling device is an adaptation of the basic Remotely Initiated Illuminating Perimeter Rocket (RIPER) developed by the Wasatch Division of Thiokol for the USALWL. A new grain was designed, using the RIPER propellant, TP-L-3014, to achieve the burn time and altitude requirement of 7000 feet above ground level (AGL) for the present system.

An inexpensive, fiber-glass, tripod launcher with folding legs was designed for use as both the launcher and the rocket storage container to be carried by the patrols.

The rocket system contains a pulse encoded transmitter system supplied by USALWL. To expedite development and minimize additional cost, maximum use was made of the electronic equipment developed for an earlier USALWL task by the Bell & Howell Communication Company, Waltham, MA, the Discreet Signalling System. Except for a minor redesign of the on-off timing circuit, the transmitter portion of the system was adapted for the rocket application by repackaging. The base station receiver/decoder portion of the Discreet Signalling System provided the necessary receiver/decoder and display console for the Emergency Signalling System without modification.

A sub-contract was let to Catalyst Research Corporation, Baltimore, MD by Thiokol to develop a suitable power source for the transmitter system. Catalyst Research provided the engineering and development work to produce a thermal battery with adequate power capacity for the transmitter and a suitable firing mechanism that would fit within the existing rocket case and give positive battery activation upon deployment of the electronic package.

#### DESCRIPTION

The Emergency Distress Signalling Rocket System (Figure 1) is a groundlaunched, rocket-boosted, parachute-deployed radio transmitter system which transmits a pulse encoded radio signal to a base station receiver system (Figure 2).

The Signalling Rocket System (Figure 3) is contained in a combination shipping and launch tube which includes folded tripod legs. The length of the rocket system is approximately 24 inches. The combined weight of the rocket and the launch tube is 5.5 pounds.

The rocket launch is initiated by an M60 fuse starter which ignites an M700 safety fuse delay. This then ignites a No. 2M Boran pellet which ignites a pyro-fuse contained inside the rocket motor. This method of activation produces a delay time of approximately 30 seconds between activation and launch permitting the operator sufficient time to move a safe distance from the launch area. The rocket attains an elevation of approximately 7000 feet (AGL) in approximately 20 seconds from launch. The solid propellant rocket motor provides a boost thrust of 40 pounds for roughly 1 second and a sustained average thrust of 5 pounds for 13 -15 seconds prior to ignition of the ejection charge (same as first firetransfer mix). The parachute, transmitter, and thermal battery are ejected from the body of the projectile by the ignition charge. Upon ejection the parachute deploys, the thermal battery activates, and the transmitter starts to radiate a signal. In a deployed state the parachute is 30 inches in diameter and with the attached 0.5 pounds electronic package its descent rate is approximately 10 feet per second.

The average transmitter power output is 1.75 watts at approximately 148 megahertz (MHz). The transmitter is frequency-modulated by two 2-second, sequential audio tones. The duty cycle of the transmitted signal is approximately 5 seconds on and 10 seconds off. The thermal battery will produce adequate power of 17 volts @ 150 milliamps for approximately 3 minutes. A metal shroud line of the parachute is used as the transmitter antenna.

The base-station decoder/display unit produces both a visual and audible output upon receipt of the transmitted signal. The base station receiver equipment has a .05 micro-volt sensitivity. The receiver antenna system is an RC/292 antenna modified for use at 148 MHz. The base station has a 60 channel decoding capability. Thirty operating channels and thirty back-up channels are used with the Emergency Distress Signalling System. At a minimum altitude of 3000 feet (AGL), the transmitting range is 50 miles.





Figure 2. Base Station Console



#### TESTING

The testing program was divided into three phases. The prime contractor, Thiokol Corporation, Elkton, MD performed essentially all testing under close supervision by LWL technical representatives from the Communications/ Electronics and Munition Branches of the Development Engineering Division.

Phase I of the testing program demonstrated the feasibility of using the existing RIPER System as the propulsion system for the airborne transmitter. This was successfully accomplished through actual as well as static tests conducted at the contractor's facility. This phase was concluded during late March 1972 with the flight test of three projectile systems using existing RIPER propulsion and hardware.

Phase II involved a series of rocket motor static tests conducted on a modified propulsion and expulsion/deployment system. Testing of the rocket motors started May 1972 and consisted of 18 motor firings. These tests revealed several minor problems that needed to be resolved. The principal problem was the transfer of the flame front from the propellant grain through the first fire mix to the expulsion charge. A redesigned vent for better conduction of the flame resolved the problem. A second problem surfaced during expulsion charge burn, the hot gases blew past the propellant container 0-ring seal and fused the nylon parachute shroud lines together. This problem was resolved by the incorporation of a teflon seal back-up ring.

Ten complete Emergency Distress Signalling Systems were flight tested at the Wasatch Division of Thiokol, Cosmo Testing Range, located at Brigham City, Utah, as part of the Phase II test program. The purpose of these tests were to obtain dynamic test information that could not be gathered in the static test program. The program was directed by USALWL personnel and involved personnel from both the Wasatch and Elkton Divisions of Thiokol as well as the Utah Army National Guard.

The tests were conducted during August 1972 with rockets at both ambient temperature and after temperature conditioning at -65°F. The program successfully demonstrated that the Emergency Distress Signalling System would meet its operational performance goals. Table I contains a summary of the flight test results including attained altitudes based on Theodolite tracking, and also lists the number of signals detected at each receiving station. Ignition problems were encountered with four units during the Wasatch flight test program. A redesign of the ignition fire train, and a modification in pellet size corrected the problems.

Subsequent to the Wasatch flight tests, the rocket systems were subjected to vibration and drop tests conducted at the contractor's facility. The objective of these limited environmental tests was to determine the survivability or effect on the operation of the electronic package after exposure to the rigors of standard shipping and handling techniques. The transmitter package showed no apparent degradation or damage as a result of these tests.

Test Date: August 9-10, 1972	Location: Cosmo Test Range, Brigham City, Utah	ined Measured Descent Descent Rate, Dual-tone FM Signals Received FPS Remarks	HU-1 Helicopter Launch Area Ground Station Launch Site Sta. No. 1, Preston, Idaho Sta. No. 3 TCC Airstrip TCC Airstrip Brigham City, U.	. 16 16 13 0 9 - Deployment not tracked	185 16 16 14 5 14	571 18 18 15 9 14 9.66	435         18         15         0         5         8.43         Probable case wall	696 16 16 14 5 13 10 70 burn thru	- 12 2 0 0 - Deployment not tracked	486 0 0 0 9 8.7 Polarity between battery	880 16 15 3 14 - Altitude based upon only 1 Theodolite reading & Wasatch's personnel's	one best judgment.	250 15 12 8 13 - Iallure	
		Attained Altitude (above Ground Level), ft. 1	HU-I Helicopter Launch Area	- 16	6,185 16	5,571 18	3,435 18	5,696 16	-	5,486	4,880	None	5,250	airron station mi
		Pretest Conditioning Tempera- ture		Ambient	Ambient	Ambient	Ambient	Ambient	-65ºF	-650F	-650F	-65ºF	-650F	annch site to new
		Trans- mitter Number		15	14	19	20	18	11	13	12	16	17	ance from 1
		Item		1	2	3	4	5	9	2	œ	6 LTRN	10	Dist

EMERGENCY DISTRESS SIGNAL DEVICE FLIGHT TEST SUMMARY

TABLE I

LLDG. 305 LBERDEEN PROVING GROUND, MD. STEAP-TL

Phase III of the test program dealt with flight testing conducted at both Aberdeen Proving Ground, MD and at Fort Richardson, AK. A decision was made to flight-test fifteen systems at APG and to demonstrate the remaining fifteen systems in Alaska.

The APG tests were conducted during March 1973. The launch site was located at Aberdeen Proving Ground, MD and the base-station receiving station was located approximately 60 miles away at Columbia, MD. Of the nine units launched, all projectiles functioned normally; however, only seven transmitter systems emitted a usable signal. The cause of problem with the transmitter systems could not be determined since no hardware recovery was made.

The Alaskan demonstration firings were conducted between June 4 and June 8, 1973. The launch site selected was a target impact area of Ft Richardson near the Cook Inlet. The base receiver was established at Portage, Alaska, separated from the test site by 6,900 ft high peaks. The base site was changed after some signals failed to reach this base station. A second base station site was selected at Fish Lake which provided a 50-mile distance from the launch site at Eagle River Flats separated by 4,500 ft peaks.

The test series then concluded successfully except for two unusual launches where two units failed to achieve the design altitude. The rockets left the launcher normally but at approximately 1,500 ft altitude veered off the vertical launch angle to one nearly horizontal. Observers at the launch site could see the plastic end closure fall off the ogive. The ogive had apparently carried the closure out of the launcher and the resulting drag deflected the units from a normal flight profile.

All 15 units ignited successfully and, with the exception of the two units discussed above, all worked satisfactorily with various results attained in the communication function.

Table II provides the results of the entire flight test program conducted under Phase III of the test programs.

Subsequent to these tests, USARAL expressed a desire to increase performance to provide altitudes of 12,000 ft and signalling ranges of 100 miles.

OGRAM	General Remarks	<ol> <li>Aborted unit S/N 33 could not be launched due to mechanical failure of the fuze. Fuze pulled out of ignition train due to damage in assembly.</li> <li>See Note 1.</li> </ol>	<ol> <li>Aborted unit S/N 36 was an ignition failure due to termination of flame front in the GFE supplied M700 fuze.</li> </ol>	<ol> <li>Repaired Unit S/N 33 was successfully launched.</li> <li>Clear sky conditions per- mitted visual sighting of de- ployment which was judged to be as designed.</li> <li>See Note 1.</li> </ol>
S, PHASE III PR	Transmitter Operation	7 good 2 "no-signal"		
TEST RESULT	Projectile Operation	9 good 1 Abort	l good 1 abort	
DEVISE	Qty Tested	10	ы	
SENCY DISTRESS SIGNAL	Test Location/Date	Aberdeen Proving Grounds March 23, 1973	Aberdeen Proving Grounds April, 1973	
EMERC	Unit S/N's Tested	32 32 55 55 55 55 56 57 56 57 56 57 56 57 57 57 57 57 57 57 57 57 57 57 57 57	о с с с с с с с с с с с с с с с с с с с	
	T est Group	#1	#2	,

TABLE II

Two units had an unsuccessplastic spacer in the launch tube. station may have been caused by the signals at the 50-mile base ful launch trajectory due to the 2) Failure to receive some of site selection for the receiving projectile ogive capturing the General Remarks See Note 1. station. 1) 3) tant base station. distant receiver. nals received at to emit any sigand the 10-mile at launch point One unit failed a 50-mile dis-14 sets of signals received 6 sets of sig-Transmitter Operation nals. Projectile Operation 13 good 2 bad Tested Qty 15 Test Location/Date Ft. Richardson, June 4-8, 1973 Alaska Tested S/N's 46 48 53 56 38 39 Unit 44 50 52 54 60 35 47 51 31 Group Test #3

NOTE 1: "No signal transmission" is probably attributable to a problem in the transmitter package although no instrument packages could be recovered to verify the assumption.

12

TABLE II (Con't)

### CONCLUSIONS AND RECOMMENDATIONS

#### Conclusions

1. The operational concept of the Emergency Distress Signalling System was successfully demonstrated to USARAL.

2. The operational performance goals of the rocket as well as the transmitter system were met. At an altitude of 7000 ft (AGL) the radio range obtained was 50 miles.

3. USARAL plans to draft a ROC to include the new altitude requirement of 12,000 ft (AGL) and the extension of the communication range to 100 miles.

#### Recommendations

Further design and development effort by the parent agency, ECOM, should incorporate the following recommendations:

1. The base station should be designed to withstand operational environmental conditions.

2. The physical size of the base station should be reduced, not to exceed that of an SB22 system. In support of this goal, the channel capacity can be reduced from 60 to 10 without loss of tactical versatility in this application.

3. The rocket propulsion system should be redesigned to increase altitude capability from present 7000 ft to 12,000 ft (AGL).

4. If necessary, transmitter performance should be increased to provide a 100 mile radio range.

5. Develop a frequency translator system for the AN/PRC-77 to provide launch site monitoring capability. This will provide patrols with a means for confirming transmission of distress signals.

# DISTRIBUTION LIST

	Copies
Commander US Army Materiel Command ATTN: AMCDL 5001 Eisenhower Avenue Alexandria, VA 22333	1
Commander US Army Materiel Command ATTN: AMCRD 5001 Eisenhower Avenue Alexandria, VA 22333	3
Commander US Army Materiel Command ATTN: AMCRD-P 5001 Eisenhower Avenue Alexandria, VA 22333	1
Director of Defense, Research & Engineering Department of Defense WASH DC 20301	1
Director Defense Advanced Research Projects Agency WASH DC 20301	3
HQDA (DARD-DDC) WASH DC 20310	4
HQDA (DARD-ARZ-C) WASH DC 20310	1
HQDA (DAFD-ZB) WASH DC 20310	1
HQDA (DAMO-PLW) WASH DC 20310	1
Commander US Army Training & Doctrine Command ATTN: ATCD Fort Monroe VA 23651	1

Commander US Army Combined Arms Combat Developments Activity (PROV) Fort Leavenworth, KS 66027	1
Commander US Army Logistics Center Fort Lee, VA 23801	1
Commander US Army CDC Intelligence & Control Systems Group Fort Belvoir, VA 22050	1
TRADOC Liaison Office HQS USATECOM Aberdeen Proving Ground, MD 21005	1
Commander US Army Test and Evaluation Command Aberdeen Proving Ground, MD 21005	1
Commander US Army John F. Kennedy Center for Military Assistance Fort Bragg, NC 28307	1
Commander-In-Chief US Army Pacific ATTN: GPOP-FD APO San Francisco 96558	1
Commander Eighth US Army ATTN: EAGO-P APO San Francisco 96301	1
Commander Eighth US Army ATTN: EAGO-FD APO San Francisco 96201	1
Commander-In-Chief US Army Europe ATTN: AEAGC-ND APO New York 09403	4
Commander US Army Alaska ATTN: ARACD APO Seattle 98749	1

Commander 1 MASSTER ATTN: Combat Service Support & Special Programs Directorate Fort Hood, TX 76544 Commander 2 US MAC-T & JUSMAG-T ATTN: MACTRD APO San Francisco 96346 Senior Standardization Representative 1 US Army Standardization Group, Australia c/o American Embassy APO San Francisco 96404 Senior Standardization Representative 1 US Army Standardization Group, UK Box 65 FPO New York 09510 Senior Standardization Representative 1 US Army Standardization Group, Canada Canadian Forces Headquarters Ottawa, Canada K1A0K2 Director 1 Air University Library ATTN: AUL3T-64-572 Maxwell Air Force Base, AL 36112 Battelle Memorial Institute 1 Tactical Technical Center Columbus Laboratorics 505 King Avenue Columbus, Oll 43201 Defense Documentation Center (ASTIA) 12 Cameron Station Alexandria, VA 22314 Commander 2 Aberdeen Proving Ground ATTN: STEAP-TL Aberdeen Proving Ground, MD 21005 Commander 1 US Army Edgewood Arsenal ATTN: SMUEA-TS-L Aberdeen Proving Ground, MD 21010

US Marine Corps Liaison Officer Aberdeen Proving Ground, MD 21005

Director Night Vision Laboratory US Army Electronics Command ATTN: AMSEL-NV-D (Mr. Goldberg) Fort Belvoir, VA 22060

Commander US Air Force Special Communications Center (USAFSS) ATTN: SUR San Antonio, TX 78243 1

1

1

1

Commander US Army Armament Command ATTN: AMSAR-ASF Rock Island, IL 61201