

UNCLASSIFIED

AD NUMBER
AD833750
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; MAR 1968. Other requests shall be referred to Aeronautical Systems Div., AFSC, Wright-Patterson AFB, OH 45433.
AUTHORITY
ASD ltr 15 Sep 1971

THIS PAGE IS UNCLASSIFIED

AD-833 750

CALCULATING THE BYPASS RATIO OF A TURBOFAN ENGINE BY USING THE ENERGY EQUATION

MICHAEL S. GOALSON, CAPTAIN, USAF

TECHNICAL REPORT ASD-TR-68-1

MARCH 1968

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Deputy for Engineering, Aeronautical Systems Division, W-PAFB, Ohio.

DEPUTY FOR ENGINEERING
AERONAUTICAL SYSTEMS DIVISION
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO

NOTICE

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Deputy for Engineering, Aeronautical Systems Division, W-PAFB, Ohio.

The distribution of this report is restricted to protect information relating to tests and evaluation of military operational weapon systems.

Copies of this report should not be returned unless return is required by security considerations, contractual obligations, or notice on a specific document.

CALCULATING THE BYPASS RATIO OF A TURBOFAN ENGINE BY USING THE ENERGY EQUATION

MICHAEL S. COALSON, CAPTAIN, USAF

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Deputy for Engineering, Aeronautical Systems Division, W-PAFB, Ohio.

FOREWORD

The technique presented herein was conceived in May 1966 and first formally presented in a Technical Memorandum, SENX-TM-247. The technique was developed as the result of a need to determine the bypass ratio of an engine when data is inadequate for determination by the conventional method. Data from a TF30-P-1 engine obtained in tests conducted at the Naval Air Propulsion Test Center was used in the analysis.

This development was conducted in relation to Program 324A. The author served as project engineer for this phase of the program.

This report was submitted by the author in January 1968.

This technical report has been reviewed and is approved.



George F. Gillespie, Colonel, USAF
Director, Propulsion & Power Subsystems
Engineering
Deputy for Engineering
Aeronautical Systems Division

ASD-TR-68-1

ABSTRACT

A method by which the energy equation is used to calculate the bypass ratio of a turbofan engine is presented. Only standard instrumentation is required for data except for that needed to measure the fan discharge total temperature. Results of calculations are presented and analyzed to indicate the sensitivity of the calculated bypass ratio to the measured parameters.

This abstract is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Deputy for Engineering, Aeronautical Systems Division, W-PAFB, Ohio.

SYMBOLS

A	flow area, ft^2
c_p	rate of change of enthalpy with respect to temperature, $\text{Btu/lbm}/^\circ\text{R}$
h_{lf}	enthalpy of the liquid fuel, Btu/lbm
h_t	total enthalpy, Btu/lbm
HV	lower heating value, Btu/lbm
P_t	total pressure, lbf/ft^2
T_f	fuel temperature
T_t	total temperature, $^\circ\text{R}$
W	mass flow, lbm/sec
W_{a_c}	airflow entering engine core, lbm/sec
W_{a_e}	total airflow entering engine, lbm/sec
W_{a_f}	discharge airflow at fan, lbm/sec
W_{f_e}	fuel flow, lbm/sec
W_{g_c}	gas flow at turbine discharge, lbm/sec

Subscripts

2	parameter at engine inlet
7	parameter at turbine discharge
25	parameter at fan discharge

Superscript

prime	parameter including error in a measured temperature
-------	---

SECTION I

INTRODUCTION

In order to assess the performance and stability characteristics of a turbofan engine, the bypass ratio (BPR) must be known. The most straightforward and accurate approach to a determination of BPR is to measure the total engine airflow and the airflow through some part of the engine. Making these measurements requires considerable instrumentation in addition to the standard engine instrumentation. In addition, an accurate determination of BPR by the conventional procedure requires that all bleeds be known. Controllable bleeds are generally closed during test runs to determine BPR, but engines using compressor air to cool the turbine require cooling air continuously. Consequently, the bleeds cannot be closed and the turbine cooling air flow rate must be obtained. Data on turbine cooling air flow rate is frequently inadequate, and that which is available is often suspect. Therefore, some other method for determining BPR is needed.

This report presents a method for determining BPR that eliminates the need for ascertaining the turbine cooling air flow rate. It is simpler and less costly, since the only instrumentation required in addition to standard engine instrumentation is that required to measure the fan discharge total temperature. This method was applied to data for the TF30-P-1 engine and the results are plotted and analyzed for a series of simulated flight conditions. Repeatability of test results indicates accuracy is very good.

SECTION II

CALCULATION PROCEDURES

1. CHOKED TURBINE NOZZLE DIAPHRAGM METHOD

The conventional method of determining BPR is based on the flow parameter at the turbine nozzle diaphragm. The flow is measured here because the impact of error on the calculated flow parameter determined from pressure and temperature measurements is essentially inversely proportional to the flow Mach number; therefore, measurements of pressure and temperature should be made at a point where the flow Mach number is high and, preferably, where it is known, as is the case at the turbine nozzle diaphragm. Thus, the procedure is known as the choked turbine nozzle diaphragm method. The flow parameter is $\frac{W \sqrt{T_t}}{A P_t}$, where

- (a) T_t , the total temperature, is calculated from fuel flow and compressor temperature,

(b) P_t , the total pressure, is either measured directly or is determined by measuring the compressor discharge pressure and assuming a pressure drop across the burner, and

(c) A , the minimum flow area, is determined from design data.

2. ENERGY EQUATION METHOD

The underlying theory for this method is quite straightforward and involves nothing more than using the energy equation and the continuity equation for the flow through the engine. Thus the procedure involves two equations and two unknowns, so no iteration is required.

The solution to these equations depends upon the split in the airflow, as depicted in Figure 1. To determine the split in the airflow, we need measurements for the following parameters:

- (a) Total engine airflow, W_{a_e}
- (b) Engine inlet total temperature, T_{t2}
- (c) Fan discharge total temperature, T_{t25}
- (d) Fuel flow, W_{f_e}
- (e) Fuel temperature, T_f
- (f) Turbine discharge total temperature, T_{t7} , and
- (g) Fuel lower heating value, HV.

The energy equation is then written:

$$W_{a_e} \times h_{t2} + W_{f_e} (h_{lf} + HV) = W_{a_f} \times h_{t25} + W_{g_c} \times h_{t7} \quad (1)$$

The continuity equation is:

$$W_{a_e} + W_{f_e} = W_{a_f} + W_{g_c} \quad (2)$$

Substituting the continuity equation into the energy equation and rearranging yields:

$$W_{g_c} = W_{a_e} \left[\frac{h_{t2} + \frac{W_{f_e}}{W_{a_e}} (h_{lf} + HV) - h_{t25} - \frac{W_{f_e}}{W_{a_e}} (h_{t7})}{h_{t7} - h_{t25}} \right] \quad (3)$$

and

$$W_{a_f} = W_{a_e} - W_{g_c} \quad (4)$$

The bypass ratio, BPR, can then be determined from

$$\text{BPR} = \frac{W_{a_f}}{W_{a_c}} \quad (5)$$




Figure 1. Schematic of Engine Showing Station Designation

SECTION III

RESULTS OF THE CALCULATION

The accuracy of the calculation method outlined in Section II was tested by applying the procedure to data for a specific engine. Data of the TF30-P-1 engine collected in tests conducted at the Naval Air Propulsion Test Center were used for this calculation. BPR was determined under varying conditions of Mach number and altitude, and the results in terms of BPR versus EPR (engine pressure ratio) are plotted in Figure 2. The consistency of the calculated BPR at the different Mach number and altitude conditions indicates the method is valid.

Analysis of these results indicates that the bypass ratio is not uniquely dependent on engine pressure ratio. There is a nongeneralization of data which is ascribed, in part, to an inadequacy of the instrumentation. There is generally a considerable variance in the temperature gradients at the turbine discharge (Station 7). Consequently, a substantial amount of instrumentation was used at Station 7 to measure turbine discharge temperature, and an arithmetic average of the probe readings was made to account for the variance. An arithmetic average of the individual probe readings, however, probably was not representative of the average temperature at all power settings. The instrumentation used in the tests that provided the data for these calculations is shown in Figure 3.

Tests are now being conducted on a TF30-P-3 engine in which twice as much instrumentation is being used in the fan duct as was used in the tests of the TF30-P-1. This additional instrumentation is expected to provide more accurate measurements of fan discharge total temperature, which is expected to provide more accurate computations of BPR.




Figure 2. Bypass Ratio vs. Engine Pressure Ratio




Figure 3. Instrumentation Diagram

SECTION IV

SENSITIVITY ANALYSIS

The sensitivity of the calculated bypass ratio to the accuracy of the measured parameters is of particular interest in this analytical exercise. The analytical portion of this investigation was directed toward determining those parameters which have first order effects on the accuracy of the calculated bypass ratio. Those parameters that also affect the bypass ratio when calculated by the choked turbine nozzle method, however, were not considered (e.g., the accuracy of total engine airflow, fuel flow, fuel heating value).

No temperature gradients of any consequence were found at Station 2, so no temperature gradients were expected at the fan discharge. However, small gradients in this measurement affect the calculation considerably, so more instrumentation to measure this parameter would have provided better data for this technique.

Obtaining an average total temperature at the turbine discharge (T_{t7}) was the biggest problem, so the greatest amount of instrumentation was used for this measurement. Since T_{t7} is large, however, small errors in the measurement of this parameter affect the calculated bypass ratio less than equivalent errors in other measurements.

The sensitivity of c_p , the rate of change of enthalpy with respect to temperature, is so small over the temperature band 50 to 100°R that it is treated as a constant in this analysis. This is not to say that c_p does not vary with temperature, but rather that, for the purposes of this analysis, changes in c_p in the expected error band of the measured temperatures will be quite small. Assuming that c_p and W_{a_e} are constant, the sensitivity of W_{a_c}/W_{a_e} to a 1°R variation in T_{t7} , T_{t25} , and T_{t7} can be determined from Equations 6, 7, and 8, respectively.

$$\frac{d}{dT_{t2}} \left(\frac{W_{a_c}}{W_{a_e}} \right) = \frac{1}{T_{t7} - T_{t25}} \quad (6)$$

$$\frac{d}{dT_{t25}} \left(\frac{W_{a_c}}{W_{a_e}} \right) = \frac{1}{(T_{t7} - T_{t25})^2} \left[T_{t2} + \frac{Wf_e}{W_{a_e} \times c_p} (h_{lf} + HV) - T_{t7} \left(1 + \frac{Wf_e}{W_{a_e}} \right) \right] \quad (7)$$

$$\frac{d}{dT_{t7}} \left(\frac{W_{a_c}}{W_{a_e}} \right) = \frac{-1}{(T_{t7} - T_{t25})^2} \left[T_{t2} + \frac{Wf_e}{W_{a_e} \times c_p} (h_{lf} + HV) - T_{t25} \left(1 + \frac{Wf_e}{W_{a_e}} \right) \right] \quad (8)$$

Then, using the sensitivity of W_{a_c}/W_{a_e} , we can determine the sensitivity of the bypass ratio from the following equations:

$$W_{a_c}' = W_{a_e} - W_{a_c} - \Delta W_{a_c} \quad (9)$$

$$W_{a_f}' = W_{a_e} - W_{a_c}' \quad (10)$$

$$BPR' = W_{a_f}' / W_{a_c}' \quad (11)$$

The accuracy of these expressions was evaluated by inserting test data for the TF30-P-1 engine and assuming a nominal value of 0.26 for c_p . An error of $+1^\circ\text{R}$ in T_{t2} , T_{t25} , and T_{t7} caused an error in the calculated bypass ratio of -0.6%, +0.4%, and +0.3%, respectively.

SECTION V

CONCLUSIONS

When adequate instrumentation is not available to provide sufficient data for calculating the bypass ratio of an engine by means of the choked turbine nozzle diaphragm method, the method outlined herein can be used. The repeatability of the calculations is good, as shown in Figure 2.

This method, which uses the energy equation for determining the bypass ratio, does not require an accurate measurement of the turbine cooling air or the flow area. The only extra instrumentation required (i.e., total temperature probes downstream of the fan exit) can generally be installed through fan duct ports after the engine is installed. This method is less time-consuming and costly than the existing method of determining bypass ratio, but the instrumentation used should be of significantly higher reliability because no additional hot section instrumentation is used.

DOCUMENT CONTROL DATA - R&D		
<small>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</small>		
1. ORIGINATING ACTIVITY (Corporate author) Deputy for Engineering Aeronautical Systems Division Wright-Patterson Air Force Base, Ohio		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED
		2b. GROUP
3. REPORT TITLE CALCULATING THE BYPASS RATIO OF A TURBOFAN ENGINE BY USING THE ENERGY EQUATION		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial) Michael S. Coalson, Capt, USAF		
6. REPORT DATE March 1968	7a. TOTAL NO. OF PAGES 16	7b. NO. OF REFS
8a. CONTRACT OR GRANT NO. A. PROJECT NO. 324A C. D.	8a. ORIGINATOR'S REPORT NUMBER(S) ASD-TR-68-1	
8b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)		
10. AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Deputy for Engineering, Aeronautical Systems Division, W-PAFB, Ohio		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Deputy for Engineering Aeronautical Systems Division Wright-Patterson Air Force Base, Ohio	
13. ABSTRACT A method by which the energy equation is used to calculate the bypass ratio of a turbofan engine is presented. Only standard instrumentation is required for data except for that needed to measure the fan discharge total temperature. Results of calculations are presented and analyzed to indicate the sensitivity of the calculated bypass ratio to the measured parameters. This abstract is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Deputy for Engineering, Aeronautical Systems Division, W-PAFB, Ohio.		

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Turbofan Engines						
By-Pass Ratio						
TF-30-P-1 Engine						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification