

UNCLASSIFIED

AD NUMBER

AD834860

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; MAY 1968. Other requests shall be referred to Office of Naval Research, Field Projects Branch, Washington, DC 20360. This document contains export-controlled technical data.

AUTHORITY

onr ltr, 28 jul 1977

THIS PAGE IS UNCLASSIFIED

ADD 834 860
Lateral Deviation of Obliquely
Propagated HF Radio Rays

by

T.W. Washburn

MAY 1968

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Office of Naval Research, Field Projects Branch, Washington, D.C., 20360.


Technical Report No. 137

Prepared under

Office of Naval Research Contract

Nonr-225(64), NR 088 019, and

Advanced Research Projects Agency ARPA Order 196



RADIO SCIENCE LABORATORY

STANFORD ELECTRONICS LABORATORIES

STANFORD UNIVERSITY • STANFORD, CALIFORNIA



LATERAL DEVIATION OF OBLIQUELY PROPAGATED
HF RADIO RAYS

by

T. W. Washburn

May 1968

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Office of Naval Research, Field Projects Branch, Washington, D.C., 20360.

Technical Report No. 137

Prepared under

Office of Naval Research Contract
Nonr-225(64), NR 088 019, and
Advanced Research Projects Agency
ARPA Order No. 196

Radioscience Laboratory
Stanford Electronics Laboratories
Stanford University Stanford, California

ABSTRACT

As is well known, magnetoionic splitting of obliquely propagated HF radio waves may result in deviation of such waves from the great-circle plane between transmitter and receiver. A computer raytracing routine has been employed at Stanford to investigate the properties and maximum extent of this phenomenon under realistic ionospheric conditions. It is concluded that for a 1000 km path the difference in azimuthal bearing between the ordinary and extraordinary modes could reach a maximum of 0.5 deg, corresponding to an 0.25 deg variation of either mode from the true bearing. However, in most practical bearing estimation problems, the difference is an order of magnitude smaller than this maximum, and thus is truly small in comparison with other sources of error.

CONTENTS

	<u>Page</u>
I. INTRODUCTION	1
II. COMPUTATION OF LATERAL DEVIATION	5
III. ACCURACY AND SIGNIFICANCE OF THE COMPUTATION	14
BIBLIOGRAPHY	17

ILLUSTRATIONS

Figure

1. Electron density profile used in computation of lateral deviation	6
2. Example of a ray path exhibiting net lateral deviation. .	7
3. Representative ground projections of ordinary and extraordinary ray paths exhibiting net lateral deviation . . .	8
4. Difference between o and x bearings vs magnetic azimuth	9
5. Difference between o and x bearings ($\Delta\theta$) vs range R	10
6. Difference between o and x bearings vs frequency for magnetic dip angles of 0° and 62°	12

I. INTRODUCTION

It is well known that interaction with the earth's magnetic field may cause obliquely propagated HF radio rays to deviate from the great-circle path determined by the initial direction of the ray. Under certain ionospheric conditions an obliquely propagated ray may return to earth in a great-circle plane different from, but parallel to, the initial great-circle plane. This phenomenon can be a source of error in determining the azimuthal bearing from a point of observation to the source of a ray, as in a direction-finding system. A number of investigators have studied this problem with varying degrees of success; most of the limitations on their findings have arisen by virtue of extensive approximations necessary to make the problem amenable to manual computation.

In this report the results of a study of the possible import of lateral deviation caused by the earth's magnetic field will be described. A fairly sophisticated raytracing technique has been used in a high-speed digital computation routine. It should be pointed out that this study represents only a brief inquiry into the properties and extent of lateral deviation. A particular goal was to obtain a working estimate of the maximum value of deviation obtained in realistic propagation situations. For this reason, the results depicted herein are only representative examples of lateral deviation, rather than an exhaustive study of the phenomenon.

Perhaps it is best to begin by summarizing some of the earlier work, which by and large gives a good account of the qualitative aspects of the problem, but a somewhat inconsistent picture of the maximum magnitude of bearing errors which one may expect.

Booker (1949)[†] employed his famous quartic formulation to obtain an analytical expression for the differential lateral displacement of a radio ray. This expression, when integrated over the ray path, could yield a value for the net lateral deviation of the ray. However, Booker did not perform any calculations for this net effect, and observed only that its magnitude would be small except in unusual circumstances. Elghozi (1953) reviewed the work of Al'pert (1948) and extended Booker's analysis to determine the extent of lateral deviation over some specific paths (mostly near-vertical). Millington (1951, 1954) reduced the quartic equation to a quadratic equation under a number of assumptions and looked at the limiting value of lateral deviation as the ray moved toward vertical incidence. His notation is difficult to follow, but Gething (1962) reformulated Millington's work into a more conventional format and extended the calculations somewhat to arrive at an estimate of the maximum bearing error that is possible because of lateral deviation in a parabolic ionospheric layer. Titheridge (1959) employed many approximations to enable him to calculate lateral deviation in a linear or parabolic layer. His parameterization of the problem is somewhat ambiguous, and his results do not compare in a reliable manner with those described in this report. Furthermore, he compared his results with those of Chatterjee (1952) and drew attention to good agreement between the two sets of results; yet his choice of layer critical frequency was significantly different from the choice Chatterjee made for the purpose of his calculation.

[†] All references are listed alphabetically in the Bibliography at the end of the paper.

Several other investigators have considered the lateral deviation problem, particularly for vertical incidence [see Kelso (1964) and NBS Monograph 80 for a review for this work]. A summary of the various aspects of direction finding may be found in the recent review article by Gething (1966). Without embarking upon a critical review of the generous supply of previous work on this subject, it is important to observe that all of the previous work assumed a single linear or parabolic ionospheric layer for ease of computation. Use of a more realistic ionospheric profile should give one greater confidence in the results obtained. Furthermore, in the previous work values were used for several ionospheric parameters, which are not found in practice; yet no attempts were made to verify that the use of such values does not alter the results significantly.

As an example, Gething (1962) computes the maximum bearing error over a path where $Y = 1/2$, which corresponds to signal frequencies in the vicinity of 2 MHz. Near the gyro frequency the rays have stronger magnetic interaction and will display relatively large deviation. Gething quotes a maximum bearing error of 6.8 deg for the ordinary mode and 4.1 deg for the extraordinary mode in a parabolic ionospheric layer; however, this condition occurs where the ratio of plasma frequency at the path apex to plasma frequency at the layer maximum tends very closely to one (0.98 and higher). In practice, very little energy ever gets this deep within the ionosphere without penetrating the entire layer. Reference to Fig. 1 in Gething's paper will show that revising the maximum attained value of the ratio downward to 0.97 will reduce his estimate of maximum bearing errors by a factor of three. One may also note that in Gething's

figure, the ratio mentioned above is incorrectly interpreted as the ratio of signal frequency to maximum usable frequency (MUF). This incorrect interpretation was first pointed out to the author by Dr. J. M. Kelso of the ITT Electro-Physics Laboratories. Finally, one should emphasize that Gething's computations were made for a range of about 600 km. As will be pointed out later, range is a major factor in determining angular bearing errors.

II. COMPUTATION OF LATERAL DEVIATION

In 1963, Finney programmed a solution of the Haselgrove equations [Haselgrove (1954)] to trace rays through an ionosphere of arbitrary vertical electron density profile while employing a dipole model of the earth's magnetic field. Dr. T. A. Croft of the Radioscience Laboratory at Stanford University has implemented Finney's work for use at the university. A number of ionospheric ray paths have been computed by means of the resulting program, and by varying the parameters involved, a fairly good description of the qualitative features of lateral deviation may be constructed. In accordance with the primary purpose of the present study, an estimate of the magnitude of the lateral deviation effect is obtained under various ionospheric conditions. This technique appears to provide a quick and inexpensive way to obtain the bearing error over types of oblique paths found in practice. In the summary of the technique that follows, it becomes readily apparent that a qualitative description of the features of the phenomenon of lateral deviation is complex, since the effects of the several ionospheric parameters involved are highly interdependent.

A convex electron density profile with a critical frequency of 9 MHz (see Fig. 1) was employed for most of the computation. Such a density profile is fairly representative of daytime ambient conditions.

The magnetic azimuth θ_M , defined as the clockwise angle from the vertical plane that passes through the magnetic field lines to the vertical plane that passes through the initial ray direction, is an important parameter. For $\theta_M = 0$ deg or 180 deg the raypath remains in the great-circle path between take-off and landing points. For $\theta_M = 90$ deg or





FIG. 1. ELECTRON DENSITY PROFILE USED IN COMPUTATION OF LATERAL DEVIATION. Critical frequency, 9 MHz.

270 deg the ray path may be diverted from the great-circle path while the ray is in the ionosphere; but it always returns to the great-circle path upon returning to earth. These properties were observed analytically by Booker (1949); and the computations performed by the author of the present study, using the Finney raytracing routine, bear out the predictions. If the magnetic azimuth for an oblique path lies between the two extremes, a net lateral deviation with attendant bearing error may arise.

Figure 2a depicts an example of a ray path that exhibits net lateral deviation upon returning to earth. The observation that the ray comes to earth in a plane parallel to, but not necessarily coincident with,




A43313

FIG. 2. EXAMPLE OF A RAY PATH EXHIBITING NET LATERAL DEVIATION.

- a. Profile of ray path
- b. Ground projection of ray path

its plane of departure has been confirmed analytically by Budden (1961) directly from the Booker formulation. The condition comes about because the ray direction departs from the plane of incidence while in the ionosphere, although the wave normal remains in the plane of incidence at all times. Figure 2b shows the ground projection of the ray path. The ground projection contains the pertinent information for azimuthal bearing determination. Direction A is the true bearing to the transmitter, while direction B indicates the apparent bearing. The angle of error in bearing is θ .

Figure 3a depicts an example of the ground projection of the ordinary and extraordinary rays in a ray path with lateral deviation. The angle



A43314

FIG. 3. REPRESENTATIVE GROUND PROJECTIONS OF ORDINARY AND EXTRAORDINARY RAY PATHS EXHIBITING NET LATERAL DEVIATION.

- a. $\phi_M = 30^\circ$, $\beta = 32^\circ$, $f = 10$ MHz, $R = 1000$ km
 b. $\phi_M = 54^\circ$, $\beta = 27^\circ$, $f = 12$ MHz, $R = 1022$ km

θ_o is the angular bearing error for the ordinary ray, and θ_x for the extraordinary ray. A convenient measure of bearing errors is $\Delta\theta$, which is the angular magnitude of the difference between θ_o and θ_x ; this measure is useful because the ray paths for the two modes are usually much like mirror images of each other; therefore


$$|\theta_o - \theta_{\text{true}}| \approx \frac{1}{2} \Delta\theta,$$

and similarly for θ_x . As is well known (see NBS monograph 80), the point of reflection for the ordinary ray is deflected toward the nearer pole, while the extraordinary ray is deflected toward the equator. If used carefully, this observation serves as a guide for outlining qualitative features of the ray path behavior.

Under some conditions, the loci of the ground projections of the ray paths are more distorted than in Fig. 3a, as is indicated in Fig. 3b; however, the essential features of the situation do not change much.

One comment is in order here--namely, that the deviated rays are near the great-circle path in the region of the path midpoint, except for the case of propagation transverse to the field lines. This means, contrary to the conclusions drawn by some observers, that the deviated ray does not sample a significantly different part of the ionosphere than does an undeviated ray, particularly near the path apex, where ionospheric variability is large and tends to have maximum effect upon ray path parameters.

Figure 4 shows the variation of bearing error $\Delta\theta$ vs magnetic azimuth. For the paths used in obtaining Fig. 4 the signal frequency f was 14.0 MHz; the take-off angle β was 31.5 deg; the range R was



A43315

FIG. 4. DIFFERENCE BETWEEN o AND x BEARINGS VS MAGNETIC AZIMUTH. Ray paths chosen near penetration to maximize difference in bearing.

1000 km; and the magnetic dip at the receiver was 62 deg. The maximum difference between the bearings of the two modes is roughly 0.2 deg, occurring near 45 deg magnetic azimuth. The magnitude of $\Delta\theta$ vs ϕ_M was also computed with other values of the parameters; however, because of the small number of cases surveyed in this study, it is valid only to suggest that the effects of net lateral deviation have a broad maximum centered at an angle about midway between the field direction and the perpendicular to the field direction. This behavior occurred in ray-tracings in all four of the azimuthal quadrants. This result also formed a conclusion of the several papers cited in the Introduction.

It is interesting to observe the variation of bearing error with range. Figure 5 shows the result of varying the range for the case where $\phi_M = 45$ deg, magnetic dip = 62 deg, and frequency is chosen to




FIG. 5. DIFFERENCE BETWEEN o AND x BEARINGS ($\Delta\theta$) VS RANGE R. Receiver at Stanford.


be roughly 0.95 MUF. Since apparent bearing errors are small, one finds

$$\Delta\theta \simeq \frac{l_o + l_x}{R},$$

where l_o and l_x are, respectively, the ordinary and extraordinary lateral deviations in km, and R is the range in km. A slow variation of the lateral deviation with range gives rise to a variation of $\Delta\theta$ approximately as $1/R$ over the range increment 500-2000 km, as is shown in Fig. 5 by a comparison of the computed points with the dashed curve. For shorter ranges, of course, this trend must change; however, shorter range paths have not been computed.

It was found that bearing errors tended to be larger for smaller magnetic dip, other conditions being held fixed as closely as possible. A plot of the difference, $\Delta\theta$, between o and x bearings (i.e., bearing error) vs signal frequency for two magnetic dips (62 deg and 0 deg) is shown in Fig. 6. Particularly for F-layer propagation, the effect is larger at 0 deg dip. As far as the interaction of the ray with the magnetic field is concerned, it is not the magnetic azimuth in itself that is important, nor the magnetic dip in itself. The really important parameter is the angle between the field lines and the ray direction. For this reason it is only partially satisfactory to describe the lateral deviation of radio rays in terms of parameters such as magnetic azimuth and magnetic dip which are descriptive of an oblique path as a whole.

In line with the primary interest in this study, it was thought desirable to determine some value for the maximum bearing error resulting from lateral deviation under ionospheric conditions which might be met in



A43317

FIG. 6. DIFFERENCE BETWEEN \circ AND \times BEARINGS VS FREQUENCY FOR MAGNETIC DIP ANGLES OF 0° AND 62° . Range = 1000 km, magnetic azimuth = 45° .

practice. As indicated by Figs. 4, 5, and 6, the effect is largest (1) for the shorter ranges; (2) near the MUF; (3) at 0° magnetic dip; and (4) for propagation at 45° from the magnetic meridian. For a range of 1000 km, it is seen in Fig. 6 that the maximum value of $\Delta\theta$ for F-layer propagation in a region of 0° magnetic dip is roughly 0.5° (corresponding to a situation in which the ordinary and extraordinary modes each have an apparent bearing 0.25° away from the true bearing). A plot similar to Fig. 5, except for employing a magnetic dip of 0° , would demonstrate that shorter ranges can increase this maximum value several-fold to roughly 2° at 500 km; however, the principal interest here was in ranges of 1000 km and more. It is worth repeating,

however, that any estimate of maximum bearing errors due to lateral deviation over oblique paths should include the range as a parameter.

III. ACCURACY AND SIGNIFICANCE OF THE COMPUTATION

Comparison of the predictions made in Section II for lateral-deviation bearing errors with predictions made by previous investigators shows some divergences. Generally speaking, the Finney program gives reasonable values for lateral deviation which appear to be consistent within themselves and are consistent qualitatively with what has been predicted from the analytical considerations of Booker and Millington. However, some means of verification of the accuracy of computations based on the Finney program is clearly necessary. Such a need became apparent in the present investigation when the computations for several paths were performed with transmitter and receiver locations interchanged. For the reversed paths, the angular deviation from the great-circle bearing differed by as much as 10 percent from that for the initial path configurations. This suggests that round-off errors made an appreciable contribution to the computed lateral deviation.

There are several possibilities for checking the computations referred to above. First, Jones (1968) has programmed another version of the Haselgrove equations which is more accurate than the Finney version, although it is still in the developmental stage. Comparative computations performed with both programs would lend insight into the accuracy with which the tedious computation routine itself is carried out. Secondly, it would be extremely satisfying to provide experimental verification of bearing errors caused by lateral deviation. This project would probably involve the use of a large-aperture interferometer with a means for determining fairly detailed information about the ionospheric profile over the path. (Knowledge of ionospheric tilts would be

extremely important.) Finally, a computer-aided analytical study could also provide verification for the computations performed for this report, although this too appears to present a sizable task.

Some years ago the potential bearing errors caused by magnetoionic splitting were considered negligible in most applications; however, with the gathering of knowledge about ionospheric phenomena, the state of the art has progressed to a point for which bearing errors such as those described here may be significant. Of course, the natural field of application of these results would be in direction finding, where lateral deviation may bias the estimate of bearing to the transmitter. If the constraint of making bearing estimates in minimum time is recognized, the bearing variance caused by the numerous sources of error present will almost surely be significantly larger than any bearing bias caused by lateral deviation. (See Gething, 1962, for estimates of variance.)

A further factor in interpreting the bearing errors caused by lateral deviation is that the estimates presented in the present report were computed for the two characteristic modes, ordinary and extraordinary. In general, an antenna (array) will not receive the characteristic polarization. To determine the effects of lateral deviation on the accuracy of azimuthal bearing estimates obtained with a practical receiving array setup, one should employ the estimates for errors for each mode (as in the case presented herein), together with statistical information as to the fading of the ordinary and extraordinary modes. One could then, in principle, obtain a probability distribution of apparent bearing between the two extremes of bearing (ordinary on one side of boresight bearing, and extraordinary on the other).

To summarize the results of this investigation, it may be said that the effects of lateral deviation on azimuthal bearing estimates may be detectable, particularly in the extreme cases cited in this report. For cases of practical interest, this phenomenon leads to errors that are small in relation to other sources of error.

BIBLIOGRAPHY

- Al'pert, Y. L. (1948). On the trajectories of rays in a magnetoactive ionized medium - the ionosphere, Izvestiya Akademi Nauk. USSR, Seriya Fizicheskaya, Vol. 12, p. 24, 1948.
- Booker, H. G. (1949). Application of the magneto-ionic theory to radio waves incident obliquely upon a horizontally-stratified ionosphere, J. Geophys. Res., Vol. 54, No. 3, pp. 243-274, September 1949.
- Budden, K. G. (1961). Radio Waves in the Ionosphere. Cambridge University Press, London, 1961.
- Chatterjee, B. (1952). Effect of magnetic field in oblique propagation over equatorial region, Indian J. Phys., Vol. 26, No. 6, pp. 297-312, June 1952.
- Elghozi, G. (1953). Un problème de radiogoniométrie: l'anisotropie ionosphérique, Ann. d. Télécomm., Vol. 8, No. 3, pp. 78-92, 1953.
- Finney, J. W. (1963). Raytracing development for propagation studies, NBS Rpt. No. 7697, 1963.
- Gething, P. J. D. (1962). Lateral deviation and effective path length for oblique propagation through the ionosphere, Proc. of the International Conference on the Ionosphere, pp. 421-427, Inst. of Phys. and the Phys. Soc., London.
- Gething, P. J. D. (1966). High-frequency direction finding, Proc. Inst. Elect. Engrs. London, Vol. 113, No. 1, pp. 49-61, January 1966.
- Haselgrove, J. (1954). Ray theory and a new method for ray tracing, Report of Conference on the Physics of the Ionosphere, London Phys. Soc., pp. 355-364, 1954.
- Kelso, J. M. (1964). Radio Ray Propagation in the Ionosphere. McGraw-Hill Book Co., New York, 1964.
- Millington, G. (1951). The effect of the earth's magnetic field on shortwave communication by the ionosphere, Proc. Inst. Elect. Engrs. (London), Vol. 98, Part IV, No. 1, pp. 1-114, October 1951.
- Millington, G. (1954). Ray-path characteristics in the ionosphere, Proc. Inst. Elect. Engrs. (London), Vol. 101, Part IV, No. 7, pp. 235-249, August 1954.

Nat. Bur. Stds. Monograph 80 (1965), Ionospheric Radio Propagation,
U.S. Govt. Printing Office, Washington, D.C., 1965.

Titheridge, J. E. (1959). Ray paths in the ionosphere: approximate
calculations in the presence of the earth's magnetic field,
J. Atmosph. Terr. Phys., Vol. 14, Nos. 1/2, pp. 50-62, 1959.

DISTRIBUTION LIST

U-Series

NAVY

Chief of Naval Research
Department of the Navy
Washington, D. C. 20360
2 Attn: Code 418
1 Attn: Code 2027

Director
U.S. Naval Research Lab
Washington, D. C. 20390
1 Attn: Code 5320
(Mr. E. Zettle)
1 Attn: Code 5320
(Mr. J.M. Headrick)
1 Attn: Code 5432C
(Mr. F.A. Polinghorn)

Chief of Naval Operations
Department of the Navy
The Pentagon
Washington, D. C. 20350
1 Attn: OP-07TE
1 Attn: OP-723E

Commander
U.S. Naval Missile Center
Point Mugu, California 93041
1 Attn: Code N03022

Commander
Naval Weapons Center
China Lake, California 93555
1 Attn: Code 4025
(Mr. R.S. Hughes)

Commander
Naval Command Control Communi-
cations Laboratory Center
San Diego, California 92152
1 Attn: Mr. H.J. Wirth
1 Attn: Library

Commander
Naval Weapons Center
Corona Laboratories
Corona, California 91720
1 Attn: Mr. V.E. Hildebrand

Director
Office of Naval Research
Branch Office
495 Summer Street
Boston, Massachusetts 02210
1 Attn: Mr. Stan Curley

AIR FORCE

Headquarters, USAF
The Pentagon
Washington, D.C. 20330
1 Attn: AFNICAD
(MAJ Nyquist)
1 Attn: AFRDDF

Headquarters, USAF
Office of Assistant Chief
of Staff, Intelligence
Washington, D. C. 20330
1 Attn: AFNCAA

Commander
Rome Air Development Center
Research & Technology Div.
Griffiss AFB, New York 13442
1 Attn: EMASO
(Mr. S. DiGennaro)
1 Attn: EMAES
(MAJOR D.R. Wipperman)
1 Attn: EMASR
(Mr. V.J. Coyne)
1 Attn: EMASA

Headquarters, AF Systems Command
Foreign Technology Division
Wright-Patterson AFB.
Ohio 45433
1 Attn: TDC (Mr. Zabatakas)
1 Attn: TDEED
(Mr. W. L. Picklesimer)
1 Attn: TDCES
1 Attn: TDCE
(Mr. M.S.J. Grabener)

U-Series - Air Force (Cont)

Headquarters
AF Systems Command
Research & Technology Division
Bolling AFB, Washington,
D.C. 20332
1 Attn: RTTC
(Mr. Philip Sandler)

Headquarters
USAF Security Service (OSA)
San Antonio, Texas 78241
1 Attn: Mr. W. L. Anderson
ODC-R

Headquarters
Air Defense Command
Ent AFB, Colorado Springs,
Colorado 80912
1 Attn: NPSD-A
1 Attn: ADLPC-2A
(LCOL R.J. Kaminski)
1 Attn: ADOAC-ER
1 Attn: NELC-AP

Electronics Systems Div. (ESSL)
L. G. Hanscom Field
Bedford, Massachusetts 01731
1 Attn: 440L

Headquarters SAC (OAI)
Offutt AFB
Omaha, Nebraska 68113
1 Attn: Mrs. E. G. Andrews

Headquarters, AFCRL
L.G. Hanscom Field
Bedford, Massachusetts 01731
1 Attn: CRUI
1 Attn: CRUP (Dr. G.J. Gassman)

U.S. Air Force
Western Test Range
Vandenberg AFB,
California 93437
1 Attn: WTGT
(Mr. Stanley Radom)

Headquarters, USAF AFTAC
Washington, D. C. 20333
1 Attn: TD-3

Major T.D. Damon
Hqtrs. Air Weather Service
(AWVDC)
1 Scott Air Force Base, Illinois
62265

ARMY

Office of the Assistant Chief
of Staff for Intelligence
Department of the Army
The Pentagon, Room 2B 457
Washington, D. C. 20310
1 Attn: Mr. Joseph Grady

U. S. Army SLAG
The Pentagon, Room 1B 657
Washington, D. C. 20310
1 Attn: Mr. N. R. Garofalo

Chief, Army Security Agency
Arlington Hall Station
Arlington, Virginia 22212
1 Attn: Mr. R. R. Neill
1 Attn: IAOPS-O(SA)

Commanding Officer
U.S. Army Security Agency
Processing Center
Vint Hill Farms Station
Warrenton, Virginia 22186
1 Attn: LT Alan Bagully
1 Attn: Technical Library

Commander, Electronics
Warfare Lab
Mt. View Office, USAEC
P.O. Box 205
Mt. View, California 94040
1 Attn: Mr. Joseph Bert

U. S. Army Foreign Science &
Technology Center
Munitions Building
Washington, D. C. 20315
1 Attn: Communications &
Electronics Division

U Series - Army (Cont)

Commanding General
U. S. Army Missile Command
Redstone Arsenal, Alabama 35809
1 Attn: AMSMI-RES

DEPT. OF DEFENSE

Director
Advanced Research Projects Agency
The Pentagon
Washington, D. C. 20301
1 Attn: Mr. Alvin Van Every

Office of the Assistant Director
Intelligence & Reconnaissance
Office of the Director of Defense
Research & Engineering
The Pentagon, Room 3E 119
Washington, D. C. 20301
1 Attn: Mr. H. A. Staderman

Director
National Security Agency
Ft. George G. Meade
Maryland 20755
1 Attn: K-344 (Mr. C. Gandy)
1 Attn: C3-TDL

Deputy Director
Research & Technology
Office of the Director of
Defense Research & Engineering
The Pentagon, Room 3E 1030
Washington, D. C. 20301
1 Attn: Dr. C. W. Sherwin

Office of the Assistant
Director (Defense Systems)
Defense Research & Engineering
The Pentagon, Room 3D 138
Washington, D. C. 20301
1 Attn: Mr. Daniel Fink

Director, Defense
Intelligence Agency
The Pentagon, Room 3B 259
Washington, D. C. 20301
1 Attn: DIACO-4
1 Attn: DIAST-2B

Director, Weapons Systems
Evaluation Group
Office of the Director of
Defense, Research & Engineering
1 Washington, D. C. 20301

Defense Documentation Center
Cameron Station
20 Alexandria, Virginia 22314

National Aeronautics & Space
Administration
Ames Research Center
Moffett Field, California 94035
1 Attn: Dr. Kwok-Long Chan
1 Attn: Mr. Lawrence Colin

OTHER

ITT Electro-Physics Labs Inc.
3355 - 52nd Avenue
Hyattsville, Maryland 20781
1 Attn: Mr. W. T. Whelan

Institute for Defense Analyses
400 Army-Navy Drive
Arlington, Virginia 22202
1 Attn: Dr. Louis Wetzel

MITRE Corporation
E Bldg., Room 353
Bedford, Massachusetts 01730
1 Attn: Mr. W.A. Whitcraft, Jr.
1 Attn: Mr. Bill Talley

RAND Corporation
1700 Main Street
Santa Monica, California 90406
1 Attn: Dr. Cullen Crain
1 Attn: Library

Raytheon Company
Spencer Laboratory
2 Wayside Road
Burlington, Massachusetts 01803
1 Attn: Mr. L. C. Edwards

U-Series - Other (Cont)

<p>Stanford Research Institute Menlo Park, California 94025 1 Attn: Dr. David Johnson</p> <p>Sylvania Electronics Systems Electronics Defense Laboratory P. O. Box 205 Mt. View, California 1 Attn: Mr. John DonCarlos</p> <p>Mr. Thurston B. Soisson Box 8164 SW Station 1 Washington, D. C. 20024</p> <p>Astrophysics Research Corporation 10889 Wilshire Blvd. Los Angeles, California 90024 1 Attn: Dr. Alfred Reifman</p> <p>Institute of Science & Technology The University of Michigan P. O. Box 618 Ann Arbor, Michigan 48105 1 Attn: BAMIRAC Library</p> <p>Bendix Corporation Bendix Radio Division Baltimore, Maryland 21204 1 Attn: Mr. John Martin</p> <p>AVCO Systems Division Lowell Industrial Park Lowell, Massachusetts 01851 1 Attn: Mr. Sidney M. Bennett</p> <p>U.S. Department of Commerce TSA - ESSA Boulder, Colorado 80302 1 Attn: Mr. William Utlaut 1 Attn: Mr. L. H. Tveten 1 Attn: Mr. W. A. Klemperer, Div. 530, ESSA</p> <p>Page Communications, Inc. 3300 Whitehaven St., NW Washington, D. C. 20008 1 Attn: Mr. David Fales, III</p>	<p>Massachusetts Institute of Technology Lincoln Laboratory P. O. Box 73 Lexington, Massachusetts 02173 1 Attn: Dr. J. H. Chisholm</p> <p>Massachusetts Institute of Technology Center for Space Research Building 33-109 Cambridge, Massachusetts 02138 1 Attn: Dr. J.V. Harrington</p> <p>Princeton University James Forrestal Research Center Plasma Physics Laboratory P. O. Box 451 Princeton, New Jersey 08540 Attn: Dr. Edward Frieman</p> <p>University of California Mathematics Department Berkeley, California 94720 1 Attn: Dr. E. J. Pinney</p> <p>Electronics Research Laboratory University of California Berkeley, California 94720 1 Attn: Prof. D. J. Angelakos</p> <p>Battelle-Defender Battelle Memorial Institute 505 King Avenue 1 Columbus, Ohio 43201</p> <p>HRB-Singer, Inc. Science Park P.O. Box 60 State College, Pennsylvania 16801 1 Attn: Library</p> <p>Pickard & Burns, Research Department 103 Fourth Avenue Waltham, Massachusetts 02154 1 Attn: Dr. J. C. Williams</p>
--	--

Other U-Series (Cont)

Sylvania Electronic Systems
Applied Research Laboratory
40 Sylvan Road
Waltham, Massachusetts 02154

1 Attn: Library

Department of Electrical
Engineering
Radiolocation Research Laboratory
University of Illinois
Urbana, Illinois 61803

1 Attn: 311 EERL (Mr. D.G. Detert)

Arecibo Ionospheric Observatory
Box 995
Arecibo, Puerto Rico 00613

1 Attn: Librarian

The University of Texas
Electrical Engineering Research
Laboratory
Route 4, Box 189
Austin, Texas 78756

1 Attn: Mr. C. W. Tolbert

Rice University
Fondren Library
P.O. Box 1892

1 Houston, Texas 77001

Purdue University
Library

1 West Lafayette, Indiana

Telcom, Incorporated
5801 Lee Highway
Arlington, Virginia 22207

1 Attn: Mr. J. D. Ahlgren,
Vice President

DOCUMENT CONTROL DATA - R & D

Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified

1. ORIGINATING ACTIVITY (Corporate author) Stanford Electronics Laboratories Stanford University, Stanford, California		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP	
3. REPORT TITLE LATERAL DEVIATION OF OBLIQUELY PROPAGATED HF RADIO RAYS			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Technical Report			
5. AUTHOR(S) (First name, middle initial, last name) T. W. Washburn			
6. REPORT DATE May 1968		7a. TOTAL NO. OF PAGES 18	7b. NO. OF REFS 14
8a. CONTRACT OR GRANT NO. Office of Naval Research Contract		9a. ORIGINATOR'S REPORT NUMBER(S) SEL-68-045 TR No. 137	
b. PROJECT NO. Nonr-225(64), NR 088-019 ARPA Order No. 196		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c.			
d.			
10. DISTRIBUTION STATEMENT This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Office of Naval Research, Field Projects Branch, Washington, D. C., 20360.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Office of Naval Research Advanced Research Projects Agency	
13. ABSTRACT As is well known, magnetoionic splitting of obliquely propagated HF radio waves may result in deviation of such waves from the great-circle plane between transmitter and receiver. A computer raytracing routine has been employed at Stanford to investigate the properties and maximum extent of this phenomenon under realistic ionospheric conditions. It is concluded that for a 1000 km path the difference in azimuthal bearing between the ordinary and extraordinary modes could reach a maximum of 0.5 deg, corresponding to an 0.25 deg variation of either mode from the true bearing. However, in most practical bearing estimation problems, the difference is an order of magnitude smaller than this maximum, and thus is truly small in comparison with other sources of error.			

14.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	IONOSPHERIC PROPAGATION RAYTRACING LATERAL DEVIATION DIRECTION FINDING, AS AZIMUTHAL BEARING ERROR						