# UNCLASSIFIED

# AD NUMBER

## AD856385

# LIMITATION CHANGES

## TO:

Approved for public release; distribution is unlimited.

# FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; MAR 1969. Other requests shall be referred to U.S. Army Aviation Materiel Laboratories Fort Eustis, Virginia. This document contains export-controlled technical data.

# AUTHORITY

USAAML ltr, 3 Oct 1969

THIS PAGE IS UNCLASSIFIED

# **USAAVLABS TECHNICAL REPORT 68-77**

20

AD85638

AD

doou

with

# APPLICABILITY OF THE SOUTHWELL PLOT TO THE INTERPRETATION OF TEST DATA FROM INSTABILITY STUDIES OF SHELL BODIES

By W. H. Horton

F. L. Cundari



#### Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

٩.

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission, to manufacture, use, or sell any patented invention that may in any way be related thereto.

#### **Disposition Instructions**

Destroy this report when no longer needed. Do not return it to the originator.



#### DEPARTMENT OF THE ARMY U. S. ARMY AVIATION MATERIEL LABORATORIES Fort Eustis, Virginia 23604

#### ERRATUM

USAAVLABS Technical Report 68-77

TITLE: Applicability of the Southwell Plot to the Interpretation of Test Data From Instability Studies of Shell Bodies

Delete the statement on cover, title page, and block 10 of DD Form 1473 which reads

"This document has been approved for public release and sale; its distribution is unlimited."

and replace with the following statement:

"This document is subject to special export controls, and each transmittal to foreign governments or foreign nationals may be made only with prior approval of US Army Aviation Materiel Laboratories, Fort Eustis, Virginia 23604."



L

DEPARTMENT OF THE ARMY HEADQUAFTERS US ARMY AVIATION MATERIEL LABORATORIES FORT EUSTIS, VIRGINIA 23604

The program was carried out under Contract DA 44-177-AMC-258(T) with Stanford University.

The research was directed toward the development of a better understanding of the fundamental processes in the buckling of shell bodies. The data contained in this report are the result of experimental studies of the instability of shell bodies and the interpretation of the data by means of the Southwell plot.

The report has been reviewed by the U.S. Army Aviation Materiel Laboratories and is considered to be technically sound. It is published for the exchange of information and the stimulation of future research.

#### Task 1F162204A17001 Contract DA 44-177-AMC-258(T) USAAVLABS Technical Report 68-77

ı

.

#### March 1969

#### APPLICABILITY OF THE SOUTHWELL PLOT TO THE INTERPRETATION OF TEST DATA FROM INSTABILITY STUDIES OF SHELL BODIES

By

W. H. Horton F. L. Cundari

Prepared by

Stanford University Stanford, California

for

,

U. S. ARMY AVIATION MATERIEL LABORATORIES FORT EUSTIS, VIRGINIA

> This document has been approved for public release and sale; its distribution is unlimited.

#### ABSTRACT

This report demonstrates, from experimental studies, that the classic critical loads computed from small displacement theory are correct for perfect shells under ideal loading conditions. The method used is an implicit rather than an explicit one. It makes use of the fact that for a realistic structure, the elastic deformation can be associated with the initial displacement from ideal form, the load which produces the motion, and the classic load for the structure by the hyperbolic expression



By choosing the variables to be  $\delta/P$  and  $\delta$ , the relationship can be presented in the form of a straight line whose slope corresponds to the critical load for the ideal case. This is, in essence, the method developed by Aryton and Perry, in 1889, to analyze column data. The generalization to include other structures was foreseen by Southwell in his classic paper of 1932, although he offered no proof. In effect, a general proof exists in the theory of elastic stability as presented by Westergaard in 1922. However, the practical application to shells has, until now, not been made.

By using this technique, the behaviour of cylinders under the action of external pressure, torsion, and axial load and of the instability of spheres and spherical caps under the action of external pressure is examined. In the main, the analyses are conducted on experimental data already published. However, there are notable exceptions, the cylindrical shell under axial load being a case in point.

# **BLANK PAGE**

#### FOREWORD

The work reported in this paper was supported by the U. S. Army under Contract DA 44-177-AMC-258(T), U. S. Air Force under Contract AF 49(638) 1495, and the U. S. Navy via a research grant from the U. S. Naval Postgraduate School. Their support is gratefully acknowledged.

### TABLE OF CONTENTS

۱

	Page
ABSTRACT	iii
FOREWORD	v
LIST OF ILLUSTRATIONS	vii
LIST OF TABLES	vii
LIST OF SYMBOLS	viii
INTRODUCTION	l
EXPERIMENTAL EVIDENCE	2
CONCLUSIONS	17
REFERENCES CITED	18
DISTRIBUTION	20

.

#### LIST OF SYMBOLS

#### ARABIC SYMBOLS

a = radius of base of spherical cap

- A = amplitude of the displacement
- E = Young's modulus
- L = length
- n = integer 1, 2, 3
- p = pressure
- $p_{cr}$  = the critical value of p
  - P = load
- $P_{cr}$  = the prime critical value of p
- $P_{n cr}$  = the critical value of p corresponding to the  $n^{th}$  mode
  - R = radius
  - s = circumferential distance
  - t = distance
  - w = displacement function
  - W = elastic displacement amplitude parameter
  - W' = initial displacement amplitude parameter
    - x = coordinate direction

#### GREEK SYMBOLS

$$\lambda = \left[ a^{4} (12(1-\mu^{2})/(Rt^{2}) \right]^{\frac{1}{4}}$$
  

$$\delta = \text{total elastic deflection}$$
  

$$\delta_{o} = \text{initial displacement}$$
  

$$\mu = \text{Poisson's ratio}$$

#### LIST OF ILLUSTRATIONS

۱

Figur	<u>e</u>	Page
1	Load-Sway Relationship for Elastic Arch and Corresponding Southwell Plot (Ref 6)	3
2	Circular Cylindrical Shell under External Pressure	3
3	Circular Cylindrical Shell under External Pressure (Fata from Figure 18, Ref 7)	4
4	Lundquist-Type Plot for Thin-Walled Circular Cylinder under Axial Compression Observation Point No 1	9
5	Lundquist-Type Plot for Thin-Walled Circular Cylinder under A Axial Compression Observation Point No 2	10
6	Torsion Versus Inward Wall Motion and Corresponding Southwell Plot for Orthotropic Cylinder	10
7	Load-Deflection Relationship and Corresponding Southwell Plot for Sphere with Point Load at Apex (Ref 19)	11
8	Southwell Plot for Sphere (Data from Ref 20)	13
9	Southwell Plot for Spherical Cap under External Pressure (Ref 21)	14
10	Critical Pressure Versus $\lambda$ as Determined by Southwell Plots (Ref 21)	14
11	Pressure-Displacement Relation and Corresponding Southwell Plot for Nickel Sphere under External Pressure	15
12	Southwell Plot for Sphere External Pressure (Data from Ref 23)	15

## LIST OF TABLES

.

•

Table				Page
I	Comparison	of	Multiobservations on Single Specimen	5
II	Comparison	of	Single Observations on a Range of Specimen	7

#### INTRODUCTION

Shell structures are very common. For over a century, engineers have investigated experimentally and discussed theoretically their behavior under various loading conditions. The extent of this endeavor is clear from the fact that some 23391, 2books and papers were written in the field prior to 1956. Nevertheless, many facets of the subject are still unresolved. Indeed, it has become traditional to expect wide divergence between experimental results and theoretical predictions when certain problems of stability are considered. This is particularly so for circular cylindrical shells under axial compression and spherical shells under external pressure. The exact causes of the discrepancy are hard to identify. However, one factor of importance is easily recognized. Theories are normally developed for ideal bodies with perfect loading conditions and boundary restraint; whereas tests are always made with realistic structures imperfectly loaded and constrained. Thus, if agreement between theory and experiment is to be achieved, it will be through an implicit rather than an explicit process. The Southwell<sup>3</sup> technique, which has already been demonstrated to have general applicability in questions of elastic stability of plates and columns, 4 is such a process. The present paper establishes the validity of this technique for shell problems.

The analytical basis of the work is older than the Southwell concept itself, being found in the study made by Westergaard<sup>5</sup>in 1922. In this very general analysis, the relationship among elastic deformation, the initial deviation from ideal form, the load level, the critical load and its harmonics was derived. The starting point was the Lagrangian expressed in generalized coordinates. Westergaard considered not only initial geometric variances but also nonhomogeneity and eccentricities of loading. He applied the theory of minimum potential and obtained a general relationship among the actual load (P), the critical load for a particular mode ( $_{n}P_{cr}$ ), the amplitude of that component of the initial irregularity which corresponds to the n<sup>th</sup>mode ( $_{n}\delta_{0}$ ), and the appropriate associated component of elastic deflection ( $\delta$ ).

This relationship is

 $\delta = \frac{P}{n^{P}cr^{-P}} n^{\delta}o$  (1)

Clearly, there are n terms of this type and the total elastic deflection of the structure under the given load system is

 $\delta = \sum_{n=1}^{\infty} \frac{P}{n^{P} cr^{-P}} n^{\delta} o$  (2)

In many problems, the first mode predominates, and, thus, a single-term expression of the type given in equation (2) adequately describes the behavior. Hence, the relationship between  $\delta$  and P is hyperbolic. However, if the variables are taken as  $\delta/P$  and  $\delta$ , the relationship is linear.

#### EXPERIMENTAL EVIDENCE

To illustrate the process, we chose the simplest curved structure with the most elementary loading; viz, a circular arch compressed by a point load at its vertex. Langhaar, Boresi, and Carver have examined this problem both theoretically and experimentally. The arch which they used was of 10-inches radius and was made from a strip of aluminum 2.5 in. wide and .031 in. thick. It was simply supported at its ends. The load displacement relationship obtained in the test is given in Figure 1. When this is plotted in the Southwell fashion, the characteristic straight line (Figure 1) is obtained. The critical load determined from this line is 4.12 lbs, which is in excellent agreement with the theoretically predicted value of 4.17 lbs.

A somewhat more complex problem is the behavior of a tube under external pressure (p). This problem has been treated analytically by Sturm<sup>1</sup>, and the validity of his solution has been well established by his own tests and those of Cleaver.<sup>8</sup> However, from the viewpoint of this paper, the most important factor in Sturm's analysis lies in his demonstration that for a slightly imperfect cylinder, the initial radial deformation amplitude is related to the subsequent amplitude by the equation

$$\delta = \frac{P \delta_0}{P_{cr} - P}$$
(3)

This equation is, of course, identical to the general equation derived by Westergaard and clearly shows that a Southwell representation of test data should be applicable. When the load displacement data given in Figure 16 and 18 of Sturm's paper are replotted in the Southwell form, the straight lines given in Figures 2 and 3 of this report are obtained. The critical loads obtained from the several slopes are in excellent agreement with the theoretical predictions.

Subsequent to the work of Sturm, a number of experimental studies were made on the stability of ring-reinforced circular cylinders under external pressure loading. (In one particular series of tests, the shells failed by general instability.) It is with reference to the interpretation of these tests that the first practical application of the Southwell method to shell bodies is recorded. Galletly and Reynolds' made the analysis. In their paper, they noted the applicability of the Southwell process to many problems and suggested a modification for the case in question. This was the use of strains instead of displacements, a step which is readily seen admissable and which is analytically demonstrated in Westergaard's paper. The results which they obtained are most important. For the first test which they report, observations were made at 21 different points on the body. The critical loads derived from these measurements are in excellent agreement with one another. They are listed in Table I.

It is seen that the critical loads range from 168 lb to 178 lb, with a mean of 172.2 lb. These values compare well with the theoretical load of 173 lb computed in accordance with Kendrick's theory.

The second set of data presented by these researchers is a comparison of the



FIGURE 1. Load-Sway Relationship for Elastic Arch and Corresponding Southwell Plot (Ref 6).



FIGURE 2. Circular Cylindrical Shell under External Pressure (Data from Fig 16, Ref 7).





TABLE I.	COMPARISON ON SINGLE	OF MULTION SPECIMEN	3SERVATIONS		
Station	Southwell	Station	Southwell		
No.	Load	No.	Load		
1 2	172 171	12 13	171 172		
3	173	14	174		
4	171	15	173		
5	173	16	169		
6	169	17	168		
7	171	18	174		
8	178	19	174		
9	174	20	168		
10	173	21	174		
11	174				
Mean Theo	Mean value of load 172.2 Theoretical value 173				
Ratio of	mean value theoretical	value =	• 995		

results of tests made on five similarly constructed shells, whose theoretical collapse pressures are 150 psi and 1000 psi. The ratios of the critical load levels computed from Kendrick's theory and the values deduced from the tests are given in Table II. Again, the comparisons are seen to be very good indeed.

Donnell<sup>11</sup> in his classic paper on the Southwell method appears to have been the first to consider whether or not the process could be applied to the thin-walled circular cylinder under axial load. He examined the problem analytically, taking as his starting point his approximate solution for the instability of a cylinder under axial compression in which he had considered initial deviations from cylindrical shape.

He chose the deflection function to be given by

$$w = W \sin \frac{\pi}{L} \sin \frac{\pi}{L} + W(W+2W') \frac{\pi^2 R}{8L^2} \cdot \cos \frac{2\pi}{L}$$
(4)

The reason for this choice lay in the fact that the second term was most useful in annulling some of the second-order extension with first-order extensions and, thus, was effective in reducing the internal energy. This initial deviation from cylindrical form was taken to be given by

$$w' = \frac{W'}{W} w \tag{5}$$

From this basis, he computed that the relationship among the load, the critical load, and the initial and subsequent deformations would be given by

$$\mathbf{P} = \frac{W}{W' + W} \cdot \frac{P_{cr}}{L} - \frac{1 + \frac{\pi^{4}R^{2}}{4L} \cdot (W + 2W') (W + W')}{1 + \frac{\pi^{4}R^{2}}{8L^{4}} \cdot \frac{(W + 2W')^{2} (2W + W')}{W + W'}}$$
(6)

where P is the critical load for the perfect shell and is given by the normal equation

$$P_{cr} = \sqrt{\frac{E.t.}{3(1-\mu^2)}} \cdot \frac{1}{R} \cdot 2\pi t$$
 (7)

It is clear that if Donnell's large displacement derivation is true, there must be some classes of shells for which the multiplying factor on the Southwell form is not unity. But it is apparent that if W and W' are small compared with 2L<sup>2</sup>/N<sup>2</sup>R or when W' is very small compared with W, the South-well plot should yield accurate results.

In view of Donnell's analytical development and the acute interest in circular cylinders under axial compression, it might be thought that the question would have been experimentally resolved. Unfortunately, at the time that Donnell was studying this problem, it was not technically feasible to use noncontacting displacement transducers to measure the radial movement of the wall of an axially compressed shell model with the degree of accuracy

TABLE II.	COMPARISON OF SINGLE OBSERVATIONS ON A RANGE OF SPECIMENS
Specimen No.	Southwell Load Theoretical Load
1	1.011
2	1.022
3	.861
4	1.076
5	. 882
Average	.970

required to verify the analysis. Thus, Donnell was constrained to theoretical observation only.

Flügge,<sup>12</sup> in his text on "Stresses in Shells," appears to be the next author to refer application of the Southwell plot to test results on shell bodies. In his discussion, he emphasizes that more than one mode may be involved in the total deformation; thus, since in many shells there exist a number of critical loads immediately above the lowest one, several terms of the displacement series may grow to infinity together. In this detail, then, the cylinder under axial compression differs from the column for which the eigenvalues are significantly separated.

However, he states that if care is taken to measure a displacement which is large for the lowest buckling load but small for all others, then the Southwell technique is applicable. He substantiated his remark by reference to unpublished experiments conducted by Kromm and Flugge in the early 1940's. These tests were made on cylinders under various combinations of axial compression and torsion. Professor Flügge has remarked that Southwell plots were obtained only when the predominant loading was torsional.

In our research, we have found that if well-made thin-walled shells are tested with extreme care to ensure uniformity of load distribution, and if noncontacting probes of high resolution are used to determine the wall motion, load-displacement relationships of the hyperbolic type are obtained. Data for typical tests are given in Figures 4 and 5. Both these observations were made on the same shell. The data have been plotted in the Lundquist manner. The agreement between the classic critical loads and the values computed for these plots is good (maximum error, 1.98%). The cylinder used was male from a thick-walled tube of aluminum by machining and was circular to within 1/1,000 in. and was uniform in thickness to better than 1/10,000 in. It had an R/t of 335 and an 1.4 D of 1.87. The test was made in which loading was via a thermal ram. Deflection measurements were made using a Fotonic sensor, an electro-optical measuring device of high resolution. The test is fully described in reference 16.

In the case of torsional loading, it is much easier to determine experimentally the wall motions during instability. Consequentially, it is relatively easy to obtain good results in this case. A typical set of data, obtained from a test on an orthotropic cylinder, is given in Figure 6.

The literature contains much material with reference to the instability of spheres and spherical caps under the action of normal point loads, uniform external pressure and combinations thereof. This has been examined in Reference 18.

The experimental work of Ashwell<sup>19</sup> and Evan-Ivanowski, Cheng, and Loo<sup>20</sup> on spherical caps subjected to a concentrated load at the apex provides several cases in which the load-displacement curves can be successfully analyzed by the Southwell method. The load-displacement curve and the corresponding Southwell line are given in Figure 7 for Ashwell's test on a



.

FIGURE 4. Lundquist-Type Plot for Thin-Walled Circular Cylinder under Axial Compression Observation Point No 1.



1

FIGURE 5. Lundquist-Type Plot for Thin-Walled Circular Cylinder Under Axial Compression Observation Point No 2.



FIGURE 6. Torsion Versus Inward Wall Motion and Corresponding Southwell Plot for Orthotropic Cylinder.



FIGURE 7. Load-Deflection Relationship and Corresponding Southwell Plot for Sphere with Point Load at Apex (Ref 19).

specimen with a  $\lambda$  of 6.4. The corresponding case for the Evan-Ivanowski, Cheng, and Loo research ( $\lambda$ =6.3) is given in Figure d. The critical values of P'R/Et<sup>-</sup> derived from the plots are in very close agreement, being 3.09 and 3.1 units, respectively.

Although the majority of the data cannot be analyzed in this fashion, it is interesting to note that those results which can be so treated appear to be consistent and to agree reasonably well with Ashwell's computed values. It would seem, however, that before a positive statement is made in this regard, another series of tests should be made with the method of correlating via load displacement firmly in mind from the onset. The behavior of a spherical cap under uniform external pressure has been considered analytically and experimentally by Kaplan and Fung. The majority of their data is amenable to this method of analysis, and a typical  $\delta/p$  versu.  $\delta$  plot is given in Figure 9. In Figure 10, the deduced critical pressures are plotted as a function of the geometric parameter  $\lambda$ , which describes the caps.

It is seen that all the points are on a smooth curve. The lower portion of this curve corresponds very well with that computed by Kaplan and Fung as an approximate solution to their equations.

The spherical cap under combined loading, a normal force at the apex and a distributed\_pressure, has been examined experimentally by Loo and Evan-Ivanowski. Many of their load-displacement curves can be analyzed by the Southwell method, but there is no theory available for comparison.

The behavior of complete spheres under external pressure loading is another area in which problems of correlating test data currently exist.

An experimental study was made on a thin-walled nickel sphere to check the possibility of relating radial displacement, pressure, and theoretical critical external pressure. The experiment is reported in full<sub>6</sub> in Reference 18. The basic material had a Young's modulus of 29.3 X 10<sup>-1b</sup>/in.<sup>2</sup> as determined by routine material tests. This value was confirmed for several points on the sphere by measurement of decrease in radius as a function of pressure. The shell was elastically buckled;\* when the point of buckle inception had been thus established, a test was made using a sensitive noncontacting displacement probe located at, or very near, the buckle center. The variation of displacement with pressure is clearly seen in Figure 11. There are two properties of this curve which are both apparent and important. First, the initial deflection is linear. Second, the final displacement curve is hyperbolic. The hyperbolic curve gives an excellent Southwell plot (Figure 12), whose slope corresponds closely

<sup>\*</sup>The sphere was restrained against excessive motion by the use of an internal mandrel. As a result, on the second and subsequent buckling tests, the load levels for instability reached the same value as on the initial test.



FIGURE 8. Southwell Plot for Sphere (Data from Ref 20).



۱

FIGURE 9. Southwell Plot for Spherical Cap under External Pressure (Ref 21).



,

IGURE 10. Critical Pressure Versus λ as Determined by Southwell Plots (ref 21).



FIGURE 11. Pressure-Displacement Relation and Corresponding Southwell Plot for Nickel Sphere under External Pressure.



FIGURE 12. Southwell Plot for Sphere External Pressure (Data from Ref 23).

to the critical load computed on classic theory when the modulus has the value indicated by the initial slope.

۱

The data presented by Thompson<sup>23</sup> have also been examined in the same manner.<sup>12</sup> The conclusions reached were identical. The Southwell plot predicts the classic critical load for this sphere, also. It should be noted that in this case, too, the buckle generating defect was located at a point which was characterized by an apparent reduced modulus. The modulus value used in the data correlation was that which corresponded to the initial linear portion of the load-displacement curve.

#### CONCLUSIONS

The experimental and theoretical study presented in this report concludes a broad analysis which has been conducted on the range of applicability of the Southwell plot as a means of data interpretation for tests on shells. The results presented, when taken in conjunction with those given in a previous report for plate structures, provide evidence that the method is of absolute generality. However, it may be reasoned in the case of structures in which many buckles can be formed, that the true process of buckling may be controlled by the individual character of the structures. In this case, imperfection could influence local boundary values and would thus show as an apparent lowering or an elevating in critical load as given by the Southwell plot. If this i. so, we should anticipate that the distribution of Southwell values will be essentially normal if many observations are made at devious points over the body.

With this process, then, we feel confident in asserting that theories for perfect bodies which give estimates not in agreement with experimental values derived on the basis of Southwell-type plots must be considered inadequate, incomplete, or in error.

#### REFERENCES CITED

- Nash, W. A., BIBLIOGRAPHY ON SHELLS AND SHELL-LIKE STRUCTURES, 1954-1956, University of Florida, Contract DA-01009-ORD-404, U. S. Army, Office of Ordnance Research, 1957.
- Nash, W. A., BIBLIOGRAPHY ON SHELLS AND SHELL-LIKE STRUCTURES TMB Report 863, U. S. Navy Department, David Taylor Model Basin, Washington D. C., 1954.
- 3. Southwell, R. V., ON THE ANALYSIS OF EXPERIMENTAL OBSERVATIONS IN PROB-LEMS OF ELASTIC STABILITY, <u>Proceedings of the Royal Society</u>, Vol. 135A, page 601.
- 4. Horton, W. H., Cundari, F. L., and Johnson, R. W., THE ANALYSIS OF EXPERIMENTAL DATA OBTAINED FROM STABILITY STUDIES ON ELASTIC COLUMN AND PLATE STRUCTURES, <u>Israel Journal of Technology</u>, Vol. 4, No. 1, 1967.
- 5. Westergaard, H. M., BUCKLING OF ELASTIC STRUCTURES, Transactions of American Society of Civil Engineers, Vol. 85, 1922, pages 576-654.
- American Society of Civil Engineers, Vol. 85, 1922, pages 576-654.
  Langhaar, H. L., Boresi, A.P. Carver, D. R., ENERGY THEORY OF BUCKLING OF CIRCULAR ELASTIC RINGS AND ARCHES, Proceedings of Second U.S. National Congress on Applied Mechanics, 1954.
- 7. Sturm, R. G., A STUDY OF THE COLLAPSING PRESSURE OF THIN-WALLED CYL-INDERS, Engineering Experiment Station Bulletin, No. 329, University of Illinois, Urbana, Illinois.
- 8. Cleaver, P. C., STRENGTH OF TUBES UNDER EXTERNAL PRESSURE, Royal Aircraft Establishment Report No. Structures 193, November 1955, Farnborough, Hants, England.
- 9. Galletly, G. D., and Reynolds, T. E., A SIMPLE EXTENSION OF SOUTHWELL'S METHOD FOR DETERMINING THE ELASTIC GENERAL INSTABILITY OF RING STIFFENED CYLINDERS SUBJECTED TO EXTERNAL PRESSURE, <u>Proceedings</u> <u>SESA</u>, Vol. XIII, No. 2, 1956, pages 141-151.
- Kendrick, S., THE BUCKLING UNDER EXTERNAL PRESSURE OF CIRCULAR CYLINDRI-CAL SHELLS WITH EVENLY SPACED EQUAL STRENGTH CIRCULAR RING FRAMES, Part I NCRE/R No. 211, Naval Construction Research Establishment, Dumfurine, Scotland, 1953.
- Donnell, L. H., ON THE APPLICATION OF SOUTHWEIL'S METHOD FOR THE ANALYSIS OF BUCKLING TESTS, S. Timoshenko 60th Anniversary Volumn, Mac-Millan Company, New York, 1938.
- 12. Flugge, W., STRESSES IN SHELLS, Springer, Berlin, 1960.
- 13. Lundquist, E. E., GENERALIZED ANALYSIS OF EXPERIMENTAL OBSERVATIONS IN PROBLEMS OF ELASTIC STABILITY, NACA Technical Note 658, 1938.
- 14. Horton, W. H., Bailey, S. C., and Smith, S., A NEW FAMILY OF TEST MACHINES AND TRANSDUCERS FOR STABILITY STUDIES ON THIN-WALLED SHELLS, Paper in Preparation.
- 15. Horton, W. H., Craig, J. I., and Shover, D., ON THE MEASUREMENT OF MOTIONS, DEFORMATIONS AND GEOMETRIC PARAMETERS IN STUDIES OF INSTABILITY OF THIN-WALLED SHELLS, Paper in preparation.
- 16. Cundari, F. L., ON THE ANALYSIS OF EXPERIMENTAL DATA OBTAINED FROM STA-BILITY STUDIES, Ph. D. Thesis in preparation.
- 17. Banks, M., THE EFFECT OF FIBER DIRECTION ON THE STABILITY OF SINGLE-LAYER RESIN IMPREGNATED GLASS CLOTH CYLINDERS UNDER TORSION, Engineer's Thesis in preparation.
- 18. LeBouc, P., SOME STUDIES ON THE INSTABILITY OF SPHERES AND SPHERICAL CAPS, Engineer's Thesis in preparation.

- 19. Ashwell, D. G., ON THE LARGE DEFLECTION OF A SPHERICAL SHELL WITH AN INWARD POINT LOAD, Proceedings of the Symposium Theory of Thin Elastic Shells (Delft, 24th-28th August 1959),1960.
- 20. Evan-Ivanowski, R. M., Cheng, H. S., and Loo, T. C., EXPERIMENTAL INVESTIGATIONS OF DEFORMATIONS AND STABILITY OF SPHERICAL SHELLS SUB-JECTED TO CONCENTRATED LOAD AT THE APEX, Proceedings of the Fourth U.S. National Congress of Applied Mechanics, 1962, page 563.
- 21. Kaplan, A., and Fung, Y. C., A NONLINEAR THEORY OF BENDING AND BUCKLING OF THIN ELASTIC SHALLOW SPHERICAL SHELLS, NACA TN 3212, August 1954.
- 22. Loo, T. C., and Evan-Ivanowski, R. M., DEFORMATIONS AND COLLAPSE OF SPHERICAL DOMES SUBJECTED TO UNIFORM PRESSURE AND NORMAL CONCENTRATED LOADS AT THE APEX, Proceedings of World Conference on Shells and Structures, San Francisco, 1962.
- 23. Thompson, J. M. T., THE ELASTIC INSTABILITY OF A COMPLETE SPHERICAL SHELL, The Aeronautical Quarterly, Vol. 13, Part 2, May 1962, page 189.

DOCUMENT	CONTROL DATA -	C & D	
(Security classification of title, body of abstract and in	dezing annotation must be	entered when the	overall report is classified)
Change and The second states		Inclassi	ECURITY CLASSIFICATION
Stanford University		14. GROUP	
Stanora, Camornia		1	
AEPORT TITLE			
APPLICABILITY OF THE SOUTHWELL PLO INSTABILITY STUDIES OF SHELL BODIE	YT TO THE INTERP	RETATION OF	F TEST DATA FROM
DESCRIPTIVE NOTES (Type of report and inclusive dates)			
AUTHOR(S) (First name, middle initial, last name) Wilfred H. Horton			
Frank L. Cundari			
March 1969	74. TOTAL NO.	OF PAGES	78. NO. OF REFS
CONTRACT OF GRANT NO.	21		23
Contract DA 44-177-AMC-258(T)	USAAVI.A	REPORT NUM	BERIS)
PROJECT NO.	oblatting		
Task 1F162204A17001			
	this report)	ORT NO(S) (ANY	omer numbers that may be assigned
	US Army	Aviation	Materiel Laboratorie
ABSTRACT	US Army Fort Eus	Aviation tis, Virgi	Materiel Laboratorie nia
This report demonstrates, from expe loads computed from small displacen ideal loading conditions. The meth one. It makes use of the fact that deformation can be associated with load which produces the motion, and hyperbolic expression	US Army Fort Eus erimental studie ment theory are- hod used is an i t for a realisti the initial dis d the classic lo	Aviation etis, Virgi es, that th correct fo mplicit ra c structur eplacement ad for the	Materiel Laboratorie nia e classic critical r perfect shells unde ther than an explicit e, the elastic from ideal form, the structure by the
This report demonstrates, from expendeds computed from small displacemideal loading conditions. The methone. It makes use of the fact that deformation can be associated with load which produces the motion, and hyperbolic expression	US Army Fort Eus erimental studie ment theory are- hod used is an it the initial dis d the classic lo $\frac{P_{cr}}{P} - 1 = \delta_{o}$	Aviation etis, Virgi es, that th correct fo mplicit ra c structur placement ad for the	Materiel Laboratorie nia e classic critical r perfect shells unde ther than an explicit e, the elastic from ideal form, the structure by the
This report demonstrates, from expe- loads computed from small displacer ideal loading conditions. The meth one. It makes use of the fact that deformation can be associated with load which produces the motion, and hyperbolic expression $\delta_{\ell}^{-}$ By choosing the variables to be $\delta/F$ form of a straight line whose slope case. This is, in essence, the meth analyze column data. The generaliz by Southwell in his classic paper of a general proof exists in the theor gaard in 1922. However, the practi- been made.	US Army Fort Eus erimental studie ment theory are hod used is an in t for a realistic the initial dis d the classic loc $\frac{P_{cr}}{P} - 1 = \delta_{o}$ e and $\delta$ , the relevant though developed to the d developed to the include of 1932, although ry of elastic st local application	Aviation etis, Virgi es, that the correct for mplicit rates are structured placement and for the stionship of the critic of Aviation and the structure placement and for the structure placement at other structure ability as to shells	Materiel Laboratorie nia e classic critical r perfect shells unde ther than an explicit e, the elastic from ideal form, the structure by the can be presented in the cal load for the ideal nd Perry, in 1889, to ructures was foreseen ed no proof. In effect presented by Wester- has, until now, not
This report demonstrates, from experimental displacer ideal loading conditions. The methode one. It makes use of the fact that deformation can be associated with load which produces the motion, and hyperbolic expression $\delta_{\rm e}^{\rm f}$ . By choosing the variables to be $\delta/{\rm F}$ form of a straight line whose slope case. This is, in essence, the met analyze column data. The generalize by Southwell in his classic paper of a general proof exists in the theor gaard in 1922. However, the practiblem made. By using this technique, the behavior pressure, torsion, and axial load a caps under the action of external pare conducted on experimental data.	US Army Fort Eus erimental studie ment theory are hod used is an it the initial dis d the classic lo $\left(\frac{P_{cr}}{P}-1\right) = \delta_{o}$ e and $\delta$ , the rel e corresponds to thod developed to thod developed to thod developed to the classic st cal application or of cylinders and of the insta already public	Aviation etis, Virgi es, that the correct for implicit ration constructure placement and for the ationship of the critic y Aryton at e other st h he offer ability as to shells under the bility of s ined. In f	Materiel Laboratorie nia e classic critical r perfect shells unde ther than ar explicit e, the elastic from ideal form, the structure by the can be presented in th cal load for the ideal and Perry, in 1889, to ructures was foreseen ed no proof. In effect presented by Wester- has, until now, not action of external spheres and spherical the main, the analyses
This report demonstrates, from expe loads computed from small displacer ideal loading conditions. The meth one. It makes use of the fact that deformation can be associated with load which produces the motion, and hyperbolic expression $\delta_{\rm c}^{\rm c}$ . By choosing the variables to be $\delta/{\rm F}$ form of a straight line whose slope case. This is, in essence, the met analyze column data. The generaliz by Southwell in his classic paper of a general proof exists in the theor gaard in 1922. However, the practi- been made. By using this technique, the behavi- pressure, torsion, and axial load a caps under the action of external p are conducted on experimental data exceptions, the cylindrical shell u	US Army Fort Eus erimental studie ment theory are- hod used is an it the initial dis d the classic lo $\left(\frac{P_{cr}}{P}-1\right) = \delta_{o}$ P and $\delta$ , the rel e corresponds to thod developed to thod developed to thod developed to tation to includ of 1932, althoug ry of elastic st loal application or of cylinders and of the insta aressure is exam already publish	Aviation etis, Virgi es, that the correct for implicit ration constructure splacement and for the ationship of the critic y Aryton at e other st h he offer ability as to shells under the bility of s ined. In the a case in	Materiel Laboratorie nia e classic critical r perfect shells unde ther than ar explicit e, the elastic from ideal form, the structure by the can be presented in th cal load for the ideal and Perry, in 1889, to ructures was foreseen ed no proof. In effect presented by Wester- has, until now, not action of external spheres and spherical the main, the analyses er, there are notable point.
This report demonstrates, from expendeds computed from small displacer ideal loading conditions. The methone. It makes use of the fact that deformation can be associated with load which produces the motion, and hyperbolic expression $\delta_{\rm exp}^{(-)}$ By choosing the variables to be $\delta/F$ form of a straight line whose slope case. This is, in essence, the methonalyze column data. The generalize by Southwell in his classic paper of a general proof exists in the theor gaard in 1922. However, the practible made. By using this technique, the behavior pressure, torsion, and axial load a caps under the action of external pare conducted on experimental data are exceptions, the cylindrical shell units of the set of the conducted on the	US Army Fort Eus erimental studie ment theory are- hod used is an it the initial dis d the classic lo $\left(\frac{P}{r}-1\right) = \delta_{0}$ e and $\delta$ , the rel e corresponds to thod developed h zation to includ of 1932, althoug ry of elastic st ical application or of cylinders and of the insta- ressure is exam already publish mder axial load	Aviation etis, Virgi es, that the correct for mplicit ration placement and for the estionship of the critic particular of the sationship of the critic part of the estimation of the sationship of the critic part of the sationship of the critic the critic sationship of the critic the critic sationship of the critic sationship of the critic sationship of the critic sationship of the critic sationship of the critic sationship sationship of the critic sationship sation	Materiel Laboratorie nia e classic critical r perfect shells unde ther than an explicit e, the elastic from ideal form, the structure by the can be presented in the cal load for the ideal ad Perry, in 1889, to ructures was foreseen ructures was foreseen presented by Wester- has, until now, not action of external spheres and spherical the main, the analyses er, there are notable point. assified

	LINI		LIN	K B	LIN	ĸc	
	KEY WORDS	ROLE	WT	ROLE	WT	ROLE	w
istability				14			
ell boales				6.1.20		Sec. 24.14	
Duthwell Plot		in the second		Sec. 1			
KIAL LOAD		이 이 이 것 같은 가슴과		1.000			
xternal pressure							
ulindona							
pharas							
pheres							
							1.9.2
				Sec. 1			1
			1 . A .				
				1.1			
					Sec. Sec.		
						1	
						0000	
			Incle				