UNCLASSIFIED

AD NUMBER

AD857892

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; SEP 1969. Other requests shall be referred to Atomic Energy Commission P. O. Box 5400 Albuquerque, NM 87115. This document contains export-controlled technical data.

AUTHORITY

AEDC ltr, 23 Jan 1975

THIS PAGE IS UNCLASSIFIED

AEDC-TR-69-151

accentacato

SERIE BIL

1E000

밊 C

ŋ

9

ARCHIVE COPY DO NOT LOAN

Cy !

DYNAMIC TESTS OF A 10-DEG CONE HAVING THREE ANGULAR DEGREES OF FREEDOM AT MACH 8

L. K. Ward, Jr., and A. C. Mansfield

ARO, Inc.

September 1969 This document has been approved for public releas liam C. Cole.

 \cdot its distribution is unlimited. h

This document is subject to special export controls and each ransmittal to foreign governments or foreign nationals may be made only with prior approval of tomic Energy Commission, Albuquerque Operations Office, P. O. Box 5400, Albuquerque, New Mexico 87115.

VON KÁRMÁN GAS DYNAMICS FACILITY ARNOLD ENGINEERING DEVELOPMENT CENTER AIR FORCE SYSTEMS COMMAND **ARNOLD AIR FORCE STATION, TENNESSEE**

PROPERTY OF U. S. AIR FORCE MACC DED. MPY F40300 - 60 - 0 - 0201



When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

DYNAMIC TESTS OF A 10-DEG CONE HAVING THREE ANGULAR DEGREES OF FREEDOM AT. MACH 8

L. K. Ward, Jr., and A. C. Mansfield ARO, Inc.

This document has been approved for public release its distribution is unlimited. Per AF Letter affair 3 Jan. 75 Dissiel cultured.

This document is subject to special export controls and each transmittal to foreign governments or foreign pationals may be made only with prior approval of Atomic Energy Commission, Albuquerque Operations Office, P.O. Box 5400, Albuquerque, New Mexico 87115.

FOREWORD

The work reported herein was sponsored by the Sandia Corporation, Sandia Base, Albuquerque, New Mexico, under authority of the Atomic Energy Commission (AEC) Order Number AL 67-255, Sub Order 012, and Air Force Systems Command (AFSC) Program 921D.

The results of tests presented were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), AFSC, Arnold Air Force Station, Tennessee, under Contract F40600-69-C-0001. The test was conducted on March 27, 1969, under ARO Project Number VB1892, and the manuscript was submitted for publication on June 6, 1969.

Information in this report is embargoed under the Department of State International Traffic in Arms Regulations. This report may be released to foreign governments by departments or agencies of the U. S Government subject to approval of the Atomic Energy Commission, Albuquerque, New Mexico, or higher authority. Private individuals or firms require a Department of State export license.

This technical report has been reviewed and is approved.

Eugene C. Fletcher Lt Colonel, USAF AF Representative, VKF Directorate of Test Roy R. Croy, Jr. Colonel, USAF Director of Test

Per, AF litter 5 It'd 23 an "Elleane O. Date. This document has been approved for public release ite distribution is unlimited. A

ABSTRACT

Dynamic stability data were obtained on a slightly blunted 10-deg half-angle cone at Mach number 8. The tests were conducted using a unique balance system which allowed the model to have three angular degrees of freedom. Both a symmetrical model and a model having compound configurational asymmetries were tested at free-stream Reynolds numbers, based on model length, of from 1.61 x 10⁶ to 2.95×10^{6} . Data obtained on the symmetrical model at roll rates up to 300 rev/min showed the damping-in-pitch derivatives to be nearly constant with roll rate.

This document has been approved for public release, the 75 its distribution is unlimited. The AF Jun 75

This document is subject to special export controls and each transmittal to foreign governments or fereign nationals may be made only with prior approval of Atomic Energy Commission, Abuquerque Operations Office, P. O. Box 5400, Albuquerque, New Mexico 87115.

•

CONTENTS

		Page
	ABSTRACT	iii
	NOMENCLATURE	vi
I.	INTRODUCTION	1
II.	APPARATUS	
	2.1 Three-Degree-of-Freedom Dynamic Balance	3
	2.2 Model	3
	2.3 Wind Tunnel	4
ш.	PROCEDURE	
	3.1 Tunnel Tests	6
	3.2 Data Reduction	6
IV.	RESULTS AND DISCUSSION	8
v.	CONCLUSIONS.	18
	REFERENCES	18

ILLUSTRATIONS

.

Figure

.

.

.

1.	Coordinate Systems	1
2.	Sketch of the Model	2
3.	Balance Assembly	4
4.	Photograph of the Model	5
5.	Typical Motion Patterns from Configuration 1, $M_{\infty} = 7.9$, Res = 1.61 x 10 ⁶	
	a. $P \approx 0$	9
	b. $P = 23 \text{ rpm}$	10
	c. $P = 126 \text{ rpm} \dots \dots$	11
	d. $P = 2.14 \text{ rpm}$	1 2
	e. $P = 271 \text{ rpm} \dots \dots$	13
	f. $P = 225 \text{ rpm}$	14
	g. $P = 313 \text{ rpm}$	15
	h. $P = 236 \text{ rpm}$	16
6.	Static and Dynamic Derivatives as a Function of $Pd/2V_{\infty}$, Configuration 1, Mean Oscillation Ampli-	
	tude ≈ 5 deg	17

•

TABLE

																Page
I.	Test Conditions	•	•	•	•	•	•	•	•		•	•	•	•		6

NOMENCLATURE

А	Reference area (model base area)
с _М	Pitching-moment coefficient of a model which has triagonal or greater symmetry (independent of model roll orientation)
$c_{Mp\alpha}$	$C_{Mp\alpha} = C_{mp\beta} = C_{np\alpha}$, Magnus-moment coefficient
$\mathbf{C}_{\mathbf{M}_{\mathbf{q}}}$	$C_{Mq} = C_{mq} = C_{n_r}$, damping-in-pitch derivative coefficient
$C_{M_{\alpha}}$	$C_{M_{\alpha}} = C_{m_{\alpha}} = -C_{n_{\beta}}$, slope of the pitching-moment coefficient curve
$\mathrm{C}_{\mathbf{M}_{oldsymbol{lpha}}}$	$C_{M_{\alpha}} = C_{m_{\alpha}} = -C_{n_{\beta}}$, damping-in-pitch derivative coefficient
C _m	Pitching-moment coefficient, pitching moment/ $q_{\omega}^{}Ad$
$c_{mp\beta}$	$\partial^2 C_m / \partial (Pd/2V_w) \partial \beta$
Cmq	$\partial C_{m} / \partial (qd/2V_{\omega})$
$C_{m_{\alpha}}$	$\partial C_m / \partial \alpha$
$c_{m_{\alpha}}$	$\partial C_m / \partial (\dot{\alpha} d / 2V_{\omega})$
c _n	Yawing-moment coefficient, yawing moment/ q_{ω}^{Ad}
$C_{np\alpha}$	$\partial^2 C_n / \partial (Pd/2V_w) \partial \alpha$
C_{n_r}	$\partial C_n / \partial (rd/2V_{\omega})$
Cnβ	∂ C _n / ∂ β
Cnβ	$\partial C_n / \partial (\dot{\beta} d / 2V_{\omega})$
đ	Model base diameter
I	Transverse moment of inertia
I_X	Axial moment of inertia
[·]	Nutation, precession, and trim complex modal vectors

L	Model length, 27.98 in.
$\mathbf{M}_{\mathbf{\omega}}$	Free-stream Mach number
Р	Roll rate
q	Pitch rate
q _∞	Free-stream dynamic pressure
Re _l	Free-stream Reynolds number based on model length
r	Yaw rate
r_n/r_b	Ratio of model nose radius to base radius
t	Time
V _∞	Free-stream velocity
XYZ	Body coordinates (Fig. 2)
	Nonrolling body coordinates (Fig. 2)
$\mathbf{X}_{\mathbf{T}}\mathbf{Y}_{\mathbf{T}}\mathbf{Z}_{\mathbf{T}}$	Tunnel fixed coordinates (Fig. 2)
z _{cg}	Displacement of the model center of gravity from the axis of symmetry along the Z axis (Fig. 3)
Θ, Ψ, Φ	Angles of pitch, yaw, and roll (Fig. 1)
$\lambda_{n, p}$	Nutation and precession damping rates
ζ.uγ	Complex angle of attack $(\Theta + i\Psi)$
ω _{n, p}	Nutation and precession angular circular frequencies ($\omega_{trim} = \dot{\Phi}$)

SUBSCRIPTS

٤.

•

•

E	Effective values	
0	Quantity at reference condition	$(\tilde{\xi} = 0)$

SUPERSCRIPTS

• ,••	First and second derivatives with respect to time
~	Complex quantities

A Relative to nonrolling coordinates

.

-

SECTION I

Research is being conducted by the Sandia Corporation to study the dynamic behavior of a slightly blunted $(r_n/r_b = 0.0156)$ 10-deg half-angle cone. The research includes computer studies of six-degree-of-freedom motion, the present wind tunnel test program, and a full-scale flight test program.

The purpose of the present wind tunnel tests was to investigate the dynamic behavior of a conical model having three angular degrees of freedom. Both a symmetrical model and a model having compound asymmetries were tested using the von Karman Gas Dynamics Facility (VKF) three-degree-of-freedom dynamic balance (Ref. 1). The compound asymmetries were obtained by offsetting the balance pivot point from the model centerline to a point in the XZ plane (See Figs. 1 and 2) and additionally rotating the principal inertia axes in the XY plane.



Fig. 1 Coordinate Systems



XYZ Principal Axis of Configuration 1

X'Y'Z' Principal Axis of Configuration 2

All Dimensions in Inches

N







The test was conducted in the 50-in.-diam tunnel B (Gas Dynamic Wind Tunnel, Hypersonic (B)) of the VKF at a nominal free-stream Mach number of 8 and at free-stream Reynolds numbers, based on model length, of 2.92×10^6 and 1.61×10^6 .

SECTION II

2.1 THREE-DEGREE-OF-FREEDOM DYNAMIC BALANCE

A sketch of the balance assembly is shown in Fig. 3. The balance consists of a spherical gas bearing pivot, a three-axis variable reluctance angular transducer, a model release mechanism, and a model locking device. The spherical gas bearing provides a near-frictionless pivot which is desirable for dynamic stability testing at hypersonic speeds where it is necessary to minimize tare damping. The variable reluctance angular transducers provide continuous analog signals proportional to the angular displacements Θ and Ψ of the nonrolling axes (Fig. 1) and provide roll rate data. Models can be released from an initally pitched position with a yaw rate using the displacement arm and arm lock (Fig. 3). Both these initial conditions can be varied. The rotating arms are used to lock the model at zero angle of attack. The turbine and air jets are used to increase or decrease model roll rate when the model is in the locked position. These same air jets, when pulsed together, may be used to induce angular motion. A more detailed description of the balance system may be found in Ref. 1.

2.2 MODEL

The conical model (Figs. 2 and 4) was fabricated by the Sandia Corporation according to specifications supplied by the VKF. The model had a 10-in. base diameter, a 10-deg half-angle, and a nose-tobase bluntness ratio (r_n/r_b) of 0.0156. Provisions were made to add ballast fore and aft of the pivot point to allow both static and dynamic balancing. A sketch of the model (Fig. 2) shows that the model pivot point was located both on the centerline for Configuration 1 ($z_{cg}/d = 0$) and 0.100 in. off of the centerline ($z_{cg}/d = 0.01$) in the Z direction for Configuration 2 and at stations 55 percent aft from the model nose ($x_{cg}/\ell = 0.55$) for both configurations. These positions denote the location of the balance pivot point and, since the center-of-gravity of the model-balance system was also positioned at $x_{cg}/\ell = 0.55$, are henceforth termed the model center-of-gravity positions. Additionally, Configuration 2 had the principal inertia axes tilted approximately 0.5 deg in the body fixed XY plane as shown in Fig. 2. This axes tilt along with the offset center of gravity provided the compound configurational asymmetries.



Fig. 3 Balance Assembly

2.3 WIND TUNNEL

Tunnel B is a continuous, closed-circuit, variable density wind tunnel with an axisymmetric contoured nozzle and a 50-in.-diam test section. The tunnel can be operated at a nominal Mach number of 6 or 8 at stagnation pressures from 20 to 300 and 50 to 900 psia, respectively, at stagnation temperatures up to 1350°R. The model may be injected into the tunnel for a test run and then retracted for model cooling or model changes without interrupting the tunnel flow. A description of the tunnel may be found in Ref. 2.



Fig, 4 Photograph of the Model

SECTION III PROCEDURE

3.1 TUNNEL TESTS

A typical test run procedure was to inject the model into the test section tank and release it at the required initial conditions. After the desired amount of data had been obtained, the model was locked and retracted into the test section tank. At this point the model was cooled internally by directing cooling air on the model-balancing mounting bulkhead and externally by the standard test section tank model nose cooling system.

During the data-taking interval the analog signals, provided by the angular transducers, are simultaneously recorded on an analog tape and input directly to an analog-to-digital converter for storage on magnetic tape. The digital data are then input to the VKF digital computer for final data reduction. A summary of the test conditions is given in Table I.

			Wind I	unnel Te	st Conditio	ns		
Configuration No.	M_	Reg x 10	0-6	Stilling C Pressure	hamber S c, psia T	tilling Chamber emperature, °R	q _o , psia	V _o , ft/sec
1 2	7.90 7.95	1.61 2.95		125 250	i)	1170 1235	87.8 169.9	3606 3709
			V	lodel Par	ameters			
Configui	ation No.	xcg/l	z _{cg} /d	r_n/r_b	IX, slug-	ft^2 Iy, slug-ft ²	IZ, slug	-ft ²
	1 2	0,55 0,55	0 0.01	0.0156 0.0156	0.0416 0.0464	0.2686 0.2874	0,268 0,287	6 7

TABLE I TEST CONDITIONS

3.2 DATA REDUCTION

The data were reduced using the linear tricyclic theory in nonrolling coordinates as developed originally by Nicolaides in Ref. 3. The equation of a model suspended in an airstream and restricted to three angular degrees of freedom about a point fixed in space is noted as

$$\ddot{\tilde{\xi}} + [G + iH]\dot{\tilde{\xi}} + [J + iK]\tilde{\xi} = Le^{iPt}$$
(1)

where

$$G = -\frac{q_{\infty} Ad^{2}}{2 V_{\infty} I} (C_{M_{q}} + C_{M_{\alpha}^{*}})$$

$$H = -\frac{I_{x}}{I} P$$

$$J = -\frac{q_{\infty} Ad}{I} C_{M_{\alpha}}$$

$$K = -\frac{q_{\infty} Ad^{2}}{2 V_{\infty} I} C_{M_{p\alpha}} P$$

$$.$$

$$L = \frac{i q_{\infty} Ad}{I} (C_{m_{o}} + i C_{n_{o}})$$

$$i = \sqrt{-1}$$

The tricyclic solution to Eq. (1) is given in Ref. 3 as

$$\tilde{\xi} = \tilde{K}_{n} e^{(\lambda_{n} + i\omega_{n})t} - \tilde{K}_{p} e^{(\lambda_{p} + i\omega_{p})t} + \tilde{K}_{t} e^{iPt}$$
(2)*

where

$$K_{n} = \frac{\dot{\tilde{\xi}} - (\lambda_{p} - i\omega_{p}) (\tilde{\xi}_{o} - K_{t})}{\lambda_{n} - \lambda_{p} + i (\omega_{n} - \omega_{p})}$$
$$K_{p} = \frac{\dot{\tilde{\xi}} - (\lambda_{n} - i\omega_{n}) (\tilde{\xi}_{o} - K_{t})}{\lambda_{p} - \lambda_{n} + i (\omega_{p} - \omega_{n})}$$

^{*}The subscripts n and p, denoting nutation and precession, are used only as a convenient notation. The nutation arm is identified after fitting the data as the arm (K) having the largest absolute frequency $|(|\omega_n| > |\omega_p|)$ and the same rotational direction as the roll rate.

$$K_{t} = \frac{L}{(P - \omega_{n}) (P - \omega_{p}) + \lambda_{n} \lambda_{p} + i [\lambda_{n} (P - |\omega_{p}) + \lambda_{p} (P - \omega_{n})]}$$

$$\lambda_{n,p} \pm i \omega_{n,p} = - \frac{(G + iH) \pm \sqrt{G^2 - i2GH - H^2 - 4(J - iK)}}{2}$$

The model damping rates (λ_n, λ_p) and angular frequencies (ω_n, ω_p) are obtained by fitting Eq. (2) plus a constant complex vector to the model displacement-time history using a least-squares differential correction method. The solution is "fitted" over short overlapping segments of the displacement-time history. Once the model damping rates and frequencies have been determined, the aerodynamic coefficients may be obtained using the following relationships:

$$C_{M_q} + C_{M_{\alpha}} = \frac{2 V_{\infty} I}{q_{\infty} A d^2} \cdot (\lambda_n + \lambda_p)$$

$$C_{M_{\alpha}} = \frac{1}{q_{\infty} A d^2} (\omega_n \omega_p - \lambda_n \lambda_p)$$

$$C_{M_{p\alpha}} = - \frac{2 V_{\infty} I}{q_{\infty} A d^2} - \frac{1}{P} (\lambda_n \omega_p + \lambda_p \omega_n)$$

SECTION IV RESULTS AND DISCUSSION

All data were obtained at a nominal Mach number of 8 (Table I). Only representative data obtained from the symmetrical model (Configuration 1) are presented; the analysis of the results obtained on Configuration 2 will be published at a later date by the Sandia Corporation.

The tests were conducted at Reynolds numbers which were low enough to provide a laminar boundary layer over the full length of the model. Previous experience with conical models (Refs. 4 and 5) at hypersonic speeds has shown the damping derivatives to be higher when the model boundary layer is partially laminar or partially turbulent than when a laminar or near fully turbulent boundary layer exists on the model. Data obtained under the latter conditions are thought to be representative of a larger portion of the vehicle reentry trajectory. Typical motion patterns obtained from the symmetrical model for various spin rates are shown in Fig. 5. These data indicate the uniformity with which the motion may be defined as the symbols represent only every tenth data point obtained.



a. P \approx 0 Fig. 5 Typical Motion Patterns from Configuration 1, M $_{\infty}~=~7.9,~Re\ell~=~1.61~\times~10^6$

9



b. P = 23 rpm Fig. 5 Continued

AEDC-TR-69-151



يلغم ا

c. P = 126 rpm Fig. 5 Continued



d. P = 214 rpm Fig. 5 Continued

•

.



•

.

e. P = 271 rpm Fig. 5 Continued



f. P = 225 rpm Fig. 5 Continued



g. P = 313 rpm Fig. 5 Continued



h. P = 236 rpm Fig. 5 Concluded

The static and dynamic derivatives $(C_{M_{\alpha}} \text{ and } C_{M_{\alpha}} + C_{M_{\alpha}})$ are shown in Fig. 6 as a function of $Pd/2V_{\infty}$ (also P in rev/min). The derivatives were evaluated for a mean oscillation amplitude of 5 deg. No effect of $Pd/2V_{\infty}$ was noted for $C_{M_{\alpha}}$; however, as may be seen in the figure, $C_{M_{\alpha}} + C_{M_{\alpha}}$ appeared to decrease slightly with increasing $Pd/2V_{\infty}$. The data are compared with the unsteady flow field theory of Brong (Ref. 6). The experimental values obtained for $C_{M_{\alpha}}$ agree quite well with the theory (Brongs' results yield the same value as the Stone-Kopal results). The damping derivatives are, however, somewhat lower than the theory.



Fig. 6 Static and Dynamic Derivatives os o Function of Pd/2V∞, Configuration 1, Mean Oscillation Amplitude ≈ 5 deg

SECTION V CONCLUSIONS

Wind tunnel tests at $M_{\infty} = 8$ were conducted using a dynamic balance having three angular degrees of freedom. Data obtained on a symmetrical 10-deg half-angle cone $(r_n/r_b = 0.0156, x_{Cg}/\ell = 0.55)$ at $\text{Re}_{\ell} = 1.16 \times 10^6$ showed the static stability parameter, $C_{M\alpha}$, to be invariant with model roll rate (0 < P < 313 rev/min) and the damping derivatives, $C_{Mq} + C_{M\alpha}$, to decrease slightly with increasing roll rate.

REFERENCES

- Ward, L. K., Jr. and Hodapp, A. E., Jr. "A Three-Degreeof-Freedom Dynamic Stability Balance for Use in the VKF Continuous Flow Hypersonic Tunnels (M_m = 6 through 12)." AEDC-TR-68-62 (AD832200), May 1968.
- <u>Test Facilities Handbook</u> (Seventh Edition). "von Karman Gas Dynamics Facility, Vol. 4." Arnold Engineering Development Center, July 1968.
- Nicolaides, J. D. "On the Free-Flight Motion of Missiles Having Slight Configurational Asymmetries." BRL Report 858 (AD26405), June 1953.
- Ward, L. K. "Influence of Boundary Layer Transition on Dynamic Stability at Hypersonic Speeds." Transactions of the Second Technical Workshop on Dynamic Stability Testing, Arnold Engineering Development Center, Vol. II (AD472298), April 20-22, 1965.
- 5. Ward, L. K. and Uselton, B. L. "Dynamic Stability Results for Sharp and Blunted 10-Deg Cones at Hypersonic Speeds." AEDC-TR-68-277 (AD845053), December 1968.
- Brong, E. A. "The Unsteady Flow Field about a Right Circular Cone in Unsteady Flight." AFFDL-TDR-64-148, January 1967.

Security Classification		-					
DOCUMENT CONT	ROL DATA - R	& D	overall report is cleasified.				
Arnold Engineering Development Cent	er	2. REPORT SE	CURITY CLASSIFICATION NCLASSIFIED				
ARO, Inc., Operating Contractor Arnold Air Force Station, Tennessee	,	25. GROUP	N/A				
3. REPORT TITLE DYNAMIC TESTS OF A 10-DEG CONE HAVI AT MACH 8	NG THREE A	NGULAR D	EGREES OF FREEDOM				
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) Final Report March 27, 1969							
5. AUTHOR(S) (First name, middle initial, last name)			······································				
L. K. Ward, Jr., and A. C. Mansfiel	d, ARO, In	с.					
6. REPORT DATE Sentember 1969	74. TOTAL NO. 01	FPAGES	7b. NO. OF REFS				
84. CONTRACT OF GRANT NO. F40600-69-C-0001	94. ORIGINATOR	REPORT NUM	0 BER(\$)				
AFSC Program 921D		AEDC-T	R-69-151				
AEC Order AL67-255, Jub Order 012	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A						
10. DISTRIBUTION STATEMENT This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Atomic Energy Commission, Albuquerque Opera- tions Office, P. O. Box 5400, Albuquerque, New Mexico 87115. 11 SUPPLEMENTARY NOTES 12 SPONSORING MILITARY ACTIVITY Atomic Energy Commission P. O. Pox 5400							
	Albuquerque, New México 87115						
Dynamic stability data were obtained on a slightly blunted 10-deg half-angle cone at Mach number 8. The tests were conducted using a unique balance system which allowed the model to have three angular degrees of freedom. Both a symmetrical model and a model having com- pound configurational asymmetries were tested at free-stream Reynolds numbers, based on model length, of from 1.61×10^6 to 2.95×10^6 . Data obtained on the symmetrical model at roll rated up to 300 rev/min showed the damping-in-pitch derivatives to be nearly constant with roll rate.							
This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of Atomic Energy Commission, Albuquerque Operations Office, P. O. Box 5400, Albuquerque, New Mexico 87115. This document has been approved for public release its distribution is unlimited. The AF Letter dtd its distribution is unlimited. The AF Letter dtd							

UNCLASSIFIED

Security Classification	LIN		LIN			
KEY WORDS	ROLE	WT	ROLE	WT	ROLE	WT
Wind Tunnel tests hypersonic flow cones dynamic stability characteristics						
1. Cones Stati 2 " Hyp	lite	7 nie	F	la	Ī	
1-2,				·		
AFSC Vradic AF8 Tym						

Security Classification