



2007 Joint Service Power Expo

“Power & Energy Independence for Warfighters”

24 – 26 April 2007

San Diego, CA

Table of Contents

Agenda

TUESDAY, 24 APRIL 2007

OIF – Stories From the Field – Lessons Learned

- A Few OIF Power Observations, *LtCol K. Jansen*
- Battlefield Power for the Warfighter: Lessons for the Development Community, *Dr. Ken Zemach*, Ph. D., Lion Cells, Inc.
- OIF 5-7 Commercial Power Generators, *GySgt G.V. Yanez*
- Doing Business with the Government, *Ms Yvonne Bova & Ms Shekela Hutchinson*
- Doing Business with the Marine Corps, *Ms. Shekela Hutchinson*
- Marine Corps Systems Command Purchasing & Evaluation of Power Items, *Mr. Michael Gallagher*
- Power Optimizer for the Warfighter’s Energy Requirements “Battery Calculator”, *Mr. Don Brockel*
- Power Optimizer for the Warfighter Energy Requirements, *Mr. Don Brockel*
- Planning and Decision Support for Enhanced Power and Energy Management through Seminar Gaming and Analysis, *Mr. Gordon Steward*
- Future Trends and Thrust for Army Manportable Power Sources – CERDEC, *Mr. Michael Brundage*
- Advancements in Navy and USMC Power Systems – NSWC Carderock, *Ms. Daphne Fuentevilla*
- Battery Technical Working Group, *Mr. Marc D. Gietter*
- Marine Corps Mobile Electric Power Distribution System Replacement , *MSgt Fred McCue*
- The Case for Smart/Safe Power Management and Distribution for the Military, *Mr. Rick Silva*

WEDNESDAY, 25 APRIL 2007

- Mobile Electric Power for Today and Tomorrow, *Mr. Paul Richard*
- Common Sense Approach to the Selection, Design/Fabrication, & Testing of Safe Operational Power Sources, *Mr. Robert Byrnes, Sr.*
- Fighter/EW/Helo/Patrol Arc Fault Circuit Breaker Development, *Ms Susan Waggoner*
- Large-sized Li-ion battery module for hybrid powered energy systems, *Mr. William A Moll*
- Communications Power Sources and Vehicle Battery Maintenance, *Mr. Mike Bissonnette*
- Power Generation Lesson Learned OIF 5-07, *MSgt Dickson*
- Case Study – Reducing Premature Failure of Parts with Interactive Virtual Training for Generator Operators, *Mr. Erik Kaas*
- Lightweight 2-kW Generator with Integrated Starter Alternator (ISA), *Mr. Gregory Cole*
- Servicing Hawker Vehicle Batteries with Standard Battery Charging and Test Equipment, *Mr. Fred Krestik*
- Testing of COTS/NDI Products, *Mr. John O’Donnell*

Lunch Speaker:

“Warfighting in a Climate Warming World – Implications for U.S. National Security Policies”, *Honorable Philip Coyle*, Senior Advisor, World Security Institute

- On Board Vehicle Power, *Mr. Michael Gallagher*
- On-Board Vehicle Power Briefing & Way Forward, *Dr. Jim Cross*
- Onboard Vehicle Power: Talking Points on Emerging Requirements, *Mr. Tim Raney*
- Marine Corps On-Board Vehicle Power Systems for Legacy Military Vehicles, *Mr. Michael Gallagher*
- Tactical Generators, *MSgt Fred McCue*
- AutoDISE, *MSgt Fred McCue*
- On Board Vehicle Power, *Mr. Michael Gallagher*
- Electric Drive Approach to Mobile Power Platforms, *Mr. Nader Nasr*
- Video *NATC Proving Grounds*
- Video *MTVR BVP*
- Power-Managed HMMWV Demonstrator, *Mr. Stephen Cortese*

Workshop Battery Technical Manuals and Milspecs, *Ms Susan Waggoner*

- Solar Power Adapters and Deployable and Renewable Alternative Energy Module, *Major David Morris*
- Tactical Power Systems, *Mr. Tom Lederle*
- Self-Generated Field Power Sources, *Mr. Albert Hartman*

THURSDAY, 26 APRIL 2007

- USMC Family of Environmental Control Equipment, *Major David C. Morris*
- Integrated Trailer-ECU-Generator (ITEG), *Major David C. Morris*
- Solving power supply obsolescence, reliability, and power density issues by advances in power electronics technology, *Mr. Richard Sidley*
- Advances in Chemical Hydride Based PEM Fuel Cells for Portable Power Applications, *Shailesh Shah*
- Advances in Chemical Hydride Based PEM Fuel Cells for Portable Power Applications, *Mr. Andy Wallace*
 - Video *Customer Broadcast*
 - Video *Customer UAV*
 - Video *Customer UGV*
- Data Systems for Enhanced Power and Energy Management, *Mr. John Adams*
- Back up Slides - Data Systems for Enhanced Power and Energy Management, Part 2 *Mr. John Adams*
- Portable Power Sources: One Size Fits None – Protonex Technology Corp, *Mr. Phil Robinson*
- Solid Oxide Fuel Cell Power Systems for Small UAV's, *Mr. Timothy LaBreche*
 - Video *UAV Fuel Cell Flight with Timer*
 - Video *11.5 Hr Ground Test with Timer*
 - Video *BOP Buner UAV*
 - Video *Short Crash Loop*
- Portable, JP-8 fueled battery charger for remote operation and portable solid oxide fuel cell systems, *Ms. Christine Martin*

Monday, April 23, 2007

1:00 p.m. - 5:00 p.m.

Exhibitor Move-in

Tuesday, April 24, 2007

7:30 a.m. - 8:30 a.m.

Continental Breakfast

8:30:00 a.m. - 9:30 a.m.

General Session	
Admin Remarks	
Color Guard	
Welcoming Address	
Keynote Speaker	Major General Stephen T. Johnson

9:30 a.m. - 5:00 p.m.

Exhibit Hall Open

9:30 a.m. - 10:00 a.m.

BREAK in Exhibit Hall

10:00 a.m. - 11:30 a.m.

OIF - Stories from the Field - Lessons Learned	
LtCol K. Jansen	A Few OIF Power Observations
Ken Zemach	Battlefield Power for the Warfighter Lessons for the Development Community
GySgt R.L. Gardner	9th COMM BN ENGINEERS OIF LESSONS LEARNED
GySgt G.V. Yanez	OIF 5-7 Commercial Power Generators

11:30 a.m. - 1:30 p.m.

LUNCH

1:30 p.m. - 3:00 p.m.

Session 1 - Chair: Joanne Martin joanne.martin@usmc.mil Doing Business with the Government - Yvonne Hicks & Shekela Hutchinson Doing Business with the Marine Corps - Shekela Hutchinson Marine Corps Systems Command Purchasing & Evaluation of Power Items - Michael Gallagher	Session 2 - Chair: Don Brockel Donald.Brockel@us.army.mil Determining the Right Type and Quantity of a Power Source - US Army CERDEC/LRC, Don Brockel (#4931) Future of US Navy Electromotive Power Logistics - NAVAIR, LCDR Davis Spurlock (#4841) Planning and Decision Support for Enhanced Power and Energy Management - MTS Technologies, Inc., Stephen Sullivan (#4823)
---	--

3:00 p.m. - 3:45 p.m.

BREAK in Exhibit Hall

3:45 p.m. - 5:15 p.m.

Session 3 - Chair: Mike Brundage Michael.Brundage1@us.army.mil Future Trends and Thrust for Army Manportable Power Sources - CERDEC, Mike Brundage (#4930) Advancements in Navy and USMC Power Systems - NSWC Carderock, Justin Govar (#4902) DoD Battery Technical Working Group - US Army roadmaps and databases CERDEC, Marc Gietter (#4929)	Session 4 - Chair: Bob McKenzie robert.h.mckenzie@usmc.mil Marine Corps Mobile Electric Power Distribution System Replacement - USMC, MSgt Fred McCue (#4649) The Case for Smart/Safe Power Management and Distribution for the Military - Custom Manufacturing & Engineering (CME), Rick Silva (#4835 & 4839) Fuel reduction solutions for deployment of mobile electric power systems - Oerlikon Contraves, Philippe Bisailon Eng. MEM (#4805)
--	---

6:00 p.m. - 8:00 p.m.

Conference Reception in Exhibit Hall

Wednesday, April 25, 2007

7:00 a.m. - 5:30 p.m.

Exhibit Hall Open

7:00 a.m. - 8:00 a.m.

Continental Breakfast in Exhibit Hall

8:00 a.m. - 9:30 a.m.

Session 5 - Chair: Maj Daniels regina.daniels@us.army.mil
Mobile Electric Power for Today and Tomorrow - DoD Project Manager Mobile Electric Power, Paul Richard (#4829)

Session 6 - Chair: Julie Banner julie.banner@navy.mil
Ultralast Chinese Li/FeS ₂ Cells - David Hale Associates, Inc., Robert Byrnes Sr. (#4860)
High Voltage Systems: Do's and Don'ts - Naval Surface Warfare Center Crane, Susan Waggoner (#4918)
Large-sized Li-ion battery module for hybrid powered energy systems - GS Yuasa Corp., Koichi Nishiyama (#4690)

Session 7 - Chair: Mike Bissonnette mbissonnette@mkisystems.com
MILITARY TRAINING
Communications power sources & vehicle battery maintenance

9:30 a.m. - 10:15 a.m.

BREAK in Exhibit Hall

10:15 a.m. - 11:45 a.m.

Session 8 - Chair: Maj Daniels regina.daniels@us.army.mil
Mobile Electric Power Lessons Learned in the Global War on Terror - USMC, Robert McKenzie III (#4647)
Case Study - Reducing Premature Failure of Parts with Interactive Virtual Training for Generator Operators - NGRain Corp., Erik Kaas (#4840)
Lightweight 2-kW Generator with Electric Start and Voltage Regulation - Mainstream Engineering Corp., Gregory Cole (#4884)

Session 9 - Chair: Don Brockel Donald.Brockel@us.army.mil
Servicing Hawker Vehicle Batteries with Standard Battery Charging and Test Equipment - US Army, TARDEC, Fred Krestik (#4672)
Battery Maintenance and Management - Pulsetech Products Corp., Mark Abelson (#4818)
Hybrid Li-ion/VRLA Battery for Silent Watch - Modular Energy Devices, Stephen Eaves (#4668)

Session 10 - John O'Donnell john.h.odonnell@usmc.mil
Testing of COTS/NDI products (Joint presentation) (#4882)

11:45 a.m. - 1:45 p.m.

LUNCH
Speaker - Hon. Philip E. Coyle III

1:45 p.m. - 3:15 p.m.

Session 11 - Chair: Mike Gallagher michael.a.gallagher@usmc.mil
DOD Efforts in On-Board Vehicle Power (Joint presentation) (#4639)

Session 12 - Chair: Marc Gietter marc.d.gietter@us.army.mil
Research and Development, GEN4 Zinc Air Battery Technology - Electric Fuel Battery Corp., Darrel Morris (#4830)
Flexible Hybrid Power Architecture and Evaluation of Multiple Sources Under Load - US Air Force Research Labs, Lt Joshua Johnson (#4837)
Power Surety for the Long War - US Army, Rapid Equipping Force Power Surety Branch, Daniel Nolan III (#4662)

Session 13 - Chair: CWO5 Good pamela.good@usmc.mil
MILITARY TRAINING
Generators & AUTODISE

3:15 p.m. - 4:00 p.m.

BREAK in Exhibit Hall

4:00 p.m. - 5:30 p.m.

Session 14 - Chair: Mike Gallagher michael.a.gallagher@usmc.mil
Oshkosh Truck's electric drive approach to mobile power platforms - Oshkosh Truck Corp., Nader Nasr (#4822)
30 kW On-Board Vehicle Power for the HMMWV - ePower LLC, William Henrickson (#4700)

Session 15 - Chair: Sue Waggoner susan.waggoner@navy.mil
Workshop - Battery Documents Navy Aircraft and Army C/E - US Navy & US Army, Susan Waggoner & Pat Lyman (#4917)

Session 16 - Chair: Jonathan Hernandez jhernandez@fbiacademy.edu
Solar Power Adapters and Deployable and Renewable Energy Alternative Module - Marine Corps Systems Comand, Maj David Morris, (#4673 & 4686)
Need for Tactical Off-Grid Solar Power System - NEST Energy Systems, Tom Lederle (#4940)

Self-Generated Field Power Sources - High
Tide, Albert Hartman (#4807)

Thursday, April 26, 2007

7:00 a.m. - 12:00 p.m.

Exhibit Hall Open

7:00 a.m. - 8:00 a.m.

Continental Breakfast in Exhibit Hall

8:00 a.m. - 9:30 a.m.

Session 17 - Chair: Maj Daniels regina.daniels@us.army.mil
The Family of Environmental Control Equipment - Marine Corps Systems Command, MSgt Teresa Terry (#4689)
Integrated Trailer, Environmental Control Unit, and Generator (ITEG) - Marine Corps Systems Command, Maj David Morris (#4674)
Solving power supply obsolescence, reliability, and power density issues by advances in power electronics technology. - Custom Manufacturing & Engineering, Richard Sidley (#4833)

Session 18 - Chair: Jonathan Hernandez jhernandez@fbiaacademy.edu
Moving Forward with Fuel Cells: Army CERDEC Development & Demonstration Progress - US Army, CERDEC, Elizabeth Bostic (#4684)
XX25 Reformed Methanol Fuel Cell for Portable Power Applications - UltraCell Corp., Ian Kaye (#4755)
Advances in Chemical Hydride Based PEM Fuel Cells for Portable Power Applications - Millennium Cell Inc., Shailesh Shah (#4877)

9:30 a.m. - 10:15 a.m.

BREAK in Exhibit Hall

10:15 a.m. - 12:00 p.m.

Session 19 - Chair: Sue Waggoner susan.waggoner@navy.mil
Data Systems for Enhanced Power and Energy Management - MTS Technologies, Inc., Zachary P. Hubbard (#4826)
Powering the Mobile Warfighter: One Size Fits None - Protonex Technology Corp., Phil Robinson (#4832)
The Next Level of Intelligent Power Management & Distribution - Energy Technologies, Inc., Tim Lowe (#4836)

Session 20 - Chair: Jonathan Hernandez jhernandez@fbiaacademy.edu
Durability and Performance issues of PEM Fuel Cell Systems for Portable Applications - Hampton University, Dr. Amir Hoshang Chegini (#4685)
Solid Oxide Fuel Cell Power Systems for Small UAVs - Adaptive Materials, Inc., Brad Clawson (#4838)
Military 3 kW Jet-Fueled Tactical Fuel Cell Generator - IdaTech, LLC, Eric Simpkins (#4706)
Portable, JP-8 fueled battery charger for remote operation and portable solid oxide fuel cell systems - Mesoscopic Devices, LLC, Christine Martin & Dr Jerry Martin (#4709 & 4710)

12:00 p.m.

Conference Adjourns

12:00 p.m. - 4:00 p.m.

Exhibitor Move-out

Battlefield Power for the Warfighter

Lessons for the Development Community

Ken Zemach, Ph.D.

Lion Cells, Inc.

April 2007



SF soldiers in theater ripping apart dozens of MBITR boxes to run them from BA-5590s



Actual operational power supply rigged by soldiers to run \$500,000 thermal sight in theater

BLUF

2 years of developing, deploying, and supporting technology in OIF and OEF



- **20% of successful technology deployment is the technology... 80% is logistics (materials, repair, training, support)**
- **Power is a large part of the logistics nightmare for many items... avoid proprietary solutions whenever possible**

Proprietary Batteries: Resupply/Charge

Cooling Vest for Mounted Operations



Viable technology solution but used proprietary battery:

- **Field use impaired by battery choice**
- **Reduced value for Warfighter, military, manufacturer**


Correct solution:

- **BB-2557 and/or BB-2590**
- **More utility, lower initial cost, lower long term cost, countless substitutes**



Proprietary Batteries: Logistics

ECM Device for Critical Application



Proprietary Batteries: Support

Robot

Proprietary
battery
problems

Unit cold calls
manufacturer

Manufacturer
calls us, we
contact unit

Travel from Baghdad
to Mosul (2 weeks)

Replace/update
batteries (2 days)

Travel back
(3 days)

...three days after
returning to Baghdad...

...unit calls:
CHARGER DIED

Move charger
through LNOs
(2 weeks)

Total Time ~ Six Weeks to support due to proprietary power system

Good News: Use the “Standards”



UAV uses standard mil batteries, HMMWV, and/or other sources to run both OCU and recharge lightweight aircraft batteries... best that could be done

Good News: Use the “Standards”



Both these robots run directly off of BB-390/2590 standard military batteries, saving battery and charger logistical nightmares.

Good News: Use the “Standards”



Unique split-body robot for rough terrain under vehicle inspection uses military standard BB-2847 batteries and military standard chargers.

Good News: Use the “Standards”

Run anything COTS from an x90



COTS:

- Cell phones
- Sat phones
- PDAs
- AA chargers
- Laptops
- Camcorders
- DVRs
- LCD monitors
- Surveillance cameras
- Loudspeakers
- Spotlights
- Dremel tool
- Etc.



Good News: Use the “Standards”

LRAS3: Developed for Mounted Units



VS.

No AC power supply was ever envisioned to be required in the initial fielding....

LRAS3: Developed for Mounted Units



...so soldiers were hacking together field expedient solutions. Left: HMMWV taken off line to run sight. Right: field rigged power supply. This is not the way!

**Two proposed solution approaches for the LRAS3...
Question: which approach is right?**

NEITHER

COTS Approach

- UK marine manufacturer
- \$2,700 each
- 1 month lead time



Military Solution

- US military manufacturer
- 9 -12 month lead time
- \$250k NRE
- \$5k+ each
- Meets strict equipment specs

vs.

Good News: Use the “Standards”

SSG D.W. of the 1/506th INF REGT wins with:



Moving to a “standard” 24V Power Supply:

- Saved 9+ months of R&D
- Saved over \$250k in NRE for development
- Saved over \$800k in power supply costs
- Avoided logistics/support issues for new custom equipment

Solar Battery Charging + UPS

Problem: what's the best way to power long term, remote sensors in theater?

- Lots of BA-5590s in parallel
- Several BA-8180s (Zn-Air) in parallel
- Solar UPS... Yes! (self operating, etc); modified military standard SP-4 to get there easily





Product Design and Fielding Issues

Why manufacturers should standardize and/or have the right adapters

- **It CAN be done, and it's not that hard.**
 - Examples: MARCbot, ODIS, Raven, LRAS3
- **For manufacturers:**
 - Reduces time to market, battlefield
 - Increases military acceptance
 - ? Reduces product cost ?
- **For Military:**
 - Increases standardization (a good thing)
 - Reduces logistics and support issues (HUGE)
- **Manufacturers (military and consumer) need:**
 - Directive AND understanding why
 - Help with how: recommended options, dimensions, sources, connectors, DC-DC converters, suppliers, etc.

Most power problems encountered in theater are OUR FAULT (incompatible / proprietary batteries, connectors, cables, etc), not because of the operational scenario.

Contact Info

Ken Zemach

Email: kzemach@alum.mit.edu

Useful Website: www.warfightersolutions.com

Export Power Developments

2007 Joint Service Power Expo

25 April 2007

**Presenter: Tom Trzaska
Manager, Advanced Programs**

**General Dynamics Land Systems
Muskegon Technical Center
604 Seminole Rd.
Muskegon, Michigan 49441
trzaskat@gdls.com
231.780.5815**

Agenda

- **Background**
- **Technical Objectives**
- **System Design**
- **Performance Testing**
- **Durability Testing**
- **Future Developments**

Background

- **GDLS and Magnet Motor GmbH Collaboration**
- **Robust Power Electronics Solutions**
 - **Electric Drive**
 - **Power Conditioning**
 - **Power Generation**
- **High Power Densities**
 - **Inverters to 13.8 kW/l**
 - **Bi-Directional DC/DC to 6 kW/l**



Power Generation and Management Experience

30 kW Export Power Unit

- **Developed Under RST-V Program with support of USMC, DARPA, ONR and GDLS**
- **Provide Power to UOC and Fire Finder Radar**
- **Goal to Provide Similar Capability to 805 and 813 Gensets**
- **Exploit Inherent Power Generation Capability of Series Electric Drive**




Targeted Applications



Replaced in Expeditionary Roles

Technical Objectives

- **Provide AC Power:**
 - **30kW 0.8Pf @ 60 Hz**
 - **10kW 0.8Pf @ 400 Hz**
 - **208/120VAC 3 Φ , 4 wire**
 - **Mil Std 1332 Class 2A/B**
- **Synchronize and Load Transfer**
- **131°F Operating Temp**
- **IEC 309, 100 amp connections**



Unit Installed on USMC/ONR/DARPA RST-V



Output Voltage Waveform

System Description

- High Density Solid State DC/AC Inverter System
- Commercial IGBT Based
- PWM Waveform Synthesis
- Three Modules for Adaptable Integration
- Dual Frequency Capability
- Water Cooled Inverter/Filter
- Growth to 50hz and 240/416 VAC output




ACC04 30 kW Inverter / Filter Unit



Interface and Control Panel


Summary Specifications

- **System Characteristics:**
 - ↗ **Input Voltage 300-800 VDC**
 - ↗ **Output: 120 / 208 VAC**
 - ↗ **Dual Frequency 60 / 400 Hz**
 - ↗ **WPG Cooled (10 l/min @ 70 °C)**
 - ↗ **Weight 110 kg**
 - ↗ **Volume 85 Liters**
 - ↗ **Voltage Regulation <2%**
 - ↗ **Frequency Regulation <1%**




30 kW Inverter/ Filter Module

System Block Diagram



Performance Predictions




Simulation of Synchronization Process to Grid Stabilization within 75 msec


- **Full Circuit and Control Model Refined and Validated through Lab and Field Testing**

Performance Testing

- Full Series Of Development Bench Tests Completed
- On Vehicle Lab Testing
 - Inverter / Vehicle Control Tuning
 - Power Quality
 - Load Cycling: Step Apply & Load Dump
 - Inductive Load Start
 - Short Circuit
 - Thermal Limits



Steady State Thermal Loading



Step Load

Field & Durability Testing

- **Durability Testing**
 - **Mixed Course Durability**
 - **2 hour Export Power Cycles Every 100 Miles**
 - **Over 275 hours operation**
 - **Reliability Database Established**
- **Technical & Durability Testing at APG**
 - **705 Testing**
 - **EMC**
 - **Durability Cycles**




RST-V with Export Power Units




Durability Load Test

Current Developments (Cont.)

- **Current System Being Applied to HMMWV**
- **Core Electronics, Software Repackaged**
- **High Density PM Generator Added to Provide Power Generation**
- **Low Impact 20/30 kW Retrofit Kit**



Block Diagram



20/30 kW Export Power Concept

Current Developments (Cont.)


- **Initiating Portability Study to Other Platforms**
- **Initial Focus on Select MRAP Candidates**
- **Scope of Effort:**
 - **Develop BTA Installation concept for each platform**
 - **Design Mod Kit including installation hardware**




Portability Study Candidates

Summary

- **GDLS / Magnet Motor Team Has Demonstrated 30kw Export Power System**
- **High Density System Reduces Impact to Host Vehicle**
- **Extending and Refining Design for Portable Application to Wide Range Of Vehicles**



Current Generation Remains in Test



Future Electronics Assembly

Hybrid Chemistry Li-ion/VRLA Battery for Silent Watch

Stephen Eaves

Scott Lichte

EnerSys/ModEnergy

Rev. C

The World's Largest Industrial Battery Company



- EnerSys manufactures, markets, and distributes batteries in three markets
 - Reserve Power
 - Motive Power
 - Aerospace & Defense
- Global leader
 - 25% share in the \$3.5 billion commercial market
 - Broadest product line in industry
- Leading worldwide presence
 - 21 manufacturing facilities in North America, Europe and Asia
 - 10,000 customers in over 100 countries
- Sales of over \$1.3 billion, about 7,550 employees

Lead-Acid Products

Reserve



Motive



Aerospace and Defense



Exide Products



PowerSafe Telecom Products



Armasafe, Hawker and Varta Products

DataSafe UPS Products

Exide, Hawker and General Products

The Armasafe Plus (A+) Battery



- 120Ah, 1225 CCA
- Drop-in Operation
- Thin Plate Pure Lead VRLA Technology
- 2X Cold Cranking Amps at -18°C and -40°C vs. 6T
- 10X Cycle Life vs. 6T
- Several years of field use
- Proven in the harshest environments
- Recovery using standard equipment

A+ Silent Watch Test

- 12 A+ Batteries installed in M1A2SEP tank
- 6 in NPS compartment
- 11.3 Hours of Silent Watch at 1350 Watts
- Followed by several starts on only 4 batteries

ModEnergy Lithium-ion Products

2.5kW for 5 Min. 48V – 19" Rack



67 to 160Ah, 48V, 23" Rack




16 to 220Ah, 14.8V

2.5kW, 5 to 20 Min. 48V



Li-ion Design Team Defense Experience



XSS-11 Satellite
Li-ion Battery Electronics



B2 Bomber
Li-ion Battery Electronics



Navy SEA JET - 1/4 Scale Destroyer
720 Hawker 40Ah VRLA Monoblocks



Advanced Seal Delivery System (ASDS)
>1000 cells Li-ion Electronics


Hybrid Chemistry Design Drivers

- Combine Lithium-ion and ArmaSafe+ Batteries
 - Mitigates technology insertion risk
 - A+ batteries ensure that vehicle will start
 - User may mix A+ and Li-ion as needed
 - Allows safer more compact design by off loading pulse power to A+
- Li-ion must closely match envelope of A+ battery
- Seamless operation on 28V Bus
- Bus Conforms to MIL-STD-1275D
- Derive guidance where applicable from MIL-PRF-32143


Hybrid Chemistry Design Drivers

- Utilize ModEnergy Redundant Array Architecture
 - Very high reliability numbers
 - Cell failure is isolated and does not disable battery
 - Uses mass produced, UL1642 approved cells
- Base design on COTS Li-ion modules
 - UL, UN Approvals
 - Cost and availability advantages
 - High level of quality from established production

28V Bus Architecture




Charging Under MIL-STD-1275



Li-ion Building Block


Capacity Option Code -C	Rated Capacity (Ah)	D Case Depth (In)	D Case Depth (mm)	Module Weight (Lbs)	Module Weight (kg)
28	28	4.075	103.5	6.66	3.03
38	38	4.875	123.8	8.25	3.75
47	47	5.675	144.1	9.84	4.47
56	56	6.475	164.5	11.44	5.20
66	66	7.275	184.8	13.03	5.92
75	75	8.075	205.1	14.62	6.65
85	85	8.875	225.4	16.22	7.37
94	94	9.675	245.7	17.81	8.10
103	103	10.475	266.1	19.41	8.82
113	113	11.275	286.4	21.00	9.55
122	122	12.075	306.7	22.59	10.27
132	132	12.875	327.0	24.19	10.99
141	141	13.675	347.3	25.78	11.72
150	150	14.475	367.7	27.37	12.44
160	160	15.275	388.0	28.97	13.17
169	169	16.075	408.3	30.56	13.89
179	179	16.875	428.6	32.15	14.62
188	188	17.675	448.9	33.75	15.34
197	197	18.475	469.3	35.34	16.06
207	207	19.275	489.6	36.94	16.79
216	216	20.075	509.9	38.53	17.51
226	226	20.875	530.2	40.12	18.24
235	235	21.675	550.5	41.72	18.96
244	244	22.475	570.9	43.31	19.69
254	254	23.275	591.2	44.90	20.41
263	263	24.075	611.5	46.50	21.14

11.1V, 103Ah, 8.8Kg





Design uses 3 modules with DC-DC converter. Equivalent to 125Ah at 24V considering 86% efficiency


Li-ion Performance Testing




14-160 Module, 40 Amp Discharge, 55 Deg. C




14-160 Module, 40 Amp Discharge, -30 Deg. C



Redundant Cell Array Technology (RedCAT™)



Redundant Cell Array Technology (RedCAT™)




Failed
Cell

A+ and Li-ion Module Specifications

Characteristic	Li-ion	A+
Acceptable Charge Voltage	18 - 36	13.5 to 15
Discharge Volt Range	27	13.2 to 10
Charge time to 90%, @ -40°C (Hours)	7.6	3 to 5
Cranking Current, 30 Sec @ -40°C	20	>400
Energy 25 Deg. C, 4 Hour Rate (kWh)	3	1.32
Energy -40 Deg. C, 4 Hour Rate (kWh)	2.25	0.53
Op. Temp. Range (°C)	-40 to 65	-40 to 80
Cycle Life, 80% DoD	500	320
Weight (kg)	33	39
Width (mm)	267	267
Height (mm)	241	231
Depth (mm)	287	287

Conceptual Module Design



Li-ion




A+

Vehicle Architecture

- A+ and Li-ion batteries work in parallel on the 28V bus
- Li-ion power electronics accommodate MIL-STD-1275
- A+ batteries provide starting and pulse currents
- Li-ion provides extended Silent Watch capabilities

A+ and Li-ion/A+ Configuration M1A2SEP Vehicle



Starting
Main Compartment

Silent
Watch
NPS Compartment

M1A2SEP Vehicle Design Specifications

Characteristic	Li-ion/A+	A+
Modules	12	12
Cranking Current @ -40°C	>960	>2400
Energy 25°C, 4 Hour Rate (kWh)	29.3	15.8
Energy -40°C, 4 Hour Rate (kWh)	20.12	6.36
Run Time @ 1.5kW 25°C (Hrs)	19.5	10.6
Run Time @ 1.5kW -40°C (Hrs)	13.4	4.2
Volume (l)	218.5	212.4
Weight (kg)	420	468
Energy Density Wh/l @ 25°C	134.0	74.6
Specific Energy Wh/kg @ 25°C	69.7	33.8


Testing

- Single string of A+ in parallel with single Li-ion String
- 25°C and -40°C
- 10.4 A Load
- 280W/String from Li-ion
- 250W/String from A+
- Scales to 2246W on M1A2SEP concept Li-ion Only
 - (8 strings x 280W = 2264W)
- Scales to 500W when down to A+ only operation
 - (2 strings x 250W = 500W)

Test Configuration

Li-ion

A+




Battery Management
& DC-DC Converters

Load/Charger


28VDC BUS

25° Discharge Mixed Chemistry

Mixed Chemistry Discharge 10.4 A Load, 25°C



-40° Discharge Mixed Chemistry



Test Summary, Mixed Chemistry

Parameter	25°C	-40°C
Bus Current	10.4	10.4
Li-ion Run Time	10.7 hrs	8.4 hrs
A+ Run Time	12 hrs	5.4 hrs
Total Run Time	22.7 hrs	13.8 hrs
Total Energy	6 kWh	3.7 kWh

Conclusions

- Li-ion can operate in parallel with Armasafe Plus (A+) batteries
- Li-ion power electronics meet MIL-STD-1275 bus voltage requirements
- The system can be configured to use Li-ion first and leave A+ on reserve for starting and reserve energy if necessary
- The user can mix A+ and Li-ion as needed
- 2X runtime vs. A+ alone at 25°C
- 3X runtime vs. A+ alone at -40°C



SAFT





saft

2007 Joint Services Power Expo & Conference

Leadership in Battery Technology





saft

Recent Advances in Saft Li-ion

Bridget Deveney





saft

Broad Product Range





Military Applications



saft

DOD's Main Provider of Primary Lithium Batteries

- World's leading supplier of primary Lithium batteries the U.S. military
- Offer complete range of technologies: Li-SO₂, Li-SOCl₂, Li-MnO₂
- Supporting our troops in Iraq - producing over 120,000 BA-5590s per month - during 24-7 operations for >2 years non-stop
- Delivered >90% of OIF and OEF Primary Batteries





saft

High Power Lithium Ion






SAFT

Advanced Li-ion Technology

SPECIFIC POWER/SPECIFIC ENERGY OF RECHARGEABLE CELLS





Space & Defense Division Cockeysville, MD

SAFT

Dedicated to manufacturing advanced Li-ion cells and batteries for Space and Defense application



Type of Cell	VL4V	VL8V	VL8P	VL16P	VL30P	VL44E	VL50E
	Very High Power	Very High Power	High Power	High Power	High Power	High Energy	High Energy
Dimension							
Diameter (mm)	34	41	47	47	54	54	54
Case Length (mm)	156	156	104	178	208	220	208
Mass (kg)	0.33	0.47	0.38	0.67	1.05	1.12	1.05
Capacity (AH)	5.5	8.6	8	16	31	44	51
Specific Energy (Wh/kg)	60	65	75	85	106	148	175
Energy Density (Wh/L)	138	155	158	187	234	300	390
Power (W/kg)							
→ 18 sec. Pulse (at 50% SOC)	3600	4000	1420	1430	1190	NA	NA
→ Continuous	2100 (60C)	2500 (60C)	850 (15C)	950 (15C)	800 (10C)	278 (2.6C)	60 (C/2)




Defense Applications



saft

SEAL Delivery Vehicle



- **Lithium Ion Battery with 50% Energy Improvement**
- **Dual Redundancy for Improved Safety and Survivability**
- **Major Life Cycle Cost Savings**





saft

AUV Power



- **21" High Energy System**
- **Modular Approach with Standard Cell and CANProbe Board**





ITAS Improved Target Acquisition System

saft



Raytheon



Li Ion
Battery





saft

JSF 270 V Battery

- **First producible 270V Aviation Battery**
- **85 lbs, 1kWh over full temperature range**
- **Pursuing full qualification**





High Power Experience

SAFT

- SAFT has been working on high power Li-ion since 1995.
- The **Very High Power** technology is a natural evolution for SAFT's Li-ion expertise.
- SAFT is already participating in the development phase of DE Applications
 - **A Solid State Heat Capacity Laser (SSHCL) program is under way in Laurence Livermore National Laboratory**
- SAFT is gearing up to manufacture VHP products. A good example is the Joint Strike Fighter Aircraft program where a 270V Emergency Battery using VL4V cells is under development and qualification





48 Volt High Power Module

saft

- Discharge Current: 250 A typical
 - Peak Power: 8 kW / kg (continuous discharge)
 - Pulse Power: 12 kW / kg (2 sec duration)
 - Charge Current: 100 A max
 - Battery Capacity: 8 Ahrs
 - Stored Energy: > 345 Whrs
-
- Module Weight 7.6 kg (16.8 lbs)
 - Module Voltage Max: 49.2 V (charged)
Avg: 43.2 V
Min: 36.0 V





Cutting Edge Development



SAFT

LiFePO₄ Development

- **What is Iron Phosphate and why are people talking about it?**
 - UT & Phostech
 - Technology benefits and cost





SAFT

LiFePO₄ Development

- **SAFT initiated work on LiFePO₄ under a developmental program with Army Research Laboratory**
 - SAFT contributed with high power electrode and cell design expertise
 - The scientists at ARL developed advanced electrolytes targeting life and improvement
- **SAFT is continuing the LiFePO₄ work under US Army MANTECH effort. Very High Power cells with the LiFePO₄ cathode have been produced using standard hardware. These cells are undergoing testing.**
- **In all this work SAFT is using material from the only licensed by UT supplier of LiFePO₄ – Phostech/Sud-Chemie.**





saft

LiFePO₄ Development

Cell	VL10Fe	VL12V
Cathode	LiFePO ₄	NCA
Nominal Voltage (V)	3.3	3.6
Nominal Capacity at C rate (Ah)	10	12
V = f(SOC) at 50% DoD at C rate (mV/SOC%)	0.13	0.66
Maximum Discharge Current at 25°C (A)		
Continuous	1500	1500
2s Pulse	1700	2200
200ms pulse	2200	3200
Specific Energy (W/L)	54	74
Energy Density (Wh/L)	128	175
Specific Power at 25°C 100% SOC (W/kg)		
Continuous	4375	4600
2s Pulse	5000	6800
200ms Pulse	6400	10,000





SAFT



- **Performance parameters Important for use in military application**
 - Availability of very high power
 - Operation at wide temperature range from -40°C to 72°C
 - Retention of low temperature power after exposure to high temperature





LiFePO₄ Development

saft



Total Energy Delivered Compared to a standard VL12V (NCA cathode):

● **75% of VL12V Energy at 12Amps**


50% of the VL12V Energy at 1500Amps





LiFePO₄ Development

SAFT







SAFT

LiFePO₄ Development


- Pulse testing - 5 sec 1750A

5400W/kg  **SECOND MOST POWERFUL CELL
AFTER SAFT VL-V CHEMISTRY**





SAFT



- Calendar life testing is incomplete but expected to be shortened by elevated temperature similar to other Iron Phosphate cells
- Temperatures above 60°C significantly reduce life







SAFT

LiFePO₄ Development

● Pulse Power retention with ageing


- 2500 W/kg 18sec Discharge PP @ (70-100)% SOC & 25°C
- 1900 W/kg 18sec Charge PP @ (20-80)% SOC & 25°C
- Nearly no power loss after 700 full cycles @ 1C rate & 60°C





saft

LiFePO₄ Development



- Low Temperature Performance Needs Improvement





saft

LiFePO₄ Development


- LiFePO₄ cathode: enhanced safety
 - **less lithium excess + reduced oxygen evolution →**
 - **less heat generation + lower energy density → lower temperature rise**





LiFePO₄ Development: Safety

SAFT



0.63 mOhm Short Circuit


- No event
- T < 100°C





LiFePO₄ Development: Safety

SAFT



2C (24A) Overcharge
Vented with no smoke
& no fire
● **T < 100°C**





saft

● Conclusion

- Iron Phosphate is suitable for high power applications that require an added level of redundant safety.
- The requirements of the application must be considered as there are tradeoffs in:
 - Lower power & energy
 - Poorer low temperature performance
 - Less robust at high temperature for storage



Four Facilities

North Haven, Connecticut

Valdosta, Georgia

Cockeysville, Maryland

Valdese, North Carolina

The World's Largest Specialty
Defense Battery Manufacturer

The military's power resource



saft

Discover Saft.

Even if you know us already.



Warfighting in a Climate Warming World - Implications for U.S National Security Policies

2007 Joint Service Power Expo
Power and Energy Independence for the
Warfighter

Hon. Philip Coyle
Senior Advisor
World Security Institute

Hon. Martha Krebs, Ph.D
Deputy Director for R&D
California Energy Commission

April 25, 2007



Positive proof of global warming.



18th
Century

1900

1950

1970


1980

1990

2006


In the last 150 Years

- Temperatures have risen
- Sea level is higher
- Snow cover is down



In the last 400,000 years


- Temperatures are at the upper end of historical variability, but
- Carbon dioxide levels are significantly beyond historical levels



CO₂, CH₄ and
estimated global
temperature (Antarctic
 $\Delta T/2$
in ice core era)
0 = 1880-1899 mean.

Source: Hansen, *Clim.
Change*, 68, 269, 2005.

You think Katrina was bad; Here's where I
Live under a 6m storm surge!



Report of the United Nations Intergovernmental Panel on Climate Change

Fourth major assessment since 1990

2500+ scientific expert reviewers

800+ contributing authors and

450+ Lead authors from


130+ countries

6 years work


4 volumes

1 report

Detection and attribution conclusions of IPCC Second and Third Assessment Reports (1995, 2001)



“The balance of evidence suggests a discernible human influence on global climate”



“There is new and stronger evidence that most of the warming observed over the last 50 years is attributable to human activities”

Climate Change 2007: The Physical Science Basis

Working Group I Contribution to the IPCC Fourth Assessment Report

Direct Observations of Recent Climate Change

Warming of the climate system is unequivocal, as is now evident from observations of increases in global average air and ocean temperatures, widespread melting of snow and ice, and rising global mean sea level.

Observed sea ice September 1979




Observed sea ice September 2003



Climate Change 2007: The Physical Science Basis Working Group I Contribution to the IPCC Fourth Assessment Report


Human and Natural Drivers of Climate Change

The understanding of **anthropogenic** warming and cooling **influences on climate** has improved since the Third Assessment Report (TAR), leading to **very high confidence** that the globally averaged net effect of human activities since 1750 has been **one of warming**, with a radiative forcing of $+1.6$ [$+0.6$ to $+2.4$] $W m^{-2}$.



Limitations of the UN Study

- Data behind the UN study were frozen two years ago.
- The problem is actually worse.
- Greenland is melting faster than we expected



E. Rignot et al., Science 311, 986 -990 (2006)

Recent DOD Studies

- Defense Science Board Task Force on DOD Energy Strategy. Chartered May 2, 2006.
- National Security and the Threat of Climate Change, The CNA Corporation, Gordon Sullivan, Chair, April 16, 2007.
- Reducing DOD Fossil-Fuel Dependence, JASON, September 2006, JSR-06-135.
- An Abrupt Climate Change Scenario and Its Implications for United States National Security, Peter Schwartz and Doug Randall, Global Business Network, October, 2003.

What's the Threat?

- Cost of fuels
- Availability of fuels
- Operational flexibility
- Deployability
- Strategic Balance
- Sustainability

Yes, but What's the Real Threat?

The Good News

- No extended world-wide shortage of fossil fuels for ~ 25 years.
- DOD fuel consumption is < 2% of total U.S. domestic fuel consumption.
- DOD fossil fuel spending is only 2.5-3% of the national defense budget.

The Bad News

- The world will need as much oil in the next 25-30 years as has been produced over the last 150 years.
- DOD fuel consumption is 93% of U.S. Government use.
- Mobility fuels = vast majority of DOD fuels use.
- JP-8 cost is up 2.8X since 2004= >\$4B/year

More Bad News

- Current logistics supply chain designed when “behind the front lines” meant “safe.” Today = Iraq, IEDs, etc.
- Air-to Air = \$20-25 per gallon.
- Army theater = \$100-600 per gallon.
- Ethanol and Hydrogen unsuitable?
- But 62% of DOD fuel use is CONUS.


What's the Real Threat?

- Massive population displacements due to loss of land mass.
 - China, India, Bangladesh, Myanmar
 - Persian Gulf
 - Vietnam, Thailand
 - Indonesia, Phillipines
- Impacts on water availability, growing seasons
- Geographical range of infectious disease

Complete melting of Greenland glaciers = 6.55 meter sea rise

Complete melting of all glaciers = 80.32 meter sea rise

USGS Fact Sheet 002-00 January, 2000



93 million Chinese (~7%) at risk in 6m storm surges.

Loss of Land Mass ~ China

- 93 million people in China could be displaced by a 6 meter sea-level rise.
- In terms of loss of territory, loss of lives, economic disruption, and long term effects, global warming can be compared to nuclear war.

Region (total population in millions, 2000)	Population Under Water (for given sea level rise)			
	<i>6m</i>	<i>25 m</i>	<i>35m</i>	<i>75m</i>
United States (283)				
East Coast	9	41	51	70
West Coast	2	6	9	19
China + Taiwan (1275+23)	93	224	298	484
India + Sri Lanka (1009+19)	46	146	183	340
Bangladesh (137)	24	109	117	130
Indonesia + Malaysia (212+22)	23	72	85	117
Japan (127)	12	39	50	73
Western Europe (454)	26	66	88	161

Hansen

Sea-level rise in Regions of Importance to the U.S. Military

- Norfolk, Virginia
- Florida
- Gulf Coast
- Carolinas
- Hawaii



Dover

Ocean City

Hampton

Virginia Beach

Norfolk

Sea Level +1M



Dover

Ocean City

Hampton



Virginia Beach

Norfolk

Sea Level +6M

Strategic Oil Supply

EIA International Energy Annual 2006
Reference Case



Expectations

- The U.S. Military as a microcosm of U.S. society
- Preserving the American way of life;
Preserving American values
- Domestically, American support of the U.S. Military depends on consistency with U.S. values.

Expectations

- The realization of climate warming and its actual early physical manifestations will come to have an impact on the U.S. military as well as on other sectors of American endeavor.
- While in battle the U.S. military could well be exempted from the constraints of climate warming, but during periods of low intensity conflict or relative peace, the U.S. military could well be expected to do its share to reduce these impacts.

National Security can drive innovation in energy supply

An Historical Precedent

The U.S. Synthetic Fuels Corporation was
created as an amendment (January 15,
1979) to the Defense Production Act of
1950

What the U.S. Military is Already Doing

- Army
- Navy
- Air Force
- Marines


Ft. Bliss Ethanol Pump



M-13 SIP ISSUE

(Pt Mugu Ship Channel)

- **Feb 1998 Navy proposal to establish working group to study speed reduction as alternative to moving channel.**
 - CARB establishes working group(June 1998) Participation by Navy, Shipping Industry, Ports, USEPA
- **Dec 2000 Final Report**
 - Relocated commercial channel increases estimated 2010 SIP NOx pollution by 1.3 tons per day (greater steaming distance of relocated channel)
 - Estimated 2010 SIP NOx reductions ranging from 3.9-10.7tons per day from speed reduction in existing channel
 - All exceed M-13 target and are feasible for shipping industry
- **Marine vessel emission reduction/Navy operations can co-exist**



“Unleash us from the tether of
Fuel.” Lt.Gen. James Mattis, USMC

“Commit to hybrid electric architecture for
Tactical Wheeled Vehicles (TWV)”

“Long term commitment to manufactured
liquid hydrocarbon fuels from domestically
abundant feedstocks.”

Key Actions, Naval Research Advisory Committee Report, April 2006.

“Flying Out In Front: *The Air Force Is Taking The Lead On Synthetic Fuel; Will You Follow Us? Asks Michael Wynne*”

Dallas Morning News □ January 27, 2007 □ Pg. 21



Strategic Supply

Oil prices and availability are still being determined by geo-politics, especially Middle Eastern politics, not raw supply.

Saudi Arabia can and does dampen Iranian adventurism by reducing the price of oil.



“Yes, some time next decade demand may indeed start to bump up against supply, but the price of oil today is as much political as it is supply and demand.” John Mauldin, 1-12-07

Strategic Supply is Important

- But coal to liquids makes carbon problem worse.
- 50% Coal-To-Liquids efficiency leads to 2X more CO₂ emissions than from petroleum diesel.
- Must be coupled to Carbon Capture and Storage, e.g. carbon sequestration ~ injecting CO₂ into the ground.
- Large scale demo of carbon sequestration, possibly at one or major U.S. military bases.

Carbon, carbon, carbon


World Carbon Dioxide Emissions by Region, 2001-2025
(Million Metric Tons of Carbon Equivalent)



U.S. Anthropogenic Greenhouse Gas Emissions by Gas, 2001
(Million Metric Tons of Carbon Equivalent)


California Electricity Consumption

Per Capita Electricity Sales (not including self-generation)
(kWh/person) (2005 to 2008 are forecast data)



Red States and Blue States

Per Capita Electricity Consumption



Conclusions

- The cost of fuels is already becoming a burden to the U.S. military.
- Global warming will become an increasing factor in U.S. military planning.
 - DSB Study
 - CNA Study
 - Global Business Network study
- To make a difference, reducing carbon emissions will be key.

Backup slides


Sustainability ~ a Military Definition

- “The ability to maintain the necessary level and duration of operational activity to achieve military objectives.
- Sustainability is a function of providing for and maintaining those levels of ready forces, materiel, and consumables necessary to support military effort.”

Sustainability is Development that meets the needs of the present without compromising the ability of future generations to meet their own needs. 1987


– World Commission on Environment and Development (the Brundtland Commission)

espacial.com



Loss of Land Mass ~ China

- Western China is not under government control like the eastern and coastal regions of China.
- Western China lives as though the central government does not exist.



Senator Joseph I. Lieberman

- Still, it is my strong hope that having addressed issues of conventional energy supply through this legislation, we will turn, in the very near future, our urgent attention to the most pressing issues - the clear and inextricable linkage between energy supply and national security, the resulting urgent need for aggressive development of a portfolio of alternative and renewable fuels and conservation strategies, and the need to take comprehensive steps to set mandatory caps on greenhouse gas emissions. Solving these problems – and soon – is a responsibility that we have to today's public as well as our children and grandchildren, an obligation that we will not have fulfilled when this legislation passes. - *July 29, 2005*



Senator John McCain

- Global warming is a serious threat. There is overwhelming evidence that increasing amounts of carbon dioxide and other greenhouse gases are heating up the Earth's climate and that inaction could be disastrous. - January 8, 2003
- The status quo is a strong and stubborn force. People and institutions are averse to change, even when that change is critical for their own well-being, and that of their children and grandchildren. If the scientists are right and temperatures continue to rise, we could face environmental, economic, and national security consequences far beyond our ability to imagine. If they are wrong and the Earth finds a way to compensate for the unprecedented levels of greenhouse gases in the atmosphere, what will we have accomplished? Cleaner air; greater energy efficiency, a more diverse and secure energy mix, and U.S. leadership in the technologies of the future. There is no doubt; failure to act is the far greater risk.— January 30, 2007

**POWER GENERATION
LESSON LEARNED
OIF 5-07**

MSgt Dickson

1st Marine Expeditionary Force

Headquarters Group

Engineer Chief

INTRODUCTION

- Issues / Dilemmas encountered
- Selecting Commercial Generators
- Purchasing / Contracts
- MEF Emergency Pool
- Reserve Pool

ISSUES/ DILEMMAS

- Insufficient quantity of tactical generators.
- Continuous increase in power requirements for bases.
- Vendors can't deliver equipment in required time.
- Technical experts not involved in selection process.

ISSUES/DILEMMAS

- Improper generator sizing.
- Ambient temperature.
- Refurbished equipment (pictures).

ISSUES/DILEMMAS

- Multiple manufactured engines and generators.
- Equipment maintenance plan.

SELECTING GENERATORS

- Electrical Assessment (Seabees/Marine/Army).
- Indefinite Delivery Indefinite Quantity (IDIQ).
- Blanket Purchase Agreement.

IDIQ

All new permanent, upgrade, enhancement and renovation base construction projects document shall stipulate use of approved generation systems on all bases, camps or posts in the Al Anbar province of Iraq.

IDIQ

An Indefinite Delivery Indefinite Quantity contract will:

- Help stabilize the generator purchase process.
- Simplify the generator purchasing process.
- Shorten the generator delivery time.

IDIQ

- Standardized ordering will encourage standardized base power grids, thereby lowering maintenance (less repair parts for multiple manufactured engines and generators).
- The recommended generator sizes are standard for the industry.

IDIQ (CONT...)

Generators under IDIQ

- 1) Cummins
- 2) Caterpillar
- 3) FG Wilson
- 4) Marapco

GENERATOR SPECS

- Prime Power only.
- Capable of operating at temperatures as high as 55 degree Celsius.
- 50 hertz (HZ).
- 220volts low side and 415 volts high side
- Generator must be covered by a weather / sound reduction enclosure including a muffler.
- Secondary containment.

GENERATOR SPECS

- Must include 6 month “push package”.
- Repair parts for diesel motor and generator must be readily available in Iraq, Saudi Arabia, Kuwait.
- Diesel motors must be manufactured by the Cummins and/or Caterpillar and licensed for sale and distribution.
- Diesel motor and generator warranty starts at the time generator has been delivered and accepted.

WHAT WE MUST AVOID

- CONTRACT FOR NEW GENERATORS.
- RECEIVED REFURBISHED GENERATORS.







AC GENERATOR		TYPE	
REP. NO.		SERIAL NO.	
HP		KVA	
PP		RPM	
VOLTS		AMPS	
RATING		AMBIENT TEMP	
EXCITATION VOLTS		AMPS	
		PHASE	
		ITS NO.	
		ITS OR.	
		ENCLOSURE	
		INS. CLASS.	

WARNING: REFER TO INSTRUCTION BOOK BEFORE GLAZING OR REPAIRING PARTS.

STAMFORD

STAMFORD ELECTRICAL WORKS LIMITED
100, NEW BRIDGE ROAD, SOUTHAMPTON, ENGLAND





2006 6 18



2006 6 18

PURCHASING/CONTRACTS

STEPS

- Validate base/unit requirements.
- **Statement of Work.**
- Contingency Contracting Office.
- Iraqi first concept

MEF EMERGENCY POOL

- Established to provide an emergency generator to units until their primary generator can be repaired.
- Located in two location to better support Coalition and Iraqi Security Forces.
- Generators repaired by ARKEL.

MEF EMERGENCY POOL

- Generators for pool are new or repaired generators from bases not maintained by Kellogg Brown and Root and closed bases.

RESERVE POOL

- Used to fill new power requirements aboard coalition bases.
- List supplied by KBR of available Commercial Generators.
- Saves millions and prevents unnecessary spending.

SUMMARY

- Issues encountered.
- Selecting proper generators to meet requirements.
- Purchasing / Contracts.
- MEF Emergency / Reserve Pool.

Lightweight 2-kW Generator with Integrated Starter Alternator (ISA)

April 25, 2007

2007 Joint Service Power Expo

San Diego, CA

Gregory Cole

gsc@mainstream-engr.com

Mainstream Engineering Corporation

200 Yellow Place

Rockledge, FL 32955

www.mainstream-engr.com

Solutions Through Advanced Technology™


MAINSTREAM

Engineering Corporation

Origin of Mainstream's 2-kW Generator


- Engine Development (1991-)
 - Customer: U.S. Army RD&E Center (Natick)
 - Application: Small, diesel-powered, personal cooling system
- Alternator Development (1994 -)
 - Customer: U.S. Army Aberdeen / OST
 - Application: Miniature, multi-fueled generator
- Results
 - Diesel-cycle is better than Rankine, Stirling, Brayton, and converted spark ignition (gasoline)
 - Mainstream designs and produces integrated, custom machines

Advantages of Mainstream's 2-kW Generators



Alternator integrated into engine flywheel

- smaller and lighter
- more reliable



Fan integrated into flywheel

- cools power electronics, engine head, oil sump
- runs cooler - increases life and reliability



Custom engine and generator designs

- sized specifically for application
- not just packaging of commercial components

Solutions Through Advanced Technology™

MAINSTREAM

Engineering Corporation

Evolution of Mainstream's 2-kW Generator



48 lbs unmounted

80 lbs fully instrumented and framed



2000-05: SBIR Program to develop generator for Marine Corps' Team Portable Collection System (TPCS)

- Marines wanted 1-kW (min.) 28-VDC generator weighing less than 50 lbs
- Manual recoil starter was desired because external starting power not available for electronic start
- Voltage regulation was not required because external power conditioning system in use
- Result: 2-kW 28-VDC generator

Future of Mainstream's 2-kW Generator



- 2006-07: IR&D
 - Developed patent-pending ISA
 - Developing integral AC inverter with soft-start motor technology
- 2006-2007: Hybrid-Electric Refrigerated Container
 - Mainstream's generator powers a 24-VDC bus and recharges batteries
 - Demo at JOCOTAS next week
- 2007: Cooperative Research and Development Agreement (CRADA) with Army RDECOM
 - Army RDECOM to perform lab tests this summer at Ft. Belvoir

Solutions Through Advanced Technology™

MAINSTREAM

Engineering Corporation

COPYRIGHT © MAINSTREAM ENGINEERING CORPORATION

Page 5

Integrated Starter/Alternator

- Electric start
- Voltage regulation
- Auto-start/stop
- Battery charging circuit
- Allows integration into 24-VDC hybrid electric systems

Army RDECOM Laboratory Tests (per MIL-STD-705C)

- Physical Characterization
- 503.1c Start and Stop Test
- 601.4b Voltage Waveform Test (Harmonic Analysis)
- 601.5 Voltage Waveform Test (Deviation Factor)
- 602.1b Voltage Modulation Test
- 608.1b Frequency and Voltage Regulation, Stability, and Transient Response Test (Short Term)
- 610.1b Voltage and Frequency Droop Test
- 619.2c Voltage Dip and Rise for Rated Load Test
- 640.1d Maximum Power Test (at 125°F)
- 650.1b Ripple Voltage Test
- 660.1d Inclined Operation test
- 661.2c Sound Level Test
- 670.1b Fuel Consumption Test
- 690.1d Endurance Test
- 701.1d Starting and Operating Test (Extreme Cold Battery Start)
- 710.1d High Temperature Test

Physical Characterization

28-VDC Generator Comparison		
Model	MEP-501A	Mainstream MFEG-020028
Dry Weight	124 lbs ¹	93 lbs
Wet Weight	138 lbs ²	102 lbs
Size	30'' (L) ¹ 16'' (W) ¹ 22'' (H) ¹	18'' (L) 18'' (W) 20'' (H)

120-VAC Generator Comparison		
Model	MEP-531A	Mainstream MFEG-020120
Dry Weight	143 lbs ¹	118 lbs ³
Wet Weight	158 lbs ²	127 lbs ³
Size	30'' (L) ¹ 16'' (W) ¹ 22'' (H) ¹	18'' (L) 18'' (W) 20'' (H)

¹ Army TM 9-6115-673-13&P

² <http://www.pm-mep.army.mil/technicaldata/2kw.htm>


³ Projected based on design

503.1c Start and Stop Test

28-VDC Generator		
	Performance Specification For Military Mobile Power Sources (0.5kW TO 15kW)	Mainstream MFEG-020028
Start Time	Threshold – 5 min Objective – 3 min	3.3 sec
Stop Time	2 min	3.8 sec

608.1b Frequency and Voltage Regulation, Stability, and Transient Response Test

Prior test results from Army RDECOM with Mainstream's unregulated generator



28-VDC Generator

	MIL-STD-1332B	Mainstream Unregulated Generator
Voltage - Regulation	4%	20.9%
Voltage - Steady-State Stability	2%	6.6%

Solutions Through Advanced Technology™


MAINSTREAM

Engineering Corporation

COPYRIGHT © MAINSTREAM ENGINEERING CORPORATION

608.1b Frequency and Voltage Regulation, Stability, and Transient Response Test

Current test results with Mainstream's regulated generator with ISA



28-VDC Generator


	MIL-STD-1332B	Mainstream MFEG-020028
Voltage - Regulation	4%	3.9% @ 100% load* 3.9% @ 75% load 3.4% @ 50% load 2.8% @ 25% load
Voltage - Steady-State Stability	2%	1.1 @ 100% load 1.1 @ 75% load 1.1 @ 50% load 1.1 @ 25% load 1.0 @ 0% load

Solutions Through Advanced Technology™

MAINSTREAM

Engineering Corporation


610.1b Voltage and Frequency Droop Test



28-VDC Generator		
	MIL-STD-1332B	Mainstream MFEG-020028
Voltage - Droop	not specified	1.4%

619.2c Voltage Dip and Rise for Rated Load Test

Prior test results from Army RDECOM
with Mainstream's unregulated generator



28-VDC Generator

	MIL-STD-1332B	Mainstream Unregulated Generator
Voltage – Dip	30%	24.8%
Recovery Time	2 sec	0 sec
Voltage - Rise	40%	22%
Recovery Time	2 sec	0 sec

Solutions Through Advanced Technology™



MAINSTREAM

Engineering Corporation

COPYRIGHT © MAINSTREAM ENGINEERING CORPORATION

619.2c Voltage Dip and Rise for Rated Load Test

Current test results with Mainstream's regulated generator with ISA



28-VDC Generator

	MIL-STD-1332B	Mainstream MFEG-020028
Voltage – Dip	30%	6.2%
Recovery Time	2 sec	0.1 sec
Voltage – Rise	40%	5.5%
Recovery Time	2 sec	0.6 sec

Solutions Through Advanced Technology™


MAINSTREAM

Engineering Corporation

COPYRIGHT © MAINSTREAM ENGINEERING CORPORATION

650.1a Ripple Voltage Test

Prior test results from Army RDECOM
with Mainstream's unregulated generator



28-VDC Generator

	MIL-STD-1332B	Mainstream Unregulated Generator
Voltage - Ripple	5.5%	9.4%*

* Reduced to 2.9% with 0.16 lb capacitor

Solutions Through Advanced Technology™


MAINSTREAM

Engineering Corporation

COPYRIGHT © MAINSTREAM ENGINEERING CORPORATION

650.1a Ripple Voltage Test

Current test results with Mainstream's regulated generator with ISA



28-VDC Generator		
	MIL-STD-1332B	Mainstream MFEG-020028
Ripple 0% Load	5.5%	0.55%
Ripple 25% Load	5.5%	0.55%
Ripple 50% Load	5.5%	0.60%
Ripple 75% Load	5.5%	0.59%
Ripple 100% Load	5.5%	0.63%

Solutions Through Advanced Technology™

MAINSTREAM

Engineering Corporation

670.1b Fuel Consumption Test

Prior test results from Army RDECOM with Mainstream's unregulated generator

28-VDC Generator			
Load (W)	Load (%)	Fuel Consumption (lbs/hr)	Fuel Consumption (gal/hr)
0	0%	0.80	0.120
425	21%	1.04	0.156
975	49%	1.07	0.160
1460	73%	1.23	0.185
1990	100%	1.49	0.223

For Comparison: “The Power Generation Branch has numbers showing some MTGs to use only 0.26 gal/hr of JP-8 at full load. The 0.33 is a fleet maximum.” – Army CECOM

No Change Expected for the Following Tests

- 660.1d Inclined Operation Test
 - 20°
- 661.2c Sound Level Test
 - 79 dBA at 7 m
- 690.1d Endurance Test
 - RDECOM testing for 150 hrs
- 710.1d High Temperature Test
 - RDECOM will test to 135°F (previously 125°F)

Changes Expected for the Following Tests

- 640.1d Maximum Power Test
 - More efficient power converter will increase max power
- 701.1d Starting and Operating Test (Extreme Cold Battery Start)
 - ISA with electric start will allow for extreme cold weather starting

Summary



- Mainstream's 2-kW Generators
 - 28 VDC
 - 120 VAC, 60 Hz
- 39% smaller than MTG
- 17-25% lighter than MTG
- 33% more efficient than MTG
- 3-6x more reliable than MTG
- New Features:
 - ISA
 - Battery charging circuit
 - Auto-start/stop
 - Hybrid-electric ready
 - AC inverter with soft-start

Contact Information

- Company Address
 - Mainstream Engineering Corporation
 - 200 Yellow Place
 - Rockledge, FL 32955
 - (321) 631-3550
 - www.mainstream-engr.com
- Points of Contact
 - Technical: Greg Cole, gsc@mainstream-engr.com
 - Contracts: Michael Rizzo, mar@mainstream-engr.com
- Booth #312



Workshop

Battery Technical Manuals and Milspecs

Susan M. Waggoner
Electronics Engineer
Code 6095, Bldg. 3287W
300 Highway 361
Crane, IN 47522-5001
Phone 812-854-4103, DSN 482-4103
Fax 812-854-1212
susan.waggoner@navy.mil



- **Update**
- **Comments**
- **Q&A**



- **Technical Manuals**
- **Milspecs**
- **Batteries**
- **Battery chargers**





Case Study – Reducing Premature Failure of Parts with Interactive Virtual Training for Generator Operators

Joint Service Power Expo
San Diego
April 24-27, 2007

Erik Kaas
Director, Product Management
NGRAIN Corporation
ekaas@ngrain.com



Agenda

- ◆ Training Challenges
- ◆ Virtual Maintenance Trainers
- ◆ Case Study – 3kW Tactical Quiet Generator
- ◆ Conclusions



Common Challenges in Training


- ✘ Some tasks cannot be trained, due to **expense** or **lack of access to equipment**
- ✘ Soldiers receive limited training before being deployed: task-based, **on-the-job training** is critical
- ✘ Training **budgets are limited**, yet training demand is increasing
- ✘ Total Package Fielding requires rapid and effective **New Equipment Training**





Learning Theory



Students Remember



Source: Airbus/Journal of Civil Aviation Training (Issue 1, 2006)



Training Methods



Text

Multimedia

Hard Trainers

Live Equipment

Interactive Virtual Maintenance Trainers

- ✓ Low cost
- ✓ Easy to create and update
- ✓ Anytime, anywhere access
- ✗ Low learning effectiveness

- ✓ Low cost
- ✓ Easy to create and update
- ✓ Anytime, anywhere access
- ✓ High learning effectiveness

- ✗ High cost
- ✗ Difficult to create and update
- ✗ Limited access
- ✓ High learning effectiveness



Virtual Maintenance Trainers

Virtual 3D equipment simulations to:

- *Familiarize*
- *Acquire*
- *Practice*
- *Validate & Test*



Proven ROI: Train 60% Faster





Benefits of Virtual Maintenance Trainers

- ✓ Let students learn from their mistakes, **safely**
- ✓ Let training take place **without the expense** of equipment
- ✓ **Reduce wear and tear** on equipment
- ✓ Enable **task-based, on-the-job training**
- ✓ Students are more engaged and **motivated**






Case Study: 3kW TQG Operator Course

Challenge: Premature failure of generator parts due to operator error

Objective: Provide more effective refresher and sustainment training

Results: Reduced premature failure of parts



PM-MEP - Microsoft Internet Explorer provided by NGRAIN Corporation

HELP MENU

Project Manager - Mobile Electric Power (PM-MEP)

COURSE MENU

- Introduction
- Description & Principles of Operation
- Technical Documentation
- Controls, Indications, & Terminals
- Preventative Maintenance (PMCS)
 - PMCS Overview
 - Before Operation
 - During Operation
 - After Operation
- Operating Procedures
- Troubleshooting
- Freeplay Exploration

DURING: AFTER 8 HOURS

After 8 hours of continual operation, you will need to shut down the generator set and check the oil level. The generator set is not fully mission capable if the oil level is at or below the minimum oil level mark on the dipstick.

After 8 hours of continual operation you will also need to check the fuel filter/water separator to make sure water and fuel are not mixed. Again, the generator set should be shut down during this procedure. If you find that water and fuel are mixed, you will need to drain water from the fuel filter/water separator by turning a valve on the separator.

Fuel Filter/Water Separator

Oil Fill Cap

After 8 Hours of Continuous Operation

LESSON: PMCS DURING Page 3 of 7 FRAME: DURING: AFTER 8 HOURS

1 2 3



Case Study - Implementation

Based on Technical Manual


- Cross reference
- Follow the procedure

Visual & Interactive

- Engage students
- More intuitive explanations
- Validate & test

Computer Based

- Used by instructor
- Used by students
- Used by deployed soldiers to refresh or just in time training





Case Study - Demonstration

Course Layout

Component Familiarization

Controls

PMCS

Operating

Troubleshooting

PM-MEP - Microsoft Internet Explorer provided by n-GRAIN Corporation

HELP MENU

Project Manager - Mobile Electric Power (PM-MEP)

INTRODUCTION

Welcome to the 3 kilowatt (kW) Tactical Quiet Generator (TQG) Set Operator Training Course for the MEP 831A (60Hz) and MEP 832A (400Hz) generator set models! Upon successful completion of this course you will be able to operate and perform operator maintenance on the 3kW TQG Set.

COURSE MENU

- Introduction
- Introduction
- Description & Principles of Operation
- Technical Documentation
- Controls, Indications, & Terminals
- Preventative Maintenance (PMCS)
- Operating Procedures
- Troubleshooting
- Freeplay Exploration

LESSON: INTRODUCTION

Page 1 of 6

FRAME: INTRODUCTION



Course Layout

PM-MEP - Microsoft Internet Explorer provided by NGRAIN Corporation

COURSE MENU

- Introduction
- Description & Principles of Operation
- Technical Documentator
- Controls, Indications, & Terminals
- Preventative Maintenance (PMCS)
- PMCS Overview
- Before Operation
- During Operation
- After Operation
- Operating Procedures
- Troubleshooting
- Freeplay Exploration

HELP MENU

Project Manager - Mobile Electric Power (PM-MEP)

INTRODUCTION

Welcome to During Operation lesson. This lesson reviews the PMCS procedures for during operation of the generator set. This lesson reviews the procedures you need to conduct while the generator set is running, Remember to refer to Table 2-1: Preventative Maintenance Checks and Services located in the Operator's Unit, and Direct Support Maintenance Manual for a complete guide to PMCS procedures to perform during operation of the generator set.

ARMY TM 9-4115-428-13
AIR FORCE TO 35C2-3-288-01
MARINE CORPS TM 10156A-13

Table 2-1. Operator Preventive Maintenance Checks and Services for MEP 4024 - (R124 continued)

Item No.	Interval	Location: Screw to Check/ Service	Procedure	See Field Manual Caption ID
11	Before	Start box		
12	Before	Engine oil	a. Measure fuel level during generator set operation. WARNING: Some service personnel use white engine oil. Ensure that level is correct. Start engine and before filling with fuel. Ensure to personal use source of proper grade/brand oil as follows: 1. Replace fuel as follows. Stop down generator set. Remove fuel fill cap and fill with proper fuel. Insert fuel fill cap.	Fuel level is empty or level color is irregular.
13	During	VOLTAGE and LOAD meters (control panel)	a. Monitor generator set while engine is running. Stop down and before stopping oil. Ensure to personal use source of proper grade/brand oil as follows: 1. Replace fuel as follows. Stop down generator set. Remove fuel fill cap and fill with proper fuel. Insert fuel fill cap.	Oil level is at or below maximum oil level mark on dipstick.
14	Before	Engine oil filter	a. Start down generator set. Open machine cover. 1. Remove engine oil fill cap and check oil level. Service as required in accordance with page 3-1.	

LESSON: PMCS DURING

Page 1 of 7

FRAME: INTRODUCTION



Component Familiarization

C:\Documents and Settings\lekaas\Desktop\N-GRAIN Demo\3kW Generator Course by MTC\ngrain\interac - Microsoft Internet Explorer p

File Edit View Favorites Tools Help

Back Forward Stop Search Favorites Folders

Step 1: Click on each component to view its part on the 3kW Generator.

Major Components:

- Enclosure
- Hinged cover
- Skid base
- Vibration Isolators
- Battery
- Engine
- Generator
- Slave Receptacle
- Control Box Assembly
- Output Terminals

Step 2: Take a comprehensive Quick Check on what you just learned.

[Advance to Quick Check!](#)

The engine is a single cylinder, air cooled, direct injection, 4-stroke cycle, diesel

Part Descriptions:

isolates engine generated vibrations from the rest of the generator set



Controls, Indicators & Terminals

PM-MEP - Microsoft Internet Explorer provided by NGRAIN Corporation



COURSE MENU

- Introduction
- Description & Principles of Operation
- Technical Documentator
- Controls, Indications, & Terminals
- Controls, Indications, & Terminals
- Preventative Maintenance (PMCS)
- Operating Procedures
- Troubleshooting
- Freeplay Exploration

HELP MENU
Project Manager - Mobile Electric Power (PM-MEP)

ENGINE GROUP

HOURS:

FUEL LEVEL: 

VOLTAGE: 

EMERGENCY STOP:

AUX FUEL:

PREHEAT:

START:

ENGINE HIGH TEMP

LOW OIL PRESSURE

NO FUEL

OVERVOLTAGE

OVERLOAD SHORT CIRCUIT

FAULT RESET

BATTLE SHORT

PUSH TEST

VOLTAGE ADJUST:

CIRCUIT INTERRUPT:

DESCRIPTIONS

The FAULT INDICATOR MODULE is an area where important indicators are displayed. It contains indicator lights that illuminate during fault conditions which assist in troubleshooting the generator set. A list of these indicators is found on the right.

Click on each item name to view its location on the FAULT INDICATOR MODULE as well as its description.

CLICK ON EACH ITEM TO SEE ITS LOCATION

- Engine High Temperature
- Over Voltage
- Low Oil Pressure
- Overload Short Circuit
- No Fuel
- Battle Short On
- Fault Reset/ Push Test

LESSON: CONTROLS & INDICATIONS

Page 3 of 6

FRAME: GENERATOR SET STARTING SYSTEM



PMCS

PM-MEP - Microsoft Internet Explorer provided by NGRAIN Corporation

COURSE MENU

- Introduction
- Description & Principles of Operation
- Technical Documentator
- Controls, Indications, & Terminals
- Preventative Maintenance (PMCS)
- PMCS Overview
- Before Operation
- During Operation
- After Operation
- Operating Procedures
- Troubleshooting
- Freeplay Exploration

HELP MENU

Project Manager - Mobile Electric Power (PM-MEP)

DURING: AFTER 8 HOURS

After 8 hours of continual operation, you will need to shut down the generator set and check the oil level. The generator set is not fully mission capable if the oil level is at or below the minimum oil level mark on the dipstick.

After 8 hours of continual operation you will also need to check the fuel filter/water separator to make sure water and fuel are not mixed. Again, the generator set should be shut down during this procedure. If you find that water and fuel are mixed, you will need to drain water from the fuel filter/water separator by turning a valve on the separator.

Fuel Filter/Water Separator

Oil Fill Cap

After 8 Hours of Continuous Operation

LESSON: PMCS DURING

Page 3 of 7

FRAME: DURING: AFTER 8 HOURS

1 2 3




PMCS Procedure Illustration

C:\Documents and Settings\lekaas\Desktop\INGRAIN Demos\3KW Generator Course by MTC\ingrain\Interac - Microsoft Internet Explorer p

File Edit View Favorites Tools Help

Back Forward Stop Home Search Favorites Folders


Google Go Back Forward Home Bookmarks Check AutoLink Print Send to Settings



Step 1: Click on each PMCS Before procedures to view animation representing the inspection of items.

PMCS Before:

- Entire Set
- Enclosure Cover
- Intake & Exhaust Ducts
- Control Panel
- Convenience Receptacle
- Slave Receptacle
- Output Panel
- Muffler
- Fuel Fill Area
- Fuel Tank/Hoses
- Fuel/Water Separator
- Skid Base
- Vibration Mounts
- Battery and Cables
- Power Inverter
- Engine Oil
- Air Filter



Item No.	Interval	Location: Item to Check/ Service	Procedure	Not Fully Mission Capable If:
13	Before	AS	Open enclosure cover. Inspect AS and area around AS for signs of water. If water is present, thoroughly dry out AS before starting generator.	Water is in AS
			a. Open enclosure cover. Remove oil fill cap and check level. If correct, replace cap.	Class III oil leaks are present.




PMCS Practice


C:\Documents and Settings\ekaas\Desktop\NGRAIN Demos\3KW Generator Course by MTC\ngrain\interac - Microsoft Internet Explorer.p

File Edit View Favorites Tools Help

Back Forward Stop Home Search Favorites Folders



Quick Check:
Match the Component name or description below by clicking the that part in the model.



Microsoft Internet Explorer

! CORRECT!

OK


Click on the model above to match the part below:

Single cylinder, air cooled, direct injection, 4-stroke cycle, diesel



Operating & Troubleshooting

PM-MEP - Microsoft Internet Explorer provided by NGRAIN Corporation



COURSE MENU

- Introduction
- Description & Principles of Operation
- Technical Documentator
- Controls, Indications, & Terminals
- Preventative Maintenance (PMCS)
- Operating Procedures
- Troubleshooting
- Procedures
- Freeplay Exploration

HELP MENU

Project Manager - Mobile Electric Power (PM-MEP)

WHITE SMOKE


When the generator set is running you may see white smoke emitted from the engine. If you see white smoke, try the following procedures:



OIL FILL CAP

STEP 1:
First, check the engine oil level to see if it is too high. If it is too high, you will need to refer the trouble to the unit maintenance level so they can drain and service the engine oil.

STEP 2:
If the engine oil level is acceptable, check for water in fuel filter/water separator. If water is present, you will need to drain water from filter separator by turning the valve. (Refer to paragraph 3-8 of the Operator Unit and Direct Support Maintenance Manual for more detail.)



**FUEL FILTER/
WATER SEPARATOR**

STEP 3:
If the fuel filter/water separator checks out to be fine, you should refer the trouble to unit level maintenance.

LESSON: PROCEDURES

Page 4 of 7

FRAME: WHITE SMOKE





Conclusions

Interactive virtual maintenance trainers offer numerous benefits:

- ◆ Lets training take place even if there is no equipment available
- ◆ More effective for task-based learning objectives
- ◆ Operationally deployable
- ◆ Very suitable to address TQG training challenges





Thank you! Questions?

For more information:

Erik Kaas

604-669-9973 ext 267

ekaas@ngrain.com

Case studies and Whitepapers:

www.ngrain.com

To order 3kW TQG Operator Course Computer-Based
Training CD:

www.pm-mep.army.mil/logistics/TrgMat.htm

Electric Drive Approach to Mobile Power Platforms

Oshkosh Truck Corporation

Nader Nasr
Chief Engineer
Advanced Products Group




On Board Vehicle Power

Responding to military's needs for power in the theater

- **Military Relevance**

- Increased mobility, power for onboard weapons
- Back up power for mission critical equipment
- Increased cargo space, reduced logistic footprint
- Power options for early entry forces, high speed mobility

ProPulse® Electric Drive System



- Benefits

- Large amounts of AC power available for export
- Energy storage is an option
- No batteries
- Zero voltage maintenance
- Improved fuel economy
- Enhanced packaging flexibility

HEMTT A3

- TACOM PM Heavy
- Improved fuel efficiency
- 100 kW Export power




MTVR OBVP

- ONR funded program
- 120 kW of export power
- Maintain vehicle performance



Advanced Heavy Hybrid Propulsion System

- DOE / NREL 3 yr program
- Target 2x fuel economy
- Validation vehicle / Waste Management



Homeland
Security



ARFF
Applications


HEMTT A3



HEMTT A3

Program Primary Objectives

- Export Power Capability - 100kW
- Improved fuel economy
- Advanced Load Handling System
light weight design
- Meet HEMTT
objective requirements



HEMTT A3

Key Technologies - Present

- Light weight modular design
- Diesel electric series hybrid
- Ultracapacitor Energy Storage
 - No batteries, life of vehicle design
- 100kW Exportable AC power
- Variable height independent suspension
- Multiplexed electrical system w/ advanced diagnostics
- C-130 unload capability
 - Enhanced Load Handling System (ELHS)




HEMTT A3

Testing Completed

- 12K miles off road - Nevada
- Vehicle Performance testing
 - PSD Aberdeen
- Export Power Performance
 - PSD Aberdeen
- Fuel Economy >20% improvement



HEMTT A3 – Power Module



Reconnect Panel

Export Power Interface

Exportable Power:

100 kW @ 480 V or 240 V 60 Hz

86 kW @ 416 V or 208 V 50 Hz

86 kW @ 120 V 50 Hz or 60 Hz

Export Power Vehicle Interface Screens

Export Power Controlled From Inside Cab

- Adjustable voltage (primary voltage and fine adjustment)
- Adjustable frequency (primary frequency and fine adjustment)
- AC contactor on/off (turning on and off output power)



Export Power

Platform System Demo, August 2006 Aberdeen Test Center

Tests Performed:

- Short Term Transient
 - Response MIL-STD-705C
 - Section 608.1
- Long Term Steady State
 - Stability MIL-STD-705C
 - Section 608.2
- Harmonic Analysis
 - MIL-STD-705C
 - Section 601.4



MTVR On-Board Vehicle Power Office of Naval Research

BAA – 04 – 011



MTVR

- Performance

- Oshkosh TK-4™ Independent Suspension
- 70% Offroad Mission Profile
- 7.1 ton payload cross country
- 15 ton payload primary and secondary roads



- MTVR Based Variants


- Cargo, Dump Truck, Wrecker, HIMARS Re-Supply Vehicle, Tractor, LHS (load handling system)

MTVR OBVP Program – ONR Objectives


- Provide vehicle integrated power source
 - 120 kW of military grade export power
 - 21 kW of power on the move
- Easy retrofit of existing MTVR vehicle
- Use host vehicle's diesel engine for both mobility and power generation
- Retain MTVR performance
- Minimize weight
 - 25 lb / kW Threshold
 - 20 lb / kW Objective



OBVP System Overview



Export Power Interface



- Pure diesel electric solution
- No Energy Storage
- Synchronous generator design

OBVP Design

- 300 kW traction generator used for vehicle driving and providing stationary export power
- Synchronous generator design
 - Clean military grade power
 - No need for power electronics or conditioning
- Cab display is used to initiate switch over, voltage and frequency adjustments and diagnostics



Export Power Performance

- 5 wire CAM style connection - Marine Corps request
- Meets requirements of tactical quiet generator
 - 120 kW of stationary export power
 - 21 kW of power on the move
- Exceeds objective requirements, achieved 19 lb/kW



Project Status

- OBVP build complete – January 2007
- Vehicle commissioning complete – March 2007
 - Basic driving functionality
 - 120kW stationary export power
- Deliver for Government durability testing – December 2007



Summary

- Oshkosh's diesel electric technology presents a unique and superior solution for large mobile power requirements
 - lb/kW
 - \$/kW
 - Power quality
 - No batteries
- Leverage developed ProPulse[®] system and components
- Provide simple wiring interface, and swift transition to exporting power



Far Reaching Benefits

- Commercial
 - Improved MPG
 - Lower emissions
 - Packaging flexibility
 - Disaster relief
 - Export power 100 kW+
- Defense
 - Lower logistics burden
 - Export power
 - 100 kW+ Mil spec AC power
 - Higher performance
 - Increased functionality
 - Improved MPG



ProPulse® Technology Demonstrator – Katrina Support

MEP Power Generation

Generation

Distribution



3 kW TQG
MEP – 831A
B0730



Commercial 25 kW
HMMWV Towable
Non-TQG
No TAMCN



60 kW TQG
MEP – 806 A/B – 60 Hz
MEP – 816A – 400 Hz
B1021 / B1016



15, 30, & 100 kW
MEPDIS
B0595 / B0600 / B0605



2 kW MTG
MEP – 531A
New to USMC



10 kW TQG
MEP – 803A – 60 Hz
MEP – 813A – 400 Hz
B0891 / B0921



30 kW TQG
MEP – 805 A/B – 60 Hz
MEP – 815A – 400 Hz
B0953 / B0971




100 kW Mil-Std
MEP – 007A/B/C
B1045 / B1046



100 kW TQG
MEP – 807A
Fielding in FY06

120 kW
Mil-Std
MTVR OBVP

100 kW Mil-Std
HEMTT A3 Option



Your Questions




On-Board Vehicle Power



Joint Service Power Exposition
25 April 2007



Session 12





Session 14


In no order of preference

- William Henrickson E-power
- Nadr Nasr Oshkosh Truck Co
- Stephen Cortese BAE Systems
- Tom Trzaska General Dynamics



Alternator Amperage Rating on HMMWV at 28 VDC

AMPS



Marine Corps On-Board Vehicle Power Systems for Legacy Military Vehicles



**Joint Service Power Exposition
2007**




On-Board Vehicle Power Systems

DC-AC Power Inverters
1500- 3000 watts



OBVP - Medium
30 kW Add-on HMMWV




**Retrofits for
In-Theater Assets**



OBVP - Small
5 – 8 kW (HMMWV)



OBVP - Large
120 kW (MTRV)





Vehicle Power Inverters



- **Requirement for DC-AC Power Inverter**
 - **18-32 VDC input**
 - **120 VAC, single phase output**
 - **1800 watts minimum output**
 - **Easily installed**
 - **Readily available / commercial based item**
- **Market Research and testing conducted**
- **GSA schedule showed adequate competition**
- **Solicited, competed, awarded in 2007**
- **Multi-year contract awarded to IRIS QP-1800**
 - **Inverter**
 - **Ruggedized carrying case**
 - **NATO cable connector**
 - **5600 articles planned**



On-Board Vehicle Power - Small




- Up to 400 Amps at 28 VDC needed
- Army has lead on retrofit kit
 - Vehicles in theater
 - DC power needs



- USMC will procure kits in 2007/2008
 - M1114, M1151, M1152 configurations
- Continuing to investigate / test inverters at higher power levels for AC power needs
- Future USMC vehicles will be procured with 400 Amp capacity (LVSR, MRAP)



Alternator Amperage Rating on HMMWV at 28 VDC






On-Board Vehicle Power Medium & Large Systems

- **Technology Demonstrations funded by Office of Naval Research**
- **HMMWV based system:**
 - **30 kilowatts stationary / 10 kilowatts on-the-move**
 - **Will be mounted on HMMWV M1123**
 - **Power output at 120/208 VAC, 60 hz**
 - **Two vehicles can be connected in parallel (60 kW output)**
 - **Can synchronize to MEP-805B generator**
- **MTVR based system:**
 - **120 kilowatts stationary / 20 kilowatts on-the-move / 3 kW transition**
 - **Mk 23 Truck**
 - **Power output at 120/208 VAC, 60 hz**
 - **Can synchronize to MEP-807A generator**
- **Vehicles will be delivered in 2007 for evaluation**



On-Board Vehicle Power - Medium


DRS Technologies Selected for Hardware Fabrication Phase






On-Board Vehicle Power - Large

OshKosh Selected for Hardware Fabrication Phase





OBVP Schedule (HMMWV & MTRV)






On-Board Vehicle Power Unique Applications

- **Power community continually requested to support other platforms**
 - **Tanks**
 - **Logistics Vehicle System**
 - **HIMARS**
 - **Light Armored Vehicle**
 - **Lightweight 155 Howitzer**
 - **Amphibious Assault Vehicle**
 - **Force Protection / Military Police**
- **Continued need for power for Jammers, Silent Watch, stationary applications**
- **Necessary when host vehicle incapable of power load, or host vehicle can not be retrofitted with larger alternator**
- **28 VDC Gensets needed (various sizes, ratings, restrictions)**



On-Board Vehicle Power - Unique



Watch FedBizOpps for solicitations

On-Board Vehicle Power



Joint Service Power Exposition
25 April 2007



Briefings

- **Oshkosh Truck Corporation**
 - Nadr Nasr
 - Oshkosh Truck's Electric Drive approach to Mobile Power Platforms
- **ePower LLC**
 - William Henrickson
 - 30 kW On-Board Vehicle Power for the HMMWV
- **General Dynamics Land Systems**
 - Tom Trzaska
 - On-Board Vehicle Power for the HMMWV and MRAP
- **BAE Systems**
 - Stephen Cortese
 - Power Management and Mission Capability Integration for HMMWV


On-Board Vehicle Power



Joint Service Power Exposition
25 April 2007



Session 12






Session 14

In no order of preference

- William Henrickson E-power
- Nadr Nasr Oshkosh Truck Co
- Stephen Cortese BAE Systems
- Tom Trzaska General Dynamics



Alternator Amperage Rating on HMMWV at 28 VDC



**2007 Joint Services
Power EXPO
23-27 April 2007
San Diego, CA**

Common Sense Approach to the Selection, Design/Fabrication, & Testing of Safe Operational Power Sources

Presented by
Robert Byrnes Sr.
Senior Battery Scientist
DHA Inc

Outline

Common Sense Approach

- Background
 - Bob's Terms/Advice
- Selection
- Design/Fabrication &
- Testing of Safe Power Sources
- Safety Testing of UltraLast AA Cells

BACKGROUND

MY PHILOSOPHY:

- **USE A BATTERY ONLY IF NEEDED**
- **KISS**
- **USE COMMON SENSE**
- **FEEDBACK REQUIRED**

EQUIPMENT PROBLEMS

THE CAUSES:

- ANTENNAES**
- BATTERIES**
- CONNECTORS**

BATTERY / PORTABLE EQUIPMENT

AS

BULLET / GUN

BATTERIES
THE “ACHILLES HEEL”
OF
TECHNICAL OPERATIONS

Battery Bob's Mottos:

“Trust but verify”

Ronald Reagan

“Test everything;
retain what is good.”

1 Thessalonians 5

PREMATURE BATTERY FAILURE CAN:

- **CREATE LIFE THREATENING SITUATIONS**
- **RESTRICT COLLECTION INFORMATION**

MOST BATTERY PROBLEMS ARE CAUSED BY PEOPLE WITH:

- LITTLE OR NO INFORMATION**
- MISINFORMATION**
- LACK OF TRAINING/EXPERIENCE**

BATTERY BOB'S TERMS/ADVICE

THE CAPACITY, ENERGY, POWER RELATIONSHIP

$E \neq P$

C (Ah)

$$E_{Wh} = \underbrace{V_L(V)}_{\substack{\text{Power} \\ P_L(W)}} \times \underbrace{I_L(A)}_{\substack{\text{Capacity} \\ C(Ah)}} \times t(h)$$

$P_L(W)$

L - load

THE CAPACITY, ENERGY, POWER RELATIONSHIP SYMBOLS

E = Energy (Work) (Wh)

P = POWER (W)

V = Voltage (V)

C = Capacity (Ah)

I = Current (A)

t = TIME (h)

L = load

AVOID BATTERY PROBLEMS BY:

- **Checking Mfgr's Spec Sheet**

Note: No Standard Spec Sheet

- **Buying from High Volume Stores**
- **Knowing Date Codes**
- **Screening (Primary) OCV & CCV**
- **Screening & Matching (Secondary)**
- **Using Common Sense**

BATTERY BOB'S AXIOMS:

- THERE IS NO IDEAL CELL!**
- ALL COMMERCIAL CELLS ARE ALWAYS UNDER DEVELOPMENT.**
- KEEP BATTERY STASHES ROTATED & AVAILABLE TO ALL.**
- DON'T MIX BATTERIES w/ BULLETS, COINS, or OTHER METAL ITEMS!**

This is what happens if you do.

Name	Size	Chemistry	Temp °C	Temp °F
ECO	AA	Li/SOCl ₂	113-121	235-250
ECO	AAA	Li/SOCl ₂	94-106	201-223
Sanyo	CR-2N	Li/MnO ₂	64-70	142-158
Tadiran	TL-2200 C	Li/SOCl ₂	88	190
Tadiran	TL-2300 D	Li/SOCl ₂	70-90	158-194
Blue Star	D	Li/MnO ₂	50-116	122-241
Panasonic	BR-2/3A	Li/CF	149-151	300-304
Sanyo	HR-AA	Ni/MH	108-115	226-239
Sanyo	HR/4/3A	Ni/MH	73-75	163-167
Duracell	MX1500 AA	Zn/MnO ₂	100	212
Sanyo	CR-2	Li/MnO ₂	76	169
Duracell	DL2/3A	Li/MnO ₂	91-93	196-199
Duracell	Ultra 123	Li/MnO ₂	78-93	172-199
Duracell	LM 123A	Li/MnO ₂	71-84	160-183

SECONDARY BATTERY CHEMISTRIES:

- **Nickel Cadmium-store discharged.**
- **Lead Acid-store charged.**
- **Nickel Metal Hydride-store discharged.**
- **Li-Ion-store 50% charged.**

- Check out the equipment using the selected cell or battery instead of a DC power supply.**
- The operation of equipment using a DC power supply may differ from the operation using other power sources.**
- Where possible simulate the actual use regime as closely as possible.**

SELECTION

IF YOU WANT A BATTERY FROM ME PICK ONLY TWO BELOW:

•QUICK

•CHEAP


•SMALL


•RELIABLE

Basic Tips for the User in the Selection of Batteries for Operational Use:

- Define your need as fully as possible.
- There is no ideal power source.
- Don't make the choice of a power source a last minute decision.
- Keep the power source design simple.

TYPICAL BATTERY PACKS





BATTERY

DESIGN/FABRICATION

CONSIDERATIONS

**IF I DESIGN A BATTERY,
SHOULD IT BE,
A PRIMARY OR
A RECHARGEABLE
BATTERY?**

**IF I DESIGN A BATTERY,
CAN I FABRICATE IT
SAFELY?
IN TIME?**

**IF I DESIGN A BATTERY,
CAN I SHIP IT
SAFELY?
LEGALLY?
IN TIME?**

**FOR LITHIUM BATTERY
SHIPMENT QUESTIONS
SEE YOUR
SHIPPING OFFICER
FOR GUIDANCE**

**WHAT DO I DO
WITH THE BATTERY
AFTER I HAVE
FINISHED WITH IT???**

**CAN I DISPOSE OF IT
SAFELY?
LEGALLY?**

**FOR BATTERY
DISPOSAL QUESTIONS
SEE YOUR
SAFETY OFFICER
FOR GUIDANCE**

APPLIED BATTERY DESIGN

SIMPLE APPLICATIONS

MAJOR DESIGN CONSIDERATIONS

- 1) VOLTAGE
- 2) LOAD CURRENT
- 3) BATTERY LIFE
- 4) SIZE AND WEIGHT
- 5) ENVIRONMENTAL REQUIREMENTS
- 6) SAFETY VENTING
- 7) SAFETY FUSING
- 8) LAYOUT OF PACK TO REDUCE IR LOSSES
- 9) LAYOUT OF PACK TO REDUCE I^2R LOSSES
- 10) DIODE ISOLATION
- 11) CONNECTORS
- 12) LOW VOLTAGE CUTOFF FOR SOME Li CELLS

MAJOR DESIGN CONSIDERATIONS

VOLTAGE

- The devices with which the batteries are used have limitations on the maximum and minimum voltages between which they will work properly.
- The devices may also have limitations on the maximum voltage beyond which they will be permanently damaged.
- There might also be limitations on the minimum voltages below which they will have to be “reset”.
- Does the device perform consistently over the voltage range?
- Is there a preferred voltage?
- Are there multiple voltages required in one pack?

MAJOR DESIGN CONSIDERATIONS

VOLTAGE

- Batteries have maximum, minimum, and typical voltages. How do these match with the device requirements?
- If the battery's operating voltage range does not match the requirements of the device being powered, an electronics package may be needed to regulate the voltage. Otherwise, the full capacity of the battery might not be useable.
- An electronics package might also be needed to control the charging of the battery.

MAJOR DESIGN CONSIDERATIONS

CURRENT

- Affects the life of the battery
- Affects the size of the wiring in the pack and connectors
- Continuous high load current may have a thermal impact
- What is the nature of the current? Is it pulse? Continuous? A mixture of both?

MAJOR DESIGN CONSIDERATIONS

CURRENT

PEAK CURRENT

- The voltage and capacity available from a battery is affected by the discharge current.
- As the current increases, the voltage decreases.
- As the current increases, the amount of capacity that the battery can deliver decreases.
- At some currents, the battery will not produce a usable voltage.

MAJOR DESIGN CONSIDERATIONS

CURRENT

PEAK CURRENT

- EVALUATE PRIMARY vs. SECONDARY
- Primary - good energy density
(energy measured in Wh)
- Secondary - good power density
(power measured in watts)
- Hybrid - utilize the best characteristics
of each *(but with added complications)*

MAJOR DESIGN CONSIDERATIONS

CURRENT

AVERAGE CURRENT

- The number of Ampere-hours that are required is determined by the average current consumed by the device being powered.
- If an average current is not known, it can be calculated from the individual loads, the currents during all operating conditions, and the duty cycle.

MAJOR DESIGN CONSIDERATIONS

LIFE

How Long Before The Battery Can Fail?

- *Shelf Life*
 - How long must the battery be available before the device operating time starts?
- *Operating Life*
 - How long must the battery power the device?
- *What about End of Life?*
 - How Will The Battery Be Shut Down?

MAJOR DESIGN CONSIDERATIONS

LIFE

SHELF LIFE

- Effects of self discharge on battery life.
- Passivation - high initial pulse need.
- Cell seals - different seals start to leak at different times.
- Storage time before operation.
- Battery maintenance during storage.
 - Some chemistries need to be kept charged lead acid
 - Some chemistries have “memory effects”

MAJOR DESIGN CONSIDERATIONS

LIFE

OPERATING LIFE

- Effects of discharge current on useable battery capacity.
- Effects of temperature on useable battery capacity.

MAJOR DESIGN CONSIDERATIONS

SIZE & WEIGHT

CAN THE BATTERY BE CONCEALED?

- Will the weight give it away? *Too heavy or too light?*
- Will the size give it away? *Too big?*
- Will it fit in the electronics package? *Wrong shape?*
- Certain chemistries swell upon discharge.
- If a cell should go bad, is there enough capability left in the other strings to handle the mission?
 - Often a trade-off of size/weight versus redundancy.

MAJOR DESIGN CONSIDERATIONS

ENVIRONMENTAL REQUIREMENTS

- The performance of a battery is affected by the environment in which it will be used.
- Temperature has an impact on the battery.
 - Useable capacity.
 - High power pulses.
 - Function & Survivability
- The performance and battery design can be affected by other factors
 - Will the battery need to be moved?
 - How will it be moved
 - Road vehicle, Aircraft - Passenger/Cargo, Camel, Etc.
- Worldwide use? Indoor use? Outdoor? Tactical? Jungle? Desert? Snow? Salt fog?

MAJOR DESIGN CONSIDERATIONS

THINGS TO PONDER

- SAFETY VENTING
 - If a cell should vent, a path for the escaping gases needs to be provided
 - How does this impact on the mechanical design of the electronics package?
- SAFETY FUSING
 - Depends on cell chemistry and/or # of cells

MAJOR DESIGN CONSIDERATIONS

PACK LAYOUT TO REDUCE LOSSES

- HEATING LOSSES = I^2R
- VOLTAGE LOSSES = IR
 - Length and size of wiring in the pack
 - Cell interconnects and location
- DIODE ISOLATION
 - Parallel strings of cells need to be diode isolated
 - Voltage drop across diodes
- CONNECTORS
 - Size and type
 - Wire leads?

MAJOR DESIGN CONSIDERATIONS

REFINING THE CHOICES

- Verify cell selection will meet Operational Requirements
- **Electrical**
- **Environment**
- **Size and Weight**
- **Transportation**
- **Delivery Schedule**
- **Redundancy**
- **Reliability**
- **Cost**
- **Safety**
- **Further trade-offs**

MAJOR DESIGN CONSIDERATIONS

CELL SELECTION

NOT ALL CELLS PERFORM THE SAME

- This is true for:
 - Different chemistries
 - Same chemistries, but different manufacturers
 - Same chemistry and manufacturer, but different sizes
 - Same chemistry and manufacturer, but different manufacture date
- Not all cells are equally predictable or reliable in their performance.

PERFORMANCE RELATIVE TO MODEL

Different versions of cells give different performance characteristics

Even if they are the same chemistry, manufacturer and size

PERFORMANCE RELATIVE TO MANUFACTURING DATE

Cell manufacturers change the way cells are built. A cell built one year may be different from another year.

There are many reasons:

Cost/Profit

Competitive performance

Build-to-build variation

PERFORMANCE RELATIVE TO SIZE

**Different size cells give different
performance characteristics**

**Even if they are the same chemistry,
manufacturer and general construction
(i.e. prismatic, bobbin, spiral wound).**

PERFORMANCE RELATIVE TO CHEMISTRY

Different chemistry cells give different performance characteristics.

Even if they are the same size, the chemistry has different characteristics associated with it.

There may be construction differences as well. These may be needed by the nature of the chemistry (Different materials in the can, etc.)

PERFORMANCE RELATIVE TO CUT-OFF VOLTAGE

The amount of Capacity that a cell can deliver can be greatly affected by how low a voltage that the cell can be discharged and still do useful work.

This can be affected by both discharge rate and temperature.

Low voltage cutoff a must for some high powered lithium batteries to prevent reversal.

MAJOR DESIGN CONSIDERATIONS

CELL AVAILABILITY

- **Forward Deployed**
- **Warehouse**
- **Contractor Stockpile**
- **Commercial Purchase**
- **Special Purchase**

MAJOR DESIGN CONSIDERATIONS

CELL LEVEL TESTING

- Qualification Testing
- Lot Acceptance
- Screening
- Specialized testing
 - Environmental
 - Mission Profile
 - Safety

MAJOR DESIGN CONSIDERATIONS

BATTERY LEVEL TESTING

- Environmental
- Safety
- Mission Profile
- Qualification
- Screening

BATTERY PROGRAM CHECK LIST

ELECTRICAL REQUIREMENTS

- Max. No Load Volts: _____ V
- Steady-State or No-Pulse Load Data:
Max Volts: _____ V
Min. (CUTOFF) Volts: _____ V
Current at Max. Volts: _____ V
Current at Min. Volts: _____ V
- Pulse Load Data (IF APPLICABLE):
Duration of Pulse: _____ msec
Frequency of Pulses: _____
Max. Volts _____ V
Min. (CUTOFF) _____ V
I @ Max. Volts (PEAK): _____ mA
I @ Max. Volts (AVE.): _____ mA
I @ Min. Volts (PEAK): _____ mA
I @ Min. Volts (AVE.): _____ mA
- Duty Cycle: _____ Hrs On-Off/Week
- Service:
Actual On Time (MEDIAN): _____ h
Electrical Capacity: _____ Ah
Storage Time Prior to
Use (MAX.): _____ h
Total Unit Life (Max.) _____ h

PHYSICAL REQUIREMENTS

- Size if Prismatic:
Length: _____ mm/in
Width: _____ mm/in
Height: _____ mm/in
- Size if Cylindrical:
Diameter: _____ mm/in
Height: _____ mm/in
- If Irregular Size, Specify: _____
- Weight: _____ g/oz
- Position of terminals (TOP OR SIDE): _____
- Submit Drawing (IF APPLICABLE) of Device Housing Cells/Battery Pack. (USE BACK OF SHEET FOR DRAWING.)

ENVIRONMENTAL REQUIREMENTS

(Note: The electrical requirements presume a temperature of 24 °C (75 °F). It is desirable to specify the electrical requirements at the maximum and minimum temperatures expected.)

- Storage:
Expected Temp. Range: _____ °C/°F
Expected Avg. Temp.: _____ °C/°F
Expected Humidity Range: _____
Expected Avg. Humidity: _____
- Use:
Max. Temp: _____ °C/°F
Min Temp.: _____ °C/°F
Expected Temp.: _____ °C/°F
Expected Humidity Range: _____
Expected Avg. Humidity: _____
- Shock and Vibration: _____
- Applicable Specifications: _____
- Other: _____

OTHER REQUIREMENTS

- Reliability: (What Minimum Capacity is Desired at What Confidence Level?)

- Battery Disposal: _____
- External Signature: _____
- Transportation: (Very Important For DOT Regulated Power Sources.) _____
- Delivery Schedule (Include Testing): _____
- Operation Scenario(s) – (Be As Specific as possible. Use separate sheet for details if necessary. Classify appropriately.) _____

FOR RECHARGEABLE POWER SOURCES ONLY

- Desired Charge-Discharge Cycles: _____
- Depth of Discharge (DOD) _____ %
- Minimum Charging Time: _____ h
- Normal Charging Time: _____ h
- Charging Modes:
Constant Current: _____
Current Trickle: _____
Constant potential: _____
Constant Potential (FLOATING): _____
- Types of Use:
Frequent: _____ h/week
Standby: _____ h/week
- Charging Temp Range: _____ °C/°F
- Other Charging/Charger Info:

MSDS

Material Safety & Data Sheet
Important if the cells in your
battery go south.


ULTRALAST
Li/FeS₂
AA CELLS

Circa 2006


Background Info

Chinese made AA Lithium Iron Disulfide (Li/FeS₂) cells were shipped to the US and sold under the Ultralast label. The Ultralast label was very similar in appearance to the label Energizer uses for its Li/FeS₂ AA cell. Comparative Safety Testing was done on both the Energizer and Ultralast Li/FeS₂ cells.

Introduction



Introduction



UN TESTING
of
Energizer
&
Ultralast
AA Cells

UN TEST #5:

External Short Circuit Test

- Six (6) undischarged Ultralast cells were subjected to a short circuit test of less than 100 milliohms while maintained at 55 °C.
- The output voltage, current, and skin temperature were continuously monitored during the test.
- The short circuit condition was maintained for a minimum period of one (1) hour after the cell skin temperature had returned to 55 °C. The cells were observed for an additional period of six (6) hours.

UN Test #5:

External Short Circuit Test Results

- The highest maximum short circuit current was 10.47 amps, while the lowest was 6.54 amps.
- Two cells exhibited fire, with flames emanating from the positive end vent holes, the first cell at 2 hours, 31 minutes, and the second cell at 3 hours, with enough pressure release to pop the oven door open, and temperatures exceeding 170 °C (i.e. 341 °C, and 355 °C). The other four (4) cells oozed a tan colored material from the positive end, and two (2) of them reached 134 C.

Results-Comparison

UN Test #5: External Short Circuit Test

- The Energizer L 91 cells, (with 10 cells tested under the same conditions), reached a highest maximum short circuit current of 14.13 amps, while the lowest was 12.57 amps.
- The highest skin temperature reached by any of the cells was 97 °C. None of the cells exhibited fire, rupture, disassembly, or temperature exceeding 170 C.

UN TEST #6: Impact Test

A Lot of Reaction #4 Cell.

Five (5) undischarged Ultralast cells were subjected to the United Nations Impact Test (Test # 6)

The cell under test rested upon a Pine wood “flat surface”, measuring 5 - 1/2 inches X 5 - 1/2 inches X 3/4 inch thick. A 5/8 inch diameter hardwood dowel “bar” rested upon the center of the cell, such that the “bar” was perpendicular to the longitudinal axis of the cell and parallel to the “flat surface”. A 20 pound mass was allowed to fall a distance of 24 inches before impacting the “bar”.

UN TEST #6: Impact Test Cont'd.

Upon impact, and for a six (6) hour observation period thereafter, the first three (3) cells demonstrated no evidence of fire, disassembly, or temperature exceeding 170 °C. The highest temperature achieved by any of those cells was 27 °C.

UN TEST #6: Impact Test Cont'd.

The fourth (4th) cell, at 30 seconds after impact, reacted with the ejection of the positive end cap, followed by the violent expulsion of fire and burning material from the positive end (some of which penetrated the aluminum screen), thus, meeting the definition of disassembly. During the period of burning, the cell skin temperature rose to 601 °C.

The fifth (5th) cell, upon impact, and for a six (6) hour observation period thereafter, reacted the same as the first three cells.

UN TEST #6: Impact Test

Cont'd.-Comparison

Previously, the Energizer L91 cell had five (5) cells subjected to the Impact Test.

Upon impact, and for a period of six (6) hours thereafter, there was no evidence of fire, or disassembly, and the maximum case temperature achieved by any of the cells was 95 °C (maximum allowed = 170 °C). Although the end caps were dislodged, they did **not** penetrate the aluminum screen. Therefore, the cells did **not** meet the definition of disassembly.

UN TESTS #5 & #6:

Conclusions:

- Ultralast Li/FeS₂ cells failed UN Tests #5 & #6.
- Energizer Li/FeS₂ cells did not fail UN Tests #5 & #6.
- Cells which do not meet UN Tests should not be imported into the US for sale.
- The Ultralast AA Li/FeS₂ cells are no longer being sold in the US but other Chinese AA Li/FeS₂ cells are available on the Internet.

Note: 49 CFR 171.12 (a)

Battery Importers

“Each person importing a hazardous material into the US shall provide the shipper and the forwarding agent at the place of entry into the US timely information on the requirements of the regulations that apply to the shipment.”

SAFETY TESTING
VIDEO of
ULTRALAST
Li/FeS₂
AA Cells

Contact Information



David Hale Associates, Inc.
1785 Mt. Harmony Road
Owings, MD 20736

Robert B. Byrnes Sr.
Senior Battery Scientist

703-357-0686 (Cell)

703-632-6515 (FAX)

Email: RBYRNES3@VERIZON.NET

DOD Project Manager Mobile Electric Power



Mobile Electric Power for *Today and Tomorrow*

Joint Service Power Expo
25 April 2007

Paul Richard
Acting DOD Project Manager Mobile Electric Power




Presentation Outline

- ★ PM MEP Organization/Systems
- ★ Requirements & Challenges
- ★ Major Initiatives
- ★ Technology Thrusts






PM MEP Organization



USAF Position
to be filled May 2007



Mobile Electric Power History



DFAR Requirement for PM MEP Approval for Non-standard Power Equipment



Military vs. Commercial

No Commercial Generator Set Meets Military Worldwide Requirements*

All Tactical Electric Power Generator Sets are Made from Commercial Components

Critical Military Features

- Diesel/JP-8 (DoD Policy)
- Operate at all Environmental Extremes
- Excellent Power Quality
- High Reliability
- Battlefield Mobility
- Ruggedized
- 24 Volt
- Enhanced Battlefield Survivability
 - NBC
 - IR
 - Aural
 - EMP Hardening
- Rated Power at Altitude
- Organically Supported



Less Cost
Less Weight
Less Capable



* Market Surveys; 1989; 1999, 2003



Mobile Electric Power Managed Items

Small Sets

- 2kW Military Tactical Generator, Manportable/Skid Mounted, Diesel/JP8 Fueled, AC(60Hz) and DC(28VDC)
- 3kW Tactical Quiet Generator, Skid Mounted, Diesel Fueled (60 Hz and 400Hz)



Medium Sets

- 5kW, 10kW, 15kW, 30kW, and 60kW, Skid Mounted, Diesel Fueled Tactical Quiet Generator, 60Hz and 400Hz
- AMMPS – Advanced Medium Mobile Power Sources



Large Sets

- 100kW and 200kW Tactical Quiet Generator (TQG), Skid Mounted, Diesel Fueled, 60Hz
- 840kW Deployable Power Generation and Distribution System (DPGDS), Diesel Fueled



Power Unit/Power Plant (PU/PP)

- Trailer Mounted Tactical Quiet Generators in the 3kW, 5kW, 10kW, 15kW, 30kW, 60kW, 100kW, and 200kW Power Ratings.
- 20 Different Models That Use 4 Different But Standardized TACOM Trailer Models



Power Distribution Illumination System Electric (PDISE)

Man-portable, Reliable, Modular, Quick Assembly Standardized Electrical Management and Distribution System Components

- 40 AMP/PHASE DISTRIBUTION SYSTEM
- 60 AMP DISTRIBUTION SYSTEM
- 100 AMP/PHASE FEEDER SYSTEM
- 200 AMP/PHASE FEEDER SYSTEM
- UTILITY RECEPTACLE AND LIGHTING KIT



HI-POWER

Hybrid Electric Intelligent Power Management

Develop a Tactical Hybrid-Electric Power System for use at Forward Operating Bases to minimize logistics fuel consumption related to power generation.



Improved Environmental Control Units (IECU)


New Generation of ECUs Utilizing Zero Ozone Depleting Refrigerants. Ruggedized Form, Fit, and Function Replacement Systems with Embedded Diagnostics.

9K, 18K, 36K, and 60K BTUH sizes.



***Requirements
and
Challenges***

Department of Defense Tactical Electric Power Requirements



<u>Size</u>	<u>Army # Req'd*</u>	<u>% Army Total</u>	<u>Qty Fielded</u>	<u>% Size Fielded</u>
2kW	9,576	14%	8,609	90%
3kW	19,122	29%	9,901	52%
5kW	14,779	22%	9,143	62%
10kW	12,001	18%	9,189	77%
15kW	4,370	7%	3,186	73%
30kW	3,085	5%	2,623	85%
60kW	2,950	4%	1,826	62%
100/200/DPGDS	568	1%	25	4%
	66,451		44,502	67%

* BOIP05

2kW thru 840kW Generator Sets

Requirements

Army	66,451
Navy	1,540
Air Force	13,340
Marines	6,552
Total	87,883

Fielded

	MIL-STD	TQG
Army	21,949	44,502
Navy	676	864
Air Force	3,451	9,889
Marines	0	6,552
Total	26,076	61,807

Data Thru Feb 07

Current Army Priorities

- GWOT
- TOC Central Power
- Modularity
- Modernization

MIL-STD = Military Standard
First Generation Gasoline and Diesel Engine Generator Sets

TQG = Tactical Quiet Generator
Second Generation, Modernized, Diesel Engine Generator Sets



Tactical Electric Power Families / Generations

Department of Defense Standard Family of Mobile Electric Power Generating Sources

MIL-STD Military Standard

Aging, First Generation DOD Standard Family of Mobile Electric Power Generating Sources

- 37 Generator Set Models
- Sizes 0.5kW Through 750kW
- Gasoline, Gas Turbine, and Diesel Engines



Average Annual Cost Per Generator **\$13,347**

MIL STD (Military Standard)

TQG

Tactical Quiet Generators

Modernized, Second Generation DOD Standard Family of Mobile Electric Power Generating Sources

- 18 Generator Set Models
- Sizes 2kW Through 920kW
- All Diesel Engines
- R&D On-going for Some Models



Average Annual Cost Per Generator **\$9,582**

TQG (Tactical Quiet Generator)

Next Generation Power Sources

AMMPS

Advanced Medium Mobile Power Sources

- 12 Generator Set Models
- 5kW through 60kW Sizes
- Procurement 2009

LAMPS

Large Advanced Mobile Power Sources

- 100kW through 1mW Sizes
- Procurement TBD

STEP

Small Tactical Electric Power

- Less Than 3kW Sizes
- Procurement ~2013

- Leverage Commercial Technologies
- Minimize Number of Sizes and Models
- Use Proven Technologies
- Replace Entire DOD Generator Fleet Approximately Every 15 Years
- Maximize Competition

AMMPS Projected Average Annual Cost Per Generator **\$8,143**

Next Generation

1965 1970 1975 1980 1985 1990 1995 2000 2005 2010 2015 2020 2025

Improved Environmental Control Units (IECU) Requirements

IECU Procurement Quantities

9K (115V, 1PH, 50/60Hz)	3,180
18K (230V, 1PH, 50/60Hz) and (208V, 3PH, 50/60Hz)	3,767
36K (208V, 3PH, 50/60Hz)	<u>1,577</u>
Army Total	8,524
<hr/>	
60K (208V, 3PH, 50/60Hz)	Army 4,960
	Air Force <u>787</u>
Total	5,747

Unvalidated Requirements

- TOCs
- JNN
- Patriot
- UAVs
- Others

IECU Challenge

(Improved Environmental Control Unit)

- Approximately 17,800 MIL-STD ECU Systems currently fielded in sizes 9k, 18k, 36k and 54k BTUH
- Current ECUs do not comply with the Clean Air Act 2010 Mandate for Ozone Depleting Refrigerants
- IECUs will comply with EPA Clean Air Act
- Only 60k BTUH IECU currently funded
- 9k, 18k, 36k BTUH IECUs funded for development
 - Procurement funding to be added in FY10-15 POM



Electronic systems will overheat and fail without the critical cooling ECU's provide

Major Initiatives

TOC Central Power & Power Assessment

What it Is

Program to Assess and Optimize the use of Tactical Electrical Power Production and Distribution in the Field

What it Does

- Significantly Reduces Logistics Footprint
- Increases Operational Availability
- Reduces Fuel Consumption
- Reduces Transportability Requirements
- Determines Most Efficient Use of Resources

**Consolidates
Power Sources in TOCs**

**Provides Back-up for
Mission Critical Systems**


**Decreases
Logistics Footprint
of TOCs**



“Right Number and Right Size Generator Sets”


4ID DMAIN As Seen

- Legend**
- TQG (3)
 - Commercial Generator (2)
 - Commercial Self-powered ECU (14)
 - ◆ PDISE (1)
 - ◆ Commercial PDU (36)



4ID DMAIN
Recommendation

- Legend**
- TQG (3)
 - Commercial Generator (2)
 - Commercial Self-powered ECU (14)
 - ◆ PDISE (11)
 - ◆ Commercial PDU (0)



Power Assessment Benefits and Savings

Optimized power grid for:

- Soldier safety
- 24/7 operation of mission-critical equipment
- Better reliability, supportability and readiness
- Minimum footprint and increased transportability
- Reduction of Non-standard Commercial Hardware
- Organic Support by Soldiers

When Central Power Design Applied to 4ID Main TOC MTOE,
Savings are:

- | | |
|-------------------------------------|-------------------------------|
| • Generator Sets | 11 |
| • Fuel Reduction | ~ 200 gal/day |
| • Weight | 23,353 lbs (~ 12 tons) |
| • Volume | 4,735.2 cu ft |
| • Reduced Pintle Requirement | HMMWV 5
FMTV 3 |
| • First Year Savings | \$384,146.35 |

Not Including Savings for Reduced Contractor Field Support




HI-POWER

Hybrid Electric Intelligent Power Management

3kW Hybrid Electric System



SkyBuilt Hybrid Electric System




Develop a tactical hybrid-electric power system for use at Forward Operating Bases to minimize logistics fuel consumption related to power generation.

Objectives Of HI-POWER Program

- **Develop tactical transportable hybrid electric power sources**
 - ❖ To reduce logistics fuel consumption related to power generation
 - ❖ To meet niche operational capabilities for remote reliable power
 - ❖ Minimizes logistics or operational impacts
- **Validate HI-POWER concept**
 - ❖ Evaluate real-world utility (cf, REF SkyBuilt and USMC DREAM)
 - ❖ Identify and document requirements for systems (TRADOC)
 - ❖ Establish analytical business case (cost-benefit analysis)
- **Develop strategy that**
 - ❖ Establishes HI-POWER as Joint Standard Mobile Electric Generating Source (IAW DoDD 4120.11)
 - ❖ Supports current military and commercial protocols and standards (esp., MIL STD 1332B)
 - ❖ Provides opportunities for near-term spiral insertions for quick-reaction capabilities (if required)
 - ❖ Ensures supportable systems within the military logistics system


HI-POWER Program Acquisition Summary



Acquisition Development Strategy

- Two step process –technology validation & system development
- Tech Dev to validate technologies and integration strategies
- Competitive shootoff (“fly before buy”) strategy in SDD
- Spiral Development to accelerate quick reaction to field
- Ensure standardized, logistically supportable, Joint Service capable systems

DOD Acquisition Lifecycle Model



Technology Thrusts

Technology Thrusts

Where We Need To Push the Envelope

Easier Deployment

(More per aircraft/ship)

- **Less Weight per kW**
 - Increased power density
 - Lightweight materials
- **Less volume per kW**
 - Increased power density
 - Improved packaging/integration

Easier Sustainment

(Less supplies and manhours needed to operate)

- **Less Fuel Consumption**
 - Increased efficiency
 - Better load management/power distribution
- **More Reliable**
 - Fault tolerant design
 - Embedded prognostics/diagnostics
 - Less maintenance hours

Less Life Cycle Cost

- **Less Initial Cost**
 - Increased use of commercial components
 - Modularity
- **Less Fuel Consumption**
- **More Reliable**
- **Longer Life**
 - Improved reliability
 - Improved efficiency

Improved Capability

- **Less Weight**
 - Easier/faster to move
 - Easier to move off road/non-prepared positions
 - More vehicle payload in APU/trailer applications
- **Less Noise**
 - Use further forward
 - Less communication/rest interference
- **Less Fuel Consumption**
 - Runs longer on same fuel
 - Fewer fuel trucks doing convoys/fewer soldier manhours spent refueling
- **More Reliable**
 - Runs longer between shutdowns
 - Prognostics predict impending shutdowns; allows scheduled shutdown versus unexpected shutdown
- **Less than 1kW**
 - New units to go where power was previously not available
 - Manportable

We are relying on Industry to bring innovation forward.

Potential Technologies

- **Advanced High Speed Diesel Engines**
- **Advanced Environmental Control Systems & Combined Power / ECU Systems**
- **Power Electronics & Digital Controls**
- **Composite Materials & Lightweight Alloys**
- **Diagnostic & Prognostic Controls**
- **Microturbines**
- **Battery Technology**
- **Stirling Engines**
- **Direct Energy Conversion**
 - Thermophotovoltaics
 - Fuel Cells
- **Tactical Inverters (Vehicle & Shelter)**
- **Permanent Magnet Alternators**
- **On-Board Vehicle Power**



**Technologies Must Satisfy
Operational Needs**



DoD Project Manager Mobile Electric Power Information / Points of Contact

Phones

Project Management
Office

DSN: 654-3162

COM: (703) 704-3162

FAX (703) 704-3257



Mailing Address

Project Management Office

Project Manager –
Mobile Electric Power
10205 Burbeck Road
Fort Belvoir, VA 22060-5863

E-mail Addresses

Mr. Richard paul.richard@belvoir.army.mil

Acting Project Manager - Mobile Electric Power

Mr. Coady alan.coady@belvoir.army.mil

Acting Deputy PM

LtCol Bowers thomas.s.bowers@belvoir.army.mil

Product Manager (Small Generator Sets)

LTC Kelleher john.kelleher@belvoir.army.mil

Product Manager (Medium Generator Sets)

LTC Kelleher john.kelleher@belvoir.army.mil

Product Manager (Large Generator Sets)

Dr. Parrish eric.parrish@belvoir.army.mil

Chief Engineer

Mr. Coady alan.coady@belvoir.army.mil

Chief, Logistics Division



www.pm-mep.army.mil





PM-MEP *Home Page*

- DOD Directive 4120.11
- TQG Technical Data
- “What’s New”
- Safety of Use Messages
- Organization and Points of Contact
- DOD Generator Master Plan
- Manuals, Tools, PLL/ASL
- PS Magazine Articles
- References
(i.e. MIL-STDs, ARs, etc.)

MORE !



www.pm-mep.army.mil


Comments / Recommendations Solicited

Back Up

Joint Service Power Expo

April 2007

Tactical Electric Power Acquisition Strategy



15 Year Buyout Plan

PROS (Benefits):

- Maintain hot production base for wartime conditions
- Supports Industrial Base by leveling requirements
- Maintains Only Two Generations of Hardware in the field at one time
- Reduces O&S Costs
- Maintains Average Age of Fleet at Economic Useable Life Reducing O&S Costs
- Supports Continual Modernization of Army TEP Fleet

CONS:

- Keeps Technology in Field for 30 year period

Near Term Business Opportunities

◆ Distribution Illumination System Electric (DISE)

- Solicitation Release
3Q – 4Q FY07



◆ Switchboxes for Power Units / Power Plants

- Solicitation Release
1Q FY08


◆ Improved Environmental Control Units (IECU)

- 9k, 18k, 36k, BTUH sizes
- Solicitation Release 1Q FY08






Tactical Electric Power Development Strategy



Improved Environmental Control Unit (IECU) Development Strategy



Iraq/Afghanistan Lessons Learned

Generator Sets and ECUs

- Power distribution – training/equipment/procedures
- High temperature operation critical
- Sand/dust impacts
- Solar loading (especially on displays)
- Preventive maintenance paramount (but not being done)
- Inadequate parts support – sluggish, but improving
- Requirement for systems assessments
- Military vs. commercial – warfighting vs. base operations

Environmental Impacts & MEP Actions

- TQG Master Switch –
Developed Dust Proof Form, Fit, and Function Replacement Master Switch
- TQG Computer Interface Module (CIM)
Overheating Failures Resolved by Operational Techniques to Reduce Effects of Incoming Solar Radiation (Insolation)

Analog

Digital



CIM

Designed to Operate in All Environmental Conditions



Medium Power Sources

LTC John Kelleher

Product Manager



Description-

5kW, 10kW, 15kW TQG: Primary Power Source on the Battlefield (TOCs, C4ISR, etc.)

CHARACTERISTICS/PERFORMANCE:

Fuel Diesel/JP-8
 Noise 70 dBA @ 7m
 Reliability 600 hrs MTBF
 Operating Temp -25° to +120°F
 Altitude Full Rating @ 4000ft/95°F

PRIME CONTRACTOR:

5, 10, 15kW: DRS - Fermont,
 Bridgeport, CT
 30 & 60kW: L3, Tulsa, OK

	<u>5kW</u>	<u>10kW</u>	<u>15kW</u>	<u>30kW A/B</u>	<u>60kW A/B</u>
Weight (lbs)	888	1182	2124	3006/3040	4063/4200
Fuel Consumption (gal/hr)	0.56	0.97	1.44	2.43/2.60	4.51/4.70
Size (Cu ft.)	34	41	77	88/88	103/103

ORD - Feb 88

Benefits/Capabilities

- 5 – 60 kW TQG
- Multi-Fuel
- Reduced Noise and IR Signature Levels
- More Reliable
- Less Weight
- HAEMP Protected
- Reduced Fuel Consumption
- Total Package Fielding (Organically Supportable)
- Power Units/Power Plants
- Less Cost (Procurement, Support Cost)
- Transportable

From: Required Operational Capability (ROC)

Requirements Documents

**ROC and O&O Plan for the Commercial Generator Sets and Assemblages (CGSA) –
 25 February 1988, Revised 10 July 1995**

Milestones Achieved/Scheduled

	<u>5,10,15kW and 30 & 60kW A Models</u>	<u>30 & 60kW B Models</u>
Milestone III	July 1992	Aug 2000
Type Classification	July 1992	Aug 2000
Production Release	July 1992	Aug 2000
Materiel Release	Nov 1993	May 2001
FUE Fort Bragg	Dec 1993	
Europe		Sep 2001

10 yr Production Contract (FY97 through FY07)

Advanced Medium Mobile Power Sources AMMPS

LTC John Kelleher – Product Manager

Photo
NA

Description- **AMMPS:** Future DOD Standard Family of medium (5-60kW) generator sets in 48 different configurations.

Desired CHARACTERISTICS/PERFORMANCE:

TEP ORD Thresholds	TEP ORD Objectives (Compared to TQG)
10% Lighter	25% Lighter
15% More Fuel Efficient	25% More Fuel Efficient
3 dBA Quieter	6 dBA Quieter
20% More Reliable	50% More Reliable
Maint Ratio: 0.025	Maint Ratio: 0.015
EPA Compliant Engines	EPA Compliant Engines

SPECIAL FEATURES MAY INCLUDE:

- Digital Controls, Diagnostics/Prognostics
- Variable Speed Diesel Engines
- Advanced Structural Materials
- Modular Components

KEY CONTRACTORS:

- ONAN Corp./Cummins Power Generation
- DRS - Vermont

Benefits/Capabilities

- 3kW Through 200kW
- Multi-Fuel (JP-8, JP-4, JP-5, DF-1, DF-2, DF-A)
- Reduced Noise and IR Signature Levels
- More Reliable
- Less Weight
- HAEMP Protected
- Reduced Fuel Consumption
- Total Package Fielding (Logistically Supportable)
- Power Units/Power Plants
- Less Cost (Procurement, Support Cost)
- Transportable (EAT, 5 & 10 kW Air Drop, etc.)

Requirements Documents

<u>Title</u>	<u>Date</u>	<u>App'd by</u>
Tactical Electric Power Operational Requirements Document (TEP ORD)	24 March 2004	JROC

Milestones Achieved/Scheduled

MS B	1QFY04
MS C	3QFY08*
Full Materiel Release	1QFY09*
FUE	2QFY09*

*Pending revision based on Phase II/III contract award.

Large Power Sources

LTC John Kelleher
Product Manager



Description-

100kW & 200kW TQG: Replaces the current 100kW & 200kW MIL-STD gen sets. Available in both skid and trailer mounted. Typical units – Medical, COSCOMs, Hospitals, Homeland Defense.

100kW & 200kW CHARACTERISTICS/PERFORMANCE:

Fuel	Diesel/JP-8
Noise	70 dBA @ 7m
Reliability	840 hrs MTBF
Operating Temp	-25°F to +120°F
Altitude	Rated pwr to 4000ft/95°F

	<u>100kW</u>	<u>200kW</u>
Weight (lbs)	5,800	9,100
Fuel Capacity (gal)	60	120
Fuel Consumption (gal/hr)	7.8	13.9
Size (Cu ft.)	160	250

ORD - CGSA ROC (100kW), Mar 88/Jul 95

PRIME CONTRACTOR: DRS - Fermont, Bridgeport, CT

DPGDS CHARACTERISTICS/PERFORMANCE:

Fuel	Diesel/JP-8
Noise	< 85 dBA
Reliability	TBD
Weight (Wet)	28,560
Size (cu ft)	1,907
Operating Temp	-25°F to +125°F
Altitude	Rated up to 4,000/95°F
Fuel Capacity	120 gal
Fuel Consumption	60 gph
ORD	AFORD (Aug 96)

PRIME CONTRACTORS:

DRS-Fermont, Bridgeport, CT (Contract Ends March 08)
Radian, Inc., Alexandria, VA (Contract Ends March 08)

Benefits/Capabilities

- 100kW, 200 kW and 840 kW (DPGDS)
- Multi-Fuel
- Reduced Noise and IR Signature Levels
- More Reliable
- Less Weight
- HAEMP Protected
- Reduced Fuel Consumption
- Total Package Fielding (Logistically Supportable)
- Power Units/Power Plants
- Less Cost (Procurement, Support Cost)
- Transportable

From: Required Operational Capability (ROC)

Requirements Documents

- **ROC and O&O Plan for the Commercial Generator Sets and Assemblages (CGSA) – 25 February 1988, Revised 10 July 1995**
- **Joint ORD (USAF / USA) CAF-USA 316-92-I/II-E for a NEW FAMILY OF BARE BASE ELECTRONIC POWER GENERATION & DISTRIBUTION SYSTEMS - 29 August 1996, Commander, Air Combat Command**

Milestones Achieved/Scheduled

**100kW & 200kW TQG MS C 3QFY04
Materiel Release: Sept '06**

DPGDS: USAF-Managed Program. Currently being fielded to 249th Engr. Bn (Prime Power)



Power Units / Power Plants (PU/PP)

Ms. Sidi Mathews

Description PU/PP: Provide Tactical Quiet Generators (TQG) in trailer-mounted configurations in sizes 3kW, 5kW, 10kW, 15kW, 30kW, and 60kW.

CHARACTERISTICS/PERFORMANCE:

- **Power Unit (PU)** One Generator Set mounted on one trailer
5kW, 10kW, 15kW, 30kW, and 60kW TQGs mounted on HMT, 1T, or 2½T trailer, towed by HMMWV or 2½T truck (10 separate models)
- **Power Plant (PP)** Two Generator Sets with switchbox and ancillary equipment mounted on one or two trailers (depending on generator set size and weight)
3kW, 5kW, 10kW, 15kW, 30kW, and 60kW TQGs mounted on HMT, 1T, 1½T, 2½T or 5T trailer, towed by HMMWV, 2½T or 5T truck (11 separate models)

KEY CONTRACTORS / Gov't Activities:

- Schutt Industries, Inc, Clintonville, WI
- Turtle Mountain Manufacturing Co., Belcourt, ND
- Silver Eagle Manufacturing, Portland, OR
- DOL Ft Drum, NY
- DLA Tobyhanna Army Depot, PA
- CECOM Ft Monmouth, NJ & Tobyhanna, PA
- PM-Trailers, Warren, MI

Benefits/Capabilities

- Provide mobility capability for 3-200kW TQG fleet
- Configurations towable behind HMMV, 2 ½ T and 5T trucks
- Trailer platforms reliable and supportable

Requirements Documents

- **ROC and O&O Plan for the Commercial Generator Sets and Assemblages (CGSA) – 25 February 1988, Revised 10 July 1995**
- **ORD for the Less-Than-3kW (LT3kW) Generator – 14 July 1992, Amended 7 March 1996**
- **Tactical Electric Power Operational Requirements Document (TEP ORD) 24 March 2004**

Milestones Achieved/Scheduled

Driven by TQG milestones

Small Power Sources

LtCol Tom Bowers, USMC, Product Manager



2kW MTG



3kW TQG

Description-

2kW MTG: Smallest set in DOD Standard Family. Replaces 1.5kW Gasoline MIL-STD set. Derived from FCT of Canadian design. Very versatile, diesel/JP-8 fueled, man-portable generator set.

CHARACTERISTICS/PERFORMANCE:

Fuel	Diesel/JP-8
Noise	79 dBA
Reliability	500+hrs MTBF
Weight (Wet)	138 lbs DC 158 lbs AC
Size	5.95 cu ft
Operating Temp	-50° to +120°F
Altitude	2kW @ 4000ft/120°F derated up to 8000ft
Fuel Capacity	4 hours @ 100% Load
Fuel Consumption	.33gal/hr

ORD-LT3kW 14 Jul 1992

SPECIAL FEATURES:

- Diesel / JP-8 Fuel
- Man-portable
- High Reliability
- Supports MKT modern burner unit (MBU); TUAV / EPLRS / AHS / HIMARS / Woodworking Set / Army Air Traffic System

3kW TQG: Most technically advanced generator set PM-MEP has fielded to date. Replaces gasoline and diesel MIL-STD generator sets.

CHARACTERISTICS/PERFORMANCE:

Fuel	Diesel/JP-8
Noise	70 dBA @ 7m
Reliability	>560 hrs MTBOMF
Weight (Wet)	326 lbs
Size	15.05 cu ft
Operating Temp	-25° to +120°F
Altitude	3kW @ 1000ft/107°F de-rated up to 8000ft
Fuel Capacity	8 hours + Auxiliary
Fuel Consumption	.33gal/hr

ORD – CGSA ROC w/Revision 1995

SPECIAL FEATURES:

- Variable Speed Diesel Engine
- Permanent Magnet Alternator
- Digital Controls

Benefits/Capabilities

- Multi-Fuel (JP-8, JP-4, JP-5, DF-1, DF-2, DF-A)
- Reduced Noise and IR Signature Levels
- More Reliable
- Less Weight
- HAEMP Protected
- Reduced Fuel Consumption
- Total Package Fielding (Logistically Supportable)
- Less Cost (Procurement, Support Cost)
- Transportable (EAT, 5 & 10 kW Air Drop, etc.)

Requirements Documents

- ROC and O&O Plan for the Commercial Generator Sets and Assemblages (CGSA) – 25 February 1988, Revised 10 July 1995
- ORD for the Less-Than-3kW (LT3kW) Generator – 14 July 1992, Amended 7 March 1996

Milestones Achieved/Scheduled

2kW

Re-Buy Production
Award Sep 01
10 Year Contract

3kW

Re-Buy Production
Award Sep 01
10 Year Contract

PDISE Components



Power Distribution Illumination System Electrical (PDISE) LtCol Tom Bowers, USMC, Product Manager

Description: A set of man portable power distribution components allowing the distribution of power within a tactical unit. The components consist of four different distribution boxes plus associated cables and a lighting system.

Characteristics/Performance:

Two feeder systems (M200 and M100)
Two distribution systems (M40 and M60)
Utility receptacle and lighting system (M46)
Operating Temp -25°F to +120°F

	M200	M100	M40	M60	Utility Kit
Weight (lbs)	140	77	55	45	85

Future Operational Improvements:

Ability to manage power distribution.
Disconnect low priority loads.
Bring generators on-line as power demands increase.

KEY CONTRACTORS:

- Federal Prison Industries (thru 2013)
- Tobyhanna Army Depot (FY05 contract)

Benefits/Capabilities

Expeditionary Attributes

- Distribute Power
- Ruggedized
- Uses Military Standard Connectors

Quality Power

- Consolidates Power Sources

Requirements Documents

<u>Title</u>	<u>Date</u>	<u>App'd by</u>	<u>Status</u>
Performance Specification For PDISE MIL-REF-53126	20 April 1992	CECOM	Requires Update

Milestones Achieved/Scheduled

FY05 - 06

- Placed production order with Tobyhanna Army Depot
- Completed fielding to 4th ID and SBCT 1-6 to enable TOC Central Power
- Completed Power distribution evaluation program (CERDEC)

FY07

- Award competitive five year contract
- Field to SBCT-7
- Field to 101 ABN

Improved Environmental Control Unit (IECU)

LtCol Tom Bowers, USMC, Product Manager



Description-

The Family of IECUs will provide cooling, heating and dehumidification to soldiers and materiel systems in Combat, Combat Support, and Combat Service Support units. The IECU requirement is derived from the Clean Air Act Amendments of 1990, which bans the use and production of ozone-depleting substances used in existing military standard ECUs by 2030 and bans the production of the current ECUs in 2010. The IECUs have Joint Service applications.

- New generation of ECUs to replace the current Military Standard (MIL STD) family of ECUs.
- IECUs utilize zero ozone depleting refrigerants.
- Form, fit and function replacement to current MIL-STD ECUs.
- Procurement based on performance based requirements vs. technical data package drawings.



Benefits/Capabilities

- Reduced system weight by 10 – 15%
- Reduced power consumption by 25%
- Soft start (i.e. reduced inrush current)
- Increased reliability: MTBF = 2100 vs. 960 hrs
- Increased supportability due to readily available commercial components
- Logistics footprint is greatly reduced by lighter-weight IECUs that require much less electrical power and, consequently, less fuel and potentially downsized generators.
- IECUs utilize zero ozone-depleting refrigerant.
- IECUs are designed for "military environment". Able to survive "military" handling and transportation requirements.
- NBC filtration compatible and EMP/EMI protected
- Operate at wider operating temperatures
- More ruggedized than commercial ECUs.
- Embedded diagnostics.
- Automatic safety controls.
- Remote control capability.

Requirements Documents

<u>Title</u>	<u>Date</u>	<u>App'd by</u>	<u>Status</u>
ORD for IECU CARDS #16123	Oct 2004	Army G-3	Approved

Milestones Achieved/Scheduled

- 60K IECU -

- Awarded 60k IECU SDD contract – Apr 06
- Logistics Demonstration – May 07
- PQT Completion – Jul 07
- TM Val-Ver; User Evaluation – Aug 07

- 9/18/36K IECU -

- Award SDD Contract – Mar 08



Fighter/EW/Helo/Patrol Arc Fault Circuit Breaker Development



April 2007

Sue Waggoner

Naval Surface Warfare Center

Crane

(812) 854-4103

susan.waggoner@navy.mil





What is the Arcing Fault Problem



Problem Description



Thermal Circuit Breakers are not designed to detect arcing (sputtering) faults for aircraft to prevent electrical fires.

- Arcing faults are the predominate typed of fault on aircraft wiring and do lead to many maintenance actions and possibly fires such as Swissair 111.
- The FAA reports an average of 3 smoke in the aircraft events/day in the civilian aircraft fleet





Navy



Problem Definition

- NALDA average annual incident rate of 127.4 per aircraft type, 38 types of aircraft corresponds to an incident rate of 4841 per year.
- Naval Safety Center documented 30 In-flight Navy aircraft wiring fires which caused mission aborts.
- Existing thermal circuit breakers are not designed to detect arcing faults



Expected Payoffs



- **AFCB protects/provides maintenance information on power wires (15-20% of system wiring)**

1 to 2 million organizational man-hours per year are spent troubleshooting and repairing aircraft wiring. With respect to power wiring incidents, AFCB technology will

- reduce maintenance man-hours by 35% (70,000 hours)
- reduce mission aborts and NMC hours by 35% (\$9M/year)

- ***AFCB will protect A/C wiring power system by detecting and isolating arcing fault which can cause smoke in the cockpit mission aborts and fires***

reduce in-flight electrical fires and subsequent loss of aircraft by 80% (\$27.3M/year)

- **Estimated savings of \$37.5M per year after full implementation.**




What Does An Arc Fault Current
Waveform Look Like?


Fixed Wing AC Generator Dry Arc

Condition

F-18 AC 10 AWG 25 Amp (A) MIN



c:\documents and settings\michael.i.allen\my documents\programs\afcb ground tests 2003\f18 afcb mar2003\f18 ac 10 awg25 amp 01.wft




c:\documents and settings\michael.i.allen\my documents\programs\afcb ground tests 2003\f18 afcb mar2003\f18 ac 10 awg25 amp 04.wft

Fixed Wing AC Generator Wet Arc


Condition

F-18 AC 10 AWG 25 Amp (1) MIN, Drip Test





c:\documents and settings\michael.t.allen\my documents\programs\afcb ground tests 2003\f18 afcb mar2003\ f18 ac 10 awg 25 amp drip 01.wt

F-18 AC 10 AWG 25 Amp (1) MIN, Drip Test



c:\documents and settings\michael.t.allen\my documents\programs\afcb ground tests 2003\f18 afcb mar2003\ f18 ac 10 awg 25 amp drip 04.wt



Helo AC Generator Dry Arc Condition



244 Amps RMS Current

77 msec



Helo AC Generator Wet Arc Condition



258 Amps RMS Current
25 msec

Helo AC Generator w/ 200 Amp T/R Dry

Arc DC Condition





What Is Being Developed And Tested?



Arc Fault Circuit Breaker Developmental Timeline



Fiscal Year

00 01 02 03 04 05 06 07 08

Transport Aircraft



Development

Lab Test

Flight Tests

Prod.

**ONR/FAA/AAIPT
Component Impr Program**

Fighter/Helo/Patrol A/C

Begin Devel

Lab Test

Ground Test

Flight Test

Prod.





AFCB - MS14105



- Qualified for Commercial Transportation and Military-Commercial Derivatives
- Originally trying to get from household circuit breaker to a large MS24571 circuit breaker
- Industry fitted arc fault circuitry into a MS14105 and MS3320





AFCB Testing



- Defining Arcing Waveforms
- Defining Electrical Load Waveform
- EMI Testing
- Temperature Altitude Testing
- Vibration Testing
- Electrical Testing
- Flight Testing



Flight Tests



- NAVAIR
 - C-9B 500 Flight Hours – Six AFCB
 - H-53 25 Flight Hours – Six AFCB
 - F/A-18, H-60, P-3 Planned for FY07
- FAA
 - Boeing 727 50 Flight Hours – 20 AFCB
- Industry 10000 Flight Hours
 - Boeing 767
 - Quantus 737



AFCB Transition Plan



- Transition for legacy aircraft through retro-fit on typical 30 month inspection phase
- Transition through retrofit or preferred spare part
- Transition Starts in FY07 depending upon company tooling capability
- Transition Platforms
 - H-53 PMA-261
 - P-3C PMA-290
 - F/A-18 PMA-265
 - H-60 PMA-299



Project Highlights



- Arc Faults have been a constant problem for the past 10 years
- Timeline
 - 6.3 development in FY02
 - ready for transition to E&MD in FY07
- AFCEB selected as part of the Core Program under FNC-TOC (6.3 funds)
- Cooperating with Air Force and FAA investigating the problems of arc faults in aging wiring systems with transition opportunities exist within Navy, other Government agencies, and industry

**2007 Joint Services
Power EXPO
23-27 April 2007
San Diego, CA**

Common Sense Approach to the Selection, Design/Fabrication, & Testing of Safe Operational Power Sources

Presented by
Robert Byrnes Sr.
Senior Battery Scientist
DHA Inc

Outline

Common Sense Approach

- Background
 - Bob's Terms/Advice
- Selection
- Design/Fabrication &
- Testing of Safe Power Sources
- Safety Testing of UltraLast AA Cells

BACKGROUND

MY PHILOSOPHY:

- **USE A BATTERY ONLY IF NEEDED**
- **KISS**
- **USE COMMON SENSE**
- **FEEDBACK REQUIRED**

EQUIPMENT PROBLEMS

THE CAUSES:

- ANTENNAES**
- BATTERIES**
- CONNECTORS**

BATTERY / PORTABLE EQUIPMENT

AS

BULLET / GUN

BATTERIES
THE “ACHILLES HEEL”
OF
TECHNICAL OPERATIONS

Battery Bob's Mottos:

“Trust but verify”

Ronald Reagan

“Test everything;
retain what is good.”

1 Thessalonians 5

PREMATURE BATTERY FAILURE CAN:

- CREATE LIFE THREATENING SITUATIONS**
- RESTRICT COLLECTION INFORMATION**

MOST BATTERY PROBLEMS ARE CAUSED BY PEOPLE WITH:

- LITTLE OR NO INFORMATION**
- MISINFORMATION**
- LACK OF TRAINING/EXPERIENCE**

BATTERY BOB'S TERMS/ADVICE

THE CAPACITY, ENERGY, POWER RELATIONSHIP

$E \neq P$

C (Ah)

$$E_{Wh} = \underbrace{V_L(V)}_{\substack{\text{P}_L \text{ (W)}}} \times \underbrace{I_L(A)}_{\substack{\text{C (Ah)}}} \times t(h)$$

P_L (W)

L - load

THE CAPACITY, ENERGY, POWER RELATIONSHIP SYMBOLS

E = Energy (Work) (Wh)

P = POWER (W)

V = Voltage (V)

C = Capacity (Ah)

I = Current (A)

t = TIME (h)

L = load

AVOID BATTERY PROBLEMS BY:

- **Checking Mfgr's Spec Sheet**

Note: No Standard Spec Sheet

- **Buying from High Volume Stores**
- **Knowing Date Codes**
- **Screening (Primary) OCV & CCV**
- **Screening & Matching (Secondary)**
- **Using Common Sense**

BATTERY BOB'S AXIOMS:

- THERE IS NO IDEAL CELL!**
- ALL COMMERCIAL CELLS ARE ALWAYS UNDER DEVELOPMENT.**
- KEEP BATTERY STASHES ROTATED & AVAILABLE TO ALL.**
- DON'T MIX BATTERIES w/ BULLETS, COINS, or OTHER METAL ITEMS!**

This is what happens if you do.

Name	Size	Chemistry	Temp oC	Temp oF
ECO	AA	Li/SOCI2	113-121	235-250
ECO	AAA	Li/SOCI2	94-106	201-223
Sanyo	CR-2N	Li/MnO2	61-70	142-158
Tadiran	TL-2200 C	Li/SOCI2	88	190
Tadiran	TL-2300 D	Li/SOCI2	70-90	158-194
Blue Star	D	Li/MnO2	50-116	122-241
Panasonic	BR-2/3A	Li/CF	149-151	300-304
Sanyo	HR-AA	Ni/MH	108-115	226-239
Sanyo	HR-4/3A	Ni/MH	73-75	163-167
Duracell	MX-1500 AA	Zn/MnO2	100	212
Sanyo	CR-2	Li/MnO2	76	169
Duracell	DL2/3A	Li/MnO2	91-93	196-199
Duracell	Ultra 123	Li/MnO2	78-93	172-199
Duracell	LM 123A	Li/MnO2	71-84	160-183

SECONDARY BATTERY CHEMISTRIES:

- **Nickel Cadmium-store discharged.**
- **Lead Acid-store charged.**
- **Nickel Metal Hydride-store discharged.**
- **Li-Ion-store 50% charged.**

- Check out the equipment using the selected cell or battery instead of a DC power supply.**
- The operation of equipment using a DC power supply may differ from the operation using other power sources.**
- Where possible simulate the actual use regime as closely as possible.**

SELECTION

**IF YOU WANT A BATTERY FROM ME
PICK ONLY TWO BELOW:**

•QUICK

•CHEAP


•SMALL


•RELIABLE

Basic Tips for the User in the Selection of Batteries for Operational Use:

- Define your need as fully as possible.
- There is no ideal power source.
- Don't make the choice of a power source a last minute decision.
- Keep the power source design simple.

TYPICAL BATTERY PACKS





BATTERY

DESIGN/FABRICATION

CONSIDERATIONS

**IF I DESIGN A BATTERY,
SHOULD IT BE,
A PRIMARY OR
A RECHARGEABLE
BATTERY?**

**IF I DESIGN A BATTERY,
CAN I FABRICATE IT
SAFELY?
IN TIME?**

**IF I DESIGN A BATTERY,
CAN I SHIP IT
SAFELY?
LEGALLY?
IN TIME?**

**FOR LITHIUM BATTERY
SHIPMENT QUESTIONS
SEE YOUR
SHIPPING OFFICER
FOR GUIDANCE**

**WHAT DO I DO
WITH THE BATTERY
AFTER I HAVE
FINISHED WITH IT???**

**CAN I DISPOSE OF IT
SAFELY?
LEGALLY?**

**FOR BATTERY
DISPOSAL QUESTIONS
SEE YOUR
SAFETY OFFICER
FOR GUIDANCE**

APPLIED BATTERY DESIGN

SIMPLE APPLICATIONS

MAJOR DESIGN CONSIDERATIONS

- 1) VOLTAGE
- 2) LOAD CURRENT
- 3) BATTERY LIFE
- 4) SIZE AND WEIGHT
- 5) ENVIRONMENTAL REQUIREMENTS
- 6) SAFETY VENTING
- 7) SAFETY FUSING
- 8) LAYOUT OF PACK TO REDUCE IR LOSSES
- 9) LAYOUT OF PACK TO REDUCE I^2R LOSSES
- 10) DIODE ISOLATION
- 11) CONNECTORS
- 12) LOW VOLTAGE CUTOFF FOR SOME Li CELLS

MAJOR DESIGN CONSIDERATIONS

VOLTAGE

- The devices with which the batteries are used have limitations on the maximum and minimum voltages between which they will work properly.
- The devices may also have limitations on the maximum voltage beyond which they will be permanently damaged.
- There might also be limitations on the minimum voltages below which they will have to be “reset”.
- Does the device perform consistently over the voltage range?
- Is there a preferred voltage?
- Are there multiple voltages required in one pack?

MAJOR DESIGN CONSIDERATIONS

VOLTAGE

- Batteries have maximum, minimum, and typical voltages. How do these match with the device requirements?
- If the battery's operating voltage range does not match the requirements of the device being powered, an electronics package may be needed to regulate the voltage. Otherwise, the full capacity of the battery might not be useable.
- An electronics package might also be needed to control the charging of the battery.

MAJOR DESIGN CONSIDERATIONS

CURRENT

- Affects the life of the battery
- Affects the size of the wiring in the pack and connectors
- Continuous high load current may have a thermal impact
- What is the nature of the current? Is it pulse? Continuous? A mixture of both?

MAJOR DESIGN CONSIDERATIONS

CURRENT

PEAK CURRENT

- The voltage and capacity available from a battery is affected by the discharge current.
- As the current increases, the voltage decreases.
- As the current increases, the amount of capacity that the battery can deliver decreases.
- At some currents, the battery will not produce a usable voltage.

MAJOR DESIGN CONSIDERATIONS

CURRENT

PEAK CURRENT

- EVALUATE PRIMARY vs. SECONDARY
- Primary - good energy density
(energy measured in Wh)
- Secondary - good power density
(power measured in watts)
- Hybrid - utilize the best characteristics
of each *(but with added complications)*

MAJOR DESIGN CONSIDERATIONS

CURRENT

AVERAGE CURRENT

- The number of Ampere-hours that are required is determined by the average current consumed by the device being powered.
- If an average current is not known, it can be calculated from the individual loads, the currents during all operating conditions, and the duty cycle.

MAJOR DESIGN CONSIDERATIONS

LIFE

How Long Before The Battery Can Fail?

- *Shelf Life*
 - How long must the battery be available before the device operating time starts?
- *Operating Life*
 - How long must the battery power the device?
- *What about End of Life?*
 - How Will The Battery Be Shut Down?

MAJOR DESIGN CONSIDERATIONS

LIFE

SHELF LIFE

- Effects of self discharge on battery life.
- Passivation - high initial pulse need.
- Cell seals - different seals start to leak at different times.
- Storage time before operation.
- Battery maintenance during storage.
 - Some chemistries need to be kept charged lead acid
 - Some chemistries have “memory effects”

MAJOR DESIGN CONSIDERATIONS

LIFE

OPERATING LIFE

- Effects of discharge current on useable battery capacity.
- Effects of temperature on useable battery capacity.

MAJOR DESIGN CONSIDERATIONS

SIZE & WEIGHT

CAN THE BATTERY BE CONCEALED?

- Will the weight give it away? *Too heavy or too light?*
- Will the size give it away? *Too big?*
- Will it fit in the electronics package? *Wrong shape?*
- Certain chemistries swell upon discharge.
- If a cell should go bad, is there enough capability left in the other strings to handle the mission?
 - Often a trade-off of size/weight versus redundancy.

MAJOR DESIGN CONSIDERATIONS

ENVIRONMENTAL REQUIREMENTS

- The performance of a battery is affected by the environment in which it will be used.
- Temperature has an impact on the battery.
 - Useable capacity.
 - High power pulses.
 - Function & Survivability
- The performance and battery design can be affected by other factors
 - Will the battery need to be moved?
 - How will it be moved
 - Road vehicle, Aircraft - Passenger/Cargo, Camel, Etc.
- Worldwide use? Indoor use? Outdoor? Tactical? Jungle? Desert? Snow? Salt fog?

MAJOR DESIGN CONSIDERATIONS

THINGS TO PONDER

- SAFETY VENTING
 - If a cell should vent, a path for the escaping gases needs to be provided
 - How does this impact on the mechanical design of the electronics package?
- SAFETY FUSING
 - Depends on cell chemistry and/or # of cells

MAJOR DESIGN CONSIDERATIONS

PACK LAYOUT TO REDUCE LOSSES

- HEATING LOSSES = I^2R
- VOLTAGE LOSSES = IR
 - Length and size of wiring in the pack
 - Cell interconnects and location
- DIODE ISOLATION
 - Parallel strings of cells need to be diode isolated
 - Voltage drop across diodes
- CONNECTORS
 - Size and type
 - Wire leads?

MAJOR DESIGN CONSIDERATIONS

REFINING THE CHOICES

- Verify cell selection will meet Operational Requirements
- **Electrical**
- **Environment**
- **Size and Weight**
- **Transportation**
- **Delivery Schedule**
- **Redundancy**
- **Reliability**
- **Cost**
- **Safety**
- **Further trade-offs**

MAJOR DESIGN CONSIDERATIONS

CELL SELECTION

NOT ALL CELLS PERFORM THE SAME

- This is true for:
 - Different chemistries
 - Same chemistries, but different manufacturers
 - Same chemistry and manufacturer, but different sizes
 - Same chemistry and manufacturer, but different manufacture date
- Not all cells are equally predictable or reliable in their performance.

PERFORMANCE RELATIVE TO MODEL

**Different versions of cells give different
performance characteristics**

**Even if they are the same chemistry,
manufacturer and size**

PERFORMANCE RELATIVE TO MANUFACTURING DATE

Cell manufacturers change the way cells are built. A cell built one year may be different from another year.

There are many reasons:
Cost/Profit
Competitive performance
Build-to-build variation

PERFORMANCE RELATIVE TO SIZE

**Different size cells give different
performance characteristics**

**Even if they are the same chemistry,
manufacturer and general construction
(i.e. prismatic, bobbin, spiral wound).**

PERFORMANCE RELATIVE TO CHEMISTRY

Different chemistry cells give different performance characteristics.

Even if they are the same size, the chemistry has different characteristics associated with it.

There may be construction differences as well. These may be needed by the nature of the chemistry (Different materials in the can, etc.)

PERFORMANCE RELATIVE TO CUT-OFF VOLTAGE

The amount of Capacity that a cell can deliver can be greatly affected by how low a voltage that the cell can be discharged and still do useful work.

This can be affected by both discharge rate and temperature.

Low voltage cutoff a must for some high powered lithium batteries to prevent reversal.

MAJOR DESIGN CONSIDERATIONS

CELL AVAILABILITY

- **Forward Deployed**
- **Warehouse**
- **Contractor Stockpile**
- **Commercial Purchase**
- **Special Purchase**

MAJOR DESIGN CONSIDERATIONS

CELL LEVEL TESTING

- Qualification Testing
- Lot Acceptance
- Screening
- Specialized testing
 - Environmental
 - Mission Profile
 - Safety

MAJOR DESIGN CONSIDERATIONS

BATTERY LEVEL TESTING

- Environmental
- Safety
- Mission Profile
- Qualification
- Screening

BATTERY PROGRAM CHECK LIST

ELECTRICAL REQUIREMENTS

1. Max. No Load Volts: _____ V
2. Steady-State or No-Pulse Load Data:
Max Volts: _____ V
Min. (CUTOFF) Volts: _____ V
Current at Max. Volts: _____ V
Current at Min. Volts: _____ V
3. Pulse Load Data (IF APPLICABLE):
Duration of Pulse: _____ msec
Frequency of Pulses: _____
Max. Volts _____ V
Min. (CUTOFF) _____ V
I @ Max. Volts (PEAK): _____ mA
I @ Max. Volts (AVE.): _____ mA
I @ Min. Volts (PEAK): _____ mA
I @ Min. Volts (AVE.): _____ mA
4. Duty Cycle: _____ Hrs On-Off/Week
5. Service:
Actual On Time (MEDIAN): _____ h
Electrical Capacity: _____ Ah
Storage Time Prior to
Use (MAX.): _____ h
Total Unit Life (Max.) _____ h

PHYSICAL REQUIREMENTS

1. Size if Prismatic:
Length: _____ mm/in
Width: _____ mm/in
Height: _____ mm/in
2. Size if Cylindrical:
Diameter: _____ mm/in
Height: _____ mm/in
3. If Irregular Size, Specify: _____
3. Weight: _____ g/oz
4. Position of terminals (TOP OR SIDE): _____
5. Submit Drawing (IF APPLICABLE) of Device Housing Cells/Battery Pack. (USE BACK OF SHEET FOR DRAWING.)

ENVIRONMENTAL REQUIREMENTS

(Note: The electrical requirements presume a temperature of 24 °C (75 °F). It is desirable to specify the electrical requirements at the maximum and minimum temperatures expected.)

1. Storage:
Expected Temp. Range: _____ °C/°F
Expected Avg. Temp.: _____ °C/°F
Expected Humidity Range: _____
Expected Avg. Humidity: _____
2. Use:
Max. Temp: _____ °C/°F
Min Temp.: _____ °C/°F
Expected Temp.: _____ °C/°F
Expected Humidity Range: _____
Expected Avg. Humidity: _____
3. Shock and Vibration: _____
4. Applicable Specifications: _____
5. Other: _____

OTHER REQUIREMENTS

1. Reliability: (What Minimum Capacity is Desired at What Confidence Level?)

2. Battery Disposal: _____
3. External Signature: _____
4. Transportation: (Very Important For DOT Regulated Power Sources.) _____
5. Delivery Schedule (Include Testing): _____
6. Operation Scenario(s) – (Be As Specific as possible. Use separate sheet for details if necessary. Classify appropriately.) _____

FOR RECHARGEABLE POWER SOURCES ONLY

1. Desired Charge-Discharge Cycles: _____
2. Depth of Discharge (DOD) _____ %
3. Minimum Charging Time: _____ h
4. Normal Charging Time: _____ h
5. Charging Modes:
Constant Current: _____
Current Trickle: _____
Constant potential: _____
Constant Potential (FLOATING): _____
6. Types of Use:
Frequent: _____ h/week
Standby: _____ h/week
7. Charging Temp Range: _____ °C/°F
8. Other Charging/Charger Info:

ULTRALAST

Li/FeS₂


AA CELLS

Circa early 2006


Background Info

Chinese made AA Lithium Iron Disulfide (Li/FeS₂) cells were shipped to the US and sold under the Ultralast label. The Ultralast label was very similar in appearance to the label Energizer uses for its Li/FeS₂ AA cell. Comparative Safety Testing was done on both the Energizer and Ultralast Li/FeS₂ cells.

Introduction



Introduction



UN TESTING
of
Energizer
&
Ultralast
AA Cells

UN TEST #5:

External Short Circuit Test

- Six (6) undischarged Ultralast cells were subjected to a short circuit test of less than 100 milliohms while maintained at 55 °C.
- The output voltage, current, and skin temperature were continuously monitored during the test.
- The short circuit condition was maintained for a minimum period of one (1) hour after the cell skin temperature had returned to 55 °C. The cells were observed for an additional period of six (6) hours.

UN Test #5:

External Short Circuit Test Results

- The highest maximum short circuit current was 10.47 amps, while the lowest was 6.54 amps.
- Two cells exhibited fire, with flames emanating from the positive end vent holes, the first cell at 2 hours, 31 minutes, and the second cell at 3 hours, with enough pressure release to pop the oven door open, and temperatures exceeding 170 °C (i.e. 341 °C, and 355 °C). The other four (4) cells oozed a tan colored material from the positive end, and two (2) of them reached 134 C.

Results-Comparison

UN Test #5: External Short Circuit Test

- The Energizer L 91 cells, (with 10 cells tested under the same conditions), reached a highest maximum short circuit current of 14.13 amps, while the lowest was 12.57 amps.
- The highest skin temperature reached by any of the cells was 97 °C. None of the cells exhibited fire, rupture, disassembly, or temperature exceeding 170 C.

UN TEST #6: Impact Test

A Lot of Reaction #4 Cell.

Five (5) undischarged Ultralast cells were subjected to the United Nations Impact Test (Test # 6)

The cell under test rested upon a Pine wood “flat surface”, measuring 5 - 1/2 inches X 5 - 1/2 inches X 3/4 inch thick. A 5/8 inch diameter hardwood dowel “bar” rested upon the center of the cell, such that the “bar” was perpendicular to the longitudinal axis of the cell and parallel to the “flat surface”. A 20 pound mass was allowed to fall a distance of 24 inches before impacting the “bar”.

UN TEST #6: Impact Test Cont'd.

Upon impact, and for a six (6) hour observation period thereafter, the first three (3) cells demonstrated no evidence of fire, disassembly, or temperature exceeding 170 °C. The highest temperature achieved by any of those cells was 27 °C.

UN TEST #6: Impact Test Cont'd.

The fourth (4th) cell, at 30 seconds after impact, reacted with the ejection of the positive end cap, followed by the violent expulsion of fire and burning material from the positive end (some of which penetrated the aluminum screen), thus, meeting the definition of disassembly. During the period of burning, the cell skin temperature rose to 601 °C.

The fifth (5th) cell, upon impact, and for a six (6) hour observation period thereafter, reacted the same as the first three cells.

UN TEST #6: Impact Test

Cont'd.-Comparison

Previously, the Energizer L91 cell had five (5) cells subjected to the Impact Test.

Upon impact, and for a period of six (6) hours thereafter, there was no evidence of fire, or disassembly, and the maximum case temperature achieved by any of the cells was 95 °C (maximum allowed = 170 °C). Although the end caps were dislodged, they did **not** penetrate the aluminum screen. Therefore, the cells did **not** meet the definition of disassembly.

UN TESTS #5 & #6:

Conclusions:

- Ultralast Li/FeS₂ cells failed UN Tests #5 & #6.
- Energizer Li/FeS₂ cells did not fail UN Tests #5 & #6.
- Cells which do not meet UN Tests should not be imported into the US for sale.
- The Ultralast AA Li/FeS₂ cells are no longer being sold in the US but other Chinese AA Li/FeS₂ cells are available on the Internet.

Note: 49 CFR 171.12 (a)

Battery Importers

“Each person importing a hazardous material into the US shall provide the shipper and the forwarding agent at the place of entry into the US timely information on the requirements of the regulations that apply to the shipment.”

SAFETY TESTING
VIDEO of
ULTRALAST
Li/FeS₂
AA Cells

Contact Information



David Hale Associates, Inc.
1785 Mt. Harmony Road
Owings, MD 20736

Robert B. Byrnes Sr.
Senior Battery Scientist

703-357-0686 (Cell)
703-632-6515 (FAX)

Email: RBYRNES3@VERIZON.NET

BATTERY MAINTENANCE PROCEDURES and CHALLENGES

Presented by:
PulseTech Products Corporation
Mark Abelson
800-580-7554, ext. 167
817-307-5603 (cell)
mabelson@pulsetech.net
www.pulsetech.net

Course Outline:

- I. Introduction**
- II. Conventional battery design**
- III. AGM battery design**
- IV. Basic battery facts**
- V. Common causes of battery failure**
- VI. Battery Maintenance Procedures**
 - Diagnostics**
 - Corrective maintenance**
 - Preventative maintenance**
- VIII. Conclusion**

WHY IS ANY OF THIS
IMPORTANT
TO ME?



87,000 batteries in Kuwait

What is the **GOAL** of this training?

1. Learn methods and procedures to keep batteries in service for over **FIVE** years
2. Improve readiness and save money at the same time


Biggest Challenge:

Change the way to do business with regard to lead acid batteries!


II. Conventional battery design



II. Conventional battery design



(+) and **(-)** plates are connected to make a 2 volt cell.



All 6 cells are connected inside the box to make a 12 volt battery

The case is filled with electrolyte (sulfuric acid & water)

Electrolyte must always cover the battery plates (but don't fill to top).

II. Conventional battery design

Conventional style batteries in use by the US Military:

6TL, 6TLFP, 6TMF, 4HN, 2HN and other commercially available batteries

All of these batteries are flooded (“wet”) cell lead acid batteries.

Though they appear similar they have different chemistry, capacities and voltages.

6TMF

The current battery provided by military supply.

Brown case with a black top.

It is also a lead calcium plate chemistry.

Built-in hydrometer (a green eye).

Note: The green eye only allows you to look at one cell in the battery and as such is not a reliable indication of overall battery condition. That is why the “eye” can indicate a battery is good but it still doesn’t perform properly.

II. Conventional battery design

Conventional style batteries in use by the US Military:

6TL, 4HN, 2HN

- Use lead antimony plates, many are still in the government system.
- Vary in size and voltage.
- 2HN, 12 volt. Used in small generators, i.e. the 5kW
- 4HN battery is a 24-volt battery (cannot be recovered in current military battery shops due to the lack of a 24-volt charger).

6 TLFP

- This was an interim battery until the 6TMF was fielded.
- Black top and lead calcium chemistry plates.
- Produced and shipped overseas as a dry battery with an acid over-pack.

III. AGM battery design



III. AGM battery design

COMPARISON OF BATTERY SPECIFICATIONS 6TMF LEAD-CALCIUM vs. HAWKER AGM SEALED RECOMBINANT BATTERIES

MILITARY LEAD-CALCIUM BATTERIES

- 12 volts
- CCA – **650**
- **Reserve Capacity – 200 minutes**
- Amp-hours (C/20) – **120**
- Usable Reserve – 30% DOD
- Shelf life – **2-3 months**
- Type Battery – SLI
- Cycle Life – Unknown
- Life (cradle-grave) – **13 months**
- Technology – lead-calcium flooded
- Internal resistance – 0.009 ohms
- Resistance to shock – poor
- Transport Class – **wet battery (hazardous)**
- Environmental designation – **“hazardous”**
- Weight – 75 pounds (34kg)
- Size (NATO 6T) - 10” (256mm) x 10.5” (269mm) x 8.9”h (227mm)

HAWKER AGM SEALED BATTERIES

- 12 volts
- CCA – **1225**
- Reserve Capacity – **240 minutes**
- Amp-hours (C/20) – **120**
- Usable Reserve – 70% DOD
- Shelf life – **30 months @ 25°C**
- Type Battery – SLI, Deep Cycle
- Cycle Life – 400~ @ 100% DOD
- Life (cradle-grave) – **36/60 months**
- Technology – AGM, sealed, recombinant
- Internal resistance – 0.0017 ohms
- Resistance to shock – excellent
- Transport Class – **non-spillable, can ship by air or other commercial transport**
- Environmental designation – **“non-hazardous”**
- Weight – 88 pounds (40kg)
- Size (NATO 6T) - 10” (256mm) x 10.5” (269mm) x 8.9”h (227mm)


Same basic design as conventional battery, except:

- AGM batteries use an Absorbent Glass Mat to contain all the electrolyte.
 - The AGM holds all the electrolyte like a “super sponge”. Battery won’t leak or spill even if tipped over or accidentally cracked.
- Contains a one way safety valve to prevent out-gassing & loss of liquid during normal operation.
- High purity lead (not recycled) plus a little tin
- Plates are compressed into cell partition
 - Prevents plate to plate movement & shorting
 - Prevents loss of active paste material
 - Increases vibration resistance.

Advantages of AGM batteries:

- **Longer life**
- **Less maintenance**
- **Safer**
 - No leaking acid
 - Eliminates corrosion to terminals & battery trays
 - No holes in your clothes, or burning skin
 - Reduced chance of battery explosion
- **Battery will work temporarily after cracked open or taking a round.**
- **Lower internal resistance**
 - Higher cranking power
 - More usable reserve capacity
 - Faster recharge

A little voltage means a lot!



Hawker/Optima state of charge versus OCV

IV. Basic battery facts

**All batteries discharge when not being used.
("self discharge" or "shelf life")**

The rate of self discharge increases as the temperature goes up

**For every 10°C rise in temperature
the self discharge rate doubles!**

IV. Basic battery facts



Where are your batteries?



Impact of Congressional Plus Ups and the Vehicle Battery Consignment Program (VBCP)

1. Many of the Hawkers in service today were supplied via dedicated Congressional funding
2. The VBCP is a DLA program that applies to flooded cell batteries (6T; 4HN; 2HN)
 - a. One for one replacement
 - b. Replacement is NOT FREE
3. The VBCP does not apply to Hawkers
 - a. Local DLA may not accept Hawkers
 - b. There is no one for one exchange

Common causes of battery failure

Deficit charging:

- **When the vehicle cannot fully charge the battery during normal operation. Results in a decline in capacity (shorter run time of electronics) and reduced battery life.**

Typical causes are:

- **Engine alternator voltage and/or amperage is too low,**
- **Engine run time not long enough to recharge batteries.**
- **High accessory loads (lights, radios, etc)**

Solutions:

- **Install a higher amperage alternator**
- **Shut off accessories when possible (or leave engine running)**
- **Periodically use an external charger to fully charge the batteries.**

Mixing different types of batteries together

Connecting different types of batteries together in the vehicle will lead to shorter battery pack life and possible overcharge or undercharge problems with individual batteries. Premature failure WILL happen.

Solution:

- Only connect together batteries of identical make and model.
- NEVER mix different battery types.

VI. Common causes of battery failure

Leaving (parking vehicle) batteries in a discharged condition:

Even a partial discharge will cause sulfation on the plates that reduces battery capacity and leads to premature battery failure.

Do not leave batteries discharged!


Damage can occur in a very short period.

Solution:

- **Check batteries before storing vehicle & recharge batteries if needed.**
- **If the vehicle or equipment is not used on a regular basis, periodically check the battery OCV and charge when necessary.**
- **Charge whenever the battery OCV is:**
 - **Wet/flooded: 12.5 or less**
 - **AGM: 12.7 or less**
- **When storing vehicles that have on-board electronics use a maintenance charger such as those provided by PulseTech Products to prevent reoccurring battery discharge.**


VI. Common causes of battery failure - plate sulfation

Ohio State University
5-year old fully charged batteries



**Cathode crystalline structures remaining
after charging without pulsing**

VI. Common causes of battery failure - plate sulfation



**Cathode after charging and pulsing with Solargizer.
Area in box is enlarged on next view.**

VI. Common causes of battery failure - plate sulfation

Ohio State University
5-year old fully charged batteries



Cathode after charging and pulsing with Solargizer

If the engine starts, the battery must be good, right?

NOT NECESSARILY!

A borderline battery may start the engine, but fail shortly after.

VII. BMMP - Diagnostics

If a battery does not pass the diagnostics tests, it MUST be pulled from the vehicle and sent to the shop for corrective maintenance. If you don't do this, your BMMP will not achieve it's full potential results AND vehicle operation is jeopardized.

Not conducting the diagnostic portion of the BMMP and ensuring your batteries are in good condition as you implement your program is one of the biggest causes for a BMMP to fail.

Diagnostics are an ongoing part of any preventative maintenance program. It will ultimately reduce battery consumption and the money and man-hours expended on corrective maintenance or battery replacement.

Historically the three most common methods of battery testing have been:

- **Multi-meter**
- **Load tester**
- **Specific gravity tester (Duo-check).**

Multi-meter – A good first glance tool to check out a battery.

Voltage and a battery's capability to operate may have little to do with one another. This is especially true with flooded conventional batteries.

An excellent example of this is the occasional battery that won't start a vehicle shortly after being taken off of a battery charger. When the battery is just off charge, a multi-meter will often give you a reading of over 13 volts. Yet when you try to start a vehicle or power radios, it immediately fails and the voltage drops to 12 volts or less. The battery had voltage (surface voltage) but no capacity.

OCV readings alone on flooded batteries are not suitable for determining battery condition or capacity.

OCV readings are more accurate with AGM batteries.

AGM: OCV < 12.7 (25.4 on a 24 volt battery pack) recharge immediately.

Flooded: OCV < 12.5 (25.0 on a 24 volt battery pack) recharge immediately.

Load Testing – One of the most effective ways to test a battery's condition.

A battery shop procedure

Creates a dead short across the battery's terminals with a gauge that indicates how the battery handles the load.

Battery **MUST** first be fully charged which makes load testing impractical anywhere except in a battery shop.

Load test battery per the equipment's instructions.

If tester is not automatic, set for $\frac{1}{2}$ the battery CCA rating.
(6TMF: 325 amps, Hawker Armasafe: 600 amps)

Discharge for 15 seconds.

To pass the test the battery voltage during load must stay above 9.6 volts

Passing batteries must be recharged again after load test.

Load Testing

Works on both Flooded & AGM batteries

OK for battery shop. Impractical in the field.

Use of Load testers takes time and requires caution.

Enormous heat and mishandling can cause burns.

Tester must be allowed to cool after every couple of batteries.

It is a time-consuming process that presents some genuine training and safety issues to users.

Specific Gravity Testers (Duo-check)

– In the past, Specific Gravity Testers were considered to be the standard for testing military batteries.

Can identify state of charge and bad cells.

Requires that each battery cap must be opened individually and each cell must be tested individually.

Associated safety issues from exposure to battery acid
(ruined uniforms, chemical burns, etc.)

Time consuming - opening and closing each cap on a 5-ton truck means that at a minimum, properly testing four truck batteries will take over 30 minutes per truck. At today's manning levels, that is too many man-hours.

(Specific Gravity tests are not applicable to sealed AGM batteries)

So how do you quickly, safely and efficiently test batteries?

CONDUCTANCE TESTING - Excellent snapshot of a battery's condition.

Conductance testing is performed with the **490 PT**. It's easy to use and it can test all four batteries on a truck in about 90 seconds.

The battery does not have to be fully charged, but it does need to be over 5.5 volts.

The 490 PT can be used repeatedly without heating up, opening caps or dealing with sulfuric acid.

CONDUCTANCE TESTING -

Uses an algorithm to compare the battery's available capacity to a known standard.

The PulseTech 490 PT provides the operator with a digital read-out that displays

- > **Cold Cranking Amps (CCA)**
- > **Whether the battery needs to be recharged and re-tested**
- > **If it has a bad cell**
- > **OCV**

Conductance testing is the fastest, most efficient way to test battery condition available at this time.

VII. BMMP - Diagnostics

490 PT and MBT-1

Part Nos. 741x490 and 741x800

(NSNs: 6130-01-510-9594 and 6130-01-463-8499)



Corrective maintenance is intended to reverse or correct a problem that has already occurred.

**You found a dead or questionable battery,
what's the next step?**

**The first question that must be asked
when batteries are dead is**

“Why?”

- **Run switch, lights or other electrical devices left on**
- **Short engine run times**
(“can’t refill the bucket” without running the engine longer)
- **Key off loads**
(loads that are still drawing current from the batteries even with the switch in the off position) newer vehicles have many microprocessors that often add to this problem.
- **Parasitic drain**
Small shorts in the wires of one or more pieces of equipment on the vehicle. These are generally not large loads or they would trip a fuse or breaker. They pull batteries down over time. These loads must be found and fixed. See Appendix 2 – Parasitic Loads for how to test to see if you have this problem

- Acid on the outside of the battery case



Place one probe of a multi-meter (set to DC volts) on either post of a battery and place the other probe on the “non-conductive” plastic case. With a dirty, shiny, or oily top (acid film), you will often see voltage on the meter. That means that the debris on the case has created an electric path and is drawing the battery down. To stop this, the case must be washed with soap and water to remove the oil. Baking soda must also be used to neutralize the acid (DO not allow baking soda to get into the battery cells). They can all be mixed together to make it easier.

Once you have identified and hopefully corrected the cause of the problem -

The dead batteries are sent to the battery shop for testing and attempted recovery.

Battery corrective maintenance must recover batteries to their rated CCA level or they are not worth trying to keep in service!

**If not sufficiently recovered,
replace them with known good batteries!**

VII. BMMP - Corrective Maintenance

Chargers - Must be designed for the specific battery type!

Flooded lead acid batteries use conventional automotive type chargers.

When possible the charger should be an automatic type as to not accidentally overcharge the battery if it's left connected.

AGM batteries need a high quality charger

Voltage needs to be properly controlled
(some automotive chargers can have a very wide voltage swing)

**If it does NOT have an AGM or sealed battery setting:
Voltage should be regulated between 14.25 and 14.75 volts.**

Recommended amperage ratings of 10 to 40.

All Chargers should be built for rough treatment:

Heavy Duty power supply
Tough clamps for good electrical connection.

Pulse Chargers – The Pulse Charger/World Version PLUS is four products in one.

- 110-volt & 220-volt switch for use within the United States or abroad.
- Switch (on back) for unique requirements of flooded lead-acid batteries and AGM or Gel Cell batteries.
- There is a Pulse Only setting designed to pulse clean the battery internally.
- Pulse & Charge, which simultaneously pulses the battery while it is being charged.

It's also a 20 amp “smart” charger that constantly tests the battery to insure a proper charge. Once the battery is fully charged, the unit switches to Pulse Only to maintain the battery.

(Note: The Pulse Charger incorporates a safety feature that prevents it from starting its charge regimen if a battery is below approximately 6 volts. Batteries below 6 volts can seldom be recovered, however by charging a known mechanically sound battery at low amperage for an hour you can get the Pulse Charger to activate though this is not recommended for safety reasons.)

Pulse Chargers

- The Pro HD is a “smart charger” for use on both 12- and 24-volt systems.
- Fully automatic smart charger senses battery condition and provides only what the battery can accept.
- Charges all conventional lead-acid battery types (flooded cell and AGM).
- Smart technology and pulsing prevents battery gassing and allows charging in the vehicle.
- 40-amp DC output in 12- or 24-volt mode (automatically switches between 12- and 24-volt systems).

Adjusts charge voltage and current to maximize battery recovery and charging. Smart technology and pulsing prevents battery gassing which allows charging with batteries installed in the vehicles.

Pulse Chargers

- The HD Pallet Charger is for use on all 12-volt batteries
 - Senses battery condition and provides appropriate charge current per channel.
 - Charges all conventional lead-acid battery types (flooded cell, AGM & gel).
 - Smart technology and pulsing prevents battery gassing, which allows charging with batteries sitting on the pallet.
 - Batteries can be left on pallets and not handled needlessly.
 - **Very effective on deeply discharged AGM batteries that have been taken out of service in the past.**
 - Charges and conditions up to 12 batteries at a time.
 - Batteries no longer need to be separated by type or state-of-charge.

Corrective Maintenance Systems



HD Pallet Charger
Part No. 746x820
NSN: 6130-01-532-7711



Redi-Pulse Pro HD
Part No. 746x800
NSN: 6130-01-500-3401



Pulse Charger/World Version
Part No. 746x725
NSN: 6130-01-398-6951



Redi-Pulse Pro-12
Part No. 746x912
NSN: 6130-01-535-2718

VII. BMMP - Corrective Maintenance



HD Pallet Charger
Part No. 746x820
NSN: 6130-01-532-7711



Redi-Pulse Pro HD
Part No. 746x800
NSN: 6130-01-500-3401



MBT-1
Part No. 741x800
NSN: 6130-01-463-8499



490PT
Part No. 741x490
NSN: 6130-01-510-9594



Redi-Pulse Pro-12
Part No. 746x912
NSN: 6130-01-535-2718

Battery Service Equipment Set (BSES)

- 1 – HD Pallet Charger
- 1 – Redi-Pulse Pro-HD 12/24 volt Charger
- 1 – Redi-Pulse Pro-12
- 10 – MBT-1 Battery Testers
- 1 – 490PT Battery Analyzer

“Initially we didn’t think it was going to be anything other than additional charging stations, but immediately we found that we could recover twice as many batteries using the technology incorporated into the BATTCAVE Chargers.”

DOL – Fort Lewis

Preventative Maintenance

After diagnosis and correction of your battery's condition, the batteries are reinstalled in the vehicles and equipment.

PM also includes checking and charging batteries prior to installation. It is very common to get "new" batteries that have been sitting idle for months prior to your purchasing them. Not starting with a fully charged battery will reduce the battery's life.

VII. BMMP - Preventative Maintenance

Ignored batteries will soon be right back to their start point.

PM is an action to prevent a problem from occurring or reoccurring.

Some PM actions are easy and cost nothing but time, others take more work and have a dollar value assigned to them.

During PM batteries will often be found to be dead or in a low state of charge (this is where the ongoing diagnostic cycle is most evident).

As discussed before, remember the common causes of discharged & failed batteries:

Common causes discussed previously:

- **Dirty battery cases**
- **Parasitic loads**
- **Key off discharge**
- **Operator error (lights & switches left on)**
- **Self Discharge**
- **Insufficient engine run time**

PM equipment:

Solar Charging Systems – Battery maintenance devices used on vehicles to prevent and break up large crystal sulfates on battery plates which occur in discharged batteries.

Sulfate crystal formations slowly destroy the battery's capacity.

Solar charge systems can be powered by either sunlight (Solar panel) or an AC receptacle.


Older model solar maintenance systems offset the 6TL's self-discharge from 4.4% to .8% per month.

New solar charge systems maintain and/or charge battery systems.

PM equipment:



24-volt Pulse Charge Monitor System
Part No. 735x643
NSN: 6130-01-497-0964



24-volt Pulse Solar Charger
Part No. 735x640
NSN: 6130-01-487-0035

PM reminders:

- Use of PM equipment described above does not eliminate the requirement of checking electrolyte levels in flooded lead acid batteries.
- PM equipment will not keep dirt and grime off the batteries; they still need to be cleaned.
- Solargizer type products will slow the self-discharge rate of a 6TL, but not overcome it. However, a Solargizer will overcome the self-discharge rate of an AGM battery.

VII. BMMP - Preventative Maintenance

PM reminders:

- Check batteries on a regular basis -
Whenever doing other PM inspections, or at a minimum every month
 - Battery connections checked and cleaned if needed.
 - Battery hold-down brackets, tighten if battery is loose.
 - Dirty batteries, clean if necessary.
 - Voltage or conductance test. Check and charge or send to battery shop if necessary.
 - Equipment with known battery problems should be checked more frequently until problem is solved.

A properly administered PM program will reduce the requirement for Corrective Maintenance and create huge savings in man-hours and money

Conclusion:

The information and maintenance practices described today will provide direct benefits in terms of:

- **Optimal vehicle electrical system performance**
 - **Lower battery related maintenance expenses**
 - **Fewer dead vehicles and jump starts**
 - **The longest battery life possible**
-
- **NEVER DISPOSE OF A HAWKER WITHOUT TESTING AND ATTEMPTING RECOVERY**

Any final questions?

Communications Power Sources and Vehicle Battery Maintenance



Session 7

Joint Service Power Exposition

25 April 2007



Session 7


- Power for Manpacked Radio Communications Equipment
- Mr. Mark Abelson
 - Battery Basic's for Vehicle Lead Acid Batteries
 - Keeping Batteries in Service
 - 2nd Infantry Division Case Study



Reference Material CD

- BMMP for Lead Acid Batteries
- FY07 Primary & Secondary battery price lists
- POWER 1.2 and Instruction Manual
- Power for Manpacked Radio Systems & QP-1800 (PowerPoint)
- SPC Software Version E
- Zinc-Air battery (PowerPoint)

BENEFICIAL SUGGESTIONS



POWER FOR MANPACKED RADIO COMMUNICATIONS EQUIPMENT



PURPOSE

To review the primary, secondary, and alternative power devices used to energize manpacked radio equipment.



12 VOLT RADIO SYSTEMS

SINGGARS RADIOS

BA-5590B/U	TAB B
BA-5590A/U W/SOCI	TAB B
BA-5390/U	TAB B
BA-5390A/U W/SOCI	TAB B
BA-8140	TAB C
BA-8180	TAB C
BB-390B/U	TAB F
BB-2590/U	TAB F

SINGGARS SINGLE POWER ADAPTER (SSPA) AN/PAC-216	TAB K
MULTI-SINGGARS POWER ADAPTER (MSPA) ASAPS-6	TAB K
MULTI-RADIO POWER ADAPTER (MRPA) ASAPS-SC/SNAP 6CC	TAB K

Note: The SSPA will not work with the AN/PRC-119F. The VB-90 (TAB L) is designed for the AN/PRC-119F (ASIP).

AN/PRC-148 (MBITR)

POWER SOURCES

MBITR Battery	TAB L
BA-8140/U	TAB C
BA-8180/U	TAB C
MRC-41	TAB L
Battery Cell Holder	TAB L

The MBITR battery is a unique rechargeable battery manufactured by Thales Inc. When initially fielded the only battery charger to support the MBITR battery was the Thales AC/DC commercial charger. Adapters have been developed to allow use of the SPC and VMC chargers (TAB I) to charge the MBITR battery.



MBITR Battery



Thales
AC/DC Charger

24 VOLT RADIO SYSTEMS

AN/PRC-117F, AN/PSC-5, AN/PRC-113 and AN/PRC-150

POWER SOURCES

BA-5590B/U	TAB B
BA-5590A/U W/SOCI	TAB B
BA-8180/U	TAB C
BB-390B/U	TAB F
BB-2590/U	TAB F
MRC-93 Single Radio Power Adapter	TAB K

REMARKS

Although the MRC-93 will operate from AC or DC power, the QP-1800 (TAB M) can be used to convert VEH DC power to AC power and energize the MRC-93.



QP-1800

BA-8180/U with J-6687/U
24V radio adapter (TAB C)



The BA-5390 has not been approved for use in any 24V radio system (refer to TAB B).

PRIMARY BATTERIES (ONE TIME USE)


NEW TYPE	NEW NSN	U/I	FY07 PRICE	OLD TYPE	OLD NSN	OLD U/I
BA-5093/U	6135-01-216-9771	EA	\$111.42	N/A	N/A	N/A
BA-5372/U	6135-01-214-6441	PG (10ea)	\$91.05	BA-1372	6135-00-801-3493	PG
BA-5112A/U	6135-01-439-6229	PG (4ea)	\$196.43	BA-5112	6135-01-235-4168	EA
BA-5557A/U	6135-01-448-4680	PG (4ea)	\$370.35	BA-5557	6135-01-088-2707	EA
BA-5567A/U	6135-01-447-5082	PG (12ea)	\$63.53	BA-5567	6135-01-090-5365	PG
BA-5567A/U	6135-01-447-5082	PG (12ea)	\$63.53	BA-1567	6135-00-485-7402	EA
BA-5588A/U	6135-01-447-5083	PG (5ea)	\$198.35	BA-5588	6135-01-088-2708	EA
BA-5590B/U	6135-01-438-9450	PG (4ea)	\$293.15	BA-5590	6135-01-036-3495	EA
BA-5590A/U	6135-01-523-3037	PG (4ea)	\$348.08	N/A	N/A WITH SOC LED	N/A
BA-5390/U	6135-01-501-0833	PG (4ea)	\$446.03	N/A	N/A	N/A
BA-5390A/U	6135-01-517-6060	PG (4ea)	\$480.27	N/A	N/A WITH SOC LED	N/A
BA-5598A/U	6135-01-447-5081	PG (4ea)	\$176.40	BA-5598	6135-01-034-2239	EA
BA-5599A/U	6135-01-447-4001	PG (4ea)	\$163.27	BA-5599	6135-01-069-8575	EA
BA-5600A/U	6135-01-441-0402	PG (8ea)	\$286.57	BA-5600	6135-01-168-2944	EA
BA-5800A	6135-01-440-7774	PG (8ea)	\$182.25	BA-5800	6665-99-760-9742	EA
BA-5347/U	6135-01-455-7946	EA	\$45.07	BA-5347	N/A	N/A
BA-5368/U	6135-01-455-7947	PG (10ea)	\$294.65	BA-1568	6135-00-838-0706	EA
BA-5374/U	6135-01-455-9646	PG (10ea)	\$131.30	BA-1574	6135-00-073-8939	EA
BA-8140/U	6135-01-517-0952	EA	\$275.00	N/A	REQ ADAPTERS	N/A
BA-8180/U	6135-01-500-0572	EA	\$355.58	N/A	REQ ADAPTERS	N/A

**WARNING – ensure personnel are using the correct NSN's and units of issue.
Many units of issue changed from EA (1) to PG (4), (5), (8), (10) or (12).**

TAB A

PRIMARY BATTERIES (ONE TIME USE)

The most widely used primary battery is the BA-5590B/U Lithium Sulfur Dioxide battery. An alternative to the BA-5590B/U is the BA-5390/U Lithium Manganese battery. The BA-5390/U has a 16.5/33.0 VDC maximum voltage, higher than the BA-5590B/U at 16.0/33.0 VDC. This higher voltage can cause equipment damage. The BA-5390/U has been approved for use in SINGARS radios (MCSC 101842Z MAR 03). The BA-5390/U thermal switch will trip if exposed to temperatures greater than 190 Degrees Fahrenheit. The BA-5390/U provides approximately 40 percent more run time than the BA-5590B/U. DLA has recently stocked new models of the BA-5590B/U and BA-5390/U. These new models, shown below, have State of Charge (SOC) LED indicators.



BA-5590B/U
6135-01-438-9450
PG (4) \$293.15

BA-5590A/U W/SOC
6135-01-523-3037
PG (4) \$348.08


BA-5390/U
6135-01-501-0833
PG (4) \$446.03

BA-5390A/U W/SOC
6135-01-517-6060
PG (4) \$480.27

State of Charge (SOC) indicators allow users to fully utilize battery capacity by displaying the remaining battery SOC in segments from 20% to 80%.


TAB B

ZINC-AIR PRIMARY BATTERIES AND ADAPTERS



BA-8180/U
12/24 VOLT
800 watts
Six pounds

BA-8140/U
12 VOLT
400 watts
Three pounds



BA-8140/U with J-6686/U MBITR adapter

Zinc-air batteries require special adapters. These adapters are re-usable.

Zinc-air batteries must be exposed to air and will not work if submerged.

SAMPLE PERFORMANCE TIMES

EQUIPMENT	BA-8180/U	BA-8140/U
AN/PRC-119F	5-10 Days	4-6 Days
SINGGARS (A-E)	5-9 Days	4-6 Days
SATCOM HF	5-7 Days	N/A
MBITR (PRC-148)	14 Days	7 Days

ADAPTER	APPLICATION	NSN	PRICE	U/I
J-6687/U	SATCOM/HF	5940-01-516-9787	\$505.00	EA
J-6686/U	MBITR (PRC-148)	5940-01-517-3990	\$233.00	EA
J-6633/U	AN/PRC-119F ASIP	5940-01-504-3218	\$113.78	EA
J-6634/U	SINGGARS (A-E)	5940-01-504-5597	\$51.46	EA



J-6633/U



J-6634/U

Zinc-air batteries react with air and experience continual discharge once removed from their packaging.

TAB C

RECHARGEABLE BATTERY OPERATING & STORAGE TEMPERATURE PLANNING INFORMATION

Rechargeable batteries are designed to operate and accept a recharge cycle from -4 degrees F to +122 degrees F (-20 degrees C to +50 degrees C). At low temperatures, they may operate, but will not accept a recharge cycle. Use primary batteries when temperatures outside these specifications are encountered.

Storage temperatures for rechargeable batteries should not exceed -4 degrees F to 122 degrees F. In hot climates, keep storage temperatures as low as possible. High storage temperatures will ruin a battery. Generally, the cooler the better.

Charging should occur above 40 degrees F. In temperatures below 40 degrees F, the batteries will take much longer to charge and may not charge fully. Batteries left in temperatures below -4 degrees F must be thawed before charging or they may vent. Allow batteries to thaw for at least six hours.

Stored rechargeable batteries will permanently lose capacity . . . even faster in HOT environments . . . so . . . charge them at least every six months or better yet . . . **USE THEM!**

WHEN WORKING WITH RECHARGEABLES

USE THEM OR LOSE THEM

TAB D

SECONDARY BATTERIES (RECHARGEABLE)

					ADAPTER REQ	ADAPTER REQ
BATTERY NAME	EQUIVALENT	BATTERY NSN	U/I	FY-07 PRICE	FOR SPC	FOR VMC
BB-2590/U	BA-5590	6140-01-490-4316	EA	\$295.18	J-6358B/P	J-6520A/U J-6581/U
BB-390B/U	BA-5590	6140-01-490-4317	EA	\$242.59	J-6358B/P	J-6520A/U J-6581/U
BB-388A/U	BA-5588	6140-01-490-4313	EA	\$68.23	J-6357A/P	J-6520A/U
BB-326/U	BB-516A/U	6140-01-533-7674	EA	\$91.07	J-6356/P	J-6520A/U
BB-503A/U	N/A	6140-01-419-8193	EA	\$80.10	J-6355/P	
BB-2847A/U	BA-5347	6140-01-493-8092	EA	\$94.75	J-6354/P	J-6520A/U
BB-557/U	BA-5557	6140-01-071-5070	EA	\$93.63	J-6523A/P	J-6584/U
BB-2557	BA-5557	6140-01-490-5387	EA	\$160.45	J-6523A/P	J-6584/U
BB-2600A/U	BA-5600	6140-01-490-4311	EA	\$139.92	J-6521/P	J-6584/U
BB-2800/U	BA-5800	6140-01-490-5372	EA	\$117.82	J-6587/P	J-6520A/U
AA Rechargeables			EA		J-6589/P	
MBITR Battery		6140-01-487-1153	EA	\$174.25	J-6588/P	J-6584/U



J-6589/P



SPC with various battery adapters



TAB E

SECONDARY BATTERIES (RECHARGEABLE)

The most widely used secondary (rechargeable) batteries are the BB-390B/U and the BB-2590/U.



BB-390B/U

Nickel Metal Hydride.
4 year warranty.
Lasts 16 to 20 hours
in SINCGARS radios.
Life cycle 3 – 5 years.
Requires periodic
conditioning.

Lithium-Ion. Desert
tan. Weighs one
pound less than the
BB-390B/U and has
a higher capacity.
Does not require
conditioning.
4 year warranty.



BB-2590/U

The BB-390B/U and the BB-2590/U are warranted for four years. Check the manufacturing date (7/03) to the left of the S/N. The first digit is the month, the second is the year. This date starts the warranty clock.

The BB-2590/U is approved for use in the AN/PRC-104, AN/PRC-113, AN/PRC-117, AN/PRC-150, AN/PSC-5, KY-57, KY-99, and all SINCGARS models.

Note: The BB-2590/U is NOT APPROVED for use in the Javelin Command Launch Unit. The higher voltage of the BB-2590/U will damage the CLU control unit.

ALTERNATIVE POWER EQUIPMENT DATA CHART

NOMENCLATURE	MODEL	TAMCN	NSN	FY-07 PRICE
BATTERY CHARGER/ANALYZER CASP 2000H(M)	PP-8333/U	A7700	6130-01-341-2073	
VEHICLE MOUNTED CHARGER (VMC)	PP-8481B/U	H6002	6130-01-527-2726	\$2,272.00
SUITCASE PORTABLE CHARGER (SPC)	PP-8498/U	A0012	6130-01-495-2839	\$2,028.00
SINGLE RADIO POWER ADAPTER 24V	MRC-93	H7706	6130-01-520-8178	\$1,994.85
SINGGARS SINGLE POWER ADAPTER (SSPA)	PAC-216/U	H7710	5985-01-465-2867	\$2,495.00
MULTI-SINGGARS POWER ADAPTER (MSPA)	ASAPS-6 / SNAP 6	H7715	6130-01-458-4041	\$2,375.00
MULTI-RADIO POWER ADAPTER (MRPA)	ASAPS-SC / SNAP 6CC	H7705	6130-01-473-0349	\$2,260.00
QP-1800 System W/NATO Slave cable and case	QP-1800	H0004	TBA	\$2,555.00
DISCHARGE CAP	PP-8497/U	N/A	6130-01-490-4310	\$66.54
SPC SLAVE CABLE	J-6362A/U	N/A	5940-01-501-6714	\$172.09
SPC NATO SLAVE Y-CABLE	CX-13560/G	N/A	5995-01-505-7883	\$65.05
MBITR BATTERY BOX for AN/PRC-148	MRC-41	N/A	McDowell Corp	\$1,371.46
MBITR BATTERY CELL HOLDER for AN/PRC-148		N/A	6160-01-487-1151	\$157.00
SCAVENGER		N/A	6130-01-539-0646	\$308.00
AN/PRC-119F (ASIP) POWER ADAPTER	VB-90		IRIS Technology	\$2,045.00

In order to be effective on the battlefield, a unit must be able to Move, Shoot and Communicate. Early into the invasion of Iraq, severe shortages of BA-5590/U batteries almost delayed combat operations. Units can mitigate future problems by training with and employing alternative power. Become BATTERY INDEPENDENT.

TAB G


BATTERY CHARGERS

PP-8333/U CHRISTIE BATTERY CHARGER/ANALYZER



Programmable.
Requires periodic calibration.
SL-3 cables support the BB-516, BB-586, BB-557, BB-590, BB-390B/U, BB-588, and BB-699. Other cables are available (refer to PP-8333/U data sheet in TM-12359A-OD located in the Electronic Tool Box).
Will not charge the BB-2590/U.
Requires MI-09591A-25/1B for the BB-390B/U.

PP-8498/U SUITCASE PORTABLE CHARGER



Sequentially charges up to eight batteries (two at a time) in approx. 8 hours.
Operates from AC or DC.
Comes with AC cable, DC cable must be ordered.
Will charge the BB-2590/U.
Will not charge the BB-590.
Software upgradeable.

PP-8481B/U VEHICLE MOUNTED CHARGER



Mounts in a tactical vehicle.
Charges two batteries at a time and moves to the next two in queue. Operates from DC or AC. Comes with AC & DC Cable. Will charge the BB-2590/U. Will not charge the BB-590. Software upgradeable.

See TAB I for SPC/VMC adapter chart.

See TAB J for SPC/VMC software updates.


Both the SPC & VMC are equipped with VEH battery low voltage detection & cutoff protection.

TAB H

SPC/VMC CHARGER TO ADAPTER REF TABLE

ADAPTER	ADAPTER NSN	FY-07 PRICE	U/I	RECHARGEABLE BATTERY	SPC	VMC
J-6358B/P	5940-01-501-3312	\$79.62	EA	BB-2590/U BB-390B/U	X	
J-6357A/P	5940-01-493-6388	\$28.14	EA	BB-388A/U	X	
J-6356/P	5940-01-427-9183	\$28.14	EA	BB-326/U (old BB-516A/U)	X	
J-6355/P	5940-04-427-9247	\$44.96	EA	BB-503A/U	X	
J-5354/P	5940-01-427-9278	\$60.47	EA	BB-2847A/U	X	
J-6523A/P	5940-01-492-7238	\$46.25	EA	BB-557/U BB-2557	X	
J-6521/P	5940-01-467-8813	\$44.96	EA	BB-2600A/U	X	
J-6587/P	5940-01-493-6750	\$43.66	EA	BB-2800/U	X	
J-6589/P	5940-01-493-7622	\$84.39	EA	AA BATTERIES	X	
J-6588/P	5940-01-493-6751	\$68.88	EA	MBITR BATTERY (PRC-148)	X	
J-6520A/U	5940-01-493-8744	\$331.64	EA	BB-2590/U BB-390B/U		X
J-6520A/U	5940-01-493-8744	\$331.64	EA	BB-388A/U BB-2800/U		X
J-6520A/U	5940-01-493-8744	\$331.64	EA	BB-516A/U BB-326		X
J-6520A/U	5940-01-493-8744	\$331.64	EA	BB-2847A/U		X
J-6581/U	5940-01-494-7116	\$312.31	EA	BB-2590/U BB-390B/U		X
J-6584/U	5940-01-494-7120	\$312.31	EA	BB-2557B/U BB-557/U		X
J-6584/U	5940-01-494-7120	\$312.31	EA	BB-2600A/U MBITR		X

Red indicates UNIVERSAL ADAPTERS which are designed to hold various different types of batteries at the same time.



J-6584/U Universal Adapter for the VMC.

BATTERY CHARGER ANCILLARY DEVICES



J-6362A/U DC slave cable for the PP-8498A/U (SPC). Disregard the smaller cable (attached), it is only used with the legacy PP-8444A/U.



CX-13560/G connects two SPC's to one DC slave cable (J-6362A/U).



PP-8497/U Self-Discharge Device (CAP), black, tan or dual colored, is used to discharge (condition) the BB-390B/U or “Quick Check” that both 12-volt sections of the battery are working. When used with the BB-2590/U, it is only used to provide a “Quick Check”. The BB-2590/U does not require conditioning.

SPC/VMC SOFTWARE UPDATES

The current version of software for the SPC is 3_30_.00.exe program E. Software updates can be downloaded from the U.S. Army rechargeable battery web site (TAB N) or call your supporting FSR (TAB Q). As new SPC adapters are developed supporting software updates will be published. The VMC, although software upgradeable, does not require a software upgrade at this time.



TAB J

12/24V RADIO POWER ADAPTERS

SINGGARS SINGLE POWER ADAPTER (SSPA) or AN/PAC-216



Replaces battery box. Energizes one SINGGARS radio using AC input. Built in UPS. Does not operate off DC power.

12V

POWER ADAPTER, 24V MRC-93



24V

Replaces battery box. Energizes one 24V radio using AC or DC input.

The MRC-93 is UPS capable when any BA-5590 equivalent battery is inserted into the adapter. Will not charge batteries used in this configuration. Warranted for 4-years.

MULTI-SINGGARS POWER ADAPTER (MSPA) or ASAPS-6



Energizes up to six SINGGARS radios using AC or DC power.

12V

MULTI-RADIO POWER ADAPTER (MRPA) or ASAPS-SC/SNAP 6CC



Energizes up to six 12V radios using AC or DC power. Supplied with six 12-foot radio power cables.

12V

The MSPA & MRPA are more effective when connected to both AC & VEH DC. While operating from the AC source, the VEH battery acts as an UPS. The AC power also maintains the VEH battery SOC.

TAB K

COMMERCIAL-OFF-THE-SHELF (COTS)



VB-90 Power Adapter for the AN/PRC-119F (ASIP).



SCAVENGER – recharge AAs in 100 minutes scavenging unused energy from BA-5590 equivalent batteries.



MRC-41 – holds primary or rechargeable battery, powers the AN/PRC-148.



Products pictured (TAB L) have not been tested to MIL SPEC standards.

Buyer beware, many vendors will attempt to sell products they claim to meet military specifications. They may or may not fail at high or low operating temperatures or in field environments.

Any product containing Lithium must be tested and approved for Marine Corps use under the Navy Lithium Battery Safety Program.

AN/PRC-148 (MBITR) Battery Cell Holder, holds DL2/3A, provides ten hours of operation.




TAB L

DC TO AC INVERTERS



The QP-1800 is a semi-ruggedized 1800W DC to AC (True Sine Wave) inverter that enables operation of 115 VAC powered devices from vehicle power (24 VDC). The QP-1800 connects to the vehicle using a supplied NATO SLAVE cable.

BATTERY SAFETY



When used incorrectly or mishandled, batteries can be hazardous. Be familiar with the material safety data sheets for all battery types.

TAB M

WEB SITE'S

U.S. Marine Corps
Program Manager
Expeditionary Power Systems
Marine Corps Systems Command

www.marcorsyscom.usmc.mil/sites/pmeps

U.S. Army
Rechargeable Battery
Program


www.monmouth.army.mil/cecom/lrc/lrchq/power/rechargebat.html

The screenshot shows the homepage for Expeditionary Power Systems. At the top left is the Marine Corps logo. The main header reads "Expeditionary Power Systems" with a "Program Manager" badge. The page is divided into several sections: "PM EPS Links" (a list of navigation items), "Popular Links" (a list of key resources), and a central area with various product and service images labeled: "Advanced Power Sources", "Field Service Reps", "Mobile Electric Power", "Battery Management", "Lighting & Power Distribution", "Environmental Control Units", "Future Technology", "PQDR & Warranty", "Safety Messages", "Reference Data", and "Policy". A "HIGH VOLTAGE" warning sign is also visible.


The advertisement features two photographs of battery equipment. The top photo shows a rack of battery units with a control panel. The bottom photo shows a single battery unit in a rugged, outdoor setting. The text reads: "Introduction, NSNs and Prices DA Rechargeable Battery Policy . . . It's Time to get all 'Charged up'".

TAB N

TRAINING




Battery Maintenance and Sustainment Systems (CD is available from FSR's)




12 Volt and 24 Volt Radio Adapter and Power Supply (CD is available from FSR's)

Power Management for Communication Equipment Operators (available at www.marinenet.usmc.mil, course 0612AO)




PP-8333/U, Christie Casp 2000H Battery Charger, operator's interactive CD (available from FSR's)



TAB O

BATTERY PLANNING TOOLS

Master Battery Requirements Model



- > Battery planning tool
- > Standard record of T/E equipment that uses batteries
- > Have exercise specific records
- > Standard reports and back-up
- > Run scenario's
- > **MUST BE TRAINED** in use prior to issue
- > Available from your supporting FSR

User Input Form Version: 1.0

Record Name:

Days of Deployment:

Days of Operation:

Operating Environment:

Leeway Factor (Non-Rechargeable): % (Default 5%)

Leeway Factor (Rechargeable): % (Default 5%)

Initial Battery Capacity: % (Default 85%)

Months in Storage: Optional

Environment/Temperature Chart

Storage: 50° to 80° F
Tropical: 91° F and Above
Temperate: 51° to 90° F
Cool: 10° to 50° F
Arctic: 10° F and Below

Equipment Input

TAMCN	Avg Operating Hours per Day	Quantity of Equipment	Chargers Available
<input type="text" value="1"/>	<input type="text" value="1"/>	<input type="text" value="1"/>	<input type="text" value="Yes"/>

Record Navigation

New Delete Copy

View Reports

- Battery Report
- Principal Battery Rollup
- Alternate Battery Rollup

Print Reports

- Battery Report
- Principal Battery Rollup
- Alternate Battery Rollup

Save Reports

- Battery Report
- Principal Battery Rollup
- Alternate Battery Rollup

POWER 1.1 Battery Calculator is an excel data base application developed by the U.S. Army to estimate communications equipment battery requirements. It is available from your FSR or by contacting WebPubEPS@mcsc.usmc.mil.

POWER OPTIMIZER FOR THE WARFIGHTER'S ENERGY REQUIREMENTS
Created by USA CE-LCMC, Power Sources Team, Ft. Monmouth, NJ

Distribution authorized to U.S. Government agencies and their contractors for official use or for administrative or operational purposes only. [Click for User's Guide](#)

White Areas require user input

1) Select an End Item

Choose Item by:
 ANPRC-119F
 ANPRC-119
 ANPRC-119G
 ANPRC-119H
 ANPRC-119J
 ANPRC-119K

POC: USA CE-LCMC, Ft. Monmouth, NJ
 Ari Herman
 Email: ari119@mcsc.usmc.mil
 Phone: (732) 532-6763 DSN: 992-6763
 Please Reference: Release Candidate 1.1, 12/19/05

The selected item is the ANPRC-119F, Radio Set (SINGARS), NSN: 5820-01-451-8252

2) Select the temperature conditions in which the end item will be used

Battery option(s)	Qty	Run Time	Units	Note	Total Batt. Weight	Units
BA5390	1	35	hrs		2.3	lbs
BA5390U	1	50	hrs		3.0	lbs
BE2590	1	31	hrs		3.2	lbs
BE590	1	23	hrs		3.0	lbs
BA8180	1	165	hrs		6.0	lbs

*Note: Batteries listed here may differ from those listed in the TM of some other devices. For a list of which batteries are interchangeable, and their replacements, please use the tab labeled "Rechargeable".

3) Given the above options, which battery do you wish to use

Battery	NSN	# per Package	Description	Specific Information
BA-5390AU	6135015170660	4	Battery, Non-Rechargeable, Lithium Manganese Dioxide	With SOCI
BA-5390U	6135015010833	4	Battery, Non-Rechargeable, Lithium Manganese Dioxide	Without SOCI

4) Choose which version you wish to use

5) The BA5390 is estimated to last 49.5 hrs in the ANPRC-119F, Radio Set (SINGARS), at Normal Temperature (10F to 120F).
 The battery will be swapped out after... hrs of use
 You are using 97% of the battery's total estimated capacity

6) Input the number of ANPRC-119F to be powered devices

7) Input the number of hours per day the end item will be in operation hrs

8) How frequently will the warfighter be resupplied with charged batteries? Every hrs

9) What is the TOTAL number of rechargeable batteries that will be needed to support operations for EACH device?
 (ie 0, add 1 for the device, 1 for the charger, 1 in transit etc.)

Battery	Battery NSN	Batt. per package	# of Devices	Device
BA-5390AU	6135-01-517-0660	4	43	ANPRC-119F

	# of Batteries	# Pkgs to order	Total Weight (lbs)
1 day mission	43	10.8	129.0
3 day mission	86	21.6	258.0
30 day mission	845	161.3	1,935.0

TAB P

POINTS OF CONTACT

PM EPS FIELD SERVICE REPRESENTATIVES

I MEF CAMP PENDELTON

Mr. Talmadge Jackson
talmadge.d.jackson.ctr@usmc.mil
(760) 725-4923

II MEF CAMP LEJUENE

Mr. Ken Copeland
ken.copeland@usmc.mil
(910) 451-1902

III MEF CAMP KINSER

Mr. John O'Brien
john.o'brien@usmc.mil
011-81-611-737-5023 (DSN 637-5023)

MEF FORWARD

Mr. Daryl Wilson
WilsonDK@cssemnf-wiraq.usmc.mil
DSN 302-3640-220 (Iraq)

PM EPS MARINE CORPS SYSTEMS COMMAND

ADVANCED POWER TEAM LEADER

Ms. Joanne Martin
joanne.martin@usmc.mil
(703) 432-3584 (DSN 378-3584)

Send questions to PM EPS MCSC at
WebPubEPS@mcsc.usmc.mil

U.S. ARMY RECHARGEABLE BATTERY PROGRAM

Mr. Don Brockel
donald.brockel@us.army.mil (732) 532-4948

TAB Q




WebPubEPS@mcsc.usmc.mil

**POWER FOR MANPACKED
RADIO COMMUNICATIONS EQUIPMENT**



"IN EVERY CLIME AND PLACE"

**Quiet Power (QP-1800)
DC to AC Power Inverter**



AC POWER FROM A HMMWV

An aerial photograph of a forest with a winding path. The path is a mix of brown and green, suggesting a mix of dirt and vegetation. The surrounding forest is a dense green. The word "QUESTIONS" is written in large, bold, yellow capital letters across the center of the image.

QUESTIONS

mbissonnette@mkisystems.com



Servicing Hawker Vehicle Batteries with Standard Battery Charging and Test Equipment



Mr. Fred Krestik
TARDEC

2007 Joint Service Power Expo

Research, Development, and Engineering COMmand

UNCLAS: Dist A. Approved for public release



The Hawker Battery



Hawker Armasafe Plus Battery **NSN 6140-01-485-1472**

*Absorbent
Glass
Mat (AGM)
technology*



Research, Development, and Engineering COMmand

UNCLAS: Dist A. Approved for public release



Recoverability



Hawker batteries have proven to be *highly* recoverable using standard charging equipment:

- Ft. Drum March 2006: >90% of Hawkers sent to DOL shop were successfully recovered using standard battery shop buss bar charging equipment.
- Ft. Hood May 2006, 2 pallets of Hawker batteries from DRMO were sent to TACOM for analysis: $\approx 90\%$ were recovered using std. chargers/methods.



TB 9-6140-252-13



The technical information presented is taken from
Technical Bulletin TB 0-6140-252-13 titled:

Field and Sustainment
Maintenance and Recovery Procedures
For
Automotive HAWKER ARMASAFE Plus Battery
NSN 6140-01-485-1472

Research, Development, and Engineering **COM**mand

UNCLAS: Dist A. Approved for public release



Required Equipment



Test Equipment:

1. Multimeter or voltmeter: any type that reads in 1/10th volt increments. (Clamp-on ammeter function a plus.)
2. Battery analyzer (e.g. Midtronics or PulseTech) or heavy duty Load Tester.



Required Equipment



Charging Equipment:

- Any charger with constant voltage output (rated at 12VDC or 12/24VDC) that can apply a charge to one or more batteries at a time using alligator clamps or NATO slave connector.
- Most modern chargers have settings/capabilities for AGM batteries.
- If in doubt, test charge voltage.
- Constant current chargers are not recommended.



Charge Voltage Test



To Verify Charger Output Voltage:

- 1. Attach charger to any fully charged (6TMF or Hawker) battery.*
- 2. Apply power and wait a few minutes until ammeter reads ≈ 1 amp, and measure voltage across battery.*
- 3. If voltage reading is > 15 VDC (> 30 VDC across series pair/NATO connector) do not use on Hawker batteries.*



Pre-Charge Inspection



1. Check top, sides, and bottom for damage. (i.e. cracks, dents, leaks, or swelling)
2. Check that the battery case and lid are sealed.
3. Make sure terminals aren't melted, bent or damaged.
4. Check for missing vent caps.

Mark and immediately dispose of batteries damaged as listed above.



Pre-Charge Inspection



Cell Vent Caps

Check that all vent caps are in place (flush) and do not appear to be elevated. Gently tap any elevated vent caps back into place and mark them with an “R” with a permanent marker. If a marked vent cap elevates again during charging or operation, dispose of the battery.



Pre-Charge Testing



- 1. Clean corrosion from battery terminals with a wire brush.*
- 2. Using a voltmeter set to the lowest voltage range above 15 VDC, test the Open Circuit Voltage (OCV) and mark the OCV in pencil or chalk on the top of the battery.*
- 3. If a battery analyzer is available, use it to determine if any internal damage exists. Many analyzers will not operate if the battery voltage is very low. If no reading is given or no internal damage is indicated, charge the battery for 24 hours and retest.*

Research, Development, and Engineering COMmand



Charging Procedures



Charging Procedures Overviews:

- Buss Bar Charging Multiple Batteries
- Single Battery or “Roll Around” Chargers

WARNING:

The Charging Procedure Overviews that follow are overviews only. They do not include safety related information. Refer to TB 9-6140-252-13 for more detailed information and procedures.

Research, Development, and Engineering COMmand

UNCLAS: Dist A. Approved for public release



Overview: Buss Bar Charging Procedures



Checklist summary:

- 1. Never mix battery types on a buss bar.*
- 2. Group batteries by OCV ranges: 0 – 5.9V, 6.0 – 9.9V, 10V and up.*
- 3. Set buss bar voltage between 14.7V and 15.2V.*
- 4. Allow at least 10 Amps per battery, e.g. 100 Amp buss bar charger can support 10 batteries max.*



Overview: Buss Bar Charging Procedures



- 1. Connect the batteries to the buss bars*
- 2. Charge the batteries at least 24 to 48 hours*
- 3. Check daily (recommend more frequently) for excessive heating, gassing, leaking, and proper voltage applied.*
- 4. Immediately remove any battery that shows signs of excessive heat, gassing, leaking, or swelling during charging. Battery should be marked with date and "Charged Tested Bad", and disposed of.*
- 5. Batteries are finished when charge current drops to approximately 1 Amp per battery.*



Overview: Single Battery & “Roll Around” Chargers



- 1. Use only chargers that are compatible with AGM batteries. (Refer to charger instructions and the Charger Output Voltage test)*
- 2. Set charger to appropriate settings for battery type and voltage. (Refer to charger instructions and instructions in the TB)*
- 3. Connect charger to battery posts or NATO slave receptacle.*
- 4. Turn on charger and monitor batteries for excessive heat and gassing during the charge cycle.*



Overview: Single Battery & “Roll Around” Chargers



5. *Some chargers automatically turn off at end of charge cycle. Some of these chargers require multiple cycles to fully charge batteries.*
6. *Batteries are finished when charge current drops to approximately 1 Amp.*
7. *“Rest” the batteries for 8 hours and test using a battery analyzer or load tester.*
8. *OCV of “rested” battery may also be used as an indicator of battery state of charge.*



Rested OCV and State of Charge (SOC)



- > 12.9 Volts OCV: 95% - 100% SOC
- 12.7 Volts OCV: about 80% SOC
- 12.5 Volts OCV: about 60% SOC
- 12.3 Volts OCV: about 50% SOC
- 12.1 Volts OCV: about 35% SOC
- 11.9 Volts OCV: about 20% SOC
- 11.7 Volts OCV: about 10% SOC
- 11.5 Volts OCV: about 5% SOC
- < 11.4 Volts OCV: 0% SOC

If the battery hasn't "rested" sufficiently after charging, the voltage reading will be a bit higher than normal. If it hasn't "rested" sufficiently after discharging, the voltage reading may be a bit lower than normal.



Servicing Hawker Vehicle Batteries with Standard Battery Charging and Test Equipment



2007 Joint Service Power Expo

Research, Development, and Engineering COMmand

UNCLAS: Dist A. Approved for public release



Thank-you!



For further information refer to

TB 9-6140-252-13

Or contact: Boyd Dial or
DSN 786-2629
586-753-2629
dialb@tacom.army.mil

Fred Krestik
DSN 786-8000
586-574-8000
krestikf@tacom.army.mil

Research, Development, and Engineering COMmand

UNCLAS: Dist A. Approved for public release

Vehicle Battery Maintenance Equipment

Joint Service Power Expo

25 April 2007

- Presented by:
- PulseTech Products Corporation
 - Mark Abelson
 - 800-580-7554, ext. 167
 - 817-307-5603 (cell)
 - mabelson@pulsetech.net
 - www.pulsetech.net

I. Introduction

87,000 batteries in Kuwait



2D Infantry Division

- During FY-04 spent 1.5 million on Hawker Batteries
- New equipment without NETT
- Stored them for less than 2 Yrs
- Installed batteries without any diagnostic checks – Massive battery failure
- Updated Equipment
- Received training from PulseTech

2D Infantry Division

- Recovered over 2K batteries in 60 days
- Saved \$750,000
- Reduced battery consumption by 75% over previous FY
- Command attention, equipment and training are the keys to success

What equipment did they use?

- Diagnostic
- 490 PT and MBT-1
- Part Nos. 741x490 and 741x800
- NSNs: 6130-01-510-9594 and 6130-01-463-8499

Diagnostic

490 PT and MBT-1



What equipment did they use?

- Corrective Maintenance Equipment
- Pro HD 12/24 Charger and the World Version Plus
- Part Nos. 746 X 800 and 746 X 725
- NSNs: 6130-01-500-3401 and 6130-01-398-6951

Corrective Maintenance



Redi-Pulse Pro HD
Part No. 746x800
NSN: 6130-01-500-3401



Pulse Charger/World Version Plus
Part No. 746x725
NSN: 6130-01-398-6951

263rd Maintenance Company

- “Your products were instrumental in keeping the war-fighters and logistics elements moving in Iraq. We established the first battery mission in the AO North Sector, and have done over 1,500 batteries since October 2006. Your equipment benefits the Army, as we have saved the government over \$300,000 in new battery expenditures.”

CW3 Paul L. McLaughlin
Senior Automotive Maintenance Officer
263rd Maintenance Company

What equipment did they use?



Diagnostic
490 PT and MBT-1



What equipment did they use?

- Corrective Maintenance Equipment



HD Pallet Charger


Part No. 746x820

NSN: 6130-01-532-7711

Preventive Maintenance



24-volt Pulse Charge Monitor System
Part No. 735x643
NSN: 6130-01-497-0964



24-volt Pulse Solar Charger
Part No. 735x640
NSN: 6130-01-487-0035

How are they being used?

- Marine Corps Tactical Quiet Generator (TQG) Modification Instructions (MI's)

U.S. Air Force War Readiness Program (WRM) i.e. Long Term Storage Program
South Korea

- Miscellaneous other applications within DOD and Federal Government (FEMA, BLM, Border Patrol, etc.)

What's New at PulseTech Products?

HD Jump Start
Part No. 746x700
NSN Pending



Common Denominators to Success?

- Patented Pulse Technology
 - Easy to use equipment
- Program Application
- **TRAINING!!!!**
- **Any Questions?**



Understanding Military Requirements for Generators

Mr. Jose Antonetti

U.S. Army Aberdeen Test Center

Aberdeen Proving Ground, MD



Broad Application

- Military generator sets support all elements of Department of Defense (DOD) force structure; Army, Navy, Air Force, Marines.
 - Worldwide deployment
 - Highly diverse mission requirements
 - System platforms ranging from ground vehicles to shipboard to airborne.
 - Fixed and semi-fixed facilities
 - Common operation, maintenance, and interface characteristics for use by all DOD components.



Military Unique Requirements



- At a minimum, generators intended for military use must meet unique and interrelated standards for:
 - Environmental performance
 - Safety and human factors engineering (HFE)
 - Survivability
 - Interoperability
 - Logistical supportability
 - Strategic and tactical mobility
 - Technical performance



Environmental Performance



- Harsher conditions generally experienced by equipment in military service.
 - Naturally occurring: Worldwide deployment results in a wider range of extreme conditions:
 - -51 °C to +49 °C, operating; -51 °C to +71 °C, storage
 - Up to 10,000-ft elevation at 35 °C (low atmospheric pressure)
 - Solar radiation, thermal and actinic effects
 - Sand and dust, airborne and wind driven particulate
 - Relative humidity, to saturation
 - Ice and freezing rain
 - Salt fog (aggravated corrosion test)
 - Fungus
 - Near strike lightning (NSL)



Environmental Performance



– Induced

- Mechanical shock and vibration
 - Highway and secondary road and off-road ground movement
 - Shipboard and aircraft installations
 - Amphibious and cargo aircraft movements
 - Airdrop
 - Externally suspended helicopter loads
- Sand and dust exposure in vicinity of ground vehicles and/or aircraft.
- Thermal shock during air drop, aircraft cargo transport, or deployment from conditioned enclosure.



Safety and HFE

- Meet military standards for safety¹ and HFE²
- Emphasis on protecting operators from:
 - Audio noise 85 dB(A) and greater
 - Toxic fumes
 - Energized contacts
 - Sources of thermal energy
- Designed to provide:
 - Common operator controls and indicators
 - Standard interface with military power connections
 - Sufficient workspace and access for all operations and maintenance actions

¹**MIL-STD-882,**

²**MIL-STD-1472,**



Survivability/Interoperability



- Survivability:
 - Survive High altitude electromagnetic pulse (HAEMP); result of a nuclear weapon detonated several kilometers in the atmosphere.
 - Be non-detectable by thermal and aural (audio noise) signatures.

- Interoperability:
 - Electromagnetic Interference (EMI):
 - Radiated electrical and magnetic field emissions (RE) that may interfere with other systems and equipment.
 - Susceptibility to fields radiated (RS) by other systems and equipment (i.e. radar, radios, etc.).
 - Susceptibility to signals produced by loads and conducted (CS) along power lines.

 - Installation on or in various military systems; e.g. tactical trailers, shelters, light wheeled, and combat vehicles.



Logistical Supportability



- Supportable within the resources of the DOD system
 - Not create demand for new operation or maintenance skills (training impact)
 - Minimize need for special tools and unique repair parts (supply impact)
 - 24 volt, direct current, electrical system common to all military ground systems (interoperability)
 - Multi-fuel operation
 - Diesel fuel 1 and 2, and arctic (DF-1, DF-2, DF-A)
 - Jet plane fuel 5 and 8 (JP-5 and JP-8)
 - Referee grade with more contaminants than commercially available sources



Strategic and Tactical Mobility



- Meet the interface standard for movement by assets of the Defense Transportation System (DTS)¹
 - Railroad
 - Ship
 - Highway
 - Military cargo aircraft (internal transport)
 - Helicopter (internal and externally suspended load)
- Equipped with dedicated lift and equipment tie-down provisions
- Palletized with forklift slots

¹*MIL-STD-209K, Interface Standard for Lifting and Tiedown Provisions, 22 February 2005*



Technical Performance: Commercial Generators



- ISO 8528¹ used to qualify commercial generators: power definitions and test methods analogous to military standards for power quality, but not exact.
- ISO 8528 used as general guidance for commercial generator qualifications vs. stringent mandates of military standards.
- Most commercial generators rated at unity power factor (1.0, no reactive loading) vs. military requirement for standard rating at 0.8 power factor.

¹International Standards Organization (ISO) 8528, Parts 1 through 12, Reciprocating internal combustion engine driven alternating current generating sets, 2005



Benefits of Commercial Generators



- Generally
 - Safe and easy to use
 - Reliable
 - EPA emissions compliant
- Widespread commercial network for support
 - Most product lines use common spares and expendables
 - Large aftermarket of components
- Core generator elements – engine, alternator, controls – relatively rugged
- Typically capable of multi-fuel operation



Commercial Generator Limitations



- Power quality issues
 - Excessive deviation and harmonics of voltage waveforms
 - Stability, regulation, transient performance below standards for basic military utility power
 - Can not function in certain climatic extremes without performance degradation
- Operational issues; not ‘greened’
 - Audio noise, quiet, in a bigger footprint
 - Pronounced thermal signature
 - Exceeds military limits for radiated electromagnetic emissions



Limitations, Cont'd



- Configuration issues
 - Controls and indicators not standardized to military format
 - Lack fittings for forklift handling, lift, and/or equipment tie-down for rail/air/ship movements
 - Unique electrical connections
 - Often lack 24 volt electrical system
 - No NATO¹ connector for 'jump' starting
 - Spare parts and expendables not in military stock
 - Susceptible to wind driven sand/dust (desert operations)
 - Vulnerable to HEAMP and chemical-biological agents
 - Lack high capacity fuel/water separation
 - Shock isolation insufficient for off-road/tactical environment

¹NATO – North Atlantic Treaty Organization



Technical Performance: Military Generators



- Military power requirements are typically more stringent and set in finer increments than ISO 8528.
- Critical applications are more widespread in the military; being offline can produce more serious consequences than for most commercial systems.
- These factors accommodated in military standard 1332, Revision B¹ (MIL-STD-1332B); required for military generators

¹MIL-STD-1332B, Definitions of Tactical, Prime, Precise, and Utility Terminologies for Classification of the DOD Mobile Electric Power Engine Generator Set Family, reinstated with Notice 2, 10 July 2001



Military Generator Categories



- MIL-STD-1332B categories reflect DOD mission diversity; accommodating specialized requirements
- Types:
 - Type I, Tactical (light, small, mobile)
 - Type II, Prime (semi-fixed)
- Classes:
 - Class 1, Precise (critical applications)
 - Class 2, Utility (general purpose; three sub-classes ranging from 2A commercial equivalent to 2C general utilitarian)
- Modes:
 - Mode I, 50- or 60-Hz
 - Mode II, 400-Hz
 - Mode III, 60-Hz
 - Mode IV, 28 volt direct current



Common Ground: Power Quality



- Characterization of generator output common to MIL-STD-1332B and ISO 8528:
 - Voltage and frequency regulation
 - Voltage and frequency stability
 - Voltage and frequency transient performance
 - Voltage waveform deviation factor and harmonics
 - Voltage phase balance.
- Forms basis for adaptation of commercial generators to military applications.



Technical Performance



- Verified through testing in MIL-STD-705C^{1, 2}
- MIL-STD-705C methods accommodate numerous natural and induced environmental conditions.
- Dedicated test facility at ATC for MIL-STD-705 testing.
- Major range and test facility for all other aspects of generator testing required for military acceptance.

¹MIL-STD-705C, Generator Sets, Engine Driven, Methods of Tests and Instructions, 24 April 1989

²Pending revision D.



ATC Related Facilities



Major Missions Include:

- Automotive – Wheeled & Tracked Vehicles
 - Conduct 80% of the Army Automotive Testing.
- Firepower
- Survivability/Lethality
- Warfighter
 - Soldier Systems and Support Equipment
 - Training Exercises
- Military Environmental Technologies
- Maritime Systems



Facilities



**APG
Range
Commander**

**Range = 66K Acres
($\frac{1}{2}$ Land, $\frac{1}{2}$ Water)**

**103 Miles of Shoreline With 60 Miles
Adjacent to Live-Fire Ranges
with MOUT Facility**

Water Depths 2-14'

**Open Air Ranges w/ Modular
Instrumentation Suites**

**Traditional Laboratories w/ Advanced
Tools**

**Fabrication Facilities & Professional
Craftsman Shops**

**Isolated / Secure / Hardened Surface
& Sub-surface Opportunities**

Temperate Zone

Real-Time MET

**Airfield with Landing Capabilities
for any Military Aircraft**



Generator Test Facility



- Outdoor test area to support performance and endurance tests of engine-generator sets as specified in MIL-STD-705 and ISO 8528
- 20 concrete pads/40 test stations accommodate generators up to 200 kW
- AC resistive-reactive load banks up to 208 kW/154 kVAR on site: greater capacity available
- Test instrumentation, multichannel, automated data acquisition and reduction system
- Higher-capacity generator testing is accomplished with special requirements
- Central monitoring and control station for automated data acquisition and analysis
- Central fuel storage and pumping facility
- Mobile instrumentation trailers for testing at remote sites
- Service buildings for maintenance, modifications, and instrumentation



Mobile Generator Test System




- Complete, self-contained, mobile capability for generator testing to 300-kW, including instrumentation and data acquisition
- The above contains a load bank rated to 208 kW (frequency 50/60/400 Hz) and a control console mounted in shelter.
- The semi-trailer contains a 300 kW AC and DC (frequency 50/60/400 Hz), a work area, and a control console mounted in shelter



Human Factors Engineering (HFE)

Airflow Testing, Mobile Data Acquisition System, and General Capabilities



- Mobile instrumentation vans to support various HFE tests
- Two 6.5-kW generators for internal utilities and instrumentation
- Impulse and steady state noise tests, including hearing conservation, drive-by, and aural non-detectability
- Measure gaseous flow rates and pressures, and fluid temperatures and velocities
- Speech intelligibility
- Anthropometric characterization of test participants
- System design review



Analytical Chemistry Laboratory



- Various analytical techniques are utilized to identify and quantify the chemical composition of samples from various sources. The analysis employs standard methods from analytical and environmental chemistry. The instrumentation utilized is as follows:
 - High Performance Liquid Chromatography (HPLC)
 - Atomic Spectroscopy (AA-ICP)
 - Gas Chromatography Mass Spectrometry (GC/MS)
 - Ion Chromatography (IC)
 - Fourier Transform Infrared Spectrometry (FTIR)
- Examples of procedures are as follows; other procedures can be developed:
 - Ion Analysis: sulfate, phosphate, chloride, fluoride, nitrate, nitrite
 - Wet Chemical: pH, conductivity, total dissolved solids, hardness, turbidity, dissolved oxygen, chemical oxygen demand, total coliforms
 - Propellant Analysis: solid and liquid, effective stabilizer level, moisture, volatiles
 - Explosives identification
 - Elemental: carbon, hydrogen, nitrogen, oxygen
 - Airborne particulate
 - Polynucleic aromatic hydrocarbons (PAH)
 - Toxicity Characteristic Leaching Procedure (TCLP) and other leaching procedures
 - Metals in wastewater, drinking water, and soil; also lead in paint
 - Total petroleum hydrocarbons (TPH) in wastewater
 - Volatile organic compounds (VOC) and Semivolatile organic compounds
 - Identification of unknown samples



Fuels Laboratory (Chemistry)



- The Chemistry Team Laboratory is certified by the Army Petroleum Center as a fuel testing laboratory
- Fuels are tested to assure compliance to standards for use in test items and vehicles
- Analysis of diesel and kerosene-type fuels includes:
 - Distillation range
 - API and specific gravity
 - Flash point (closed and open cup)
 - Cetane index
 - % Water by Karl Fisher
 - Particulate contamination
 - Sulfur
 - Cloud point
 - Pour point
 - Freeze point



Oils Laboratory (Chemistry)



- Oils and lubricants are analyzed and tested to determine the wear of metals components in test items. Changes to the physical properties of the oils and lubricants are monitored
- Surveillance of lubricants during testing can help predict wearing of metal parts and help predict component failure.
 - The surveillance program can also help determine service intervals by assessing other physical properties such as viscosity
- Foreign oils and fuels are analyzed and a U.S. replacement fluid is determined for continued operation of unique test vehicles
- The Chemistry Team Laboratory is certified in the JOAP/AOAP as a special laboratory for oils analysis - procedures include:
 - Wear Metals by Spectroscopy
 - Particle Contamination
 - Particle Analysis by Ferrography
 - Acid/Base Number
 - Viscosity
 - Fluid Contamination by FTIR



Lift and Tie-Down Facility



- Utilized to test the lifting and tie-down provision capacity of military vehicles and generators in accordance with MIL-STD's 209 and 913
- Various devices are provided to impact test loads in vertical, longitudinal, and lateral directions:
 - 55-ton overhead chain hoist
 - Remotely controlled 60-ton hydraulic load application system
 - Airbag inflation system
 - Mobile cranes of varying capacities up to 250 tons
- On site ballistic proof test control room provides:
 - Protection for test personnel, test sponsor and manufacturer representatives
 - Video camera/VCRs for real-time monitoring and recording of test load applications



Rail Transport Facility



- Testing per MIL-STD-810 to ensure compliance with Military Traffic Management Command transportation certification requirements
- Fully instrumented (velocity, shock levels) test capability
- On-site locomotive and standard railcar equipment
- Covered railcar loading/unloading and tie-down facility with stocked supplies of rigging materials, tools, and wood-working machinery for producing required chocks and cribbage
- Still and video photographic coverage, including high-speed video



External Air Transport



- Testing per MIL-STD-913 to ensure compliance with certifying agency for EAT, U.S. Army Soldier Systems Command (formerly The U.S. Army Natick Research, Development and Engineering Center)
- Static lifts of aircraft slinging configurations by crane prior to flights to verify suspension orientation and clearances
- On-hand supply of approved rigging materials
- Army CH-47D Chinook and Marine Corps CH-53E Sea Station helicopters with experienced aircrews and riggers
- Aerodynamic flight tests conducted at Phillips Army Airfield, APG
- Still and video ground/aerial photography documentation
- Instrumentation available for test items and slings if desired




Internal Air Transport



- Access to all U.S. Air Force transport aircraft (C-130, C-141, C-5, C-17), pallets, rigging, and material-handling equipment for demonstrating and validating loading procedures for vehicles and equipment as required for Wright-Patterson AFB certification of IAT
- APG Phillips Army Airfield spacious facilities (8000-ft main runway and up to 800-ft ramp areas) accommodate all transport aircraft for on-site evaluations
- Proximity to local Maryland National Guard (Baltimore), Andrews Air Force Base (Washington, DC area), and Dover AFB (Delaware) for off-site evaluations
- Experienced active-duty loadmasters assist in evaluation and resolution of potential air transportability issues
- Dimensional and clearance measurements, still and video photography provided to document evaluations




Electromagnetic Interference Test Facility (EMITF)



- The EMITF delivers high degrees and ranges of attenuation to test military systems and subsystems against controlled electromagnetic military standards
- One of the largest facilities of its type, the facility measures 94' L x 60' W x 28' H, making it large enough for combat vehicles, tactical trucks, large caliber weapons systems, and helicopters and small enough for hand-held binoculars
- Multiservice test facility
- Testing from 16 Hz through 40 GHz
- Susceptibility levels up to 200 V/m
- MIL-STD, SAE, CISPR (Comité International Spécial de Perturbations Radioélectriques), and FCC testing
- One access door 16' x 16'; two access doors are 4' x 6'
- Magnetic field attenuation of 40 dB, 14 kHz to 1 MHz
- Electric field attenuation of 90 dB, 14 kHz to 30 MHz
- Plane wave attenuation of 90 dB, 30 MHz to 1000 MHz
- Floor load rating: 18,000 lb./ft²
- Ventilation: 12,000 cfm



Infrared Thermal Imaging



- ATC has a state-of-the art infrared camera system operating in the 3- to 5-um spectral range
- System is used for real-time documentation of thermal signatures profiles, burning residue identification, and fire ignition/propagation testing



Climatic Simulation Facilities/Capabilities



Blowing Rain



Solar Test



Salt Test



Dust Test

- Facilities provide climate test support requirements of MIL-STD-810F
- Wind machine - Three moveable units generate up to 100 mph winds, 40'
- Wind-driven rain - movable machine produces up to 4 in./hr of rain at up to 50 mph wind
- Temperature-humidity chambers and portable units having temperature from -80 °F to +200 °F and humidity up to 100%
- Solar radiation



Environmental Chamber No. 1



- Large controlled-temperature chamber for climatic testing of vehicles, weapon systems, and soldier systems (C4I, generator, materials handling, civil engineering, air and water purification, lift and tie down, bridging/watercraft, tents/shelters) in accordance with MIL-STD-810F
- Chamber is 15' W x 24' L x 10.9' H having a 10.3' x 10' door
- Temperature range from -70 °F to 160 °F
- Used for firing weapons up to 155-mm caliber in extreme conditions
- Sensors detect toxic/hazardous fumes and gases
- Ports for instrumentation cable access



Environmental Chambers No. 2 and 3



- Large controlled-temperature chambers and adjacent conditioning room for climatic tests of vehicles, weapon systems, and soldier systems (C4I, generators, materials handling, civil engineering, air and water purification, lift and tie down, bridging/watercraft, tents/shelters) in accordance with MIL-STD-810F
- Chamber 2 is 10' W x 19' L x 10' H with a 9' x 7' door
- Chamber 3 is 18' W x 28' L x 15' H with a 13' x 11.5' door
- Conditioning room is 23' W x 41' L x 14' H with a 14.5' x 12' door
- Chambers 2 and 3 temperature range of -65 °F to 165 °F
- Conditioning room temperature range of 0 °F to 165 °F
- Firing of weapons up to 155-mm caliber under various climatic conditions
- Toxic gas/hazardous fumes monitor/alarm system



Environmental Chamber No. 4



- Spacious multipurpose facility provides temperature, humidity, icing, thermal shock, salt fog, dust, solar radiation, and altitude test capability, meeting the requirements of MIL-STD-810F
- 40' W x 75' L x 24' H chamber
- Temperature range -70 °F to 170 °F with humidity control up to 98%
- Dividable into two 40' x 37' chambers having independent climatic controls
- Each chamber has 16' x 16' door
- 10' x 20' solar radiation area
- Adjacent area for data acquisition and control instrumentation



Munson Test Area

- Automotive field test area consisting of 9 miles of roadways/test courses encompassing 150 acres
- Paved course - 2200'
- Sand course - 500'
- Belgian block course - 3900'
- Wave course - 440'
- Vertical walls - 18" to 42" H
- Slide slopes, 20% to 40%, 100' to 700'
- Simulated loading ramp - 40' , 20°
- Improved gravel road - 10,700'
- Abrasive mud course - 950' L x 240' W
- 2- and 6-inch washboards - 800'
- 2- to 4-inch radial washboard - 240'
- 3-inch spaced bump course - 760'
- Longitudinal slopes, 5% to 60%, 80' to 480'
- Shallow and deep fording basins - 270' L x 6' D, 315' L x 20' D
- Amphibious vehicle swim area (Spesutie Narrows/Chesapeake Bay)



Perryman Test Area



- Level cross-country, secondary, and paved road vehicle endurance and reliability test area
- Six primary test courses cover about 2,000 acres:
 - 3-mile straight and level paved road with turnarounds
 - Two secondary roads, 2.4 miles and 3.2 miles
 - Four cross-country courses of varying severity, 1.8 miles to 5.2 miles
- Off-road courses vary from moderate gravel surfaces to extremely rough terrain including marshy areas
- Supports other vehicle tests, i.e., braking, stability, road vibration, steering, etc.



Churchville Test Area



- Hilly cross-country tracked and wheeled vehicle endurance and reliability test area
- 250 acres with 11 miles of interconnecting roads and test courses
- 7% to 29% grades
- 3-mile and 4-mile winding closed loop courses
- Mud, dust, and gravel surfaces
- Temperate climate
- 4-bay maintenance shop
- Complete coverage with telemetry/on-board instrumentation
- Slopes are prepared by tilling and water supply is available for wetting



Vibration Facility



Vertical Exciter



Horizontal Exciter

- Three remotely controlled electrodynamic vibration systems capable of testing to MIL-STD-810E
- Safety certified for tests of hazardous and radioactive items
- Shock and vibration tests of vehicles, equipment, weapons, and ammunition
- Damping characteristics of vehicle suspension systems
- Ride quality
- Laboratory vibration schedules developed from field data
- Temperature range from -70 °F to +170 °F
- Vibration exciter force capabilities up to 40,000 force pounds
- Single axis; three planes



Instrumentation Development



Advanced Distributed Modular data Acquisition System (ADMAS)

- ATC engineers and scientists are recognized at all levels of DoD for their expertise for the application of emerging technologies to current test methodologies and the development of test equipment, measurement instrumentation and test facilities
- Scientific and engineering services for the development and integration of:
 - Measurement instrumentation
 - Test methodologies
 - Test equipment
 - Test related infrastructure
- Development capabilities include, but are not limited to:
 - Concurrent engineering
 - Software
 - Embedded instrumentation
 - Communications
 - Data acquisition and archival
 - Mechanical design
 - Systems integration
 - Custom fabrication
 - System procurement
 - Civil engineering
 - Technical consulting



OUR ULTIMATE CUSTOMER



**Tomorrow's
Warfighter**

Testing of COTS/NDI Products



Joint Service Power Exposition
25 April 2007

Testing of COTS/NDI Products



Joint Service Power Exposition
25 April 2007



Session 10

Introduction

Mr. John O'DONNELL, USMC

Marine Corps Approaches

Mr. John O'DONNELL, USMC

Navy COTS Testing

Mr. Randy Haag, Manger, Power Systems Division NSWC Crane

COTS Testing By the ARMY

Mr. Jose Antonetti , Test Director
US Army Aberdeen Test Center

Testing of COTS/NDI Products



USMC Approach

John O'Donnell

John.h.odonnell@usmc.mil

Joint Service Power Exposition

25 April 2007

Testing For Military Use



- **Why COTS ?**
- **Cheaper**
- **Get quicker Avoid Development and Qualification**
- **Vendor handles Configuration and Tech Data Package**
- **Faster Delivery Schedule**

Why Do We Test?



- **The operating environment is more extreme**
 - Greater Temperature extremes**
 - Sand and Dust Rain and Salt Air**
 - EMI interference issues**
 - The transportation conditions are more extreme**
 - The power used for power is from Generators (greater surges sags and phase anomalies)**

Transportation



- **The Marine profile is based on transportation off road 80% of the time.**
- **The transportation is in the back of truck**
- **Units are dropped and transported to extreme altitudes and via watercraft.**

Testing



- **Road Course Testing**
- **Loose cargo bounce**
- **Drop Testing**
- **Lift and Tie Down**
- **Environmental**
- **EMI**

Testing

Lift and Tie
Down



Drop
testing




Rail Impact



Testing Transportation



Testing Environmental




Temperature -40 to 160 F storage

-25 to 130F operating with solar

**Salt Fog Rain and Humidity Dust
and Sand**

Testing Environmental





Temperature -40 to 160 F storage

-25 to 130F operating with solar

**Salt Fog Rain and Humidity Dust
and Sand**

Testing EMI



Do I effect other equipment ?

Does other Equipment Effect Me?

Testing Performance




- **How will unit work in USMC environment does performance change?**
- **Does it perform as manufacturer claims?**
- **What are the safety issues ?**
- **Human Factors Is it Marine proof?**
- **Operational Testing with training module and manual evaluation**

Sample Power Supply Performance Test Plan

2. The following tests and examinations were performed:

M
10



Visual
*Initial Electrical
Drift
*Temperature
Humidity
Thermal Shock
Altitude
Vibration
Shock
Transit Drop
Bench Handling
Dripproof
*EMI
Salt Fog
*Post Electrical
Safety
Human Factors



Visual
*Initial Electrical
*Drift



Visual
*Initial Electrical
Drift
*Temperature
Humidity
Thermal Shock
Altitude
Vibration
Shock
Transit Drop
Bench Handling
Dripproof
*EMI
Salt Fog
Post Electrical
Safety
Human Factors



Visual
Initial Electrical
Drift
*Temperature

Post Electrical

Testing Conclusion



- **How will unit work in USMC environment?**
- **Will arrive intact?**
- **What are the limits of operation ?**
- **Is it Marine proof?**



2007 Joint Service Power Expo

COTS/NDI Navy Capabilities NSWC Crane Division Power Systems Division Overview

Presented By:
Sue Waggoner
Electronics Engineer
Power Systems Division
NSWC Crane Division
25 April 2007

COTS/NDI

- Batteries currently in production and commercially available**
- Expanded definition – chemistries available commercially with modification potential for form, fit and function to military application**

- **Smaller**
- **Lighter**
- **More capacity**
- **Last longer**
- **Cheaper**
- **Safer**
- **Greener**



Electrochemistries

Battery Types


Alkaline (Sealed/Vented)	Lithium (Reserve/Active)	Thermal
Aluminum-Oxygen (Air) Cadmium-Oxygen (Air) Carbon-Zinc Mercury-Cadmium Mercury-Zinc Nickel-Zinc Nickel-Iron Nickel-Cadmium Nickel-Hydrogen Nickel-Metal Hydride Silver-Zinc Silver-Cadmium Silver-Hydrogen Silver-Metal Hydride Silver-Iron Zinc-Manganese Dioxide Zinc-Oxygen (Air)	Carbon Monofluoride Copper (II) Oxide Copper Sulfide Iodine Manganese Dioxide Iron Disulfide Oxyhalide Polymer Sulfur Dioxide Sulfuryl Chloride Thionyl Chloride Vanadium Pentoxide Polymer Electrolyte Cobalt Oxide Manganese Oxide	Calcium/Calcium Chromate Calcium/Potassium Di chromate Lithium Iron/Iron Disulfide Lithium Aluminum/Iron Disulfide Lithium Silicon/Iron Disulfide Lithium Silicon/Cobalt Disulfide Magnesium/Vanadium Pentoxide
	Lithium (Rechargeable)	Lead-Acid
	Lithium-Ion Lithium-Polymer Lithium Alloy	Absorbed Electrolyte Antimony Grid Calcium Grid Gel Electrolyte Flooded Electrolyte Pure Lead Grid
		Other
		PEM Fuel Cell Seawater Ammonium Sodium-Sulfur

Capacity Ranges: 0.03 to 10,000 Ah

Harnessing the Power of Technology for the Warfighter

Power Systems Are Mission Driven

Submarines



Lead-Acid

VRLA

Ships



Lead-Acid

Fuel Cells

Weapons



Ag/Zn

Thermal

Ambient LI

Aircraft



Lead-Acid

NiCd

NiMh

Li-Ion

Space Apps



NiCd


NiMh

NiH


Li-Ion

Progressing Technology

Our Focus Areas



Commercial Vs Naval Batteries






How Do They Compare?

- **Typical Naval Standards:**
 - 5 - 20 Year Shelf Life
 - 0.05% - 5% Per Year Shelf Discharge
 - -65F - 185F Temperature Range
 - 8g - 30,000g Shock
 - 0.05 - 4 Atm Pressure

- **Typical Commercial Standards:**
 - 1 - 2 Year Shelf Life
 - 5% - 25% Per Year Shelf Discharge
 - 10F - 140F Temperature Range
 - 1g - 4g Shock
 - 0.1 - 1.2 Atm Pressure

Battery Involvement

Development to Disposal



PRODUCTS

- Batteries
- Fuel Cells
- Supercapacitors
- Battery Chargers & UPS
- Power Supplies

PROCESSES

- Applied Research
- Design
- Systems Engineering
- System Selection
- Acquisition Engineering
- Contract Administration
- Development
- Prototyping & Limited Mfg
- Standardization
- Test & Evaluation
- Acquisition



- Safety Certification
- Technology Evaluation/Insertion
- Production Engineering
- In-Service Engineering
- Failure Analysis
- Repair & Maintenance
- Demilitarization & System Retirement

- **Technology transition**
- **Established government industry team**
- **Knowledge brokers**
- **Acquisition/smart buyer support**
- **Production engineering**
- **Independent evaluation/oversight**
- **Test and evaluation**
- **Failure analysis**
- **Total Ownership Cost reduction**

Dedicated DoD Power Systems Resources

- **Professional workforce with a unique depth of battery experience**
 - Approximately 100 govt/industry employees dedicated to the development and acquisition of power systems
 - Programs for a wide range of sponsors supporting subsurface to aerospace applications
- **Over 150,000 sq ft full spectrum power systems facilities**
 - Includes newly dedicated (Fall 2005) MILCON and unique High Energy Test Facility
- **Over \$50M state-of-the-art T&E equipment**
 - Additional leveraging capability, allowing access to wide range of material/failure analysis equipment/facilities

Facilities

- **The Electrochemistry Engineering Facility (67,000 sq ft) is a state-of-the-art building for evaluation of battery technology**
- **The facility includes : a dissection lab with a dry room, a prototyping lab, a fabrication lab, a small battery lab, and a power supply lab.**
- **Five environmental test cells**
 - **Hazardous/toxic waste collection and treatment system.**
 - **Integrated ventilation system**
 - **Physical isolated flooring (vibration systems)**
 - **Acoustical isolated walls/ceilings (vibration systems)**
 - **Reinforced walls & separation barrier (centrifuge)**
- **Integrated test control room**
- **Dry Room (3% RH)**
- **Asset Temperature Control and Conditioning Room (40° F)**



SPECIALIZING IN BATTERIES, FUEL CELLS, POWER SUPPLIES AND CHARGERS


- **The High Energy Test Facility contains 10 test cells**
 - Data acquisition, video, other sensing equipment
 - Capable of containing the energy released during abuse testing of high energy batteries (Up to 10 lbs TNT equivalent)
 - Environmental conditioning (centrifuge, shock, vibration, altitude, temperature, etc.)
 - Air scrubbing system in each test cell
- **Over 90,000 sq ft of laboratory/office space**




Who We Work With




Private Sector



Academia





- *Lead Maintenance Technology Center*
 - Electrochemical Systems (NAVAIR)
- *Technical Direction Agent (TDA)*
 - Standard Missile Batteries (NAVSEA)
 - Special Warfare Batteries (WARCOM)
 - AN/WSN-2, 2A & 5 System Batteries
- *In-Service Engineering Agent (ISEA)*
 - Swimmer Delivery Vehicle Battery
 - Submarine and Submersible Main Storage Batteries (NAVSEA)
 - Seal Delivery Vehicle Automated Battery Charger (WARCOM)
 - Advanced Seal Delivery System Battery
- *Qualifying Agent*
 - Trident, Seawolf & New Attack (Virginia Class) Submarine Battery
- *Overhaul Point*
 - AN/WSN-5 & 7 Batteries (NAVICP)

- **Co-Lead Lab**
 - Lithium Battery Safety Certification (NAVSEA)

- **MOU**
 - Weapon System Batteries (US Army Missile Command)
 - Electrochemical Power Sources (NSWC Carderock)

- **MOA**
 - AVBATTSS (Army Aviation, NAVAIR, NAVSUP, Air Force, Marine Corps Research, Development & Acquisition Command, NASA, Air Force Logistics Command on Aviation)
 - Submarine and Submersible Main Storage Battery Life Cycle Mgmt
 - Co-Chair, Submarine Main Storage Battery Steering Committee
 - Engineering Support to DSCR, such as Development, Testing, Qualification, & Specification Maintenance of Power Systems

- **Acquisition Engineering Agent**
 - Submarine and Submersible Main Storage Batteries (NAVSEA)

Examples of Collaboration

Navy/Army/Air Force/Maine Corps/MDA – Power Technical Working Group - Navy
Principal Crane/Carderock/Panama City – MK 141 Battery Design and Prototyping

Crane/PHNSY – MSRA and Fleet Support

Crane/Sperry – Partnership on WSN-7 PBL

Crane/NOSSA – Quality Evaluation Agent for STANDARD

Missile, Rolling Airframe (RAM), HARM, Sidewinder, Sparrow, NULKA

Crane/Carderock – ADS, PRC-149, Lithium Battery Safety Program

Crane/Indian Head/China Lake – Naval Energetics Enterprise

Crane/Carderock NUWC - Fuel Cell Steering Committee

Academia/Private Sector – Various Cooperative Research and Evaluation agreements
and Congressional Plus-Up Programs

MOU

- Weapon System Batteries (US Army Missile Command)
- Electrochemical Power Sources (NSWC Carderock)
- Acquisition Engineering (DSCR)





US ARMY COMBINED ARMS SUPPORT COMMAND
Materiel Systems Directorate

Onboard Vehicle Power: *Talking Points on Emerging Requirements*

2007 Joint Service Power Expo

25 April 2007

TIMOTHY RANEY

The Balding Engineer Guy with Glasses, MTC Technologies, Inc.



Approved for Release by:

Fort Lee Public Affairs Office, Ms.
Sharon Mulligan, 2 April 2007.



Overview

- Background.
- Onboard Vehicle Power (OBVP).
- Military Hybrid-Electric Vehicles.
- Summary.



Background




- OBVP installed on about 100 HMMWVs in Army / USMC Units:
 - 3rd Corps Support Command and 82nd Airborne Division (~2000).
 - 22nd Marine Expeditionary Unit (2005).
- Limited **Operational** & Technical Evaluations:
 - **OBVP Concept Experimentation Program, CASCOM & ATEC 1998.**
 - **Final Report, CASCOM - May 2001.**
 - PM LTV limited technical & safety testing - Sep. 2003.
 - Positive industry efforts - results may not apply to military environment.
 - DoD PM MEP Export Power Specification (MEP-STD-001) - 2003.
 - TACOM issued Ground Precautionary Message to Units - Dec. 2003.
 - USMC PM EPS Market Surveys & Onboard Power IPT - 2002-2004.
 - USMC OBVP [small] program - 2004.
 - TARDEC & CERDEC [PGB] Technical Evaluations - 2004-2005.
 - **CASCOM Tactical Wheeled Vehicle On-Board Power Study -2005-2006.**
 - USMC OBVP [medium & large] programs - 2005 - 2007 (ongoing).



OBVP Overview


Onboard Vehicle Power



Exports AC power from an integral onboard power source to external applications. The underlying operational capability is "exporting tactical electric power". Output power has ranged to 20kW.

General Technical Approaches:

- Belt-driven alternator.
- Shaft-driven alternator.
- Hydraulic-driven alternator.





OBVP Overview



Technical & Operational Investigations.

USMC is investigating technical solutions and the US Army has studied the operational need. The intent is to identify technical approaches & mission applications where OBVP can provide an operational advantage.



OBVP Overview



Applications.

OBVP for tactical wheeled vehicles (TWV), developed for military environments, could power external applications throughout the Services & other Government agencies. They could export power to command & control (C2) systems much the same as conventional gensets. However, OBVP is generally limited to relatively short periods of operation compared to Tactical Quiet Generators (TQGs).



OBVP Mission Criteria



- Use when unit must minimize space needs aboard aircraft or watercraft.
- Use when powered equipment is on or near TWV.
- Use if TWV & supported systems never operate independently.
- Use when mission-critical equipment needs back-up power.
- Use as auxiliary power for onboard systems when on-the-move.
- Unit must consider temporary loss of mobility given METT-T*.

* METT-T: mission, enemy, terrain, troops available & time available



OBVP Design Criteria



Design must encompass user needs -

- Export Power - MEP-STD-001.
- Power quality - MIL-STD-1332B.
- Minimize fuel consumption increases.
- Minimize onboard weight and space claims.
- Endure severe operational & climatic environments.
- No adverse affect on host vehicle reliability & maintainability.
- OBVP should minimally affect cargo capacity or towing capabilities.





Sample Applications for OBVP



- Power for maintenance & construction (power tools).
- Charging individual Soldier equipment batteries.
- Power-on-the-move for C2 - niche now filled by 5kW & 10kW auxiliary power units - APUs.
- Powering isolated company-level Command Posts for 2 to 3 days (scenario dependent).
- Onboard power for weapons, IED-defeat & targeting systems.
- Floodlights at security check-points.

*10kW Output
Range*



Sample Applications for OBVP



- Power for tactical unmanned aerial systems (UAS) support equipment.
- Early entry forces, when high speed mobility is essential & cannot tow gensets.
- Back-up power for Command Posts, Tactical Operations Centers (TOCs) & other activities.
- Emergency power for equipment supported by 3kW to 10kW TQGs.
- Provide power to teams, patrols, convoys, during unexpected delays.
- Power for movement control teams-lights, communications, battery charging.



OBVP Operational Benefits & Drawbacks




Benefits

- Power flexibility for onboard & off-board applications
- Backup power for critical systems
- Provides power where it's unavailable
- Another power option for combatant commander
- Eliminates towed genset when that's a mission need
- Least complex to implement as a kit
- Good general purpose power option until gensets become available

Drawbacks

- TWV becomes a stationary genset
- Increased fuel needs (~30%)*
- Engine wet-stacking likely
- Space claims & increased weight
- Loss of cargo space on genset trailer
- Scheduled maintenance conflict - engine hours or mileage; now both
- Added engine wear & potentially reduced system reliability

One Example



* If operated according to the Tactical Electric Power Operational Mode Summary / Mission Profile (OMS/MP)



10kW OBVP HMMWV vs. TQG Fuel Costs



- Fuel costs - 10kW TQG¹ (300 hrs = peacetime genset fleet average).
 - 0.97 gal/hr X 300 hrs = 291 gals.
 - Fuel cost² = \$15.30/gal X 291 gals = \$4452.00
- Fuel costs - HMMWV (with 10kW OBVP alternator):
 - 1.4 gal/hr X 300 hrs = 420 gals.
 - Fuel cost² = \$15.30/gal X 420 gals = \$6426.00

**~44% more
fuel used**

1. DoD PM MEP Handbook-Standard Family of MEP Generating Sources, 2002.

2. Fuel cost = \$15.30 per gallon, FY07 DESC-subsidized cost of \$2.30 per gallon for JP-8 and \$13.00 per gallon for handling. Fuel handling data extracted from "More Capable Warfighting through Reduced Fuel Burden", DoD Science Board Study, January 2001.



OBVP Study Conclusions



- 10kW OBVP recommended for ~7% of light/medium TWV fleet based on mission needs.
- 10kW OBVP system would meet most unit needs (many applications under 10kW).
- Key operational benefit is back-up power for mission-critical systems.
- OBVP will not reduce trailer needs; they have additional uses (cargo).
- OBVP can supplement, but would not eliminate conventional generator sets.
- OBVP can provide power where it's unavailable now.



OBVP Study Conclusions



- 10kW OBVP increased operating costs (fuel) are significant if employment matches TEP OMS/MP.
- OBVP can augment vehicle power for platforms with more weapons & other onboard systems.
- Most likely OBVP uses include augmentation, backup & setup/teardown at operational sites.
- Mitigating the truck vs. genset functional conflicts within units can be significant.

Potential Power Generation Capability for selected TWVs in Army Fleet



Tactical Hybrid Electric Vehicles (HEV)



≠



Many thanks to Mr. Bob Crow, Mr. Rob Roche (AMSAA) & Dr. Jim Cross, RDECOM.



Tactical H E Vs



Why haven't we fielded them yet?



Component-level progress:

- Power Electronics.
- Batteries.
- Motors.

System Progress?



~\$100M invested in HEV programs since 1995.

Many HEV components developed: motors, alternators, controls, improved semiconductors, cooling systems, etc.

Many of the basic components are almost ready to go.

But...

Two primary issues are preventing successful design and demonstration of military HEVs:

- Development of military vehicle driving cycles.
- Suitable energy storage media for a military environment.



Examples of Drive Cycle Data



- Drive cycle data collection acquires detailed time-sampled information on how Army TWVs are actually used.
- Designers use this data for systems analysis & design, e.g., design of military HEV propulsion batteries
- Before HEVs (no energy storage), driving cycles were not as important as they are now.

HEV propulsion battery design & life depends greatly on how the vehicle is used.

Inputs



Examples of Drive Cycle Data



Inputs

Mission Inputs:

- Vehicle speed & acceleration.
- Throttle position.
- Brake pedal apply force.
- Steering control position.
- Mission equipment electrical loads (radios, turret, etc.)

Environmental Inputs:

- Terrain Types.
- Primary & secondary roads.
- Cross-country (soil composition).
- Terrain slope.
- Terrain roughness.
- Ambient temperature.
- Crew-compartment temperature.



Drive Cycle Data



- The Army needs to develop driving cycles that are scientifically based on vehicle usage in a tactical environment (real data from field operations).
- Accurate & well-defined driving cycles are essential to military HEV propulsion battery design.
- Without driving cycle data, poor battery design results in a vehicle that fails to achieve expected HEV benefits.



Drive Cycle Data

Driving cycle development begins with -

- Instrumenting vehicle fleet & collect usage data.
- Statistical analysis then defines vehicle performance & becomes input for simulations.
- Designers use these simulations to model electrical loads during HEV system development.

Result =

*Efficient HEV Design
That Meets User Needs.*



Energy Storage

Efforts are on-going to develop large format, energy dense batteries for HEV propulsion.

Technical issues still remain:

- Energy density, charge & discharge cycles.
- Cell-balancing, power vs. energy density trade-offs.
- Operating at temperature extremes and safety.

Example: Each cell must have almost identical characteristics; having essentially the same internal resistance is critical.



Energy Storage



Other Technical issues...


- Weak cells can become an electrical load and/or reduce energy content & degrade output.
- Safety - lower resistance or shorted cells can become hotter & can ignite; many existing electrolytes are flammable & lithium electrodes can be very reactive.
- Better quality control, electronic cell-balancing, cell conditioning techniques & modular battery assemblies will help resolve these issues (more work is needed).
- Existing battery candidates are not suitable for military systems that experience severe climatic extremes.
- High temps accelerate self-discharge rates & complicate thermal management. Low temps reduce battery output.



Energy Storage



US Army TARDEC



US Army TARDEC

- Charge management, thermal, weight & space claim issues much greater vs. commercial HEVs.
- Military systems are much heavier
- Shock & vibration more extreme.
- Military temperatures are more extreme.



Energy Storage Issues



- Must have consistent battery chemical 'mix' (batch-to-batch & year-to-year).
- Must have consistent plate material, spacing & thickness.
- Same internal resistance for all cells (most desirable).
- Need rigorous process control & Acceptance Testing.



US Army RDECOM



HEV Summary



- Technical issues - significant R&D needed for military HEV propulsion batteries.
- Scientifically based MILITARY driving cycles are needed.... Data from a tactical environment.
- Propulsion battery design relies on having accurate & detailed driving cycles.
- Without operationally derived driving cycles, vendor fuel economy claims cannot be verified.
- If the battery is undersized for the load, reliability & life suffers.
- Battery life & reliability are dramatically affected by how it is used & misused.



Tactical Electric Power Team



E-mail Addresses, MSD-CASCOM

Mr. William Perdue - william.perdue@us.army.mil
Chief, Support Systems & Analysis Division.

Mr. Timothy Raney - timothy.raney@us.army.mil
Senior Analyst-Tactical Electric Power (MTC Tech., Inc.)

E-mail Addresses, Project Manager-MEP

Mr. Paul Richard - paul.richard@belvoir.army.mil
Acting Project Manager - Mobile Electric Power.

Mr. Alan Coady - alan.coady@belvoir.army.mil
Acting Deputy Project Manager - Mobile Electric Power.

LtCol Tom Bowers USMC - thomas.s.bowers@belvoir.army.mil
Product Manager - Small Power Sources, APUs & Power Distro.

LTC John Kelleher USA - john.kelleher@us.army.mil
Product Manager - Medium & Large Power Sources.

www.cascom.lee.army.mil



www.pm-mep.army.mil



References



MEP-STD-001, General Specification, Export Power-Vehicle Mounted (to 30kW), DoD Project Manager - Mobile Electric Power, 5 May 2004.

Onboard Power White Paper, Timothy Raney, MTC Technologies, Inc., for DoD Project Manager - Mobile Electric Power, 8 September 2005.

Tactical Electric Power Operational Requirements Document, CARDS# 16125, 11 August 2004.

MIL-STD-1332B, Definitions of Tactical, Prime, Precise and Utility Terminology for Classification of the DoD Mobile Electric Generators, 13 March 1973 (reactivated 10 July 2001).

DoD Directive# 4120-11, Standardization of Mobile Electric Power Generating Sources, 9 July 1993.

MIL-STD-1275B, Characteristics of 28V DC Electrical Systems in Military Vehicles, US Army Tank-Automotive & Armaments Command, 20 November 1997.

MIL-STD 461-E, Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems & Equipment, 20 August 1999.

MIL-STD-705C, Generator Sets, Engine-Driven, Methods of Tests & Instructions, 24 April 1989.

MIL-STD-1474D, Noise Limits for Army Material, 12 February 1997.

Army Regulation 700-101, Joint Operating Procedures Management and Standardization of Mobile Electric Power Generating Sources, 29 November 1999.

DoD Military Handbook-633F (Draft), Standard Family of Mobile Electric Power Generating Sources: General Description Information & Characteristics Data Sheets, May 2001.



Questions?

Thank You for Your Attention!



Joint Light Tactical Vehicle Power Requirements




DISTRIBUTION STATEMENT A: Approved for public release;
distribution is unlimited




Ms. Jennifer Hitchcock
Associate Director of
Ground Vehicle Power and Mobility

Ground Vehicle Power and Energy



**Non-Primary Power
Estimated Electrical Power Growth**





JLTV Vehicle Categories – Force Application

Mission Role Variants

Combat Tactical Vehicle –
Provide support for
maneuver forces (infantry
and combat arms)

- Infantry Fire Team Carrier
- Heavy Guns Carrier
- Anti-tank Missile Carrier

Power Estimates

Mobility + On Board + Exportable ~ 335-400HP

On Board Requirement – 7kW(t) 10kW(o)*

Exportable Requirement – 10Kw(t) 30kW(o)*

Silent Watch – 2 hours (t) 6 hour (o)*

(includes 2 SINCGARS, Blue Force Tracker, Remote weapon System)

* Stated in JLTV RFI Dec. 06, Attachment 2a



On Board and Export Power must be provided while vehicle is mobile or stationary



JLTV Vehicle Categories – Focused Logistics

Mission Role Variants

Provide support for combat support and combat service support forces

Utility Vehicle Light

Utility Vehicle Heavy

Shelter Carrier

Ground Mobility Vehicle

Power Estimates

Mobility + On Board + Exportable ~335-400HP


On Board Requirement – 7kW(t) 10kW(o)*

Exportable Requirement – 10Kw(t) 30kW(o)*

Silent Watch – 2 hours (t) 6 hour (o)*

(includes 2 SINCGARS, Blue Force Tracker, Remote weapon System)

* Stated in JLTV RFI Dec. 06, Attachment 2a



On Board and Export Power must be provided while vehicle is mobile or stationary



Mission Role Variant

Long Range Surveillance

Provide support for conventional force long range surveillance, Special Operations Command, plus other Service reconnaissance and surveillance forces conducting intelligence, surveillance and reconnaissance missions.

General Purpose

C2

Power Estimates

Mobility + On Board + Exportable ~280-320HP


On Board Requirement – 10kW(t) 14kW(o)*

Exportable Requirement – 10Kw(t) 30kW(o)*

Silent Watch – 4 hours (t) 12 hour (o)*

(includes 2 SINCGARS, Blue Force Tracker, Remote weapon System and Long Range Acquisition Sensor)

* Stated in JLTV RFI Dec. 06, Attachment 2a




On Board and Export Power must be provided while vehicle is mobile or stationary



Requirements - Functional Decomposition



Non Primary Power



Advanced Suspension


Ground Vehicle Power and Energy




JP8 Reformer



Hybrid Components



Militarized Commercial Engines



Energy Storage



Power Dense Quiet Power Generation





Back-up



Armor Holdings (AH) – FTTS Demonstrator

Maneuver Sustainment Vehicle (MSV) & Companion Trailer (CT)



Survivability & Force Protection

- Monocoque cab
- Modular Armor Kit
- Front, rear and side cameras
- NBC system
- Collision avoidance
- 2 person cab

Network Centricity

- Integrated communications suite
- Integrated computer system

Sustainability

- 30 kW exportable AC power
- Enhanced On-board Diagnostics
- Lube for Life (bushings & bearings)

Transportability

- 96" w x 102" h x 406" l
- C-17 transportable
- 49,000 lbs. Curb Weight
- 75,000 lbs. Gross Vehicle Weight

Mobility

- Parallel Hybrid Electric Propulsion
- Air Suspension Height Control (ASHC) and Load Monitoring System (LMS)
- Central Tire Inflation System (CTIS) / run-flat
- Anti-Lock Braking System (ABS)

Payload

- 13 Tons - Residual Payload w / B Kit

Distribution

- Multi-functional LHS & MHE crane hook lift and a forklift
- 6,100 lbs at 23 feet MHE
- 13,200 lbs at 24' 3" LHS

Operational Range

- 300 miles

- C9 8.4L engine (335 kW @ 2200 rpm)
- 4 NIMH batteries 8.5 amp hrs, 336 Volts
- Integrated starter/generator (ISG) 120kW peak, 100 kW continuous
- 7 speed hydrokinetic automatic transmission



MSV Companion Trailer (CT)

Commonality with MSV

- Axles, suspension, wheels, tires, brakes, ABS, Central Tire Inflation System (CTIS), 24 Volt CAN/Bus System

Distribution

- Receives Flat Racks and ISO containers from Truck Load Handling System (LHS)
- Move loads and trailer without truck

Mobility

- 3 Axle with semi-autonomous operation
- Steering on Axle #1 and #3
- Turning radius (Autonomous): 20 ft-8 in
- Max speed 1.89 MPH
- Vertical Obstacle 24 in Step
- Gradient (Autonomous) – 30%
- Air Bag Independent Wishbone Suspension with ride height control
- 230 mm Jounce, 200mm Rebound
- Central Tire Inflation System (CTIS)

Deployability

- Self-Powered offload C-130 and operational watercraft Joint Requirement

Operational Range

- Range 65 miles
- Power Diesel Engine (73 HP)
- Hydrostatic Drive Train
- Tethered Coupled / Wireless Uncoupled Control



International Military Group – FTTS Demonstrator

Utility Vehicle (UV) & Trailer

Survivability & Force Protection

- Monocoque cab
- Modular Armor Kit
- 2 person cab

Network Centricity

- Integrated communications suite
- Integrated computer system

Sustainability

- Limited on-board diagnostics
- 75kW integrated, exportable AC power

Transportability

- 92" w x 83" h x 221" l
- CH-47 and C-130 Transportable
- Demonstrator curbweight = 18,600 lbs
- Reducible weight = 16,400 lbs

Mobility

- Parallel Hybrid electric propulsion
- Torsion bar suspension, passive shocks
- Designed for adjustable ride height control
- Central Tire Inflation Systems (CTIS)
- Rear axle steer
- Anti-Lock Braking System (ABS)

Payload

- 3400 lb payload with integral armor
- On-board crane with 800 lb lift @ 8'

Operational Range

- Over 555 mile range



UV Companion Trailer

Commonality with UV

- Common tires, suspension, brakes with truck

Payload

- 5500 lb payload





Lockheed Martin – Owego – FTTS Demonstrator

Utility Vehicle (UV) & Trailer



Survivability & Force Protection

- Monocoque cab
- Modular Armor Kit
- Machine Gun Ringmount
- 2 crew + 1 jump seat

Network Centricity

- Integrated communications suite
- Integrated computer system

Sustainability

- Limited on-board diagnostics
- 8kW integrated exportable AC power

Transportability

- 95" w x 90" h x 229" l
- CH-47 & C-130 Transportable
- Demonstrator curbweight = 21,600 lb
- Reducible curbweight = 19,705 lb

Mobility

- Parallel Hybrid electric propulsion
- SLA suspension with Air Spring, passive shocks
- Adjustable Ride height control (4 position)
- Central Tire Inflation (CTIS)
- Anti-Lock Braking System (ABS)

Payload

- 3300 lb payload with A-kit armor
- On-board crane with 1000 lb lift @ 5'

Operational Range

- 528 mile range



UV Companion Trailer

Commonality with UV

- Common tires, suspension, brakes with truck

Payload

- 6100 lb payload


On-Board Vehicle Power



Joint Service Power Exposition
25 April 2007



Session 12





Session 14


In no order of preference

- William Henrickson E-power
- Nadr Nasr Oshkosh Truck Co
- Stephen Cortese BAE Systems
- Tom Trzaska General Dynamics



Alternator Amperage Rating on HMMWV at 28 VDC

AMPS



Marine Corps On-Board Vehicle Power Systems for Legacy Military Vehicles



**Joint Service Power Exposition
2007**




On-Board Vehicle Power Systems

DC-AC Power Inverters
1500- 3000 watts



OBVP - Medium
30 kW Add-on HMMWV




**Retrofits for
In-Theater Assets**



OBVP - Small
5 – 8 kW (HMMWV)



OBVP - Large
120 kW (MTRV)





Vehicle Power Inverters



- **Requirement for DC-AC Power Inverter**
 - **18-32 VDC input**
 - **120 VAC, single phase output**
 - **1800 watts minimum output**
 - **Easily installed**
 - **Readily available / commercial based item**
- **Market Research and testing conducted**
- **GSA schedule showed adequate competition**
- **Solicited, competed, awarded in 2007**
- **Multi-year contract awarded to IRIS QP-1800**
 - **Inverter**
 - **Ruggedized carrying case**
 - **NATO cable connector**
 - **5600 articles planned**



On-Board Vehicle Power - Small




- Up to 400 Amps at 28 VDC needed
- Army has lead on retrofit kit
 - Vehicles in theater
 - DC power needs



- USMC will procure kits in 2007/2008
 - M1114, M1151, M1152 configurations
- Continuing to investigate / test inverters at higher power levels for AC power needs
- Future USMC vehicles will be procured with 400 Amp capacity (LVSR, MRAP)



Alternator Amperage Rating on HMMWV at 28 VDC






On-Board Vehicle Power Medium & Large Systems

- **Technology Demonstrations funded by Office of Naval Research**
- **HMMWV based system:**
 - **30 kilowatts stationary / 10 kilowatts on-the-move**
 - **Will be mounted on HMMWV M1123**
 - **Power output at 120/208 VAC, 60 hz**
 - **Two vehicles can be connected in parallel (60 kW output)**
 - **Can synchronize to MEP-805B generator**
- **MTVR based system:**
 - **120 kilowatts stationary / 20 kilowatts on-the-move / 3 kW transition**
 - **Mk 23 Truck**
 - **Power output at 120/208 VAC, 60 hz**
 - **Can synchronize to MEP-807A generator**
- **Vehicles will be delivered in 2007 for evaluation**



On-Board Vehicle Power - Medium


DRS Technologies Selected for Hardware Fabrication Phase





On-Board Vehicle Power - Large

OshKosh Selected for Hardware Fabrication Phase





OBVP Schedule (HMMWV & MTRV)

FY06					FY07					FY08					FY09					FY10																											
O	N	D	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S	O	N	D	J	F	M	A	M	J	J	A	S

 **Concept Definition**

 **Down Selection**

 **Detailed Design / Fabrication**

  **Design Reviews**

 **Vendor Testing**

 **Delivery to Gov't**

Gov't Testing / Demonstration 

 **Transition to MARCORSYSCOM**

 **Maturation / Kit Development**

 **Gen 2 Vehicle Kit**

 **Integ / Testing**

 **Production Decision**




On-Board Vehicle Power Unique Applications

- **Power community continually requested to support other platforms**
 - **Tanks**
 - **Logistics Vehicle System**
 - **HIMARS**
 - **Light Armored Vehicle**
 - **Lightweight 155 Howitzer**
 - **Amphibious Assault Vehicle**
 - **Force Protection / Military Police**
- **Continued need for power for Jammers, Silent Watch, stationary applications**
- **Necessary when host vehicle incapable of power load, or host vehicle can not be retrofitted with larger alternator**
- **28 VDC Gensets needed (various sizes, ratings, restrictions)**



On-Board Vehicle Power - Unique



Watch FedBizOpps for solicitations



Joint Light Tactical Vehicle Power Requirements




DISTRIBUTION STATEMENT A: Approved for public release;
distribution is unlimited




Ms. Jennifer Hitchcock
Associate Director of
Ground Vehicle Power and Mobility

Ground Vehicle Power and Energy



**Non-Primary Power
Estimated Electrical Power Growth**





JLTV Vehicle Categories – Force Application

Mission Role Variants

Combat Tactical Vehicle –
Provide support for
maneuver forces (infantry
and combat arms)

- Infantry Fire Team Carrier
- Heavy Guns Carrier
- Anti-tank Missile Carrier

Power Estimates

Mobility + On Board + Exportable ~ 335-400HP

On Board Requirement – 7kW(t) 10kW(o)*

Exportable Requirement – 10Kw(t) 30kW(o)*

Silent Watch – 2 hours (t) 6 hour (o)*

(includes 2 SINCGARS, Blue Force Tracker, Remote weapon System)

* Stated in JLTV RFI Dec. 06, Attachment 2a



On Board and Export Power must be provided while vehicle is mobile or stationary



JLTV Vehicle Categories – Focused Logistics

Mission Role Variants

Provide support for combat support and combat service support forces

Utility Vehicle Light

Utility Vehicle Heavy

Shelter Carrier

Ground Mobility Vehicle

Power Estimates

Mobility + On Board + Exportable ~335-400HP

On Board Requirement – 7kW(t) 10kW(o)*

Exportable Requirement – 10Kw(t) 30kW(o)*

Silent Watch – 2 hours (t) 6 hour (o)*

(includes 2 SINCGARS, Blue Force Tracker, Remote weapon System)

* Stated in JLTV RFI Dec. 06, Attachment 2a



On Board and Export Power must be provided while vehicle is mobile or stationary



Mission Role Variant

Long Range Surveillance

Provide support for conventional force long range surveillance, Special Operations Command, plus other Service reconnaissance and surveillance forces conducting intelligence, surveillance and reconnaissance missions.

General Purpose

C2

Power Estimates

Mobility + On Board + Exportable ~280-320HP


On Board Requirement – 10kW(t) 14kW(o)*

Exportable Requirement – 10Kw(t) 30kW(o)*

Silent Watch – 4 hours (t) 12 hour (o)*

(includes 2 SINCGARS, Blue Force Tracker, Remote weapon System and Long Range Acquisition Sensor)

* Stated in JLTV RFI Dec. 06, Attachment 2a




On Board and Export Power must be provided while vehicle is mobile or stationary



Requirements - Functional Decomposition




Non Primary Power




Advanced Suspension


Ground Vehicle Power and Energy



JP8 Reformer



Hybrid Components



Energy Storage



Power Dense Quiet Power Generation



Militarized Commercial Engines





Back-up



Armor Holdings (AH) – FTTS Demonstrator

Maneuver Sustainment Vehicle (MSV) & Companion Trailer (CT)



Survivability & Force Protection

- Monocoque cab
- Modular Armor Kit
- Front, rear and side cameras
- NBC system
- Collision avoidance
- 2 person cab

Network Centricity

- Integrated communications suite
- Integrated computer system

Sustainability

- 30 kW exportable AC power
- Enhanced On-board Diagnostics
- Lube for Life (bushings & bearings)

Transportability

- 96" w x 102" h x 406" l
- C-17 transportable
- 49,000 lbs. Curb Weight
- 75,000 lbs. Gross Vehicle Weight

Mobility

- Parallel Hybrid Electric Propulsion
- Air Suspension Height Control (ASHC) and Load Monitoring System (LMS)
- Central Tire Inflation System (CTIS) / run-flat
- Anti-Lock Braking System (ABS)

Payload

- 13 Tons - Residual Payload w / B Kit

Distribution

- Multi-functional LHS & MHE crane hook lift and a forklift
- 6,100 lbs at 23 feet MHE
- 13,200 lbs at 24' 3" LHS

Operational Range

- 300 miles

- C9 8.4L engine (335 kW @ 2200 rpm)
- 4 NIMH batteries 8.5 amp hrs, 336 Volts
- Integrated starter/generator (ISG) 120kW peak, 100 kW continuous
- 7 speed hydrokinetic automatic transmission



MSV Companion Trailer (CT)

Commonality with MSV

- Axles, suspension, wheels, tires, brakes, ABS, Central Tire Inflation System (CTIS), 24 Volt CAN/Bus System

Distribution

- Receives Flat Racks and ISO containers from Truck Load Handling System (LHS)

- Move loads and trailer without truck

Mobility

- 3 Axle with semi-autonomous operation
- Steering on Axle #1 and #3
- Turning radius (Autonomous): 20 ft-8 in
- Max speed 1.89 MPH
- Vertical Obstacle 24 in Step
- Gradient (Autonomous) – 30%
- Air Bag Independent Wishbone Suspension with ride height control
- 230 mm Jounce, 200mm Rebound
- Central Tire Inflation System (CTIS)

Deployability

- Self-Powered offload C-130 and operational watercraft Joint Requirement

Operational Range

- Range 65 miles
- Power Diesel Engine (73 HP)
- Hydrostatic Drive Train
- Tethered Coupled / Wireless Uncoupled Control



International Military Group – FTTS Demonstrator

Utility Vehicle (UV) & Trailer

Survivability & Force Protection

- Monocoque cab
- Modular Armor Kit
- 2 person cab

Network Centricity

- Integrated communications suite
- Integrated computer system

Sustainability

- Limited on-board diagnostics
- 75kW integrated, exportable AC power

Transportability

- 92" w x 83" h x 221" l
- CH-47 and C-130 Transportable
- Demonstrator curbweight = 18,600 lbs
- Reducible weight = 16,400 lbs

Mobility

- Parallel Hybrid electric propulsion
- Torsion bar suspension, passive shocks
- Designed for adjustable ride height control
- Central Tire Inflation Systems (CTIS)
- Rear axle steer
- Anti-Lock Braking System (ABS)

Payload

- 3400 lb payload with integral armor
- On-board crane with 800 lb lift @ 8'

Operational Range

- Over 555 mile range



UV Companion Trailer

Commonality with UV

- Common tires, suspension, brakes with truck

Payload

- 5500 lb payload





Lockheed Martin – Owego – FTTS Demonstrator

Utility Vehicle (UV) & Trailer

Survivability & Force Protection

- Monocoque cab
- Modular Armor Kit
- Machine Gun Ringmount
- 2 crew + 1 jump seat

Network Centricity

- Integrated communications suite
- Integrated computer system

Sustainability

- Limited on-board diagnostics
- 8kW integrated exportable AC power

Transportability

- 95" w x 90" h x 229" l
- CH-47 & C-130 Transportable
- Demonstrator curbweight = 21,600 lb
- Reducible curbweight = 19,705 lb

Mobility

- Parallel Hybrid electric propulsion
- SLA suspension with Air Spring, passive shocks
- Adjustable Ride height control (4 position)
- Central Tire Inflation (CTIS)
- Anti-Lock Braking System (ABS)

Payload

- 3300 lb payload with A-kit armor
- On-board crane with 1000 lb lift @ 5'

Operational Range

- 528 mile range



UV Companion Trailer

Commonality with UV

- Common tires, suspension, brakes with truck

Payload

- 6100 lb payload



US ARMY COMBINED ARMS SUPPORT COMMAND
Materiel Systems Directorate

Onboard Vehicle Power: *Talking Points on Emerging Requirements*

2007 Joint Service Power Expo

25 April 2007

TIMOTHY RANEY

The Balding Engineer Guy with Glasses, MTC Technologies, Inc.



Approved for Release by:

Fort Lee Public Affairs Office, Ms.
Sharon Mulligan, 2 April 2007.



Overview

- Background.
- Onboard Vehicle Power (OBVP).
- Military Hybrid-Electric Vehicles.
- Summary.



Background



- OBVP installed on about 100 HMMWVs in Army / USMC Units:
 - 3rd Corps Support Command and 82nd Airborne Division (~2000).
 - 22nd Marine Expeditionary Unit (2005).
- Limited **Operational** & Technical Evaluations:
 - **OBVP Concept Experimentation Program, CASCOM & ATEC 1998.**
 - **Final Report, CASCOM - May 2001.**
 - PM LTV limited technical & safety testing - Sep. 2003.
 - Positive industry efforts - results may not apply to military environment.
 - DoD PM MEP Export Power Specification (MEP-STD-001) - 2003.
 - TACOM issued Ground Precautionary Message to Units - Dec. 2003.
 - USMC PM EPS Market Surveys & Onboard Power IPT - 2002-2004.
 - USMC OBVP [small] program - 2004.
 - TARDEC & CERDEC [PGB] Technical Evaluations - 2004-2005.
 - **CASCOM Tactical Wheeled Vehicle On-Board Power Study -2005-2006.**
 - USMC OBVP [medium & large] programs - 2005 - 2007 (ongoing).



OBVP Overview




Onboard Vehicle Power



Exports AC power from an integral onboard power source to external applications. The underlying operational capability is "exporting tactical electric power". Output power has ranged to 20kW.

General Technical Approaches:

- Belt-driven alternator.
- Shaft-driven alternator.
- Hydraulic-driven alternator.





OBVP Overview



Technical & Operational Investigations.

USMC is investigating technical solutions and the US Army has studied the operational need. The intent is to identify technical approaches & mission applications where OBVP can provide an operational advantage.



OBVP Overview



Applications.

OBVP for tactical wheeled vehicles (TWV), developed for military environments, could power external applications throughout the Services & other Government agencies. They could export power to command & control (C2) systems much the same as conventional gensets. However, OBVP is generally limited to relatively short periods of operation compared to Tactical Quiet Generators (TQGs).



OBVP Mission Criteria



- Use when unit must minimize space needs aboard aircraft or watercraft.
- Use when powered equipment is on or near TWV.
- Use if TWV & supported systems never operate independently.
- Use when mission-critical equipment needs back-up power.
- Use as auxiliary power for onboard systems when on-the-move.
- Unit must consider temporary loss of mobility given METT-T*.

* METT-T: mission, enemy, terrain, troops available & time available



OBVP Design Criteria



Design must encompass user needs -

- Export Power - MEP-STD-001.
- Power quality - MIL-STD-1332B.
- Minimize fuel consumption increases.
- Minimize onboard weight and space claims.
- Endure severe operational & climatic environments.
- No adverse affect on host vehicle reliability & maintainability.
- OBVP should minimally affect cargo capacity or towing capabilities.





Sample Applications for OBVP



- Power for maintenance & construction (power tools).
- Charging individual Soldier equipment batteries.
- Power-on-the-move for C2 - niche now filled by 5kW & 10kW auxiliary power units - APUs.
- Powering isolated company-level Command Posts for 2 to 3 days (scenario dependent).
- Onboard power for weapons, IED-defeat & targeting systems.
- Floodlights at security check-points.

*10kW Output
Range*



Sample Applications for OBVP



- Power for tactical unmanned aerial systems (UAS) support equipment.
- Early entry forces, when high speed mobility is essential & cannot tow gensets.
- Back-up power for Command Posts, Tactical Operations Centers (TOCs) & other activities.
- Emergency power for equipment supported by 3kW to 10kW TQGs.
- Provide power to teams, patrols, convoys, during unexpected delays.
- Power for movement control teams-lights, communications, battery charging.



OBVP Operational Benefits & Drawbacks




Benefits

- Power flexibility for onboard & off-board applications
- Backup power for critical systems
- Provides power where it's unavailable
- Another power option for combatant commander
- Eliminates towed genset when that's a mission need
- Least complex to implement as a kit
- Good general purpose power option until gensets become available

Drawbacks

- TWV becomes a stationary genset
- Increased fuel needs (~30%)*
- Engine wet-stacking likely
- Space claims & increased weight
- Loss of cargo space on genset trailer
- Scheduled maintenance conflict - engine hours or mileage; now both
- Added engine wear & potentially reduced system reliability

One Example



* If operated according to the Tactical Electric Power Operational Mode Summary / Mission Profile (OMS/MP)



10kW OBVP HMMWV vs. TQG Fuel Costs



- Fuel costs - 10kW TQG¹ (300 hrs = peacetime genset fleet average).
 - 0.97 gal/hr X 300 hrs = 291 gals.
 - Fuel cost² = \$15.30/gal X 291 gals = \$4452.00
- Fuel costs - HMMWV (with 10kW OBVP alternator):
 - 1.4 gal/hr X 300 hrs = 420 gals.
 - Fuel cost² = \$15.30/gal X 420 gals = \$6426.00

**~44% more
fuel used**

1. DoD PM MEP Handbook-Standard Family of MEP Generating Sources, 2002.

2. Fuel cost = \$15.30 per gallon, FY07 DESC-subsidized cost of \$2.30 per gallon for JP-8 and \$13.00 per gallon for handling. Fuel handling data extracted from "More Capable Warfighting through Reduced Fuel Burden", DoD Science Board Study, January 2001.



OBVP Study Conclusions



- 10kW OBVP recommended for ~7% of light/medium TWV fleet based on mission needs.
- 10kW OBVP system would meet most unit needs (many applications under 10kW).
- Key operational benefit is back-up power for mission-critical systems.
- OBVP will not reduce trailer needs; they have additional uses (cargo).
- OBVP can supplement, but would not eliminate conventional generator sets.
- OBVP can provide power where it's unavailable now.



OBVP Study Conclusions



- 10kW OBVP increased operating costs (fuel) are significant if employment matches TEP OMS/MP.
- OBVP can augment vehicle power for platforms with more weapons & other onboard systems.
- Most likely OBVP uses include augmentation, backup & setup/teardown at operational sites.
- Mitigating the truck vs. genset functional conflicts within units can be significant.

Potential Power Generation Capability for selected TWVs in Army Fleet



Tactical Hybrid Electric Vehicles (HEV)



≠



Many thanks to Mr. Bob Crow, Mr. Rob Roche (AMSAA) & Dr. Jim Cross, RDECOM.



Tactical H E Vs



Why haven't we fielded them yet?



Component-level progress:

- Power Electronics.
- Batteries.
- Motors.

System Progress?



~\$100M invested in HEV programs since 1995.

Many HEV components developed: motors, alternators, controls, improved semiconductors, cooling systems, etc.

Many of the basic components are almost ready to go.

But...

Two primary issues are preventing successful design and demonstration of military HEVs:

- Development of military vehicle driving cycles.
- Suitable energy storage media for a military environment.





Examples of Drive Cycle Data



- Drive cycle data collection acquires detailed time-sampled information on how Army TWVs are actually used.
- Designers use this data for systems analysis & design, e.g., design of military HEV propulsion batteries
- Before HEVs (no energy storage), driving cycles were not as important as they are now.

HEV propulsion battery design & life depends greatly on how the vehicle is used.

Inputs



Examples of Drive Cycle Data



Inputs

Mission Inputs:

- Vehicle speed & acceleration.
- Throttle position.
- Brake pedal apply force.
- Steering control position.
- Mission equipment electrical loads (radios, turret, etc.)

Environmental Inputs:

- Terrain Types.
- Primary & secondary roads.
- Cross-country (soil composition).
- Terrain slope.
- Terrain roughness.
- Ambient temperature.
- Crew-compartment temperature.



Drive Cycle Data



- The Army needs to develop driving cycles that are scientifically based on vehicle usage in a tactical environment (real data from field operations).
- Accurate & well-defined driving cycles are essential to military HEV propulsion battery design.
- Without driving cycle data, poor battery design results in a vehicle that fails to achieve expected HEV benefits.



Drive Cycle Data

Driving cycle development begins with -

- Instrumenting vehicle fleet & collect usage data.
- Statistical analysis then defines vehicle performance & becomes input for simulations.
- Designers use these simulations to model electrical loads during HEV system development.

Result =

*Efficient HEV Design
That Meets User Needs.*



Energy Storage

Efforts are on-going to develop large format, energy dense batteries for HEV propulsion.

Technical issues still remain:

- Energy density, charge & discharge cycles.
- Cell-balancing, power vs. energy density trade-offs.
- Operating at temperature extremes and safety.

Example: Each cell must have almost identical characteristics; having essentially the same internal resistance is critical.



Energy Storage



Other Technical issues...


- Weak cells can become an electrical load and/or reduce energy content & degrade output.
- Safety - lower resistance or shorted cells can become hotter & can ignite; many existing electrolytes are flammable & lithium electrodes can be very reactive.
- Better quality control, electronic cell-balancing, cell conditioning techniques & modular battery assemblies will help resolve these issues (more work is needed).
- Existing battery candidates are not suitable for military systems that experience severe climatic extremes.
- High temps accelerate self-discharge rates & complicate thermal management. Low temps reduce battery output.



Energy Storage



US Army TARDEC



US Army TARDEC

- Charge management, thermal, weight & space claim issues much greater vs. commercial HEVs.
- Military systems are much heavier
- Shock & vibration more extreme.
- Military temperatures are more extreme.



Energy Storage Issues



- Must have consistent battery chemical 'mix' (batch-to-batch & year-to-year).
- Must have consistent plate material, spacing & thickness.
- Same internal resistance for all cells (most desirable).
- Need rigorous process control & Acceptance Testing.



US Army RDECOM



HEV Summary



- Technical issues - significant R&D needed for military HEV propulsion batteries.
- Scientifically based MILITARY driving cycles are needed.... Data from a tactical environment.
- Propulsion battery design relies on having accurate & detailed driving cycles.
- Without operationally derived driving cycles, vendor fuel economy claims cannot be verified.
- If the battery is undersized for the load, reliability & life suffers.
- Battery life & reliability are dramatically affected by how it is used & misused.



Tactical Electric Power Team



E-mail Addresses, MSD-CASCOM

Mr. William Perdue - william.perdue@us.army.mil
Chief, Support Systems & Analysis Division.

Mr. Timothy Raney - timothy.raney@us.army.mil
Senior Analyst-Tactical Electric Power (MTC Tech., Inc.)

E-mail Addresses, Project Manager-MEP

Mr. Paul Richard - paul.richard@belvoir.army.mil
Acting Project Manager - Mobile Electric Power.

Mr. Alan Coady - alan.coady@belvoir.army.mil
Acting Deputy Project Manager - Mobile Electric Power.

LtCol Tom Bowers USMC - thomas.s.bowers@belvoir.army.mil
Product Manager - Small Power Sources, APUs & Power Distro.

LTC John Kelleher USA - john.kelleher@us.army.mil
Product Manager - Medium & Large Power Sources.

www.cascom.lee.army.mil



www.pm-mep.army.mil



References



MEP-STD-001, General Specification, Export Power-Vehicle Mounted (to 30kW), DoD Project Manager - Mobile Electric Power, 5 May 2004.

Onboard Power White Paper, Timothy Raney, MTC Technologies, Inc., for DoD Project Manager - Mobile Electric Power, 8 September 2005.

Tactical Electric Power Operational Requirements Document, CARDS# 16125, 11 August 2004.

MIL-STD-1332B, Definitions of Tactical, Prime, Precise and Utility Terminology for Classification of the DoD Mobile Electric Generators, 13 March 1973 (reactivated 10 July 2001).

DoD Directive# 4120-11, Standardization of Mobile Electric Power Generating Sources, 9 July 1993.

MIL-STD-1275B, Characteristics of 28V DC Electrical Systems in Military Vehicles, US Army Tank-Automotive & Armaments Command, 20 November 1997.

MIL-STD 461-E, Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems & Equipment, 20 August 1999.

MIL-STD-705C, Generator Sets, Engine-Driven, Methods of Tests & Instructions, 24 April 1989.

MIL-STD-1474D, Noise Limits for Army Material, 12 February 1997.

Army Regulation 700-101, Joint Operating Procedures Management and Standardization of Mobile Electric Power Generating Sources, 29 November 1999.

DoD Military Handbook-633F (Draft), Standard Family of Mobile Electric Power Generating Sources: General Description Information & Characteristics Data Sheets, May 2001.



Questions?

Thank You for Your Attention!



U.S. Army Research, Development & Engineering Command

On-Board Vehicle Power Briefing & Way Forward

25 April 2007



Power & Energy Integrated Product Team

Co-Chairs

Dr. Jim Cross, PM-MEP/CERDEC

Dr. Ed Shaffer, ARL

Mr. Tom Nguyen, RDECOM SOSI



Outline & Purpose

Purpose

Summarize results of collaborative RDECOM Power & Energy IPT assessment, recommendations, and way forward for meeting On-board Vehicle Power Needs Statement

Background

- **On Board Vehicle Power JUONS, 17 Jul 06**
- JRAC agreement to support, O/A 7 Sep 06
- P&E IPT initial assessment, 12 Sep 06
- Briefing to JIEDDO, 5 Oct 06 (updated 6 Oct 06)
- CERDEC Power Assessment, Sep – Oct 06
- COS IPT Face-to-Face, 18 Oct 06
- MG Nadeau and COL (P) Dellarocco briefing, 19 Oct 06
- JRAB Pre-Brief, 9 Nov 06
- AR2B (Army Resources and Requirements Board) – validates reqms
- **JRAC Briefing/Decision, 16 Nov 06**



Buffalo



6x6 EOD JERRV



RG-31



M1114



Bottom Line Up Front

- IPT conducted detailed technical analysis and power assessment versus JUONS nominal requirements
- JIEDDO PIR defeat systems represent major contributor to power requirements
- On-going and future vehicle power programs do not address urgent/immediate need for legacy fleet
- **Recommended Approach:**

HMMWV (M1114)

- **Technical Approach:**
 - 400A Niehoff MIL-STD alternator using enhanced pulley
 - Include 150-400W DC/AC inverter with convenience outlets
 - If increased power required above 60A (e.g., to meet CREWS future spirals) add Automatic Throttle Control in production kits
- **Cost:** \$0.86M for initial integration, testing/safety qualification, fielding and operational user assessment of 15 integration kits
- **Schedule:**
 - 120 days from approval to delivery of kits in theater
 - 165 days to operational assessment; procurement approval
 - TBD days to first production kit deliveries

RG-31

- **Technical Approach:**
Consider two approaches - evaluate on risk and component availability.
 - **ALT 1: Immediate Requirement:** 280A Niehoff alternator (MIL-STD, on Stryker) using enhanced pulley and high idle; include 150-400W DC/AC inverter convenience outlets
 - **ALT 2: Potential Spiral Improvement:** 400A Alternator (e.g. Fisher A5/60, Niehoff, other), coupled to AC/DC converter; include 150-400W DC/AC inverter convenience outlets
- **Cost:**
 - **ALT 1:** \$0.55M for initial integration, testing/safety qualification, fielding and operational user assessment of 5 integration kits
 - **ALT 2:** \$1.08M for initial integration, testing/safety qualification, fielding and operational user assessment of 5 integration kits
- **Schedule (ALT 1 only)**
 - 120 days from approval to delivery of kits in theater
 - 165 days to operational assessment; procurement approval
 - TBD days to first production kit deliveries

- REF and CERDEC conducting real world power assessment in theater – 60 day effort



Need Statement

System Definition and Power Requirements

- **Operate Following Systems**

- Communications Equipment - SINCGARS
- Blue Force Tracker (BFT)
- IED Defeat Equipment
 - Rhino
 - Blowtorch
 - Electra
 - Dragon Spike
- Common Remote Operating Weapon System (CROWS)
- Counter Radio-control- IED Electronic Warfare system (CREW)

- **Installation on Following Vehicles**

- M11XX HMMWVs
- RG-31
- Buffalo
- Cougar

- **DC Power**

- 28 VDC (14 VDC for engine controls)
- 250/390 amp (Standard/High Idle)
- Stationary Power (with vehicle in park) 15-20 kW
- Alternator must fit in same location as OEM alternator

- **AC Power**

- 3 phase 115V AC 400 Hz
- 220V AC split phase 60 Hz
- 120V AC single phase 60 Hz
- Require no more than 30 HP to generate 15 kW

- **Power Management**

- DC Objectives: 40 lbs / 1.5 cu. ft.
- AC Objectives: 50 lbs / 1.5 cu. ft.

“The On-Board Mobile Power System is a vehicle mounted power generation system designed to support the high amperage requirements of current and future vehicle mounted Counter-Improvised Explosive Device (C-IED), Command & Control (C2) and Force Protection Systems.”

Information extracted from need statement dated July 2006.



Note: Power requirements continue to evolve. Additional equipment will be added and/or removed from this system definition.



CERDEC Systems' Power Analysis Data

SYSTEM		Listed in Needs Statement	Voltage (DC)	CURRENT (Amps)		
				Standby	Nominal	Peak
Blowtorch		X	28	0.1	60	190
BFT	(Blue Force Tracker)	X	28	0.5	2.9	20
CREW	Current System	X	28	4.5	0	13
	Upgrade (Due Dec 06)		28	4.5	0	20
CROWS	M151 Protector	X	28	5	7	30
	XM101 CROWS		28	4	18	36
Gyrocam	GyroCam system		28	0	6	15
	Laserdyne Monitor		28	0	2	2
	Microwave		13.5	0	5	5
	Mast (w/ vehicle pneumatic)		28	0	0	2
	Mast (w/o vehicle pneumatic)		28	0	0	22
Rhino		X	28	0	40	48
SCIMITAR			28	0	26	73
SINGGARS	VRC-87, 88 (Single Short Range)	X	28	1.0	2.1	4.0
	VRC-89, 91 (Short/Long Range)		28	1.3	8.7	14.0
	VRC-90 (Long Range)		28	1.0	2.0	4.0
	VRC-92 (Dual Long Range)		28	1.4	13.9	18.5
Spirit Hawk	Current Prototype		28	0.7	0.7	2
	Rugged Version (being designed)		28	2.9	2.9	8
TALON	(Battery Charger)		120 VAC	0	2.5	4

Note: Information displayed in this chart was provided by system PM Office, responsible RDEC, or system manufacturer's engineering department.

 System owner recommended design load.
 Denoted significant JIEDDO system requirements



CERDEC Power Generation Analysis

- Analysis of **operational** current requirements shows that the vehicle will require 155 amps (HMMWV) and 173 amps (RG-31).
- Amperage (current) requirements significantly lower than stated in the Need Statement – decreased by more than 50%.
- Assumes all systems being used **at the same time** (worst case).
- On-board batteries will support short duration (< 1 sec) power spikes (common approach)
- TALON robot and Spirit Hawk not included in Need Statement.
- SCIMITAR not included per JIEDDO instructions.
- AC Power not required for interim solution
- Inadequate power with existing equipment at curb idle.

System	M1114	RG-31
	(Amps @ 28 VDC)	(Amps @ 28 VDC)
Basic Vehicle Load *	35	40
Battery Charging	5	5
SINGARS **	13.9	13.9
Blue Force Tracker	2.9	2.9
Subtotal	56.8	61.8
CROWS	18	18
CREW	20	20
Rhino ***	N/A	N/A
Blowtorch	60	60
Gyrocarn	N/A	13
Subtotal	98	111
TOTAL	154.8	172.8

* - RG-31 not verified at the time of this briefing

** - Load during dual channel long range transmission. During active receiving load drops to 1.4 A

*** - JIEDDO/REF indicate Rhino and Blowtorch not likely co-mounted. Blowtorch is worst case.



Potential HMMWV Solutions

Decision Summary

Potential Solution	Derated Amperage (A)	Excess Current (A)	Technical Risk	Operational Risk	Schedule	First Article Integration, Testing & Field Eval Costs	Fielding Cost (Per Unit)
400 A alternator, high idle setting	275.2	120	Low	Med	120 days	\$0.86 M	\$ 8 K
✓ 400 A alternator, enhanced pulley	215	60	Low	Low	120 days	\$0.86 M	\$ 9.5 K
400 A alternator, high idle setting, enhanced pulley	309.6	155	Low	Med	120 days	\$ 1 M	\$ 9.5 K
Fisher A5/60 Alternator	250	95	Med	Low	120 days	\$ 11.7 M	\$ 36 K
Fisher A5/60 Alternator, high idle	392	237	Med	Med	120 days	\$ 11.7 M	\$ 36 K

* Costs are engineering estimates as of 19 Oct.



Potential RG-31 Solutions

Decision Summary

Potential Solution	Derated Amperage (A)	Excess Current (A)	Technical Risk	Operational Risk	Schedule	Development First Article Integration, Testing & Field Eval Costs	Fielding Cost (Per Unit)
280 A alternator, high idle setting, enhanced pulley	176	3.5	Low	Med	120 days	\$ 0.550M	\$ 9.7 K
Fisher A5/60 Alternator (drop in)	250	77	Med	Low	220	\$1.08M	\$16 K
Fisher A5/60 Alternator, high idle	392	219	Med	Med	120 days	\$ 11.0 M	\$ 46 K
280 A Alternator & Fisher A5/60 Alternator Co-mount	465	292	Med	Low	120 days	\$ 11.0 M	\$ 46 K

* Costs are engineering estimates as of 19 Oct.



Strategies for Meeting CREW Spiral Power Increases

- Potential increases in near- and far-term power requirements due to new CREW spiral developments
- FY07 - <30-80A (Spiral 2.1)
- FY08 - <80-160A (Spiral 3.2)
- Estimates are "swags" – not based on actual technical information at present
- Likely to be much lower

HMMWV (M1114)

- **Current Recommended Technical Approach:**
 - 400A alternator with enhanced pulley
 - provides >60A extra power to current reqms
- **Spiral 2.1 (FY07) Technical Approach (if reqd):**
 - Use 400A alternator with enhanced pulley if final power increase <60A
 - Use 400A alternator with enhanced pulley with Automatic Throttle Control (ATC) if power increase >60A
 - Provides >75A excess power above CREW 2.1 reqm
- **Spiral 3.2 (FY08) Technical Approach (if reqd):**
 - Use 400A alternator with enhanced pulley with Automatic Throttle Control
 - Provides 155A of projected (conservative) spiral power requirement
 - Nearly meets even most pessimistic

RG-31

- **Current Technical Approach:**
 - 280A alternator with enhanced pulley and high idle
 - provides ~4A extra power to current reqms
- **Spiral 2.1 (FY07) Technical Approach (if reqd):**
 - Run parallel development of drop in 400A alternator (Fisher A5/60, Niehoff, or other).
 - Doesn't meet 120day requirement due to lead time on alternator
 - Provides 77A excess power over current requirements
 - Substantially meets maximum potential requirement of 80A.
 - Cost only marginally higher (<\$1M)
- **Spiral 3.2 (FY08) Technical Approach (if reqd):**
 - Use ~400A (Fisher A5/60, Niehoff, other) alternator with high idle setting
 - Add high idle to Spiral 2.1 solution
 - Provides ~219A extra power requirement over current requirements

SOLUTIONS



HMMWV – simply add ATC later (if reqd)
 RG-31 – run parallel effort using different 400A (Fisher, Niehoff, or other)



Recommended HMMWV & RG-31 Solutions

VEHICLE	TECHNICAL APPROACH	SCHEDULE (Delivery to Theater)	FIRST ARTICLE INTEGRATION, TESTING & FIELD EVAL COSTS (15 HMMWV & 5 RG-31)	PRODUCTION / INSTALLATION COSTS Unit / Total (18669 HMMWV & 321 RG-31)	RISK & POTENTIAL ISSUES
HMMWV (M1114)	400A Niehoff Alternator w/ enhanced pulley	120 days	\$ 0.860M	\$ 9.5 K / \$177.8 M	Low risk Availability of production alternator
R G 3 1	280A Niehoff w/ enhanced pulley and high idle	120 days	\$ 0.550M	\$ 9.7 K / \$3.1M	Moderate risk Availability of alternator Design of pulley and throttle control
	400A Alternator (Fisher A5/60, Niehoff, other) (Drop-in replacement)	220 days	\$1.08M	\$ 16 K / \$5.1M +	Moderate-High risk Availability of alternator Power Conditioning development

For RG-31, pursue 280A Niehoff solution initially.
Run parallel evaluation of larger (e.g. 400A) alternators in preparation for potential CREW spiral power requirements.

+ - Rough production cost estimate, will change with development



HMMWV On-Board Power Management Plan



15 - M1114 Vehicle Kits

- **Description:**
 - 400 Amp alternator upgrade with advanced pulley
 - AC/DC Inverter
- **Capability Gap**
 - Current 75 Amp at idle, min goal 155 Amp with a target of 200Amp at idle.
- **Program**
 - OBP JUONS
 - Quantity: Total 15 # OIF 0 # OEF
 - POC PM: Robert Rappold, PM LTV, DSN 786-2319
 - POC TARDEC: Andrew Schultz, Engineering, DSN 786-5075


• Funding

Event	Funding Request	Obligated	Remaining
Management	\$175,000.00		
Engineering/Test	\$350,000.00		
Integration	\$20,000.00		
Documentation	\$35,000.00		
Component Acquisition	\$207,000.00		
Transport	\$3,000.00		
Field Support	\$70,000.00		
TOTAL	\$860,000.00 (includes 15 kits)		
Production*	\$177.8 M for 18669 vehicle kits		

Projected 1st KIT in Theater : 1 March 07 based on start date of 01 Nov.

* Engineering estimate

• Schedule:



As of: 13 Nov 06



RG-31 OBVP (280A) Management Plan




- **Description:**
 - 280 Amp alternator upgrade with advanced pulley
 - AC/DC Converter
- **Capability Gap**
 - Current 100Amp alternator, 65 Amp at idle .
 - min goal 173 Amp with a target of 200 Amp at idle.
- **Program**
 - OBP JUONS
 - Quantity: Total 5 # OIF 0 # OEF
 - POC PM: Ross Boelke, PM AMS, DSN 786-8852
 - POC TARDEC: Sean Tominna, Engineering, DSN 786-8909

• Funding

Event	Budget	Obligated to date	Remaining
Management	\$175,000.00		
Engineering/Test	\$200,000.00		
Integration	\$20,000.00		
Documentation	\$14,800.00		
Component Acquisition	\$107,000.00		
Transport	\$3,000.00		
Field Support	\$30,080.00		
TOTAL	\$549,880.00 (includes 5 kits)		
Production*	\$3.1M (includes 321 kits)		

Projected 1st KIT in Theater : 1 March 07 based on start date of 01 Nov.
* Engineering estimate

• Schedule:



As of: Date



Path Forward

- JRAC supported recommendations
- Funding received January 2007
- TARDEC executing program
 - Components identified
 - Technical integration issues resolved
 - Testing on-going at Yuma Proving Grounds
 - Fielding to theater for evaluation in May
- 2nd Phase RG-31 solution pending
- Funding for implementation deferred until field tests completed
- Lessons learned to be transitioned to USMC and JLTV programs



DISCUSSION

Flexible Hybrid Power Architecture and Evaluation of Multiple Sources Under Load

25 Apr 07




Lt Josh Johnson
Propulsion Directorate
Air Force Research Laboratory
joshua.johnson@wpafb.af.mil

BRITES




AFRL/PR



Spiral Development/Transition

Technology Investment Schedule (FY) As of: 14 Aug 06



Description	Benefits to the War Fighter
Hybrid renewable energy sources deliver same energy in less weight.	<ul style="list-style-type: none"> • 50% reduction in weight over current batteries • Energy harvesting allows war fighter to recharge from multiple sources in the field • Easily upgradeable in the future • Versatility will accommodate/interface with new equipment
Technology	
<ul style="list-style-type: none"> • Optimized Li Ion battery for high power requirements • High Energy Density Fuel Cells • Intelligent Power Management harvests energy 	



Airman Energy Need

- **Battlefield Airmen operate a wide range of electronic equipment in order to image, target, compute, and communicate**
- **Airmen are often limited to the resources they can carry on their backs**

Power

Average: 25-50W

Peak: 400W

Mission Length: 1-14 days






BRITES Solution

High Rate Power/ Energy Storage



High Energy Density Power Source



Power Manager



Energy Harvesting


**Power
to
Equipment**

GOAL: 50% Weight Reduction

BRITES Spiral 1



- **Spiral 1 System**
 - MediPak Li Ion battery
 - SFC Power Manager
 - Electric Fuel Zn Air battery
- **Passed Developmental Tests**
 - Jul 06
- **Passed Operational Tests**
 - Sept 06
- **Currently in LRIP**





BRITES Spiral 2

- **Two contracts for Fuel Cells and Power Manager**

- Smart Fuel Cell



- Protonex



- **Two contracts for optimized Li Ion battery pack**

- Microsun

- MediPak



- **Received all systems 2Q FY07**

- **Currently testing various combinations of power sources**



BRITES Testing




- **Goal: Take several state-of-the-art fuel cells, batteries, and solar panels and test them under realistic load conditions in a hybridized system**
- **Test Setup:**
 - **MicroSun battery was used as Li Ion battery pack**
 - **Protonex power manager used to connect to all sources and all loads**
 - **Various power sources include: Ultracell, Protonex, AMI, SFC, Zn Air, and solar**
 - **Load profile developed for both 30V and 15V output, 40W average over 3hr cycles**



BRITES 30V & 15V Load Profile




BRITES Combined 30V & 15V Load





Zn Air Hybrid Testing


Zinc-Air Hybrid Tests





Ultracell Hybrid Testing


Ultracell Hybrid Tests





SFC Hybrid Testing

SFC Hybrid Test





Solar Hybrid Testing

- **Solar panel provided ~5W under hybrid load**
- **Solar panel provided as much as 42W charging battery only**
- **Some work must be done on Peak Power Tracking algorithm**
- **System capable of harvesting energy from:**
 - **5590s**
 - **Cigarette adapters**
 - **Power supplies**
 - **Car batteries directly**



Current Evaluation

- **System has shown “power source agnostic” capability**
 - System can draw power from multiple fuel cells of different types
 - System can draw power from alternative sources, i.e. solar
- **Increased energy density is achievable over 5590s**
 - 25% weight savings for Spiral 1 (MediPak battery, Zn Air battery, SFC power manager)
 - Initial test indicates 33% weight savings for Spiral 2 (Microsun battery, SFC fuel cells, SFC power manager)
- **Power Manager provides increased situational awareness of power usage**
- **Power Manager key to providing control over fuel cell operation and hybridization**
- **But several challenges still ahead...**



Hybrid Challenges

- **Fuel Cell reliability**
 - Could not run tests on all available fuel cells
 - Several fuel cells failed during testing
 - Goal: To run hybrid test for 72hrs straight
- **Fuel Cell stability**
 - Control needed when combining 2 or more fuel cells sharing load
- **Power Manager Communication**
 - Power Manager could not communicate with all fuel cells or batteries
 - Better communication and control of fuel cells needed



Hybrid Challenges

- **Power Manager Information**
 - Power Manager provided some but not all system information – Battery SOC, Fuel Level, Output Voltage, etc.
- **Power Manager Peak Power Tracking could Improve**
 - Implement better algorithm
- **Ruggedization and Reliability need to be increased in fuel cell technology**
- **Integration on rucksack and cable management can be improved**



BRITES Spiral 3

- **Continuing to develop high energy density sources in conjunction with other DoD agencies**
- **Power management development will finish out under existing contracts**
- **FY08 last year for AFRL funding**
- **Integration a lead challenge to make multi-technology energy system fieldable with future equipment suite**
- **AFRL plans to contract a leading integrator for Spiral 3 systems**
 - **Opportunities exist to insert high energy density (>600Wh/kg) technologies under this effort**



**PROGRAM MANAGER
EXPEDITIONARY POWER SYSTEMS
MARINE CORPS SYSTEMS COMMAND**

AutoDISE

**MSgt Fred McCue
Project Officer - Mobile Electric Power
Fred.mccue@usmc.mil**



Agenda

- **History**
- **System Capabilities**
- **USMC Version**



AutoDISE History



AutoDISE is the current U.S. Army computer based electrical camp planning tool.

Information and downloads are available on the internet at <http://www.autodise.net/>

- **Computer model developed to simulate the use of:**
 - **Distribution Illumination System, Electrical (DISE),**
 - **Power Distribution Illumination Systems, Electrical (PDISE).**
- **Designed for the use in Army systems**
- **Uses graphics interface.**
- **Standalone client application**
- **No formal install**
- **Run directly off of a CD**



AutoDISE History

- **AutoDISE is used to engineer Army DISE Layouts for systems that consist of:**
 - **Multiple shelters,**
 - **Electrical consumers, and**
 - **Electrical power generators.**
- **DISE (Army) and MEPDIS (USMC) consists of electrical cables, connectors, feeder centers, and distribution centers that are used to distribute electrical power to the equipment.**
- **A user of AutoDISE should refer to the operator and maintenance manual for MEPDIS**
 - *It is the authority over information presented in the user's guide and software.*




System Capabilities

- **Camp layouts to scale.**
- **Required equipment inventory.**
- **Phase balancing.**
- **Automatic connection of power distribution and power consuming items.**
- **Individual tent/shelter layouts.**
- **System analysis to include total kw, total loads, and available kW.**
- **User defined power distribution systems.**
- **User defined loads.**




System Capabilities





System Capabilities




Windows based pull down menus with drag and drop capability.



System Capabilities

Item Properties

Item Detail

Type: Generator
Name: 100kW
Icon:  [Change Icon](#)
Rating per Ø: 277.8 A
Mode: 120/208V, 3Ø 4-wire
Comments:

Connected Devices

Device	# Ø	Phase Loads			Rotation
		A	B	C	
M100 (1)	3	25	30	30	
Phase Load Totals:		25	30	30	

Item 1 of 10
Cancel

* Moving to new item auto-saves changes
- "Cancel" only applies to current item.


Ability to view each generator set and connected devices with load and phase details.



System Capabilities

Item Properties

Item Detail

Type: DISE
Name: M100 (1)
Icon: 
Comments:

Power Connections

Status	Name	I/O	# Ø	Rating (A)	Phase Loads			
					A	B	C	Ø
In Use	J-1	input	3	100	25	30	30	
Open	J-2	output	3	100	0	0	0	
Open	J-3	output	3	60	0	0	0	
In Use	J-4	output	3	40	5	10	10	
In Use	J-5	output	3	40	5	10	10	
In Use	J-6	output	3	60	15	10	10	
Open	J-7	output	1	20	-	-	0	C
Open	J-8	output	1	20	0	-	-	A

User can view each individual power distribution panel and all connected loads. The system allows views of available connection points. Also an automatic phase balancing feature will notify the user when phases are outside of user defined tolerances.



System Capabilities

Layout Inventory Inventory by Shelter Analysis

Layout Inventory (Click on column headers to sort)

Type	Name	Mode	Quantity	In Shelter?	# Ø	AC/DC	Generator
Generator	10kW	120/208V, 3Ø 4-wire	1	No	3	AC	10kW
Breaker Panel	A BOX	-	1	Yes - ICU (1)	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - PLX	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - ICW	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - ICU	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - Radiology Tent	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - PRE-OP/ICMS/POST-OP	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - TOC	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - ICU (2)	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - Sanitation Center	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - TOC	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - Feeding Tent	3	AC	Not connected
Breaker Panel	A BOX	-	1	Yes - Company HQ	3	AC	Not connected

Ability to export inventories to Excel, MS Word, or Adobe PDF Files.



USMC Version

- **USMC final version will include Army systems, plus:**
 - Old USMC MEPDIS,
 - New USMC MEPDIS,
 - USMC Field Wiring Harness,
 - All standard cable sets
- **Ability to recognize paralleled generator sets**
 - Beyond the Army power plant model,
 - Including operating in parallel through the new MEPDIS.
- **Warning when generator is running under wet stacking conditions**



USMC Version

- **CD-ROM will be the delivery medium**
 - **To be run as stand alone application**
 - **Will not be NMCI supported**
 - **Data files will need to be stored to your computer**
- **Crib-sheet handout for quick reference**
- **PowerPoint training package**
- **Final version available now.**



Fielding Issues

- **CDs are available now.**
- **See your FSR for your copy and training.**



IF NOTHING ELSE, REMEMBER THIS:

- **AutoDISE does not take the place of formal school training.**
- **It is designed to be used by someone trained in electrical camp planning.**



PROGRAM MANAGER EXPEDITIONARY POWER SYSTEMS MARINE CORPS SYSTEMS COMMAND

Questions ?





**PROGRAM MANAGER
EXPEDITIONARY POWER SYSTEMS
MARINE CORPS SYSTEMS COMMAND**

Tactical Generators

**MSgt Fred McCue
Project Officer Mobile Electric Power
fred.mccue@usmc.mil**



Agenda

- **Current Family of Equipment**
- **Recent Additions**
- **Supporting Efforts**
- **Equipment Buys and Deliveries**



Family of Mobile Electric Power

2KW 60HZ MEP-531A TAMCN B0980

3KW 60HZ MEP-16B TAMCN B0730

3KW 60HZ MEP-831A TAMCN B0730

10KW 60HZ MEP-003A TAMCN B0891

10KW 60HZ MEP-803A TAMCN B0891

10KW 400HZ MEP-813A TAMCN B0921

20KW 60HZ MMG-25 TAMCN B0930

30KW 60HZ MEP-005A TAMCN B0953

30KW 400HZ MEP-114A TAMCN B0971

30KW 60HZ MEP-805A/B TAMCN B0953

30KW 400HZ MEP-815A/B TAMCN B0971

60KW 60HZ MEP-006A TAMCN B1021

60KW 400HZ MEP-115A TAMCN B1016

60KW 60HZ MEP-806A/B TAMCN B1021

60KW 400HZ MEP-816A/B TAMCN B1016

100KW 60HZ MEP-007A/B TAMCN B1045

100KW 60HZ MEP-807A TAMCN B1045




ITEMS IN RED ARE AT, OR BEYOND, THE END OF THEIR LIFE CYCLE AND ARE BEING REPLACED



Recent Addition – B0980

Technical / Performance Data

- **Model:** MEP-531A Military Tactical
- **Weight:** 152 lbs (wet)
- **Fuel:** Diesel & JP-8
- **Noise:** 79dBA @7m
- **Starting:** Manual and Slave Start
- **Fuel Usage:** 0.33 gph
- **Dimensions:** 30" L x 16" W x 22" H
- **Output:** 2 kW @ 120 VAC, Single Phase, 60Hz
- **Transport:** Man-Portable
- **Acquisition:** Currently being fielded



General usage for this item is for remote security lighting and to replace commercial man-portable sub 2kw units already in use.

Currently 455 sets have been received.

36 for MARFORRES, 83 in support of the UOC program and 197 for Operating Force units.



Recent Addition – B0930

Technical / Performance Data

- **Model:** MMG25 (USMC Configuration)
- **Weight:** 2200 lbs. (wet)
- **Fuel:** Diesel & JP-8
- **Noise:** 65 dBA @23 ft.
- **Starting:** Electric
- **Fuel Usage:** 2.1 gph
- **Dimensions:** 77" L x 35" W x 52" H
- **Output:** 22 kW 120/208, Three Phase
- **Transport:** HMMWV towable (M-116 / LTT-MCC)
- **Acquisition:** Continued purchase by MARCORSSYSCOM
- **Support:** Direct Vendor support for supply



This unit was originally purchased based off an Urgent Needs Statement from OIF. The equipment was brought into the inventory specifically to support the TRC-170.

Currently 74 sets are in Iraq, 6 in MARFORRES, 20 at III MEF, 28 at II MEF and 26 at I MEF.

A full O & I level military TM with cataloged (NSN assigned) parts is under development and is scheduled for completion by the end of April 07.



Recent Addition – B1045

Technical / Performance Data

- **Model:** MEP-807A
- **Weight:** 5860 lbs.
- **Fuel:** Diesel & JP-8
- **Noise:** 72dBA @7m
- **Starting:** Electric
- **Fuel Usage:** 7.85 gph
- **Dimensions:** 106" L x 40" W x 65" H
- **Output:** 100 kW @ 120/208/240/416 VAC
- **Transport:** MTRV new trailer, LVS
- **Acquisition:** Fielding began in 2006



USMC received its first sets in April 06 and were used to meet a critical MPF Shortfall.

22 sets were fielded to II MEF in November 2006. The first 7 of 50 sets for I MEF are here now.

All MEFs will receive some sets and New Equipment Training before the end of FY07.

380 sets have been purchased 190 sets will be delivered to the USMC before the end of CY07.

72 of the sets were purchased by PM-Engineers to support the new Containerized Batch Laundry System



Supporting Efforts

- **Field Service Representatives (FSR) within each MEF and forward deployed to Iraq.**
- **MARCORSYSCOM funded Training FSR based at Marine Corps Engineer School (MCES).**
- **Inclusion of MCES and Operating Forces personnel in equipment demonstrations and evaluations.**
- **Enhanced New Equipment Training (NET) with follow on training available.**



Equipment Buys – PEI Rotation

- **\$91M in equipment buys in FY05, FY06 and FY07.**
- **618 - 3kW, 60hz sets**
- **1453 - 10kW, 60hz sets**
- **39 - 10kW, 400hz sets**
- **134 - 22kW, 60hz sets**
- **1139 - 30kW, 60hz sets**
- **13 – 30kW, 400hz sets**
- **444 - 60kW, 60hz sets**
- **22 - 60kW, 400hz sets**
- **380 - 100kW, 60hz sets**



Major Deliveries

ITEM	QTY	DESTINATION	DELIVERY DATE
MEP-831	522	ALBANY	MARCH 2006 -APRIL 2007
MEP-803A	219	ALBANY	FEBRUARY-MARCH 2007
MEP-803A	130	ALBANY / BARSTOW	APRIL-AUGUST 2007
MEP-805B	240	ALBANY	JULY-AUGUST 2006
MEP-805B	90	BARSTOW	JUNE 2007
MEP-805B	140	ALBANY	OCTOBER 2007
MEP-806B	50	ALBANY	APRIL 2007
MEP-807A	34	ALBANY	APRIL 2007
MEP807A	32	ALBANY	MAY 2007
MEP807A	31	ALBANY	JUNE 2007

This table shows major equipment deliveries only. Smaller shipments will arrive. Information on equipment availability is available from the Project Officer or Equipment Specialist. Because of the need to Reset the Force and Principle End Item (PEI) rotation requirements, most equipment purchase are being directed to Albany. All using units, regardless of location, will still have backorders filled as equipment becomes available.



Fielding Issues

- **New generators replace old hardware; get rid of the old.**
- **Ensure you factor new equipment into your embark & pre-deployment plans.**
- **Ensure your Marines get trained.**
- **Submit TOECRs via TFSMS to change allowances.**



IF NOTHING ELSE, REMEMBER THIS:

- **New equipment is continuously arriving.**
- **Ensure your backorders are submitted properly.**
- **Contact the Material Manager or Equipment Specialist at Albany if you are not receiving the replacements you need.**
- **Contact your FSR for technical assistance or remedial training.**



PROGRAM MANAGER EXPEDITIONARY POWER SYSTEMS MARINE CORPS SYSTEMS COMMAND

Questions ?



Power-Managed HMMWV Demonstrator

Joint Service Power Expo
April 25, 2007




Problem statement

- There is an urgent theater requirement for a self protection and IED defeat suite of subsystems on tactical wheeled vehicles (TWVs)
- HMMWV and EOD armored trucks (i.e. Buffalo, Cougar, RG31, etc.) do not have enough electrical power for this equipment
- The immediate power requirement is for 28VDC... 400 amps across the entire engine operating range
 - ONR/USMC OBVP program is developing AC export power
 - 115/230VAC is a future requirement for IED defeat
- DoD is seeking alternatives

Urgent Warfighter need

HMMWV integration considerations

HMMWV chassis packaging







No space claim available under the chassis


HMMWV engine with v-belts (old 6.2L)



HMMVV engine with serpentine belt (new 6.5L)



-  A) Static belt tension force vector
-  B) Pulley torque force vector (acts on crankshaft key)
-  C) Pulley torque reaction force (due to sum of all mechanical loads)
-  Engine main journal bearing side load (vector sum of A and C)



Bearing side load and crankshaft Woodruff key torque are serious HMMWV engine constraints

Potential solutions



Dual belt driven HV generator




Alternator + belt driven HV generator




Turbo alternator



Conventional 28VDC alternators



Flywheel ISG




Front crank mount ISG

Solution comparison

- Single and dual belt driven high voltage generators
 - + COTS solution, easy to install, low cost
 - Won't make full 400 amps 28VDC at idle, belt drive issues
- Turbo alternator
 - + Small, lightweight, easy to install
 - Will not make power at idle, high risk approach
- Conventional 28VDC alternators
 - + Easy to install, low cost, mature technology
 - Won't make full 400 amps 28VDC at idle, belt drive issues, inefficient
- Flywheel integrated starter generator (ISG)
 - + Ideal solution for new vehicle designs
 - Retrofit intrusive, requires transmission and torque converter removal / mod
- Front crank mount ISG
 - + Will make 400 amps 28VDC at idle, field retrofittable, efficient, robust
 - Retrofit more complex than belt drive approaches


Front crank mount integrated starter generator
(ISG) w/ electric accessories
Power-managed HMMWV

Power-managed HMMWV overview



- Provides 400 amps of 28VDC power (11.2kW) over the entire engine operating range
- Provides 1kW 115VAC power (expandable to 30kW 230VAC power)
- Generator installs directly on engine crankshaft for high reliability and high power capability
- Automotive accessories are electrified for high efficiency and superior health monitoring
- Cooling system is electrified for superior engine cooling performance, even at low speeds

System architecture



Engine dress



ISG mounted on HMMWV engine crankshaft

Electric motor powering existing power steer pump

Generator and electronics cooling pump

HMMWV cooler stack removed for clarity

Cooler stack and electric accessories installation



Engine fan controllers (4)

Electronics and generator Cooler

Main cooling fans (two of 4)

Engine radiators

Engine water pump and controller

All engine accessories are power-managed

Demonstrator status



- Vehicle build complete
- 400 Amp power delivery and electric accessory functions verified
- Final integration and road testing in process
- Will be available for targeted customer demonstrations in May 2007

Summary

- Satisfies urgent theater requirement for vehicle power
- Provides 400 amps of 28VDC over the entire engine operating range
- 30kW of clean 230VAC power may be added (as an option)
- May be installed in the field
- Space claim is compatible with HMMWV
- Will work on transmission PTO (for armored trucks)
- Improves HMMWV fuel consumption and system reliability
- Enhances HMMWV cooling system performance
- Flexible common modular power system (CMPS) architecture leverages FCS and ground combat vehicle developments

Electric Drive Approach to Mobile Power Platforms

Oshkosh Truck Corporation

Nader Nasr
Chief Engineer
Advanced Products Group




On Board Vehicle Power

Responding to military's needs for power in the theater

- **Military Relevance**

- Increased mobility, power for onboard weapons
- Back up power for mission critical equipment
- Increased cargo space, reduced logistic footprint
- Power options for early entry forces, high speed mobility

ProPulse® Electric Drive System



- Benefits

- Large amounts of AC power available for export
- Energy storage is an option
- No batteries
- Zero voltage maintenance
- Improved fuel economy
- Enhanced packaging flexibility

HEMTT A3

- TACOM PM Heavy
- Improved fuel efficiency
- 100 kW Export power




MTVR OBVP

- ONR funded program
- 120 kW of export power
- Maintain vehicle performance



Advanced Heavy Hybrid Propulsion System

- DOE / NREL 3 yr program
- Target 2x fuel economy
- Validation vehicle / Waste Management



Homeland
Security



ARFF
Applications


HEMTT A3



HEMTT A3

Program Primary Objectives

- Export Power Capability - 100kW
- Improved fuel economy
- Advanced Load Handling System
light weight design
- Meet HEMTT
objective requirements



HEMTT A3

Key Technologies - Present

- Light weight modular design
- Diesel electric series hybrid
- Ultracapacitor Energy Storage
 - No batteries, life of vehicle design
- 100kW Exportable AC power
- Variable height independent suspension
- Multiplexed electrical system w/ advanced diagnostics
- C-130 unload capability
 - Enhanced Load Handling System (ELHS)




HEMTT A3

Testing Completed

- 12K miles off road - Nevada
- Vehicle Performance testing
 - PSD Aberdeen
- Export Power Performance
 - PSD Aberdeen
- Fuel Economy >20% improvement



HEMTT A3 – Power Module



Reconnect Panel

Export Power Interface

Exportable Power:

100 kW @ 480 V or 240 V 60 Hz

86 kW @ 416 V or 208 V 50 Hz

86 kW @ 120 V 50 Hz or 60 Hz

Export Power Vehicle Interface Screens

Export Power Controlled From Inside Cab

- Adjustable voltage (primary voltage and fine adjustment)
- Adjustable frequency (primary frequency and fine adjustment)
- AC contactor on/off (turning on and off output power)



Export Power

Platform System Demo, August 2006 Aberdeen Test Center

Tests Performed:

- Short Term Transient
 - Response MIL-STD-705C
 - Section 608.1
- Long Term Steady State
 - Stability MIL-STD-705C
 - Section 608.2
- Harmonic Analysis
 - MIL-STD-705C
 - Section 601.4



MTVR On-Board Vehicle Power Office of Naval Research

BAA – 04 – 011



GET THERE FIRST

MTVR

- Performance

- Oshkosh TK-4™ Independent Suspension
- 70% Offroad Mission Profile
- 7.1 ton payload cross country
- 15 ton payload primary and secondary roads



- MTVR Based Variants


- Cargo, Dump Truck, Wrecker, HIMARS Re-Supply Vehicle, Tractor, LHS (load handling system)

MTVR OBVP Program – ONR Objectives


- Provide vehicle integrated power source
 - 120 kW of military grade export power
 - 21 kW of power on the move
- Easy retrofit of existing MTVR vehicle
- Use host vehicle's diesel engine for both mobility and power generation
- Retain MTVR performance
- Minimize weight
 - 25 lb / kW Threshold
 - 20 lb / kW Objective



OBVP System Overview



Export Power Interface



- Pure diesel electric solution
- No Energy Storage
- Synchronous generator design


OBVP Design

- 300 kW traction generator used for vehicle driving and providing stationary export power
- Synchronous generator design
 - Clean military grade power
 - No need for power electronics or conditioning
- Cab display is used to initiate switch over, voltage and frequency adjustments and diagnostics



Export Power Performance

- 5 wire CAM style connection - Marine Corps request
- Meets requirements of tactical quiet generator
 - 120 kW of stationary export power
 - 21 kW of power on the move
- Exceeds objective requirements, achieved 19 lb/kW



Project Status

- OBVP build complete – January 2007
- Vehicle commissioning complete – March 2007
 - Basic driving functionality
 - 120kW stationary export power
- Deliver for Government durability testing – December 2007



Summary

- Oshkosh's diesel electric technology presents a unique and superior solution for large mobile power requirements
 - lb/kW
 - \$/kW
 - Power quality
 - No batteries
- Leverage developed ProPulse[®] system and components
- Provide simple wiring interface, and swift transition to exporting power



Far Reaching Benefits

- Commercial
 - Improved MPG
 - Lower emissions
 - Packaging flexibility
 - Disaster relief
 - Export power 100 kW+
- Defense
 - Lower logistics burden
 - Export power
 - 100 kW+ Mil spec AC power
 - Higher performance
 - Increased functionality
 - Improved MPG



ProPulse® Technology Demonstrator – Katrina Support

MEP Power Generation

Generation

Distribution



3 kW TQG
MEP – 831A
B0730



Commercial 25 kW
HMMWV Towable
Non-TQG
No TAMCN



60 kW TQG
MEP – 806 A/B – 60 Hz
MEP – 816A – 400 Hz
B1021 / B1016



15, 30, & 100 kW
MEPDIS
B0595 / B0600 / B0605



2 kW MTG
MEP – 531A
New to USMC



10 kW TQG
MEP – 803A – 60 Hz
MEP – 813A – 400 Hz
B0891 / B0921



30 kW TQG
MEP – 805 A/B – 60 Hz
MEP – 815A – 400 Hz
B0953 / B0971




100 kW Mil-Std
MEP – 007A/B/C
B1045 / B1046



100 kW TQG
MEP – 807A
Fielding in FY06

120 kW
Mil-Std
MTVR OBVP

100 kW Mil-Std
HEMTT A3 Option



Your Questions



Export Power Developments

2007 Joint Service Power Expo

26 April 2007

Presenter:

**Tom Trzaska
Manager, Advanced Programs
GDLS Muskegon Technical Center
Muskegon, Michigan**

Agenda

- **Background**
- **Technical Objectives**
- **System Design**
- **Performance Testing**
- **Durability Testing**
- **Future Developments**

Background


- **GDLS and Magnet Motor GmbH Collaboration**
- **Robust Power Electronics Solutions**
 - **Electric Drive**
 - **Power Conditioning**
 - **Power Generation**
- **High Power Densities**
 - **Inverters to 13.75 kW/L**
 - **Bi-Directional DC/DC to 32.5 kW/L**



Power Generation and Management Experience

30 kW Export Power Unit

- Developed Under RST-V Program and GDLS Funding
- Provide Power to UOC and Fire Finder Radar
- Goal to Provide Similar Capability to 805 and 813 Gensets
- Exploit Inherent Power Generation Capability of Series Electric Drive



Unit Installed on USMC/ONR/DARPA RST-V



Replaced in Expeditionary Roles

Technical Objectives

- **Provide AC Power:**
 - **30kW 0.8Pf @ 60 Hz**
 - **10kW 0.8Pf @ 400 Hz**
 - **208/120VAC 3 Φ , 4 wire**
 - **Mil Std 1332 Class 2A/B**
- **Synchronize and Load Transfer**
- **131°F Operating Temp**
- **IEC 309, 100 amp connections**



Targeted Applications



Output Voltage Waveform

System Description

- **High Density Solid State DC/AC Inverter System**
- **Commercial IGBT Based**
- **PWM Waveform Synthesis**
- **Three Modules for Adaptable Integration**
- **Dual Frequency Capability**
- **Water Cooled Inverter/Filter**
- **Growth to 50hz and 240/416 VAC output**




ACC04 30 kW Inverter / Filter Unit




Interface and Control Panel

System Block Diagram




Summary Specifications

- **System Characteristics:**
 - ↗ **Input Voltage 300-800 VDC**
 - ↗ **Output: 120 / 208 VAC**
 - ↗ **Dual Frequency 60 / 400 Hz**
 - ↗ **WPG Cooled (10 l/min @ 70 °C)**
 - ↗ **Weight 110 kg**
 - ↗ **Volume 85Liters**
 - ↗ **Voltage Regulation <2%**
 - ↗ **Frequency Regulation <1%**



30 kW Inverter/ Filter Module


Performance Predictions



**Simulation of Synchronization Process to a Grid
-> Stabilization within 75 msec**

- **Full Circuit and Control Model Refined and Validated through Lab and Field Testing**



Performance Predictions



● Synchronization Control Model

Performance Testing

- Full Series of development bench tests completed at Magnet Motor
- On Vehicle Lab Testing
 - Inverter / Vehicle Control Tuning
 - Power Quality
 - Load Cycling: Step Apply and Load Dump
 - Inductive Load Start
 - Short Circuit



Step Load

Field & Durability Testing

- **Durability Testing**
 - **Mixed Course Durability**
 - **2 hour Export Power Cycles Every 100 Miles**
 - **Over 275 hours operation**
 - **Reliability Database established**
- **Technical & Durability Testing at APG**
 - **705 Testing**
 - **EMC**
 - **Durability Cycles**



RST-V with Export Power Units




Durability Load Test

Current Developments


- **RST-V System Upgrades Under Development**
 - **High Frequency Filtering**
 - **Voltage Measurement**
 - **Control Loop Calibration For High Power Factor Operation**
 - **Refinement Of Fault Detection Algorithm To Improve Motor Start Capability**

Current Developments

- **Current System Being Applied To HMMWV**
- **Core Electronics, Software Repackaged**
- **High Density PM Generator Added To Provide Power Generation**
- **Low Impact 20/30 kW Retrofit Kit**



Block Diagram



20/30 kW Export Power Concept

Current Developments (Cont.)


- **Initiating Portability Study to Other Platforms**
- **Initial Focus on Select MRAP Candidates**
- **Scope of Effort:**
 - **Develop BTA Installation concept for each platform**
 - **Design Mod Kit including installation hardware**




Portability Study Candidates

Summary

- **GDLS / Magnet Motor Team Has Demonstrated 30kw Export Power System**
- **High Density System Reduces Impact To Host Vehicle**
- **Extending And Refining Design For Portable Application To Wide Range Of Vehicles**



Current Generation Remains in Test



Future Electronics Assembly

On-Board Vehicle Power



Joint Service Power Exposition
25 April 2007



Briefings

- **Oshkosh Truck Corporation**
 - Nadr Nasr
 - Oshkosh Truck's Electric Drive approach to Mobile Power Platforms
- **ePower LLC**
 - William Henrickson
 - 30 kW On-Board Vehicle Power for the HMMWV
- **General Dynamics Land Systems**
 - Tom Trzaska
 - On-Board Vehicle Power for the HMMWV and MRAP
- **BAE Systems**
 - Stephen Cortese
 - Power Management and Mission Capability Integration for HMMWV

Electric Drive Approach to Mobile Power Platforms

Oshkosh Truck Corporation

Nader Nasr
Chief Engineer
Advanced Products Group




On Board Vehicle Power

Responding to military's needs for power in the theater

- **Military Relevance**

- Increased mobility, power for onboard weapons
- Back up power for mission critical equipment
- Increased cargo space, reduced logistic footprint
- Power options for early entry forces, high speed mobility

ProPulse® Electric Drive System



- **Benefits**

- Large amounts of AC power available for export
- Energy storage is an option
- No batteries
- Zero voltage maintenance
- Improved fuel economy
- Enhanced packaging flexibility

HEMTT A3

- TACOM PM Heavy
- Improved fuel efficiency
- 100 kW Export power




MTVR OBVP

- ONR funded program
- 120 kW of export power
- Maintain vehicle performance



Advanced Heavy Hybrid Propulsion System

- DOE / NREL 3 yr program
- Target 2x fuel economy
- Validation vehicle / Waste Management



Homeland
Security



ARFF
Applications


HEMTT A3



HEMTT A3

Program Primary Objectives

- Export Power Capability - 100kW
- Improved fuel economy
- Advanced Load Handling System
light weight design
- Meet HEMTT
objective requirements



HEMTT A3

Key Technologies - Present

- Light weight modular design
- Diesel electric series hybrid
- Ultracapacitor Energy Storage
 - No batteries, life of vehicle design
- 100kW Exportable AC power
- Variable height independent suspension
- Multiplexed electrical system w/ advanced diagnostics
- C-130 unload capability
 - Enhanced Load Handling System (ELHS)




HEMTT A3

Testing Completed

- 12K miles off road - Nevada
- Vehicle Performance testing
 - PSD Aberdeen
- Export Power Performance
 - PSD Aberdeen
- Fuel Economy >20% improvement



HEMTT A3 – Power Module



Reconnect Panel

Export Power Interface

Exportable Power:

100 kW @ 480 V or 240 V 60 Hz

86 kW @ 416 V or 208 V 50 Hz

86 kW @ 120 V 50 Hz or 60 Hz

Export Power Vehicle Interface Screens

Export Power Controlled From Inside Cab

- Adjustable voltage (primary voltage and fine adjustment)
- Adjustable frequency (primary frequency and fine adjustment)
- AC contactor on/off (turning on and off output power)



Export Power

Platform System Demo, August 2006 Aberdeen Test Center

Tests Performed:

- Short Term Transient
 - Response MIL-STD-705C
 - Section 608.1
- Long Term Steady State
 - Stability MIL-STD-705C
 - Section 608.2
- Harmonic Analysis
 - MIL-STD-705C
 - Section 601.4



MTVR On-Board Vehicle Power Office of Naval Research

BAA – 04 – 011



GET THERE FIRST

MTVR

- Performance

- Oshkosh TK-4™ Independent Suspension
- 70% Offroad Mission Profile
- 7.1 ton payload cross country
- 15 ton payload primary and secondary roads



- MTVR Based Variants


- Cargo, Dump Truck, Wrecker, HIMARS Re-Supply Vehicle, Tractor, LHS (load handling system)

MTVR OBVP Program – ONR Objectives


- Provide vehicle integrated power source
 - 120 kW of military grade export power
 - 21 kW of power on the move
- Easy retrofit of existing MTVR vehicle
- Use host vehicle's diesel engine for both mobility and power generation
- Retain MTVR performance
- Minimize weight
 - 25 lb / kW Threshold
 - 20 lb / kW Objective



OBVP System Overview



Export Power Interface



- Pure diesel electric solution
- No Energy Storage
- Synchronous generator design

OBVP Design

- 300 kW traction generator used for vehicle driving and providing stationary export power
- Synchronous generator design
 - Clean military grade power
 - No need for power electronics or conditioning
- Cab display is used to initiate switch over, voltage and frequency adjustments and diagnostics



Export Power Performance

- 5 wire CAM style connection - Marine Corps request
- Meets requirements of tactical quiet generator
 - 120 kW of stationary export power
 - 21 kW of power on the move
- Exceeds objective requirements, achieved 19 lb/kW



Project Status

- OBVP build complete – January 2007
- Vehicle commissioning complete – March 2007
 - Basic driving functionality
 - 120kW stationary export power
- Deliver for Government durability testing – December 2007



Summary

- Oshkosh's diesel electric technology presents a unique and superior solution for large mobile power requirements
 - lb/kW
 - \$/kW
 - Power quality
 - No batteries
- Leverage developed ProPulse[®] system and components
- Provide simple wiring interface, and swift transition to exporting power



Far Reaching Benefits

- Commercial
 - Improved MPG
 - Lower emissions
 - Packaging flexibility
 - Disaster relief
 - Export power 100 kW+
- Defense
 - Lower logistics burden
 - Export power
 - 100 kW+ Mil spec AC power
 - Higher performance
 - Increased functionality
 - Improved MPG



ProPulse® Technology Demonstrator – Katrina Support

MEP Power Generation

Generation

Distribution



3 kW TQG
MEP – 831A
B0730



Commercial 25 kW
HMMWV Towable
Non-TQG
No TAMCN



60 kW TQG
MEP – 806 A/B – 60 Hz
MEP – 816A – 400 Hz
B1021 / B1016



15, 30, & 100 kW
MEPDIS
B0595 / B0600 / B0605



2 kW MTG
MEP – 531A
New to USMC



10 kW TQG
MEP – 803A – 60 Hz
MEP – 813A – 400 Hz
B0891 / B0921



30 kW TQG
MEP – 805 A/B – 60 Hz
MEP – 815A – 400 Hz
B0953 / B0971




100 kW Mil-Std
MEP – 007A/B/C
B1045 / B1046



100 kW TQG
MEP – 807A
Fielding in FY06

120 kW
Mil-Std
MTVR OBVP

100 kW Mil-Std
HEMTT A3 Option



Your Questions





Workshop

Battery Technical Manuals and Milspecs

Susan M. Waggoner
Electronics Engineer
Code 6095, Bldg. 3287W
300 Highway 361
Crane, IN 47522-5001
Phone 812-854-4103, DSN 482-4103
Fax 812-854-1212
susan.waggoner@navy.mil



- **Update**
- **Comments**
- **Q&A**



- **Technical Manuals**
- **Milspecs**
- **Batteries**
- **Battery chargers**





Tactical Solar Power Systems

**Presented by:
NEST Energy Systems Inc.
Prescott, AZ**

**Tom Lederle
VP Product Development**

Tactical Solar Power Systems

- Types of electrical power sources
- What's wrong with what we have now?
- If we had our druthers
- What's deliverable TODAY

TACTICAL ENERGY SOURCES

Generators



Batteries



Fuel Cells



Solar



Why bother with renewable energy?

COST OF FUEL IN FORWARD AREAS

Depreciation	\$1.5M	8%	
Maintenance	\$1.5M	8%	
Fuel	\$7.9M	43%	} → (78%)
Support personnel	\$6.3M	35%	
Transport on battlefield	\$0.1M		
Transport to battlefield	\$0.8M		
TOTAL COST	\$18.1M		

Total KWH capacity 6,031,200 KWH (5600 hrs x 1077KW)

Cost delivered in forward areas → **\$3.00/KWH**



“State of the Art”

**Currently, there is no clean, quiet,
and “fuel-less” solution for
supporting large electrical loads
with highly portable units.**

DRUTHERS MEET REALITY

A reasonable compromise

- Sustain 3kw load continuously for 12 hours without harvesting or generation
- Support a 3kw load continuously for 15 days without intervention or refueling
- Towable on an LTTTC trailer behind a HMMWV over any terrain
- Ready for real-world deployment ASAP

Raven LTSU

Lightweight Towable Solar Unit



- Hybrid design uses onboard automatic genset
- Uses much less fuel than genset alone
- Easy to set up
- Immediate electrical power
- At Technology Readiness Level 6 now

Reduces fuel usage by nearly half

Raven LTSU

Lightweight Towable Solar Unit

LTSU vs genset-only, 15 day mission

Solar Gain and Fuel Consumption			
	GENSET ONLY		4.8 kw LTSU
Continuous load	3.0 kw		3.0 kw
Total kwh/day	72.0 kwh		72.0 kwh
Total kwh 15 days	1080.0 kwh		1080.0 kwh
Insolation factor			6.0
Solar collection		kw	4.8 kw
Solar gain / day		kwh	28.8 kwh
Solar gain 15 days		kwh	432.0 kwh
% of load by solar	0%		40%
Accumulated kwh deficit	1080.0 kwh		648.0
Less stored energy			40.0 kwh
Genset size	3.0 kw		3.0 kw
Genset fuel usage	0.33 hr		0.33 hr
Genset run time	360.0 hrs		202.7 hrs
Fuel used 15 days	118.8 gal		66.9 gal
Weight of jp8 / lb	6.42		6.42
Weight of fuel	762.7 lbs		429.4 lbs
Weight of genset	326.0 lbs		326.0 lbs



WEIGHT	
Container	700
Battery pack	890
Inverter, etc	100
Rack 3 x 24 foot truss	260
Panels 24 * 45# ea	1080
Genset (2kw diesel)	326
Fuel	429
TOTAL	3785

Raven LTSU

Lightweight Towable Solar Unit




- **Total weight 3800#**
- **3kw for 15 days without intervention**
- **3kw for 12 hours without generation or harvesting**
- **Droppable, flyable, etc.**
- **Literally bulletproof**



Large Scale Renewable Energy Production

LARGE SCALE RENEWABLE ENERGY PRODUCTION

NEST Transportable Solar Grid



- Arranged in “clusters” of 10-12 units (100kw+)
- For longer term requirements (6months+)
- All-up cost, less than \$1 per KWH in forward area

LARGE SCALE RENEWABLE ENERGY PRODUCTION

NEST Transportable Solar Grid




- **Deliverable by air, land and sea**
- **Clean, quiet power - no fuel required**
- **Power for force support areas**
- **Can be combined with genset for HYBRID operation**

LARGE SCALE RENEWABLE ENERGY PRODUCTION

NEST Transportable Solar Grid

- Supports reconstruction projects
- Disaster relief shelters/housing
- Military base housing
- Remote, off-grid areas





Technological Advancements Today and Tomorrow

Portable Renewable Energy Solutions

Enabling Technological Advancements


Innovative aluminum solar truss

Lightweight high-output PV
(encapsulated polycrystalline PV)

Computerized power management
and monitoring (SOLIS)

Hybrid steel / foam / kevlar
enclosure

High density battery pack
(LiFePO₄)



Portable Renewable Energy Solutions

Near Future (3-5 year) Developments

What's on tap...

- **Solar panels with 40-50% efficiency (2 to 3 times current COTS)**
- **Solar panel will cost \$1.50 per watt instead of \$5.00 per watt**
- **Batteries ten times as weight-efficient as lead-acid**

Portable Renewable Energy Solutions

Near Future Developments

If technology that's in the laboratory today were available tomorrow...

- We could provide a portable, towable solar unit that would supply 100% of the DREAM energy needs from solar alone. No noise, no fuel, no maintenance.
- We could manufacture large-scale solar systems that could be transported on two medium size trucks and would replace a 100kw generator that burns 200 gallons of fuel per day.

QUESTIONS / COMMENTS



NEST Energy Systems Inc.
7500 W. Pasture Lane, Prescott, AZ
8367 E. Pecos Drive, Prescott Valley, AZ
(928) 460-2811
www.NestEnergySystems.com






Portable Renewable Energy Solutions

Enabling Technological Advancements

SOLIS™ Energy Management and Security System




- **Secure, web-based communications protocol**
- **Interactive communications between unit & HQ**
- **Alerts to power fluctuations / intruders**
- **Optional surveillance / security system**

Portable Renewable Energy Solutions

Enabling Technological Advancements

Aluminum truss grid



- **Patented “truss-rack” design**
- **Accelerates deployment of large-scale PV systems**
- **Support panels at correct angle**
- **Wind, torsion, shear, load tested**
- **2 person set up, no special tools, expertise needed**

Portable Renewable Energy Solutions

Enabling Technological Advancements

Hybrid steel / foam / Kevlar shell



- In production
- Strong as reinforced 14g steel shell
- Reduces enclosure weight from 1200# to 360#
- Insulated, bulletproof (Kevlar sandwich)
- EMP protection

Portable Renewable Energy Solutions

Enabling Technological Advancements

Encapsulated polycrystalline PV



- **Encapsulation eliminates aluminum frame**
- **Simplifies assembly process**
- **U.S. -made**
- **Highest efficiency possible with COTS product**

Portable Renewable Energy Solutions

Enabling Technological Advancements

Lithium Iron Phosphate Energy Storage (LiFePO₄)



- **Much lighter than lead-acid, NiCad**
- **Safer than Lithium-polymer**
- **Faster charge, no heat issues**
- **Integrated battery charging / power management**



**PROGRAM MANAGER
EXPEDITIONARY POWER SYSTEMS
MARINE CORPS SYSTEMS COMMAND**

Solar Power Adapters and Deployable and Renewable Alternative Energy Module

**Major David C. Morris
Deputy Program Manager / Project Officer
david.c.morris@usmc.mil**



AGENDA

- **SPACES Project**
 - **Past Solar Power Adapter Efforts (SPACES)**
 - **Current SPACES Projects**
 - **Multipurpose Solar Device**
 - **24 Volt Tactical Radio Power Adapter (RPA)**
 - **Computer Power Adapter**
- **DREAM Project**



SPACES

- **Solar power adapters are part of the Solar Portable Alternative Communications Energy Sources (SPACES) project.**
- **SPACES is a family of solar powered devices intended to increase employment flexibility and reduce external power requirements.**
- **Some standard interfaces will be required**





PAST SPACES EFFORTS

- **Began in late 2005, concluded in mid-2006**
- **SPACES (v1.0) Included the following items:**
 - **Lead-acid battery chargers**
 - **Generator**
 - **Vehicle**
 - **Communications-electronics battery charger**
 - **Computer power adapter and battery charger**
 - **Radio power adapter and battery chargers**
 - **12 Volt Tactical Radios**
 - **24 Volt Tactical Radios**
 - **Variable power supply**



SPACES v1.0 OUTCOME

ITEM	OUTCOME
Lead Acid (Gen)	GSA (Pulse-Tech)
Lead Acid (Veh)	GSA (Pulse-Tech)
Battery Charger	RFP/no successful proposals
Computer Adapter	RFP/no successful proposals
12 Volt RPA	RFP/no successful proposals
24 Volt RPA	RFP/no successful proposals
Var Power Supp	Not pursued




LEAD-ACID BATTERY CHARGERS

- **Lead-acid battery chargers**
 - SP-BC-LA-G (Generator)**
 - SP-BC-LA-V (Vehicle)**
- **Intended to maintain charge in generator and vehicle batteries**
- **Separate competitive selections were made for the generator and vehicle chargers**
- **Pulse-Tech 24 Volt chargers were selected for both items**
 - **Generator charger does not have push-to-test battery meter**
 - **Vehicle charger has push-to-test battery meter**



LEAD-ACID BATTERY CHARGERS

- **Current status:**
 - **Vendor selected**
 - **Available**
 - **Modification Instruction (MI) for generator version is complete and published for TQG series**
 - **MI for vehicles is pending**





SPACES v1.0 REVIEW

- **Success for only 2 of 6 items in the SPACES family.**
- **What went wrong?**
 - **Did not communicate with industry during our specification development (no request for information, industry day, etc.)**
 - **Did not develop industry contacts to disseminate our request for proposals widely**
 - **Attempted an off-the-shelf contracting strategy when industry would have to develop the item**
 - **Requested performance levels were ambitious**



SPACES v1.0 REVIEW

- **What else went wrong?**
 - **Small business set aside (based on market research) probably limited us to vendors who could least afford to absorb initial development/integration costs**
 - **We required bid samples – they were intended to reduce risk for the government, but providing them probably exacerbated all the other issues in play at the time.**




SPACES v2.2 STRATEGY

- **Most SPACES (v1.0) solicitations failed to attract successful proposals.**
- **The original strategy for SPACES was to pursue an integrated system for the second generation.**
- **Our approach is to seek an integrated solution now rather than continue to pursue the original SPACES items.**
- **Focus is on three items that provide full capability set of the original project:**
 - **Multipurpose Solar Device (MSD)**
 - **24 Volt Radio Power Adapter**
 - **Computer Power Adapter**



REVISED DEVELOPMENT PATH






MSD SYSTEM CONCEPT

- **Multipurpose Solar device (MSD)**
- **Multiple components packaged together as a kit.**
- **Components may be used or left behind as the mission dictates (within weight limit of 12 lbs).**
- **“Heart” of the system is a battery box/battery charger.**
- **Battery box/battery charger accepts multiple types of power input.**
- **Battery box/battery charger has an output connector that allows adapters to power various 12 Volt tactical radios.**
- **Expanded capability for 24 Volt radios is a planned upgrade.**




MULTIPURPOSE SOLAR DEVICE




Solar panel(s)

Probably need two 55 W or one 100 W (?) to meet power requirements

“Y” cable to connect if two panels are used



AN/PRC-119 A/B/C/D Adapter, probably rubber gasket and cord used with existing battery box




Contains one battery and charging electronics

Waterproof


12-32 VDC input with ECO-Mate connector (polarity protected)

Single radio compatible output (2x12V) connector TBD

Acts as BB charger



AN/PRC-119 (F) Adapter, probably replacement battery door with cord



AN/PRC-148 MBITR battery adapter

Other Input Adapters

24 VDC mini-NATO

110 VAC wall plug TO 24 VDC

10 foot ECO-Mate to ECO-Mate extension cord (for vehicle distribution system)



MSD VS SP4 AND SP4+

	SP4	SP4+	MSD
Solar Input	Yes	Yes	Yes
Other DC Input	No	Yes	Yes
AC Input	No	Yes	Yes
Charge BB-2590/U	Yes	Yes	Yes
Charge BB-390B/U	No	?	Yes
Charge other batteries	No	Yes	No
Radio Power Adapter	No	No	Yes



MSD TIMELINE

- • **Discussions with vendors** Feb 07-Apr 07
- **Request For Proposals** May 07-Jul 07
- **Select/Award up to two vendors** Oct 2007
- **Deliver 2 systems for Test** Dec 2007
- **First article Testing and LUE** Dec 07-Mar 08
- **Select final configuration/vendor** Mar 08
- **Conduct Production Verification Test and FUE** May 08-Aug 08
- **Production Articles available** late 08/early 09



SPACES v2.0

- **Multipurpose Solar device (MSD)**

In Progress

- **24 Volt Radio Power Adapter**

Planned Upgrade to MSD

- **Computer Power Adapter**

Pending




SPACES MSD

- **What are we doing differently this time?**
 - Released a request for information to industry and disseminated as widely as possible.
 - Modified performance specification based on responses.
 - Open to discussions on draft performance specification prior to release of request for proposals.
 - Changed contracting strategy to include a separate phase for first article production (in place of bid samples)



DREAM PROJECT

- **Deployable & Renewable Energy Alternative Module (DREAM)**
- **Combination:**
 - Diesel generators (backup)
 - Solar
 - Wind
 - Battery storage





DREAM PROJECT

- **MNF-West (Iraq) submitted Joint Rapid Resource Request**
- **Objective is for 3 alternative/renewable energy capabilities to lessen fuel transport demand**
 - **HMMWV Towable small system – 3-5 kilowatts output power**
 - **Medium Truck Towable – 10-15 kilowatts output power**
 - **Heavy Truck Transportable – 30 kilowatts output power**
- **We have selected the small (3-5 kW) system as the first effort.**



DREAM PROJECT

- **USMC effort with ONR Rapid Technology Transition (RTT) funding (FY07-08)**
 - **Loaded Weight \leq 4200 lbs**
 - **HMMWV towable**
 - **Up to 5 kW Output (3 kW continuous output)**
 - **Energy storage in batteries**
 - **May use:**
 - solar
 - wind
 - Back-up generator
 - **\geq 15 days without refuel**



Previous US Army demonstration



DREAM PROJECT

- **Contract is for R&D - 3 phases**
 - **Phase 1 – Trade-studies for system performance, sizing**
 - **Phase 2 (Option 1) - Build, test, and demonstrate prototype system**
 - **Phase 3 (Option 2) - Support to Government test events**
- **Schedule:**
 - **Award Apr 07 (three vendors)**
 - **Phase 1 Apr 07-Jul 07 (three vendors)**
 - **Phase 2 Jul 07-Feb 08 (up to two vendors)**
 - **Phase 3 Mar 08-Jul 08 (one vendor)**
 - **Final hardware configuration available late 08/early 09**



DREAM PROJECT





PROGRAM MANAGER EXPEDITIONARY POWER SYSTEMS MARINE CORPS SYSTEMS COMMAND

Questions ?



Major David C. Morris
david.c.morris@usmc.mil
(703) 432-3607

<http://www.marcorsyscom.usmc.mil/sites/pmeps/default.asp>

Self-Generated Field Power Sources

2007 Joint Service Power Expo

Albert Hartman

Mobile Electronics

- Power Requirements
- Available Field Sources
- EM Energy-Harvesting Technology

Electrical Power Req's

1. How Many Watts?
2. Usage Duty Cycle?
(intermittent/continuous?)




0 1 5 10 30 100
Watts

Chemical Batteries

- Enabled mobile electronics
- Industry - 6%/yr, cheap labor/lax laws
- Primaries - use once, dispose. \$60B
- Secondaries - \$6B

Primary Batteries Procurement

Difficult & Expensive



Primary Batteries Disposal

Spending Money & Taking Risks



for Trash!

Secondaries

- Economics driving popularity
 - cellphones, computers, ipods, shavers, toothbrush
 - electric car
- Nothing new, Li-ion 6%/yr
- MIL directive to use rechargeables
 - replace only 1/yr

Secondaries - Power

- Huge
- Log
- Red



atts
y chain
smaller



How Much Should You Pack?





Energy is Everywhere



- Can Find a Fresh AA every 5-10 mins

10 - 30W



30-50 W



40 - 200W

If You Can Walk Up These Stairs ...



So How Much Effort Does it Take?

You Can Charge a AA Battery

How About Us?

- Leverage Hard Disk Drive technology (electro-magnetics, digital switchers, uP)
- All electricity comes from E-M
- Human power is same as as diesel or hydro or nuke or wind, etc.

Early Effort

- Made a modern G-67



Stuff We Found Out

- Power Variability: users, time
- Destructive Power Levels, need buffer
- User Interface: ergonomics (50%), info, effort adjust
- Multiple device sinks




Stuff We Found Out (cont.)

- Unanticipated Uses: PV, UPS, volt conversion (AUX)




- Connectors: many MIL, use COTS, cig lighter, USB

Current System Overview



Jammer P125



Applications

- Emergency kits - crash kits, rubber rafts air/seacraft, w/first aid kits
- Dismounted soldier rucksacks
- Anything low power (single AA apps)
- Looking For Your Ideas Too

We`re Putting A Build Together

- 5 yr history: CECOM Powerbranch, SOCOM
- Add Your Name to the List
- Controls Charger Costs
- Last chance for input before hardtool lockdown

Recap:

- Mobile Electronics - great, modest power
- Plenty of power everywhere
- Portable EM chargers are effective
- Dead batteries? No problem.

Field Energy Harvesting with High Tide

You Are NEVER Without
Power

Contact Info:

Albert Hartman

650-245-5424

ahartman@hightidelabs.com



**PROGRAM MANAGER
EXPEDITIONARY POWER SYSTEMS
MARINE CORPS SYSTEMS COMMAND**

**Solar Power Adapters
and
Deployable and Renewable Alternative
Energy Module**

**Major David C. Morris
Deputy Program Manager / Project Officer
david.c.morris@usmc.mil**



AGENDA

- **SPACES Project**
 - **Past Solar Power Adapter Efforts (SPACES)**
 - **Current SPACES Projects**
 - **Multipurpose Solar Device**
 - **24 Volt Tactical Radio Power Adapter (RPA)**
 - **Computer Power Adapter**
- **DREAM Project**



SPACES

- **Solar power adapters are part of the Solar Portable Alternative Communications Energy Sources (SPACES) project.**
- **SPACES is a family of solar powered devices intended to increase employment flexibility and reduce external power requirements.**
- **Some standard interfaces will be required**





PAST SPACES EFFORTS

- **Began in late 2005, concluded in mid-2006**
- **SPACES (v1.0) Included the following items:**
 - **Lead-acid battery chargers**
 - **Generator**
 - **Vehicle**
 - **Communications-electronics battery charger**
 - **Computer power adapter and battery charger**
 - **Radio power adapter and battery chargers**
 - **12 Volt Tactical Radios**
 - **24 Volt Tactical Radios**
 - **Variable power supply**



SPACES v1.0 OUTCOME

ITEM	OUTCOME
Lead Acid (Gen)	GSA (Pulse-Tech)
Lead Acid (Veh)	GSA (Pulse-Tech)
Battery Charger	RFP/no successful proposals
Computer Adapter	RFP/no successful proposals
12 Volt RPA	RFP/no successful proposals
24 Volt RPA	RFP/no successful proposals
Var Power Supp	Not pursued



LEAD-ACID BATTERY CHARGERS

- **Lead-acid battery chargers**
 - SP-BC-LA-G (Generator)**
 - SP-BC-LA-V (Vehicle)**
- **Intended to maintain charge in generator and vehicle batteries**
- **Separate competitive selections were made for the generator and vehicle chargers**
- **Pulse-Tech 24 Volt chargers were selected for both items**
 - **Generator charger does not have push-to-test battery meter**
 - **Vehicle charger has push-to-test battery meter**



LEAD-ACID BATTERY CHARGERS

- **Current status:**
 - **Vendor selected**
 - **Available**
 - **Modification Instruction (MI) for generator version is complete and published for TQG series**
 - **MI for vehicles is pending**





SPACES v1.0 REVIEW

- **Success for only 2 of 6 items in the SPACES family.**
- **What went wrong?**
 - **Did not communicate with industry during our specification development (no request for information, industry day, etc.)**
 - **Did not develop industry contacts to disseminate our request for proposals widely**
 - **Attempted an off-the-shelf contracting strategy when industry would have to develop the item**
 - **Requested performance levels were ambitious**



SPACES v1.0 REVIEW

- **What else went wrong?**
 - **Small business set aside (based on market research) probably limited us to vendors who could least afford to absorb initial development/integration costs**
 - **We required bid samples – they were intended to reduce risk for the government, but providing them probably exacerbated all the other issues in play at the time.**




SPACES v2.2 STRATEGY

- **Most SPACES (v1.0) solicitations failed to attract successful proposals.**
- **The original strategy for SPACES was to pursue an integrated system for the second generation.**
- **Our approach is to seek an integrated solution now rather than continue to pursue the original SPACES items.**
- **Focus is on three items that provide full capability set of the original project:**
 - **Multipurpose Solar Device (MSD)**
 - **24 Volt Radio Power Adapter**
 - **Computer Power Adapter**



REVISED DEVELOPMENT PATH






MSD SYSTEM CONCEPT

- **Multipurpose Solar device (MSD)**
- **Multiple components packaged together as a kit.**
- **Components may be used or left behind as the mission dictates (within weight limit of 12 lbs).**
- **“Heart” of the system is a battery box/battery charger.**
- **Battery box/battery charger accepts multiple types of power input.**
- **Battery box/battery charger has an output connector that allows adapters to power various 12 Volt tactical radios.**
- **Expanded capability for 24 Volt radios is a planned upgrade.**




MULTIPURPOSE SOLAR DEVICE




Solar panel(s)

Probably need two 55 W or one 100 W (?) to meet power requirements

“Y” cable to connect if two panels are used



AN/PRC-119 A/B/C/D Adapter, probably rubber gasket and cord used with existing battery box




Contains one battery and charging electronics

Waterproof


12-32 VDC input with ECO-Mate connector (polarity protected)

Single radio compatible output (2x12V) connector TBD

Acts as BB charger



AN/PRC-119 (F) Adapter, probably replacement battery door with cord



AN/PRC-148 MBITR battery adapter

Other Input Adapters

24 VDC mini-NATO

110 VAC wall plug TO 24 VDC

10 foot ECO-Mate to ECO-Mate extension cord (for vehicle distribution system)



MSD vs SP4 & SP4+

	SP4	SP4+	MSD
Solar Input	Yes	Yes	Yes
Other DC Input	No	Yes	Yes
AC Input	No	Yes	Yes
Charge BB-2590/U	Yes	Yes	Yes
Charge BB-390B/U	No	?	Yes
Charge other batteries	No	Yes	No
Radio Power Adapter	No	No	Yes



MSD TIMELINE

- • **Discussions with vendors** Feb 07-Apr 07
- **Request For Proposals** May 07-Jul 07
- **Select/Award up to two vendors** Oct 2007
- **Deliver 2 systems for Test** Dec 2007
- **First article Testing and LUE** Dec 07-Mar 08
- **Select final configuration/vendor** Mar 08
- **Conduct Production Verification Test and FUE** May 08-Aug 08
- **Production Articles available** late 08/early 09



SPACES v2.0

- **Multipurpose Solar device (MSD)**

In Progress

- **24 Volt Radio Power Adapter**

Planned Upgrade to MSD

- **Computer Power Adapter**

Pending




SPACES MSD

- **What are we doing differently this time?**
 - Released a request for information to industry and disseminated as widely as possible.
 - Modified performance specification based on responses.
 - Open to discussions on draft performance specification prior to release of request for proposals.
 - Changed contracting strategy to include a separate phase for first article production (in place of bid samples)



DREAM PROJECT

- **Deployable & Renewable Energy Alternative Module (DREAM)**
- **Combination:**
 - Diesel generators (backup)
 - Solar
 - Wind
 - Battery storage





DREAM PROJECT

- **MNF-West (Iraq) submitted Joint Rapid Resource Request**
- **Objective is for 3 alternative/renewable energy capabilities to lessen fuel transport demand**
 - **HMMWV Towable small system – 3-5 kilowatts output power**
 - **Medium Truck Towable – 10-15 kilowatts output power**
 - **Heavy Truck Transportable – 30 kilowatts output power**
- **We have selected the small (3-5 kW) system as the first effort.**



DREAM PROJECT

- **USMC effort with ONR Rapid Technology Transition (RTT) funding (FY07-08)**
 - **Loaded Weight \leq 4200 lbs**
 - **HMMWV towable**
 - **Up to 5 kW Output (3 kW continuous output)**
 - **Energy storage in batteries**
 - **May use:**
 - solar
 - wind
 - Back-up generator
 - **\geq 15 days without refuel**



Previous US Army demonstration



DREAM PROJECT

- **Contract is for R&D - 3 phases**
 - **Phase 1 – Trade-studies for system performance, sizing**
 - **Phase 2 (Option 1) - Build, test, and demonstrate prototype system**
 - **Phase 3 (Option 2) - Support to Government test events**
- **Schedule:**
 - **Award Apr 07 (three vendors)**
 - **Phase 1 Apr 07-Jul 07 (three vendors)**
 - **Phase 2 Jul 07-Feb 08 (up to two vendors)**
 - **Phase 3 Mar 08-Jul 08 (one vendor)**
 - **Final hardware configuration available late 08/early 09**



DREAM PROJECT





PROGRAM MANAGER EXPEDITIONARY POWER SYSTEMS MARINE CORPS SYSTEMS COMMAND

Questions ?



Major David C. Morris
david.c.morris@usmc.mil
(703) 432-3607

<http://www.marcorsyscom.usmc.mil/sites/pmeps/default.asp>


Large-sized Li-ion Battery Module for Hybrid Powered Energy System

**Takefumi Inoue, Koichi Nishiyama*
and William A. Moll****

*** GS Yuasa Corporation
United Lithium Systems

Background of Development

- Increasing demand of large-scale lithium ion batteries for high power industrial applications such as hybrid powered energy systems



Development of new, large-scale lithium ion cell and battery modules which have **high power, long life and **superior cooling performance****

Agenda

- **Cell Specifications, Technologies and Performance**
- **Battery Module Specifications and Cooling Evaluation**
- **Evaluation of Energy Efficiency for Hybrid Powered Energy System (Railway Vehicle Systems)**

LIM30H Cell Specification



Mass / kg	2.0
Dimension / mm	47W, 170L, 133H
 / in	1.85" x 6.7" x 5.2"
Nominal voltage / V	3.6
Nominal capacity / Ah	30

Key Technologies of LIM30H

- **Positive active material:**

LiMn₂O₄ improved for safety and long life


- **Negative active material:**

Hard carbon for improved high rate charge/discharge performance and high energy efficiency

- **Structure:**

Robust current collecting construction for high amperage charge/discharge

Cycle Life Performance of Improved Manganese Active Material




○ Previous LiMn₂O₄
△ Modified LiMn₂O₄

Charge : 1.0 mA / cm² to 4.3 V
Discharge : 2.0 mA / cm² to 3.0 V
Temperature : 60 °C
Electrolyte : Standard
Working electrode : LiMn₂O₄
Counter electrode : Li metal
Reference electrode : Li metal

Reference Cell

Quick Charge Performance of the Cells with Various Negative Active Materials



1. Proto-type cell

2. Reference cell

Charge conditions


Negative active material: **Hard carbon**

Negative active material: **Graphite**

Discharge : 1CA to 2.75 V at 25°C

Charge : 10CA to 4.15 V at 25°C

Structure of LIM30H




Negative current collector

Positive current collector


Positive electrode

Negative electrode

Separator




Quick Charge Performance of LIM30H



Charge : (○)30 , (△)150, and (□)300 A to 4.15 V followed by constant voltage of its value for 3 hours at 25 °C


Discharge Performance of LIM30H



Charge : 30 A to 4.15 V followed by constant voltage of its value for 3 hours at 25°C

Discharge : Discharge with various current at 25°C


Discharge Capacities of LIM30H at Various Ambient Temperature



Charge : 30 A to 4.15 V followed by constant voltage for 3 hours at 25°C


Discharge : 30 A to 2.75 V at various ambient temperature

Life Performance of LIM30H under Large Current Charge Discharge Pulse Cycle



300A pattern cycle:

Charge- 300A 30sec.
Discharge- 300A 30sec.
Rest- 480sec.




Agenda

- **Cell Specifications, Technologies and Performance**
- **Battery Module Specifications and Cooling Evaluation**
- **Evaluation of Energy Efficiency for Hybrid Powered Energy System (Railway Vehicle Systems)**

LIM30H-8R Module Specifications

Items	Specifications
Cell	LIM30H (8 cells in series)
Nominal capacity	30 Ah
Nominal voltage	28.8 V (3.6 V / cell)
Operating voltage	20.0 – 33.6 V (2.5 – 4.2 V / cell)
Dimensions	W231 – D375 – H147 / mm
Mass	18.5 kg
Cooling	Designed for forced air cooling
Cell management	Cell Scanner(CS) installed

LIM30H-8R



Negative Terminal


Cell Scanner

Air Intake


Positive Terminal



Battery Monitoring System of LIM30H-8R



Cooling Air Flow of LIM30H-8R



Battery powered tram

(Railway Technical Research Institute, Japan)-




Cell **55Ah-class proto type**
(92W, 170L, 133H)

Battery system **168 cell-series**

LIM30-8

Environmental Test




Vibration test

➤ UN3090

➤ JIS E 4031 2B (JIS : Japanese Industrial Standard)

Temperature Rise of LIM30H-8R with Large Current (120A) Operation with Various Air Flow




Agenda


- **Cell Specifications, Technologies and Performance**
- **Battery Module Specifications and Cooling Evaluation**
- **Evaluation of Energy Efficiency for Hybrid Powered Energy System (Railway Vehicle Systems)**

Example of Hybrid Powered Energy System (Hybrid Railway Vehicle Power System)

Overhead wires




Fly-back line
(Rail)



Evaluation of Energy Efficiency for Hybrid Railway Vehicle Power System


**Test Battery: LIM30H-8R-22series
(30Ah-634V)**



Charge discharge conditions:

- 1. Discharge (Acceleration assist): 90kW for 60 sec.**
- 2. Rest (Constant speed running): 180 sec.**
- 3. Charge (Regeneration at Decelerating): 200kW for 30 sec.**
- 4. Rest (Stop at the station): 30 sec.**

Result of Energy Efficiency Test for Hybrid Railway Vehicle Power System



Energy efficiency

$$\frac{\int W_{out} dt}{\int W_{in} dt}$$

$$= 82\%$$

Conclusions

Newly developed Large-sized Li-ion Battery Module(LIM30H-8R) for Hybrid Powered Energy System has the following features:

- **High rate charge and discharge capability**
- **Longer life performance under large current charge discharge pulse cycles**
- **CS (cell scanner) is included in each battery module, Battery Monitor communicates to vehicle**
- **Thermal management for large current continuous operation**
- **Higher energy efficiency suitable for hybrid energy system**

Contact Information

- **United Lithium Systems/GS Yuasa**
- **William Moll (678) 739-2140**
- **bill.moll@unitedlithium.com**
- **www.unitedlithium.com**

- **SALES Contact:**
- **Jeff Cason (678) 739-2139**
- **jeff.cason@unitedlithium.com**

Power-Managed HMMWV Demonstrator

Joint Service Power Expo
April 25, 2007




Problem statement

- There is an urgent theater requirement for a self protection and IED defeat suite of subsystems on tactical wheeled vehicles (TWVs)
- HMMWV and EOD armored trucks (i.e. Buffalo, Cougar, RG31, etc.) do not have enough electrical power for this equipment
- The immediate power requirement is for 28VDC... 400 amps across the entire engine operating range
 - ONR/USMC OBVP program is developing AC export power
 - 115/230VAC is a future requirement for IED defeat
- DoD is seeking alternatives

Urgent Warfighter need

HMMWV integration considerations

HMMWV chassis packaging







No space claim available under the chassis


HMMWV engine with v-belts (old 6.2L)



HMMVV engine with serpentine belt (new 6.5L)



-  A) Static belt tension force vector
-  B) Pulley torque force vector (acts on crankshaft key)
-  C) Pulley torque reaction force (due to sum of all mechanical loads)
-  Engine main journal bearing side load (vector sum of A and C)




Bearing side load and crankshaft Woodruff key torque are serious HMMWV engine constraints

Potential solutions



Dual belt driven HV generator




Alternator + belt driven HV generator




Turbo alternator



Conventional 28VDC alternators



Flywheel ISG




Front crank mount ISG

Solution comparison

- Single and dual belt driven high voltage generators
 - + COTS solution, easy to install, low cost
 - Won't make full 400 amps 28VDC at idle, belt drive issues
- Turbo alternator
 - + Small, lightweight, easy to install
 - Will not make power at idle, high risk approach
- Conventional 28VDC alternators
 - + Easy to install, low cost, mature technology
 - Won't make full 400 amps 28VDC at idle, belt drive issues, inefficient
- Flywheel integrated starter generator (ISG)
 - + Ideal solution for new vehicle designs
 - Retrofit intrusive, requires transmission and torque converter removal / mod
- Front crank mount ISG
 - + Will make 400 amps 28VDC at idle, field retrofittable, efficient, robust
 - Retrofit more complex than belt drive approaches


Front crank mount integrated starter generator
(ISG) w/ electric accessories
Power-managed HMMWV

Power-managed HMMWV overview



- Provides 400 amps of 28VDC power (11.2kW) over the entire engine operating range
- Provides 1kW 115VAC power (expandable to 30kW 230VAC power)
- Generator installs directly on engine crankshaft for high reliability and high power capability
- Automotive accessories are electrified for high efficiency and superior health monitoring
- Cooling system is electrified for superior engine cooling performance, even at low speeds

System architecture



Engine dress



ISG mounted on HMMWV engine crankshaft

Electric motor powering existing power steer pump

Generator and electronics cooling pump

HMMWV cooler stack removed for clarity

Cooler stack and electric accessories installation



Engine fan controllers (4)

Electronics and generator Cooler

Main cooling fans (two of 4)

Engine radiators

Engine water pump and controller

All engine accessories are power-managed

Demonstrator status



- Vehicle build complete
- 400 Amp power delivery and electric accessory functions verified
- Final integration and road testing in process
- Will be available for targeted customer demonstrations in May 2007

Summary

- Satisfies urgent theater requirement for vehicle power
- Provides 400 amps of 28VDC over the entire engine operating range
- 30kW of clean 230VAC power may be added (as an option)
- May be installed in the field
- Space claim is compatible with HMMWV
- Will work on transmission PTO (for armored trucks)
- Improves HMMWV fuel consumption and system reliability
- Enhances HMMWV cooling system performance
- Flexible common modular power system (CMPS) architecture leverages FCS and ground combat vehicle developments