



**US Army Corps  
of Engineers®**  
Engineer Research and  
Development Center

**ERDC**  
INNOVATIVE SOLUTIONS  
for a safer, better world

*Engineering for Polar Operations, Logistics, and Research (EPOLAR)*

## **Autonomous Sea-Ice Thickness Survey**

James H. Lever

June 2016



**The U.S. Army Engineer Research and Development Center (ERDC)** solves the nation's toughest engineering and environmental challenges. ERDC develops innovative solutions in civil and military engineering, geospatial sciences, water resources, and environmental sciences for the Army, the Department of Defense, civilian agencies, and our nation's public good. Find out more at [www.erdclibrary.usace.army.mil](http://www.erdclibrary.usace.army.mil).

To search for other technical reports published by ERDC, visit the ERDC online library at <http://acwc.sdp.sirsi.net/client/default>.

# **Autonomous Sea-Ice Thickness Survey**

James H. Lever

*U.S. Army Engineer Research and Development Center (ERDC)  
Cold Regions Research and Engineering Laboratory (CRREL)  
72 Lyme Road  
Hanover, NH 03755-1290*

Final Report

Approved for public release; distribution is unlimited.

Prepared for National Science Foundation, Division of Polar Programs,  
Antarctic Infrastructure and Logistics  
4201 Wilson Boulevard  
Arlington, VA 22230

Under Engineering for Polar Operations, Logistics, and Research (EPOLAR)  
EP-ANT-14-17, "Autonomous Ice-Thickness Survey of Sea Ice Runway"

## Abstract

We conducted an autonomous survey of sea-ice thickness using the Polar rover *Yeti* to tow an electromagnetic induction meter over sea ice in McMurdo Sound, Antarctica. This proof-of-concept survey aimed to demonstrate improved efficiency relative to manual surveys routinely conducted to assess the safety of roads and runways constructed on the sea ice. *Yeti* executed the autonomous survey on 11 November 2014. This report describes the methods used, compares the measured ice-thickness profiles with manual borehole measurements, assesses the merits of autonomous surveys relative to manual ones, and describes potential future applications.

**DISCLAIMER:** The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products. All product names and trademarks cited are the property of their respective owners. The findings of this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

**DESTROY THIS REPORT WHEN NO LONGER NEEDED. DO NOT RETURN IT TO THE ORIGINATOR.**

# Contents

<b>Abstract .....</b>	<b>ii</b>
<b>Figures and Tables.....</b>	<b>iv</b>
<b>Preface .....</b>	<b>v</b>
<b>Acronyms and Abbreviations .....</b>	<b>vi</b>
<b>1 Introduction.....</b>	<b>1</b>
1.1 Background .....	1
1.2 Objectives.....	2
1.3 Approach .....	3
<b>2 Equipment and Methods .....</b>	<b>4</b>
<b>3 Results .....</b>	<b>8</b>
<b>4 Discussion and Recommendations.....</b>	<b>11</b>
<b>References .....</b>	<b>14</b>
<b>Report Documentation Page</b>	

# Figures and Tables

## Figures

1	The runway and roads on McMurdo Sound sea ice in November 2009. (Map data: Google, DigitalGlobe.) .....	1
2	<i>Yeti</i> towing an EM31 electromagnetic ice-thickness meter along the Pegasus Cut-Off Road near McMurdo Station, Antarctic, on 11 November 2014.....	3
3	<i>Yeti</i> with a GPR sled in the McMurdo Shear Zone. The black case housed the radar controller, batteries, and GPS receiver and supported the GPS antenna ( <i>white disk</i> ). The orange 200 MHz antenna and smaller 400 MHz antenna (not visible) mounted in front of the black case. The black polyethylene sled included two steel rudders to reduce yaw motions. The sled and GPR equipment weighed 74 kg. <i>Yeti</i> 's radio antenna carried a red flag; its GPS antenna mounted on the opposite side in front of the battery box.....	4
4	The EM31 in the sled towed by <i>Yeti</i> along Pegasus Cut-Off Road on McMurdo Sound sea ice. The blue box housed the battery-powered EM31 electronics. The instrument's horizontal, white-plastic poles separated the transmitter and receiver coils by 3.66 m. The sled also carried a small datalogger and a GPS receiver (not visible). The survey crew conducted three manual borehole ice-thickness measurements to compare with data from the EM31.....	5
5	The <i>Yeti</i> -EM31 survey track plot. GPS track points ( <i>circles</i> ) were logged at 10 s intervals. The course was north-south along the Pegasus Cut-Off Road near the sea-ice transition at McMurdo Station. The background image was acquired 29 October 2014. (Map data: Google, DigitalGlobe.).....	8
6	A continuous record of measured ice thickness from the EM31 compared with borehole measurements. The distance from the origin is based on GPS coordinates.....	10

## Tables

1	Parameter values for Equation (1) from available sources .....	6
2	Borehole measurements of snow depth and ice thickness and corresponding EM31 ice-thickness measurements.....	9

## Preface

This study was conducted for the National Science Foundation, Division of Polar Programs (NSF-PLR), under Engineering for Polar Operations, Logistics, and Research (EPOLAR) EP-ANT-14-17, “Autonomous Ice-Thickness Survey of Sea Ice Runway.” The technical monitor was Margaret Knuth, Operations Manager, NSF-PLR, Antarctic Infrastructure and Logistics.

The work was performed by Dr. James H. Lever (Force Projection and Sustainment Branch, Dr. Sarah Kopczynski, Chief), U.S. Army Engineer Research and Development Center, Cold Regions Research and Engineering Laboratory (ERDC-CRREL). At the time of publication, Janet Hardy was the program manager for EPOLAR. Dr. Loren Wehmeyer was Chief of the Research and Engineering Division of ERDC-CRREL. The Deputy Director of ERDC-CRREL was Dr. Lance Hansen, and the Director was Dr. Robert Davis.

The author thanks Jeff Scanniello and Dugan Greenwell for their help conducting the survey and making the borehole measurements. The author also thanks Margaret Knuth for her support and coordination of the fieldwork; Professor Laura Ray for the use of *Yeti*; Kerry Claffey, Bruce Elder, and Dr. Jackie Richter-Menge for EM31 use and training; and Dr. Elias Deeb for mapping assistance.

COL Bryan S. Greene was the Commander of ERDC, and Dr. Jeffery P. Holland was the Director.

## Acronyms and Abbreviations

AFCESA	Air Force Civil Engineer Support Agency
CRREL	U.S. Army Cold Regions Research and Engineering Laboratory
EPOLAR	Engineering for Polar Operations, Logistics, and Research
ERDC	Engineer Research and Development Center
GIS	Geographic Information System
GPR	Ground-Penetrating Radar
GPS	Global Positioning System
NSF	National Science Foundation
PLR	Division of Polar Programs
USAP	U.S. Antarctic Program



# 1 Introduction

## 1.1 Background

McMurdo Station is the largest facility operated under the U.S. Antarctic Program (USAP) and is the logistics and transportation hub for USAP's South Pole Station and deep-field science camps. The station itself is located on the southern tip of Ross Island, bordered by the McMurdo Sound to the west and the Ross Sea to the east (Figure 1). Sea ice grows on McMurdo Sound through the winter and reaches thicknesses in excess of 2 m by station opening in early October. This sea ice typically can support heavy vehicles and cargo aircraft through late November or early December. Easy access and proximity to the station has made the sea ice attractive as a location for an aircraft runway, runway access roads, and roads to research and logistics sites around McMurdo Sound.

Figure 1. The runway and roads on McMurdo Sound sea ice in November 2009. (Map data: Google, DigitalGlobe.)



The bearing capacity of sea ice depends on the thickness, structure, and temperature of the ice. The U.S. Air Force operates the cargo aircraft re-supplying McMurdo Station, and its Air Force Civil Engineer Support Agency (AFCESA) has established methods to determine safe landing and parking loads for the sea-ice runway (AFCESA 2007). The guidance notes that ice thickness is the most critical parameter, and it requires a minimum of 16 borehole ice-thickness measurements distributed along the runway with repeat measurements at time intervals ranging from weekly to daily during flight periods. For known ice thickness, the guidance provides allowable aircraft loads and parking times, binned according to measured surface-ice temperatures.

Using similar ice-temperature bins, Weale and Sodhi (2015) calculated the required ice thickness to support heavy tracked vehicles traversing McMurdo Sound to resupply a fuel cache and camp at Marble Point. They did not specify the spatial or temporal distributions of ice-thickness measurements, but the route is about 80 km long. Conducting manual borehole measurements with separation distances even as long as one kilometer would be a substantial undertaking for each resupply traverse.

USAP personnel currently measure ice thickness manually. Each measurement requires clearing the surface snow, drilling a borehole by using a powered ice auger, measuring ice thickness with a toggled line, and recording the result in a logbook. The location of the borehole is also recorded using a handheld global positioning system (GPS) receiver. The thickness measurements must then be analyzed and combined with the GPS data to determine the thickness distribution and the locations of any areas of concern. Each thickness measurement takes about 15 min to execute in addition to post-processing time and travel time between locations.

## 1.2 Objectives

Researchers at U.S. Army Cold Regions Research and Engineering Laboratory (CRREL) and Dartmouth College have collaborated to develop the Polar rover *Yeti* to conduct autonomous ground-penetrating radar surveys to detect and map subsurface crevasses and other safety hazards. We sought to use the rover to conduct proof-of-concept autonomous surveys of sea-ice thickness in McMurdo Sound to demonstrate improved efficiency relative to manual surveys.

### 1.3 Approach

We conducted an autonomous survey of sea-ice thickness using *Yeti* to tow an electromagnetic induction meter over sea ice in McMurdo Sound, Antarctica. This proof-of-concept survey aimed to demonstrate improved efficiency relative to manual surveys routinely conducted to assess the safety of roads and runways constructed on the sea ice. *Yeti* executed the autonomous survey on 11 November 2014 (Figure 2). This report describes the methods used, compares the measured ice-thickness profiles with manual borehole measurements, assesses the merits of autonomous surveys relative to manual ones, and describes potential future applications.

Figure 2. *Yeti* towing an EM31 electromagnetic ice-thickness meter along the Pegasus Cut-Off Road near McMurdo Station, Antarctic, on 11 November 2014.



## 2 Equipment and Methods

*Yeti* is a 4-wheel-drive, battery-powered rover co-developed by Dartmouth College and CRREL. *Yeti* has successfully conducted over-snow, ground-penetrating-radar (GPR) surveys in Greenland and Antarctica to detect and map buried hazards (Lever et al. 2013; Lever et al. 2016).

We shipped *Yeti* to Antarctica in 2014 under National Science Foundation, Division of Polar Programs (NSF-PLR), science grants 1246400 and 1245915 to conduct systematic GPR surveys across a crevasse-ridden section of the shear zone between the Ross and McMurdo Ice Shelves and thereby gain insight into its state of fracture and long-term stability. In November 2014, *Yeti* conducted over 600 km of autonomous GPR surveys across this 5.7 km wide shear zone, operating continuously for seven days with stops only to change batteries and to store data (Figure 3). It experienced no immobilizations, and other than two operator-induced errors, it completed each over-and-back survey run on schedule. The autonomous sea-ice survey leveraged this field deployment.

Figure 3. *Yeti* with a GPR sled in the McMurdo Shear Zone. The black case housed the radar controller, batteries, and GPS receiver and supported the GPS antenna (*white disk*). The orange 200 MHz antenna and smaller 400 MHz antenna (not visible) mounted in front of the black case. The black polyethylene sled included two steel rudders to reduce yaw motions. The sled and GPR equipment weighed 74 kg. *Yeti's* radio antenna carried a red flag; its GPS antenna mounted on the opposite side in front of the battery box.




We conducted the sea-ice thickness survey after *Yeti's* deployment in the Shear Zone. We swapped the GPR equipment for a Geonics EM31 electromagnetic induction meter to measure ice-thickness and towed it in the



same sled (Figure 4). The rover weighed 77 kg, and the sled with the EM31 weighed 13 kg. The average survey speed was 5.3 km/h (1.5 m/s). Based on the Shear Zone surveys, average rover power consumption was 340 W, which allowed the rover's 1200 Wh battery pack to provide 3.5 h of operation or 18 km of survey length between battery changes. The GPS receiver on *Yeti* typically saw 18–22 satellites, with position accuracy (horizontal dilution of precision) of 0.6–0.7 m. The resulting survey lines normally deviated only 1–2 m from a straight line between the two end waypoints.

Figure 4. The EM31 in the sled towed by *Yeti* along Pegasus Cut-Off Road on McMurdo Sound sea ice. The blue box housed the battery-powered EM31 electronics. The instrument's horizontal, white-plastic poles separated the transmitter and receiver coils by 3.66 m. The sled also carried a small datalogger and a GPS receiver (not visible). The survey crew conducted three manual borehole ice-thickness measurements to compare with data from the EM31.



The EM31 measures apparent conductivity (mS/m) of the terrain beneath the instrument (Geonics 2010). A transmitter coil at one end of the instrument induces circular eddy current loops in the terrain, and the receiver coil at the other end senses the resulting magnetic fields. The transmitter operates at 9.8 kHz, and the transmitter and receiver coils are separated by 3.66 m. The instrument does not require electrical contact with the terrain, and it is calibrated to read the correct conductivity when the terrain is uniform.

For layered terrain, the apparent conductivity is a distance-weighted average over the several-meter footprint of the instrument. The problem simplifies for the horizontally layered air-snow-ice-seawater terrain of interest

here. Because the conductivity of seawater (2400–2500 mS/m) is much higher than that of air, snow, or sea-ice (0–80 mS/m), apparent conductivity largely depends on the distance between the instrument and the seawater. Secondary effects include the extent of brine inclusion in the sea ice and the presence of under-ice, low-salinity meltwater.

Numerous studies have used the EM31 for sea-ice thickness surveys (e.g., Kovaks and Morey 1991; Haas et al. 1997, 2011; Eicken et al. 2001; Haas and Eicken 2001; Mahoney et al. 2007). Because apparent conductivity falls off exponentially with distance to the seawater, most studies have used a logarithmic relationship to convert instrument readings of apparent conductivity,  $\sigma_a$ , into distance to the seawater,  $D_{sw}$ :

$$D_{sw} = A - B \ln(\sigma_a - C) \quad (1)$$

where the coefficients  $A$ ,  $B$ , and  $C$  are determined by best-fitting EM31 readings with measured ice thickness for the conditions of interest. The asymptote  $\sigma_a = C$  is interpreted as the conductivity of an infinitely thick slab of sea ice. Ice thickness,  $H_{ice}$ , is then obtained by subtracting the height of the instrument above the ice (air plus snow heights) from  $D_{sw}$ . Table 1 provides for Equation (1) a list of parameters from several sources.

Table 1. Parameter values for Equation (1) from available sources.

Source	Ice Conditions	A (m)	B (m)	C (mS/m)
Haas et al. (1997)	Central Arctic Ocean	7.0–7.9	1.0–1.1	57–96
Eicken et al. (2001)	Northern Chukchi Sea	8.2	1.2	57
Haas and Eicken, (2001)	Central Arctic Ocean	7.9–8.4	1.1–1.2	57–80
Haas et al. (2011)	Central Arctic Ocean	8.2	1.2	45
Mahoney et al. (2007)	Landfast sea ice near Barrow, AK	4.4–9.0	0.6–1.4	67–170
Dilliplaine et al. (2013)	Landfast sea ice near Barrow, AK	8.6	1.3	22

Eicken et al. (2001) summarized sources of uncertainty in EM31-based ice-thickness measurements and estimated that, compared with borehole measurements, their errors averaged 0.05 m for 2 m of level sea ice. They attributed most of the uncertainty to differences in the sampled footprints, namely less than 0.2 m for boreholes versus more than 2 m for the EM31. Haas and Eicken (2001) found average errors of 6% or 0.12 m for 2 m of ice, although their measurements included deformed and ridged ice that probably increased average errors.

For our study, the EM31 was equipped with an Archer handheld computer for system setup and data logging. We set it to sample at 5 Hz and synchronized its clock (within 1 s) with a Garmin 60CSx GPS receiver to geo-reference the survey. That GPS unit saw 10–12 satellites, resulting in horizontal position accuracy of 2–3 m.

### 3 Results

On 11 November 2014, we conducted the autonomous ice-thickness survey adjacent to the Pegasus Short-Cut Road near the transition from McMurdo Station (Figure 5). The survey course consisted of a 0.82 km outbound (southward) leg and a 0.56 km inbound (northward) leg on either side of the road for a total course length of 1.4 km. The run itself included three stops for manual borehole measurements of snow depth and ice thickness.

Figure 5. The *Yeti*-EM31 survey track plot. GPS track points (*circles*) were logged at 10 s intervals. The course was north–south along the Pegasus Cut-Off Road near the sea-ice transition at McMurdo Station. The background image was acquired 29 October 2014. (Map data: Google, DigitalGlobe.)




Table 2 summarizes the manual borehole measurements. Time constraints of the survey crew limited the number of boreholes, but the measurements showed relatively uniform snow depth and ice thickness.



Table 2. Borehole measurements of show depth and ice thickness and corresponding EM31 ice-thickness measurements.

Time	Ice Thickness (m)	Snow Depth (m)	EM31 Ice Thickness (m)	Error (m)	Error (%)
15:09:00	2.01	0.56	2.06	-0.05	2.6
15:20:00	2.08	0.46	2.04	0.04	-2.1
15:40:00	2.13	0.56	2.37	-0.24	11.1

Table 2 also compares the borehole-measured ice thicknesses with the corresponding values calculated from *Yeti's* EM31 readings nearby. We tried several published conversion equations and found reasonable agreement with the borehole measurements by using the following equation to convert the apparent conductivity to the depth to the saltwater interface:


$$D_{sw} = 8.64 - 1.26 \ln(\sigma_a - 21.9) \quad (2)$$

This specific conversion was based on an unpublished report archived at the University of Alaska (Dilliplaine et al. 2013). That report described a systematic method to calibrate the EM31 by placing it over level, land-fast sea ice and raising the instrument in increments to increase  $D_{sw}$ . This approach avoids the need to find level ice of different thicknesses to conduct a calibration. It also avoids mixing non-uniform ice conditions into the calibration, a concern expressed by several of the published sources listed in Table 1.

To obtain ice thickness, we subtracted the average height of the EM31 coils (0.30 m) and the average snow depth (0.52 m) from the calculated  $D_{sw}$  values. The resulting errors averaged 3.9% of the readings (Table 2), a reasonably low value.

Figure 6 shows the continuous record of ice thickness obtained from the survey compared with the borehole measurements. For convenience, we converted GPS-based geographic coordinates to distance from the survey origin.

Figure 6. A continuous record of measured ice thickness from the EM31 compared with borehole measurements. The distance from the origin is based on GPS coordinates.



As seen in Figure 6, variations in the EM31-based thickness measurements were small during stationary periods of the borehole measurements and increased during the autonomous survey sections. The lower-frequency variation probably reflects real variations in ice thickness of about  $\pm 0.1$  m while the higher-frequency variations probably resulted from movement of the arms of the instrument over rough snow.

As measured by the EM31, ice thickness varied 2.0–2.4 m with a clear trend of increasing thickness towards the south (outbound) end of the course. Note that the third borehole measurement captured only 0.1 m of the 0.3 m increase in ice thickness seen in the EM31 readings. The general agreement in shape of the outbound and inbound EM31 profiles provides some confidence that the measured increase in ice thickness over the 500–800 m section of the route was a real effect. As noted, the EM31 samples a larger footprint of ice compared with borehole measurements. It is likely that the third borehole sampled a locally thin area of ice, suggesting that the underside of the ice cover was rougher than the relatively smooth top surface. In general, widely spaced borehole measurements can insufficiently sample areas of varying ice thickness, which could be important for assessing sea-ice safety for aircraft and vehicles.

## 4 Discussion and Recommendations

We met our objective to demonstrate that autonomous sea-ice thickness surveys offer improved efficiency relative to manual surveys. The rover *Yeti* was able to conduct 1.4 km of measurements at 5 Hz, or one measurement every 0.3 m, with average error under 4% based on limited borehole measurements. If conducted without stops, the autonomous survey would have taken only 16 min, or about the same time as one borehole measurement. Scaled up, four survey lines along a 3000 m sea-ice runway at 20 m line spacing (12 km total survey length) would take 2.3 h, or about the same time as nine borehole measurements. Autonomous surveys thus offer the potential for significantly higher spatial resolution and coverage than is practical for manual surveys.

Reliable equipment now exists to conduct routine autonomous ice-thickness surveys to support Antarctic operations. The EM31 is a commercial product with a long record of deployments to measure sea-ice thickness. It is reliable and easy to use by technical personnel (e.g., surveyor or science technician). *Yeti*, although custom-made, has displayed excellent reliability and mobility over polar snowfields. It is also easy for technical personnel to operate and maintain. With two sets of batteries, *Yeti* could conduct 38 km of autonomous surveys on sea ice in 7 h. All of the data are geo-referenced, so areas of concern (i.e., locally thin ice) can be relocated and assessed in greater detail if needed. The data can readily be mapped using a standard geographic information system (GIS), such as ArcMap or Google Earth, which can then display the data relative to geographic and man-made features of interest.

Initially, mobilization, demobilization, and data-processing times would likely be longer for autonomous surveys than for manual ones until USAP personnel become more experienced with autonomous surveys. In the present case, the author operated *Yeti* and the EM31. We parked *Yeti* overnight at the McMurdo sea-ice transition after our shear-zone field-work. It took less than an hour to install batteries, attach the sled, mount and initialize the EM31, send the survey coordinates, and begin the survey. Post-processing of the data to create ice-thickness profiles took about 4 h but would be faster with frequent, routine surveys. Manual borehole measurements would still be needed periodically to check the calibration of the EM31, but personnel deploying the rover could make these measurements while the rover executes the survey. The calibration process

could subsequently be streamlined if the results produce similar calibration curves each year.

For routine surveys, data processing can be semi-automated by using dedicated scripts, and the standard data files (course coordinates, EM31 ice thickness measurements, and GPS tracks) can be formatted to link easily with a GIS for visualization. We have done this for *Yeti* GPR surveys and could help transfer this capability to USAP survey personnel.

USAP has ongoing needs to conduct sea-ice surveys to support airfields, roads, and staging areas near McMurdo. Additionally, a rover such as *Yeti* can tow other instrument payloads in lightweight, efficient sleds. Example payloads include GPR to map crevasse fields, assess snow roads, and survey land-ice transition areas and radiometers to measure albedo of compacted-snow or white-ice runways. Rover preparation, course planning, and data mapping are all very similar for these payloads, so operator skill and efficiency should improve rapidly. Importantly, systematic autonomous surveys are possible across terrain conditions where the safety of personnel could prevent or limit manual surveys, such as heavily crevassed glaciers and ice sheets. Recognizing these ongoing needs, USAP has funded CRREL to build a second-generation over-snow rover based on *Yeti's* design. This rover (named *SPoTbot*) is nearly complete and should be available for the 2016–17 USAP season.

Therefore, we make the following recommendations to USAP based on this proof-of-concept autonomous survey:

- Assess the needs within USAP for systematic sea-ice surveys, and compare the costs of manual and autonomous methods to address those needs.
- Acquire an EM31 for USAP if sea-ice survey needs justify it. Note that the instrument could also be offered to science projects if their schedules are compatible with those of USAP operations.
- Deploy the Polar rover *SPoTbot* to conduct a variety of surveys, including sea-ice thickness surveys, to gain experience with planning and executing autonomous surveys to support operational needs. *SPoTbot* could also be offered to science projects if their schedules are compatible with those of USAP operations.

- Assess the efficiency gains and cost savings derived from autonomous surveys relative to manual ones to document efficiency improvements resulting from this technology.

By following these recommendations, USAP can implement routine autonomous surveys to support its operations and research activities, leading to substantial cost savings, safer operating environments, and enhanced data collection. These improvements will be important as USAP seeks to reduce costs to support an ever-broadening science program.

## References

- AFCEA (Air Force Civil Engineer Support Agency). 2007. *Design, Construction, Maintenance, and Evaluation of the McMurdo Sound (Antarctica) Sea Ice Runway for Heavy Wheeled Aircraft Operations*. Engineering Technical Letter (ETL) 07-12. Tyndall Air Force Base, FL: Department of the Air Force, Headquarters Air Force Civil Engineer Support Agency.
- Dilliplaine, K., B. Hassett, N. Kanna, M. Oggier, A. Szymanski, and M. Wester. 2013. Module 2: Sea Ice Morphology. Course G695, Module 2, 30 June 2013. Unpublished report archived at University of Alaska, Fairbanks.
- Eicken, H., W. B. I. Tucker, and D. K. Perovich. 2001. Indirect Measurements of the Mass Balance of Summer Arctic Sea Ice with an Electromagnetic Induction Technique. *Annals of Glaciology* 33:194–200. doi:10.3189/172756401781818356.
- Geonics. 2010. *EM31-MK2 (with Archer) Operating Manual*. Ontario, Canada: Geonics Limited.
- Haas, C., and H. Eicken. 2001. Interannual Variability of Summer Sea Ice Thickness in the Siberian and Central Arctic Under Different Atmospheric Circulation Regimes. *Journal of Geophysical Research* 106 (C3): 4449–4462. doi:10.1029/1999JC000088.
- Haas, C., S. Gerland, H. Eicken, and H. Miller. 1997. Comparison of Sea-Ice Thickness Measurements Under Summer and Winter Conditions in the Arctic Using a Small Electromagnetic Induction Device. *Geophysics* 62:749–757.
- Haas, C., H. Le Goff, S. Audrain, D. Perovich, and J. Haapala. 2011. Comparison of Seasonal Sea-Ice Thickness Change in the Transpolar Drift Observed by Local Ice Mass-Balance Observations and Floe-Scale EM Surveys. *Annals of Glaciology* 52 (75): 97–102. doi:10.3189/172756411795931778.
- Kovaks, A., and R. M. Morey. 1991. *Evaluation of a Portable Electromagnetic Induction Instrument for Measuring Sea Ice Thickness*. CRREL Report 91-12. Hanover, NH: U.S. Army Cold Regions Research and Engineering Laboratory.
- Lever, J. H., A. J. Delaney, L. E Ray, E. Trautmann, L. A. Barna, and A. M Burzynski. 2013. Autonomous GPR Surveys Using Polar Rover *Yeti*. *Journal of Field Robotics* 30 (2): 194–215.
- Lever, J. H., Z. Courville, and D. Punt. 2016. Robotic Ground-Penetrating-Radar (GPR) Surveys to Support the 2014 Greenland Inland Traverse. ERDC-CRREL TR-16-8. Hanover, NH: U.S. Army Engineer Research and Development Center.
- Mahoney, A., H. Eicken, and L. Shapiro. 2007. How Fast Is Landfast Sea Ice? A Study of the Attachment and Detachment of Nearshore Ice at Barrow, Alaska. *Cold Regions Science and Technology* 47:233–255.

Weale, J. C., and D. S. Sodhi. 2015. Bearing Capacity of Floating Ice Sheets under Short-Term Loads: Over-Sea-Ice Traverse from McMurdo Station to Marble Point. ERDC/CRREL TR-15-1. Hanover, NH: U.S. Army Engineer Research and Development Center.

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

<b>1. REPORT DATE (DD-MM-YYYY)</b> June 2016		<b>2. REPORT TYPE</b> Special Report/Final		<b>3. DATES COVERED (From - To)</b>	
<b>4. TITLE AND SUBTITLE</b>  Autonomous Sea-Ice Thickness Survey				<b>5a. CONTRACT NUMBER</b>	
				<b>5b. GRANT NUMBER</b>	
				<b>5c. PROGRAM ELEMENT NUMBER</b>	
<b>6. AUTHOR(S)</b>  James H. Lever				<b>5d. PROJECT NUMBER</b>	
				<b>5e. TASK NUMBER</b> EP-ANT-14-17	
				<b>5f. WORK UNIT NUMBER</b>	
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b>  U.S. Army Engineer Research and Development Center (ERDC) Cold Regions Research and Engineering Laboratory (CRREL) 72 Lyme Road Hanover, NH 03755-1290				<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ERDC/CRREL SR-16-4	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> National Science Foundation, Division of Polar Programs Antarctic Infrastructure and Logistics 4201 Wilson Boulevard Arlington, VA 22230				<b>10. SPONSOR/MONITOR'S ACRONYM(S)</b> NSF	
				<b>11. SPONSOR/MONITOR'S REPORT NUMBER(S)</b>	
<b>12. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution is unlimited.					
<b>13. SUPPLEMENTARY NOTES</b>  Engineering for Polar Operations, Logistics, and Research (EPOLAR)					
<b>14. ABSTRACT</b> We conducted an autonomous survey of sea-ice thickness using the Po-lar rover <i>Yeti</i> to tow an electromagnetic induction meter over sea ice in McMurdo Sound, Antarctica. This proof-of-concept survey aimed to demonstrate improved efficiency relative to manual surveys routinely conducted to assess the safety of roads and runways constructed on the sea ice. <i>Yeti</i> executed the autonomous survey on 11 November 2014. This report describes the methods used, compares the measured ice-thickness profiles with manual borehole measurements, assesses the merits of autonomous surveys relative to manual ones, and describes potential future applications.					
<b>15. SUBJECT TERMS</b> Antarctica, Electromagnetic induction, EM31 electromagnetic meter, EPOLAR, McMurdo Station (Antarctica), NSF, Sea-ice runway, Yeti rover					
<b>16. SECURITY CLASSIFICATION OF:</b>			<b>17. LIMITATION OF ABSTRACT</b>  SAR	<b>18. NUMBER OF PAGES</b>  24	<b>19a. NAME OF RESPONSIBLE PERSON</b>
<b>a. REPORT</b>  Unclassified	<b>b. ABSTRACT</b>  Unclassified	<b>c. THIS PAGE</b>  Unclassified			<b>19b. TELEPHONE NUMBER</b> (include area code)