

REPORT DOCUMENTATION PAGE			Form Approved OMB NO. 0704-0188		
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA, 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 24-08-2015		2. REPORT TYPE Conference Proceeding		3. DATES COVERED (From - To) -	
4. TITLE AND SUBTITLE High-Power All-solid Photonic Bandgap Fiber Lasers			5a. CONTRACT NUMBER W911NF-10-1-0423		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHORS Fanting Kong, Guancheng Gu, Thomas Hawkins, Joshua Parsons, Maxwell Jones, Christopher Dunn, Monica T. Kalichevsky-Dong, Kunimasa Saitoh, Benjamin Pulford, Liang Dong, Iyad Dajani			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAMES AND ADDRESSES Clemson University Research Foundation Office of Sponsored Programs Clemson University Research Foundation Clemson, SC 29631 -0946			8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS (ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSOR/MONITOR'S ACRONYM(S) ARO		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S) 58391-EL-HEL.43		
12. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.					
14. ABSTRACT Fiber lasers have demonstrated great potentials for providing high average powers with diffraction-limited beam. Further power scaling of fiber lasers requires significant mitigation of nonlinear effects. Beam combining can then be used to further increase power. Mode area scaling of optical fibers using innovative fiber designs is key to increase nonlinear thresholds. Recently, we have also learned that strong higher-order-mode (HOM) control is critical for mitigation of mode instability, another key to achieve single-mode output at high average powers. In the next few years, we have been studying all-solid photonic bandgap fibers as means for power scaling. This					
15. SUBJECT TERMS fiber laser, photonic bandgap fibers					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	15. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Liang Dong
a. REPORT UU	b. ABSTRACT UU	c. THIS PAGE UU			19b. TELEPHONE NUMBER 864-656-5915

Report Title

High-Power All-solid Photonic Bandgap Fiber Lasers

ABSTRACT

Fiber lasers have demonstrated great potentials for providing high average powers with diffraction-limited beam. Further power scaling of fiber lasers requires significant mitigation of nonlinear effects. Beam combining can then be used to further increase power. Mode area scaling of optical fibers using innovative fiber designs is key to increase nonlinear thresholds. Recently, we have also learned that strong higher-order-mode (HOM) control is critical for mitigation of mode instability, another key to achieve single-mode output at high average powers.

In the past few years, we have been studying all-solid photonic bandgap fibers as means for power scaling. This approach provides an all-solid design, which significantly eases fabrication of robust and compact monolithic fiber laser systems for DoD applications. In addition, this design also provides significant HOM suppression at large-mode areas due to a combination of open and dispersive cladding. Recently, we have demonstrated mode area approaching of $2000\mu\text{m}^2$ with the best HOM suppression at this mode area among all known designs, to our knowledge.

We have also fabricated ytterbium-doped all-solid photonic bandgap fibers and are in the progress demonstrating and exploring many new capabilities provided by this design. In addition to the potential for large mode areas, all-solid photonic bandgap fibers only transmit lights over a narrow spectrum, i.e. photonic bandgap of the cladding. This can be used to suppress stimulated Raman scattering as well as undesired ASE. We will summarize and update our progress in this area.

Conference Name: 17th Annual Directed Energy Symposium, Anaheim

Conference Date: March 02, 2015

High-power all-solid photonic bandgap fiber lasers

Liang Dong¹, Fanting Kong¹, Guancheng Gu¹, Thomas Hawkins¹, Joshua Parsons¹, Maxwell Jones¹, Christopher Dunn¹, Monica T. Kalichevsky-Dong¹, Kunimasa Saitoh², Benjamin Pulford³, and Iyad Dajani³

¹ECE/COMSET, Clemson University, 91 Technology Drive, Anderson, SC, 29625, USA

²Graduate School of Information Science and Technology, Hokkaido University, Sapporo 060-0814, Japan

³Air Force Research Laboratory, 3550 Aberdeen Ave SE, Kirtland AFB, NM, USA 87117

Abstract:

Fiber lasers have demonstrated great potentials for providing high average powers with diffraction-limited beam. Further power scaling of fiber lasers requires significant mitigation of nonlinear effects. Beam combining can then be used to further increase power. Mode area scaling of optical fibers using innovative fiber designs is key to increase nonlinear thresholds. Recently, we have also learned that strong higher-order-mode (HOM) control is critical for mitigation of mode instability, another key to achieve single-mode output at high average powers.

In the past few years, we have been studying all-solid photonic bandgap fibers as means for power scaling. This approach provides an all-solid design, which significantly eases fabrication of robust and compact monolithic fiber laser systems for DoD applications. In addition, this design also provides significant HOM suppression at large-mode areas due to a combination of open and dispersive cladding. Recently, we have demonstrated mode area approaching of $2000\mu\text{m}^2$ with the best HOM suppression at this mode area among all known designs, to our knowledge.

We have also fabricated ytterbium-doped all-solid photonic bandgap fibers and are in the progress demonstrating and exploring many new capabilities provided by this design. In addition to the potential for large mode areas, all-solid photonic bandgap fibers only transmit lights over a narrow spectrum, i.e. photonic bandgap of the cladding. This can be used to suppress stimulated Raman scattering as well as undesired ASE. We will summarize and update our progress in this area.

Keywords:

Fiber lasers, photonic bandgap fibers, specialty optical fibers

Acknowledgments

This material is based upon work supported in part by the U. S. Army Research Laboratory and the U. S. Army Research Office under contract/grant number W911NF-10-1-0423 through a Joint Technology Office MRI program.