

Operational Influence on Thermal Behavior of High-Speed Helical Gear Trains

Robert F. Handschuh U.S. Army Research Laboratory Glenn Research Center, Cleveland, Ohio

Charles J. Kilmain Bell Helicopter Textron, Inc., Fort Worth, Texas

NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI Program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Reports Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION. Englishlanguage translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services also include creating custom thesauri, building customized databases, organizing and publishing research results.

For more information about the NASA STI program, see the following:

- Access the NASA STI program home page at http://www.sti.nasa.gov
- E-mail your question via the Internet to *help@sti.nasa.gov*
- Fax your question to the NASA STI Help Desk at 301–621–0134
- Telephone the NASA STI Help Desk at 301–621–0390
- Write to:
 NASA STI Help Desk
 NASA Center for AeroSpace Information
 7121 Standard Drive
 Hanover, MD 21076–1320



Operational Influence on Thermal Behavior of High-Speed Helical Gear Trains

Robert F. Handschuh U.S. Army Research Laboratory Glenn Research Center, Cleveland, Ohio

Charles J. Kilmain Bell Helicopter Textron, Inc., Fort Worth, Texas

Prepared for Forum 62 sponsored by the American Helicopter Society International, Inc. Phoenix, Arizona, May 9–11, 2006

National Aeronautics and Space Administration

Glenn Research Center Cleveland, Ohio 44135

Level of Review: This material has been technically reviewed by technical management.

Available from

NASA Center for Aerospace Information 7121 Standard Drive Hanover, MD 21076–1320 National Technical Information Service 5285 Port Royal Road Springfield, VA 22161

Available electronically at http://gltrs.grc.nasa.gov

Operational Influence on Thermal Behavior of High-Speed Helical Gear Trains

Robert F. Handschuh U.S. Army Research Laboratory Glenn Research Center Cleveland, Ohio 44135

Charles J. Kilmain Bell Helicopter Textron, Inc. Fort Worth, Texas 76101

Abstract

An experimental effort has been conducted on an aerospace-quality helical gear train to investigate the thermal behavior of the gear system as many important operational conditions were varied. Drive system performance measurements were made at varying speeds and loads (to 5,000 hp and 15,000 rpm). Also, an analytical effort was undertaken for comparison to the measured results. The influence of the various loss mechanisms from the analysis for this high speed helical gear train gearbox will be presented and compared to the experimental results.

Introduction and Background

Current and future high speed, heavily loaded, and lightweight gearing components will be a part of all propulsion systems for rotorcraft. These systems are expected to deliver high power from the gas turbine engines to the high-torque/low-speed rotor with reduction ratios in the range of 25:1 to 100:1 (refs. 1 to 14). Gearing systems in these extreme duty applications can also have thermal behavior issues due to the high pitch line velocities. While design considerations for gear tooth bending and contact capacities are usually considered initially, high speed gearing design needs to carefully consider the consequences of pitch line velocities approaching 25000 ft/min. In prior studies, the thermal behavior characteristics of mechanical components are the least understood and have received a minimum amount of attention in the open literature (refs. 15 to 19).

In rotorcraft drive systems, such as that of tiltrotors (fig. 1), a helical gear train is used to connect the parallel engine and mast shafting on the aircraft. Therefore, the drive system is not only needed to provide the necessary reduction between the engine and rotor, but also has to make the system operate in emergency conditions (refs. 20 and 21) such as one engine inoperative and oil out conditions. The propulsion configuration for a tiltrotor aircraft is shown in figure 2 (ref. 22).

For the drive system components of interest in this study, the gearing between the parallel axes of rotation of the engine and mast is composed of a series of helical gears (or gear train). In this arrangement, the idler gears receive two thermal cycles per revolution. Since these gears have two thermal cycles per revolution and are extremely light-weight (low heat carrying capacity) the successful operation of the system in all possible normal and emergency conditions can be difficult. Other recent publications have looked at several topics of interest with respect to this high-speed gear train (refs. 23 and 24). Effects of speed, load, shrouds, and lubrication flow rate have been studied. The most drastic performance effect of all the conditions that can be imposed is the pitch line velocity of the system. The resultant gear windage from the high speed components can produce a dramatic increase in power loss.

The objective of this paper is to present the effects of speed and load on the operating performance (power loss) of the helical gear train. A high-speed helical drive train facility that utilizes full scale, aerospace quality components was used to generate the data presented in this study. The system can operate to 15,000 rpm (to simulate the engine input rotational speed) and at power levels to 5,000 hp. Also, an analysis of the facility gearing, bearing, and windage losses was conducted. The experimentally measured efficiency is compared to that attained via analysis methods.

Test Facility, Test Hardware, Data Acquisition, and Test Procedure

Test Facility

The test facility used for this study is shown in figure 3 (ref. 23). The facility is a closed-loop, torque-regenerative testing system. There is a test gearbox and slave gearbox that are basically mirror images of each other. Each gearbox has an input gear, three idlers, and one bull gear. The gearboxes are joined together through the input gears and bull gears via shafting.

The facility is powered by a 500 hp DC drive motor and its output speed is increased using a speed-increasing gearbox. The output of the speed-increasing gearbox then passes through a torque and speed sensor before connecting to the slave gearbox. A diagram of the entire test stand configuration is shown in figure 4.

Each gearbox has separate supply pumps, scavenge pumps, and reservoirs. Lubrication system flow rate is controlled using the supply pressure. Temperature is controlled via immersion heaters in the reservoir and heat exchangers that cool the lubricant returned from the gearboxes. Each lubrication system has a very fine 3-micron filtration. Nominal jet pressure into the test or slave gearboxes is at 80 psi. The lubricant used in the tests to be described was a synthetic turbine engine lubricant (DoD-PRF-85734).

Test Instrumentation/Data Acquisition

The test instrumentation used in this study only required measurement of the oil inlet and exit temperatures from the test gearbox, the loop torque (measured via a strain gaged shaft and telemetry), the lubricant supply pressure, and the test gearbox outside case temperature. This data was collected at 2 sec intervals throughout the test and averaged over a 30 sec period at steady state conditions.

Test Hardware

The test hardware used in the tests to be described is aerospace quality hardware. The basic gear design information is contained in table 1. The input and bull gear shafts have ball bearings to contain the resultant thrust loads whereas the idler gears only have roller bearings. The partially disassembled test gearbox is shown in figure 5. The bearing inner race is integral to the shafts on the idler gears and at other radially-loaded bearings on the input and bull gear shafts. Shrouds for the gears used to minimize the windage losses are shown in figure 6.

Test Operation

The test procedure used for collecting the data was the following. For a given set of conditions (speed, load, lubricant pressure, and lubricant oil inlet temperature) the facility was operated for at least 5 min or until the temperatures of interest had stabilized.

Analytical Method

An analysis of the losses of the test gearbox will now be described. In the test gearbox there are a total of five gears and four gear meshes. All the gear meshing and bearing power losses were found for a total of six conditions. The conditions were at two input shaft speeds, 12,500 and

15,000 rpm, and at three levels of applied loop torque, 33, 67, and 100 percent of full load.

Each mesh was analyzed using the method of (ref. 25) for the gear sliding and rolling losses. This gear meshing analysis can only analyze spur gears. Therefore, the gear train components were assumed to be spur gears with the same diametral pitch and face width as the test hardware. Since the gears have only a 12° helix angle this affect was assumed to be negligible.

The gear meshing losses are found along the line of action and numerically integrated. The gear sliding losses use a position varying friction coefficient based on the gear tooth sliding/rolling velocity, lubricant inlet temperature, and the load being applied. The sliding losses are calculated by the following equation:

$$P_{Sliding}(x) = C_1 V_{Sliding}(x) f(x) W(x)$$
(1)

where

C_1	Constant
V _{Sliding}	Sliding velocity
F	Friction coefficient
W	Applied load
Χ	Position along the line of action

The rolling power losses are give by:

$$P_{Rolling} = C_2 V_{Rolling}(x) h(x) \phi_t(x)$$
(2)

where

 C_2 Constant V_{Rolling} Rolling velocity h Lubricant film thickness Lubricant film thickness thermal reduction factor $\mathbf{\Phi}_t$

The gear windage is based on the method contained in the work of (ref. 26). In this model the effects of gear size, shrouding, rotational speed, and environment can be treated. This portion of the gearing losses is given by the following equation:

$$P_{Windage} = C_3 C' \rho N^{2.85} D^{4.7} v^{0.15} \lambda \tag{3}$$

where

~

C_3	Constant
Ć'	Shape factor, related to the number of
	teeth, face width to diameter ratio of the gear
ρ	Density of environment (air and lubricant)
N	Gear rotational speed
D	Gear diameter

- *v* Kinematic viscosity (air and lubricant)
- λ Enclosure factor, 0.5 for tight fitting housing

As an example of the lubricant/air effect on the windage of the helical gear train under study in this paper, the method of (ref. 25) is used and the results are shown in figure 7. In the calculation, lubricant/air percentages are varied. Assuming just air in the gearbox produces very low windage losses. By increasing the lubricant/air percentage to just 1 percent lubricant and 99 percent air results in a 20× increase in windage losses.

The bearing losses were found using the method in (ref. 27). The friction torque necessary to rotate the bearings under the assumed power and speed conditions were calculated. The calculation is based on the type of bearing, bearing size, applied load and rotational speed. The power loss from the bearings is given by the following:

$$P_{Bearing} = \sum_{i=1}^{j} C_4 \left(M_{l_i} + M_{\nu_i} \right) \tag{4}$$

where the friction torque due to the applied load is given by:

$$M_l = f_1 F_\beta d_m \tag{5}$$

- f_1 Factor dependent on bearing design and relative bearing load
- F_{β} Dependent on magnitude and direction of the applied load
- d_m pitch diameter of the bearing

Where the viscous friction torque is given by:

$$M_v = C_5 f_o (v_o n)^{2/3} d_m^3 \tag{6}$$

or

$$M_v = C_6 f_o d_m^3 \text{ for } v_o n \le 2000$$
 (7)

 C_4, C_5, C_6 Constants f_o Parameter dependent on bearing type and
lubrication method v_o Kinematic viscosity of the lubricant
nnBearing rpm

The seals on the test rig are only at the input and bull gear shaft locations. The input shaft has a labyrinth seal and the bull gear uses a carbon face seal. The losses from the sealing system were found to be negligible for this system for the conditions under study in this paper.

Summary of Losses Via Analysis

A summary of the analytical results for the gear system under study are presented in table 2. As mentioned earlier, six conditions were analyzed. A break down of the loss mechanisms are also shown in figure 8 for the 15,000 rpm input shaft speed with the load varying between 33 to 100 percent. The windage losses were assumed to have a lubricant/air mixture of 0.75 and 99.25 percent respectively. The efficiency predicted ranged from 95.81 to 98.29 percent depending on the conditions applied.

Measured Losses

The losses from the test facility are a combination of the heat rejected to the lubricant and surroundings via convection. These loss mechanisms are overcome by the power supplied to the test facility. For the conditions of interest (approximately the same conditions analyzed) the amount of drive motor power supplied as a function of load and speed are shown in figure 9. The drive motor rotates the test and slave gearboxes and supplies the necessary power to maintain the operating conditions. For a given operation input speed, increasing load results in a linear increase in drive motor power. Increasing speed from 12500 to 15000 rpm input speed (16 percent increase) results in a much larger increase of operating power (30 percent increase) required.

The heat rejected to the lubricant is simply the product of the lubricant mass flow rate, specific heat of the lubricant, and the temperature difference across the gearbox and given by the following equation:

$$P_{Lube} = C_7 \dot{m} C_p \Delta T \tag{8}$$

where

$$\begin{array}{lll} C_7 & \text{Constant} \\ \dot{m} & \text{Mass flow rate} \\ C_p & \text{Specific heat of the lubricant} \\ \Delta T & \text{Lubricant temperature change across the gearbox} \end{array}$$

The convection losses are those due to free convection. Flat plate heat transfer coefficients were assumed for the six faces of the gearbox (ref. 28). The surface temperature of the gearbox was measured at the mid-height and width. This temperature was assumed to exist on each face of the gearbox. The ambient temperature was assumed to be 75 °F, since the system is operated in a temperature controlled (air conditioned) test facility. These losses are given by the following equation:

$$P_{Conv} = \sum_{i=1}^{6} h_i A_i \Delta T \tag{9}$$

where

- h_i Free convection heat transfer coefficient
- A_i Area of convection surface *i*
- ΔT Temperature difference between outside of case and ambient conditions

The losses measured are shown in table 3. The data shown in table 3 was the average of 15 readings over a 30 sec period of time after the test facility had reached steady state. As shown in the table, the vast majority of the heat is absorbed in the lubricant and the convection only makes up a very small percentage of the overall losses. The efficiency for each of the conditions is also shown in this table.

Comparison of Analytical and Experimental Results

For the six conditions of interest the results from analysis and experiment are shown in figure 10. As can be seen from the figure, results generated by analysis and experiments indicated that the efficiency increases with increasing load and decreases with increasing input rotational speed. For the analytical results shown, the windage losses are a substantial percentage of the losses. As was mentioned earlier, the power losses are affected by the assumed lubricant/air mixture content that is used for the windage analysis. For this study, the lubricant portion (0.75 percent) was chosen to match the maximum power loss at the highest speed condition and then fixed. The results followed the experimental trends for the conditions under study, but the results diverged at lower power levels.

The windage assessment is believed to be the weakest portion of the analytical tools available for predicting the resultant losses. A rigorous windage assessment program needs to be developed to further understand the basic physics of this phenomenon. As prior studies on high speed gear systems have shown, configuration and environmental conditions can definitely affect the results. Therefore a model capable of handling these system and environment issues is needed for use in a relevant aerospace environment where gear windage is often the dominant power loss mechanism.

Conclusions

Based on the analytical and experimental work completed in this study the following conclusions can be drawn:

1. From the experimental data and analysis results, power loss increases linearly if the load is increased at constant shaft speed. A large increase in power is required to change rotational speed from 12,500 to 15,000 rpm.

Changing speed has the most dramatic effect on the windage loss for a constant air/oil environment.

- 2. Each of the gears and bearings were analyzed for their power loss contribution, for various input speeds and transmitted powers. Gear windage is a large contributor to the total power to drive the system loss at all of the conditions of interest in this study since the pitch line velocity at the two conditions of interest was approximately 20,000 ft/min and 24,000 ft/min.
- 3. A comparison of the results indicated that the analysis followed the efficiency measured trends and the lubricant/air mixture assumption can alter the predicted loss and efficiency predicted.

References

- Henry, Z.: Preliminary Design and Analysis of an Advanced Rotorcraft Transmission, American Helicopter Society, AHS Preprint No. 3, November 13– 15, 1990.
- Bossler, R. and Heath, G: Advanced Rotorcraft Transmission (ART) Program Status, American Helicopter Society, AHS Preprint No. 4, November 13– 15, 1990.
- Lenski, J.: Boeing Helicopters Advanced Rotorcraft Transmission (ART) Program, American Helicopter Society, AHS Preprint No. 2, November 13–15, 1990.
- Kish, J.: Advanced Rotorcraft Transmission (ART) Program Review, American Helicopter Society, AHS Preprint No. 5, November 13–15, 1990.
- Drago, R. and Lenski, J.: Advanced Rotorcraft Transmission Program – A Status Report, American Gear Manufacturers Association, FTM-10, 1990.
- 6. Krantz, T. and Kish, J.: Advanced Rotorcraft Transmission (ART) Program Summary, NASA TM-105790, AVSCOM TR 92–C–004, July 1992.
- 7. Bossler, R. and Heath, G.: Advanced Rotorcraft Transmission Program Summary, AIAA–92–3363, Presented at AIAA/SAE/ASME/ASEE 28th Joint Propulsion Conference, July, 1992.
- Henry, Z.: Advanced Rotorcraft Transmission (ART) Component Test Results, AIAA–92–3366, Presented at AIAA/SAE/ASME/ASEE 28th Joint Propulsion Conference, July, 1992.
- 9. Bossler, R., Heath, G., and Sheth, V.: Advanced Rotorcraft Transmission (ART) Program Status, American Helicopter Society, Preprint No. 6, Oct. 1993.
- Heath, G. and Bossler, R.: Advance Rotorcraft Transmission (ART) Program – Final Report, NASA CR-191057, ARL–CR–14, Jan. 1993.
- Kish, J.: Sikorsky Aircraft Advanced Rotorcraft Transmission (ART) Program – Final Report, NASA CR-191079, March 1993.

- Krantz, T.: NASA/Army Rotorcraft Transmission Research, A Review of Recent Significant Accomplishments, NASA TM-106508, ARL–MR–138, AHS Forum 50, May 1994.
- Lenski, J.: Advanced Rotorcraft Transmission (ART) Program, NASA CR-195461, ARL-CR-224, April 1995.
- Henry, Z.: Bell Helicopter Advanced Rotorcraft Transmission (ART) Program, NASA CR-195479, ARL-CR-238, June 1995.
- Lewicki, D., Decker, H., and Shimski, J.: Development of a Full-Scale Transmission Testing Procedure to Evaluate Advanced Lubricants, NASA TP-3265, AVSCOM TR 91-C-026, August 1992.
- Handschuh, R.: Effect of Lubricant Jet Location on Spiral Bevel Gear Operating Temperatures, NASA TM-105656, AVSCOM TR-91-C-033, Sept. 1992.
- 17. Handschuh, R.: Thermal Behavior of Spiral Bevel Gears, NASA TM-106518, ARL-TR-403, Jan. 1995.
- Handschuh, R. and Kicher, T.: A Method for Thermal Analysis of Spiral Bevel Gears, Journal of Mechanical Design, vol. 118, no. 4, Dec. 1996.
- Henry, Z. and Stapper, W.: Evaluation of Navy 9cSt Oil in Bell Helicopter M412 HP Gearboxes, NASA CR-1998-208517, ARM–CR–430, August 1998.
- 20. Morales, W. and Handschuh, R.: A Preliminary Study on the Vapor/Mist Phase Lubrication of a Spur Gearbox, NASA TM-1999-208833, ARL–TR–1912, May 1999.

- Handschuh, R. and Morales, W.: Lubrication System Failure Baseline Testing on an Aerospace Quality Gear Mesh, NASA/TM—2000-209954, ARL–TR–2214, May 2000.
- 22. Kilmain, C., Murray, R., and Huffman, C.: V–22 Drive System Description and Design Technologies, American Helicopter Society 51st Annual Forum, May 1995.
- Handschuh, R. and Kilmain, C.: Efficiency of High-Speed Helical Gear Trains, NASA/TM—2003-212222, ARL–TR–2968, April, 2003.
- Handschuh, R. and Kilmain, C.: Preliminary Comparison of Experimental and Analytical Efficiency Results of High-Speed Helical Gear Trains, ASME 2003 Design Engineering Technical Conference, September 2003, Chicago, IL.
- 25. Anderson, N. and Lowenthal, S.: Spur Gear System Efficiency at Part and Full Load, NASA TP-1622, AVRADCOM TR-79-46, February 1980.
- 26. Dawson, P.H.: High Speed Gear Windage, pp. 164–167, GEC Review, vol. 4, no. 3, 1988.
- 27. Harris, T.: <u>Rolling Bearing Analysis</u>, pp. 504–509, 1991.
- 28. Holman, J.P.: Heat Transfer, 4th Edition, 1976.

Number of teeth, Input and 2nd Idler/1st and 3rd Idler/Bull Gear	50/51/139
Module (mm), (Diametral Pitch (1/in))	3.033 (8.375)
Face Width mm (in)	67.2 (2.625)
Helix Angle, deg.	12
Gear Material	Pyrowear EX-53

TABLE 1.—BASIC DESIGN DATA FOR GEARS IN HIGH-SPEED HELICAL GEAR TRAIN TEST FACILITY

TABLE 2.—POWER LOSS AND EFFICIENCY PREDICTIONS AT GIVEN CONDITIONS

High speed input shaft torque	High speed input shaft speed	Gear Sliding and rolling losses	Gear Windage losses (0.75 percent lube)	Roller bearing losses	Ball bearing losses	Total Power Loss	Loop power	Efficiency
(in*lb)	(rpm)	(hp)	(hp)	(hp)	(hp)	(hp)	(hp)	(%)
6834	12500	10.891	29.406	3.34	0.34	43.977	1355.4	96.756
14028	12500	20.982	29.406	7.03	0.90	58.318	2782.3	97.904
20863	12500	29.942	29.406	10.10	1.45	70.898	4137.9	98.287
6834	15000	13.331	49.443	4.81	0.52	68.104	1626.5	95.813
14028	15000	25.300	49.443	9.80	1.32	85.863	3338.7	97.428
20863	15000	36.078	49.443	14.54	2.22	102.281	4965.5	97.940

TABLE 3.—EXPERIMENTAL RESULTS AT SIX CONDITIONS, 200 °F LUBRICANT INLET TEMPERATURE, 80 PSI LUBRICANT JET PRESSURE

Low speed	High speed	Input	Heat	Heat	Total heat	Efficiency
input shaft	input shaft	power to	rejected to	conv. to	rejection	
torque	speed	test	the lube	envir.		
		gearbox				
(in*lb)	(rpm)	(hp)	(hp)	(hp)	(hp)	(%)
19895	12540.0	1423.94	56.34	1.32	57.66	95.95
39266	12529.6	2808.04	58.52	1.35	59.87	97.87
58306	12527.9	4169.09	63.45	1.40	64.85	98.44
19511.8	15023.9	1673.13	83.82	1.54	85.36	94.90
39663.5	15070.8	3411.75	91.25	1.59	92.84	97.28
58555.9	15024.7	5021.41	98.70	1.64	100.33	98.00



Figure 1.—Tiltrotor aircraft.



Figure 2.—Typical tiltrotor aircraft propulsion system arrangement.



Figure 3.—NASA High-Speed Helical Gear Train Test Facility.



Figure 4.—Layout of NASA High-Speed Helical Gear Train Test Facility.



Figure 5.—NASA High-Speed Helical Gear Train Test Facility Components.



Figure 6.—Photographs of shrouding on the test gearbox (left entire gearbox and right photograph is a close up of the input-1st idler gear shrouds).



Figure 7.—Effect of lubricant—air mixture on windage of high speed helical gear train.



Figure 8.—Predicted power loss at 15000 rpm input shaft speed for each of the components in the test gearbox.



Figure 9.—Drive motor power required to rotate the entire test facility system.



Figure 10.—Comparison of experimentally attained and analytically predicted efficiency.

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of i gathering and maintaining the data needed, a collection of information, including suggestion Davis Highway, Suite 1204, Arlington, VA 22	nformation is estimated to average 1 hour per r and completing and reviewing the collection of it is for reducing this burden, to Washington Head 2202-4302, and to the Office of Management ar	esponse, including the time for reviewing nformation. Send comments regarding th quarters Services, Directorate for Informa d Budget, Paperwork Reduction Project	i instructions, searching existing data sources, is burden estimate or any other aspect of this ation Operations and Reports, 1215 Jefferson (0704-0188), Washington, DC 20503.		
1. AGENCY USE ONLY (Leave bland	k) 2. REPORT DATE November 2006	3. REPORT TYPE AND DA	TTYPE AND DATES COVERED Technical Memorandum		
4. TITLE AND SUBTITLE		5 6			
Operational Influence on T	Thermal Behavior of High-Speed	Helical Gear Trains	WDS 561591 02 07 02 02 01		
6. AUTHOR(S)			WBS 301381.02.07.03.03.01		
Robert F. Handschuh and (Charles J. Kilmain				
7. PERFORMING ORGANIZATION	NAME(S) AND ADDRESS(ES)	8. P R	ERFORMING ORGANIZATION REPORT NUMBER		
Iohn H. Glonn Possarah C	Space Administration				
Cleveland, Ohio 44135–3		E-15571			
9. SPONSORING/MONITORING AG	ENCY NAME(S) AND ADDRESS(ES)	10.	SPONSORING/MONITORING AGENCY REPORT NUMBER		
National Aeronautics and S	Space Administration				
Washington, DC 20546-0	0001		NASA TM-2006-214344		
			ARL-TR-3969		
11. SUPPLEMENTARY NOTES					
May 9–11, 2006. Robert F Bell Helicopter Textron, In organization code RXM.	F. Handschuh, U.S. Army Researc nc., 600 E. Hurst Blvd., Fort Wor	h Laboratory, Glenn Researd th, Texas 76101. Responsibl	ch Center; Charles J. Kilmain, e person, Robert F. Handschuh,		
12a. DISTRIBUTION/AVAILABILITY	STATEMENT	12b.	DISTRIBUTION CODE		
Unclassified - Unlimited Subject Category: 37					
Available electronically at http	·//oltrs orc nasa ooy				
This publication is available fro	om the NASA Center for AeroSpace In	formation, 301–621–0390.			
13. ABSTRACT (Maximum 200 wor	rds)				
An experimental effort has the gear system as many in made at varying speeds an to the measured results. Th train gearbox will be prese	s been conducted on an aerospace mportant operational conditions v id loads (to 5,000 hp and 15,000 n he influence of the various loss m ented and compared to the experim	e-quality helical gear train to vere varied. Drive system pe pm). Also, an analytical effo echanisms from the analysis mental results.	investigate the thermal behavior of rformance measurements were ort was undertaken for comparison s for this high speed helical gear		
14. SUBJECT TERMS			15. NUMBER OF PAGES		
Gears; Transmissions		16. PRICE CODE			
17. SECURITY CLASSIFICATION	18. SECURITY CLASSIFICATION	19. SECURITY CLASSIFICATION			
	OF THIS PAGE	OF ABSTRACT			
Unclassified	OF THIS PAGE Unclassified	OF ABSTRACT Unclassified			