

AD-A010 582

NEW INFRARED LASER CONCEPTS

Walter H. Christiansen

Washington University

Prepared for:

Office of Naval Research  
Advanced Research Projects Agency

14 May 1975

DISTRIBUTED BY:

**NTIS**

National Technical Information Service  
U. S. DEPARTMENT OF COMMERCE

167096

Form Approved, Budget  
Bureau No. 22-R02013

AD A010582

**Semiannual Technical Report**

**May 14, 1975**

**Period Covered: 74 Oct 01 - 75 Mar 31**

**ARPA Order Number 2840**

**Contract Number N00014-75-C-0316**

**Program Number 5E20**

**Principal Investigator:**

**Walter H. Christiansen**

**Phone: (206) 543-6321**

**Contractor:**

**Board of Regents**

**University of Washington**

**Seattle, WA 98195**

**Scientific Officer:**

**Director, Physics Program**

**Physical Sciences Division**

**Office of Naval Research**

**800 N. Quincy Street**

**Arlington, VA 22217**

**Effective Date of Contract:**


**74 Oct 01**

**Title: "New Infrared Laser Concepts"**

**Contract Expiration Date:**

**75 Nov 30**

**Amount of Contract: \$60,000.**



The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Advanced Research Projects Agency or the U.S. Government.



Unclassified

SECURITY CLASSIFICATION

THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle)  New Infrared Laser Concepts		5. TYPE OF REPORT & PERIOD COVERED 74 Oct 01-75 Mar 31 Semiannual Technical Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s)  Walter H. Christiansen		8. CONTRACT OR GRANT NUMBER(s)  N00014-75-C-0316
9. PERFORMING ORGANIZATION NAME AND ADDRESS Aerospace Research Laboratory University of Washington Seattle, Washington 98195		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS ARPA Order Number 2840 Program Number 5E20
11. CONTROLLING OFFICE NAME AND ADDRESS Procuring Contracting Officer Officer of Naval Research Department of the Navy Arlington, VA 22217		12. REPORT DATE May 14, 1975
		13. NUMBER OF PAGES 8
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Office of Naval Research Resident Representative University of Washington 3710 Brooklyn Ave. N.E., Unit No. 2 Seattle, Washington 98195		15. SECURITY CLASS. (of this report)  Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  Infrared laser concepts that have high efficiency or high power applications are being studied. As part of this interest, the possibilities of lasing homonuclear molecules such as H <sub>2</sub> or N <sub>2</sub> directly without the use of permanent dipole additives have been analyzed. Basically the idea is to produce an inversion in a gas by a high-pressure e-beam-stabilized electric discharge and then induce radiative transitions via collision partners or electric fields. Of the many molecular possibilities, H <sub>2</sub> has been chosen as a likely		

candidate for such a laser because of its relatively short wavelength transitions ( $2.8\mu$ ) and easily achieved population inversion. Gain has been predicted over a bandwidth extending from  $2.7\mu$  to  $10\mu$  using the principle of collisionally induced dipole. The magnitude of the peak gain which occurs at  $2.8\mu$  is proportional to pressure squared and for a mixture of  $H_2$  and Xe equals approximately 5%/meter at 50 atmospheres.

## TECHNICAL PROGRAM

### I. Collisionally Induced Laser

#### Summary

Infrared laser concepts that have high efficiency or high power applications are being studied. As part of this interest, the possibilities of lasing homonuclear molecules such as  $H_2$  or  $N_2$  directly without the use of permanent dipole additives have been analyzed. Basically the idea is to produce an inversion in a gas by a high-pressure e-beam-stabilized electric discharge and then induce radiative transitions via collision partners or electric fields. Of the many molecular possibilities,  $H_2$  has been chosen as a likely candidate for such a laser because of its relatively short wavelength transitions ( $2.8\mu$ ) and easily achieved population inversion. Gain has been predicted over a bandwidth extending from  $2.7\mu$  to  $10\mu$  using the principle of collisionally induced dipole. The magnitude of the peak gain which occurs at  $2.8\mu$  is proportional to pressure squared and for a mixture of  $H_2$  and Xe equals approximately 5%/meter at 50 atmospheres.

#### Technical Progress and Tasks

As part of the collisionally induced laser program the following tasks have been identified and have been studied during this period:

1. Dissociative recombination measurements of  $H_2$ -Xe mixtures: In order to insure that gain is observed @  $2.8\mu$ , the continuum absorption due to electron-neutral bremsstrahlung must be small. This is expected to be the case after crowbaring the sustainer discharge and e-beam so that electron recombination will sizably reduce the electron concentration. Preliminary measurements of this recombination in mixtures of  $H_2$ -Ar,

N<sub>2</sub>-Ar, H<sub>2</sub>-Xe at pressure from 5 to 10 atm and electron density of 10<sup>13</sup>/cm<sup>3</sup> to 10<sup>14</sup>/cm<sup>3</sup> have shown recombination rates which are satisfactorily fast and in good agreement with experimental results of others carried out at lower pressure. These measurements were carried out in a small scale e-beam device that was available and not the larger device being built and described below.

2. Aerodynamic disturbances: Measurements of any aerodynamic disturbances with time due to nonuniform discharge heating will be attempted using laser holography. The holographic apparatus using a Q switched ruby is almost complete and ready to be tested.
3. V-V rate measurement in H<sub>2</sub>: The first measurements of v-v rates in H<sub>2</sub> will be attempted shortly. This information is necessary to accurately predict the rate of electrical pumping required. Measurements of v-v energy transfer rates will be obtained in vibrationally excited D<sub>2</sub> and HD. By absorbing a short pulse of HF laser radiation ( $\approx 1$  joule in 30 nsec), the D<sub>2</sub> or HD molecules are excited to the first vibrational level. The v-v rates will be obtained by recording the time variation of the collision-induced spontaneous overtone emission radiation from different vibrational levels. The electrical discharge of the HF laser has been studied and is now operational. While still in the development stage, it appears that the laser is capable of 0.5 joule output suitable for the experiment. The high-pressure absorption cell for the D<sub>2</sub>/HD-Xe mixtures has also been constructed. The cell has been vacuum checked.
4. Inverse Bremsstrahlung measurements: Preliminary measurements were carried out in mixtures of N<sub>2</sub>-Ar last fall. These important experiments of the continuum absorption have been delayed until an enlarged e-beam

apparatus is completed.

5. Gain measurements at  $2.8\mu$ : An optical bridge and HF laser probe for  $2.8\mu$  has been constructed. The power supply for the sustainer is being re-constructed. A high pressure sustainer cell is available. Measurements of gain await completion of the e-beam apparatus. The electron beam apparatus to be used for induced dipole laser experiments is being tested. Vacuum tests showed the chamber could be evacuated to pressures on the order of  $10^{-5}$  torr, sufficient for electrical operation of the device. A comprehensive series of electrical tests using a variety of cold cathodes is being carried out presently. To date, about 3 amps/cm<sup>2</sup> (about 200 amps total) have been drawn thru the foil window at 180kv without arcing problems. We are concentrating at improving the efficiency of this device as well as increasing the voltage output.

## II. V-V Pumped Balanced Laser Program

### Summary

In the search for new lasers having the possibility of increased efficiency, the N<sub>2</sub>-DCl and D<sub>2</sub>-HCl molecular systems have also been analyzed as examples of possible v-v transfer lasers. Experimental apparatus in the form of a low pressure mixing laser setup was built and used as a means for preliminary study.

### Tasks

After initially lasing both CO and CO<sub>2</sub> in the apparatus, attempts at lasing DCl and HCl were carried out in the previous year. Unfortunately these tests were not positive. During the latter part of 1974 lasing was reattempted (also using CO-CS<sub>2</sub> and N<sub>2</sub>-CS<sub>2</sub>) using better optics with the

same result. Line reversal measurements of the vibrational energy in  $\text{CS}_2$  were carried out and showed a vibrational temperature of about  $600^\circ\text{K}$  at best, which is too low for lasing. Thus it appears that v-v transfer in  $\text{N}_2\text{-CS}_2$  and  $\text{CO-CS}_2$  mixtures is too slow.