ADA 029168 DAVID W. TAYLOR NAVAL SHIP RESEARCH AND DEVELOPMENT CENTER Bethesda, Md. 20084 APPLICATION OF CIRCULATION CONTROL ROTOR TECHNOLOGY TO A STOPPED ROTOR AIRCRAFT DESIGN PPLICATION OF CIRCULATION CONTROL ROTOR TECHNOLOGY TO A STOPPED ROTOR AIRCRAFT DESIGN by Robert M. Williams APPROVED FOR PUBLIC RELEASE. DISTRIBUTION UNLIMITED. SEP 1 1976 8 211115 AVIATION AND SURFACE EFFECTS DEPARTMENT RESEARCH AND DEVELOPMENT REPORT Report 4574 December 1975 5



Wallie X

- Emiles

anterior de la

A REAL PROPERTY AND A REAL	ATION PAGE	READ INSTRUCTIONS
1. REPORT NUMBER	2. GOVT ACCESSION NO	. 3. RECIPIENT'S CATALOG NUMBER
4574		
TITLE (and Subilia)		S. TYPE OF REPORT & PERIOD COVERE
APPLICATION OF CIRCULAT	ION CONTROL ROTOR	
AIRCRAFT DESI	GN .	6. PERFORMING ORG. REPORT NUMBER
2. AUTHOR(A)		Aero Report 1218
Robert M. Williams		
. PERFORMING ORGANIZATION NAME AND A	ODRESS	10. PROGRAM ELEMENT, PROJECT, TASH AREA & WORK UNIT NUMBERS
David W. Taylor Naval Ship H Bethesda, Maryland 20084	R&D Center	Work Upit 4-1600-001
11. CONTROLLING OFFICE NAME AND ADDRE	35 (11	December 25
Naval Air Systems Command		
wasnington, D. C. 20361		32
14. MONITORING AGENCY NAME & ADDRESS	I dillerent from Contrelling Office)	18. SECURITY CLASS. (of this report)
Research and devel	lopment rept.	Unclassified
		SCHEDULE
6. DISTRIBUTION STATEMENT (of this Report))	<u> </u>
17. DISTRIBUTION STATEMENT (of the abbirger	DTNSRDC - 45	74
10. SUPPLEMENTARY NOTES Presented at the First	European Rotorcraft a Southampton England on	and Powered Lift Aircraft n 22-24 September 1975.
Forum at the University of S The report is prepared in the then in DTNSPDC format	ne style established :	tor the forum rather
Forum at the University of S The report is prepared in th than in DTNSRDC format.	ne style established)
Forum at the University of S The report is prepared in th than in DTNSRDC format. 9. KEY WORDS (Continue on reverse elde if nece V/STOL Aircraft Stopped Rotor Aircraft	ne style established :)
Forum at the University of S The report is prepared in th than in DTNSRDC format. KEY WORDS (Continue on reverse elde if nece V/STOL Aircraft Stopped Rotor Aircraft High Lift Aerodynamics	ne style established :	
Forum at the University of S The report is prepared in th than in DTNSRDC format. V/STOL Aircraft Stopped Rotor Aircraft High Lift Aerodynamics Circulation Control	ne style established :)
Forum at the University of S The report is prepared in th than in DTNSRDC format. V/STOL Aircraft Stopped Rotor Aircraft High Lift Aerodynamics Circulation Control Rotary Wing (Helicopters)	ne style established : beeary and identify by block number;	
Forum at the University of S The report is prepared in th than in DTNSRDC format. KEY WORDS (Continue on reverse elde If nece V/STOL Aircraft Stopped Rotor Aircraft High Lift Aerodynamics Circulation Control Rotary Wing (Helicopters) AUSTRACT (Continue on reverse elde If nece This paper presents the technology to a revolutionar V/STOL. This design affords aircraft speed, range-payloa of highly innovative aerodyn for the concept has been der	ne style established : 	ulation control rotor (CCR) ptthe X-Wing stopped rotor ajor advances in rotary wing cost through the applicatio design. The technology base ears of related CCR (See reverse side)

LE

LUNHITY CLASSIFICATION OF THIS PAGE (When Date Baland)

(Block 20 Continued)

aerodynamic and structural design studies at the David W. Taylor Naval Ship Research and Development Center (DTNSRDC) and from earlier research in the United Kingdom. Additional design insight has been gained from the experience of various stopped and stowed rotor concepts of the 1960's and also from recent studies of the NASA "oblique wing" transonic transport concept.

White Section Bull Section	000
AVAILARILITY	CODES
	White Section Butt Section /AVAILABILITY VALL and/or S

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	Page
INTRODUCTION	1
DESCRIPTION OF CONCEPT	1
AERODYNAMICS	2
EMPTY WEIGHT	5
MISSION ANALYSIS	6
ROTOR AEROELASTICITY AND DYNAMICS	7
STABILITY AND CONTROL	8
SUMMARY	8
REFERENCES	26

LIST OF FIGURES

1	 Circulation Control X-Wing V/STOL Aircraft Concept	•	•	•	•	•	•	10
2	 Compressibility Characteristics of Two Dimensional CC Airfoils at Zero Angle of Attack	•	•	•	•	•	•	11
3	 X-Wing Transonic Design Features	•	•	•	•	•	•	11
4	 Circulation Control Rotor - Basic Concept	•	•	•	•	•	•	12
5	 Dual Blowing Concept for Transition through High Advance Ratios	•	•	•	•	•.	•	12
6	 Effect of Simultaneous Leading and Trailing Edge Blowing	•	•	•	•	•	•	13
7	 Rotor Aerodynamic Environment during Transition Flight ($\mu = 0.7$, $\alpha_s = 0$, $C_{T/\sigma} = 0.129$)	•	•	•	•	•	•	14
8	 Maximum X-Wing/Rotor Thrust Capability	•	•	•	•	•	•	17
9	 X-Wing Aircraft Equivalent Lift-to-Drag Ratio	•	•	•	•	•	•	18
10	 Drag Coefficient (Based on Hub Planform Area) for Three Hubs with Shanks		_					19

		Page
11	 Wing/Rotor Design and Weight Analysis Approach	20
12	 Aluminum Blade Construction: Effect of Design Parameters	21
13	 Graphite Composite Construction: Effect of Blade Design Parameters	22
14	 X-Wing Dual Cross-Spar Rotor Hub Structural Design	23
15	 Impact of the X-Wing Design on Rotary Wing VTOL Empty Weight Trends	24
16	 Comparison of X-Wing Payload Capability with Other Rotary Wing VTOL Aircraft	24
17	 X-Wing Rotor Blade Frequency Characteristics	25
18	 Effect of Four Blades on the Reduction of Peak-to-Peak Moments during the Rotor Revolution	25

APPLICATION OF CIRCULATION CONTROL ROTOR TECHNOLOGY TO A STOPPED ROTOR AIRCRAFT DESIGN*

Robert M. Williams

INTRODUCTION

This paper presents the application of circulation control rotor (CCR) technology to a revolutionary new aircraft concept--the X-Wing stopped rotor V/STOL. This design affords the potential for major advances in rotary wing aircraft speed, range-payload, productivity, and cost through the application of highly innovative aerodynamic and structural design. The technology base for the concept has been derived from almost 6 years of related CCR aerodynamic and structural design studies at the David W. Taylor Naval Ship Research and Development Center (DTNSRDC) and from earlier research in the United Kingdom. Additional design insight has been gained from the experience of various stopped and stowed rotor concepts of the 1960's and also from more recent studies of the NASA "oblique wing" transonic transport concept.

DESCRIPTION OF CONCEPT

The basic design is illustrated in Figure 1 for an attack-type configuration. Salient features include four highly loaded rotor blades (150-psf wing loading) of moderate aspect ratio (12.0), which are stopped in flight at the 45-degree azimuth position. The rotor/wing is both aerodynamically efficient (hover Figure of Merit ≈ 0.70 , fixed-wing lift system equivalent lift-to-drag ratio ≈ 20.0) and is also structurally ideal (20-percent root thickness ratio, 10-percent tip, and planform taper ratio of 2:1). The high wing sweep, in conjunction with the excellent critical Mach number characteristics of the CC airfoils (Figure 2), permits the wing to have a drag rise Mach number of approximately 0.90. Also, because of a combination of low solidity ratio and the basic symmetry of the wing corss-sectional area distribution, the X-Wing

1

^{*}Presented at the First European Rotorcraft and Powered Lift Aircraft Forum, Southampton, England, 22-24 September 1975.

aircraft is <u>inherently</u> area-ruled without "coke bottling" (Figure 3). These features permit design of an internal engine configuration with unexcelled transonic drag rise characteristics without the internal space problem, structural difficulties, and added subsonic drag penalty normally associated with area-ruled designs. In addition to these more obvious characteristics, the X-Wing possesses several other unique properties which, when taken as a whole, offer a revolutionary improvement in V/STOL capability. These are discussed briefly in the following section.

AERODYNAMICS

The CCR concept is illustrated schematically in Figure 4. Basically, a thin jet sheet of air is ejected tangetially over the rounded trailing edge of a quasi-elliptical airfoil, suppressing boundary layer separation and moving the rear stagnation streamline toward the lower surface. thereby increasing lift in proportion to the duct pressure.* For a pneumatically controlled rotor application, the azimuthal variation of lift is controlled by a simple nondynamic valve in the hub. At higher speeds and advance ratios, a second duct and leading edge slot are used (Figure 5) so that the rotor can develop significant lift in the region of reverse flow. Two-dimensional airfoil experiments have shown that it is possible to develop large lift coefficients by blowing from either slot individually or from both simultaneously. The latter technique is used for advance ratios from 0.5 to 1.0 where the retreating blade experiences "mixed flow" (i.e., locally reversed flow on the inboard • sections and forward flow on the outer sections). Test results for this unique airfoil are shown in Figure 6.

The significance of CCR aerodynamics can be assessed by noting that the critical design parameter for any high speed horizontal rotor concept

^{*}For reasons of brevity, it is not possible to discuss the details of the CC section aerodynamics in the paper. The reader is referred to the bibliography contained in Reference 1 for more information on these unique airfoils.

¹Stone, M. B. and R. J. Englar, "Circulation Control -- A Bibliography of NSRDC Research and Selected Outside References," ASED Report 4108, Naval Ship Research and Development Center, Bethesda, Maryland (1974). A complete listing of references is given on page 26.

is, in fact, the maximum lift capability in the intermediate advance ratio range (0.7 to 0.9) where the retreating side of the disc is immersed in mixed flow of low average velocity. Traditionally, the solution to this problem has been to add more blade area, to employ a separate wing, or to use a second contrarotating rotor. Without exception, these approaches have resulted in large and fundamentally limiting weight penalties and usually a hover and/or cruise efficiency penalty. The X-Wing minimizes the transition lift problem by blowing out of both slots in the mixed flow region and by using a cyclic pressure control schedule which shifts the maximum loading to the fore and aft regions of the disc. Figure 7 illustrates the extreme aerodynamic environment which is made tractable by these simple pneumatic techniques in conjunction with the high lift properties of the basic CC airfoil sections. The crucial significance of the transitional lift capability is that it permits the X-Wing to develop blade loadings on the order of three times that of conventional rotors. Figure 8 illustrates performance calculated through the advance ratio range.*

The design implications of this blade-loading capability are far reaching indeed for they permit high aspect ratio blades to be used for efficient hover while also allowing the aircraft to operate in very high speed cruise at the lift coefficient for maximum efficiency. The calculated cruise efficiency for one aircraft design shown in Figure 9 (range is proportional to L/D_e) indicates that a peak vehicle L/D_e of 10.0 is achievable at 350 knots (10,000-foot altitude).

The details of the transitional aerodynamic performance are too lengthy to be described in this paper. Basically, however, the aircraft will accelerate as a thrust compounded helicopter up to the transition advance ratio of 0.7 (approximately 250 knots). Then while maintaining a constant flight velocity, the rotor RPM is rapidly reduced to zero by

^{*}These theoretical results $(C_T/\sigma = 0.16 \text{ at } \mu = 0.7)$ have just been experimentally confirmed at this writing by tests on a 7-foot diameter rotor in the DTNSRDC 8- by 10-foot wind tunnel. A DTNSRDC report on these tests will be issued in the near future.

using a rotor brake to decelerate and stop the rotor (approximately 30second total conversion time). A simple arrestment and lockout system is then used to position the blades during their final revolution. The symmetry of the rotor allows the blades to be stopped in any 45-degree location, thus simplifying the problem of indexing. The aircraft can then either accelerate up to high cruise speeds or operate in a fixedwing mode at very low forward speeds (below transition speed). The aircraft would also have the capability for STOL takeoffs and landings in the "blown" fixed-wing mode with the large compressor power source used for transition.

Another special aerodynamics problem of high speed rotorcraft is that the excessive drag associated with the rotor hub may account for more than one-half of the total parasite drag. The X-Wing circumvents the problem by eliminating the usual bluff protuberances such as shafting, pitch linkages, control horns, etc., which give rise to flow separation. The rotor blades and hub are designed to be extremely rigid with a 3degree built-in coning angle. A limited +7-degree blade pitch travel is also included for designs requiring maximum efficient hover operations. The pitch change mechanism is designed to fit within the envelope of the root section so that an aerodynamically efficient hub fairing can be employed. The half-scale model data shown in Figure 10 for several hubshank designs indicate hub drag values an order of magnitude lower than current helicopter hubs (Reference 2). The remainder of the body aerodynamic design is relatively conventional so that except for the hub contribution, the fuselage drag levels are representative of current fixed-wing designs.

Two alternate modes of operation also appear attractive for the X-Wing. For missions which require extensive low speed operation the rotor could be indexed to a 90-degree orientation (thus increasing the effective wing span). If supersonic operation were desired the blades could be "scissored" so that for an included angle of 60 degrees a Mach number of 1.40 should be achievable. The mechanical implementation of the necessary 15 degree increase in

²"Rotorcraft Parasite Drag," special report presented to the 31st Annual National Forum by the Ad Hoc Committee on Rotorcraft Drag, Washington, D.C. (May 1975).

sweep would be quite straightforward using a variation of the crossed spar hub design discussed in the next section.

EMPTY WEIGHT

Notwithstanding its unique aerodynamic capability, possibly the most important characteristic of the X-Wing is its potential for significantly reducing the empty weight penalty of a VTOL. By obviating the traditional requirement for separate hover and cruise lifting systems, the X-Wing is capable of achieving rotor blade/wing weight fractions below 6 percent of gross weight by using aluminum construction and below 4 percent by using a high modulus carbon fibre composite. A preliminary rotor/wing structural analysis has been employed to design the X-Wing. As indicated in Figure 11, the final structural design must efficiently satisfy the diverse requirements of (1) fixed-wing ultimate maneuvering loads, (2) aeroelastic divergence of the forward swept blade, (3) rotor frequency placement to avoid resonant amplification, and (4) rotor loads and fatigue life. Figure 12a illustrates the typical structural-aerodynamic design tradeoff involved for aluminum construction. Minimum weight is achieved at combinations of high disc loading and blade loading. Consideration of the maximum blade loading during transition flight limits the design blade loading to 150 psf. If one then determines that a high aspect ratio is desirable for a particular mission (say, a range-payload mission), then the indicated point would be a good solution. The disc loading value of 15 psf, although somewhat high for Army helicopters, is satisfactory for Navy shipboard use and results in a smaller diameter rotor. Figure 12b indicates that the divergence speed for this particular design is sufficient for the mission chosen.

Figures 13a and 13b indicate a similar tradeoff for a graphite composite structure with spanwise and 45-degree cross-ply construction. Significant weight savings relative to aluminum were found with a considerably reduced dependence on aspect ratio. The divergence characteristics were also markedly superior to aluminum. It is apparent from these results that although an X-Wing could be fabricated with aluminum, it is actually <u>ideally</u> suited to the high specific stiffness of composite graphite material. The graphite also possesses important advantages in natural frequency placement design for the rotating blade conditions.

5

The hub and retention system shown in *T* igure 14 also represents a new area of structural design for the X-Wing. The use of a titanium "yoke" was found preferable to a composite design (at this time) in view of the requirements for high strength, high fatigue stress, ease of fabrication and machining, and most importantly the need for a high fatigue strength joint with the steel pitch pinion shown in the figure. An additional design feature is the crossed spar layout which permits the root moments and shears to be carried efficiently across the hub, yet allows the blades to be aligned parallel for storage. Collective pitch actuation was accomplished as shown in Figure 14 by using a single spur gear and pinion design with redundant actuators and linkages.

Another new area of weight technology was the fan-in-tail installation. This was designed to comply with MIL-8501A specifications and utilized current knowledge from several industrial sources. The remaining component designs and their weight calculations were straightforward and used the detailed fixed-wing methodology of Reference 3 together with state-ofthe-art rotary wing methods. Two levels of materials technology were considered: (1) all aluminum and (2) limited use of advanced materials in structural areas which have been demonstrated in current aircraft programs and are considered practical for a 1980 prototype aircraft.

Figure 15 illustrates the overall impact of the X-Wing empty weight on traditional trends for rotary-wing VTOL's. Note that a reversal of the weight trend has been achieved by utilizing the rotor as the sole lifting system and minimizing the propulsion weight required for efficient aerodynamics.

MISSION ANALYSIS

The results of the weight and aerodynamic studies were combined with a propulsion/drive system study to provide inputs for a mission analysis. From weight and performance standpoints, the optimum propulsion arrangement appeared to be a single fan engine for thrust and dual shaft

³Ahl, W. H., Hypersonic Aerospace-Vehicle Structures Program. "Volume II -- Generalized Mass Properties Analysis," Martin-Marietta Corporation, Technical Report AFFDL-TR-68-129, Vol. II, Part I (Jan 1969).

engines for rotor drive and compressor power. The detailed mission calculation shown in Figure 16 illustrates the potential benefits of the X-Wing for such diverse applications as ASW and civilian transport. It indicates that the potential payload improvements of the X-Wing for a typical medium range mission may be greater than 100 percent compared to other rotary-wing VTOL's.

ROTOR AEROELASTICITY AND DYNAMICS

The critical aeroelastic and dynamic aspects of the design are (1) aeroelastic bending divergence in the stopped wing mode, (2) resonant amplification of blade vibratory bending stresses during rotor slowing and stopping, and (3) potential high frequency coupled instabilities of isolated blades, multiblades, and the rotor/body combination. The divergence design has been alluded to previously. In general, it is not found to impact the blade weight fraction for blade aspect ratios below approximately 13.0. The mode of divergence is dominantly a clamped root pure bending condition and, as such, is straightforward to analyze. Resonant amplification of blade airloads is a potentially serious problem for any variable RPM rotor. Although the problem was not found to be severe with an unloaded rotor (Reference 4), it will be of much greater significance for the highly loaded X-Wing. The major excitation will occur with the lower blade modes at tip speeds near maximum. For example, a stress buildup was known to occur on previous unloaded, slowed and stopped rotors when the first flatwise bending crossed the 2 per rev excitation near 60-percent RPM. This was due partially to the frequency coalescence and partially to a significant second harmonic airload content at the high advance ratio range. The solution for this problem with X-Wing has been twofold: (1) the rotor is decelerated rapidly by using a mechanical

No. A.

のないないの

⁴Fradenburgh, E. A., R. J. Murrill and E. F. Kiely, "Dynamic Model Wind Tunnel Tests of a Variable-Diameter, Telescoping-Blade Rotor System (Trac Rotor)," USAAMRDL Technical Report 73-32, U. S. Army Air Mobility Research and Development Laboratory, Ft. Eustis, Virginia (Jul 1973).

brake so that only a limited number of high fatigue cycles will occur; and (2) the first flatwise blade frequency has been placed above 2 per rev. The latter condition is quite unusual for rotor design as it implies extremely high stiffness. However, the constraint is compatible with good divergence design so that a value of approximately 2.2 per rev is obtained for composite construction without varying either mass or stiffness distributions from the values needed for the basic wing design. Figure 17 indicates the frequency characteristics of a 30,000-pound design.

The potentially high frequency instabilities are currently being analyzed for X-Wing. The design philosophy has been to use high stiffness in all modes in order to avoid strong coupling effects. However, the nature of the section design requires the elastic axis and mass center to be coincident at midchord. It thus remains to be seen whether the rotor system can be designed to be flutter free at very high speeds.

STABILITY AND CONTROL

The stability and control characteristics of X-Wing are very specialized. Traditionally coupled rotor/body low frequency dynamics during transition has constituted the most critical stability and control problems as stopped/stowed rotors. A promising solution (Figure 18) is to employ <u>four</u> blades, to transition around <u>zero</u> angle of attack and to use blowing to obtain the lift and control required. This should reduce the oscillatory rolling and pitching moments on the X-Wing very substantially even when allowing for gust effects.

SUMMARY

A new aircraft concept has been presented which employs circulation control rotor technology to achieve an efficient compromise of hover and cruise performance with only a single lifting system. The concept also offers a speed potential approaching Mach 1.0 with excellent fixed-wing maneuvering capability. A low empty weight fraction appears possible by using the efficient structure of the rotor blades. Certain potential dynamic and stability and control problems are currently being studied both analytically and experimentally. At the present time, there do not appear to be any fundamentally limiting technical problems which will prevent the timely development of this unique aircraft.















-

, ś



Figure 6 - Effect of Simultaneous Leading and Trailing Edge Blowing



Figure 7 – Rotor Aerodynamic Environment during Transition Flight ($\mu = 0.7, \alpha_s = 0, C_{T/\sigma} = 0.129$)

Figure 7a - Angle of Attack Distribution, Degrees



.

.

٠

Figure 7b - Mach Number Distribution



•

.

Figure 7c - Lift Coefficient Distribution, C_L



Figure 8 – Maximum X-Wing/Rotor Thrust Capability (w/c is slot height to chord ratio)



Figure 9 - X-Wing Aircraft Equivalent Lift-to-Drag Ratio



Figure 10 – Drag Coefficient (Based on Hub Planform Area) for Three Hubs with Shanks

(1) X-WING DESIGN POINT CONDITIONS

BLADE LOADING, DISC LOADING, GROSS WEIGHT, LOAD FACTOR ENVELOPE, DIVERGENCE SPEED, AND ALTITUDE



(4) STRUCTURAL ANALYSIS

BENDING AND SHEAR, SKIN AND WEB BUCKLING, TORSIONAL DEFLECTION, INTERNAL PRESSURE, DUCT LOSSES, FATIGUE LOADING AND STRESS, PRECONE ANGLE



(2) EXTERNAL BLADE GEOMETRY

ASPECT RATIO, TAPER RATIO, THICKNESS DISTRIBUTION, ROOT ATTACHMENT, AND HUB GEOMETRY



(5) DYNAMIC/AEROELASTIC ANALYSIS

AEROELASTIC DIVERGENCE, FLATWISE, IN-PLANE AND TORSIONAL FREQUENCY PLACEMENT, MODE SHAPES

Ω

(3) MATERIAL PROPERTIES

ALUMINUM, ADVANCED COMPOSITES, STATIC AND FATIGUE PROPERTIES



(6) WEIGHT CALCULATION

SKINS, WEBS, ROOT STRUCTURE, CARRY THRU STRUCTURE, DEAD WEIGHT ITEMS







Figure 12b -- Divergence Dynamic Pressure

Figure 12 - Aluminum Blade Construction: Effect of Design Parameters



Figure 13a - Blade Weight/Gross Weight Ratio



Figure 13b - Divergence Dynamic Pressure

Figure 13 - Graphite Composite Construction: Effect of Blade Design Parameters

, je



あったいですたと





Figure 15 - Impact of the X-Wing Design on Rotary Wing VTOL Empty Weight Trends



Figure 16 – Comparison of X-Wing Payload Capability with Other Rotary Wing VTOL Aircraft (200-nautical mile mission)





REFERENCES

1. Stone, M. B. and R. J. Englar, "Circulation Control -- A Bibliography of NSRDC Research and Selected Outside References," ASED Report 4108, Naval Ship Research and Development Center, Bethesda, Maryland (1974).

2. "Rotorcraft Parasite Drag," special report presented to the 31st Annual National Forum by the Ad Hoc Committee on Rotorcraft Drag, Washington, D.C. (May 1975).

3. Ahl, W. H., Hypersonic Aerospace-Vehicle Structures Program. "Volume II -- Generalized Mass Properties Analysis," Martin-Marietta Corporation, Technical Report AFFDL-TR-68-129, Vol II, Part I (Jan 1969).

4. Fradenburgh, E. A., R. J. Murrill and E. F. Kiely, "Dynamic Model Wind Tunnel Tests of a Variable-Diameter, Telescoping-Blade Rotor System (Trac Rotor)," USAAMRDL Technical Report 73-32, U. S. Army Air Mobility Research and Development Laboratory, Ft. Eustis, Virginia (Jul 1973).

5. Shivers, J. P., "Wind-Tunnel Investigation of Various Small-Scale Rotor/Wing Configurations for VTOL Composite Aircraft in the Cruise Mode," NASA Technical Note D-5945, Langley Research Center, Hampton, Virigina (Oct 1970).

6. Rogers, E. O., "Critical Mach Numbers of Circulation Control Airfoils as Determined by Finite-Difference Methods," ASED Technical Note AL-273, Naval Ship Research and Development Center, Bethesda, Maryland (Aug 1972).

INITIAL DISTRIBUTION

のないのないのであるので、

Copies		Copies	
1	AMC/AMCRD-FA		NAVAIRSYSCOM (Continued) 1 AIR 530B (H. Andrews)
1	ARO/Engr Sci Div S. Kumar, Asso Dir		1 AIR 530214A (R. Malatino) 1 AIR 530112 (R. Tracey) 1 AIR 530311 (F. Paglianete)
1	AASC/L1b		1 AIR 604 1 AIR PMA-247
1	AAMCA/AMXAM-SM		CDR Friichtenicht)
2	AAMRDL/Ft. Eustis 1 Lib 1 SAVRE-AM	2	NAVAIRTESTCEN 1 Dir, TPS 1 N. Jubeck
2	AAMRDL/Ames Res Cen 1 Tech Dir	12	DDC
	1 A. Kerr	1	AF Dep Chief of Staff AFRDT-EX
1	CMC/Sci Advisor A. L. Slafkosky	2	AFFDL 1 FDV, VTOL Tech Div
1	ONR/Aeronautics, Code 461		1 FDMM, Aeromech Br
2	NRL 1 Tech Info Office 1 Lib, Code 2029	1 1	AFOSR/Mechanics Div FAA, Code DS-22
1	USNA	2	V/STOL Programs
2	NAVPSCOL 1 J. Miller/Aero-Engr 1 L. Schmidt	J	1 A. Evans 1 A. Gessow 1 J. Ward (MS-85)
4	NAVAIRDEVCEN l Tech Dir l Tech Lib l R. McGiboney l G. Woods	6	NASA Ames Res Cen 1 Tech Lib 1 Full-Scale Res Div 1 M. Kelley/Lg-Scale Aero Br 1 R. T. Jones 1 J. McCloud
16	NAVAIRSYSCOM 1 AIR 03		1 J. Rabbot
	1 AIR 03PA (W. Koven) 1 AIR 03B (F. Tanczos) 1 AIR 03P CAPT von Gerichten 2 AIR 320D (R. Siewert) 4 AIR 320B (A. Somoroff) 1 AIR 5104	4	NASA Langley Res Cen 1 Tech Lib 1 R. Huston 1 L. Jenkins 1 R. Tapscott Va Polytechnic Inst/Dept Engr Mech
	I AIR JIV4	+	D.T. Mook

Copies

Copies

2	West	Va	U/Dept Aero	Engr
	1	J.	Fannuci	
	1	J.	Loth	

- 1 Analytical Methods/F. Drorak
- 1 Bell Aerospace Corp/Ft. Worth Lib
- 2 Boeing Co/Seattle 1 Tech Lib 1 P. E. Ruppert
- 2 Boeing Co/Vertol Div 1 Tech Lib 1 W. Z. Stepniewski
- 1 Fairchild-Hiller/Farmingdale 1 Republic Aviation Div
- 1 Gen Dyn/Convair Div Tech Lib
- 1 Grumman Aerospace Corp M. Siegel
- 2 Honeywell, Inc/S&R Div 1 Tech Lib 1 R. Rose
- 2 Hughes Tool Co/Culver City 1 E. Wood 1 A/C Div
- 3 Kaman Aerospace Corp 1 Tech Lib 1 D. Barnes 1 A. Lemnios
- 1 Ling-Temco-Vought, Inc/Lib
- 4 Lockheed A/C Corp/Burbank
 1 Tech Lib
 1 P. Kesling
 1 E. Martin
 1 B. R. Rich
- 1 Lockheed-Georgia Corp/Lib

- 1 McDonnell-Douglas/Long Be T. Cebeci
- 1 Northrop Corp/Hawthorne Lib
- 1 Paragon Pacific Inc. J. H. Hoffman
- 1 Piasecki Aircraft Corp
- 1 Rochester Appl Sci Asso, Inc/Lib
- 2 Teledyne Ryan Aeronautical 1 P. F. Girard 1 Lib
- 1 United A/C Corp/E. Hartford
- 3 United A/C Corp/Sikorsky l Lib l T. Carter l I. Fradenburgh
- 1 Vizex, Inc/R. A. Piziali

CENTER DISTRIBUTION

- Copies Code
 - 30 5211 Reports Distribution
 - 1 5221 Library (C)
 - 1 5222 Library (A)
 - 2 5223 Aerodynamics Library