

AD-A044 103

HARRY DIAMOND LABS ADELPHI MD  
AN ASSEMBLY-LANGUAGE DIGITAL DIVISION COMPUTER PROGRAM FOR USE --ETC(U)  
SEP 77 C R HEIMBACH  
HDL-TM-77-20


F/G 9/2

UNCLASSIFIED


NL

1 of 1  
ADAO44103

1



END  
DATE  
FILMED  
10-77  
DDC



HDL-TM-77-20

AD A044103

An Assembly-Language Digital Division  
Computer Program for Use  
in Proton-Recoil Spectroscopy

September 1977



U.S. Army Material Development  
and Readiness Command  
HARRY DIAMOND LABORATORIES  
Adelphi, Maryland 20783

AD No.

JDC FILE COPY!



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

The following is the report on the work of the committee on the subject of the "New" program which is designated by the name "New" program.

During the period of the work of the committee on the subject of the "New" program, it is reported that the committee has been working on the subject of the "New" program.

During the period of the work of the committee on the subject of the "New" program, it is reported that the committee has been working on the subject of the "New" program.



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 14 HDL-TM-77-20	2. GOVT ACCESSION NO.	3. REPORT'S CATALOG NUMBER 19
4. TITLE (and Subtitle) 6 An Assembly-Language Digital Division Computer Program for Use in Proton-Recoil Spectroscopy.	5. TYPE OF REPORT & PERIOD COVERED Technical Memorandum	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) 10 Craig R. Heimbach	8. CONTRACT OR GRANT NUMBER(s) Pron: A17R000402A1A9	9. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program: 6.21.18.A
10. PERFORMING ORGANIZATION NAME AND ADDRESS Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783	11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Materiel Development and Readiness Command Alexandria, VA 22333 11	12. REPORT DATE September 1977
13. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) 12 12p.	14. SECURITY CLASS. (of this report) Unclassified	15. NUMBER OF PAGES 16
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES HDL Project No.: X75721 DRCMS Code: 6121188750011		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Proton recoil Computer program Pulse-height division		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A computer program has been modified to circumvent the need for an analog divider for a neutron-energy spectrometer in use at the Harry Diamond Laboratories. The spectrometer is a proton-recoil system, and some division process is necessary to discriminate against gamma sensitivity of the gas proton-recoil detectors. The program is written in basic machine language for the minicomputer that controls spectrometer operation and collects and		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

163050

1/3

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

analyzes data. Coincident dual-parameter data (energies of recoiling protons and pulse rise times) are acquired by the program. The rise-time pulse-height distribution is divided by the energy distribution before storage in the computer memory. This normalization facilitates subtraction of the unwanted gamma sensitivity of the proton-recoil detectors, particularly at low neutron energies.

The elimination of the analog divider improves performance and simplifies the operation of the spectrometer.

ACCESSION for ☒ White Section  
NTIS ☐ B II Section  
DDC  
DISTRICT/STATE/INVENTORY TYPES  
A

## CONTENTS

	<u>Page</u>
1 INTRODUCTION . . . . .	5
2 METHOD OF GAMMA-RAY DISCRIMINATION . . . . .	5
3 DIFFICULTIES WITH METHOD . . . . .	6
4 METHOD OF SOLUTION . . . . .	6
5 ELECTRONIC MODIFICATIONS . . . . .	6
6 PROGRAM MODIFICATIONS . . . . .	7
6.1 Description of Program . . . . .	7
6.2 Explanation of Subroutines . . . . .	8
6.3 Use of Program . . . . .	8
6.4 Constraints on Method . . . . .	8
7 SUMMARY . . . . .	9
LITERATURE CITED . . . . .	9
DISTRIBUTION . . . . .	15
APPENDIX A.--DIGITAL DIVIDE PROGRAM . . . . .	11

## FIGURES

1 Distribution of neutron and gamma-ray pulses . . . . .	5
2 Dual-parameter data distribution . . . . .	6
3 Electronics with analog voltage division . . . . .	7
4 Electronics with digital voltage division . . . . .	7

## 1. INTRODUCTION

Harry Diamond Laboratories (HDL) is presently developing a capability for fast-neutron spectrometry. One method being pursued is the proton-recoil technique.<sup>1,2,3</sup> With this method, neutrons from a nuclear reactor penetrate a detector containing hydrogen or methane gas and collide with the protons. The protons recoil and create in the gas ion pairs that are collected by an applied electric field. The voltage pulses resulting from the collected ions are proportional to the energy of the protons. Pulse-height analysis of the voltage pulses allows the energy spectrum of the protons to be determined. The proton spectrum is then analyzed to provide the energy spectrum of the high-energy neutrons.

Any cause of ionization in the detector gas other than the protons is a source of noise. In particular, gamma rays that accompany the high-energy neutrons also ionize the gas. Voltage pulses that have gamma rays as their origin must be separated from those which are due to the neutrons.

## 2. METHOD OF GAMMA-RAY DISCRIMINATION

Usually, this separation of pulses is performed by pulse-shape discrimination. Because the protons have a greater specific ionization than Compton electrons that result from gamma interactions, they have shorter path lengths in the gas. Hence, their voltage pulses have shorter rise times than those due to the gamma rays.

Figure 1 illustrates the pulse-separation technique. Figure 1(a) shows the differences in pulse-height distributions from neutrons and gamma interactions. In figure 1(b), the separation is increased for the smaller pulse heights by use of specific ionization rather than rise time to distinguish between the neutron- and gamma-ray-induced pulses. The specific ionization is obtained by dividing the rise time of each voltage pulse by its magnitude. The resulting dual-parameter distribution is pictured in figure 2.




Figure 1. Distributions of neutron and gamma-ray pulses. Energy versus rise time (a) and energy versus specific ionization (b).

<sup>1</sup> E. F. Bennett and T. J. Yule, *Techniques and Analyses of Fast-Reactor Neutron Spectroscopy with Proton-Recoil Proportional Counters*, Argonne National Laboratory, ANL-7763 (1971).

<sup>2</sup> E. F. Bennett, *Nuclear Science Engineering*, 27(1967), 16-27.

<sup>3</sup> *Fast Neutron Physics*, V, Ch IIA, Interscience (1966).






Figure 2. Dual-parameter data distribution.

### 3. DIFFICULTIES WITH METHOD

A key element of the gamma-ray separation technique is the division of rise-time pulses by voltage pulse height. The desired division can be accomplished by either an analog or a digital divider. However, experience with an analog divider was the principal emphasis for our need to develop a digital divide technique. In order to perform the analog division correctly, the rise-time and pulse-height signals had to enter the analog voltage divider in coincidence. Because of this requirement, the analog divider was very sensitive to fluctuations in time. It was also sensitive to variation in signal size or the presence of a dc level in the input signal. The elimination of the divider eliminates these problems and greatly reduces the time necessary to place the system into operation.

### 4. METHOD OF SOLUTION

The method developed to do this division was to modify the electronics and the computer program which control data acquisition from the proton-recoil detectors. The electronic modification is relatively simple and is described first. The modification of the computer program and background information necessary to operate the program and to interpret the results are discussed in the remainder of the report.

### 5. ELECTRONIC MODIFICATIONS

Originally, the electronics that couple the proton proportional counters (the detectors for the neutron spectrometer) through the ADC's (analog-to-digital converters) to the minicomputer were arranged as shown in figure 3. The signals from the proton-recoil counters were amplified to give a total amplitude




Figure 3. Electronics with analog voltage division.

pulse in one ADC. Such pulses are proportional to the energies of the recoiling protons. Simultaneous with this energy measurement, the timing-filter amplifier differentiates and amplifies the signals to give the rate of rise. These signals (energy and rate of rise) are fed in coincidence into the Y/X analog-voltage divider to produce the input to the second ADC, which forms the specific ionization axis of the dual-parameter array.

Since the ADC's and memory units are under control of a minicomputer, it is possible to have the alternative arrangement shown in figure 4. The total amplitude (energy) signal is the same as before, but since the Y/X division is now done digitally within the minicomputer, the second ADC accepts rate-of-rise information directly.




Figure 4. Electronics with digital voltage division.

## 6. PROGRAM MODIFICATIONS

### 6.1 Description of Program

The digital divide program is listed in appendix A. It is written in assembly language<sup>4</sup> for the ND812 computer and is in the form of an overlay for the ND-1075-01, which is the dual-parameter data-acquisition program.<sup>5</sup>

<sup>4</sup> Nuclear Data Incorporated, Software Instruction Manual, BASC-12 General Assembler, Palatine, IL (1962).

<sup>5</sup> Nuclear Data Incorporated, Software Instruction Manual, ND4420 Single/Dual Parameter Monitor, Palatine, IL (1972).

The ND-1075-01 has a special subroutine which handles data coming from the ADC's. Normally, this subroutine polls the ADC's to collect X and Y input and then increments the appropriate point in memory. The digital divide modification leaves the X input unchanged, but modifies the Y input by dividing it by X. Then the appropriate point in memory is incremented. All the other routines of ND-1075-01 are unaffected, with the exception of the auto-experiment routines. These routines are changed only because the overlay had to be put somewhere in memory and the auto-experiment routines are rarely used for proton-recoil data acquisition. If one had to use these routines, the overlay would have to be moved to an unused portion of memory.

### 6.2 *Explanation of Subroutines*

The digital divide overlay consists of four subroutines: RSSAV, RSRES, NEW1, and NEW2. The subroutine RSSAV modifies the ADC handling routine to save the R and S registers so that these registers may be used by the other portions of the ND-1075-01. RSRES restores the R and S registers to whatever their original contents were before the ADC interrupt occurred. This is necessary because the R and S registers have meaning to portions of the 1075 program external to the ADC routines. Location FIRST also has to be saved and restored because the location of the patches eliminates the instruction that normally does this.

The routine NEW1 stores the results of the X-ADC for future reference. The routine NEW2 takes the results of the Y-ADC, multiplies by a scale factor FMP, divides by the X-ADC results, and then returns control to the ND-1075-01 program with the results in the K register. The ND-1075-01 uses the results in the K register as the Y input and increments the appropriate location in memory.

### 6.3 *Use of Program*

First, the ND-1075-01 program is loaded into fields 00 and 01 of the ND812 computer. A binary version of the digital divide program is overlaid on top of this in field 00 by the paper-tape loader. The multiplication factor FMP (location 7507, field 00) may be varied to move the Y/X result to the left or right on an oscilloscope display.

### 6.4 *Constraints on Method*

Precautions must be taken with digital division because of the size of the rate-of-rise pulses coming into ADC no. 2. With analog division, these pulses consisted of pulse height divided by rise time and were independent of pulse height. Therefore, the gain of the timing filter amplifier could be set to give adequate resolution at one energy and it was automatically adequate at all energies.

In the digital division arrangement, the pulses coming into ADC no. 2 are proportional to energy. One may set the timing filter amplifier to give adequate resolution in the middle of the energy range, but there are still problems at the extreme low and high ends of the energy range.

First, consider the low end of the energy range. The input to ADC no. 2 consists of small voltage pulses, which are digitized to only a few significant figures. This causes a loss of accuracy in the rise time, making the separation of gamma rays more difficult. Fortunately, sufficient accuracy may be achieved in the digital technique by increasing the resolution of ADC no. 2 from 256 divisions full scale, which was adequate with the analog division arrangement, to 4096.

Next, consider the high end of the energy range. The input pulses to ADC no. 2 grow larger with energy and may exceed the maximum signal capacity of the ADC. If this occurs, data will be lost. This data loss may be avoided by keeping the gain of the timing filter amplifier sufficiently low.

The operator must remember to set the resolution of ADC no. 2 to 4096. Since the overlay automatically interacts with the ND-1075-01, no further action on the part of the operator is necessary.

## 7. SUMMARY

An assembly-language computer program has been written which allows the electronic analog divider to be eliminated from the HDL proton-recoil spectroscopy system. This has the advantage of simplifying the electronics and greatly reducing the time necessary to set up the system. In order to use the program, the resolution of ADC no. 2 (the rise-time ADC) has to be increased to 4096 divisions and care must be taken to see that the rise-time signal does not grow beyond the capacity of ADC no. 2 before the energy signal grows beyond the capacity of its ADC.



## LITERATURE CITED

1. E. F. Bennett and T. J. Yule, Techniques and Analyses of Fast-Reactor Neutron Spectroscopy with Proton-Recoil Proportional Counters, Argonne National Laboratory, ANL-7763 (1971).
2. E. F. Bennett, Nuclear Science Engineering, 27(1967), 16-27.
3. Fast Neutron Physics, VI, Ch II A, Interscience (1966).
4. Nuclear Data Incorporated, Software Instruction Manual, BASC-12 General Assembler, Palatine, IL (1962).
5. Nuclear Data, Incorporated, Software Instruction Manual, ND4420 Single/Dual Parameter Monitor, Palatine, IL (1972).



# APPENDIX A.—DIGITAL DIVIDE PROGRAM

This digital divide program is written in assembly language<sup>1</sup> for the ND812 computer. It is in the form of an overlay for the ND-1075-01, which is the dual-parameter data-acquisition program.<sup>2</sup>

O  
V  
U

SE 5353

EXJK = 1374

FMP = 7407

NEW1 = 7400

NEW2 = 7410

NEWP = 7400

RSRES = 7440

RSSAV = 7425

RSTR = 7436

SSTR = 7437

X = 7406

ER 0000

A

A<A< A<B<\,< = < =))<=

( ),(<)<(G<

EXJK=1374

NEWP=7400

/NEWP LOCATES THE OVERLAY  
POSITION

/ THE FOLLOWING TWJMP'S ARE PATCHES INTO THE 1075 WHICH  
/ DIRECT IT TO THE DIGITAL DIVIDE ROUTINES  
/

\*0111

0111	0600	TWJMP
0112	7425	RSSAV

\*0117

0117	0600	TWJMP
0120	7440	RSRES

\*0136

0136	0600	TWJMP
0137	7400	NEW1

<sup>1</sup> Nuclear Data Incorporated, Software Instruction Manual, BASC-12 General Assembler, Palatine, IL (1962).

<sup>2</sup> Nuclear Data Incorporated, Software Instruction Manual, ND4420 Single/Dual Parameter Monitor, Palatine, IL (1972).

APPENDIX A

\*0210

0210 0600 TWJMP  
0211 7410 NEW2

\*NEWP

/ UPON ENTERING NEW1, J CONTAINS THE VALUE OF THE X ADC.  
/ THE EXJK, TWSTJ DO WHAT USED TO BE DONE BY THE 1075  
/ WHERE THE TWJMP NEW1 IS NOW LOCATED  
/

7400 5406 NEW1, STJ X  
7401 1374 EXJK  
7402 0540 TWSTJ  
7403 0175 0175  
7404 0600 TWJMP  
7405 0140 0140 /RETURN TO THE 1075

7406 0000 X, 0  
7407 0400 FMP, 0400 /NORMALIZATION FACTOR

/ NEW2 TAKES THE Y-ADC VALUE, MULTIPLIES BY THE SCALE FACTOR  
/ FMP, DIVIDES BY THE X-ADC VALUE, AND STORS THE RESULT INTO  
/ THE 1075 SO THAT THE APPROPRIATE DATA LOCATION MAY BE  
/ INCREMENTED AND DISPLAYED  
/

7410 1374 NEW2, EXJK /K=Y AFTER  
7411 0540 TWSTJ / SAVE J  
7412 0175 0175  
7413 5104 J LDJ FMP  
7414 1000 MPY /NORMALIZE Y  
7415 5107 J LDJ X  
7416 1303 EXJRKS  
7417 1001 DIV /Y/X  
7420 1374 EXJK /PUT IN K  
7421 0500 TWLDJ / RESTORE J  
7422 0175 0175  
7423 0600 TWJMP  
7424 0212 0212 /RETURN TO 1075

/ RSSAV SAVES THE CONTENTS OF THE R AND S REGISTERS  
/ SO THAT R AND S MAY BE USED IN THE DIVIDE INSTRUCTION  
/  
/ FIRST MUST BE SAVED BECAUSE THE TWJMP RSSAV IS IN THE  
/ LOCATION WHERE FIRST IS USUALLY SAVED  
/

## APPENDIX A

```

7425 5000 RSSAV, LDJ FIRST
7426 0540 TWSTJ
7427 0173 0173 /STORAGE LOCATION FOR FIRST IN ADC
7430 1302 LJKFRS INTERRUPT
7431 5405 STJ RSTR
7432 0550 TWSTK
7433 7437 SSTR
7434 0600 TWJMP
7435 0113 0113 /RETURN TO 1075

7436 0000 RSTR, 0 /STORAGE LOCATION FOR R
7437 0000 SSTR, 0 /STORAGE LOCATION FOR S

```

/ RESTORE R AND S BEFORE LEAVING ADC INTERRUPT ROUTINE

```

/
7440 5102 RSRES, LDJ RSTR
7441 0510 TWLDK
7442 7437 SSTR
7443 1301 LRSFJK
7444 1410 CLR FLAG
7445 1450 CLR 0
7446 0600 TWJMP
7447 0121 0121

```

SE 5353

```

EXJK = 1374
FMP = 7407
NEW1 = 7400
NEW2 = 7410
NEWP = 7400
RSRES = 7440
RSSAV = 7425
RSTR = 7436
SSTR = 7437
X = 7406
ER 0000

```

DISTRIBUTION

DEFENSE DOCUMENTATION CENTER  
CAMERON STATION, BUILDING 5  
ALEXANDRIA, VA 22314  
ATTN DDC-TCA (12 COPIES)

COMMANDER  
USA RSCH & STD GP (EUR)  
BOX 65  
FPO NEW YORK 09510  
ATTN LTC JAMES M. KENNEDY, JR.  
CHIEF, PHYSICS & MATH BRANCH

COMMANDER  
US ARMY MATERIEL DEVELOPMENT  
& READINESS COMMAND  
5001 EISENHOWER AVENUE  
ALEXANDRIA, VA 22333  
ATTN DRXAM-TL, HQ TECH LIBRARY  
ATTN DRCDE-A, PROGRAM SUPPORT OFC

COMMANDER  
US ARMY ARMAMENT MATERIEL  
READINESS COMMAND  
ROCK ISLAND ARSENAL  
ROCK ISLAND, IL 61201  
ATTN DRSAR-ASF, FUZE & MUNITIONS  
SPT DIV

COMMANDER  
USA MISSILE & MUNITIONS CENTER & SCHOOL  
REDSTONE ARSENAL, AL 35809  
ATTN ATSK-CTD-F

NAVAL TRAINING EQUIPMENT CENTER  
ORLANDO, FL 32813  
ATTN TECHNICAL LIBRARY

ARGONNE NATIONAL LABORATORY  
9700 SOUTH CASS AVE  
ARGONNE, IL 60439  
ATTN ENGINEERING R&D

US DEPARTMENT OF COMMERCE  
ASSISTANT SECRETARY FOR SCIENCE  
& TECHNOLOGY  
WASHINGTON, DC 20230

US DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS  
WASHINGTON, DC 20230

US ENERGY RESEARCH & DEVELOPMENT  
ADMINISTRATION  
WASHINGTON, DC 20545  
ATTN DIV OF REACTOR RES & DEV

US ENERGY RESEARCH & DEVELOPMENT  
ADMINISTRATION  
TECHNICAL INFORMATION ORGANIZATION  
P.O. BOX 62  
OAK RIDGE, TN 37830

DIRECTOR  
ARMED FORCES RADIOBIOLOGY RESEARCH  
INSTITUTE  
DEFENSE NUCLEAR AGENCY  
NATIONAL NAVAL MEDICAL CENTER  
BETHESDA, MD 20014

DIRECTOR  
DEFENSE ADVANCED RESEARCH  
PROJECTS AGENCY  
ARCHITECT BLDG  
1400 WILSON BLVD  
ARLINGTON, VA 22209  
ATTN TECH INFO OFFICE

DIRECTOR  
DEFENSE NUCLEAR AGENCY  
WASHINGTON, DC 20305  
ATTN PETER HAAS, DEP DIR,  
SCIENTIFIC TECHNOLOGY  
ATTN RADIATION DIRECTORATE

CHIEF  
LIVERMORE DIVISION,  
FIELD COMMAND, DNA  
LAWRENCE LIVERMORE LABORATORY  
P.O. BOX 808  
LIVERMORE, CA 94550  
ATTN H. KLAPPER

OFFICE, CHIEF OF RESEARCH, DEVELOPMENT  
& ACQUISITION  
DEPARTMENT OF THE ARMY  
WASHINGTON, DC 20310  
ATTN DAMA-AR, RESEARCH PROGRAMS

PROJECT MANAGER, M60 TANKS  
US ARMY MATERIEL DEV &  
READINESS COMMAND  
28150 DEQUINDRE  
WARREN, MI 48092

COMMANDER  
US ARMY NUCLEAR AGENCY  
FORT BLISS, TX 79916  
ATTN ATCN-W, WEAPONS EFFECTS DIV

COMMANDER  
WHITE SANDS MISSILE RANGE, NM 88002  
ATTN STEWS-ID, INSTRUMENTATION IDR  
ATTN STEWS-IN, INFO OFFICE



DISTRIBUTION (Cont'd)

COMMANDER  
EDGEWOOD ARSENAL  
EDGEWOOD ARSENAL, MD 21010  
ATTN SAREA-R, RES LABORATORIES

COMMANDER  
US ARMY ARMAMENT RESEARCH &  
DEVELOPMENT COMMAND  
PICATINNY ARSENAL  
DOVER, NJ 07801  
ATTN DRDAR-ND-W, WEAPONS VULNERABILITY

COMMANDER  
US ARMY ABERDEEN PROVING GROUND  
ABERDEEN PROVING GROUND, MD 21005  
ATTN STEAP-TL, TECH LIB  
ATTN STEAP-MTM, METHODOLOGY & INSTR

OFFICE OF RESEARCH, DEVELOPMENT,  
TEST & EVALUATION  
DEPT OF THE NAVY  
WASHINGTON, DC 20360  
ATTN NOP-985, NUCLEAR ENERGY DIV

DIRECTOR  
NAVAL RESEARCH LABORATORY  
WASHINGTON, DC 20375  
ATTN CODE 2620, LIBRARY  
ATTN CODE 4000, RESEARCH DEPT  
ATTN CODE 6620, RADIATION EFFECTS

COMMANDER  
AEROSPACE RESEARCH LABORATORIES  
WRIGHT-PATTERSON AFB, OH 45433

DIRECTOR  
AF OFFICE OF SCIENTIFIC RESEARCH  
1400 WILSON BLVD  
ARLINGTON, VA 22209  
ATTN DO, RES OPERATIONS

COMMANDER  
AF WEAPONS LAB, AFSC  
KIRTLAND AFB, NM 87117  
ATTN SE, NUCLEAR SYS DIV

DIRECTOR  
NASA  
GODDARD SPACE FLIGHT CENTER  
GREENBELT, MD 20771  
ATTN 250, TECH INFO DIV

HARRY DIAMOND LABORATORIES  
ATTN RAMSDEN, JOHN J., LTC, COMMANDER/  
FLYER, I.N./LANDIS, P.E./  
SOMMER, H./OSWALD, R. B.  
ATTN CARTER, W.W., DR., TECHNICAL  
DIRECTOR/MARCUS, S.M.  
ATTN DANIEL, CHARLES D., JR., MG,  
COMMANDING GENERAL (ERADCOM)  
ATTN KIMMEL, S., PAO  
ATTN CHIEF, 0021  
ATTN CHIEF, 0022  
ATTN CHIEF, LAB 100  
ATTN CHIEF, LAB 200  
ATTN CHIEF, LAB 300  
ATTN CHIEF, LAB 400  
ATTN CHIEF, LAB 500  
ATTN CHIEF, LAB 600  
ATTN CHIEF, DIV 700  
ATTN CHIEF, DIV 800  
ATTN CHIEF, LAB 900  
ATTN CHIEF, LAB 1000  
ATTN RECORD COPY, BR 041  
ATTN HDL LIBRARY (5 COPIES)  
ATTN CHAIRMAN, EDITORIAL COMMITTEE  
ATTN CHIEF, 047  
ATTN TECH REPORTS, 013  
ATTN PATENT LAW BRANCH, 071  
ATTN GIDEP OFFICE, 741  
ATTN HEIMBACH, C. R., (20 COPIES)