

AD-A056 651

DAVID W TAYLOR NAVAL SHIP RESEARCH AND DEVELOPMENT CE--ETC F/G 13/10
OPEN-WATER PERFORMANCE OF TANDEM PROPELLERS.(U)

JUN 73 C T DAVIS, R HECKER


UNCLASSIFIED

DTNSRDC/SPD-530-01

NL

| OF |

AD
A056 651



END
DATE
FILMED
9-78
DDC

SPD-530-01

AD A056651

OPEN-WATER PERFORMANCE OF TANDEM PROPELLERS

LEVEL

(6)

DAVID W. TAYLOR NAVAL SHIP
RESEARCH AND DEVELOPMENT CENTER

Bethesda, Md. 20084



(6) OPEN-WATER PERFORMANCE OF TANDEM PROPELLERS.

(9) Final rept.

BY

(10) C. T. Davis and Richard Hecker

(11) Jun 73

(12) 16p.



APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED

(16) F61412

(17) SF61412001

SHIP PERFORMANCE DEPARTMENT
DEPARTMENTAL

10 No. JDC FILE COPY

78 07 17 152


JUNE 1973
Reissued

(14) DTNSROC/SPD-530-01

389 694

JCB

MAJOR DTNSRDC ORGANIZATIONAL COMPONENTS



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER SPD-530-01	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Open-Water Performance of Tandem Propellers		5. TYPE OF REPORT & PERIOD COVERED Final
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) C. T. David and R. Hecker		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Ship Research and Development Center Bethesda, Md. 20084		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62756N, SF61 412 001 Work Unit 1528-024
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Ship Research and Development Center Bethesda, Md. 20084		12. REPORT DATE June 1973
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 11
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
15a. DECLASSIFICATION/DOWNGRADING SCHEDULE		
16. DISTRIBUTION STATEMENT (of this Report) APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Tandem propellers Propeller efficiency Thrust coefficient		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Tandem propellers, defined as two propellers coaxially mounted to the same shaft, were characterized in open water. The motivation for this work was to determine if the reduced loading per propeller would improve efficiency. Other potential gains such as reduced vibration and decreased cavitation are to be studied later. The experiments were performed at two angular positions and only one axial spacing for direct comparison to a standard		

DD FORM 1473

1 JAN 73

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

parent propeller. The performance shows that improved efficiency is obtainable with tandem propellers. The results also show that changes in performance occur with different angular positions of the propellers. Additional experiments are recommended.

ACCESSION for	
NTIS	Write Section ☒
DDC	B. H. Section ☐
UNANNOUNCED	
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	SPECIAL
A	

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

INTRODUCTION

The tandem propellers described in this report consist of two propellers operating one behind the other, on the same shaft with the same rotational speed and direction of rotation. The proper design of such propellers requires special consideration of the distance between forward and after propellers, relative angular position of the blades of the two propellers, and an accurate prediction of the interaction between the two propellers in order that the prescribed loading may be attained. Drawings of one set of tandem propellers (4148 and 4149) designed at the Naval Ship Research and Development Center (NSRDC) are shown in Figures 1 and 2.

The concept of tandem propellers is being explored in an attempt to determine if greater propeller efficiency (η_0) can be obtained (than for a single propeller) while maintaining the same thrust coefficient (K_T). Also, the possibilities exist for reducing blade cavitation by increasing the effective total blade area and/or reducing the loading on each propeller. Other advantages are potential reductions in propeller induced hull and machinery vibrations. Preliminary (unreported) experiments with propellers 4148 and 4149 showed a greater efficiency than was predicted, thus meriting further investigation into their capabilities. This report presents an open water evaluation of these propellers, and compares their performance to the parent propeller, NSRDC propeller 4118.

78 07 17 152

ADMINISTRATIVE INFORMATION

This work was sponsored by Naval Ship Research and Development Center (NSRDC), funded by IR, IED, and performed under Work Unit Number 1528-024.

PROCEDURE

Open water experiments were conducted at NSRDC on Propellers 4148 and 4149 in April 1973, utilizing Carriage I, the propeller boat, and a 100 inch-pound transmission type dynamometer for measuring propeller thrust and torque (Figure 3). The propellers were run at a speed of advance (V_A) varying from 3.0 to 12.0 ft/sec and a rotational speed (N) from 7.0 to 11.0 revolutions per second permitting operation at Reynolds numbers R_n from 4.1×10^5 to 6.7×10^5 .

Since it was probable that various angular positions of the forward blades with respect to the aft blades would have an effect on the performance of the unit, the propellers were tested at two blade settings: the design setting (Setting 4), where the blades of the aft propellers were centered between those of the forward propeller (Figure 4), and Setting 1, where the blades of the two propellers were in line with each other (Figure 5).

RESULTS

The comparison of the open water curves for Tandem Propellers 4148 and 4149 and parent Propeller 4118 are shown in Figure 6. Tabulated open water data for the tandem propellers at both blade settings are presented in Table 1. Both the tandem propellers and the parent propeller were

designed for uniform inflow for a K_T near 0.15 at a speed coefficient, J , of 0.833. It can be seen from the performance characteristics shown in Table 2 that at the design angular spacing, the tandem propellers produced a higher thrust and torque than designed for but percentage wise were as near design as was the parent propeller. Overall, a peak efficiency of 75 percent is observed at a J of 0.94 for setting 1 (tandem) and an efficiency of .737 at a J of 0.91 for setting 4 (tandem) while the peak efficiency of propeller 4118 was 72 percent at a $J = 0.94$.

CONCLUSIONS AND RECOMMENDATIONS

Based on the design performance characteristics the tandem propellers appear to be a suitable substitute for the parent propeller. Further studies are recommended for tandem propellers to determine which aspects of the design of such propellers, such as relative angular and axial position of the individual propellers, have the greatest affect on the overall performance characteristics of the unit. Also, since one of the potential gains of tandem propellers is to reduce cavitation, cavitation tests for the existing propellers should be performed and compared with cavitation tests of the parent propeller.

SETTING 1

SETTING 4 (DESIGN)

J	K _T	10K _Q	η _O	J	K _T	10K _Q	η _O
.050	.451	.632	.057	.050	.468	.702	.053
.100	.434	.618	.112	.100	.454	.6	.106
.150	.417	.603	.165	.150	.438	.6	.157
.200	.401	.588	.217	.200	.422	.64	.208
.250	.384	.572	.267	.250	.404	.622	.259
.300	.368	.555	.316	.300	.386	.599	.308
.350	.351	.538	.363	.350	.367	.574	.356
.400	.334	.520	.409	.400	.347	.548	.404
.450	.316	.501	.453	.450	.327	.521	.449
.500	.299	.480	.495	.500	.305	.492	.494
.550	.281	.458	.536	.550	.284	.463	.536
.600	.262	.435	.575	.600	.262	.433	.577
.650	.243	.410	.612	.650	.239	.402	.615
.700	.223	.384	.646	.700	.216	.370	.650
.750	.202	.355	.678	.750	.193	.337	.682
.800	.180	.325	.706	.800	.169	.304	.708
.850	.158	.293	.729	.850	.145	.270	.727
.900	.134	.258	.744	.900	.121	.236	.737
.950	.110	.222	.749	.950	.097	.201	.733
1.000	.084	.183	.733	1.000	.073	.165	.706
1.050	.057	.141	.679	1.050	.049	.130	.637
1.100	.029	.097	.528	1.100	.026	.094	.480
1.150	0.000	.050	0.000	1.150	.002	.058	.068
				1.155	0.000	.054	0.000

Table 1 - Paired Values of Open Water Data for
Two Settings of Propellers 4148-49

Propeller Number	Coefficient	Design	Open Water	Pct. Difference
<u>4118</u>	J	0.833	0.833	0
	K_T	0.154	0.150	-3
	$10K_Q$	0.290	0.285	-2
	η_o	0.706	0.698	-1
<u>4148-49</u> Setting 1	J		0.833	
	K_T		0.166	
	$10K_Q$		0.305	
	η_o		0.723	
<u>4148-49</u> Setting 4	J	0.833	0.833	0
	K_T	0.150	0.154	+3
	$10K_Q$	0.275	0.281	+2
	η_o	0.723	0.722	0

Table 2 - Open Water Performance at
Design Advance Speed



Figure 1 - Drawing of Propeller 4148 (Fwd)




Figure 2 - Drawing of Propeller 4149 (Aft)




Figure 3 - Test Rig for Open Water Experiments





Figure 4 - Photographs of Propellers 4148-49 at
Setting 4 (Design Setting)





Figure 5 - Photographs of Propellers 4148-49 at
Setting 1




Figure 6 - Open Water Characteristics for Propellers 4148-49 and 4118

DTNSRDC ISSUES THREE TYPES OF REPORTS

1. DTNSRDC REPORTS, A FORMAL SERIES, CONTAIN INFORMATION OF PERMANENT TECHNICAL VALUE. THEY CARRY A CONSECUTIVE NUMERICAL IDENTIFICATION REGARDLESS OF THEIR CLASSIFICATION OR THE ORIGINATING DEPARTMENT.

2. DEPARTMENTAL REPORTS, A SEMIFORMAL SERIES, CONTAIN INFORMATION OF A PRELIMINARY, TEMPORARY, OR PROPRIETARY NATURE OR OF LIMITED INTEREST OR SIGNIFICANCE. THEY CARRY A DEPARTMENTAL ALPHANUMERICAL IDENTIFICATION.

3. TECHNICAL MEMORANDA, AN INFORMAL SERIES, CONTAIN TECHNICAL DOCUMENTATION OF LIMITED USE AND INTEREST. THEY ARE PRIMARILY WORKING PAPERS INTENDED FOR INTERNAL USE. THEY CARRY AN IDENTIFYING NUMBER WHICH INDICATES THEIR TYPE AND THE NUMERICAL CODE OF THE ORIGINATING DEPARTMENT. ANY DISTRIBUTION OUTSIDE DTNSRDC MUST BE APPROVED BY THE HEAD OF THE ORIGINATING DEPARTMENT ON A CASE-BY-CASE BASIS.

IED
78