



NOTICE

••••

.

.

.

The United States Government does not endorse products or manufacturers. Trade or manufacturer's names appear herein solely because they are considered essential to the object of this report.

. Report No.	2. Government Accession No.	J. Recipient - cerere				
FAA-RD-78-135						
Title and Subtitle	1	5. Report Date				
		December 1978				
POOL FIRE RADIATION THR AIRCRAF	OUGH A DOOR IN A SIMULATED T FUSELAGE	6. Performing Organization Code				
		8. Performing Organization Report No.				
. Author(s) Thor T	Fklund	FAA_NA_79_39				
	- EKIUNG	FAA-NA-78-38				
Federal Aviation Adminis	tration	IU. Work Unit No. (IRAIS)				
National Aviation Facili	ties Experimental Center	11. Contract or Grant No.				
Atlantic City, New Jerse	181-521-000					
2 Carrow 1 - A		13. Type of Report and Period Covered				
2. Sponsoring Agency Name and Address U.S. Department of Trans Federal Aviation Adminis	August 1977-December 19					
Systems Research and Dev Washington, D.C. 20590	elopment Service	14. Sponsoring Agency Code ARD-520				
This study evaluates sma adjacent to fuselage ope down and their radiant h ducts of 1-, 2-, 3-, and tions to radiative trans mental heat fluxes at tw that the doorway can be Fahrenheit (97), and tha calculated. A compariso	all-scale methods of simulat in doors. Pool fires in a que transfer through fuselag 4-foot diameter were employ for equations were developed to locations within each mode treated as a radiating black theat fluxes to other areas on of heat flux to the model	ing postcrash fuel spill finities ge doorways evaluated. Ster yed as models. Analytic so d and matched with the expec- el. The analysis demonstratic body surface of 1,874 deg s around the doorway can be exterior was compared with				
This study evaluates sma adjacent to fuselage ope down and their radiant h ducts of 1-, 2-, 3-, and tions to radiative trans mental heat fluxes at tw that the doorway can be Fahrenheit (97), and tha calculated. A compariso existing full-scale fire	all-scale methods of simulation of a simulation of the second sec	ing postcrash fuel spill fr uiescent environment were s ge doorways evaluated. Ste yed as models. Analytic so d and matched with the expe el. The analysis demonstra c body surface of 1,874 deg s around the doorway can be exterior was compared with				
This study evaluates sma adjacent to fuselage ope down and their radiant h ducts of 1-, 2-, 3-, and tions to radiative trans mental heat fluxes at tw that the doorway can be Fahrenheit (9F), and tha calculated. A compariso existing full-scale fire visting full-scale fire Radiation Scaling Fuel Fire Cabin Fire Aircraft	Ill-scale methods of simulation doors. Pool fires in a queat transfer through fuselage 4-foot diameter were employ for equations were developed to locations within each mode treated as a radiating black theat fluxes to other areas on of heat flux to the model test data. Ill. Distribution Sterman Document is through the Service, Sprend Ser	ing postcrash fuel spill fri diescent environment were a ge doorways evaluated. Ste yed as models. Analytic so d and matched with the expe el. The analysis demonstra c body surface of 1,874 deg s around the doorway can be exterior was compared with exterior was compared with available to the U.S. publ National Technical Informa- ingfield, Virginia 22161				
This study evaluates sma adjacent to fuselage ope down and their radiant h ducts of 1-, 2-, 3-, and tions to radiative trans mental heat fluxes at tw that the doorway can be Fahrenheit (OF), and tha calculated. A compariso existing full-scale fire visting full-scale fire Radiation Scaling Fuel Fire Cabin Fire Aircraft 9. Security Clease (of this report)	11-scale methods of simulation doors. Pool fires in a queat transfer through fuselage 4-foot diameter were employ of fer equations within each mode treated as a radiating black theat fluxes to other areas on of heat flux to the model test data. 18. Distribution Stere Document is through the Service, Spr 20. Security Clessif. (of this page)	ing postcrash fuel spill finitescent environment were as ge doorways evaluated. Ster yed as models. Analytic so d and matched with the expe- el. The analysis demonstration to body surface of 1,874 deg s around the doorway can be exterior was compared with exterior was compared with waterior was compared with National Technical Information ingfield, Virginia 22161				
This study evaluates sma adjacent to fuselage ope down and their radiant h ducts of 1-, 2-, 3-, and tions to radiative trans mental heat fluxes at tw that the doorway can be Fahrenheit (97), and tha calculated. A compariso existing full-scale fire wisting full-scale fire adiation Scaling Fuel Fire Cabin Fire Aircraft 9. Security Classif. (of this report)	11-scale methods of simulation doors. Pool fires in a queat transfer through fuselage 4-foot diameter were employ for equations were developed to locations within each mode treated as a radiating black theat fluxes to other areas on of heat flux to the model test data. 18. Distribution Step 20. Security Clessif. (of this pege)	tement available to the U.S. publ National Technical Informa ingfield, Virginia 22161				

METRIC CONVERSION FACTORS

•	11231	333	8.2	= K + 85 B	*	
1.	inches inches fec vards niles			fluid cunces prints quarts quarts quality cubic yands	Fahranhoit Tamparatura	••••••••••••••••••••••••••••••••••••••
risions from Motr Multiply by LENGTH		1211		0.0 21 20 20 20 20 20 20 20 20 20 20 20 20 20	3/5 (Sheen add 32)	96.6 96.6 20 37 40 37
Approximate Conv Mon Yu Kan	millimeters continuess anters meters tribuness	equare continuents equare continuents equare biformers percents (10,000 m ²			Celsius temperature	20
ļ	115	נרר	.1.	177	°	<u><u>+</u> <u>+</u> <u>+</u> <u>+</u> <u>+</u> <u>+</u> <u>+</u> <u>+</u> <u>+</u> <u>+</u></u>
.1.1.1.1.1.1.1.1 ''''''''''''''''''''''					1.1.1.1.1.1.1 Manpanpanja	
1	17 5 5 e 5	1. 1. Jan Ja	• • • • •	b b	، ۲. ۴	1 inches
		i :				ā
!	continues continues continues non tiones		ıłı		cubic meters Calsius	lemperature bies, see NBS Misc. Pu
!	LENGTH 		ASS (wujukt) 24 0.44 Unterne 0.5 Unterne	s s s s s s s s s s s s s s	0.76 cubic merers EAATURE (exact) 5/9 (after Calsius	subfracting britanceure 20 30 30 30 30 30 40 40 40 40 40 40 56 40 56 40 56 40 56 40 56 50 56 50 50 50 50 50 50 50 50 50 50 50 50 50
	LENGTH LENGTH	ALL	Index (meight) Index	terrene e e e e e e e e e e e e e e e e e	cubic yards 0.76 cubic meters TEMPERATURE (exaet) Edimentatic 5/9 (exaet) Calisius	temperature subtracting temperature 32) 14). For other exact conversions and more detailed tables, see NBS Misc. Pu Nessures, Price 92.25, SD Catalog No. C13.10286.

0 . : .

> • .

٠

.

PREFACE

•

•

The assistance of Messrs. Louis J. Brown, William E. Neese, and Joseph A. Wright in the varying activities of instrumentation, testing, and data analysis is acknowledged.

MCESSION	for	
NTIS DDC UNANNOUN JUSTIFICATI	White 6 Buff 64 CED CN	iactical ER Instica C2
	m/AYMLABU	IT CODES
Dist. Al	ALL and	T SPECIFIC
A		5 12

TABLE OF CONTENTS

2

.

•

L.

			Pa	ige	
INT	TRODUCTION			1	
	Purpose Background			1	
	Experimental Objective	tanana in the for birt		2	
DIS	CUSSION			2	
	Test Configuration Test Development			2	
	Test Data			5	
RES	ULTS		i.	8	
CON	CLUSIONS			8	
REF	ERENCES		01	9	
APP	ENDIX				
		Con-Fort Bact Teat			
	2. Eost Suit				
					·* .
	•				
					-
			•		
			- American State (18 - Sa		
		V			and the second

LIST OF ILLUSTRATIONS

Figure		Page
1	Four-Foot Pan Fire	10
2	Overall Test Configuration	11
3	End View of Duct and Pan Configuration	12
4	Sensors in 4-Foot Duct	13
5	Sensors in 3-Foot Duct	14
6	Sensors in 2-Foot Duct	15
7	Sensors in 1-Foot Duct	16
8	Undamped Oscillograph Traces	17
9	Damped Oscillograph Traces	18
10	Four-Foot Duct Test	19
11	Three-Foot Duct Test	20
12	Two-Foot Duct Test	21
13	One-Foot Duct Test	22
14	Fire Separated from Duct	23
15	Interior View of Fire	24
16	Calorimeters Imbedded in Skin of 2-Foot Duct	25
17	External Heat Fluxes and Locations	26

vi

LIST OF TABLES

1

Table		Page
1	Interior Heat Flux with Fire Adjacent to Fuselage	4
2	Interior Heat Flux with Fire Separated from Fuselage	6
3	Heat Flux to Fuselage Skin	7

1

vii

INTRODUCTION

PURPOSE.

The purpose of this program is to evaluate small-scale cabin fire tests as a means for more economical but suitably realistic aircraft fire testing. The report describes the experimental results of heat transfer through the doors of simulated fuselages subjected to external pool fires in a quiescent atmosphere. A mathematical procedure is developed which allows calculation of radiant heat fluxes to the cabin interior on a point-by-point basis.

BACKGROUND.

In the event of a postcrash aircraft fire, survival of the passengers may depend on the environment of the cabin interior during the time interval required for evacuation. Because of the large quantities of aviation kerosene carried aboard commercial jets and its potential for release and ignition during a crash, the effect of external fuel fires on the fuselage and its interior must be defined if cabin safety improvements are to be realistically evaluated. Past full-scale tests on a narrow body fuselage subjected to pool fires (reference 1) showed that aluminum panels on the aircraft skin melted within 40 seconds. The thicker aluminum skins and insulation of widebody jets may yield additional time before the fuselage fails to provide protection to cabin occupants.

Prior to thermal failure of the fuselage, an external fuel fire threatens the cabin interior through its effect on any openings--fuselage breaks, opened doors, or melted windows. Any fire penetration or radiative flux provides a potential for fire involvement with interior materials before the fuselage itself would fail through melting. Because of the potential of these interior materials to yield heat, smoke, and toxic gases, such material involvement might jeopardize the passengers prior to thermal failure of the fuselage.

Full-scale tests of the effect of pool fires on the fuselage have examined the heat flux to the aircraft skin under varying wind conditions (references 1, 2, 3). Although the data varies considerably with fire placement and wind conditions, these tests provide a realistic spectrum of heat transfer values that can be expected in postcrash fire. Heat transfer values as high as 13 British thermal units per foot squared second $(Btu/ft^2 s)$ were documented in one set of tests (reference 1), 16 $Btu/ft^2 s$ in another (reference 2), and 18 $Btu/ft^2 s$ in tests on a titanium fuselage (reference 3). These are upper extremes; the measured fluxes are typically between 1 and 8 $Btu/ft^2 s$. The average flux from reference 3 was 12 $Btu/ft^2 s$. Wind conditions are the dominant cause of this variability.

The characterization of a free standing pool fire has been the subject of exhaustive investigation (references 4, 5, 6, 7, 8, 9, 10). This is due to the hazard associated with pool fires in the oil industry as well as from spills from transport vehicles. Extensive data exist on heat fluxes from

these pool fires (references 8, 9, 10), and a number of predictive techniques for the heat flux have been developed (references 11, 12). A number of conclusions from these studies have a bearing on small-scale aircraft fire tests. First, the pool fire becomes fully turbulent at about 3-feet in diameter. Also, the flame becomes optically thick at a pool diameter between 3 and 10 feet. For test purposes, a 3-foot fire can be considered optically thick. The existing data indicate that the pool fires can be scaled down to 3 feet but still maintain the radiative characteristics of large fires. This scalability of the pool fire suggests that radiative exposure of material and structures to large fires could be adequately tested with relatively small pool fires. Furthermore, for radiative exposure, a 1-foot diameter fuselage adjacent to a 4-foot fire, shown in figure 1, is considered equivalent to a 20-foot fuselage adjacent to an 80-foot fire. Varying the fire size could be simulated by changing the fuselage size and maintaining a constant fire size.

This type reasoning can be applied to measure radiative flux through a fuselage opening in a quiescent atmosphere. In a wind environment, additional scaling factors may be required since the tilt angle of a flame in a constant wind is a function of fire size (reference 13).

The development of a methodology for scaling the interaction of a fuselage with a pool fire has several applications. First, small-scale testing provides a means for economically developing a broad data base to support fullscale tests. Second, small-scale testing offers a promising method for evaluating cabin interior materials as to their ignitability when subjected to a highly realistic radiative source. Pool fires show time-dependent fluctuations in their radiative output even when their time-averaged flux is repeatable. This type fluctuation is not easily reproduced by radiant heaters in laboratory-type material flammability tests.

EXPERIMENTAL OBJECTIVE.

The experimental objective of these quiescent pool fire tests was: (1) to quantify the radiative heat transfer from a pool fire through a fuselage opening, (2) to determine the repeatability of the test, and (3) to develop the methodology for conducting such tests. The testing involved different combinations of fuselage diameter, pool fire size, and distance between fuselage and fire.

DISCUSSION

TEST CONFIGURATION.

Figure 2 shows an overall view of the test configuration. The tests were performed in a warehouse-type building which is 102-foot long and 39-foot wide. The side walls are 20-foot high, and the roof has a 26-foot peak running the length of the building. The fires were set under the peak and 20 feet from the front of the building. Each test article was a 10-foot long open-ended duct simulating a fuselage. Each duct interior was insulated with Kaowool, a noncombustible ceramic fibrous insulation, to prevent any reradiation from the wall to the sensors inside. All radiative flux would, therefore, enter through a simulated cabin door. The door was sized to geometrical scale with the door of the C-133 fuselage used concurrently for full-scale fire tests (reference 14). Figure 3 shows the end view of the duct and pan configuration and the dimensions of the four ducts used, along with significant measurements of fire placement and sensor location. The fuel pans were all placed in a larger water pan to prevent warping of the fuel pan during the fire. Kaowool insulation was placed between the duct and pans to prevent air from flowing upwards at this juncture. The fire was ignited by an electric spark and extinguished by two remotely actuated nozzles connected to a Cardor system.

The primary sensors were calorimeters within the doorway and radiometers set around the fire pan. The data were recorded on a Honeywell model 1858 cathode ray tube (CRT) Visicorder. Figures 4, 5, 6, and 7 show the placement of the calorimeters and radiometers in the doorway. The calorimeters are Hy-Cal model C-1300A, and the radiometers are Hy-Cal model R-8015C with calcium fluoride windows. Figure 4 shows the interior of the 4-foot duct with the radiometer riding piggyback on the calorimeter. They are both supported on a traversing mechanism which allows horizontal and vertical motion along the midplane of the ducts. Also visible is a calorimeter mounted in an upwardfacing configuration midway between the traversing calorimeter and the door edge. This calorimeter senses the heat flux that flooring materials might undergo from an external fire at the doorway. Figures 5, 6, and 7 show the same calorimeters and radiometers as placed in the doorways of the 3-, 2-, and 1-foot diameter ducts, respectively. In these cases, the heat sensors are rigidly held, and the horizontally facing sensors are located at the duct midplane.

TEST DEVELOPMENT.

Numerous preliminary tests were performed with the 4-foot diameter duct. Figure 8 shows a data trace of radiometer output from an early test. For ease of data reduction, the fluctuations were electrically damped by addition of a 50-microfarad capacitor to each calorimeter and radiometer amplifier. A damped oscillograph trace is shown and labeled in figure 9. The tests were generally limited to a 60-second duration to prevent overheating of the building roof structure. The 20-second buildup time on the calorimeters was typical. A steady-state heat flux would remain until the end of the test when the action of the carbon dioxide (CO₂) extinguishers would momentarily increase the heat transfer to the calorimeters.

With the 4-foot duct, the 3-foot-square fuel pan was not representative of door exposure to a large fuel fire. The fire flattened itself against the duct with some loss in radiative thickness. In addition, random bending of the fire would uncover the door. The consistency of the data was significantly improved by use of a 4-foot-square fuel pan, and test repeatability was markedly improved and heat flux values increased as the fuselage was reduced in diameter. This indicates that the sideways bending of the flame is still a problem with the 4-foot duct. With smaller ducts, the duct door faced low TABLE 1. INTERIOR HEAT FLUX WITH FIRE ADJACENT TO FUSELAGE

<u>c2/c1</u>	1.3	0 4 6 . 7 4 6 .	4°7 1,33 4,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00	1.3	115	4°1 1,3 4°2 1,3 1,3 1,3 1,4 1,4 1,4 1,4 1,4 1,4 1,4 1,4 1,4 1,4	0 4 0 V	1.3 1.3	• •		
Floor Cal (C ₂) (Btu/ft ² s)	4.9.0	2.3	2.2.2 2.4.4 2.4.4	2.2	2.7	2.2	2.3	0.1 9.0 1.8	11	11	
Midplane Cal (C1) (Btu/ft ² s)	1.8 1.8 2.1	1.7	1.8 1.8 0 10	1.7	1.8	11-1 1-8 1-1 1-8 1-1 1-0	212 212	1.5 1.6	1.5	1.4 1.3	1.8
Duct Diameter (ft)		- 9 9 9	N N N C		100	N W W S	044.	4 4 4	.44	444	14
Date/Run	12/22/6 7	12/15/1 2 2	12/16/1 2 2	1/17/21	12/29/1	3 12/23/12 13	10/28/4 11/9/5	1/11/11	11/29/1* 2*	3* 4*	*2 5*

4

* In these tests, the fuselage door faced a fire pan 5.5 feet long (distance perpendicular to fuselage) and 4.5 feet wide. In the rest of the tests the fire pan was 4 feet by 4 feet.

.....

......

1

)

- No data collected.

. .

enough into the fire to be unaffected by the flame bending. Figures 10, 11, 12, and 13 show examples of the fire geometry from the 4-, 3-, 2-, and 1-foot diameter ducts, respectively. Tests were also conducted with the fires offset from the fuselage as shown in figure 14.

Trial and error tests were performed to find the fuel quantity required for consistent fire radiative energy. Fuel quantities were incrementally increased until no additional radiative output was noted. In the 4-foot pan fires, 4 gallons of JP-4 were found to be an adequate fuel quantity. In a given sequence of tests, fuel was replenished after each 1-minute fire so that a minimum of 4 gallons was present at the start of each test. Although some distillation did occur during a test and although different fuel cuts could result in somewhat different radiative output (reference 4), this effect was not considered a serious problem for these tests.

Placement of the pool fire directly under the building peak was essential because any offset from the building center resulted in bending of the fire towards the building peak.

No fire penetration through the door into the duct was noted in these tests. Because the ducts were open ended, air could presumably feed the fire by passing through the duct out of the door and into the fire. A typical view of the fire from inside the duct is shown in figure 15a. Figure 15b shows a flame pulse over the doorway. This phenomenon was evidenced as a periodic pulsing of fire at the upper end of the door.

Since fire radiation through doorways was not studied during prior full-scale testing nearly so extensively as fuselage burn-through, some limited measurements of heat flux to the skin of the 2-foot duct were made. The two calimeters are shown in figure 16.

TEST DATA.

The primary information from these tests is the calorimeter data at the fuselage midplane and on the cabin floor. This data show the heat fluxes that cabin interior materials might experience from pool fire radiation through an open doorway. Table 1 provides the data points from tests with ducts of 1-, 2-, 3-, and 4-foot diameters adjacent to a 4-foot pool fire. From the data it is clear that the test repeatability is better with the smaller ducts as the heat flux approaches a value of 1.8 Btu/ft^2 s at the fuselage midplane and 2.5 Btu/ft^2 s on the floor. The variability in the data for the 4-foot duct in part arises from the bending of the fire enough to uncover the door. The differences in fluxes may also be partly due to the fact that the doors on the smaller ducts look into relatively lower portions of the fire.

Table 2 shows calorimeter data for 4-foot-square pool fires separated from the fuselage. Included in this table is data for different sized ducts. In table 1 when the 4-foot diameter duct was employed, the peak calorimeter readings were taken approximately 40 seconds into the test. The traversing mechanism was started 20 seconds into the test and reached the middle of the door at approximately 40 seconds into the test. In data for 1-, 2-, and 3-foot

diameter ducts, reported in table 1, the peak sensor value between 25 and 35 seconds after ignition was used. In cases of pans adjacent to ducts, this was generally a satisfactory procedure. However, in tests with the fuel pan offset from the duct, the recorded fluxes on the calorimeters continued to rise slightly through the 25- to 35-second period. The peak flux generally occurred between 40 and 45 seconds into the test and could rise as much as 30 percent higher than the values shown in table 2. However, values were taken within the 25- to 35-second interval for comparison with results shown in table 1. Although the sensed heat flux of both interior calorimeters dropped as the fire is moved away from the duct, the calorimeter on the floor showed the most dramatic reduction. The reason for this is that while the midplane calorimeter still senses fire over most of the doorway, the floor calorimeter "sees" vertically through the opening to regions where no fire is visible.

Date/ Run	Duct Diameter (ft)	Distance Between Duct and Fire Pan (ft)	Midplane Calorimeter <u>(Btu/ft²s)</u>	Floor Calorimeter (Btu/ft ² s)
12/22/9	1	2	1.3	.7
10	1.1	2	1.2	.5
11	1	2	1.3	.8
12/21/3	2	2	1.1	.7
4	2	2	1.2	.8
5	2	2	1.1	.7
12/23/15	3	2	.8	.3
16	3	2	1.0	.4
17	3	2	.9	.3
10/28/1	4	ad not were 4 this sent	.5	.3
2	4	ber det de 4 monte entre	Tanka 2.5 0 2.911	.2
3	4	2	.8	.6

TABLE 2. INTERIOR HEAT FLUX WITH FIRE SEPARATED FROM FUSELAGE

The appendix shows the development of the equations for predicting the heat flux to the internal calorimeters from an external pool fire. This development involves the solution of the view factor integral equations and the selection of appropriate fire temperatures and emissivities. The ratio of the heat flux to the floor calorimeter to the flux to the midplane calorimeter is simply the ratio of their shape factors to the fuselage door. This number is calculated to be 1.35 and agrees remarkably well with the ratios shown in table 1. Assuming an emissivity of 1, the appendix shows an average fire **temperature** of 1,874 degrees Fahrenheit (^oF) will produce a heat flux of 1.8 Btu/ft² s at the midplane calorimeter. This temperature is consistent

with values reported throughout the literature on the subject. With the equations for the shape factors developed in the appendix and with the temperature of 1,874° F used in the radiative equation, the heat flux to the interior surfaces around the doorway can be calculated. These shape factor equations are useful in mathematical cabin fire modeling and doorway fire hardening design.

Figure 17 shows a plan view of the test layout and some data from the radiometers external to the fire. In general, the external radiometer data appeared less repeatable than the data from the calorimeters within the fuselage model. In some cases the external radiometer heat fluxes leveled off in 20 to 30 seconds. In other tests the heat flux would monatonically increase throughout the test. In figure 17, external radiometer data are tabulated along with the midplane calorimeter data as a function of time for two tests run with identical fire size, duct size, and test configuration. In this figure, radiometer number 4 is 4 feet horizontally from the fire pan edge directly across from the fuselage door. Radiometer number 5 is located to the right of the fuel pan when the door is viewed across the fuel pan. Radiometer number 5 is 6 feet horizontally away from the pan edge. Both radiometer 4 and 5 are centered with respect to the fuel pan, and both are at a vertical height of 2 feet with respect to the top of the fuel pan edge. Both tests from figure 17 are included in the table 1 listing of cases with the fire adjacent to the duct.

Table 3 shows the data from the skin calorimeters on the 2-foot duct. Their values agree very closely with the average values in reference 3. Reference 3 gives data from a 20-foot fire in a 0 to 3 mile per hour (mph) wind. A fire of this size shows little bending at such low windspeeds. Consequently, this fire provides an excellent comparison to the small-scale fires. The close agreement of the measured skin heat fluxes between the 2-foot duct and the titanium fuselage lends credibility to the small-scale tests. It should be noted that the fire width to fuselage diameter ratio was approximately 2 for both the titanium fuselage test and the 2-foot model tests with skin calorimeters.

TABLE 3. HEAT FLUX TO FUSELAGE SKIN

Date/Run	Calorimeter Above Door (Btu/ft ² s)	Calorimeter Next to Door (Btu/ft ² s)
12/29/1	12	13
2	12	14
3	12	14

RESULTS

The experimental results of tests with fuselage models subjected to pool fire radiation through doorways can be summarized in four quantitative statements.

1. The heat flux to the midplane of the fuselage is 1.8 Btu/ft^2 s.

2. The heat flux to the floor one quarter of the way across the fuselage is $2.5 \text{ Btu/ft}^2 \text{ s.}$

3. The heat flux to the skin of the fuselage around the doorway is between 12 and 14 Btu/ft^2 s on a 2-foot duct exposed to a 4-foot-square fire.

4. An analytical method for calculation of radiant heat through an open door to the cabin interior from an external fuel fire was developed and matched to the experimental data.

CONCLUSIONS

1. Small-scale test procedures for measuring a radiative flux through openings of simulated fuselages are feasible and lead to several additional conclusions.

2. A 4-foot pan fire provides a highly repeatable radiation source for 1-, 2-, and 3-foot diameter fuselages.

3. Scaled tests of pool fire effects on fuselages in a quiescent atmosphere require control of fuel depth and pan size to achieve repeatable tests. Fire plume instability, as evidenced in bending, results in a less controllable source of data variability.

4. As the pool fire is displaced from the fuselage, the midplane radiation in the cabin becomes larger than radiation to the floor calorimeter; the opposite is true when the pool fire is adjacent to the fuselage opening.

5. The heat flux to surfaces around the doorway within the fuselage can be calculated if the door surface is considered to be a black body radiator at a temperature of 1.874° F.

6. The method developed for calculating heat flux on the cabin interior from an external pool fire should be further validated by full-scale tests.

REFERENCES

1. Geyer, G.B., <u>Effect of Ground Crash Fire on Aircraft Fuselage Integrity</u>, Federal Aviation Administration, Report No. FAA-RD-69-46, 1969.

2. Conley, D.W., <u>Post-Crash Fire-Fighting Studies on Transport Category</u> <u>Aircraft</u>, Federal Aviation Administration, Report No. FAA-RD-65-50, 1965.

3. Sarkos, C.P., <u>Titanium Fuselage Environmental Conditions in Post-Crash</u> Fires, Federal Aviation Administration, Report No. FAA-RD-71-3, 1971.

4. Fu, T.T., <u>Aviation Fuel Fire Behavior Study</u>, Department of Defense, Aircraft Fire Suppression and Rescue Systems Office, Report No. AGFSRS-72-2, 1972.

5. Fu, T.T., <u>Heat Radiation From Fires of Aviation Fuels</u>, Fire Technology, <u>10</u>, 54, 1974.

6. Hagglund, B., <u>The Heat Radiation from Petroleum Fires</u>, FoU-brand, <u>1</u>, 18, 1977.

7. Gordon, W. and McMillan, R.D., <u>Temperature Distribution Within Aircraft-</u> <u>Fuel Fires</u>, Fire Technology, <u>1</u>, 52, 1965.

8. Graves, K.W., <u>Fire Fighter's Exposure Study</u>, Department of Defense, Aircraft Fire Suppression and Rescue Systems Office, Report No. AGFSRS-71-2, 1970.

9. Alger, R.S. and Capener, E.L., <u>Aircraft Ground Fire Suppression and</u> <u>Rescue Systems</u>, Tri-Service System Program Office for Aircraft Ground Fire Suppression and Rescue, Report No. AGFSRS-72-1, 1972.

10. Capener, E.L. and Alger, R.S., <u>Characterization and Suppression of</u> <u>Aircraft Fuel Fires</u>, Western States Fall Meeting of the Combustion Institute, Paper WSCI-72-26, 1972.

11. Modak, A.T., <u>Thermal Radiation from Pool Fires</u>, Combustion and Flame, <u>29</u>, 177, 1977.

12. Atallah, S. and Allan, D.S., <u>Safe Separation Distances from Liquid Fuel</u> Fires, Fire Technology, 7, 47, 1971.

13. Pipkin, O.A. and Sliepcevich, C.M., Effect of Wind on Buoyant Diffusion Flames, I&EC Fundamentals, 3, 147, 1964.

14. Sarkos, C.P. and Hill, R.G., <u>Preliminary Wide Body (Cl33) Cabin Hazard</u> <u>Measurements During a Postcrash Fuel Fire</u>, Federal Aviation Administration, National Aviation Facilities Experimental Center, Report NA-78-28-LR, 1978.

15. Sparrow, E.M. and Cess, R.D., <u>Radiation Heat Transfer</u>, Brooks/Cole Publishing Company, Belmont, California, 1970.







(D) Duct Dismeter (ft)	(G) Height Of Duct Bottom Above Ground (in)	(C) Circumferential Distance From Duct Top To Door Bottom (in)	(H) Circumferential Door Height (in)	(W) Door Width (in)	(b) Height Of Midplane Calorimeter Above Duct Bottom (in)	(F) Distance Between Floor Calorimeter And Door (in)
•	. 10	41	20 5/8	10	29	12
3	12 1/2	27	16		22	,
2	15	20 1/2	10 3/4	5 1/8	14 1/2	6
1	17 1/2	10	5 3/8	2 5/8	. 7	3
	and the second sec					

NOTE: Distance Between Top Of Fuel Pan and Ground 20 Inches

FIGURE 3. END VIEW OF DUCT AND PAN CONFIGURATION









FIGURE 8.







FIGURE 9. DAMPED OSCILLOGRAPH TRACES













FIGURE 156. FLAME PULSATION PENETRATING DUCT INTERIOR

FIGURE 15. INTERIOR VIEW OF FIRE





!

*

TEST NUMBER 11/29/1

Time (s)		10	20	30	40	50	60
Midplane Cal (Btu/ft ² s)	(C ₁)	.5	1.1	1.4	1.3	1.5	1.5
Radiometer No (Btu/ft ² s)	. 4	.6	1.3	1.8	1.8	1.8	1.9
Radiometer No (Btu/ft ² s)	. 5	.4	1.0	1.3	1.4	1.5	1.7
		TEST N	UMBER 11/2	9/2			
Time (s)		10	20	30	40	50	60
Midplane Čal (Btu/ft ² s)	(C1)	.5	1.1	1.2	1.2	1.0	1.3
Radiometer Ho (Btu/ft ² s)	• •	.7	1.4	1.8	2.0	1.9	1.7
Rediometer No (Btu/ft ² s)	. 5	.5	1.1	1.7	2.2	2.2	1.7
	FIGURE 17.	EXTERN	L HEAT FLU	JAES AND LO	JUATIONS		

APPENDIX

RADIATION ANALYSIS

ANGLE FACTOR INTEGRAL.

Although tabulations of angle or shape factors for diffuse radiative interchange between two surfaces are readily available for simple geometries, complex geometries generally require an individual treatment. Stokes' theorem can be employed to find the angle factor in many applications (reference 15). This method involves reformulation of the angle factor surface integral equation into three separate line integrals. The coordinates are further selected so that the normal to the receiving element lies in the direction of one of the coordinates. In this way, two of the three line integrals disappear. In this type analysis the following equation must be solved:

F $dA_{i}-A_{j} = \int_{c_{j}} \frac{(y_{j}-y_{i}) dx_{j} - (x_{j}-x_{i}) dy_{j}}{2\pi r^{2}}$

(1)

(2).

where dA_1 is the receiving element, A_j is the radiating surface, and C_j is the contour around the radiating surface. In equation (1), F is the angle factor, r is the distance between a point on dA_1 and another on A_j , x_1 , and y_1 are the positions of a point on the receiving element, and x_j and y_j are a point on the radiating surface. In this treatment, we assume the fuselage door is the radiating surface and the calorimeter is an infinitesimal receiving element. In this manner, x_1 and y_1 reduce to constant values.

Figure A-1 shows the parameters used to find the angle factor for the midplane calorimeter. When the center of the fuselage is taken as the origin, equation (1) can be written as follows:

 $F_{dA_{j}} - A_{j} = \int_{c_{j}} \frac{(y_{j} - a_{3}) dx_{j} - x_{j} dy_{j}}{2\pi \left[x_{j}^{2} + (y_{j} - a_{3})^{2} + z_{j}^{2}\right]}$

A-1



where:

$$z_j = a_1 \cos \theta_1$$

 $dy_j = a_1 \cos \theta_1 d\theta_2$

$$-dz_1 = a_1 \sin \theta_1 d\theta_1$$

Furthermore, the contour C1 around the door can be separated into four parts,

$$F_{dA_1} - A_1 = F_1 + F_2 + F_3 + F_4$$
 (3)

where F_4 and F_2 are the bottom and top edge of the door, respectively, and F_1 and F_3 are the right and left door edge, respectively. Thus, looking out the door from the inside, the integrating path is counterclockwise.

If the door is of width w, the first integral is defined as follows:

$$F_{1} = \int_{\alpha}^{\beta} \frac{\frac{w^{2} a_{1} \cos \theta_{1} d\theta_{1}}{2 \pi \left[\frac{w^{2} + (a_{1} \sin \theta_{1} - a_{3})^{2} + a_{1}^{2} \cos^{2} \theta_{1}\right]}$$
(4)

The term $(y_j - a_3) dx_j$ drops out since x_j is the constant $-\frac{w}{2}$ on this length. This integrates to make:

$$F_{1} = \frac{-w}{8\pi a_{3}} \ln \left[1 - \frac{2a_{3}a_{1}}{\frac{w^{2}}{4} + a_{1}^{2} + a_{3}^{2}} \sin \theta_{1} \right]_{\alpha}^{\beta}$$
(5)

sont suit creation (1) and (9) are international even (1) and image include

where α is the angle between the z-axis and the line between the origin and door bottom. The angle between the z-axis and the line from the origin to the door top is β . The integral F₃ is identical to F₁ except that x_j is now w and the order of integration limits is reversed. Thus:

(6)

tern. Equation (9) integrating to form:

The integral along the door top is written as:

$$F_{2} = \int_{-\frac{W}{2}}^{\frac{Z}{2}} \frac{(a_{1} \sin \beta - a_{3}) dx_{j}}{2\pi \left[x_{j}^{2} + (a_{1} \sin \beta - a_{3})^{2} + a_{1}^{2} \cos^{2}\beta\right]}$$
(7)

and this integrates out as:

$$F_{2} = \frac{a_{1} \sin \beta - a_{3}}{2\pi} \frac{1}{\sqrt{a_{1}^{2} + a_{3}^{2} - 2a_{1}a_{3}\sin \beta}} \tan^{-1} \left\{ \frac{x_{j}}{\sqrt{a_{1}^{2} + a_{3}^{2} - 2a_{1}a_{3}\sin \beta}} \right\} \Big]_{-\frac{W}{2}}^{\frac{W}{2}}$$

(8)

34

The integral along the bottom of the door is written:

F4=
$$\int_{\frac{w}{2}}^{\frac{-w}{2}} \frac{-a_3 dx_j}{2\pi \left[x_j^2 + (a_1 \sin \alpha - a_3)^2 + a_1^2 \cos^2 \alpha\right]}$$
 (9)

Both equation (7) and (9) are integrated along a line where the y variable is held constant and thus the numerator under the integral reduces to one term. Equation (9) integrates to form:

A-4

$$F_{4} = \frac{-a_{3}}{2\pi} \frac{1}{\sqrt{a_{1}^{2} + a_{3}^{2} - 2a_{1}a_{3}\sin\alpha}} \tan^{2} \tan^{-1} \frac{x_{j}}{\sqrt{a_{1}^{2} + a_{3}^{2} - 2a_{1}a_{3}\sin\alpha}} \int_{\frac{w}{2}}^{\frac{w}{2}} (10)$$

Figure A-2 shows the variables for evaluating the angle factor for a calorimeter on the floor. As in the midplane calorimeter solution, equation (1) is applied to the geometrical arrangement shown in figure A-2. In this case,

$$F_{dA_{j}-A_{j}} = \int_{C_{j}} \frac{(y_{j} - a_{4})dx_{j} - x_{j} dy_{j}}{2\pi [x_{j}^{2} + (y_{j} - a_{4})^{2} + z_{j}^{2}]}$$
(11)

where:

٩.

:

 $y_{j} = a_{1} \cos \theta_{1}$ $z_{j} = a_{1} \sin \theta_{1}$ $dy_{j} = -a_{1} \sin \theta_{1} d\theta_{1}$ $dz_{j} = a_{1} \cos \theta_{1} d\theta_{1}$

x = x1

Once again the integral is broken into four parts, as shown in equation (4), with the same direction of integration and the same identification of the door sides. Along the right side of the door, x_j is simply half the door width or $\frac{w}{2}$, and

$$F_{1} = \int_{\alpha}^{\beta} \frac{\frac{w}{2} a_{1} \sin \theta_{1} d\theta_{1}}{2\pi \left[\frac{w}{4}^{2} + (a_{1} \cos \theta_{1} - a_{4})^{2} + a_{1}^{2} \sin^{2} \theta_{1}\right]}$$
(12)

which integrates out to form:

A-5

FTEDRE 8-2, FLOOR CALIFICATE COOLD DEATES



$$F_{1} = \frac{v}{8\pi a_{4}} \ln \left[1 - \frac{2a_{1}a_{4}}{\frac{w^{2}}{4} + a_{1}^{2} + a_{4}^{2}} \cos \theta_{1} \right] \right]_{\alpha}^{\beta}$$
(13)

By reasoning identical to that used in the midplane calorimeter solution, F_1 equals F_3 , and two of the four needed integrations are complete. Along the top of the door, y and z are constant and the integral is stated as:

$$F_{2} = \int_{\frac{W}{2}}^{\frac{-W}{2}} \frac{\left[a_{1} \cos\beta - a_{4}\right] dx_{j}}{2\pi \left[x_{j}^{2} + (a_{1} \cos\beta - a_{4})^{2} + a_{1}^{2} \sin^{2}\beta\right]}$$
(14)

and this is solved as:

ł,

•

(15)

31 .

$$F_{2} = \frac{(a_{1} \cos \beta - a_{4})}{2\pi \sqrt{(a_{1} \cos \beta - a_{4})^{2} + a_{1}^{2} \sin^{2} \beta}} \tan^{-1} \left[\frac{x_{1}}{\sqrt{a_{1}^{2} + a_{4}^{2} - 2a_{1}a_{4} \cos \beta}} \right] \int_{\frac{w}{2}}^{\frac{w}{2}}$$

The integral along the door bottom is stated as:

$$F_{4} = \int_{-\frac{w}{2}}^{\frac{w}{2}} \frac{\left[a_{1}\cos\alpha - a_{4}\right] dx_{j}}{2\pi \left[x_{j}^{2} + (a_{1}\cos\alpha - a_{4})^{2} + a_{1}^{2}\sin^{2}\alpha\right]}$$
(16)

A-7

and solved as:

$$\mathbf{F}_{4} = \frac{\mathbf{a}_{1} \cos \alpha - \mathbf{a}_{4}}{2 \pi \sqrt{\mathbf{a}_{1}^{2} - 2\mathbf{a}_{1}\mathbf{a}_{4} \cos \alpha + \mathbf{a}_{4}^{2}}} \tan^{-1} \frac{\mathbf{x}_{j}}{\sqrt{\mathbf{a}_{1}^{2} - 2\mathbf{a}_{1}\mathbf{a}_{4} \cos \alpha + \mathbf{a}_{4}^{2}}} \Big]_{-\frac{\mathbf{w}}{2}}^{\frac{1}{2}}$$

(17)

W

2

.

4

CALCULATIONS.

Because all four ducts used in the tests have the same ratio of door width and length to fuselage diameter, any angle factor solution for one sized duct is the solution for all four ducts as long as the relative placement of the calorimeter is the same.

The following dimensions will be used for a solution:

 $\frac{w}{2} = 2.56$ inches $a_2 = 10.75$ inches $a_1 = 12$ inches $a_3 = 3$ inches $a_4 = 6$ inches $\alpha = 0^{\circ}$ $\beta = 51.33^{\circ}$

Using these numbers, the angle factor for the midplane calorimeter, F_M is 0.127 and the angle factor for the floor calorimeter F_F is 0.172. The ratio F_F/F_M is 1.35 and this agrees well with the measurements for the 1-, 2-, and 3-foot diameter ducts adjacent to a 4-foot square fuel pan.

RADIATIVE FLUX.

The radiative flux between two surfaces is given as:

 $q = \epsilon \sigma T^4 F_{dA_1 - A_1}$

where q is the heat flux, ε the surface emissivity, T the absolute temperature, and σ the Stefan-Boltzmann constant. Using 0.127 as the angle factor for the midplane calorimeter and 1.8 Btu/ft² s as experimental heat flux, equation (18) can be solved to yield a blackbody temperature of 1874°F when the emissivity is taken as unity.

(18)

When this temperature is used along with the relations developed for angle factors, heat fluxes in the vicinity of the door can be readily calculated on a point-by-point basis. Using the procedures developed here, a number of heat flux profiles were calculated for the cabin interior. Figure A-3 shows the calculated heat flux incident at the cabin midplane at a height of 3 inches above the floor as the receiving element is moved parallel to the fuselage centerline. Figure A-4 shows the heat flux incident at the cabin midplane as the receiving element is moved vertically. What is apparent from these calculations is the flatness of the heat flux profile within the door outline. Objects perpendicular to the door will all be subject to similar values of heat flux. This observation was experimentally confirmed by the traversing calorimeter which encountered little change in heat flux as it moved from one end of the door to the other along the fuselage midplane.

Figure A-5 shows the heat flux as the receiving element is moved along the floor from the middle of the duct door directly back to the fuselage midplane. In this plot, the range of incident heat fluxes is significant. Flooring materials close to the doorway are subject to much higher radiant heat fluxes than materials on the floor in the middle of the fuselage. Figure A-6 shows the heat flux to the receiver on the floor at a distance of 3 inches back from the door as the receiver moves parallel to the fuselage centerline. The change in absolute value of heat flux is minimal around the door itself. The flux does significantly drop as the receiver is moved to an interior position approximately one door width beyond the door edge.

In figures A-3 through A-6, the calculated shape factor between the receiver and the door is simultaneously plotted. The shape factor and the incident heat flux differ by a constant factor when a uniform blackbody temperature across the door opening is assumed. In addition, the positions in the figures are given in generalized notation related to the fuselage diameter and door width. Since all four duct sizes used in the tests were geometrically similar, the radiation calculations are applicable to all cases when the dimensions are generalized.

A-A. WAREATION OF STREAMER FOR ATTR WITH WEREN



!

7

.

2

*





A-10



FIGURE A-5. VARIATION OF FLOOR HEAT FLUX BETWEEN DOOR EDGE AND DUCT MIDPLANE (D IS FUSELAGE DIAMETER)



FIGURE A-6. VARIATION OF FLOOR HEAT FLUX AS RECEIVING ELEMENT IS DISPLACED FROM CENTER OF DOORWAY (L IS HORIZONTAL DISTANCE FROM DOOR CENTER, a4/D is 0.250)

A-11