

4 AD AO 6372 TECHNICAL REPORT 811 EVALUATION OF COCKROACH SURVEILLANCE DEVICES 2 Oct 78 10 Robert E. Desrosiers James H. Nelson, James T. Kardatzke FILE COPY Bernard A. Schiefer BIOENGINEERING RESEARCH and DEVELOPH US **Fort Detrick** Frederick, Nd. 21701 14) USAM BRD1 - TR-7811 22 JAN 1979 DC JAN 25 1979 DISTRIBUTION STATEMENT A Approved for public releases Distribution Unlimited US ARMY MEDICAL RESEARCH AND DEVELOPMENT Fort Detrick Frederick, MD 21701 79 01 23 5 407 838

NOTICE

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents. Use of trademarked names does not imply indorsement by the US Army, but is used only to assist in identification of a specific product.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

FORE COMPLETING FORM ENT'S CATALOG NUMBER DF REPORT & PERIOD COVERED WRMING ORG. REPORT NUMBER ACT OR GRANT NUMBER ACT OR GRANT NUMBER(*) RAM ELEMENT, PROJECT, TASK & WORK UNIT NUMBERS RT DATE Oct 78 ER OF PAGES RITY CLASS. (of this report) ASSIFICATION/DOWNGRADING EDULE
RMING ORG. REPORT NUMBER ACT OR GRANT NUMBER(*) RAM ELEMENT, PROJECT, TASK & WORK UNIT NUMBERS RT DATE Oct 78 ER OF PAGES RITY CLASS. (of this report) ASSIFIED ASSIFICATION/DOWNGRADING
ACT OR GRANT NUMBER(*) RAM ELEMENT, PROJECT, TASK & WORK UNIT NUMBERS RT DATE Oct 78 ER OF PAGES RITY CLASS. (of this report) ASSIFIED ASSIFICATION/DOWNGRADING
RAM ELEMENT, PROJECT, TASK & WORK UNIT NUMBERS RT DATE Oct 78 ER OF PAGES RITY CLASS. (of this report) ASSIFICATION/DOWNGRADING
RT DATE Oct 78 ER OF PAGES RITY CLASS. (of this report) ASSIFICATION/DOWNGRADING
RT DATE Oct 78 ER OF PAGES RITY CLASS. (of this report) ASSIFICATION/DOWNGRADING
Oct 78 ER OF PAGES RITY CLASS. (of this report) ASSIFIED ASSIFICATION/DOWNGRADING
ER OF PAGES RITY CLASS. (of this report) ASSIFIED ASSIFICATION/DOWNGRADING
assified ASSIFICATION/DOWNGRADING
ASSIFICATION/DOWNGRADING
Cockroach control

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

.

produced statistically consistent results although three of the traps could be used as survey devices for cockroaches with varying degrees of utility. A cost-benefit analysis using seven parameters revealed that The Detector was the trap of choice followed closely by the Mr. Sticky. It was recommended that use of The Detector or Mr. Sticky should involve a minimum of two consecutive nights using the same trap, to dampen the inconsistency of sampling. The Roatel trap was recommended for use if colonization is the primary function of the survey. The Shock"M"All trap was not recommended for use as a control or surveillance device due to electrical hazard potential.

ar cuosudant conde une e evaluared the porential free des [5, cochester to altare datare, the Cabertoria, e. Streball, Rostal(), and Shock's as serviced to a service of caste designed to determine the effect verter

tenents material and viterab around to total and a performation in and

their a contracte is second series was destimed to rest the construction subject countricles is bytes inspire excluding the shock of all is there are

and the brought one still the states white a still a selection and the second the second states, we

SECURITY CLASSIFICATION OF THIS PAGE(When Data Enter

TABLE OF CONTENTS

		Page
I.	INTRODUCTION	1
	A. BACKGROUND	1
	B. PURPOSE	2
п.	METHODS AND MATERIALS	2
	A. TEST AREA	2
	B. TRAPS	3
	C. TESTS	4
	(1) SERIES ONE	5
	(2) SERIES TWO	6
	(3) OPERATIONAL TEST	7
	RESULTS AND DISCUSSION	7
IV.	RECOMMENDATIONS	13
٧.	LITERATURE CITED	14

TABLES

Table 1				•		•	•		•	•			•		•	8
Table 2							•			•		•	•	•		8
Table 3		•			•	•		•		•		•	•	•		9
Table 4	•	•		•	•	•	•		•	•	•	•	•	•		9
Table 5		•	•	•	•	•	•						•	•	•	10
Table 6				•		•	•	•	•		•	•	•	•	•	12

TIS	White Section
906	
MANNOUNCED	0
USTIFICATION	
DISTRIBUTIO	N/AVAILABILITY CODES
	AVAILABILITY CODES AVAIL End/or SPECIAL

EVALUATION OF COCKROACH SURVEILLANCE DEVICES

I. INTRODUCTION.

A. BACKGROUND.

Cockroaches impact severely on man's domestic environment representing a major source of potential contamination to his food. Studies have shown that cockroaches spread filth from unsanitary areas to areas where food is stored, prepared, and eaten. Laboratory studies have shown that cockroaches are capable of carrying various disease organisms (Jung and Shaffer, 1952; Rueger and Olsen, 1969) and in a recently conducted field study it was concluded that cockroaches carry bacteria capable of causing human food poisoning and disease (Frishman and Alcamo, 1977). Even if the danger of contamination is excluded, odors imparted to food and surroundings by excretions and secretions of cockroaches in areas of high infestation render cockroaches terribly noxious pests.

The cockroach management problem represents a major manpower and fiscal expenditure to the Army, where pest control personnel devote approximately 75% of their time to cockroach control (Smith, pers. com.). Through scheduled repeated treatments, the Army dispenses tons of cockroach baits and dusts and thousands of gallons of pesticide sprays yearly in an effort to control these insects. The magnitude of expenditure for cockroach control warrants development and adoption of procedures which will insure optimum efficiency of manpower and pesticides. A need exists for a simple, efficient, inexpensive cockroach surveillance device which will provide a population index to be used in establishing the need for and proper timing of control procedures, thereby reducing manpower and pesticide usage.

B. PURPOSE.

Army regulations 40-5 (Health and Environment) and 420-76 (Pest Control Services) require surveillance for cockroaches as a prerequisite to initiation of control procedures. Present surveillance procedures consist of flushing cockroaches from their harborages with pyrethrin sprays and making population estimates by visual observation. The procedure is time consuming, highly subjective, and provides only the crudest estimate of the population.

A study was initiated to evaluate four currently marketed cockroach traps to identify surveillance devices to replace the "flush and count" procedure and to provide guidelines for their use.

Attend emperation to the Arte-ware part control personer device exproviously if i device the vare part control personer device approximately if of their the to exceeded another their parts condthrough soliditied represent the treatment the Arey displayed from of controls watts and ducts and thousands of gallons of posticide sprate reactly in an effort to control three insects. The monitude of superditure for controls here and thousands de gallons of posticide sprate reactly in an effort to control three insects. The monitude of superditure for excell togets outling efficiency of manounce and electron of wrotedores units at 11 house collige efficiency of manounce and posticides in recedures units exists for a single efficiency of manounce and posticides. A need

II. METHODS AND MATERIALS

TEST AREA:

All tests were conducted in a specially prepared test room located at Fort Detrick, Maryland. Three walls and the floor of the room were tile, and one wall and the door were plywood. A translucent window was present in one tiled wall. All cracks within the test area were caulked, and the floor drain was sealed. A cockroach barrier, of masking tape and Tack Trap^(R), was placed on all walls 1.3 M from the floor. The size of the test area was $3.25 \times 2.1 \times 1.3$ M. A cardboard test chamber 45.7 x 45.7 x 35.6 cm was placed in the test area to simulate a cupboard or enclosed area under a sink. Cockroaches could easily exit and reenter the test chamber. A temperature of $21 \pm 2^{\circ}$ C was maintained in the test area using a 1500 watt electric space heater having a fan and thermostat. The humidity was monitored during the tests with a hygrometer positioned on the wall 1.4 M above the floor.

TRAPS:

Four cockroach traps were selected for evaluation as surveillance devices, The Detector (R), the Mr. Sticky(R), the Roatel(R), and the Shock"M"All(R).

Tack Trap^(R) - Animal Repellants, Inc., Griffin, GA. The Detector^(R) - Zoecon Corp., 975 California Ave., Palo Alto. CA 94304. Mr. Sticky^(R) - Mitsuboshi Boeki Inc., 587 Industrial Rd., Carlstadt NJ 07072. Roatel^(R) - Fumakilla Limited, Tokyo, Japan. Shock"M"All^(R) - Hinez Corp., 121 W. Chestnut Hill Ave., Philadephia, PA 19118

(1) The Detector is a ready-to-use, disposable, rectangular, cardboard box, 4.5 x 12.5 x 7.0 cm, with three 2 cm adhesive bands around the trap's inner surface. A burnt caramel odoriferous bait is incorporated into one of the adhesive bands. The ends of the box are open with internally directed flaps. The traps are received wrapped in pairs in cellophane and require no preparation. They do not fold for transport. Black traps were used in these tests, but different colors are available.

(2) The Mr. Sticky is a cardboard trap which comes collapsed to 9 x 18 cm. When assembled, it is a tubel8 cm long, triangular in cross section, 9 cm wide and 5 cm high. To make operational, the tops of the trap are unfolded, a protective paper sheet over the adhesive, which covers the entire inner surface of the base, is removed, and the contents of a packet of roach bait (84.5% chrysalis powder, 15.0% precipitated calcium carbonate, and 0.5% sodium benzoate) is sprinkled over the adhesive. The sides of the trap are then interlocked to form a tube.

(3) The Roatel is a clear plastic, non-disposable, two stage trap which requires baiting (Fumakilla Roatel Bait). The trap operates by allowing cockroaches, in search of food, to enter the bottom of the trap by means of one-way aluminum toothed-edge trap doors. From there, finding further progress to the bait blocked, they enter the upper bait holding level also through trap doors. The upper level is removable for periodic collection and for cleaning.

(4) The Shock"M"All is designed for permanent installation on wall baseboards. The system consists of specially designed plastic baseboard

sections which contain electric contacts that electrocute insects. The 3 ft. long sections operate on 110 or 220 volt, 50 or 60 cycle, household current. A power pack converts the household current to 850 volts and reduces the amperage to 0.9 milliamperes. A capacitance/discharge system electrocutes any insects which enter the baseboard unit. The units require periodic cleaning with a vacuum cleaner. According to Army regulations, an electrician must install the units.

TESTS:

Three comparative tests were conducted. One involved testing the traps individually in a confined space, another involved testing three of the traps simultaneously, using the entire room, and a third involved testing two of the traps under operational conditions. Twenty-four hours prior to each test replicate, cockroaches were isolated. For each replicate of the first test, 40 each 2nd and 4th instar nymphs and 20 each adult males and females (<u>Blatella germanica</u>)* were collected and five each of the same instar were placed in a clean, dry 37 ml plastic vial containing a small piece of moist filter paper. These vials were held overnight, and dead cockroaches were removed and replaced the following morning. The cockroaches were then placed in three pint mason jars for

*The specimens used were from a mixed colony consisting of individuals from the US Dept. of Agriculture, Beltsville, MD; The US Army Environmental Hygiene Agency, Fort Meade, MD; and from the stock colony maintained by the Pest Management Systems Branch, USAMBRDL.

introduction to the test site. For the second test, 150 2nd instar nymphs, 120 4th instar nymphs, and 90 each adult male and female cockroaches were similarly introduced to the test site and used for three consecutive nights.

(1) TEST ONE.

The first test was designed to determine the effectiveness of each trap in sampling a population of known density and instar composition within a confined space. Each trap was tested on four different nights. The test area was inspected for any previously uncaptured cockroaches and those found were removed. On the day of the test, food, water and harborage (six pieces of 10.2 x 10.2 x 0.3 cm masonite separated by two 4.5 x 1.3 x 0.3 cm spacers) were placed under the cardboard test chamber. The test chamber was positioned 10.2 cm from the wall, and a trap was placed between the chamber and the wall. If the test involved the Shock"M"All, the trap was thoroughly vacuumed and inspected for short circuits. Fresh bait was used in traps requiring bait. The overhead lights were turned off, and the test chamber was set aside. The tops of the cockroach holding jars were removed, and the jars were placed near the harborage and the test chamber then replaced. The door to the test area was locked and sealed with masking tape. At the end of 24 hrs the following data were recorded: temperature; relative humidity; number of cockroaches in the floor, walls, tack trap, harborage, in the trap, and the number missing by instar and sex; the time required to set, check and remove the trap and cockroaches; and the nature of any malfunctions.

(2) <u>TEST TWO</u>.

In the second test the comparative trapping capabilities of The Detector, the Roatel and the Mr. Sticky traps were tested. Four of each of the three traps were used for three consecutive nights. The twelve traps were arranged in a 75 cm radius circle an equal distance apart with the position of each trap being determined randomly and with their positions rerandomized daily. Freshly baited, clean traps were used each night. The traps were tested against an initial number of 450 cockroaches (150 2nd instar nymphs, 120 4th instar nymphs and 90 each adult males and females) released near the harborage which was positioned, with water and food, in the center of the circle. The water, food, and harborage were then covered with the cardboard test chamber. The test area was then sealed as previously described and after 24 hrs the following data were recorded: room temperature, relative humidity, trap type, replicate, position, number of cockroaches collected by instar and sex. Cockroaches trapped from the original test evaluation were not replaced.

(3) OPERATIONAL TEST.

The Mr. Sticky^(R) and The Detector^(R) traps were tested as part of an operational cockroach control program in two dining facilities at Fort Detrick. These tests were designed to demonstrate the usefulness of these traps in determining cockroach infestations and as an aid in locating harborages.

III. RESULTS AND DISCUSSION.

All traps evaluated could be used as survey devices for cockroaches with varying degrees of utility. It should be noted here that the traps did not noticeably decrease cockroach population levels in the operational test. Tables 1-3 show the effectiveness of the four traps when they were tested individually. The Shock"M"All trap had the most consistent capture rates between stages and between replication although the average percent catch was only slightly higher than the lowest value (Mr. Sticky). None of the traps produced statistically consistent results. The highest average catch was obtained with The Detector followed in order by the Roatel, Shock"M"All, and Mr. Sticky. All traps demonstrated a low proficiency in capturing 2nd instar nymphs (Table 1). Although, with the exception of the Mr. Sticky, the capture rate was essentially identical for all traps. Similarly, with the exception of the high rate of capturing 4th instar nymphs by The Detector, the capture rate for the other traps was surprisingly similar (Table 2). It is interesting to note that the capture rate of adults for the Roatel trap was nearly twice that for the other traps (Table 3). The Roatel is the only trap which will allow for collection of live cockroaches to be used for colonization and/or resistance testing. An analysis of the adult male-female capture ratio indicated The Detector and Roatel were more successful in capturing males while the Mr. Sticky and

8

6.0

and Shock"M"All were more successful in capturing females in these tests (Table 4). This reveals a balanced split between the attractiveness of the adhesive traps and non-adhesive traps.

Table 1. Catch Per Replicate, Total Catch, and Percent of Total (All Replicates) Caught of 40, 2nd Instar <u>Blatella germanica</u> Nymphs Per Replicate, By Cockroach Traps Individually Tested.

Trap	Cat 1		Repli 3	cate 4	Total Catch	Percent of Total (All Replicates) Caugh		
Detector	19	1	11	7	38	23.75		
Mr. Sticky	6	1	3	2	12	7.50		
Roate1	3	9	9	13	34	21.25		
Shock"M"A11	9	11	9	9	38	23.75		

Table 2. Catch Per Replicate, Total Catch, and Percent of Total (All Replicates) Caught of 40, 4th Instar <u>Blatella germanica</u> Nymphs Per Replicate, By Cockroach Traps Individually Tested.

Trap	Cat 1	ch/F 2	epli 3	cate 4	Total Catch	Percent of Total (All Replicates) Caught
Detector	27	11	15	18	71	44.38
Mr. Sticky	3	4	15	20	42	26.25
Roate1	13	15	7	10	45	28.13
Shock"M"A11	6	16	5	10	37	23.13

g

	Cat	ch/R	epli	cate		Percent of Total			
Trap	1	2	3	4	Total Catch	(All Replicates) Caught			
Detector	18	8	11	18	55	25.0			
Mr. Sticky	4	9	19	12	44	27.5			
Roatel	23	30	23	7	83	51.9			
Shock"M"A11	7	14	13	10	44	27.5			

Table 3. Catch Per Replicate, Total Catch, and Percent of Total (All Replicates) Caught of 40 Adult <u>Blatella germanica</u> Per Replicate, By Cockroach Traps Individually Tested.

Table 4. Male/Female Cockroaches Caught by Cockroach Traps Individually Tested.

Trap	Male/Fo	emale Ca	Male/Female	Total		
	1	2	3	4		
Detector	9/9	3/5	3/8	8/10	23/32	
Mr. Sticky	4/0	3/6	10/9	7/5	24/20	
Roatel	10/13	14/16	9/14	2/5	35/48	
Shock"M"A11	4/3	8/6	5/8	8/2	25/19	

The second test was comprised of four replicates of three of each of the attractant-containing traps for three consecutive nights to determine their relative attractivenss (Table 5). Results of these tests indicated no significant difference between traps. The Roatel caught the greatest number of cockroaches, averaging nearly six per night while The Detector caught the fewest number (average three per night).

4 6100	Ny	mphs	, an	d 90	Each A ghts.						oree
			h/Re 3 N		S	R	eplica	Χ S _D			
Trap	1	2	3	4	Total	1	2	3	4	X	All Replicates
Detector	8	4	8	17	37	2.67	1.33	2.67	5.67	3.17	1.27
Mr. Sticky	12	13	16	9	50	4.00	4.33	5.33	3.00	4.17	1.07
Roatel	21	14	23	13	71	7.00	4.67	7.67	4.33	5.92	1.60

Table 5. Relative Attractiveness of Three Cockroach Traps When Tested Together in Random Order Against A Population of Blatella

The operational tests involved use of The Detector and Mr. Sticky traps in two dining facilities. An ultra low volume (ULV) application and residual spray program using the traps as surveillance devices was initiated. By using the same traps two consecutive days, a relatively consistent and determinable level of cockroach infestation was found. Prior to this surveillance program, control was initiated in response to user requests which frequently resulted in weekly pesticide applications. The two dining facilities used in this study accounted for a time expenditure of 27 hrs. per quarter for pest control personnel. Following spraying and utilization of the surveillance traps, user requests and frequency of residual spraying were reduced significantly. One facility has averaged monthly spraying and the other has averaged quarterly treatments since inception of the surveillance program. The total manpower requirement for pesticide applications and surveillance has now been reduced by nearly one-half to 14 hrs per quarter and pesticide usage has been reduced by two-thirds.

A cost-benefit analysis was performed to determine the best possible cockroach trap for use in an Army-wide surveillance program (Table 6). Seven categories or factors were identified as being valid in evaluation of the four traps. In order to make the values dimensionless and normalized, the largest value for each factor was divided into all the values for that factor. Since all of the factors are not necessarily of equal importance their relative values and rankings were subjectively arrived at by three professional entomologists considering test results and objectives of a good cockroach control program. The highest benefit value was for consistency of count, which allowed for actual estimates of cockroach populations, followed by operational considerations. Obviously, since the traps are to be used for surveys, their effectiveness is important, and if resistance testing is to be part of a surveillance program the ability to collect live specimens acquires a high benefit value. Since surveillance must be performed with a minimum manpower expenditure, portability to and from the survey areas was given a high benefit value. Trap set-up time was given an intermediate benefit value. This factor involves both the manpower expended in set-up and the disruption caused within the surveyed activity. Of lesser benefit values were the annoying appearance of the traps and requirements for their daily maintenance. The Roatel trap had the highest sum of benefit values followed in order by The Detector and Mr. Sticky which were very close, and the Shock"M"All. The weekly (52 wks/yr) trap cost was lowest for The Detector followed by the Mr. Sticky, the Roatel, and the Shock"M"All. The Detector and Mr. Sticky

		Trap									
Factor	Value	Detector	Mr. Sticky	Roate1	Shock"M"A11						
Portability	10 Normalized Benefit	140 0.70 7.00	200 1.00 10.00	70 0.35 3.50	1 0.005 0.050						
Annoying Appearance	l Normalized Benefit	12 1.000 1.000	11 0.917 0.917	10 0.833 0.833	1 0.083 0.083						
Set-Up Time	5 Normalized Benefit	100 1.000 5.000	75 .750 3.750	50 0.500 2.500	1 0.010 0.050						
Effectiveness For Survey	10 Normalized Benefit	5 0.100 1.000	50 1.000 10.000	25 0.50 5.00	1 0.020 0.200						
Effectiveness F Colonization	or 10 Normalized Benefit	2 0.100 1.000	2 0.100 1.000	20 1.000 10.00	1 0.050 0.500						
Consistency of Count	15 Normalized Benefit	5 0.250 3.75	1 0.050 0.750	10 0.500 7.500	20 1.000 15.00						
Maintenance Required	l Normalized Benefit	100 1.000 1.000	90 0.900 0.900	50 0.500 0.500	1 0.010 0.010						
Summary of Bene	fit Values	19.75	18.317	29.833	15.893						
Trap Cost/26 us	es/Yr	\$5.20	\$7.54	\$7.80	\$400.00						
Trap Cost/52 us	es/Yr	\$10.40	\$15.08	\$15.60	\$400.00						
Benefit-Cost Ra Benefit-Cost Ra		3.79	2.43	3.82 1.91	0.039						

Table 6. Cost-Benefit Analysis of Four Cockroach Traps

are throw-aways and therefore have no capital investment while the Roatel and Shock"M"All have capital investments of \$5.00 and \$1200 per trap respectively. Life expectancy is one year for the Roatel trap and three years for the Shock"M"All. The lowest benefit-cost ratio was for the Shock"M"All trap. This point coupled with the trap's maintenance and installation requirements, the permanancy of installation, and the real potential for electrical shock render the Shock"M"All trap ineffectual for Army use as a cockroach surveillance device. The highest benefit-cost ratio was obtained with the Roatel trap which was followed very closely by The Detector and in third place in the benefit-cost ratio ranking was the Mr. Sticky. The unique positive feature of the Roatel trap is the capability of capturing live specimens for colonization and resistance testing as previously mentioned. The negative features of the Roatel are the time necessary to remove and kill the captured cockroaches, time to clean the trap with alcohol, time to discard and replace the old bait, and the inordinate amount of care exercised to insure against dropping the delicate trap.

14

3.82

IV. RECOMMENDATIONS.

A. Cockroach surveillance techniques should become an integral part of all Army pest control procedures to be in compliance with pertinent Army regulations and to reduce expenditures for cockroach control.

B. For routine surveillance The Detector is the trap of choice, followed closely by the Mr. Sticky.

C. Use of The Detector or Mr. Sticky traps should involve a minimum of two consecutive nights, using the same trap, to dampen the inconsistency of sampling.

D. If colonization is the primary function of the survey, the Roatel trap should be used.

E. The Shock"M"All trap should not be used for either control or surveillance due to electrical hazard potential and low cost-benefit.

V. LITERATURE CITED.

Frishman, A. M. and I. E. Alcamo. 1977. Domestic Cockroaches and Human Bacterial Disease. Pest Control, 45(6): 16-46.

Jung, R. C. and M. F. Shaffer. 1952. Survival of Ingested <u>Salmonella</u> in the Cockroach <u>Periplaneta americana</u>. Am. J. Trop. Med. Hyg., 1:990-998.

Rueger, M. E. and T. A. Olson. 1969. Cockroaches (Blattaria) as Vectors of Food Poisoning and Food Infection Organisms. J. Med. Ent., 6: 185-189.

DISTRIBUTION LIST

No. of Copies

2

6

2

1

Δ

2

1

1

1

Addressee

Academy of Health Sciences, US Army ATTN: MAJ Darwin B. Palmer Health and Environment Division Fort Sam Houston, TX 78234

Armed Forces Pest Control Board Forest Glen Section, WRAMC ATTN: LTC William B. DuBose III, USAF, BSC, Exec. Secretary Washington, DC 20012

Bureau of Medicine and Surgery ATTN: CDR John A. Mulrennan, Jr., MSC, USN Head, Environmental Quality Branch Occupational & Preventive Medicine Div (553) Washington, DC 20372

CINCPACAF (DEMM) ATTN: Mr. Jonathon T. Kajiwara APO San Francisco, CA 96553

Defense Construction Supply Center ATTN: DCSC-SED/Mr. Felix M. Huertas Columbus, OH 43215

Defense Documentation Center ATTN: DDC-PCA Alexandria, VA 22314

Defense Personnel Support Center ATTN: DPSC-STQ/MAJ Marvin L. Bertsch 2800 South 20th St. Philadelphia, PA. 19101

Department of Entomology 10th Medical Laboratory APO NY 09180

Directorate of Facilities Engineering US Army Support Command, Hawaii ATTN: Mr. William B. Andrews, Jr. APO San Francisco, CA 96558

No. of Copies

1

1

1

1

1

1

1

1

Addressee

Disease Surveillance Branch (Entomology) Epidemiology Division USAF School of Aerospace Medicine Brooks AFB, TX 78235

4

Disease Vector Ecology and Control Ctr Naval Air Station, Box 43 ATTN: LCDR L. Lance Sholdt, MSC, USN Officer in Charge Jacksonville, FL 32212

HQ, USA, TRADDOC ATTN: Mr. Calvin B. Spencer Engineer Office (ATEN-FE-BG) Fort Monroe, VA 23651

Insects Affecting Man Research Lab ATTN: LCDR R. H. Grothaus USDA, ARS Gainesville, FL 32604

Medical Equipment Test & Evaluation Div., US Army Medical Materiel Agency, Fort Sam Houston, TX 78234

Military Entomology Information Service Walter Reed Army Medical Center Washington, DC 20012

Commanding Officer (156) ATTN: H.B. Moore Naval Construction Battalion Ctr Port Hueneme, CA 93043

Naval Facilities Engineering Command Western Div., P.O. Box 727 ATTN: Mr. A. Reese Christopherson (10A1) San Bruno, CA 94066

No. of Copies

1

1

1

1

1

1

1

2

Addressee

Naval Facilities Engineering Command ATTN: Mr. B. B. Gillespie (10A) Special Asst for Pest Management Western Division San Bruno, CA 94066

Naval Facilities Engineering Command ATTN: Mr. Thomas H. Lauret (1143) Pacific Division FPO San Francisco, CA 96610

Naval Facilities Engineering Command ATTN: Mr. Lawrence Pinter (11431) Pacific Division FPO San Francisco, CA 96610

Naval Facilities Engineering Command Environmental Branch, Northern Div. ATTN: Mr. Frederick J. Danos (114) US Naval Base, Bldg. 77 Philadelphia, PA 19112

Naval Facilities Engineering Command ATTN: Mr. Peter L. Fish (11431) Northern Division US Naval Base, Bldg. 77 Philadelphia, PA 19112

Naval Facilities Engineering Command ATTN: Mr. Harvey A. Shultz (1143) Applied Biology Program - Northern Div. US Naval Base, Bldg. 77 Philadelphia, PA 19112

Naval Facilities Engineering Command ATTN: Mr. Don R. Estes (10A) Southern Division, Box 10068 Charleston, SC 29411

Naval Facilities Engineering Command ATTN: Mr. Melvin P. Marks (10A2) Southern Div., P.O. Box 10068 Charleston, SC 29411

Naval Facilities Engineering Command ATTN: Mr. William A. Gebhart (104B1) Biological Sciences Staff 200 Stovall Street Alexandria, VA 22332

No. of Copies

1

1

1

1

1

1

2

1

1

Addressee

•

.

Naval Facilities Engineering Command ATTN: Mr. James Eversole (10A2) Atlantic Division Norfolk, VA 23511

Naval Facilities Engineering Command ATTN: Mr. James J. Keeble (10A3) Atlantic Division Norfolk, VA 23511

Naval Facilities Engineering Command ATTN: Mr. Andrew Michael (Code 10A4) Atlantic Division Norfolk, VA 23511

Naval Facilities Engineering Command Special Asst for Applied Biology Atlantic Division Norfolk, VA 23511

Navy Disease Vector Ecology & Control Ctr ATTN: LCDR R. V. Peterson, MSC, USN Officer in Charge, Naval Air Station Alameda, CA 94501

US Army Facilities Engineering Support Agency ATTN: FESA-HBG-BG/Mr. James F. Smith Fort Belvoir, VA 22060

Office of the Surgeon General ATTN: Entomology Consultant DASG-HCH-E Washington, DC 20310

Mr. Gordon L. Smith Base Engineer Langley, VA 23365

USAEHA, Regional Division - West ATTN: Radiation & Entomological Sciences Br., Fitzsimons Army Medical Center Denver, CO 80240

No. of Copies

1

1

1

1

25

1

1

1

1

1

Addressee

USAEHA, Regional Division - South ATTN: Radiation & Entomological Sciences Br. Fort McPherson, GA 30330

US Army Environmental Hygiene Agency ATTN: HSE-M Aberdeen Proving Ground, MD 21010

USAEHA Regional Division - North ATTN: Radiation & Entomological Sciences Br. Ft. Meade, MD 20755

US Army Health Services Command Medical Entomology Consultant Health and Environment Division Fort Sam Houston, TX 78234

USAMBRDL Technical Library Ft. Detrick, Frederick, MD 21701

US Army Materiel Development and Readiness Command ATTN: DRCMM-E 5001 Eisenhower Avenue Alexandria, VA 22333

HQ AF Logistics Command ATTN: Mr. Walter G. Adams AFLC/DEMM Wright-Patterson AFB, OH 45433

HQ AFSC SMR-88 ATTN: MAJ Stephen M. Valder, USAF, BSC Staff Civil Engineer Entomologist Andrews AFB Washington, DC 20331

HQ, A.T.C./DEMM ATTN: Mr. Clifford Novosad Randolph AFB, TX 78148

HQ, Eighth US Army ATTN: Mr. Taek Ku Ki Ofc of the Engr, Facilities Engrg Div Buildings & Grounds Branch APO San Francisco, CA 96301

No. of Copies

1

1

1

1

1

1

2

1

1

1

1

Addressee

1

2

HQ, USAF (PREV) The Pentagon ATTN: Mr. Walter W. Barrett Washington, DC 20330

HQ USAF/SGPA ATTN: LTC Sherrill G. Laney Forrestal Building Washington, DC 20314

HQ, US Army Japan/IX Corps ATTN: Mr. Jack M. Rosebush Office of the Engineer APO San Francisco, CA 96343

HQ, US Army Forces Command ATTN: AFEN-FE-S/Mr. Chester L. Smola Fort McPherson, GA 30330

HQ, US Army Materiel Command I&SA ATTN: AMCIS-RI-IB/Mr. Luis C. Stover Rock Island Arsenal, IL 61201

HQ, US Army Natick Research & Development Lab ATTN: Dr. L. W. Smith, Jr. Natick, MA 01760

HQ, US Army Medical R&D Command ATTN: LTC John F. Reinert Fort Detrick, Frederick, MD 21701

USA Mobility Equipment R&D Command Sanitary Sciences Division ATTN: DRXFB-GS, Lab 2000/Mr. David Cotrona Fort Belvoir, VA 22060

US Naval Base, Bldg. 77 ATTN: Mr. Stephen Kincaid (11432) Northern Division Philadelphia, PA 19112

US Navy Public Works Center, Box 6 ATTN: Mr. Avelino F. Banaag (Code 501) FPO San Francisco, CA 96651

US Navy Public Works Center ATTN: Dr. L. Darrell Hale (Code 33) FPO San Francisco, CA 96630

Hannell Company &

No. of Copies

1

1

1

1

1

1

1

1

1

17

Addressee

US Navy Public Works Center ATTN: Mr. Tsugio Satoh, Code 31 Box 13 FPO Seattle, WA 98762

USA MEDDAC Preventive Medicine Activity Ft. Benning, GA 31905

USA MEDDAC Preventive Medicine Activity Fort Bragg, NC 28307

USA MEDDAC Preventive Medicine Activity Canal Zone APC Miami 34004

USA MEDDAC Preventive Medicine Activity FL. Dix, NJ 08640

USA MEDDAC Preventive Medicine Activity Fort Jackson, SC 29207

USA MEDDAC Preventive Medicine Activity Fort Knox, KY 40121

USA MEDDAC Preventive Medicine Activity Fort Leonard Wood, MO 65473

USA MEDDAC Preventive Medicine Activity Ft. Lewis, WA .98431