

DDC FILE COPY

AD A063881

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER HDL-TM-78-20	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) The Generation of High-Power Microwave Radiation from Intense Relativistic Electron Beams		5. TYPE OF REPORT & PERIOD COVERED Technical Memorandum
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) R. Alan Kehs Alan Bromborsky		8. CONTRACT OR GRANT NUMBER(s) DA: 1L161101A91A
9. PERFORMING ORGANIZATION NAME AND ADDRESS Harry Diamond Laboratories 2800 Powder Mill Road Adelphi, MD 20783		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Ele: 6.11.01.A
11. CONTROLLING OFFICE NAME AND ADDRESS U.S. Army Materiel Development and Readiness Command Alexandria, VA 22333		12. REPORT DATE November 1978
		13. NUMBER OF PAGES 25
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) Unclassified
		16. DECLASSIFICATION/DOWNGRADING SCHEDULE
15. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES  DRCMS Code: 611101.91A0011 HDL Project No: A10726		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  Microwave generation Relativistic electron beams		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  This report provides a basis for evaluating the current and near-future development of relativistic-electron-beam (REB) technology for the generation of microwave radiation. Magnetrons, gyrotrons, and Raman scattering are examined in some detail and references are cited for several other conversion schemes. The status of repetitively pulsed REB generation is then reviewed → next page		

DD FORM 1 JAN 78 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

1

79 01 17

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. Abstract (Cont'd)

and two hypothetical systems are constructed from the conversion schemes and generators that were considered earlier. Finally, some of the advantages (such as high power and compact size) and disadvantages (such as unproven technology) are summarized.

ACCESSION FOR	
1. IS	1. Data Section <input checked="" type="checkbox"/>
2. IS	2. Ref. Section <input type="checkbox"/>
3. IS	3. <input type="checkbox"/>
BY	
DISTRIBUTION/AVAILABILITY CODES	
SPECIAL	
A	

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

## CONTENTS

	<u>Page</u>
1. INTRODUCTION . . . . .	5
2. ELECTRON-BEAM MICROWAVE GENERATION . . . . .	5
2.1 Relativistic Magnetron . . . . .	7
2.2 Stimulated Raman Scattering . . . . .	8
2.3 Gyrotron . . . . .	9
2.4 Other Schemes . . . . .	10
3. ELECTRON-BEAM GENERATORS . . . . .	10
3.1 Nereus Relativistic Electron-Beam Generator . . . . .	13
3.2 High-Repetition-Rate Trace Machine . . . . .	13
3.3 Hypothetical Relativistic Electron-Beam Microwave Generating System . . . . .	14
4. CONCLUSIONS . . . . .	15
SELECTED BIBLIOGRAPHY . . . . .	17
DISTRIBUTION . . . . .	23

## FIGURES

1 Peak power and frequency for several different electron beams .	6
2 Magnetron diode . . . . .	7
3 Typical Raman scattering experiment . . . . .	8
4 Common gyrotron arrangement . . . . .	9
5 Pulser assembly . . . . .	14

## TABLES

I Peak Power Levels from Cyclotron Masers (Gyrotrons) Driven by Intense REB . . . . .	10
II Sampling of Soviet Repetitively Pulsed REB Machines . . . . .	11
III Sampling of U.S. Repetitively Pulsed REB Machines . . . . .	12

## 1. INTRODUCTION

This report provides a preliminary basis for evaluating the feasibility of relativistic-electron-beam (REB) generated microwaves (ref 25, 30);\* it examines the most important schemes for converting electron-beam energy to microwave and near-millimeter radiation. The current state of electron-beam generators is reviewed with an emphasis on small repetitively pulsed machines that would be suitable for Army use. Finally, two scenarios are constructed in which current and projected hardware are combined to form REB-driven microwave-radiation sources.

## 2. ELECTRON-BEAM MICROWAVE GENERATION

Although most of the current research effort is directed towards producing near-millimeter and submillimeter radiation, many devices operate in the S and X band regions where peak powers up to 4 GW have been observed (ref 42, 5). Figure 1 shows the peak power and frequency for several different schemes for converting electron-beam to microwave radiation, illustrating the wide range of operating regimes. The two high-power points, marked M, represent the results of relativistic magnetron experiments (ref 42, 5). The best high power at high frequency results have been obtained with gyrotron-type configurations, labelled G (ref 32). The next group of devices (labelled R) employ stimulated Raman scattering (ref 10, 38) to generate microwaves. The final points, labelled C (ref 53, 54), represent a new area of study: stimulated Cerenkov radiation. All these schemes employ foilless diode geometries and would conceivably make reasonable repeatable microwave sources. The relativistic magnetron, stimulated Raman scattering, and gyrotron processes are described in more detail in this report.

---

\*Because this report is a literature survey, literature citations (given in parentheses) are listed in the Selected Bibliography (p 17), rather than on the pages where cited.




Figure 1. Peak power and frequency for several different electron beams.

## 2.1 Relativistic Magnetron

The relativistic magnetron is a high-voltage version of the simple classical magnetron (ref 13) that has been in use for many years. Figure 2 is schematic of the device used by Bekefi and Orzechowski (ref 5). The anode block (inner radius of 2.1 cm) has six vane-type resonators designed to oscillate at 3.0 GHz. Each resonator is 7.2 cm long. One of the resonators is provided with a slot through which the radiant energy is coupled into a microwave horn. The coaxial cathode is a graphite cylinder 4.8 cm in radius. It is connected via a steel shank to a Nereus (ref 43) pulse line. The entire system, including the transmitting horn, is pumped to pressures less than  $10^{-6}$  torr. The axial magnetic field acting on the diode is generated by two solenoids mounted in an approximate Helmholtz-pair configuration.




Figure 2. Magnetron diode.

Typical operating parameters for this system are ~12 kA of cathode current, an accelerating potential of ~360 kV, and an 8-kG axial magnetic field. Linearly polarized microwaves of 30-ns duration with a power level of 1.7 GW are produced. This represents a conversion efficiency of electron energy into microwave energy of about 35 percent. Work is under way at the Naval Research Laboratory (NRL) to increase this efficiency still further.

## 2.2 Stimulated Raman Scattering

During the last few years investigators have observed high-powered millimeter and submillimeter radiation from intense REB's undergoing stimulated Raman scattering (ref 19, 26, 28, 37, 38, 49.) In this coherent interaction, a low-frequency electromagnetic pump wave is backscattered from an REB to yield radiation whose frequency is much larger than that of the pump wave (ref 52).

Presently, there are two methods of providing an adequate pump wave: (1) by generating an electromagnetic wave to serve as the pump (ref 28) and (2) by propagating the electron beam through a spatially rippled magnetic field (ref 19, 38). Two zero frequency pumped (method two) Raman scattering experiments are considered: (1) an experiment employing a 1.4-cm period rippled magnetic field (ref 19) and (2) one using a 6-mm pitched helical undulator (ref 38). For the 1.4-cm period experiment (shown in fig. 3), the drift tube is a coaxial waveguide with alternating brass and iron rings internally loaded in the center conductor. The electron-beam parameters are 750 kV and 10 kA, and power levels of 1 to 5 MW are measured at 7-mm wavelengths. In the helical configuration, the beam propagates in a smooth iron tube with a deep-grooved helical screw of 6-mm pitch maintained in the outer wall. In this case, the beam parameters are 860 kV and 12 kA. Power levels of 6 to 8 MW are measured at 2 mm and 0.1 to 1.0 MW at 1 mm. In both cases, the power levels depend on the magnetic field which is varied from 6 to 12 kG.




Figure 3. Typical Raman scattering experiment.



### 2.3 Gyrotron

Figure 4 shows the most popular configuration of the gyrotron (ref 17, 22, 57) (or electron cyclotron maser), namely, the axisymmetric gyrotron. The symmetry originates with the solenoid creating the magnetic field. Because of this symmetry, a cathode with a large emitting surface can produce an intense flow of electrons with rather small velocity dispersion. The flow undergoes compression by the magnetic field which increases in the direction from the cathode to the interaction space. The compression section represents a reversed magnetic mirror (shown in fig. 4) where the initial cathode orbital velocity of electrons (ref 38) grows according to the adiabatic invariance of magnetic moment. Here the orbital energy is drawn from that of the longitudinal motion and from the accelerating electrostatic field. In the interaction space, the electrons are guided by quasi-uniform magnetic fields. Escaping it, they enter the region of decreasing field (decompression section) and then settle on the surface of the collector.




Figure 4. Common gyrotron arrangement.

In the interaction region, where the electron velocity is almost entirely transverse to the magnetic field, phase bunching can occur because of the relativistic mass change of the electrons (ref 23). Electrons absorbing radiation become massive and slip back in phase while electrons emitting radiation become less massive and advance in phase. This phase bunching of gyrating electrons causes the coherence of the measured radiation. The ultimate phase distribution favors emission over absorption, thus enhancing the intensity of the wave. Some experimental results are given in table I.

TABLE 1. PEAK POWER LEVELS FROM CYCLOTRON MASERS (GYROTRONS) DRIVEN BY INTENSE REB.

Wavelength (cm)	Peak microwave power (MW)	Accelerating voltage (MV)	Diode current (kA)
4	900	3.3	80
2	350	2.6	40
0.8	8	0.6	15
0.4	2	0.6	15

#### 2.4 Other Schemes

The generation of coherent Cerenkov radiation has been observed by several researchers (ref 9, 34), including ones at Dartmouth College and Columbia University (ref 54, 53). In their experiments, they used a modest 0.5-MeV, 10-kA electron beam with a foilless diode to generate 1 MW of microwave power at frequencies from 35 to 75 GHz (4 to 10 mm).

Intense microwave emission has also been observed during reflex triode operation at the Harry Diamond Laboratories (ref 7) and at NRL (ref 36) where 10 and 90 MW were measured in K<sub>a</sub> and X microwave frequency bands.

Although there are many more schemes that have not been discussed (ref 4, 8, 14, 15, 27, 29, 33, 35, 44, 50, 51, 56) it should be clear that intense REB's can be used to produce large amounts of microwave power at a very wide range of frequencies.

### 3. ELECTRON-BEAM GENERATORS

Capabilities for producing intense REB's (ref 21) have increased dramatically over the last several years. Although most of the industry's attention has been devoted to the super-high-power generators like the AURORA (10 MeV, 1 MA) (ref 6) and the PROTO II (1.5 MeV, 4.5 MA) (ref 39) facilities, a great deal of work has been done on improving the reliability, reproducibility, and repetition rate of the smaller (0.25 to 2 MeV, 5 to 30 kA) machines. A sampling of some of these electron-beam machines is listed in tables II and III. Two of these machines are discussed in more detail.

TABLE 11. SAMPLING OF SOVIET REPETITIVELY PULSED REB MACHINES

Machine	Year	V <sub>max</sub> (KV)	I <sub>max</sub> (A)	Pulse length (μs)	PRF <sup>a</sup> (Hz)	P <sub>avg</sub> (KW)	P <sub>max</sub> (MW)	Reference
ELITA-500	1971	500	1.5	5	300	1	0.7	1
ELITA-1	1971	1000	15	4	300	8	10	
ELITA-1.3	1971	1500	100	0.05-3	100	2	150	
ELITA-3	1971	3000	40	10	300	20	100	
ELT1	1971	1300	0.07	6000	50	15	0.09	
ELT2	1971	1800	0.12	6000	50	25	0.215	
PRT	1971	1200	0.08	5000	50	10	0.295	
TEUS-15	1971	1200	0.125	?	?	150	?	
RIUS-5	1971	5000	30000	0.04	0.005	(0.03)	150000	2
ELT 1.5	1967	1500	20	?	50	?	30000	
ELT 2.5	1967	2500	?	?	50	?	?	
ELIT 1	1967	1000	100	0.06	50	3	100	
ELIT 3	1967	3000	?	?	100	?	?	3
-- <sup>c</sup>	1976	1400	50	0.03-1	100	5	(70)	
--	1976	1200	150	0.2	50	0.45	180	
--	1976	250	4000	0.015	?	?	?	
	1976	2300	?	1000	?	?	?	PORTABLE

<sup>a</sup>Pulse repetition frequency<sup>b</sup>numbers in parentheses are inferred<sup>c</sup>-- = machines not named

TABLE III. SAMPLING OF U.S. REPETITIVELY PULSED REB MACHINES

Machine <sup>a</sup>	Year	V <sub>max</sub> (kV)	I <sub>max</sub> (kA)	Pulse length (μs)	PRF (Hz)	P <sub>avg</sub> (kW)	P <sub>max</sub> (MW)	Built by	Reference
-- <sup>b</sup>	1973	125	20	0.04	1/60	?	(2.5) <sup>c</sup>	Berkeley	41
--	1976	407	7	10	125	500	?	Maxwell	12 (Burst 30 to 75 s)
--	1976	240	1000	25	10	(6000)	(240000)	Maxwell	20 (Burst 60 s)
--	1976	75	60	?	10	?	(4500)	Sandia	55
CCEBL	1976	350	3	5	50	(700)	(2800)	Army	16
--	1975	6	6	20	300	62.5	(36)	Westing- house	24
Modified Trace	1978	350	30	0.03	100	30	(10)	Sandia	47
--	1976	100	?	?	1	?	?	Maxwell	40 from modules
--	1973	35	0.015	2.5	44000	(60)	(0.525)	SLAC <sup>d</sup>	18
TRADEX	1973	130	0.14	3-128	(1000)	(0.072)	(18)	RCA	11 Burst
--	1973	78	(0.04)	16-32- 55	75-210 -300	22.6	3.27	Westing- house	31
--	1973	120	(0.083)	7.5	300	20	10	Westing- house	31
--	1973	185	0.16	2.5	360	65	30	SLAC	48

<sup>a</sup> For additional machines, see table I in reference 54.

<sup>b</sup> -- = machines not named

<sup>c</sup> Numbers in parentheses are inferred.

<sup>d</sup> SLAC = Stanford Linear Accelerator

### 3.1 Nereus Relativistic Electron-Beam Generator

Nereus machines (ref 43) are used as the electron-beam source in several of the microwave-generating schemes discussed in the preceding sections. Although they can easily be modified (and some have been) to produce higher voltages with less current, the basic machine delivers a single 80-kA pulse 250 to 400 keV with a pulse length of 30 ns.

The Nereus generator is an example of "classic" electron-beam machine design. An oil-insulated Marx Generator is used to charge a water-dielectric transmission line. This transmission line is then discharged by a polyethylene switch, past a prepulse resistor, through a vacuum diode. The entire facility could easily be placed on the back of a small flatbed truck.

### 3.2 High-Repetition-Rate Trace Machine

The original TRACE electron-beam generator (ref 45) is a simple compact machine in which a transformer is used to charge a Nereus pulse-forming line (PFL). This system is approximately 1.5 m long, 0.6 m wide, and 1.2 m high and includes all system components mounted on a roll-around platform except for the control panel and vacuum roughing pump. The system is designed to operate with up to 500 keV on the PFL and to generate a 100-kA, 30-ns electron beam.

Using this pulser as a starting point, a program to develop a series of repetitively pulsed generators has been undertaken at Sandia Laboratories (ref 47) beginning with a pulser designed to deliver 350-keV, 300-J, 100-ns pulses at a continuous rate of 100 per second. From these specifications, the output current is 8.6 kA and the generator impedance is 41 ohms. The machine that was actually built (ref 46) has a shorter pulse length (30 ns) and a correspondingly high current (30 kA).

The working system (shown in fig. 5) consists of a low-voltage modulator section, a voltage step-up transformer, a PFL, a high-voltage switch, and a load resistor or diode. The modulator converts dc power at 10 kV to primary pulsed power at 20 kV by resonant charging a 1.5- $\mu$ F capacitor from a 14.5- $\mu$ F capacitor. When the 1.5- $\mu$ F capacitor is subsequently discharged through the primary of the voltage step-up transformer, the PFL is charged to 700 kV. Near the peak of the charge cycle, the output switch closes and energizes the load. At full voltage and 100 pulses per second, the average power output of the system is 30 kW.




Figure 5. Pulser assembly including (1) 120-kV power supply, (2) primary storage capacitor ( $14 \mu\text{F}$ ), (3) charging inductor ( $300 \mu\text{H}$ ), (4) slow transfer interstage switch, (5) secondary storage capacitor ( $1.5 \mu\text{F}$ ), (6) high current switch, (7) transformer high-voltage shield (oil filled), (8) transformer, windings, and central high-voltage bus shown schematically, (9) helical pulse forming line, (10) high-voltage output switch, and (11) cylindrical salt water load resistor.

The complete pulser system has undergone tests up to 100 pulses per second at 15-kW average power and 30 pulses per second at full voltage. A total of  $2 \times 10^6$  shots was fired during the preliminary trials with individual runs of up to  $1.5 \times 10^5$  shots. During these test runs, there were no major component failures or heat buildup problems.

### 3.3 Hypothetical Relativistic Electron-Beam Microwave Generating System

The relativistic magnetron described by Bekefi and Orzechowski (ref 5) was driven by an electron beam that delivered about 12 kA at 360 keV. Linearly polarized microwaves at powers of 1.7 GW were measured at 3 GHz; the efficiency of converting electron energy into microwave radiation was 35 percent. If this experiment were driven by the repetitive generator described in the previous section (with its 30-kA output), the peak microwave output should increase by a factor of 2 to 3 to yield about 5 GW per shot at a conservative repetition rate of 30 pulses per second. This would only correspond to about 5 kW of average radiated power, but this represents an impressive "first step" towards using and developing these techniques.

It should be noted that much work would need to be done if this hypothetical system were to be constructed. The most important problem would be to determine whether REB could be operated repetitively.

The major effects to be analyzed and measured in determining the feasibility of interfacing a repetitive-pulse power supply and a super-high-power REB microwave source are (1) the thermal loading produced by electrons and ions hitting the anode and cathode of the microwave device, (2) the magnitude of plasma abrasion upon the anode and cathode, and (3) the effect of plasma formation on insulator flashover recovery time. Even at very low repetition rates (one shot every few minutes) where physics and engineering problems begin to disappear, the large bursts of generated energy must still be coupled into some sort of antenna.

Thus far, the evaluation of REB microwave-generation schemes has been conservative. Since no determination of physical limitations has been made, the potential of the merger of these two technologies should also be considered with cautious optimism. A program is under way at NRL and at the Massachusetts Institute of Technology to double the efficiency of the REB magnetron to about 70 percent, it is hoped. Also, the goal for the next generation of repetitively pulsed electron-beam machines at Sandia Laboratories is to exceed the first generation by a factor of ten. If this can be translated directly into microwave power at 70-percent efficiency, then the output would rise to nearly 100 GW per shot at 100 shots per second for an average power radiated of 100 kW. If these improvements do not require any gross increases in component size, the entire system would remain easily transportable. Of course, the above system represents a large amount of extrapolation, but repetitively pulsed electron-beam technology is in its infancy and it is impossible to predict how far and how fast the field will develop.

#### 4. CONCLUSIONS

Many different ways of converting REB energy into radiated microwaves have been demonstrated in laboratories around the world. The frequency of the generated radiation varies from 1 to 100 GHz with power levels up to several gigawatts.

Although the super-high-power REB generators like AURORA and PROTO are unreliable and inconsistent--as were their predecessors--a new generation of REB machines has begun to fill in the gaps behind them. These "new" generators (like the Nereus and TRACE machines) are characterized by high efficiency, compact size, reliable operation, reproducible output, and widely varying output ranges. Microwave engineers who are interested in an ability to produce exceptionally high peak powers and increasingly higher average powers should not overlook the attractive possibilities of REB microwave generation.

# SELECTED BIBLIOGRAPHY

- (1) E. A. Abramyan, Transformer Type Accelerators for Intense Electron Beams, IEEE Trans. Nucl. Sci., NS-18, No. 3 (1971).
- (2) E. A. Abramyan, On Possibilities of Transformer Type Accelerators, Nuclear Instr. and Methods, 59 (1968).
- (3) E. A. Abramyan, High-Voltage Pulse Generators of the Base of the Shock Transformer, Int'l Pulsed Power Conf., Lubbock, TX (1976).
- (4) B. I. Aronov, L. S. Bogdankevitch, and A. A. Rukhadze, The Excitation of Coherent Electromagnetic Radiation in Plasma Waveguides by Relativistic Electron Beams, Plasma Physics, 18 (1976), 101-121
- (5) G. Bekefi and T. J. Orzechowski, Giant Microwave Bursts Emitted from a Field Emission Relativistic Electron Beam Magnetron, Phys. Rev. Lett, 37, No. 6 (9 Aug 1976).
- (6) B. Bernstein and I. Smith, AURORA, An Electron Accelerator, IEEE Trans. Nucl. Sci., NS-20, No. 3 (1973).
- (7) H. E. Brandt, A. Bromborsky, H. B. Bruns, and R. A. Kehn, Microwave Generation in the Reflex Triode, Proc. of the 2nd Int'l Topical Conf. on High Power Electron and Ion Beam Research and Technology (1977).
- (8) J. M. Buzzi, H. J. Doucet, B. Etlicker, J. C. Faure, P. Haldenwang, A. Huetz, H. Lamain, C. Rouille, J. C. Cabi, J. Delvaux, J. C. Jonys, C. Peugnet, and M. Roche, Experimental Evidence of Relativistic Doppler Frequency Conversion on a Relativistic Electron Beam Front, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (June 1977).
- (9) Y. Carmel, J. Ivers, R. E. Kribel, and J. Nation, Intense Coherent Cherenkov Radiation due to the Interaction of a Relativistic Electron Beam with a Slow-Wave Structure, Phys. Rev. Lett., 33, No. 21 (18 November 1974).
- (10) Y. Carmel and J. A. Nation, Application of Intense Relativistic Electron Beams to Microwave Generation, J. Appl. Phys., 44, No. 12 (December 1973).
- (11) R. N. Casolaro, TRADEX S-Based Transmitter Modulator, Proc. of the 11th Modulator Symposium (1973).



# SELECTED BIBLIOGRAPHY (Cont'd)

- (12) J. E. Creedon and R. A. Fitch, A Half-Megawatt Pulse Forming Network (PFN), Int'l Pulse Power Conf., Lubbock, TX (November 1976).
- (13) G. B. Collins, Microwave Magnetrons, McGraw-Hill, New York (1948).
- (14) D. A. G. Deacon, L. R. Elias, J. M. Madey, G. J. Ramian, H. A. Schwettman, and T. I. Smith, First Operation of a Free-Electron Laser, Phys. Rev. Lett., 38, No. 16 (18 April 1978).
- (15) W. W. Destler, D. W. Hudgings, M. J. Rhee, S. Kawasaki, and V. L. Granatstein, Experimental Study of Microwave Generation and Suppression in a Non-Neutral E-Layer, J. Appl. Phys., 48, No. 8 (August 1977).
- (16) G. J. Dezenberg, W. Wright, and S. Schneider, Modulator Repetitively Pulsed Field Emission Electron Beam Bun Interface, Proc. Int'l Pulsed Power Conf., Lubbock, TX (November 1976).
- (17) A. N. Didenko, A. G. Zherlitsyn, V. I. Zelentsov, A. S. Sulakshin, G. P. Fomenko, Yu. G. Shtein, and Yu. G. Yushkov, Generation of Gigawatt Microwave Pulses in the Nanosecond Range, Sov. J. Plasma Phys., 2, No. 3 (1976).
- (18) R. A. Ecken, L. Genova, 600 kW Peak High Repetition Rate Hard Table Modulator, Proc. of the 11th Modulator Symposium (1973).
- (19) P. C. Efthimion and S. P. Schlesinger, Stimulated Raman Scattering by an Intense Relativistic Electron Beam in a Long Rippled Magnetic Field, Phys. Rev. A, 16, No. 2 (August 1977)
- (20) R. A. Fitch, Six-Megawatt (Mean Power) Pulse Generator, Proc. of the 1976 Pulsed Power Workshop, NSWC, White Oak, MD.
- (21) H. H. Fleischmann, High-Current Electron Beams, Physics Today (May 1975).
- (22) V. A. Flyagin, A. V. Gaponov, M. I. Petelin, and V. K. Yulpatov, The Gyrotron, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (1977).
- (23) A. V. Gaponov and V. K. Yulpatov, Interaction of Helical Electron Beams with the Electromagnetic Field in a Waveguide, Radio Engineering and Electronic Physics, 12, No. 4 (1967).

# SELECTED BIBLIOGRAPHY (Cont'd)

- (24) R. A. Gardenghi, E. H. Hooper, and F. S. Zimmermann, A 12.5 Megawatt Module for High Energy Pulsers, Proc. of the 1976 Pulsed Power Workshop, NSWC, White Oak, MD.
- (25) V. L. Granatstein and T. F. Godlove, Relativistic Electron Beam Interactions for Generation at High Power at Microwave Frequencies, Naval Research Laboratory, NRL-MR-367 (March 1978).
- (26) V. L. Granatstein, R. K. Parker, J. A. Pasour, P. Sprangle, and A. T. Drobot, Coherent Microwave Scattering from Intense Relativistic Electron Beams--A Powerful, Tunable Source of Millimeter and Submillimeter Radiation, Proc. of the 2nd Int'l Topical Conf. on High Power Electron and Ion Beam Research and Technology (1977).
- (27) V. Granatstein, C. Roberson, G. Benford, D. Tzach, and S. Robertson, Observation of Coherent Curvature Radiation from an Intense Relativistic Electron Beam in a Background Plasma, UCI Technical Report No. 45 (1977).
- (28) V. L. Granatstein, S. P. Schlesinger, M. Herndon, R. K. Parker, and J. A. Pasour, Production of Megawatt Submillimeter Pulses by Stimulated Magnetic-Raman Scattering, Appl. Phys. Lett., 30, No. 8 (15 April 1977).
- (29) V. L. Granatstein and P. Sprangle, Mechanisms for Coherent Scattering of Electromagnetic Waves from Relativistic Electron Beams, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (June 1977)
- (30) D. A. Hammer, M. Friedman, V. L. Granatstein, M. Herndon, W. M. Manheimer, R. K. Parker, and P. Sprangle, Microwave Production with Intense Relativistic Electron Beams, Annals of the New York Academy of Sciences.
- (31) R. A. Hill and R. A. Smith, Application of the RSR Switch, Proc. of the 11th Modulator Symposium (1973).
- (32) J. L. Hirshfield and V. L. Granatstein, The Electron Cyclotron Maser, An Historical Survey, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (June 1977).

# SELECTED BIBLIOGRAPHY (Cont'd)

- (33) F. A. Hopf and P. Meystre, Theoretical Development of the Free-Electron Laser from Cooperative Effects in Matter and Radiation, edited by C. M. Bowden, D. W. Howgate, and H. R. Robl, Plenum Press, New York (1977).
- (34) N. F. Kovalev, M. I. Petelin, M. D. Raizer, A. V. Smorgonskii, and L. E. Tsopp, Generation of Powerful Electromagnetic Radiation Pulses by a Beam of Relativistic Electrons, Zh. Eksp. Teor. Fiz. Pisma Red. 18, No. 4 (20 August 1973), 232-235.
- (35) M. Lampe, E. Ott, W. M. Manheimer, and S. Kainer, Submillimeter-Wave Production by Upshifted Reflection from a Moving Ionization Front, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (June 1977).
- (36) R. A. Mahaffey, P. Sprangle, J. Goldan, and C. A. Kapetanakis, High-Power Microwaves from a Nonisochronic Reflecting Electron System, Phys. Rev. Lett., 39, No. 13 (26 September 1977).
- (37) T. C. Marshall, F. L. Sandel, and R. M. Gilgenback, Millimeter Wave Generation Through Stimulated Scattering with an Intense Relativistic Electron Beam, Proc. of the 2nd Int'l Topical Conf. on High Power Electron and Ion Beam Research and Technology (1977).
- (38) T. C. Marshall, S. Talmadge, and P. Efthimion, High-Power Millimeter Radiation from an Intense Relativistic Electron Beam Device, Appl. Phys. Lett., 31, No. 5 (September 1977).
- (39) T. H. Martin, D. L. Johnson, and D. H. McDaniel, Super Power Generators, Proc. of 2nd Int'l Topical Conf. on High Power Electron and Ion Beam Research and Technology (1977).
- (40) Maxwell Laboratories' advertising literature, Engineering Bulletin No. 1003 (15 January 1976).
- (41) B. Meyers, S. Eylon, and M. A. Lieberman, Low Impedance Intense Electron Beam Device, Rev. Sci. Instrum., 46, No. 10, (October 1975).
- (42) T. J. Orzechowski, G. Bkefi, A. Palevsky, W. M. Black, S. P. Schlensinger, V. L. Granatstein, and R. K. Parker, Microwave Radiation from a Magnetron Driven by a 0.2 Terawatt Relativistic Electron Accelerator, Bull. Am. Phys. Soc., 21 (1976), 1112.

SELECTED BIBLIOGRAPHY (Cont'd)

- (43) K. R. Prestivich, Nereus, A 250 kV, 80 kA Electron Beam Generator, IEEE Trans. Nucl. Sci., NS-18 (1971).
- (44) G. Providakes, J. A. Nation, and M. E. Read, Microwave Generation Using Sheet Relativistic Electron Beams, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (June 1977).
- (45) G. J. Rohwein, TRACE I, A Transformer-Charged Electron Beam Generator, IEEE Trans. Nucl. Sci., NS-22, No. 6 (June 1977).
- (46) G. J. Rohwein and M. T. Buttram, Preliminary Design of a 100 Hz, 350 kV Short Pulse Generator, Sandia Report No. SAND77-0174 (1977).
- (47) G. J. Rohwein, M. T. Buttram, and K. R. Prestwich, Design and Development of a 350 kV, 100 pps Electron Beam Accelerator, Proc. of the 2nd Int'l Conf. on High Power Electron and Ion Beam Research and Technology (1977), 845-853.
- (48) R. M. Rowe, Pulse Group Operation of High Power Line Type Modulators, Proc. of the 11th Modulator Symposium (1973).
- (49) S. P. Schlesinger and P. C. Efthimion, Zero Frequency Pumped Stimulated Raman Scattering by an Intense Relativistic Electron Beam, Proc. of the 2nd Int'l Topical Conf. on High Power Electron and Ion Beam Research and Technology (1977).
- (50) S. Schneider and R. Spitzer, Interaction of Coherent Electromagnetic Waves with Relativistic Electrons in a Medium, Nature, 250 (23 August 1974), 643-644.
- (51) S. Schneider and R. Spitzer, Application of Stimulated Electromagnetic Shock Radiation to the Generation of Intense Submillimeter Waves, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (June 1977).
- (52) P. Sprangle, V. L. Granatstein, and L. Baker, Stimulated Collective Scattering from a Magnetized Relativistic Electron Beam, Phys. Rev. A, 12, No. 4 (October 1975).
- (53) J. E. Walsh, T. C. Marshall, M. R. Moss, and S. P. Schlesinger, Relativistic Electron-Beam-Generated Coherent Submillimeter Wavelength Compton Radiation, IEEE Trans. Microwave Theory Tech., MTT-25, No. 6 (1977).

SELECTED BIBLIOGRAPHY (Cont'd)

- (54) J. E. Walsh, T. C. Marshall, and S. P. Schlesinger, Generation of Coherent Cerenkov Radiation with an Intense Relativistic Electron Beam, *Phys. of Fluids*, 20, No. 4 (1977).
- (55) R. A. White, High-Energy Repetitive-Pulse Underwater Spark-Explosion Generator Design, Proc. of the 1976 Pulsed Power Workshop, NSWC, White Oak, MD.
- (56) F. Winterberg, On the Possibility to Generate Powerful Bursts of Microwaves by the Interaction of an Intense Relativistic Electron Beam with a Magnetized Plasma, *Atomkernenergie (ATKE)* Bd. 22 Lfg. 3 (1973).
- (57) N. I. Zaytsev, T. B. Pankratova, M. I. Petelin, and V. A. Flyagin, Millimeter and Submillimeter Wave Gyrotrons, *Radio Engineering and Electronic Physics*, 19, No. 5 (1974).

## DISTRIBUTION

ADMINISTRATOR  
DEFENSE DOCUMENTATION CENTER  
ATTN DDC-TCA (1.3 COPIES)  
CAMERON STATION, BUILDING 5  
ALEXANDRIA, VA 22314

COMMANDER  
US ARMY RSCH & STD GP (EUR)  
ATTN LTC JAMES M. KENNEDY, JR.  
CHIEF, PHYSICS & MATH BRANCH  
FPO NEW YORK 09510

COMMANDER  
US ARMY MATERIEL DEVELOPMENT &  
READINESS COMMAND  
ATTN DRXAM-TL, HQ TECH LIBRARY  
5001 EISENHOWER AVENUE  
ALEXANDRIA, VA 22333

COMMANDER  
US ARMY MISSILE & MUNITIONS  
CENTER & SCHOOL  
ATTN ATSK-CTD-F  
REDSTONE ARSENAL, AL 35809

DIRECTOR  
US ARMY MATERIEL SYSTEMS  
ANALYSIS ACTIVITY  
ATTN DRXSY-MP  
ABERDEEN PROVING GROUND, MD 21005

DIRECTOR  
US ARMY BALLISTIC RESEARCH  
LABORATORY  
ATTN DRDAR-TSB-S (STINFO)  
ABERDEEN PROVING GROUND, MD 21005

DEPARTMENT OF COMMERCE  
NATIONAL BUREAU OF STANDARDS  
WASHINGTON, DC 20234  
ATTN LIBRARY

US ENERGY RESEARCH & DEVELOPMENT  
ADMINISTRATION  
WASHINGTON, DC 20545  
ATTN OFFICE OF TECHNICAL INFORMATION

DIRECTOR  
DEFENSE ADVANCED RESEARCH  
PROJECTS AGENCY  
ARCHITECT BLDG  
1400 WILSON BLVD  
ARLINGTON, VA 22209  
ATTN DIR, STRATEGIC TECH OFFC  
ATTN DIR, TACTICAL TECH OFFC  
ATTN DIR, TECH ASSESSMENTS

DIRECTOR  
ARMED FORCES RADIOBIOLOGY  
RESEARCH INSTITUTE  
DEFENSE NUCLEAR AGENCY  
NATIONAL NAVAL MEDICAL CENTER  
BETHESDA, MD 20014

DIRECTOR  
DEFENSE COMMUNICATIONS AGENCY  
NATIONAL MILITARY COMMAND  
SYSTEM SUPPORT CENTER  
WASHINGTON, DC 20301  
ATTN TECHNICAL DIRECTOR

DIRECTOR  
DEFENSE COMMUNICATION ENGINEERING  
1860 WIEHLE AVE  
RESTON, VA 22090  
ATTN TECHNICAL LIBRARY

DIRECTOR  
DEFENSE INTELLIGENCE AGENCY  
WASHINGTON, DC 20301  
ATTN DEP DIR FOR SCI  
& TECH INTELLIGENCE  
ATTN DT-2, WEAPONS & SYSTEMS DIV

DIRECTOR  
DEFENSE NUCLEAR AGENCY  
WASHINGTON, DC 20305  
ATTN PETER HAAS, DEP DIR,  
SCIENTIFIC TECHNOLOGY  
ATTN RAEV, ELECTRONIC VULNERABILITY  
ATTN TISI, LIBRARY

DISTRIBUTION (CONT'D)

UNDER SECRETARY OF DEFENSE  
FOR RESEARCH & ENGINEERING  
WASHINGTON, DC 20301  
ATTN DEP DIR (RESEARCH &  
ADVANCED TECH)

BALLISTIC MISSILE DEFENSE  
PROGRAM MANAGER OFFICE  
COMMONWEALTH BUILDING  
1300 WILSON BLVD  
ARLINGTON, VA 22209  
ATTN DACS-BMT, TECH DIR  
ATTN DACS-BMT, ASST FOR PHYSICS/DIS

COMMANDER  
BALLISTIC MISSILE DEFENSE ADVANCED  
TECHNOLOGY CENTER  
PO BOX 1500  
HUNTSVILLE, AL 35807  
ATTN DIRECTOR, ATC-X

COMMANDER  
US ARMY ELECTRONICS COMMAND  
OFC OF MSL ELECTRONIC WARFARE  
WHITE SANDS MISSILE RANGE, NM 88002

COMMANDER  
US ARMY FOREIGN SCIENCE  
& TECHNOLOGY CENTER  
FEDERAL OFFICE BLDG  
220 7TH STREET, NE  
CHARLOTTESVILLE, VA 22901  
ATTN DRXST-SD, SCIENCES DIV

ARMY RESEARCH OFFICE (DURHAM)  
PO BOX 12211  
RESEARCH TRIANGLE PARK, NC 27709  
ATTN TECH LIBRARY  
ATTN DR. LEFKOWITZ

CHIEF OF NAVAL RESEARCH  
DEPT OF THE NAVY  
ARLINGTON, VA 22217  
ATTN ONR-420, PHYSICAL SCI DIV  
ATTN TECHNICAL LIBRARY

COMMANDER  
NAVAL AIR SYSTEMS COMMAND HQ  
DEPARTMENT OF THE NAVY  
WASHINGTON, DC 20361  
ATTN DR. RICHARD WASNESKI

DIRECTOR  
NAVAL RESEARCH LABORATORY  
WASHINGTON, DC 20375  
ATTN PLASMA PHYSICS DIVISION

COMMANDER  
NAVAL SURFACE WEAPONS CENTER  
WHITE OAK, MD 20910  
ATTN WA-51, ELECTROMAGNETIC PULSE  
TECHNOLOGY BR  
ATTN WR, RESEARCH & TECHNOLOGY  
DEPARTMENT  
ATTN WR-40, RADIATION DIVISION  
ATTN WR-43, ELECTROMAGNETICS BRANCH

DIRECTOR  
AF AVIONICS LABORATORY  
WRIGHT-PATTERSON AFB, OH 45433  
ATTN KJD (TEM), MICROWAVE TECH BR  
ATTN KJE (TER), ELECTRONIC RES BR

DIRECTOR  
AF OFFICE OF SCIENTIFIC RESEARCH  
BOLLING AFB  
WASHINGTON, DC 20332  
ATTN NP, DIR OF PHYSICS  
ATTN CPT R. GULLICKSON

UNIVERSITY OF MARYLAND  
COLLEGE PARK, MD 20740  
ATTN DR. W. W. DESTLER  
ATTN DR. M. J. RHEE

LABORATORY OF PLASMA SCIENCE  
CORNELL UNIVERSITY  
ITHACA, NY 14850  
ATTN DR. J. A. NATION  
ATTN DR. D. A. HAMMER

# DISTRIBUTION (CONT'D)

PHYSICS DEPARTMENT  
MASSACHUSETTE INSTITUTE OF  
TECHNOLOGY  
CAMBRIDGE, MA 02139  
ATTN DR G. BEKEFI

SANDIA LABORATORIES  
ALBUQUERQUE, NM 87115  
ATTN DIVISION 5246  
ATTN G. J. ROHWEIN

PHYS. DEPARTMENT  
COLUMBIA UNIVERSITY  
NEW YORK, NY 10027  
ATTN DR. S. P. SCHLESINGER

PHYS. DEPARTMENT  
DARTMOUTH COLLEGE  
HANOVER, NH 03755  
ATTN J. E. WALSH

PHYS. DEPARTMENT  
UNIVERSITY OF CALIFORNIA  
IRVINE, CA 92664  
ATTN DR. G. BENFORD

DEPARTMENT OF PHYS.  
USMA  
WEST POINT, NY 10996  
ATTN CPT LASCHE

US ARMY ELECTRONICS RESEARCH  
& DEVELOPMENT COMMAND  
ATTN WISEMAN, ROBERT S., DR.,  
DRDEL-CT  
ATTN PAO  
ATTN PEPPER, W. H., DRDEL-AP-CCM  
ATTN IRISH, LTC KENNETH

HARRY DIAMOND LABORATORIES  
ATTN 00100, COMMANDER/TECHNICAL  
DIR/TSO  
ATTN CHIEF, 00210  
ATTN CHIEF, DIV 10000  
ATTN CHIEF, DIV 20000  
ATTN CHIEF, DIV 30000  
ATTN CHIEF, DIV 40000  
ATTN CHIEF, LAB 11000  
ATTN CHIEF, LAB 13000  
ATTN CHIEF, LAB 15000  
ATTN CHIEF, LAB 22000  
ATTN CHIEF, LAB 21000  
ATTN CHIEF, LAB 34000  
ATTN CHIEF, LAB 36000  
ATTN CHIEF, LAB 47000  
ATTN CHIEF, LAB 48000  
ATTN RECORD COPY, 94100  
ATTN HDL LIBRARY, 41000 (5 COPIES)  
ATTN HDL LIBRARY, 41000 (WOODBRIDGE)  
ATTN CHAIRMAN, EDITORIAL COMMITTEE  
ATTN TECHNICAL REPORTS BRANCH, 41300  
ATTN LEGAL OFFICE, 97000  
ATTN LANHAM, C., 00210  
ATTN WILLIS, B., 47400  
ATTN BROMBORSKY, A., 22300  
(10 COPIES)  
ATTN KEHS, R. A., 22300 (15 COPIES)  
ATTN BRANDT, H. E., 22300  
ATTN KULPA, S., 15400  
ATTN HALPIN, J., 22800  
ATTN OLDHAM, T., 22300  
ATTN SCHALLHORN, D., 22300  
(2 COPIES)  
ATTN GRAYBILL, S. E., 22900  
ATTN CALDWELL, P. A., 22900  
ATTN WHITTAKER, D., 22900  
ATTN SILVERSTEIN, J., 22900  
ATTN ROSADO, J., 22100  
ATTN DANDO, J. 21400  
ATTN CHIEF, BR 13200  
ATTN WILLETT, C., 15400  
ATTN CIRINCIONE, G. V., 15300  
ATTN CHIEF, BR 21100  
ATTN CHIEF, BR 21200  
ATTN CHIEF, BR 21300  
ATTN CHIEF, 21500