

FTD-ID(RS)T-0933-78

FOREIGN TECHNOLOGY DIVISION



67106

INVESTIGATION OF SUPERSONIC THREE-DIMENSIONAL FLOW ABOUT SEGMENTAL BODIES

by

V. B. Minostsev





Approved for public release; distribution unlimited.

.

FTD -ID(RS)T-0933-78

EDITED TRANSLATION

FTD-ID(RS)T-0933-78

28 June 1978

MICROFICHE NR: 4D-79-C-000046

INVESTIGATION OF SUPERSONIC THREE-DIMENSIONAL FLOW ABOUT SEGMENTAL BODIES

By: V. B. Minostsev

English pages: 22

Source: Trudy Sektsii po Chislovym Metodam v Gazodinamike 2-60 Mezhdunarodnogo Kollokviuma po Gazodinamike Vzryva i Reagiruyushchikh Sistem, 1969, Vol 2, 1971, PP. 68-86.

NTIS	White Section
DDC	8 tr Section
IDSTI ICA	i"i
	• • • • • • • • • • • • • • • • • • • •
DISTRIBUT	ION/AVA. ADMINY CODES
DISTRIBUT	ION/AVA: ACHINY IDOES
	ION/AVA ACHINY FOCES Special

Country of origin: USSR Translated by: Robert A. Potts Requester: FTD/TQTA Approved for public release; distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGI-NAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DI-VISION.

PREPARED BY:

TRANSLATION DIVISION FOREIGN TECHNOLOGY DIVISION WP-AFB, OHIO.

FTD -ID(RS)T-0933-78

Date 28 June19 78

79 03 06 111

Block	Italic	Transliteration	Block	Italic	Transliteration
A a	A a	A, a	Рр	Pp	R, r
Бб	Бб	B, b	Сс	C c	S, s
Вв	B •	V, v	Тт	Tm	T, t
Гг	Г :	G, g	Уу	Уу	U, u
Дд	Дд	D, d	Φφ	\$ \$	F, f
Еe	E e	Ye, ye; E, e*	Х×	X x	Kh, kh
жж	жж	Zh, zh	Цц	4 4	Ts, ts
З з	3 ,	Ζ, Ζ	Чч	4 4	Ch, ch
Ии	Ии	I, i	Шш	Шш	Sh, sh
Йй	A 1	Y, у	Щщ	Щщ	Shch, shch
Кк	<i>K K</i>	K, k	Ъъ	ъъ	"
лл	ЛА	L, 1	Ыы	Ы м	Y, у
n 19	Мм	M, m	ЬЬ	ь.	1
Нн	Ни	N, n	Ээ	э,	Е, е
0 0	0 0	0, 0	Юю	10 10	Yu, yu
Пп	Пп	P, p	Яя	Я я	Ya, ya

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

*ye initially, after vowels, and after ъ, ь; <u>е</u> elsewhere. When written as ё in Russian, transliterate as yё or ё.

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	sinh_1
cos	COS	ch	cosh	arc ch	cosh_1
tg	tan	th	tanh	arc th	tanh_1
ctg	cot	cth	coth	arc cth	coth_1
sec	sec	sch	sech	arc sch	sech_1
cosec	csc	csch	csch	arc csch	csch ⁻¹

Russian English rot curl lg log

.....

79 03 06 111

INVESTIGATION OF SUPERSCHIC THREE-DIMENSICIAL FLOW ABOUT SEGMENTAL EODIES

PIGE #/

V. B. Minostsev

In 1966 in the Institute of Mechanics of the Moscow State University under the leadership of Prof. G. F. Telenin an investigation was conducted of superscale three-dimensional flow about bodies of segmental shape. For calculation of flow there were used the methods discussed in [1, 2]. In these methods the gas-dynamic functions on the layers are represented by Lagrange polynomials on two variables, and for transition from layer to layer during calculation of the subsonic and transchic regions of flow there is solved a system of ordinary differential equations, during calculation of the supersonic region of flow there is used the method of characteristics. Some of the obtained results of investigations are presented in articles [2-5]. Since the developed methods are adapted for calculation of smooth flows, the contour of the segmental bodies was approximated by a single analytical formula [2-5]. The DOC = 0933

PAGE

2

utilized approximation made it possible to consider flow around bodies, the contour of which differs from that of the segmental body with break of generatrix wirtually cally in the region of the maximum cross section. Calculations are performed for numbers $M_{2} \ge 5$, angles of attack a to 30°, different central angles of the frontal spherical segnent ($2\theta^*$) and different generatrix argles of the rear cone (β). As a result of calculations there are obtained distributions of the gas-dynamic parameters in the shock layer and on the surface of the body, there are constructed shock waves and the patterns of distribution of lines of flow and isobars in the plane of symmetry of flow and on the surface of the body, there is investigated the effect of the real properties of gas on the pattern of flow, distribution of the gas-dynamic parameters and the aerodynamic characteristics. In the report attention is given only to the sain gualitative results, cbtained on the basis of analysis of calculation data. All the linear dimensions provided in the report pertain to the radius of curvature of the body at the forward point, pressure I to the product of the density of incident flow by the square of maximum velocity.

Figs. 1-6 show the results of calculation of flow around a body, close to sixty-degree spherical sector, on an example of which are examined the properties of flow around bodies of such shape. The pattern of flow around the frontal surface of the body at M_{∞} ... is provided in Fig. 1a, b, c. Solid lines depict the contour of the body. lines of flow and the shock wave, dashed lines - isobars $\frac{\rho}{\rho_{max}}$ (where ρ_{max} - pressure at the critical point, the position of which for angle of attack $a = 15^{\circ}$ is marked by an arrow on Fig. 1a), dot-dash - sound line. In Fig. 1 is given the pattern of flow in the plane of symmetry, Fig. 1b and c - on the frontal surface of the body. As calculations show, provided with various angles of attack, the pattern of flow around the frontal surface with increase of angle of attack is changed in the following manner: lines of flow, exiting the critical point, with the exception of the two lying in the plane of symmetry, acquire the preferred direction and at this point have cosson tangent, which is clearly seen in Fig. 1 c.



The derivative from the modulus of velocity on the length of the arc along the line of flow in the plane of symmetry exceeds the corresponding derivative in the direction of the common tangent, in perticular, with angle of attack 30°, by 2.5 times. The displacement of the critical point from the axis of symmetry turns out to be less than that calculated by Newton theory and, particularly, for angle of attack 30° by approximately 25 o/o. The flow line with maximum entropy lags behind the flow line arriving at the critical point, bowever, this lag even for angle of attack 30° turns out to be insignificant. The isobars and sound line are deformed, being condensed in the direction parallel to the plane of symmetry.

Fig. 2 shows the field of flow in the plane of symmetry and the prejection of the flow line to this plane or the surface of the body.







The shock wave, flow lines, isobars and sourd surface are depicted by the same lines as in Fig. 1. Since the calculations are conducted for

ideal gas, the question should be examined about the effect of viscosity on the obtained rattern of flow, distribution of gas-dynamic parameters and aerodynamic characteristics. Concerning the frontal surface, up to altitudes on the order of 60-70 km the boundary layer is still quite thin and the flow field outside it can te obtained from the calculations of flow by ideal gas. On the lateral surface separation can occur. The sagnitude of the separation zone is determined by the angle of attack, cecnetry of the body and conditions in the incident flow. It is natural that during calculation of ideal gas flow around the body it is impossible to calculate the flow in the separaticn zcne, however, the effect of the separation zone on the flow cutside it and the aerodynamic characteristics of the bcdy can be sufficiently well simulated during the calculation of flow arcund segmental bedies by ideal gas. Actually, during flow around the round area in the area of the maximum cross section there cccurs considerable acceleration of flow and sharp pressure drop, which on the leeward side at the surface of the body leads to the formation of a region of very low pressure, in which there is wirtually no gas. Sc the flcw density at the surface cf the body for the case represented in Fig. 2 cn the leeward side of flow is greater than an order lower than the flow density of the windward side of flow. If we take the isobar, corresponding to the experimental value of tase pressure, and take it as the boundary of the separation zone, and assume pressure in region $P < P_{out}$ equal to

 $P_{\partial ow}$, during calculation of flow by ideal gas we obtain simulation of the effect of the separation zone on the pattern of flow and the aerodynamic characteristics of the segmental body. The area, simulating the separation zone, is limited in Fig. 2 by broken line.

The physicochemical processes occurring in the shock layer during hypersonic flow arcund blunt bodies lead to considerable change of the values of gas-dynamic parameters. The conducted investigations [5] showed that the aerodynamic characteristics of ideal gas flow around segmental bodies in the case of near-equilibrium flow around frontal surface with rather high accuracy can be obtained from the calculations of flow around a given tody by some simulating ideal gas. In this case the flow around the frental surface is considered equilibrium, and the adiabatic inder for flow, simulating the given equilibrium flow, is selected from the condition of equality of the ratio of densities in direct shock wave for equilibrium and simulating flows. It is shown that the errors obtained with such simulation in the values of gas-dynamic functions in the shock layer in the ertire subscric region do not exceed 2-3 c/o. Calculation of the supersonic region is conducted with the value of adiatatic coefficient, cttained fics the condition of "freezing" of the composition of gas in the region of the maximum cross section of the body. Comparisons with results of calculations of axisymmetric ncneguilibrium flow [5] indicate the rather high accuracy of such a

DOC = 0933 PAGE 34 9

system of simulation. Pigs. 3-5 show the results of calculation of flow with $\alpha = 15^{\circ}$ about a body, close to sixty-degree sector. Fig. 3 shows the position of shock waves in the plane of symmetry for the following cases: 1, 2, 3 - $M_{\infty} = \infty$ respectively monatomic, diatomic and triatomic gases with constant adiabatic indices (f = 1.66, 1.4, 1.53); 4, 5, 6 - $M_{\infty} = 10$, $P_{\infty} = 120$ kg/m², $T = 230^{\circ}$ K, respectively N₂, air and CO₂; 7, 8 - $M_{\infty} = 25$, $P_{\infty} = 2.5$ kg/m², $T = 250^{\circ}$ K respectively aip (or N₂) and CO₂.



For air curves 5 and 7 correspond to conditions at altitude 30 km or 60 km. These same numerical designations of curves are retained in

Figs. 4, 5, where there are provided distributions of pressure along the surface of the body P(x) and across the sheck layer $P(\xi)$ in section $x \approx 0.36$ on the windward side ($\psi \cdot \pi$) of flow $\xi = \frac{\xi - \xi_s}{\xi_w \cdot \xi_s}$, where r - distance from the axis of symmetry of the body, index s designates the surface of the body, w - shock wave. Increase of Tleads to more intense overexpansion of flow during turn in the region of the maximum cross section than is revealed relative to different dimensions of "spoons" in the distribution of pressure along the surface of the body at curves 1-3 in Fig. 4. DOC = 0933



Fig. 4.

The presence of physicochemical processes in the shock layer in the examined case of flow around a body, close in shape to spherical sixty-degree sector, leads to lowering of the pressure on the lateral surface, and consequently, to decrease of the contribution of the

-

PIGE #/2

lateral surface of the tody in the total aerodynamic characteristics. The differences in the pressure distributions for N₂, air and CO₂ (curves 4-6) are explained by the different values of time of excitation of oscillations and dissociation. If for N₂ under the examined conditions ($M_{\infty} = 10$) the effect of real properties cannot practically be considered, the real properties for CO₂ must already be considered. The corresponding values of adiabatic indices of flow, simulating flow around the frontal surface, in the examined cases will be the following: 4 - 1.3 (?1.5?), 5 - [illeg.], 6 - 1.14. With $M_{\infty} = 25$ (curves 7, 8) the corresponding values of adiabatic index for flow, simulating flow around the frontal surface, for all three examined cases $\mathcal{F}_{e_1} = 1.1$, and for "frozen" flow \mathcal{F}_{f}^{∞} 1.6, which corresponds to almost completely dissociated gas, in view of which the distributions of pressure, obtained by the given method, in all three of the examined cases are wirtually identical.





rig. S.

Let us examine now some results (Figs. 6-11) of investigation of flow around elongated segmental bodies by perfect gas ($j^{-} = 1.4$). Analysis of calculation data show that for elongated segmental bodies even with small angles of attack and small angles of back cone there is considerable run-over of flow, which leads to the fact that pressure on the leeward side of the body starts from a certain length to exceed the pressure on the windward side. The indicated length in the considered range of angles of attack virtually do not depend on the angle of attack (Fig. 6).



Large pressure gradients, appearing at considerable angles of attack, for example $a = 20^{\circ}$ (solid lines in Fig. 6) lead to separation and reorganization of flow. However, the fact described above occurs even for angle of attack 1° (broken line on Fig. 6). Fig. 7 shows the pattern of flow lines on the surface of the body in the projection to the plane of symmetry at angle of attack $a = 20^{\circ}$.



FIGE #17

Fig. 7.

DOC = 0933

The data presented in Figs. 6, 7 are calculated with $M_{a} \sim , \quad \theta^* = 25^\circ, \quad \beta$. The experimental data of Yu. Ya. Karpeyskiy, shown by points in Fig. 8, for the case of flow around a body with break of generatrix at $M_{a} = 6$, $\alpha = 10^\circ$, $\theta^* = 30^\circ$ and $\beta = 10^\circ$ indicate the guite good coincidence of calculated and experimental data. DOC = 0933

PAGE #18



Fig. 1.

The most difference is in the region of the maximum cross section of the body, which, in all protability, can be explained by the effect of rounding of the approximating contour. In Fig. 9 for the given case of flow there are shown the pressure distributions with respect to meridian angle . EOC = 0933



PAGE 25/9

Pig. 9.

With large x from the leeward side the pressure sharply rises, which leads to the appearance cf positive radial velocities at the surface of the body from the leeward side (Fig. 10), i.e. to curving of the flow lines near the surface of the body (Fig. 11).

DOC = 0933 PAGE 27 20

The broken line on Fig. 11 depicts the characteristics of the first family in plane ψ_{-0} .



DOC = 0933



FAGE 22/

Pig. 11.

It is seen that the characteristics, preceeding from the surface of the body in range 0.5 < x < 1.5, virtually flow together at x = 2.5, i.e., run-over of flow near the surface of the segmental body leads to the formation of suspended shock wave in the field of flow from the leeward side of flow.

FEFEBENCES

DOC = 0933 FAGE # 22

1. G. P. Telenin, G. F. Tinyakov. Method of calculation of three-dimensional flow around bodies with departed shock wave. DAN USSE, 1964, Vol. 154, No. 5, P. 1056-1058.

2. V. B. Minostsev. Method of calculation of supersonic three-dimensional flow around smooth bodies. IAN USSR, MZhG, 1967, No. 2, p. 126-133.

3. V. B. Minostsev, G. F. Telenin, G. P. Tinyakov. Investigation of the pattern of supersonic three-dimensional flow around segmental-shaped body. EAN USSR, 1968, Vol. 178, No. 2, p. 304-307.

4. Yu. N. D'yakonov, V. B. Minostsev, G. F. Telenin. Supersonic three-dimensional flow arcund blunt bodies. In the collection
Froblems of hydrodynamics and continium mechanics. Science, 1969, p. 213-220.

5. M. G. Lebedev, V. B. Mincstsev, G. P. Telenin, G. P. Tinyakov. Affroximate method of calculation of the reality of gas during hypersonic flow around segmental bodies. IAN USSB, MZhG, 1969, No. 2, F. 107-111.

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

MICR	OFICHE	ORGANI	ZATION	MICROFICHE
	1	E053	AF/INAKA	1
	2	E017	AF/RDXTR-W	1
	9	E403	AFSC/INA	1
	1	E404	AEDC	1
ES LABS	1	E408	AFWL	1
Y R&D	1	E41Q	ADTC	1
RSENAL	1		FTD	
S COMD	1		CCN	1
	5		ASD/FTD/NIIS	5 3
IE	1		NIA/PHS	1
	1		NIIS	2
REUR)	1			
	1			
D/SD	1			
	1			
	1			
	1			
	1			
	MICR ES LABS Y R&D RSENAL S COMD IE REUR) VSD	MICROFICHE 1 2 9 1 2 9 1 Y R&D IRSENAL IS COMD IE 1 IREUR) 1 1 1 1 1 1 1 1	MICROFICHE ORGANI 1 E053 2 E017 9 E403 1 E404 2 E403 1 E404 2 E403 1 E404 2 E017 9 E403 1 E404 2 E017 9 E403 1 E404 1 E408 1 E410 1 SCOMD 1 SCOMD 1 SCOMD 1 SCOMD 1 SCOMD 1 1 1 1	MICROFICHEORGANIZATION1E053AF/INAKA2E017AF/RDXTR-W9E403AFSC/INA1E404AEDC2E408AFWL2YR&D12E408AFWL2YR&D1E410ADTC1SCOMD11CCN5ASD/FTD/NIIS1NIA/PHS1NIIS11

FTD-ID(RS)T-0933-78

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

ORGANIZATION		MICROFICHE	ORGANIZATION		MICROFICHE
A205	DMATC	1	E053	AF/INAKA	1
A210	DMAAC	2	E017	AF/RDXTR-W	1
B344	DIA/RDS-3C	8	E403	AFSC/INA	1
C043	USAMIIA	1	E404	AEDC	1
C509	BALLISTIC RES LABS	1	E408	AFWL	1
C510	AIR MOBILITY R&D	1	E410	ADTC	1
	LAB/FIO		E413	ESD	2
C513	PICATINNY ARSENAL	1		FTD	
C535	AVIATION SYS COMD	1		CCN	1
C591	FSTC	5		ASD/FTD/NICE) 3
C619	MIA REDSTONE	1		NIA/PHS	1
D008	NISC	1		NICD	2
H300	USAICE (USAREUR)	1			
P005	ERDA	1			
P005	CIA/CRS/ADD/SD	1			
NAVOR	DSTA (50L)	1			
NASA/	KSI	1			
AFIT/	LD	1			

FTD-ID(RS)T-0933-78

them.