

AD-A069 792

ITT ELECTRO-OPTICAL PRODUCTS DIV ROANOKE VA
ULTRA LOW LOSS OPTICAL FIBER CABLE ASSEMBLIES. (U)
MAY 79 J C SMITH, R E THOMPSON

F/6 20/6

DAAB07-78-C-2922


UNCLASSIFIED

NL

1 OF 1
AD
A069792



END
DATE
FILMED
7-79
DDC






LEVEL

6

RESEARCH AND DEVELOPMENT TECHNICAL REPORT
CORADCOM- CONTRACT # DAAB07-78-C-2922
ITT PROJECT # 36027

AD A 069792

ULTRA LOW LOSS OPTICAL FIBER CABLE ASSEMBLIES



J. C. SMITH & R. E. THOMPSON

ITT *Electro-Optical Products Division*

7635 Plantation Road, Box 7065
Roanoke, Virginia 24019

**SEMI-ANNUAL REPORT FOR PERIOD
APRIL 1978 - NOVEMBER 1978**

DISTRIBUTION STATEMENT

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

CORADCOM

US ARMY COMMUNICATION RESEARCH & DEVELOPMENT COMMAND
FORT MONMOUTH, NEW JERSEY 07703

79 06 07 030

FILE COPY

NOTICES

DISCLAIMERS

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS
BEFORE COMPLETING FORM

REPORT NUMBER

2. GOVT ACCESSION NO. 1. RECIPIENT'S CATALOG NUMBER

TITLE (and Subtitle)

Ultra Low Loss Optical Fiber Cable Assemblies
Semi-Annual Report

3. TYPE OF REPORT & PERIOD COVERED

Semi-Annual *repts*
April 1978 - November 1978

4. PERFORMING ORG. REPORT NUMBER

5. AUTHOR(s)

J. C. Smith and R. E. Thompson

6. CONTRACT OR GRANT NUMBER(s)

DAAB07-78-C-2922

PERFORMING ORGANIZATION NAME AND ADDRESS

ITT Electro-Optical Products Division
P.O. Box 7065
Roanoke, VA 2401910. PROGRAM ELEMENT, PROJECT, TASK
AREA & WORK UNIT NUMBERS

12. REPORT DATE

11. CONTROLLING OFFICE NAME AND ADDRESS

Commander - Attention DRSEL-TL-ME
U.S. Army Electronics Command
Ft. Monmouth, NJ 07703

13. NUMBER OF PAGES

15. SECURITY CLASS. (of this report)

Unclassified

14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)

15a. DECLASSIFICATION/DOWNGRADING
SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release: distribution unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

None

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Fiber optics, Optical Communications, broadband transmission, low loss optical
fibers, fiber optic ruggedization, optical waveguides, TDM, Time Division
Multiplexed. Repeaterless Optical Communications.

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

This report describes the progress made from April to November, 1978, in the
development of Ultra Low Loss Fiber Optic Cable Assemblies for Time Division
Multiplexed (TDM). This effort includes the fiber optic cable as well as the
connectors needed to terminate them. Optimization of the optical fiber fabri-
cation process is in progress, the objective is to increase the fiber yield
against the cable specification.

Further ruggedization of the cable is needed in order to achieve the 100% fiber survivability in the impact testing per MIL-C-13777. It is also necessary to keep the excess cabling losses at a minimum.

The three sphere connector concept has been selected for full development, and the jeweled ferrule concept as a back up.

Accession For	
MILS GENAL	☒
DDC TAB	☐
Unannounced	☐
Justification	☐
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or special
<i>ff</i>	

ITT *Electro-Optical Products Division*

ULTRA LOW LOSS OPTICAL FIBER
CABLE ASSEMBLIES

B003

Draft Semi-Annual Report
April through November 1978

for

U.S. Army Electronics Command
Fort Monmouth, N.J.

Contract #DAAB07-78-C-2922
ITT Project #36027

Prepared by

John C. Smith and Robert E. Thompson

ITT ELECTRO-OPTICAL PRODUCTS DIVISION
P. O. Box 7065
Roanoke, VA 24019

Approved by: J. E. Goell

J.E. Goell, Vice President &
Director of Fiber Optics
Laboratory

Roanoke, Virginia

ITT *Electro-Optical Products Division*

1.0 INTRODUCTION

The objective of this contract (#DAAB07-78-C-2922), entitled "Ultra Low Loss Optical Fiber Cable Assemblies", is to develop optical fiber cable assemblies for the Army tactical field data transmission at 20 Mb/sec over eight kilometers without repeaters.

The contract effort includes the development of rugged cable, cable connectors and bulkhead connectors which are jointly optimized for Army tactical field application.

ITT Electro-Optical Products Division has spend considerable time in the search of a suitable sub-contractor who is technically qualified and acceptable to CORADCOM and at the same time willing to work within the financial frame of this contract. The following companies were approached and invited to bid for the connector development phase of the contract:

ITT Cannon

ITT Leeds

ITT Components (Europe)

Hughes Connecting Devices Division

Deutsch

Cablewave

Amphenol

AMP

Roanoke, Virginia

ITT *Electro-Optical Products Division*

Only two companies were interested in bidding: ITT Cannon Electric Division and Hughes Connecting Devices Division.

Personnel from ITT Electro-Optical Products Division met with both Hughes Connecting Devices Division and ITT Cannon Electric Division. It was judged that the three sphere and the jewelled ferruled approaches of ITT Cannon had more merits than the free floating mechanism of the Hughes Connecting Devices six channel hermaphroditic connector. Therefore, ITT Cannon Electric Division was selected as the as the Connector Subcontractor. The connector vendor solicitation and selection effort has taken longer than originally planned and has delayed portions of the program.

Roanoke, Virginia

ITT *Electro-Optical Products Division*

2.0 CABLE DEVELOPMENT

The cable development phase of this contract includes the optimization of the optical fibers as well as the design of a rugged fiber optic cable.

The fiber optimization phase has benefited from progress achieved through the ITT internal R&D program. Table 1 shows the attenuation, dispersion and length of optical fibers recently developed.

Emphasis has been placed upon the improvement of optical properties. The data in Table I is most encouraging in that 73% of fibers exhibit less than 5 dB/km and 60% less than 4.5 dB/km (attenuation measured on spool). Therefore, the intrinsic attenuation of fibers is lower than the reported values. During the first quarter of 1979, considerable effort will be expended under ITT funded programs to further reduce attenuation and dispersion while still maintaining high tensile strength (100,00 psi proof testing).

ITT-EOPD has performed some work toward the development of a 62 μm optical core fiber. This approach was considered preferable to meet the 1 dB coupling loss specification for the connector. However, this work has not been aggressively pursued because of strong indications that a 50 μm core fiber

Roanoke, Virginia

TABLE 1

<u>CVD#</u>	<u>LENGTH</u> (Kilometers)	<u>ATTENUATION</u> (dB/km @ 0.85 μ m)	<u>DISPERSION</u> (ns/km @ 0.9 μ m)
20449	2.6	4.6	1.2
20450	2.3	3.6	.9
20451	1.2	4.1	1.6
20452	1.6	5.6	.98
20453	1.3	4.0	1.7
20454	1.2	3.9	1.7
20461	3.1	4.2	.65
20462	4.5	4.4	2.3
20463	1.9	4.4	1.3
20467	1.4	5.8	.95
20469	2.5	4.6	.42
20474	2.5	5.4	1.6
20480	2.7	5.3	2.1
20481	2.8	4.0	1.2
20485	4.1	4.9	1.3

Roanoke, Virginia

ITT *Electro-Optical Products Division*

will become the international standard.

All the fibers used in this program are being proof tested at 1% elongation (100,000 psi). This proof testing is an insurance against catastrophie failure when the fiber is strained during manufacturing, installation or service.

2.2 Ultra Low Loss Optical Fiber Cable Design

The cable design plan submitted contains the current approaches which ITT-EOPD believes have the best potential to meet the Technical Guidelines of the Ultra Low Loss Fiber Optic Cable Contract, and at the same time can be mass produced.

Based on the experience acquired in the Low Cost Fiber Optic Cable Assemblies for Local Distribution Systems contract (DAAB07-77-C-2681), an external strength member cable with 1 mm buffered optical fibers not only exhibits low excess cabling losses, but meets almost all the mechanical requirements. The exception of that is that the above contract required 90% survivability while the Ultra Low Loss Fiber Optic Cable Contract requires 100% survivability. This requirement is

Roanoke, Virginia

achievable with the proposed cable design, but it still has to be demonstrated.

Table 2 shows the optical attenuation of the external strength member cables using plastic clad silica fibers.

Table 2

Attenuation - External Strength Member Cable

Cable Batch #	Fiber #	Attenuation (dB/km)				Cable Length
		.65 μ m	.79 μ m	.82 μ m	1.05 μ m	
110678-CA-II	1	8.02	5.80	9.40	13.54	367m
	2	9.53	6.63	10.56	16.41	
	3	8.81	6.80	10.66	17.11	
	4	8.09	6.76	10.50	14.84	
	5	8.67	6.98	10.84	15.09	
	6	7.62	5.79	9.51	14.52	
	7	7.45	5.84	9.46	14.30	
	Average	8.31	6.37	10.31	15.12	
110778-BA-II	1	7.48	6.04	9.61	13.53	378m
	2	11.16	8.28	11.97	19.97	
	3	8.74	6.82	10.61	16.63	
	4	7.85	6.06	9.89	16.77	
	5	7.54	6.07	9.84	17.20	
	6	8.79	6.94	10.88	18.29	
	7	8.43	6.98	10.62	15.67	
	Average	8.57	6.74	10.48	16.72	

*Note: The fibers of cables 110678-CA-II and 110778-BA-II were made with fibers having Shin Etsu RTV silicone cladding.

Roanoke, Virginia

ITT *Electro-Optical Products Division*

Table 3 shows the number of surviving and broken fibers when the cable was tested over a wide temperature range using three different impact loads (4.07, 4.41, and 4.75 Newton-meters). Note that the poor performance at -55°C was due to the use of a dull polyurethane jacket material (a flame retardant grade). That jacket has been replaced with a non-filled polyurethane compound, which previously had shown good performance at that temperature.

Table 4 shows the number of impacts before the fiber breaks. Note that since there was no light transmission at -55°C , the number of transmitting fibers was found by counting the transmitting fibers after the temperature returned to 25°C .

Flex and Twist Tests were performed, on the Low Cost Fiber Optic Cable, in accordance with MIL-C-13777. All fibers survived these tests at the the extreme temperatures as well as at room temperature.

ITT-EOPD has selected the cable design developed under the Low Cost Fiber Optic Cable Contract as Design I (Figure I) because it meets or nearly meets all the cable mechanical and environmental objectives and can be produced with low excess cabling losses. However, realizing that CORADCOM

Roanoke, Virginia

Table 3

IMPACT RESISTANCE

IMPACT LOAD	TESTING TEMP.	# OF SAMPLES	# TRANS/ # FAIL	% SURVIVABILITY
4.07 Newton Meter	R.T. (25°C)	42	39/3	93%
4.41 " "	" "	"	33/9	79
4.75 " "	" "	"	33/9	79
4.07 Newton Meter	40°C	42	42/0	100%
4.41 " "	"	"	42/0	100
4.75 " "	"	"	40/2	95
4.07 Newton Meters	60°C	42	40/2	95%
4.41 " "	"	"	42/0	100
4.75 " "	"	"	38/4	90
4.07 Newton Meters	85°C	42	40/2	95%
4.41 " "	"	"	37/5	88
4.75 " "	"	"	38/4	90
4.07 Newton Meters	-5°C	42	42/0	100%
4.41 " "	"	"	42/0	100
4.75 " "	"	"	42/0	100
4.07 Newton Meters	-30°C	42	42/0	100%
4.41 " "	"	"	42/0	100
4.75 " "	"	"	42/0	100
4.07 Newton Meters	-55°C	42	26/16	62%
4.41 " "	"	"	13/29	31
4.75 " "	"	"	16/26	38

Roanoke, Virginia

Table 4


IMPACT RESISTANCE

Energy Level/ Sample #	Room Temperature Break Location/ Fiber Trans	+85°C		+40°C		-5°C & -30°C
		Break Location/ Fiber Trans	Break Location/ Fiber Trans	Break Location/ Fiber Trans	Break Location/ Fiber Trans	
4.07 Newton Meter	S1	--/7	--/7	116/6	--/7	No fiber breakage at these two temp. levels. The outer polyurethane jacket had a slight indent- ation. -30°C seems to be the light trans- mittance transition level, because output oscillated as the temp. changed from -25°C to -35°C.
	S2	--/7	178/6	--/7	--/7	
	S3	149, 192/5	144/6	173/6	--/7	
	S4	--/7	--/7	--/7	--/7	
	S5	--/7	--/7	--/7	--/7	
	S6	*6	--/7	--/7	--/7	
4.41 Newton Meter	S7	--/7	151, 182/5	--/7	--/7	Impact Resistance at -55°C was measured by the number of trans- mitting fibers, after
	S8	127/6	82/6	--/7	--/7	
	S9	108, 135/5	--/7	--/7	--/7	
	S10	49, 69/5	65, 67/5	--/7	--/7	
	S11	49, 69/5	--/7	--/7	--/7	
	S12	116, 132/5	194/6	--/7	--/7	
4.75 Newton Meter	S13	95/6	67, 167/5	127/6	48/6	Impact Resistance at -55°C was measured by the number of trans- mitting fibers, after
	S14	--/7	91/6	--/7	--/7	
	S15	89(2)/5	--/7	82/7	--/7	
	S16	19(2), 89/4	--/7	--/7	--/7	
	S17	68/6	158/6	150/6	--/7	
	S18	57, 62/5	--/7	126/6	--/7	

*Only 6 fibers were transmitting
before testing.

DATA DISTRIBUTION
Optimized Low Cost Fiber Optic Cable


FIGURE 1



DESIGN 1. ULTRA LOW LOSS FIBER OPTIC CABLE

102 10755


FIGURE 2



DESIGN 2 ULTRA LOW LOSS FIBER OPTIC CABLE

302 10754

FIGURE 3



DESIGN 3 ULTRA LOW LOSS FIBER OPTIC CABLE

302 10757

ITT *Electro-Optical Products Division*

intends to procure large amounts of cables, modifications of the design to facilitate its production with conventional cabling equipment is being considered.

Conventional cabling equipment can accomodate larger payoff and take up spools, allowing the production of longer cable lengths thus reducing set up time and increasing the equipment utilization. But heavier spools also mean higher tension, therefore, the cable design must provide portection to the optical core during the fabrication processes.

Cable Design 1 is considered marginally suitable for fabrication in conventional equipment. The next two designs will allow cables to be produced that, in addition to being rugged, are also capable of being produced with higher manufacturing tensions than the first design.

Figure 2 shows cable Design 2. This cable is similar to Design 1 except that a non-oriented nylon monofilament is used instead of the central fiber. The central monofilament is the load member during the fabrication of the optical core. The mechanical and optical properties of Design 1 should remain unaltered.

Roanoke, Virginia

ITT *Electro-Optical Products Division*

Figure 3 shows cable Design 3. The difference between this design and Design 1 is that the central member is a yarn of Kevlar with a polyurethane jacket. This design provides the highest strength during the optical core fabrication, but its impact performance is unknown. This design involves the concept of a flexible center core that yields under impact, absorbing in this manner part of the energy of the impact.

Roanoke, Virginia

ITT *Electro-Optical Products Division*

3.0 CONNECTOR DEVELOPMENT

ITT Cannon has been selected as subcontractor to develop a hermaphroditic connector for the Ultra Low Loss Fiber Optic Cable.

During the reporting period, a study of potential fiber alignment concepts was conducted.

The ability of an alignment concept to provide minimum coupling loss is a function of the design employed and their manufacturing tolerances.

Eleven concepts were critiqued (See Appendix A). These concepts represented the basic techniques currently considered viable within the fiber optic industry. An overall merit rating was given to each approach.

The following parameters were considered while evaluating each concept:

1. Coupling loss potential
2. Physical size - diameter
3. Total number of dimensional tolerances involved
in alignment
4. Potential cost

Roanoke, Virginia

ITT *Electro-Optical Products Division*

5. Termination technique (including time to terminate)
6. Fragility (care in handling)
7. Environmental consideration
8. Required development effort

As a result of the study, ITT's recommendation is to further development effort on the three sphere concept and perform minimal effort on the jewel ferrule concept as a back up.

The choice of the three sphere concept as the number one candidate is based upon the use of precision ball bearings with diameter tolerances of ten millionths of an inch in the alignment components. As can be seen in the conceptual drawing (Appendix A), only the spheres are involved in the lateral and gap alignment. Similarly, the use of an available precision watch jewel makes the jewel ferrule concept a second choice.

Roanoke, Virginia

ITT *Electro-Optical Products Division*

4.0 WORK SCHEDULED FOR NEXT PERIOD

- o Complete fabrication of prototype samples
- o Submit prototype samples
- o Fabricate fibers for exploratory development cable models
- o Fabricate exploratory development of three sphere connector
- o Submit cable plan
- o Submit bi-monthly and cost reports

Roanoke, Virginia

ITT *Electro-Optical Products Division*

APPENDIX A

Roanoke, Virginia


TRADE OFF OF CONNECTOR ALIGNMENT CONCEPTS

<u>Approach</u>	<u>Overall Merit Rating*</u>
Three sphere	1
Jewel Ferrule	2
Double Eccentric	3
Molded Ferrule	4
Resilient Self Centering	5
Multi-Rod	6
Formed Ferrule	7
V-Groove	8
Capillary Tube	9
Viscous Lens	10
Alignment by Fixturing	11

*1 is best rating

11 is worst rating

THREE PRECISION SPHERES (BALL BEARINGS) WHEN NESTED IN A PLANE AT 120° INCREMENTS, PROVIDE AN INTERSTITIAL SPACE AT THEIR GEOMETRIC CENTER EQUAL TO THE FIBER DIAMETER. THE FERRULE CAP CONTAINS AN INTERNAL RAMPED RACE WHICH ALLOWS ADJUSTMENT FOR FIBER DIAMETER VARIATION.



TTC CANNON ELECTRIC TELEPHONE TUBE CO. (INC.) A Division of the Cannon Electric and Engineering Company	
DESCRIPTION:	THREE SPHERE
FEASIBILITY: (OVERALL RATINGS)	1

COUPLING LOSS POTENTIAL	SIZE (DIAMETER)	NUMBER OF TOLERANCES	POTENTIAL COST
0.5 db	APPROXIMATELY 2 mm	ONE - THAT OF THE SPHERE	LOW ☒ MED ☐ HI ☐

TERMINATION TECHNIQUE, (TIME):
 FIELD ☒
 FACTORY ONLY ☐

FIBER IS CLEAVED, POSITIONED IN FERRULE WITHIN THE SPHERES, AND THE CAP IS ADJUSTED TO TIGHTEN SPHERES ON VARYING FIBER DIAMETER. FIBER IS BONDED IN PLACE. TERMINATION TIME IS 10 MINUTES.

FRAGILITY:

FIBER IS PROTECTED BY THE FERRULE.

ENVIRONMENTAL CONSIDERATIONS:


CONCEPT HAS BEEN EVALUATED UNDER SEVERAL ENVIRONMENTAL CONDITIONS; AFFECT OF SAND AND DUST MUST BE FURTHER CONSIDERED.

DEVELOPMENT EFFORT:

THE ALIGNMENT CONCEPT HAS BEEN THOROUGHLY EVALUATED UNDER LAB CONDITIONS. COUPLING LOSS DATA ON SEVERAL HUNDRED TERMINATIONS IS LESS THAN ONE (1) db. FURTHER EFFORT IS REQUIRED TO PERFECT THE CONCEPT UNDER ENVIRONMENTAL CONDITIONS AND FULFILL THE DESIGN TO A PRODUCTION STATUS. THE MAJOR EFFORTS WOULD ADDRESS: 1) LIFTING OF THE SPHERES TO THE FERRULE; 2) BALL RETENTION DURING FIBER ASSEMBLY; 3) MANUFACTURING TECHNIQUE; 4) COST REDUCTION (PRESS FIT INSTEAD OF THREADED FAST AND/OR CLIP); 5) FIBER ANTI CAUSING SPRING BACK; 6) ELIMINATION OF LEAKY; 7) SELF-CLEAVING OF FIBER DURING TERMINATION.

NOTES:

CONCENTRIC FERRULES CONTAIN A CONCENTRIC, PRECISION WATCH JEWEL TO ALIGN THE FIBER. THE INTENT IS TO USE A SINGLE SIZE JEWEL I.D. WITH A FIBER WHERE DIAMETER VARIATION IS CLOSELY CONTROLLED.



JOHN CANNON ELECTRIC INCORPORATED 1000 N. 10TH AVE. SUITE 100 MINNEAPOLIS, MINN. 55412 A Division of International Telephone and Telegraph Corporation	
DESCRIPTION:	JEWEL FERRULE
FEASIBILITY: (OVERALL RATING)	2

COUPLING LOSS POTENTIAL	SIZE (DIAMETER)	NUMBER OF TOLERANCES - LIGHT MAY BE POSSIBLE TO REDUCE TO SIX BY USING A SPRING MEMBER IN THE GUIDE SLEEVE.	POTENTIAL COST
< 1 dB	< 2 mm		LOW ☒ MED ☐ HI ☐

TERMINATION TECHNIQUE, (TIME):

FIBER IS BONDED INTO FERRULE, SUBSEQUENTLY GROUND AND POLISHED. MAY BE ABLE TO DEVELOP TECHNIQUE TO USE CLEAVED FIBER THEREBY REDUCING TERMINATION TIME. CURRENT DATA IS APPROXIMATELY 10 TO 15 MINUTES.

FIELD ☒
FACTORY ONLY ☐

FRAGILITY:

METALLIC FERRULE PROTECTS THE JEWEL AND FIBER, THEREFORE BETTER THAN AVERAGE.

ENVIRONMENTAL CONSIDERATIONS:


CONCEPT HAS BEEN USED EXTENSIVELY IN VARIOUS ENVIRONMENTS.

DEVELOPMENT EFFORT:

THE FOLLOWING PARAMETERS WOULD BE THOSE NECESSARY TO CONCENTRATE UPON: 1) COST REDUCTION; 2) FERRULE CYLINDRICAL TUBE ID/OD CONCENTRICITY OPTIMIZATION; 3) JEWEL CONCENTRICITY TO 1 MICRON; 4) A MEANS TO IMPLEMENT FIBER CLEAVING TO REDUCE TERMINATION TIME; 5) A SPRING MEMBER GUIDE SLEEVE TO IMPROVE FERRULE ANGULARITY CONTROL; 6) ATTENTION OF FIBER BY A LEADS OTHER THAN EPOXY (CERAMIC OR LOW TEMP MELTING GLASS).

NOTES:

THE FIBER IS MOUNTED IN AN X-Y ADJUSTABLE FERRULE AND TERMINATED UNDER A MICROSCOPE FOR PERFECT CONCENTRICITY. OPPOSING FERRULES MATE IN A PRECISION BORE GUIDE SLEEVE.



TIT CANNON ELECTRIC
UNITED STATES PATENT OFFICE
 1964-1965

DESCRIPTION:

DOUBLE ECCENTRIC

FEASIBILITY: (OVERALL RATINGS)

3

POTENTIAL COST
 LOW ☒ - PARTS COULD BE MOLDED
 MED ☒ - PLASTIC - BUT ASSEMBLY
 HI ☐ ARE REQUIRED (ALSO TO COSTS)

NUMBER OF TOLERANCES - TWO
 FERRULE O.D. AND GUIDE SLEEVE I.D.

SIZE (DIAMETER)
 APPROXIMATELY 4 mm

TERMINATION TECHNIQUE, (TIME):

FIELD ☐

FACTORY ONLY ☒

FIBER MUST BE SECURED IN INNER SLEEVE, THEN GROUND AND POLISHED. MAY BE POSSIBLE TO USE CLEAVED FIBER AND POSTHOLD FACE PRECISELY. THE SLEEVES VARY IN WALL THICKNESS; RELATIVE ROTATION PROVIDES AN X-Y MECHANISM TO ADJUST THE FIBER CORE CONCENTRIC WITH THE OUTER DIAMETER. THIS MUST BE DONE UNDER AT LEAST 200X MAGNIFICATION AND INTRODUCES A HUMAN ELEMENT IN THE ALIGNMENT ACCURACY. TERMINATION TIME: 30 MINUTES.

FRAGILITY:

SOMEWHAT LESS FRAGILE THAN OTHER TYPES OF FERRULES.

ENVIRONMENTAL CONSIDERATIONS:


VIBRATION & TEMPERATURE CYCLING MAY CAUSE MECHANICAL SHIFT OF CORE SINCE THREE LAYERS OF MATERIAL MUST FIT TIGHTLY UPON EACH OTHER.

DEVELOPMENT EFFORT:

METHOD OF LOCKING SLEEVES TOGETHER AFTER MICROSCOPIC ALIGNMENT OF CORE WITHOUT SHIFTING CORE. MECHANICAL ASSEMBLY OF SLEEVES. DEVELOP FABRICATION PROCESS TO HOLD DIALECTRIC TOLERANCES (CONCENTRICITY IS NOT IMPORTANT). REDUCTION OF SLEEVE WALL THICKNESS TO MEET FERRULE O.D. REQUIREMENTS. DEVELOPMENT COSTS WILL BE HIGH DUE TO REQUIRED HOLD TOOLS. A MEANS TO REMOVE FIBER IN HOLDER SLIDE. IMPROVE RESISTION PROPERTIES WITH PLASTIC COMPONENTS MAY CAUSE DIMENSIONAL CHANGE AND INCREASED LOSSES.

NOTES:

PIVOT BEARING GUIDE SLEEVE



THE CANNON ELECTRIC
INC. 1215 WEST
LAWRENCE ST., CHICAGO, ILL.
A Division of International Telephone and Telegraph Corporation

DESCRIPTION:

CONCLUSIONS

FEASIBILITY: (OVERALL RATING)

1

COUPLING LOSS POTENTIAL	SIZE (DIAMETER)	NUMBER OF TOLERANCES - THREE LATERAL AND GAP ALIGNMENT DEPEND ON FERRULE CONCENTRICITY, TAPER AND SPIEGKE DIAMETER.	POTENTIAL COST
< 1 dB	AS SMALL AS 1 mm		LOW ☒ - FERRULE COST COULD BE LOW BUT TOOLING COST WILL BE VERY HIGH. MED ☐ HI ☐

TERMINATION TECHNIQUE, (TIME):

FIELD ☐

FACTORY ONLY ☒

CAN BE EITHER GRIND/POLISH OR CLEAVE. IF CLEAVED FIBER IS USED, IT MUST BE PROTECTED DURING MOLDING CYCLE. DETERMINATION TIME INCLUDES FABRICATION OF PRODUCT; COULD APPROACH 2 MINUTES.

FRAGILITY:

SINCE THE FIBER IS INSERT MOLDED INTO A FERRULE, IT IS SUSCEPTIBLE TO DAMAGE (END FACE CHIPPING) DURING THE INSERTION INTO THE TOOL. THIS MAY REQUIRE SUBSEQUENT GRIND/POLISH WHICH WILL SHORTEN THE FERRULE AND INCREASE GAP LOSSES.

ENVIRONMENTAL CONSIDERATIONS:

1) TEMPERATURE CYCLING MAY CAUSE DIFFERENTIAL EXPANSION OF GLASS AND PLASTIC RESULTING IN LOSSES OF FIBER RETENTION AND/OR ALIGNMENT.

AND/OR ALIGNMENT.

2) FIBER END FACES MUST BE INITIALLY SEPARATED (INTENTIONAL GAP) SINCE PLASTIC MATERIAL WILL COMPRESS UNDER

2) MOISTURE ABSORPTION MAY CAUSE DIMENSIONAL CHANGE IN PLASTIC PARTS.

DEVELOPMENT EFFORT:

THE MAJOR EFFORT WILL BE TO FABRICATE A MOLD TOOL WHICH WILL ALLOW THE FIBER TO BE INSERT MOLDED CONCOMITANTLY WITHIN THE OPHERENT EFFORT: EACH NEW TOOL NEEDED WILL REQUIRE THE SAME EFFORT SINCE IT WILL BE AN ITERATIVE PROCESS TO ACHIEVE THE REQUIRED ACCURACY. THE TAPER ANGLE AND WILL BE AS CRITICAL AN EFFORT. A MEANS TO CONTROL THEIR ANGULARITY WITHIN THE FIBER MUST BE DEVELOPED AS WELL AS CONTROL OF FIBER ANGULARITY WITHIN THE COLLECTOR. FALS TO CONSIDER ARE: 1) FLASH OR LEAKAGE FROM THE FIBER GUID./

POLISH DUE TO CLEARANCE IN MOLD PILOT HOLE; 2) MOLDING PRESSURE AFFECTS ON GLASS FIBER; 3) RESIDUAL COMPRESSION STRESSES DUE TO PLASTIC CURING WILL CAUSE FIBER STRESSES AND DIFFICULTY IN GRINDING/POLISHING; 4) FIBER CLEANLINESS FOR ADEQUATE BONDING.

531CN

THE CANNON ELECTRIC
114 EAST 12TH STREET
CHICAGO, ILL. 60604
A Division of International Telephone and Telegraph Corporation

DESCRIPTION:

RESILIENT SELF-CENTERING

FEASIBILITY: (OVERALL RATING)

5



COUPLING LOSS POTENTIAL
UNKNOWN - MUST DETERMINE
EXPERIMENTALLY

SIZE (DIAMETER)

**APPROXIMATELY AS SMALL AS THE
FIBER**

NUMBER OF TOLERANCES
"ABSORBED BY THE ELASTOMER"

POTENTIAL COST

☒ Low ☒

MED ☐

□

TERMINATION TECHNIQUE, (TIME):

01313 ☒

FACTORY ONLY ☐

MUST BE CLEAVED AND POSITIONED; POTENTIAL OF MINIMUM TIME TO TERMINATE.

FRAGILITY:

MAY INVOLVE EXPOSED, CANTILEVERED FIBER; ALSO A MAJOR DRAWBACK IS THE ALIGNMENT REQUIRES THE CONTINUOUS APPLICATION OF COMPRESSIVE FORCES ON THE FIBER.

ENVIRONMENTAL CONSIDERATIONS:


TEMPERATURE ENVIRONMENT MAY CAUSE COMPRESSION SET OF ELASTOMER AND RESULT IN MODULATION OF PULSE DURING SUBSEQUENT VIBRATION; EFFECTS OF ENVIRONMENT ON ELASTOMER MATERIAL I.E., OZONE MUST BE CONSIDERED.

DEVELOPMENT EFFORT:

- 1) MATERIAL DEVELOPMENT TO OVERCOME COMPRESSION SET AND TO INSURE HOMOGENEITY; 2) A MEANS TO APPLY THE DEVELOPMENT EFFORT;

NOTES:

ELASTOMER GUIDE SILVER



SAFETY GUIDE

5005 JINX

THE CANNON ELECTRIC
INCORPORATED
100 WEST 11TH STREET
NEW YORK, N. Y.
Manufacturers of Electric Motors, Generators, and Electrical Equipment

DESCRIPTION:

MUT-11-K(11)

RELIABILITY: (OVERALL RATING)

3

COUPLING LOSS POTENTIAL

BP 17

SIZE (DIAMETER)

FERRULE DIAMETER WILL BE APPROXIMATELY 5 mm BUT GUIDE WILL BE EXCESSIVE IN DIAMETER; THEREFORE, CONNECTOR WILL BE LARGE.

NUMBER OF TOLERANCES - THREE
LATERAL ALIGNMENT IS DEPENDENT UPON
DIAMETER TOLERANCES OF PIRKULE RODS
AND GUIDE RODS. GAP CONTROL TO BE
DETERMINED.

POTENTIAL COST

LOW ☒ - MAY BE ROD BEARINGS AND
MOLDED ELASTOMER GUIDE
MED ☐ SLEEVE OR SPRING GUIDE
HI ☐ SLEEVE.

TERMINATION TECHNIQUE, (TIME):

FIELD ☒

FACTORY ONLY ☐

FRAGILITY:

SIMILAR TO MOST OTHER CONCEPTS.

FIBER WILL BE CLEAVED, POSITIONING (GAP CONTROL) WILL BE SIMILAR TO HEMISPHERE BUT LESS ACCURATE SINCE ROD ENDS MAY NOT BE IN ONE PLANE. FIBER MUST BE EPOXIED INTO RODS. TERMINATION TIME MAY APPROACH 10 MINUTES.

ENVIRONMENTAL CONSIDERATIONS:


TEMPERATURE CYCLING MAY CAUSE LONGITUDINAL SHIFT OF FIBER DUE TO DIFFERENTIAL EXPANSION (RODS VERSUS GLASS). THIS SHIFT WILL CAUSE A VARIABLE END FACE SEPARATION.

DEVELOPMENT EFFORT:

DEVELOPMENT EFFORT: 1) MEANS TO CONTROL FIBER GAP; 2) PREVENT RODS FROM CRUSHING FIBER; 3) MEANS TO CLOSE HOLES ON FIBER AND RETAIN THE A
4) MEANS TO RETAIN GUIDE RODS IN PARALLEL IN ELASTIC GROMMET; 5) MEANS TO LOCATE CLAVED END FACE WITHIN RODS; 6) MEANS TO ASSEMBLE ROD ENDS IN A
PLANE; 7) GUIDE RODS TEND TO PRY FERRULE RODS OPEN, DESIGN MUST CONSIDER GROMMETARY TO PRECLUDE THIS; 8) CONSIDER GUIDE SLEEVE AS OPPOSED TO GUIDE RODS
9) MUST CONSIDER FIBER DIAMETER VARIATION WITHIN ROD LENGTH.

NOTES:

THE CONCEPT INVOLVES FABRICATING A PRECISE, CONCENTRIC FERRULE.



TOPP CANNON ELECTRIC INCORPORATED 1000 N. 10TH AVE. SUITE 100 MINNEAPOLIS, MINN. 55412	
DESCRIPTION:	FORMED FERRULE
FEASIBILITY: (OVERALL RATING)	7

COUPLING LOSS POTENTIAL	SIZE (DIAMETER)	NUMBER OF TOLERANCES	POTENTIAL COST
< 2 dB	< 3 mm	SIX	LOW ☐ MED ☐ HI ☐

TO BE DETERMINED

TERMINATION TECHNIQUE, (TIME):

FIELD ☒

FACTORY ONLY ☐

EITHER GRINDING AND POLISHING OR CLEAVING MAY BE USED. FIBER MUST BE BONDED INTO THE FERRULE. TIME COULD APPROACH 15 MINUTES.

FRAGILITY:

SIMILAR TO OTHER CONCEPTS, I.E., THE JEWELLED FERRULE; THE FIBER IS PROTECTED BY THE FERRULE.

ENVIRONMENTAL CONSIDERATIONS:

PERFORMANCE WOULD NEED TO BE EVALUATED UNDER VIBRATION AND TEMPERATURE CYCLING.

DEVELOPMENT EFFORT:

THE MAJOR EFFORT WOULD BE TO DEVELOP A FABRICATION PROCESS TO PROVIDE A HOLE (APPROXIMATELY 127 MICRONS) IN THE FERRULE FACE CONCENTRIC TO THE FERRULE O.D. WITHIN FIVE (5) MICRONS. POTENTIAL METHODS ARE: 1) LASER DRILLING; 2) CHEMICAL MILLING (USING PHOTO REDUCTION); 3) SPINNING; 4) COLD HEADING; 5) MOLDING. EACH PROCESS WOULD NEED TO BE REDUCED TO PRAGMATIC TO DECREASE LEASIBILITY THEREBY REQUIRING CONSIDERABLE TIME AND EXPENSE.

NOTES:

THE BASIC CONCEPT IS TO ALIGN TWO OPPOSING
FLARE FIBERS IN A COMMON V-GROOVE. ACCURACY
OF ALIGNMENT IS A FUNCTION OF FIBER DIAMETER
CONTROL & CORE/CLADDING CONCENTRICITY.



TRUMP CANNON ELECTRIC 10000 10th Street, N.E. Seattle, Wash. 98108
DESCRIPTION: V-GROOVE ALIGNMENT
FEASIBILITY: (OVERALL RATING) 8

COUPLING LOSS POTENTIAL	SIZE (DIAMETER)	NUMBER OF TOLERANCES	POTENTIAL COST
< 1 db	TO BE DETERMINED; POTENTIALLY QUITE SMALL RELATIVE TO OTHER CONCEPTS.	DEPENDENT ON FIBER DIAMETER TOLERANCE ONLY.	LOW ☐ MED ☒ HI ☐

TERMINATION TECHNIQUE, (TIME):

FIELD ☒

FACTORY ONLY ☐

FRAGILITY:

FIBERS ARE EXPOSED IN ORDER TO POSITION IN THE GROOVE DURING CONNECTOR MATING.

ENVIRONMENTAL CONSIDERATIONS:


CONTINUOUS COMPRESSIVE LOAD IS APPLIED TO THE FIBER; POTENTIALLY LESS AFFECTED BY ENVIRONMENTAL CONDITIONS. SUSCEPTIBLE TO VIBRATION DAMAGE AT END OF V.

DEVELOPMENT EFFORT:

THE CONCEPT HAS BEEN PROVEN AS A LAB SET UP; CONSIDERABLE EFFORT WOULD BE NECESSARY TO IMPLEMENT THE CONCEPT INTO FERRULE HARDWARE USABLE IN A HERMAPHRODITE CONNECTOR. DEVELOPMENT EFFORTS MUST ADDRESS: 1) CATHETERIZED EXPOSED FIBER; 2) CAP CONNECTOR; 3) FIBER OUTSIDE DIAMETER CLEARANCE AFTER STRIPPING BUFFER JACKET; 4) FIBER RETENTION IN FERRULE; 5) A MECHANISM TO CLAMP FIBERS AFTER MATING.

NOTES:

A LOW TEMPERATURE GLASS TUBE IS COLLAPSED ON THE LARGER OF TWO FIBERS. THE SMALLER DIAMETER FIBER IS PLUGGABLE INTO THE TUBE OPENING.



THE CANNON ELECTRIC
INCORPORATED
 10000 WILSON AVENUE
 A Division of General Electric Company

DESCRIPTION:

CAPILLARY TUBE

FEASIBILITY: (OVERALL RATING)

9

COUPLING LOSS POTENTIAL	SIZE (DIAMETER)	NUMBER OF TOLERANCES	POTENTIAL COST
< 1 db	< 1 mm	ONE	LOW ☐ FERRULE COST MAY BE SMALL, BUT TIGHTING CLOUT BE EXPENSIVE.
			MED ☒
			HI ☐

TERMINATION TECHNIQUE, (TIME):

FIELD ☐

FACTORY ONLY ☒

GLEAVED FIBERS WOULD BE USED; TERMINATION TIME INVOLVES CLEAVING, MEASURING FIBER DIAMETER, BONDING IN FERRULE AND TUBE COLLAPSE.

FRAGILITY:

FIBERS MUST BE CANTILEVERED FROM THE FERRULES AND REQUIRE MORE HANDLING THAN OTHER CONCEPTS.

ENVIRONMENTAL CONSIDERATIONS:

SINCE THE OPPOSING FIBERS ARE RIGIDLY MOUNTED, EVALUATION UNDER VIBRATION CONDITIONS WOULD BE REQUIRED.


DEVELOPMENT EFFORT:

INVESTIGATION OF GLASS TECHNOLOGY IS REQUIRED; FIBER RESIDUAL STRESSES VERSUS LIFE EXPECTATION MUST BE EVALUATED. CONTAMINATION PARTICLES ON THE FIBER SURFACE MUST BE ELIMINATED TO PRECLUDE BUCKLEBEND LOSSES AND FIBER BREAKAGE DURING TUBE COLLAPSE. A MEANS TO PREVENT END FACES CHIPPING EACH OTHER MUST BE DEVELOPED; TELESCOPING SLEEVE TYPE FERRULES MAY BE NECESSARY. THE COLLAPSING TECHNIQUE MUST BE DEVELOPED TO PRECLUDE TOO SMALL A DIAMETER HOLE TO RECEIVE THE PLUG FIBER. DUE TO THE TEMPERATURE REQUIRED IN THE PROCESS, THE HEAT MUST BE REMOVED.

NOTES:

CONCEPT IS NOT APPLICABLE TO HERMAPHRODITE CONNECTORS SINCE PREDICTION OF WHICH CABLE CONTAINS THE LARGER FIBER IS NOT POSSIBLE & not fully interchangeable.

FIBER ALIGNMENT IS ACHIEVED THROUGH THE USE OF A DOUBLE CONCAVE LENS AND A VISCOUS INDEX MATCHED FLUID.



TTC CANNON ELECTRIC
INCORPORATED
 A Division of International Telephone and Telegraph Corporation

DESCRIPTION:

VISCOUS LENS ALIGNMENT

FEASIBILITY (OVERALL RATING)

10

COUPLING LOSS POTENTIAL	SIZE (DIAMETER)	NUMBER OF TOLERANCES OPTICAL EFFECTS COMPENSATE FOR MECHANICAL TOLERANCES.	POTENTIAL COST
< 1 db	1.5 mm		LOW ☐ MED ☐ HI ☒

DUE TO NUMEROUS MATER
AND COMPONENTS

TERMINATION TECHNIQUE, (TIME):

FIBER CLEAVING IS APPROPRIATE FOR THIS CONCEPT.

10-15 min.

FIELD ☒

FACTORY ONLY ☐

FRAGILITY:

FIBER MAY BE EXPOSED AND/OR A MECHANISM REQUIRED TO PROTECT THE FIBER AND AUTOMATICALLY RETRACT UPON ASSEMBLY. CAREFUL HANDLING SO AS TO NOT LOSE VISCOUS FLUID MAY BE REQUIRED.

ENVIRONMENTAL CONSIDERATIONS:

NUMEROUS QUESTIONS MUST BE ANSWERED IN REGARDS TO AFFECT OF ENVIRONMENT. FOR EXAMPLE: 1) TEMPERATURE LIMIT ON MOIDED PLASTIC LENS, RETENTION OF VERY VISCOUS FLUID UNDER SHOCK, TEMPERATURE, VIBRATION, ETC., 2) CONTAMINATION OF VISCOUS FLUID CAUSING OPTICAL LOSS; 3) DURABILITY.

DEVELOPMENT EFFORT:

1) DESIGN OF LENS; 2) DEVELOPMENT OF VISCOUS FLUID SUCH THAT IT REMAINS IN PLACE UPON REPEATED MATINGS;

3) A MEANS TO SUPPORT THE FIBER IN A FERRULE, PROTECT IT UNTIL MATING AND ALLOW IT TO SEEK ITS OWN CENTERED POSITION IN THE LENS; 4) INVESTIGATE

POTENTIAL OF FIBER CLEAVED LONG SCRAPING THE LENS AND PRECLUDING REPEATED USAGE; 5) LENS MOLDING TECHNIQUE; 6) LENS MATERIAL; 7) MEANS TO MOUNT LENS IN SIX CHANNEL CONNECTOR; 8) MEANS TO ASSEMBLE FLUID INTO LENS. DEVELOPMENT COSTS APPEAR TO BE CONSIDERABLE.

NOTES:

~.

DESCRIPTION:

ДМИТРИЙ АР ЛАТВИНСКИЙ

FEASIBILITY: (OVERALL RATING)

11

COUPLING LOSS POTENTIAL

0.4 dB

SIZE (DIAMETER)

TO BE DETERMINED

NUMBER OF TOLERANCES

NONE

POTENTIAL COST

LOW ☒ **MOD** ☐

MED

11

TERMINATION TECHNIQUE, (TIME):

FIELD ☒

FACTORY ONLY ☐

FRAGILITY:

FIBERS WOULD BE CLEAVED AND ALIGNED IN A PRECISION FIXTURE. CONNECTOR COMPONENTS WOULD BE ASSEMBLED AS THE TERMINATION PROCEDURE. TERMINATION TIME WOULD APPROACH 30 MINUTIS.

MORE FRAGILE THAN OTHER CONCEPTS SINCE FIBERS ARE COMPLETELY EXPOSED DURING CONNECTOR ASSEMBLY.

ENVIRONMENTAL CONSIDERATIONS:

TO BE DETERMINED; SEPARABLE CONNECTOR WOULD REQUIRE USE OF ASSEMBLY FIXTURE FOR EVERY MATING.

DEVELOPMENT EFFORT:

CONSIDERABLE EFFORT IS NECESSARY TO CONCEIVE THE ARRANGEMENT OF FIXTURE AND CONNECTOR COMPONENTS TO ACHIEVE THE CONCEPT GOAL. THE PRECISION FIXTURE COULD BE A V BLOCK OR EQUIVALENT; IT WOULD BE ALTERNATE AS A TERMINATION TOOL.

NOTES:

DISTRIBUTION LIST

Defense Documentation Center
ATTN: DDC-TCA
Cameron Station (Building 5)
Alexandria, VA 22314
(12 copies)

Director
National Security Agency
ATTN: TDL
Fort George G. Meade, MD 20755

DCA Defense Comm Engrg Ctr
ATTN: Code R123, Tech Library
1860 Wiehle Ave
Reston, VA 22090

Defense Communications Agency
Technical Library Center
Code 205 (P. A. Tolovl)
Washington, DC 20305

Office of Naval Research
Code 427
Arlington, VA 22217

GIDEP Engineering & Support Dept
TE Section
PO Box 398
Norco, CA 91760

Director
Naval Research Laboratory
ATTN: Code 2627
Washington, DC 20375

Commander
Naval Electronics Laboratory Center
ATTN: Library
San Diego, CA 92152

Command, Control & Communications Div
Development Center
Marine Corps Development & Educ Comd
Quantico, VA 22134

Naval Telecommunications Command
Technical Library, Code 91L
4401 Massachusetts Avenue, NW
Washington, DC 20390

Rome Air Development Center
ATTN: Documents Library (TILD)
Griffiss AFB, NY 13441

HQ ESD (DRI)
L. G. Hanscom AFB
Bedford, MA 01731

CDR, MIRCOM
Redstone Scientific Info Center
ATTN: Chief, Document Section
Redstone Arsenal, AL 35809

Commander
HQ Fort Huachuca
ATTN: Technical Reference Div
Fort Huachuca, AZ 85613

Commander
US Army Electronic Proving Ground
ATTN: STEEP-MT
Fort Huachuca, AZ 85613

Commander
USASA Test & Evaluation Center
ATTN: IAO-CDR-T
Fort Huachuca, AZ 85613

Dir, US Army Air Mobility R&D Lab
ATTN: T. Gossett, Bldg 207-5
NASA Ames Research Center
Moffett Field, CA 94035

HQDA (DAMO-TCE)
Washington, DC 20310

Deputy for Science & Technology
Office, Assist Sec Army (R&D)
Washington, DC 20310

HQDA (DAMA-ARP/DR. F. D. Verderame)
Washington, DC 20310

Director
US Army Human Engineering Labs
Aberdeen Proving Ground, MD 21005

CDR, AVRADCOM
ATTN: DRSAB-E
PO Box 209
St. Louis, MO 63166

Director
Joint Comm Office (TRI-TAC)
ATTN: TT-AD (Tech Docu Cen)
Fort Monmouth, NJ 07703

Commander
US Army Satellite Communications Agcy
ATTN: DRCPM-SC-3
Fort Monmouth, NJ 07703

TRI-TAC Office
ATTN: TT-SE (Dr. Pritchard)
Fort Monmouth, NJ 07703

CDR, US Army Research Office
ATTN: DRXRO-IP
PO Box 12211
Research Triangle Park, NC 27709

Commander, DARCOM

ATTN: DRUDE

5001 Eisenhower Ave

Alexandria, VA 22333

CDR, US Army Signals Warfare Lab

ATTN: DELSW-OS

Arlington Hall Station

Arlington, VA 22212

CDR, US Army Signals Warfare Lab

ATTN: DELSW-AW

Arlington Hall Station

Arlington, VA 22212

Commander

US Army Logistics Center

ATTN: ATCL-MC

Fort Lee, VA 22801

Commander

US Army Training & Doctrine Command

ATTN: ATCD-TEC

Fort Monroe, VA 23651

Commander

US Army Training & Doctrine Command

ATTN: ATCD-TM

Fort Monroe, VA 23651

NASA Scientific & Tech Info Facility

Baltimore/Washington Intl Airport

PO Box 8757

Baltimore, MD 21240

Advisory Group on Electron Devices

201 Varick Street, 9th Floor

New York, NY 10014

Advisory Group on Electron Devices

ATTN: Secy, Working Group D (Lasers)

201 Varick Street

New York, NY 10014

TACTEC

Battelle Memorial Institute

505 King Avenue

Columbus, OH 43201

Ketron, Inc.

ATTN: Mr. Frederick Leuppert

1400 Wilson Blvd, Architect Bldg

Arlington, VA 22209

R. C. Hansen, Inc.

PO Box 215

Tarzana, CA 91356

CDR, US Army Avionics Lab

AVRADCOM

ATTN: DAVAA-D

Fort Monmouth, NJ 07703

Ballistic Missile Systems Defense Command

ATTN: BMDSC-HD (Mr. C. D. Lucas

PO Box 1500

Huntsville, AL 35807

Project Manager, ATACS
ATTN: DRCPM-ATC (Mr. J. Montgomery)
Fort Monmouth, NJ 07703

Commander
ERADCOM

ATTN: DELET-D

DELS-D-I-S

Fort Monmouth, NJ 07703
(2 copies)

Commander
CORADCOM

ATTN: DRDCO-COM-D

DRDCO-SEI

DRDCO-COM-RM-1

Fort Monmouth, NJ 07703
(62 Copies)

ITT Electro-Optical Prod Div
7635 Plantation Road
Roanoke, VA 24019

Corning Glass Works
Telecommunication Prod Dept
Corning, New York 14830

Galileo Electro-Optics Corp.
Galileo Park
Sturbridge, MA 01518

Times Fiber Comm, Inc.
Wallingford, CT 06492

Bell Northern Research
PO Box 3511, Station C
Ottawa, Canada K1Y 4H7

Valtec Corporation
Electro Fiber Optic Div
West Boylston, MA 01583

Hughes Research Laboratory
3011 Malibu Canyon Road
Malibu, CA 90265
ATTN: Dr. R. Abrams

Belden Corporation
Technical Research Center
2000 S. Batavia Avenue
Geneva, IL 60134
ATTN: Mr. J. McCarthy

Optelecom, Inc.
15940 Shady Grove Road
Gaithersburg, MD 20760

Bell Telephone Laboratories
Whippany Road
Whippany, NJ 07981
ATTN: Mr. G. A. Baker

Deutsch Co.

Elec.Components Div
Municipal Airport
Banning, CA 92220

General Cable Corporation
15 Prospect Lane
Colonial, NJ 07067
ATTN: Mr. I. Kolodny

Martin Marietta Corp.
Orlando, FL

Electronics Group of TRW, Inc.
401 N. Broad Street
Philadelphia, PA 19108

Hughes Aircraft Corporation
Tucson Systems Engrg Dept.
P.O. Box 802, Room 600
Tucson, AZ 85734
ATTN: Mr. D. Fox

GTE Sylvania Inc.
Communications System Division
189 B Street
Needham Heights, MA 02194
ATTN: Mr. J. Concordia

Harris Electronics Systems Division
P.O. Box 37
Melbourne, FL 32901
ATTN: Mr. R. Stachouse
Fiber Optics Plant
Rodes Boulevard

ITT Defense Communications Division
492 River Road
Nutley, NJ 07110
ATTN: Dr. P. Steensma

