





 \mathbf{O}

M A07622

FILE COP



MISCELLANEOUS PAPER SL-79-23

GROUTING INSTRUMENTATION, OLD RIVER LOW SILL CONTROL STRUCTURE

by

Donnie L. Ainsworth

Structures Laboratory U. S. Army Engineer Waterways Experiment Station P. O. Box 631, Vicksburg, Miss. 39180

September 1979

Final Report

Approved For Public Release; Distribution Unlimited



Prepared for U. S. Army Engineer District, New Orleans New Orleans, Louisiana 70160

79 11 06 020

Destroy this report when no longer needed. Do not return it to the originator.

-

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

REPORT DOCUMENTATION PAG	GE READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	OVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER
Miscellaneous Paper SL-79-23'	
4. TITLE (and Bubililo)	TYPE OF REPORT & PERIOD COVEREN
GROUTING INSTRUMENTATION, OLD RIVER LO	W SILL
CONTROL STRUCTURE ,	/ Final report. /
	. PERFORMING ORG. REPORT HUMBER
7. AUTHOR(+)	8. CONTRACT OR GRANT NUMBER(*)
Donnie L. Ainsworth	4) WE3-SL-79-23]
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK
U. S. Army Engineer Waterways Experime Structures Laboratory P. O. Box 631, Vicksburg, Miss. 39180	nt Station
11. CONTROLLING OFFICE NAME AND ADDRESS	11 12. REPORT DATE
U. S. Army Engineer District, New Orle	ans 11 September 1979
New Orleans, La. 70160	17. NUMBER OF PAGES
14. MONITORING AGENCY NAME & ADDRESS(II different from	a Controlling Office) 15. SECURITY CLASS. (of this report)
	Unclassified
	15a. DECLASSIFICATION/ DOWN GRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	
17. DISTRIBUTION STATEMENT (of the ebetract entered in Bla	ock 20, if different from Report)
17. DISTRIBUTION STATEMENT (of the abetract entered in Bio	ock 20, il dillerent from Report)
17. DISTRIBUTION STATEMENT (of the obstract entered in Bid 18. SUPPLEMENTARY NOTES	ock 20, il dillerent from Report)
17. DISTRIBUTION STATEMENT (of the obstract entered in Big 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse side if necessary and identified in the second statement of the second stateme	ock 20, il dilferent from Report) ntify by block number)
17. DISTRIBUTION STATEMENT (of the abetract entered in Bid 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse elde if necessary and iden Grouting Instrumentation Old River Control Structure	ock 20, if different from Report) ntify by block number)
 17. DISTRIBUTION STATEMENT (of the obstract entered in Bit 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse eide if necessary and idea Grouting Instrumentation Old River Control Structure 24. AFTRACT (Cartinue an reverse eide N messery and idea Instrumentation was developed and and flow of grout during remedial grou Structure. Measurements were also mad ducers installed in packers in drilled presents information on the developmen the presence of grout, the rate of bui 	ack 20, if different from Report) milly by block number) with by block number) used in the field to monitor the present tring of the Old River Low Sill Control le of uplift pressures by means of trans- holes through the slab. This report tt and field use of instruments to detect ldup under the base of the structure, and (Continued)
 17. DISTRIBUTION STATEMENT (of the obstract entered in Bid 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse elds if necessary and iden Grouting Instrumentation Old River Control Structure 24. APTRACT (Continue on reverse elds if necessary and iden Instrumentation was developed and and flow of grout during remedial grou Structure. Measurements were also mad ducers installed in packers in drilled presents information on the developmen the presence of grout, the rate of bui DD 10. FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETER 	ack 20, if different from Report) ntify by block number) ntify by block number) used in the field to monitor the present ting of the Old River Low Sill Control te of uplift pressures by means of trans- holes through the slab. This report tt and field use of instruments to detect ldup under the base of the structure, and (Continued) Unclassified SECURITY CLASSIFICATION OF THIS PAGE (Then Date End

Unclassified SECURITY CLASSIFICATION OF THIS PAGE (Then Date Entered) 20. ABSTRACT (continued). CONT \rightarrow pressure increase under the slab due to grouting operations. All data were electronically recorded and were used extensively to regulate the grouting operation. Unclassified SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)

PREFACE

The development of grouting instrumentation and field measurement of grout flow and pressure at the Old River Low Sill Control Structure were performed for the U. S. Army Corps of Engineers, New Orleans District (NOD), by the Concrete Laboratory (CL), U. S. Army Engineer Waterways Experiment Station (WES), in accordance with authority provided in DA Form 2544 dated 30 October 1973 and subsequent amendments. Mr. E. Burton Kemp, NOD, was responsible for the emergency grouting operation and the instrumentation program was under his direction.

The grouting instrumentation program was conducted during the period 1973-1975 under the direction of Messrs. Bryant Mather, Leonard Pepper, and B. R. Sullivan, CL. Mr. D. L. Ainsworth developed the instrumentation and was project leader for the field measurements. Messrs. B. R. Sullivan and Dale Glass actively participated in the preparation for and in the field measurements. Mr. D. L. Ainsworth prepared this report.

The Directors of WES during the conduct of this test program were COL G. H. Hilt, CE, and BG E. D. Peixotto, CE. The Commanders and Directors of WES during the preparation and publication of this report were COL J. L. Cannon, CE, and COL N. P. Conover, CE. Mr. F. R. Brown was Technical Director.

TIS GRA&I
inannounced
Sy
By
Distribution/
was sufficient to the second states of the second s
Availability Codes
Avail and/or
list special
N

CONTENTS

F.	age
PREFACE	1
CONVERSION FACTORS, U. S. CUSTOMARY TO METRIC (SI)	
UNITS OF MEASUREMENT	3
PART I: INTRODUCTION	4
Background	4
Purpose and Scope	5
PART II: DEVELOPMENT OF GROUTING SUPPORT INSTRUMENTATION	6
Grout Detector	6
Pressure Measuring System	7
Other Instrumentation	8
PART III: FIELD OPERATION - GROUTING INSTRUMENTATION	9
Mobilization	9
Field Measurements	9
PART IV: RESULTS	11
PART V: CONCLUSIONS	12
FIGURES 1-4	
DIATES 1-5	

CONVERSION FACTORS, U. S. CUSTOMARY TO METRIC (SI) UNITS OF MEASUREMENT

U. S. customary units of measurement used in this report can be converted to metric (SI) units as follows:

Multiply	Ву	To Obtain
feet	0.3048	metres
inches	25.4	millimetres
pounds (force) per square inch	0.006894757	megapascals
cubic yards	0.7645549	cubic metres
cubic feet	0.02831685	cubic metres

GROUTING INSTRUMENTATION, OLD RIVER LOW SILL CONTROL STRUCTURE

PART I: INTRODUCTION

Background

1. The instrumentation discussed in this report was developed for the Corps of Engineers, New Orleans District (NOD), for use at the Old River Low Sill Control Structure, Concordia Parish, Louisiana. The need for such instrumentation was recognized when remedial repair work was being planned following the 1973 flood.

2. The Old River Low Sill Control Structure, located approximately 40 miles south of Vidalia, Louisiana, on the west bank of the Mississippi River, was completed in 1960 as part of a project to prevent capture of the Mississippi River by the Atchafalaya River. It is an ll-gated, pilefounded structure approximately 600 ft long and is used to control approximately 30 to 40 percent of the flow of the Mississippi River into the Atchafalaya River.

3. During the 1973 flood, an eddy developed behind the southeast upstream wing wall, and on 12 April 1973 the major portion of this wing wall collapsed. Surveys in the forebay area indicated that a large scour hole had developed in front of gate bays 8, 9, 10, and 11 to a maximum depth of 65 ft. Since this scour hole extended 29 ft below the bottom of the sheet pile beneath the structure, a detailed boring program was carried out by NOD to investigate the foundation beneath the structure and the stilling basin. The borings indicated a cavity beneath the structure and stilling basin in the vicinity of gate bays 6 through 11 that varied in depth from a maximum of 52.2 ft in gate bay 11 to 1.8 ft in gate bay 7. Plate 1 is a photograph of the structure showing a general view from the stilling basin side. Note grouting casings anchored at bridge deck extending to and anchored in lower concrete slab.

4. The Grouting Branch of the WES Concrete Laboratory evaluated approximately 30 grout mixtures* and subsequently recommended several mixtures of low cement content and low-bond-strength grout that would have minimum bond to the supporting steel piling. It was estimated that approximately 30,000 cu yd of level-seeking grout would be required to fill the voids.

Purpose and Scope

5. During the planning stage for the remedial work, the New Orleans District engineers and geologists recognized the need for instrumentation to monitor the flow of grout and uplift pressure during grouting. Personnel of the Engineering Physics Branch, Concrete Laboratory, WES, were asked to attend a planning meeting at the structure to discuss possible instrumentation methods.

6. Members of the staff of WES suggested monitoring the grout flow with a resistivity gage that had received limited attention in the laboratory. It was agreed that WES should develop and build 10 such gages and have them ready for use at the structure upon start-up of the grouting operation.

7. Pressure measurements were also discussed and WES was requested to design a system and provide the design, equipment list, and instructions to the contractor. It was later decided that WES should also monitor the uplift pressure since the contractor had little or no instrumentation experience. It was agreed that WES should provide and monitor up to four pressure gages.

8. This report presents the design and operation of the instrumentation used in support of the grouting operation.

* Hugh K. Wilson, "Grouting of Scoured Foundation, Old River Low Sill Structure, Louisiana," Miscellaneous Paper C-78-19, Dec 1978, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.

PART II: DEVELOPMENT OF GROUTING SUPPORT INSTRUMENTATION

Grout Detector

9. Previous detection of grout in a water environment had been accomplished with some degree of success using pressure differential gages. Since these gages are expensive to fabricate, lack resolution, and are difficult to use in the field, other methods were considered when the problem of monitoring grout movement at a number of locations under the slab of the Low Sill Structure was presented.

10. Two methods which were investigated for detecting grout were: (a) capacitive and (b) resistive. A preliminary laboratory study was conducted to evaluate both methods. Two 1-in. diameter electrodes spaced 1 in. apart were connected electrically to an a-c voltage source as shown in Figure 1. Because of the effect of d-c polarization, an a-c oscillator was used to provide input a-c voltage (V_{in}) . An oscilloscope was used to monitor the change in voltage across R_1 as the dielectric was varied between the electrodes of the probe.

11. It was noted in these tests that if the electrodes were insulated, very little voltage change would occur when the probe was inserted in water or grout. It became apparent that a voltage measurement based primarily on capacitance effects would be very difficult. If the metal electrodes were in intimate contact with the surrounding dielectric medium, the capacitance and resistance (impedance) affected the output. The controlling factor for the dielectrics of interest (air, water, and grout) was the resistance change or resistivity of the dielectric.

12. The laboratory tests showed that a significant increase in voltage across R_1 occurred when the probe was inserted in tap water and a greater increase when inserted in grout. This is logical since water is more conductive than air and grout is more conductive than water. Only a small amount of cement added to water increases the conductivity of the water considerably.

13. Using information obtained from the laboratory tests, 12 grout

detectors were fabricated for field application. The gages consist basically of two 1-in. diameter electrodes spaced approximately 1-1/2 in. apart, and protruding from the main body approximately 2 in. The main body was an encapsulation of the extension cable and electrode wire connections and steel balls added for weight. Plate 2 is a photograph of the detector described and smaller detector used as a water height detector. The gage cable was 250 ft of 2-conductor 16-gage plastic-covered extension cord wire with a 2-pin connector installed on the end opposite the gage. Extension cable was fabricated to locate the gages up to 700 ft from the instrumentation trailer.

14. The associated gage instrumentation consisted of: (a) a commercial 3-kHz power supply, (b) an a-c to d-c converter (demodulator), (c) a calibration circuit, and (d) a 24-point strip chart recorder. Figure 2 shows the basic circuit diagram. The gages were calibrated by varying R_1 and input voltage so that full-scale (10-in.) deflection on the recorder was obtained with the gage in air and half-scale (5-in.) deflection with the gage inserted in water. With this calibration, grout detection was indicated by approximately a 1-in. deflection. These deflections were attainable because of the characteristics of the exciter-demodulator. If the voltage is measured across R_1 with an a-c voltmeter, an air reading would be 0 volts and a grout reading would be close to the applied voltage magnitude.

Pressure Measuring System

15. The system for making pressure measurements in encased drill holes through the structure slab was assembled and calibrated in the laboratory. Commercial pressure transducers having a range of 0-50 psi were installed in waterproof housings. Four-conductor shielded cable was used to transmit the gage excitation voltage and gage output. The transducers were calibrated over the range of 0-30 psi with the field instrumentation cable installed.

16. The measuring system consisted of the following: (a) pressure transducer, (b) 5-volt DC regulated power supply, (c) multiple channel

balancing network, and (d) multi-point strip chart recorder. The basic system circuit diagram is shown in Figure 3. The transducer was adapted to a fixture for attaching to a balloon packer for sealing off the hole during the pressure measurement period. Plate 3 is a photograph of the pressure transducer, waterproof housing, and balloon packer.

Other Instrumentation

17. Water-height detectors were fabricated for the purpose of making quick and simple pressure measurements in the field. Since the drill holes were to be encased, a measurement of the height of the column of water indicated the pressure under the slab. A detector consisted of two electrodes separated by a dielectric connected to a d-c power supply and measuring instrument by a two-wire cable. Figure 4 shows a typical circuit. When water comes in contact with the electrodes, current flows in the circuit and a voltage is developed across R_1 and is indicated on the multi-point recorder. The smaller detector shown on Plate 2 was used as a water height detector.

18. Thermistors were encased in a weighted tube for lowering into the holes to monitor temperature at various locations. A digital readout device with built-in signal conditioning and calibration circuitry was used to monitor the thermistors.

PART III: FIELD OPERATION -GROUTING INSTRUMENTATION

Mobilization

19. In October 1973, members of the staff of the WES Concrete Laboratory were requested by NOD to fabricate the instrumentation discussed in Part II of this report. The grouting operation was to begin November 1973. Twenty grout detectors, 10 water level detectors, and 12 pressure transducers were fabricated. Many extension cables were prepared for long runs up to 600 ft from the instrumentation trailer.

20. Prior to the beginning of the pumping operation, the extension cables were laid out to various sections of the structure from the instrumentation located on the south end of the structure. Gages were connected and calibrated. The pressure calibrations were field checked using a 40-ft column of water contained in 1-1/2-in. PVC pipe supported from the structure.

Field Measurements

21. The pumping operation began on Thanksgiving Day, 23 November 1973. Eighteen grout detectors were installed in gate bays 8, 9, 10, and 11 at MSL elevations of -9.2 to -45.0 ft (81.2 to 119 ft below the bridge deck) through cased drill holes. Two water-height detectors were installed in gate bays 8 and 9. Six pressure transducers were mounted in balloon packers and installed in gate bays 8 and 10. After locating the pressure gages at the desired elevations, the packers were inflated to seal off the holes above the transducers. Plate 4 is a photograph of a pressure gage and packer assembly.

22. Prior to beginning the grouting operation, the grout detectors were located approximately 1 ft above the bottom of the cavity. When the grout level reached a detector, a corresponding large deflection occurred simultaneously on the strip chart recorder. At this time, the proper authority was notified of the grout elevation and the grout detector was was raised 1 ft. It was found that the grout level could be located within 1/2 in. at a depth of 119 ft below the bridge deck. The grout detectors were moved to other holes as needed. A maximum of 24 detectors was used simultaneously at one period during the grouting operation requiring fabrication of additional detectors. Plate 5 shows the recorders and conditioning equipment for the detectors.

23. Additional instrumentation included thermistors for monitoring grout temperature and water-height detectors to supplement the pressure gages. The temperature measurements were included at the request of an OCE representative. These data were acquired from several locations under the slab for a period of several weeks. Since the holes were cased, a measurement of the height of the column of water was an indication of the pressure under the slab. The water-height detectors were used primarily as pressure alarm devices. The detectors were located approximately 2 ft above the water level requiring a 2-ft (0.866-psi) rise in the water column to activate the measuring system.

24. The grouting operation continued through February 1974, and extended into gate bays 6 and 7. Pressure and grout flow monitoring also continued through this period. After the major grouting operation had ceased with the major cavities filled, check borings were made to depths corresponding to the depth of the underlying foundation material. These borings revealed continuous grout material from the base of the slab to the base of the original cavity. Check borings continued in other bays and all small voids located were filled with grout. Grout detectors were used during this period where applicable.

25. Pressure gages installed in packers were used later in the year when additional check borings were made. During the summer of 1975, open hole piezometers were installed in several of the piers of the structure. The drilled holes extended to the base of the piers. Immediately after each hole was completed, the pressure was monitored for a period of time sufficient for pressure stabilization.

PART IV: RESULTS

26. The grout detectors were used during all grouting exercises at many locations around the injection hole to determine both the height of grout and the flow. The data from these gages were used to determine when the grouting should cease in a particular area and how well the grout was flowing into other areas. As indicated previously, grout height could be determined within 1/2 in. at distances up to 119 ft.

27. Not only would the grout detector differentiate between water and grout, but it would also detect bentonite and other materials mixed in water. When installed in the hole below water level, it would detect the fluff or water contaminated with cement. While pure grout gave deflections 1 in. from zero on the strip chart, a contaminated water would cause a deflection of 1-1/2 to 3 in. depending on degree of contamination. Muck gave a deflection of approximately 3-4 in. If the gage was located in a strong current, the deflection was approximately 6-7 in. because of the air bubbles created due to agitation.

28. The pressure transducers were used to insure against building up an excessive uplift pressure during the grouting. The transducers worked well and gave data pertinent to the operation. However, much care had to be taken to insure against cable and transducer damage. Moisture entering the cable through cuts in insulation caused erratic operation. Several transducers were damaged and were not repairable because grout penetrated their housings.

PART V: CONCLUSIONS

29. The grout detectors and pressure gages were very significant in the success of the grouting operation. As previously stated, as many as 24 grout detectors were used at one time. The success of these gages has led to their use at other installations.







Figure 2. Basic field grout detector circuit











Plate 1. Old River Low Sill Control Structure. General view from stilling basin side



Plate 2. Grout and water height detectors

n'



Plate 3. Disassembled pressure gage-packer system



Plate 4. Pressure gage-packer assembly



In accordance with letter from DAEN-RDC, DAEN-ASI dated 22 July 1977, Subject: Facsimile Catalog Cards for Laboratory Technical Publications, a facsimile catalog card in Library of Congress MARC format is reproduced below.

Ainsworth, Donnie L
Grouting instrumentation, Old River Low Sill Control
Structure / by Donnie L. Ainsworth. Vicksburg, Miss. :
U. S. Waterways Experiment Station ; Springfield, Va. :
available from National Technical Information Service,
1979.

12, [2] p., [3] leaves of plates : ill. ; 27 cm. (Miscellaneous paper - U. S. Army Engineer Waterways Experiment Station ; SL-79-23)

Prepared for U. S. Army Engineer District, New Orleans, New Orleans, Louisiana.

1. Grouting. 2. Instrumentation. 3. Old River Control Structure. I. United States. Army. Corps of Engineers. New Orleans District. II. Series: United States. Waterways Experiment Station, Vicksburg, Miss. Miscellaneous paper; SL-79-23. TA7.W34m no.GL-79-23