

AD-A090 006

TECHNICAL LIBRARY

AD-A090 006

TECHNICAL REPORT ARLCB-TR-80031

ANALYSIS OF SHIFTS IN THE POINTS OF MAXIMUM DEFLECTION AND PERMANENT DEFLECTION FOR ELASTIC- PLASTIC BENDING OF UNSYMMETRICALLY LOADED BEAMS

R. V. Milligan

August 1980



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
LARGE CALIBER WEAPON SYSTEMS LABORATORY
BENÉ WEAPONS LABORATORY
WATERVLIET, N. Y. 12189

AMCMS No. 612105840011

DA Project No. 1L162105AH84

PRON No. 1A0217131A1A

DTIC QUALITY INSPECTED 3

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official indorsement or approval.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

Block 20. Abstract

at a considerable distance from the point of loading. The maximum strains (under load) and the permanent strains occur at the point where the load is applied.

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
APPROACH	2
RESULTS AND DISCUSSIONS	5
CONCLUSIONS	15
REFERENCES	16

LIST OF ILLUSTRATIONS

1. Sketch of unsymmetrically deformed beam.	1
2. Sketch of beam showing elastic and elastic/plastic regions.	3
3. a. Sketch showing location of load.	6
b. Sketch showing dimensions of the cross section of the tube.	6
c. Sketch showing idealized elastic perfectly-plastic behavior.	6
4. Elastic/plastic deflection as a function of distance from the left support.	7
5. Load vs. point along length of beam where maximum deflection occurs.	9
6. First derivative of deflection vs. distance as a function- ing distance as determined by cubic spline technique.	10
7. Load vs. max elastic/plastic deflection.	11
8. Permanent deflection vs. distance from left support.	12
9. Maximum applied load vs. distance from left to support point of maximum permanent deflection.	13
10. Percent permanent strain vs. depth of elastic/plastic interface.	14

INTRODUCTION

In processing blank forgings for gun tube manufacturing, excessive permanent deformations are often developed. Straightening is then required to bring the tube component to within some manufacturing-specified tolerance. In some cases the maximum permanent deflection is quite close to the end of the tube which gives rise to an unsymmetrical distance-deflection curve similar to that shown in Figure 1(a). One might logically wonder if such an unsymmetrical deformation could be removed by inverting the tube and placing the straightening load at the point of maximum deflection as shown in Figure 1(b). The load would then be increased until elastic-plastic deformation was sufficiently large that when the load was removed the initial permanent deformation would be essentially eliminated. The objective of the present study was to gain a better appreciation of load-deflection relationships, which would hopefully give a better understanding of the straightening process for the case of three point, unsymmetrical bending.




Figure 1. Sketch of unsymmetrically deformed beam.

APPROACH


This report is meant to be one in a series dealing with studies concerning aspects of elastic-plastic bending both from theoretical and experimental view points. The work presented here is theoretical and based on the method of virtual work. Without going into all of the mathematical details, which will be given elsewhere,¹ it will suffice to say that a solution is obtained by integrating the expression

$$\int \frac{Mm dx}{EI}$$

where M = bending moment due to real load and
m = bending moment due to dummy load

over the length of the beam which is subdivided into four major sections as shown in Figure 2. First the integration is carried out from 0 to α , then from α to λ , which cover the elastic region on the left-hand side, then λ to A, and A to μ which cover the two elastic-plastic regions and finally from μ to L in the elastic region on the right-hand side of the beam. These deflection components give the deflection in the region 0 to λ (from the left support to the beginning of the elastic-plastic region relative to length). Next the so-called dummy load is placed between λ and A. An integration is made from 0 to λ in the elastic region, λ to α , α to A, and A to μ , all three integrals being in the two elastic-plastic regions and finally μ to L through the second elastic region. The dummy load is then placed in the region A to μ and the same type of integrations are made to determine the

¹R. V. Milligan, "Load-Deflection Relationships for Simply Supported Beams Loaded Into the Plastic Region," to be published.



REGIONS

O TO λ ELASTIC
 λ TO A ELASTIC / PLASTIC
 A TO μ ELASTIC / PLASTIC
 μ TO L ELASTIC

Figure 2. Sketch of beam showing elastic and elastic/plastic regions.

deflections in this region. Finally, the dummy load is positioned between μ and L to obtain the deflections in the elastic region on the right-hand side. In this way a continuous spectrum of deflections across the entire length of the beam is obtained. The value of M and m assume two different expressions depending on whether the section in question is to the right or left of the loads. The values λ and μ change as the load increases beyond the point of yielding up to the ultimate load. α is the distance from the left support to the point where the dummy load is applied - which is the point where the deflection is desired. Although the integrals are standard ones so as to be easily evaluated, there are a large number of them.

For determining the residual or permanent deflections, the beam is assumed to unload linearly, hence by ratio, the elastic deflection to be subtracted from the elastic-plastic deflection can be easily calculated by

$$\delta^* = \left(\frac{P_{ep}}{P_{el}} \right) \delta_{el}$$

where P_{ep} is the elastic-plastic load, P_{el} is the elastic load or at most the yield load, and δ_{el} is the elastic deflection corresponding to the particular load. The elastic deflections were calculated by using the double integration method. Of course, they can also be calculated by the method of Virtual Work, but the computer program is much longer.

RESULTS AND DISCUSSION

As an example, illustrating the results of this study, a problem for a segment of a 105 mm cannon tube was solved. The length was 216 inches and the load located 36 inches from the left end as shown in Figure 3(a). Figure 3(b) shows the cross section containing the Neutral axis and the plane of loading. The outside diameter was assumed constant. The material was assumed to be elastic-perfectly plastic with a stress-strain behavior as shown in Figure 3(c). The yield strength was taken as 160 ksi and modulus equal to 30×10^6 psi.

Figure 4 shows the elastic-plastic deflections vs length of beam for six different loads. The smallest corresponds to the yield load and the largest is 99.5 percent of the ultimate. Beyond this point the computer solution breaks down. One of the things to be noted is that the point of maximum deflection is located a considerable distance to the right of the load. Figure 5 is a plot of load vs distance to the point of maximum deflection. This figure shows that the maximum deflection shifts quite rapidly as the load approaches the ultimate but is still approximately 46 inches to the right of the load for P_{ep} equal to 99.5 percent of the ultimate load. The points of maximum deflection were obtained two different ways. First the increment of the do-loop was decreased and the point of maximum deflection simply read from the computer printout. A second method using splines² was

²R. V. Milligan, "Computer Analysis of Mechanical Test Data Using Cubic Splines," Transactions ISA, Vol. 17, No. 2, 1978, pp. 21-30.




FIG 3a

Location of load




FIG. 3b

Dimensions of cross section of tube




FIG. 3c

Idealized elastic perfectly-plastic behavior

FIGURE #3




FIGURE 4. ELASTIC/PLASTIC DEFLECTION
VS
DISTANCE FROM LEFT SUPPORT

used. In this case the deflection vs distance data is fed into a spline routine where the first and second derivatives are calculated. From a Cal-Comp plot of the slope vs distance, a horizontal line is drawn from the point of zero slope on the vertical axis to intercept the curve. Then a line is projected downward to obtain the desired point on the horizontal axis. This is illustrated in Figure 6. Finally to complete this section a load vs maximum deflection curve is shown in Figure 7.

Figure 8 shows an exaggerated vertical scale plot of the permanent deflection vs distance from the left support. The interesting thing to note here is that these points of maximum deflection have shifted a considerable distance toward the load as compared with the case for the elastic-plastic deflections. Finally, Figure 9 shows a plot similar to Figure 5 except the abscissa represents the distance to the point of maximum permanent deflection. As before we can see that the curve flattens out as P_{ep} approaches P_{ult} . However, the distance to the point of maximum deflection is still nine inches to the right of the load application point.

Figure 10 is a plot of maximum permanent strain vs depth of the elastic-plastic interface. Curve A has the expanded scale on the right, while curve B has the scale on the left. One of the interesting points which should be pointed out is that the maximum strains occur on the outside fiber and at the point of loading. Therefore, the maximum permanent strains and the maximum permanent deflections do not occur at the same place along the length of the tube.




FIGURE 5
LOAD VS POINT ALONG LENGTH OF BEAM WHERE MAX DEFL. OCCURS
(INCHES)

DEFL. VS. DIST.

FIRST DERIVATIVE OF DEFLECTION VS. DISTANCE

$P = 145,000$
(YIELD LOAD)





FIGURE 6. Deflection vs Distance






Figure 8. Permanent deflection vs. distance from left support.






Figure 9. Maximum applied load vs. distance from left to support point of maximum permanent deflection.

FIGURE 10-PERCENT PERMANENT STRAIN
VS
DEPTH OF ELASTIC-PLASTIC INTERFACE




NOTE : MAXIMUM STRAINS OCCUR AT $X = 36''$ -
THAT IS, UNDER THE LOAD WHERE
BENDING MOMENT IS MAXIMUM

PERCENT PERM. STRAIN



ELASTIC-PLASTIC
INTERFACE



These results are for the case of a constant outside diameter along the length of the tube. A tapered tube having a variable outside diameter would interject additional complications for determining these points of maximum deflection.

CONCLUSIONS

1. As in the elastic case, the point of maximum elastic-plastic deflection is located far to the right of the point of load application for a tube that is unsymmetrically loaded into the plastic region.

2. The points of maximum deflection for both the elastic-plastic and permanent cases shift rapidly towards the point of loading as the load approaches the ultimate.

3. For a load up to 99.5 percent of the ultimate load, the point of maximum permanent deformation is still a considerable distance to the right of the load point.

4. The point of maximum permanent deflection, along the length of the beam, does not coincide with the point where the maximum permanent strains occur.

REFERENCES

1. R. V. Milligan, "Load-Deflection Relationships for Simply Supported Beams Loaded Into the Plastic Region," to be published.
2. R. V. Milligan, "Computer Analysis of Mechanical Test Data Using Cubic Splines," Transactions ISA, Vol. 17, No. 2, 1978, pp. 21-30.

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
COMMANDER	1
CHIEF, DEVELOPMENT ENGINEERING BRANCH	1
ATTN: DRDAR-LCB-DA	1
-DM	1
-DP	1
-DR	1
-DS	1
-DC	1
CHIEF, ENGINEERING SUPPORT BRANCH	1
ATTN: DRDAR-LCB-SE	1
-SA	1
CHIEF, RESEARCH BRANCH	2
ATTN: DRDAR-LCB-RA	1
-RC	1
-RM	1
-RP	1
CHIEF, LWC MORTAR SYS. OFC.	1
ATTN: DRDAR-LCB-M	1
CHIEF, IMP. 81MM MORTAR OFC.	1
ATTN: DRDAR-LCB-I	1
TECHNICAL LIBRARY	5
ATTN: DRDAR-LCB-TL	
TECHNICAL PUBLICATIONS & EDITING UNIT	2
ATTN: DRDAR-LCB-TL	
DIRECTOR, OPERATIONS DIRECTORATE	1
DIRECTOR, PROCUREMENT DIRECTORATE	1
DIRECTOR, PRODUCE ASSURANCE DIRECTORATE	1

NOTE: PLEASE NOTIFY ASSOC. DIRECTOR, BENET WEAPONS LABORATORY, ATTN:
DRDAR-LCB-TL, OF ANY REQUIRED CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	NO. OF COPIES		NO. OF COPIES
ASST SEC OF THE ARMY RESEARCH & DEVELOPMENT ATTN: DEP FOR SCI & TECH THE PENTAGON WASHINGTON, D.C. 20315	1	COMMANDER US ARMY TANK-AUTMV R&D COMD ATTN: TECH LIB - DRDTA-UL MAT LAB - DRDTA-RK WARREN MICHIGAN 48090	1 1
COMMANDER US ARMY MAT DEV & READ. COMD ATTN: DRCDE 5001 EISENHOWER AVE ALEXANDRIA, VA 22333	1	COMMANDER US MILITARY ACADEMY ATTN: CHMN, MECH ENGR DEPT WEST POINT, NY 10996	1
COMMANDER US ARMY ARRADCOM ATTN: DRDAR-LC -ICA (PLASTICS TECH EVAL CEN) -ICE -ICM -ICS -ICW -TSS(STINFO) DOVER, NJ 07801	1 1 1 1 1 2	COMMANDER REDSTONE ARSENAL ATTN: DRSMT-RB -RRS -RSM ALABAMA 35809	2 1 1
COMMANDER US ARMY ARRCOM ATTN: DRSAR-LEP-L ROCK ISLAND ARSENAL ROCK ISLAND, IL 61299	1	COMMANDER HQ, US ARMY AVN SCH ATTN: OFC OF THE LIBRARIAN FT RUCKER, ALABAMA 36362	1
DIRECTOR US Army Ballistic Research Laboratory ATTN: DRDAR-TSB-S (STINFO) ABERDEEN PROVING GROUND, MD 21005	1	COMMANDER US ARMY FGN SCIENCE & TECH CEN ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	1
COMMANDER US ARMY ELECTRONICS COMD ATTN: TECH LIB FT MONMOUTH, NJ 07703	1	COMMANDER US ARMY MATERIALS & MECHANICS RESEARCH CENTER ATTN: TECH LIB - DRXMR-PL WATERTOWN, MASS 02172	2
COMMANDER US ARMY MOBILITY EQUIP R&D COMD ATTN: TECH LIB FT BELVOIR, VA 22060	1		

NOTE: PLEASE NOTIFY COMMANDER, ARRADCOM, ATTN: BENET WEAPONS LABORATORY, DRDAR-LCB-TL, WATERVLIET ARSENAL, WATERVLIET, N.Y. 12189, OF ANY REQUIRED CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER US ARMY RESEARCH OFFICE P.O. BOX 12211 RESEARCH TRIANGLE PARK, NC 27709	1	COMMANDER DEFENSE TECHNICAL INFO CENTER ATTN: DTIA-TCA CAMERON STATION ALEXANDRIA, VA 22314	12
COMMANDER US ARMY HARRY DIAMOND LAB ATTN: TECH LIB 2800 POWDER MILL ROAD ADELPHIA, MD 20783	1	METALS & CERAMICS INFO CEN BATTELLE COLUMBUS LAB 505 KING AVE COLUMBUS, OHIO 43201	1
DIRECTOR US ARMY INDUSTRIAL BASE ENG ACT ATTN: DRXPE-MT ROCK ISLAND, IL 61201	1	MECHANICAL PROPERTIES DATA CTR BATTELLE COLUMBUS LAB 505 KING AVE COLUMBUS, OHIO 43201	1
CHIEF, MATERIALS BRANCH US ARMY R&S GROUP, EUR BOX 65, FPO N.Y. 09510	1	MATERIEL SYSTEMS ANALYSIS ACTV ATTN: DRXSY-MP ABERDEEN PROVING GROUND MARYLAND 21005	1
COMMANDER NAVAL SURFACE WEAPONS CEN ATTN: CHIEF, MAT SCIENCE DIV DAHLGREN, VA 22448	1		
DIRECTOR US NAVAL RESEARCH LAB ATTN: DIR, MECH DIV CODE 26-27 (DOC LIB) WASHINGTON, D. C. 20375	1 1		
NASA SCIENTIFIC & TECH INFO FAC P. O. BOX 8757, ATTN: ACQ BR BALTIMORE/WASHINGTON INTL AIRPORT MARYLAND 21240	1		

NOTE: PLEASE NOTIFY COMMANDER, ARRADCOM, ATTN: BENET WEAPONS LABORATORY, DRDAR-ICB-TL, WATERVLIET ARSENAL, WATERVLIET, N.Y. 12189, OF ANY REQUIRED CHANGES.