


AD-A096 853 CIVIL ENGINEERING LAB (NAVY) PORT HUENEME CA
NONDESTRUCTIVE TEST EQUIPMENT FOR WIRE ROPE.(U)
OCT 80 H H HAYNES, L D UNDERBAKKE
UNCLASSIFIED CEL-TN-1594

F/G 11/6

NL

for /
200-002



END
DATE
FILMED
4-81
DTIC

12

LEVEL II

AD A 096853

Technical



Note

9
- TN ~~1594~~ -1594

6
title: NONDESTRUCTIVE TEST EQUIPMENT FOR WIRE ROPE.

author: H. H. Haynes and L. D. Underbakke

date: Oct ~~1980~~ 1980

DTIC
ELECTE

MAR 26 1981

E

10-
sponsor: Naval Facilities Engineering Command

program nos: Y0995-01-004 621

DTIC FILE COPY



CIVIL ENGINEERING LABORATORY

NAVAL CONSTRUCTION BATTALION CENTER
Port Hueneme, California 93043

Approved for public release; distribution unlimited.

3711
81 3 26 007

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TN-1594	2. GOWT ACCESSION NO. AD-8896853 DN987077	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) NONDESTRUCTIVE TEST EQUIPMENT FOR WIRE ROPE	5. TYPE OF REPORT & PERIOD COVERED Not final; Sep 1979 - Sep 1980	
7. AUTHOR(s) H. H. Haynes and L. D. Underbakke	6. PERFORMING ORG. REPORT NUMBER	
9. PERFORMING ORGANIZATION NAME AND ADDRESS CIVIL ENGINEERING LABORATORY Naval Construction Battalion Center Port Hueneme, California 93043	8. CONTRACT OR GRANT NUMBER(s)	
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Facilities Engineering Command Alexandria, Virginia 22332	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 63725N; Y0995-01-004-621	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	12. REPORT DATE October 1980	
	13. NUMBER OF PAGES 32	
	15. SECURITY CLASS. (of this report) Unclassified	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Wire rope, steel cable, inspection, nondestructive test, nondestructive evaluation, electro- magnetism, Hall effect sensors.		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Nondestructive test equipment for inspecting steel wire ropes was evaluated in labora- tory and field tests. Individual AC/DC units and a unitized AC/DC unit were tested on wire rope to detect broken wires and loss of metallic area from wear and corrosion. The unitized AC/DC units used Hall effect sensors to pick up the defects as opposed to sensor coils used in the individual AC/DC units. The Hall effect sensors enabled less equipment to be used to conduct a complete inspection and also permitted the wire rope to be inspected at speeds (continued)		

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

20. Continued

- from 0 - 500 fpm. It is recommended that Navy facilities requiring nondestructive test inspection capability for metallic wire rope inspection procure the unitized AC/DC unit.

Civil Engineering Laboratory
NONDESTRUCTIVE TEST EQUIPMENT FOR WIRE ROPE,
by H. H. Haynes and L. D. Underbakke
TN-1594 32 pp illus October 1980 Unclassified

1. Wire rope 2. Nondestructive testing I. Y0995-01-004-621

Nondestructive test equipment for inspecting steel wire rope was evaluated in laboratory and field tests. Individual AC/DC units and a unitized AC/DC unit were tested on wire rope to detect broken wires and loss of metallic area from wear and corrosion. The unitized AC/DC units used Hall effect sensors to pick up the defects as opposed to sensor coils used in the individual AC/DC units. The Hall effect sensors enabled less equipment to be used to conduct a complete inspection and also permitted the wire rope to be inspected at speeds from 0 - 500 fpm. It is recommended that Navy facilities requiring nondestructive test inspection capability for metallic wire rope inspection procure the unitized AC/DC unit.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

CONTENTS

	Page
INTRODUCTION	1
BACKGROUND	2
THEORY	3
Individual AC/DC Units	3
DC Unit	3
AC Unit	4
Unitized AC/DC Unit	4
TESTS	5
Laboratory Test	5
Field Tests	6
Manitowoc Crane	6
Floating Crane	7
COMPARISON OF FEATURES	8
SUMMARY	8
RECOMMENDATIONS	8
APPENDIX - Description of Noranda's Magnograph Equipment	21

X

Dist. Special

A

INTRODUCTION

Wire rope inspection is a problem to the Navy. At present only the outside surface of wire ropes can be inspected for broken wires, wear, and corrosion. Typically, an inspector uses a rag held around a moving wire rope as an aid in finding broken wires (Figure 1). Caliper measurements of the outside diameter of the wire rope give data on wear, and rust stains indicate corrosion. However, inspection cannot be complete without knowledge of the condition of the interior of the rope. Therefore, wire rope replacement criteria are based on conservative standards, because the alternative is risk of injury or loss of life from a rope failure.

Nondestructive test (NDT) devices have the capability to detect broken wires, wear, and corrosion throughout the entire cross section of a metallic wire rope. This inspection technique is an order of magnitude superior to the present visual method. Because the condition of the rope is known with confidence, accidents could be reduced and replacement criteria improved.

The Office of Safety and Health Administration (OSHA) requires that wire ropes be inspected periodically (frequency of inspection depends on the application.) The Department of Defense follows OSHA guidelines, and many man-hours are used for wire rope inspections. Potential users of NDT inspection equipment within the Department of Defense are numerous. The following applications are indicative of potential users:

- Crane wire ropes
- Personnel elevator wire ropes
- Ship cargo elevator wire ropes
- Bridge cables
- Mooring lines
- Underway replenishment cables for ships
- Catapults and arresting cables on aircraft carriers
- Undersea cable arrays
- Tether lines for diving bells
- Guy lines for transmission and receiving antenna towers
- Tramway wire ropes

To expand on one application, that of cranes, the Long Beach Naval Shipyard has about 430 cranes, both large and small, that require inspection. This shipyard is only one of eight Navy yards. The inspectors have the authority to "red tag" any wire rope that they deem unsafe and, thus, prevent the use of the crane until the rope is replaced. NDT

equipment would greatly help the inspector in making decisions on whether a wire rope is safe by supplying technical data on the condition of the rope. Also, because some conservatism can be replaced by knowledge, it is likely that wire ropes will remain in service for longer periods of time.

This report on evaluating nondestructive test equipment for wire rope was sponsored by the Naval Facilities Engineering Command under the Specialized Inspection Systems (SPINS) Project.

BACKGROUND

NDT equipment for inspection of wire rope has been used for over 25 yr by the mining industry in many countries.* The United States has not participated in the mining industry's development of NDT inspection equipment.

Two basic types of equipment have been developed, which will be jointly called "individual AC/DC units." The AC unit uses alternating current to produce an electromagnetic field to detect loss of metallic area in the wire rope. The DC unit uses permanent magnets (analogous to a steady direct current) to detect broken wires. Typically, either AC or DC equipment is used in an inspection, seldom both. If DC is used, the wire rope needs to be demagnetized before AC can be used. The degaussing process is slow.

Recently a Canadian firm** developed a "unitized AC/DC system." This equipment can perform the functions of the individual AC/DC units during one pass of the wire rope through a sensor head. The equipment also has the feature of inspecting wire rope traveling at speeds from extremely slow to fast (0 - 500 fpm), whereas the individual DC unit can only function at rope speeds ranging from 50 to 500 fpm. The slow speeds are invaluable when trying to locate broken wires for detailed visual inspection.

During 1979, the Civil Engineering Laboratory worked with an individual DC unit. A U.S. firm*** which manufactured NDT equipment for quality control inspection of small diameter pipe, was contracted by CEL to adapt their equipment to 1-1/8-inch-diameter wire rope. The equipment used the same engineering principles of operation as the individual DC unit for wire ropes. The equipment was tested, and the results were reported in Reference 1.****

*Partial list of manufacturers of NDT equipment for wire rope:

Kundig AG, Switzerland
Academy of Mining and Metallurgy, Poland
Rotesco Ltd., Canada
ACMI, Belgium
Mitsui Miike, Japan
Plessey-Slack, South Africa

**Noranda Research Centre, Quebec, Canada. [Manufacturer is Heath and Sherwood (1964) Limited, Ontario, Canada.]

***Magnetic Analysis Corporation, New York.

****Civil Engineering Laboratory. Technical Memorandum M-40-80-2-R: Report on NDT inspection of wire rope using electromagnetic equipment, by Earl F. Buck, Phillip C. Zubieta, and Harvey H. Haynes. Port Hueneme, Calif., Mar 1980.

During the same time period, Noranda began to market a unitized AC/DC unit, called a Magnograph. CEL observed a demonstration test and subsequently procured a Magnograph unit for test and evaluation work.

During one sequence of laboratory and field tests, individual AC/DC units were tested side-by-side with the Magnograph. The Mine Safety and Health Administration, who owned and operated the individual AC/DC units for about 1 year, came to CEL with its equipment and an experienced operator for the comparison tests. The results of the comparison are presented herein along with other results and information on the Magnograph unit.

THEORY

The principles of operation for the individual AC/DC units and the unitized AC/DC unit will be discussed in the following sections.

Individual AC/DC Units

DC Unit: In the DC unit, strong permanent magnets are placed around a section of wire rope so that the rope becomes saturated with magnetic lines of flux (Figure 2). Lines of flux can be observed by iron filings sprinkled on top of a piece of paper having magnets underneath (Figure 3). The flux appears to "flow" from the north to south pole; however, the lines are stationary. The lines of flux are also distinct because of the existence of both attractive and repulsive forces. Saturation means that if stronger magnets were used, the number of lines of flux for a given cross section (flux density) would remain essentially unchanged.

If a broken wire were present in a saturated section of rope, then a north and south pole would be formed and the lines of flux would "jump" the gap (Figure 4). It is these lines of flux, called flux leakage, that can be detected to indicate a broken wire. Pitting from corrosion and localized wear will also interrupt the saturated lines of flux and cause flux leakage.

A classic physics experiment is to demonstrate that a magnetic field can produce an induced voltage in a conductor that is passed through the magnetic field. The conductor, passing at right angles through the lines of flux, must have a minimum travel speed through the flux field in order for the voltage to be large enough to measure (Figure 5).

Flux leakage in the wire rope is detected by using this phenomenon. However, in this case, the conductor is a search coil that is held stationary while the magnetic field is moving. In the inspection equipment, search coils are placed around the saturated wire rope between the poles of the permanent magnet. The rope travels at some minimum speed; thus, any flux leakage will also be moving and will pass through the search coils (Figure 6). When this occurs, an induced voltage is generated in the search coils, and, by proper amplification and conditioning of the signals, the broken wire is detected.

For the DC unit, there must be relative motion between the sensor coil and the wire rope. This means that the rope must travel through the sensor head or, for a stationary rope, the sensor head must travel along the wire rope. A minimum velocity of about 50 fpm is required.

Below this speed the induced voltage in the sensor coil is too small to detect broken wires. The velocity must also remain constant for signal strength to be consistent; however, to account for changes in velocity, the DC unit is built with a tachometer coupled to an amplifier so that signal strength can be amplified for changes in velocity.

Two search coils are usually built into the sensor head, as shown in Figure 6, to allow the head to clamp around the rope. Data output can take several forms because signals from two search coils are available. Usually two output traces are shown so signals from coil A and B can be displayed as a combination of A, B, $A + B$, $(A + B)^2$ or AB. Typically the data is displayed as $A + B$ on one trace and $(A + B)^2$ on the second trace.

AC Unit: A relatively weak alternating magnetic field is produced by electromagnets in an AC unit sensor head. These magnets function as the primary coil of a transformer (Figure 7). The wire rope serves the purpose of the ferromagnetic core of a transformer. A secondary coil in the middle of the sensor head produces an output voltage that is proportional to the magnetic flux "flowing" through the wire rope. Variations in the cross-sectional area of the wire rope influences the strength of the magnetic flux field and, thus, the strength of the output voltage. Hence, loss of metallic area can be measured by the output voltage.

The sensor coil measures the metallic volume over a 2- to 3-inch length of wire rope. Wear and corrosion can produce a significant volume change within the finite length, but a single broken wire with a small gap between the ends reduces the volume insignificantly. If many breaks occur within the finite length or a wire is missing, then a defect signal may be recorded.

In the AC unit, the magnetic flux field always varies with time because of the alternating field. Hence, a voltage is produced in the sensor coil whether or not the rope moves.

Because of the alternating magnetic field, small electric currents are induced that circulate around the rope axis within and between the wires. These eddy currents also alternate and produce their own magnetic fields which tend to oppose that from the primary field. This opposition produces a phase shift between the peaking of the magnetizing current and that of the sensor coil voltage. Built-in circuits in the instrumentation utilize the phase shift to produce a second data trace. The first data trace, called X, is essentially proportional to the axial component of the flux field in the rope, and therefore, measures loss of metallic area. The second trace, called R, is proportional to the magnitude of the eddy currents and reflects conditions within the rope that cause changes in the eddy currents. Corrosion products or lay tightening or loosening will affect the passage of eddy currents. Thus, by comparing the X and R traces, wear and corrosion can usually be differentiated.

Unitized AC/DC Unit

The unitized AC/DC unit uses a sensor head having strong permanent magnets to saturate the wire rope with magnetic flux. This is similar to the individual DC unit; however, the means of sensing the faults in the rope is different. Hall effect sensors are used to detect faults.

Hall effect sensors are solid state devices which can detect and accurately measure magnetic fields. Figure 8 shows a sketch of a sensor. Electrical wires are bonded to all four sides of a semiconductor chip. A constant current is passed between two opposing edges. The other two edges develop a potential difference when the semiconductor chip is placed in a magnetic field. The potential difference developed by the sensor is directly related to the strength of the flux field. Static magnetic fields can be measured; this is a feature not available in the individual AC/DC units. This means that ropes traveling at extremely slow speeds can be inspected, which is desirable when trying to pinpoint a fault location.

Figure 9 shows the placement of Hall effect sensors in the Magnograph sensor head which clamps around a wire rope. The Hall effect sensors located between the poles of the magnets pick up flux leakage, which indicates broken wires or other local faults (or LF). The Hall effect sensors at the poles of the magnets measure the quantity of flux "flowing" into the wire rope. When the cross-sectional area of steel changes, so does the flux "flowing" into the rope; thus, loss of metallic area (or LMA) is measured.

TESTS

Laboratory Test

A laboratory test was conducted on a new steel wire rope, 6 x 19 independent wire rope core, 1-1/8-inch diameter, extra improved plow steel, right lay hoisting rope, which contained man-made faults. Individual AC/DC units were tested along with the Magnograph unit (Figure 10).

Data from the tests are shown in Figures 11 through 13. The numbers on the traces identify the various faults, which are explained as:

1. "Broken" outside wire: A piece of wire 2 inches long (cut from the end of the rope) was taped into the groove between two strands.
2. Corrosion: A section of wire rope about 18 inches long was soaked in nitric acid for 35 minutes to produce mild corrosion of the steel.
3. Broken outside wire: A single wire on the outside surface was cut with a chisel.
4. Wear: A hand-held power grinder was used to wear away steel.
5. "Broken" inside wire: A piece of wire 1 inch long (cut from the end of the rope) was inserted in the middle of the wire rope.

Figure 11 shows the data from the individual DC unit. The top trace presents the data for sensor coils A and B as the square of the sum $(A + B)^2$ and the bottom trace as the sum $A + B$. The broken wires, numbers 1, 3, and 5, were detected well. Note that the direction of the signal spike is in the opposite direction for the added wires, numbers 1 and 5, than that for the cut wire, number 3.

Corrosion pitting and local, uneven wear cause flux leakage; these faults (numbers 2 and 4) were detected. Fault number 2 appears to be a larger wire break (or the sum of several wire breaks) than that of faults 1 and 3; however, corrosion can usually be distinguished from broken wires because of the length of rope over which corrosion occurs. This test rope had an unrealistically short length of rope with corrosion.

Figure 12 shows the data from the individual AC unit. Little data could be obtained from the AC unit because the equipment was designed for field test situations. The full-scale LMA trace was factory set at 25%; hence, with the pen set in the middle of the trace a $\pm 12.5\%$ loss of metallic area could be recorded. Faults 2 and 4 had LMA readings around 0.5% which were too small for the AC equipment to record. The chart paper speed was also factory set at one speed, 2 mm/sec, which is appropriate for long lengths of rope (thousands of feet) but not the short test length of wire rope. The bottom R trace, which gives a relative indication of magnetic permeability, did not produce meaningful data during the laboratory test.

Figure 13 shows the data from the Magnograph unit. The top trace is LMA data and bottom trace LF data. The LMA full-scale setting was set at 5%; hence, faults 2 and 4 were both recorded as having an LMA of 0.5%. The LF trace was essentially identical to that of Figure 11. Interpretation of data is made easier by having the LMA and LF traces together. The corrosion faults, 2 and 4, can be distinguished from the broken wire faults of 1, 3 and 5.

Field Tests

Manitowoc Crane: The load line to a Manitowoc crane, series 4100, having a lift capacity of 300 tons, was inspected using individual AC/DC units and the Magnograph unit. The wire rope was a 6 x 19 independent wire rope core, 1-1/8-inch diameter, improved plow steel, right lay hoisting rope. Approximately 600 ft of wire rope was inspected.

The individual DC unit produced a trace of local faults that showed three definite defects and two probable defects. The signal size for the probable defects was larger than background noise but not as large as the other defect signals. No attempt was made to try to locate the defects in the wire rope because: (a) there was no means to pinpoint the defects, (b) a length of rope from 3 to 5 yards long would have had to be cleaned and searched, and (c) inspection by the Magnograph was to follow where the defects could be pinpointed.

Prior to using the individual AC unit, the wire rope was degaussed. The process was not only slow but also unsafe. The design of the degaussing equipment required that the unit be held by hand as the rope moved through at a maximum speed of 50 fpm (Figure 14). The close proximity to a moving wire rope while the inspector's body became fatigued holding the degaussing box was unsafe. In addition, the copper strap clamp over the wire rope became hot from resistance to current flow.

In some situations, the AC unit could be used before the DC unit so that degaussing may not be necessary. However, any stray magnetic flux picked up by sections of a wire rope produce erroneous readings on the AC trace; those sections of wire rope, and only those sections, need to be degaussed. If at any time previously (meaning months and years), the wire rope was inspected with a DC unit, then the wire rope needs to be degaussed.

The AC unit was set up on the wire rope, but an inspection was not completed. Data were unusable because clean 115 VAC line power was not available. A generator source and available shore power source were tried; however, time was not sufficient to try other sources. Electrical equipment problems were encountered.

The Magnograph unit was the equipment tested last. Degaussing was not necessary prior to using the Magnograph unit. The local fault trace showed three distinct defects while the loss of metallic area trace showed negligible wear or corrosion. After locating the defects, they were identified as: (a) a 1-inch-long piece of wire that had been completely sheared off, (b) peening from the cable hitting the side of the drum, and (c) a nick on an outside wire.

The defects coincided with those from the DC unit in signal size and relative location along the length of the wire rope. The Magnograph unit showed absolutely no indication of the two probable faults shown on the DC trace. Standard procedure calls for a wire rope to run through the sensor head twice so that signal peaks from stray background noise can be eliminated as probable defect signals. Two runs were made with the DC unit and the probable defect signals appeared both times. Two runs were also made with the Magnograph unit and no indication of the questionable defects were found. It is the opinion of the authors that the probable defects did not exist. Subsequent testing indicated that the signal strength for the probable defects was too small to be faults.

Floating Crane: A floating crane, YD171, having a lift capacity of 350 tons, is stationed at the Long Beach Naval Shipyard (Figure 15). The crane was built in Germany in 1941 and brought to the United States after WW II. Since 1946, the records show that the main wire ropes have not been replaced.

The crane has a left and right main wire rope which service separate hooks of 175 tons lift capacity. Both of the wire ropes were scheduled for replacement by using "new" wire rope that came with the crane. The Civil Engineering Laboratory inspected the main wire ropes and the replacement wire ropes with the Magnograph equipment.

Both main wire ropes were 8 x 36 construction, 1-7/8 inches in diameter; however, the left main rope had a fiber core and the right main rope had an independent wire rope core. The replacement wire ropes were of the same size as the ropes in use and both had an independent wire rope core.

Each wire rope was 930 yards long. For the wire ropes on the crane, the middle 730 yards were inspected. At the drum end, a length of about 100 yards was wrapped on a drum, and at the boom end, about 100 yards was inaccessible for safe working conditions.

The results from the inspection found one broken wire in the right main wire rope and a loss of metallic area of about 1.5% from wear and corrosion in both main wire ropes. However, the left main wire rope, which had a fiber core, showed more evidence of corrosion pitting in the LF trace than the right main wire rope. In any event, 1.5% loss of metallic area was low (10% LMA is the level for wire rope replacement), so the wire ropes were in good condition.

The replacement wire ropes did not have any broken wires, but they did have a loss of metallic area on the order of 1.5%. Sections of wire rope showed corrosion pitting to be greater for the replacement rope than for the rope in use. This finding indicated that the maintenance of the wire rope on the crane must have been excellent over the years.

As an outcome of the nondestructive test, the wire rope on the floating crane was determined to be in a safe, usable condition and need not be replaced.

COMPARISON OF FEATURES

Table 1 is a summary of the instrumentation and operational features of the Magnograph unit and the individual AC/DC units. The Magnograph unit uses fewer components to conduct a test. Three pieces of equipment, the sensor head, electronics section, and recorder section, are required to obtain LF and LMA data. To obtain the same information, the individual AC/DC units requires five pieces: DC sensor head, DC electronics section, degausser unit, AC sensor head, and AC electronics section.

The Magnograph unit has two technical features that are superior to that of the individual AC/DC units. First, the LF and LMA data are displayed on the same brush chart recorder trace. This permits a more complete interpretation of the results. It is a definite aid to inexperienced personnel in determining what types of defects the data signals represent. Second, the sensor head picks up defect signals at slow wire rope speeds. This provides a means to quickly locate the defects for visual inspection.

SUMMARY

Laboratory and field tests were conducted on NDT equipment for wire rope. A unitized AC/DC unit was found to provide several important features that individual AC/DC units were technically unable to provide. Those features were:

- (a) A range of operating speeds from 0 to 500 fpm for wire rope traveling through the sensor head. The extremely slow speeds are important for locating defects for visual inspection. An individual DC unit is limited to 50 to 500 fpm.
- (b) Data displayed on a two-channel brush chart recorder that showed concurrently the local faults and the magnitude of loss of metallic area. Data interpretation is aided by these two important parameters being displayed together. Individual AC/DC units must measure local faults and loss of metallic area separately by using different equipment for each parameter.

The unitized AC/DC unit, developed by Noranda Research Centre and called the Magnograph unit, performed well in inspecting metallic wire ropes.

RECOMMENDATIONS

Based on the test and evaluation work reported herein, the unitized AC/DC unit has two important features over that of individual AC/DC units for Navy applications. Those features are listed in the summary section. It is recommended that the Navy procure unitized AC/DC equipment for meeting its needs in inspecting metallic wire rope.

In anticipation of Navy shipyards and other operational facilities providing their inspectors with NDT equipment, it is recommended that further tests be conducted using the Magnograph unit so that a compendium of defect signals can be published to assist inspectors in data interpretation. The operational limits of the equipment need further investigation, and this information also needs to be conveyed to inspectors by an operator's manual document.

Table 1. Comparison of Features Between Unitized and Individual Units

Item	Unitized AC/DC Unit (Magnograph)	Individual AC/DC Units	Comments
Instrumentation	One sensor head for detecting local faults (LF) and loss of metallic area (LMA). One electronic section used to condition signals and to record data on cassette tape. A second recorder unit used to record data on a two-channel brush chart. Total of three pieces.	One DC sensor head for detecting LF and a different AC sensor head for LMA. Degaussing required to demagnetize wire rope before using AC unit. An electronic section required for each DC and AC unit. Total of five pieces.	Magnograph requires only one set up on the wire rope to test for LF and LMA. AC/DC units require three setups for a complete test. A degaussing unit is needed between the DC and AC units.
Data Recording	Electronic section has FM cassette tape recorder. Recorder section has a Gould two-channel brush chart real time data display.	The DC and AC electronic sections contain Gould two-channel brush chart real time data display.	Data tape recording and playback capability of Magnograph is valuable for studying defect signals. Data on tape is good for record keeping and legal evidence.
Power Supply	Electronic section and Recorder section have built-in 6-hr capacity rechargeable batteries. Terminals available to use 12 VDC car battery and 115 VDC for charging or powering units.	DC and AC electronic sections both require "clean" 115 VAC, 60 Hz.	"Clean" line power (115 VAC) difficult to find under field conditions. AC/DC units require a car battery with converter if line power is not available.

continued

Table 1. Continued

Item	Unitized AC/DC Unit (Magnograph)	Individual AC/DC Units	Comments
Rope Speeds	Two speed settings are provided: a dynamic setting for wire rope speeds of 50-500 fpm, and a static setting for wire rope speeds of 0-50 fpm.	DC unit can operate at wire rope speeds of 50-500 fpm. AC unit can operate at wire rope speeds of 0-500 fpm.	Magnograph's static setting allows pinpoint location of LF defects for visual inspection (within 2 in.). DC unit can only locate defects within 3-5 yd.
Rope Sizes	Sensor head accommodates wire rope sizes of $\frac{1}{2}$ - to $2\frac{1}{2}$ -in. diam by providing four interchangeable sleeves. Sensor head weighs 105 lb. Manufacturer is building a smaller sensor head for wire rope sizes of $\frac{1}{2}$ - to $1\frac{1}{2}$ -in. diam. Three interchangeable sleeves will be provided. This sensor head weighs 65 lb.	DC sensor heads: (a) Small head for wire ropes $\frac{1}{2}$ - to 1-in. diam, weight 40 lb. (b) Medium head for wire ropes $\frac{1}{2}$ - to $1\frac{1}{4}$ -in. diam, weight 75 lb. (c) Large head for wire ropes $\frac{3}{4}$ - to $2\frac{1}{4}$ -in. diam, weight 105 lb. AC sensor head accommodates wire $\frac{3}{4}$ - to $2\frac{1}{4}$ -in. diam, weight 30 lb.	
Data Display	LF signals easily distinguished from background noise. LMA signals can be shown at full-scale values of 5, 10 and 25% loss of metallic area for cross section of wire rope.	LF signals easily distinguished from background noise. LMA signals shown at full-scale value of 25%.	

continued

Table 1. Continued

Item	Unitized AC/DC Unit (Magnograph)	Individual AC/DC Units	Comments
	Chart paper speed controlled two ways: (a) Time drive, setting of 1, 2, 5, 10, 25, and 50 mm/sec. (b) Proportional drive chart length represents wire rope length with ratios of 1, 2, 5, and 10 mm/yard of wire rope. Length of wire rope tested is shown in two ways: (a) Digital display on electronics section (yards or meters) (b) Brush chart recorder has two markers, one marks off yards (meters) and the other marks off 50- and 100-yd (meter) distances. (c) Direction of rope travel is shown by yard marker. Speed of the wire rope is digitally displayed on the electronics section and recorded on tape.	Chart speed controlled by time drive: For DC unit, chart speeds of 1, 2, 5, 10, 25, and 50 mm/sec are available. For AC unit, the chart speed is set at 2 mm/sec. Length of wire rope tested is shown in two ways: (a) A mechanical counter records rope length. The counter does not subtract if the wire rope changes direction. (b) A marker marks 100-ft distances on brush chart. Speed of wire rope is shown on a mechanical gauge on the electronics section.	Proportional drive on Magnograph is useful when rope speeds vary during test. The chart is proportional to the wire rope length. Future charts can be made the same length for data comparison



Figure 1. Conventional method for inspector to locate broken wires on outside of wire rope.




Figure 2. Saturation of wire rope with lines of flux.




Figure 3. Lines of flux.




Figure 4. Flux leakage at location of broken wire.




Figure 5. A current is created in a conductor moving through lines of flux.




Figure 6. Search coils pick up radial component of flux leakage.




Figure 7. The basic principle of the AC method.




Figure 8. Sketch of a Hall effect sensor.




Figure 9. Hall effect sensor placement for the Magnograph.



Figure 10. Setup of Magnograph nondestructive test equipment for a test on a crane wire rope. Electronic and recorder sections are in foreground and sensor head in background.




Figure 11. Data from laboratory test on an individual DC unit.




Figure 12. Data from Laboratory test on an individual AC unit.





Figure 13. Data from laboratory test on the Magnograph unit.




Figure 14. Degaussing wire rope between tests using individual DC and AC units.




Figure 15. Floating crane at Long Beach Naval Shipyard.

Appendix

DESCRIPTION OF NORANDA'S MAGNOGRAPH EQUIPMENT

FRONT PANEL CONTROLS - ELECTRONICS (Figures A-1 and A-2)

1. Power ON/OFF Switch (should be OFF during battery charging)
2. Powerline/Mains connection
3. Sensor Head Connection (NOT necessary during playback mode)
4. Chart Recorder Connection
5. Battery Check Switch:
When depressed, battery state is indicated on LMA analog meter (6).
6. LMA Analog Meter:
Displays same signal as the chart recorder LMA channel during record and playback. May also be used for zero adjustment.
7. Metric/English Switch:
Selects either SI or Imperial Units as the basis of all measurements.
8. Rope Direction Switch:
Changes counting direction of Measured Length Up/Down Counter.
9. Loss of Metallic Area (LMA) Gain Potentiometer:
Used to set the gain of the LMA Channel according to the size and type of rope being tested.
10. LMA Zero Potentiometer:
Used to zero the LMA Signal before commencing a test.
11. Offset % LMA Switch:
Used during a test (if necessary) to move the LMA zero by a fixed percentage.

12. Local Fault (LF) Gain Potentiometer:
Used to set the gain of the LF Channel according to the size and type of rope being tested.
13. LF Zero Potentiometer:
Used to zero the LF signal before commencing a test.
14. Compression Band Division Switch:
Used to reduce the rope noise component of the LF signal.
15. LF Analog Meter:
Displays similar signals to the Chart Recorder LF channel, during record and playback. Also may be used for zero adjustment.
16. Static/Dynamic Switch:
Normally used in Dynamic mode for rope speeds 50 to 500 fpm. Below 50 fpm, static mode should be selected.
17. Measured Length Counter (and Reset):
Displays distance traveled along a rope. Counts both Up and Down. Can be Reset using the push button.
18. Wire Rope Speed:
Displays the rate of movement of the rope through the Sensor Head.
19. Tape Counter (and Reset):
Indicates position on the tape cassette.
20. Record/Play Switch:
Selects either Record or Playback mode for both the cassette recorder and the internal electronics.
21. Cassette Tape Recorder with Standard Controls:
Record Button
Tape Run
Rewind
Stop
Fast Forward
22. External Battery Connections
23. External Battery Power Indicator (illuminates if connection is correctly made)

FRONT PANEL CONTROLS - CHART RECORDER (Figure A-3)

1. Power Line/Mains Connection
2. External Battery Power Indicator Light (illuminates if connection is correctly made)
3. External Battery Connections
4. LF (Local Fault) Channel Input (for test purposes only)
5. LF Channel Pen Position
6. LF Sensitivity Variable Potentiometer:
Should be fully clockwise
7. LF Sensitivity Switch:
Should be set at 10 mV for Magnograph recordings
8. LF Channel Input Shorting Switch
9. LMA Channel Input Shorting Switch
10. Chart Speed Selectors:
Used when TIME BASE mode is selected
11. Battery State Indicators:
Battery needs recharging when indicator enters the red area
12. LMA (Loss of Metallic Area) Sensitivity Switch
13. LMA Sensitivity Potentiometer:
Should be fully clockwise
14. LMA Channel Pen Position
15. LMA Channel Input (for test purposes only)
16. Electronics Section Connector
17. Proportional Drive Selector:
Selects chart recorder timebase or proportional drive




Figure A-1. Front panel controls, electronics section.




Figure A-2. View of Magnograph sensor head.




Figure A-3. Front panel controls, chart recorder.

DISTRIBUTION LIST

AAP NAVORDSTA IND HD DET PW ENGRNG DIV, McAlester, OK
 AFB (AFITLD), Wright-Patterson OH; AF Tech Office (Mgt & Ops), Tyndall, FL; AFCECXR, Tyndall FL;
 CESCH, Wright-Patterson; HQ Tactical Air Cmd (R. E. Fisher), Langley AFB VA; HQAFESC/DEMM,
 Tyndall AFB, FL; MACDET (Col. P. Thompson) Scott, IL; SAMSO/MNND, Norton AFB CA; Stinfo
 Library, Offutt NE
 ARCTICSUBLAB Code 54, San Diego, CA
 ARMY ARRADCOM, Dover, NJ; BMDSC-RE (H. McClellan) Huntsville AL; DAEN-CWE-M (I.T.C.D.
 Binning), Washington DC; DAEN-FEU-E (J. Ronan), Washington DC; DAEN-MPE-D Washington DC;
 DAEN-MPU, Washington DC; ERADCOM Tech Supp Dir. (DELS-D) Ft. Monmouth, NJ;
 HQ-DAEN-MPO-B (Mr. Price), Tech. Ref. Div., Fort Huachuca, AZ
 ARMY - CERL Library, Champaign IL
 ARMY COASTAL ENGR RSCH CEN Fort Belvoir VA; R. Jachowski, Fort Belvoir VA
 ARMY COE Philadelphia Dist. (LIBRARY) Philadelphia, PA
 ARMY CORPS OF ENGINEERS MRD-Eng. Div., Omaha NE; Seattle Dist. Library, Seattle WA
 ARMY CRREL A. Kovacs, Hanover NH; Constr. Engr Res Branch, (Aamot)
 ARMY CRREL R.A. Eaton
 ARMY DARCOM AMCPM-CS (J. Carr), Alexandria VA
 ARMY ENG DIV HNDED-CS, Huntsville AL; HNDED-SR, Huntsville, AL
 ARMY ENG WATERWAYS EXP STA Library, Vicksburg MS
 ARMY ENGR DIST. Library, Portland OR
 ARMY ENVIRON. HYGIENE AGCY Water Qual Div (Doner), Aberdeen Prov Ground, MD
 ARMY MAT SYS ANALYSIS ACT Code DRXSY-CM (M Ogorzalek) Aberdeen Proving Grnd MD
 ARMY MATERIALS & MECHANICS RESEARCH CENTER Dr. Lenoe, Watertown MA
 ARMY MOBIL EQUIP R&D COM Code DRXFB-MR Fort Belvoir VA; F Stora Fort Belvoir VA; Fuel
 Hndng Equip Br., Ft Belvoir, VA; Mr. Cevalco, Fort Belvoir MD
 ARMY MTMC Trans Engr Agency (D F Eichhorn) Newport News VA
 ARMY TRANSPORTATION SCHOOL MAJ T Sweeney, Code ATSP CD-TE Fort Eustis VA; V Quinby Code
 ATSP-CPO-MS Fort Eustis VA
 ARMY TRNG & DOCTRINE CMD Code ATCD-SP-L Fort Monroe VA
 ASST SECRETARY OF THE NAVY Spec. Assist Energy (Leonard), Washington, DC; Spec. Assist
 Submarines, Washington DC
 BUREAU OF COMMERCIAL FISHERIES Woods Hole MA (Biological Lab. Lib.)
 BUREAU OF RECLAMATION Code 1512 (C. Selander) Denver CO
 CENTER FOR NAVAL ANALYSES Document Center (Darke), Arlington, VA
 CINCLANT Civil Engr. Supp. Plans. Ofc Norfolk, VA
 CINCPAC Fac Engrng Div (J44) Makalapa, HI
 CNAVRES Code 13 (Dir. Facilities) New Orleans, LA
 CNM Code 03462, Washington DC; Code 043 Washington DC; Code MAT-08T3, Washington, DC
 CNO Code NOP-964, Washington DC; Code OP 323, Washington DC; Code OP 405, Washington DC; Code OP
 405, Wasington DC; Code OP 414 Washington DC; Code OP 414, Washington DC; Code OP 97 Washinton
 DC; Code OP 97 Washington DC; Code OP 987 Washington DC; Code OP 987 Washinton DC; Code OP323
 Washington DC; Code OPNAV 09B24 (H); Code OPNAV 22, Wash DC; Code OPNAV 23, Wash DC;
 OP987J (J. Boosman), Pentagon
 COMCBPAC Operations Offr, Makalapa HI
 COMDEVGRUONE San Diego, CA
 COMFAIRWESTPAC Security Offr, Misawa Japan
 COMFLEACT, OKINAWA PWO, Kadena, Okinawa
 COMNAVBEACHPHIBREFTRAGRU ONE San Diego CA
 COMNAVMARIANAS Code N4, Guam
 COMOCEANSYSPAC SCE, Pearl Harbor HI
 COMSUBDEVGRUONE Operations Offr, San Diego, CA
 NAVSURFLANT Norfolk, VA
 NAVSURFPAC San Diego, CA
 COMOPTEVFOR CMDR, Norfolk, VA; Code 701A, San Diego, CA

DEFENSE INTELLIGENCE AGENCY Dir., Washington DC
 DISIE Army Logistics Mgt Center, Fort Lee, VA
 DNA STTL, Washington DC
 DOE Dr. Cohen; Litlick, Richmond, VA
 DTIC Defense Technical Info Ctr Alexandria, VA
 DTNSRDC Anna Lab (Code 1175) Annapolis MD; Anna Lab (Code 1175) Annapolis MD; Anna Lab (Code 1568) Annapolis MD
 DTNSRDC Code 172 (M. Krenzke), Bethesda MD
 DTNSRDC Code 2785 (Bloomquist), Annapolis, MD; Code 284 (A. Rufolo), Annapolis MD
 DTNSRDC Code 4111 (R. Gierich), Bethesda MD
 DTNSRDC Code 4121 (R. Rivers), Annapolis, MD
 DTNSRDC Code 42, Bethesda MD
 DTNSRDC Code 522 (Library), Annapolis MD
 FLTCOMBATTRACENLANT PWO, Virginia Bch VA
 FMFLANT CEC Offr, Norfolk VA
 FMFPAC CG Pearl Harbor
 GSA Fed. Sup. Serv. (FMBP), Washington DC
 HCU ONE CO, Bishops Point, HI
 KWAJALEIN MISRAN BMDSC-RKL-C
 LIBRARY OF CONGRESS Washington, DC (Sciences & Tech Div)
 MARINE CORPS BASE Camp Pendleton CA 92055; Code 43-260, Camp Lejeune NC; First Service Support Group Camp Pendleton CA; M & R Division, Camp Lejeune NC; PWO Camp Lejeune NC; PWO, Camp S. D. Butler, Kawasaki Japan
 MARINE CORPS HQS Code LFF-2, Washington DC
 MCAS Facil. Engr. Div. Cherry Point NC; CO, Kaneohe Bay HI; Code PWE, Kaneohe Bay HI; Code S4, Quantico VA; PWD, Dir. Maint. Control Div., Iwakuni Japan; PWO Kaneohe Bay HI; PWO, Yuma AZ
 MCDEC NSAP REP, Quantico VA; P&S Div Quantico VA
 MCRD PWO, San Diego Ca
 MILITARY SEALIFT COMMAND Washington DC
 NAD Engr. Dir. Hawthorne, NV
 NAF PWD - Engr Div, Atsugi, Japan; PWO Sigonella Sicily; PWO, Atsugi Japan
 NALF OINC, San Diego, CA
 NARF Code 100, Cherry Point, NC; Code 640, Pensacola FL; Equipment Engineering Division (Code 61000), Pensacola, FL
 NAS CO, Guantanamo Bay Cuba; Code 114, Alameda CA; Code 183 (Fac. Plan BR MGR); Code 18700, Brunswick ME; Code 18U (ENS P.J. Hickey), Corpus Christi TX; Code 6234 (G. Trask), Point Mugu CA; Code 70, Atlanta, Marietta GA; Code 8E, Patuxent Riv., MD; Dir. Maint. Control Div., Key West FL; Dir. Util. Div., Bermuda; ENS Buchholz, Pensacola, FL; Lakehurst, NJ; Lead. Chief, Petty Offr, PW/Self Help Div, Beeville TX; OIC, CBU 417, Oak Harbor WA; PW (J. Maguire), Corpus Christi TX; PWD Maint. Cont. Dir., Fallon NV; PWD Maint. Div., New Orleans, Belle Chasse LA; PWD, Maintenance Control Dir., Bermuda; PWD, Willow Grove PA; PWO Belle Chasse, LA; PWO Chase Field Beeville, TX; PWO Key West FL; PWO, Dallas TX; PWO, Glenview IL; PWO, Kingsville TX; PWO, Millington TN; PWO, Miramar, San Diego CA; PWO., Moffett Field CA; ROICC Key West FL; SCE Lant Fleet Norfolk, VA; SCE Norfolk, VA; SCE, Barbers Point HI; Security Offr, Alameda CA
 NATL BUREAU OF STANDARDS B-348 BR (Dr. Campbell), Washington DC
 NATL RESEARCH COUNCIL Naval Studies Board, Washington DC
 NATNAVMEDCEN PWO Bethesda, MD
 NAVACT PWO, London UK
 NAVACTDET PWO, Holy Lock UK
 NAVAEROSPREGMEDCEN SCE, Pensacola FL
 NAVAVIONICFAC PWD Deputy Dir. D-701, Indianapolis, IN
 NAVCHAPGRU CO Williamsburg VA
 NAVCOASTSYSCEN Code 719, Panama City, FL; Code 772 (C B Koesy) Panama City FL
 NAVCOASTSYSTCTR CO, Panama City FL; Code 423 (D. Good), Panama City FL; Code 713 (J. Quirk) Panama City, FL; Code 715 (J. Mittleman) Panama City, FL; Library Panama City, FL
 NAVCOMMAREAMSTRSTA Code W-602, Honolulu, Wahiawa HI; Maint Control Div., Wahiawa, HI, PWO, Norfolk VA; PWO, Wahiawa HI; SCE Unit 1 Naples Italy

NAVCOMMSTA CO, San Miguel, R.P.; Code 401 Nea Makri, Greece; PWO, Exmouth, Australia; PWO, Fort Amador Canal Zone
 NAVEDITRAPRODEVEN Tech. Library
 NAVEDUTRACEN Engr Dept (Code 42) Newport, RI
 NAVELEXSYSCOM Code PME-124-61, Washington DC
 NAVENVIRHLTHCEN CO, Norfolk, VA
 NAVFODFAC Code 605, Indian Head MD
 NAVFAC PWO, Cape Hatteras, Buxton NC; PWO, Centerville Bch, Ferndale CA; PWO, Guam
 NAVFAC PWO, Lewes DE
 NAVFACENGCOM Code 043 Alexandria, VA; Code 044 Alexandria, VA; Code 0451 Alexandria, VA; Code 0453 (D. Potter) Alexandria, VA; Code 0453C, Alexandria, VA; Code 0454B Alexandria, VA; Code 046; Code 0461D (V M Spaulding) Alexandria, VA; Code 04B3 Alexandria, VA; Code 04B5 Alexandria, VA; Code 06, Alexandria VA; Code 100 Alexandria, VA; Code 1002B (J. Lemmanis) Alexandria, VA; Code 1113 (M. Carr) Alexandria, VA; Code 1113 (T. Stevens) Alexandria, VA; Code 1113 Alexandria, VA; Morrison Yp, Caroline Is.; P W Brewer Alexandria, VA; PC-2 Alexandria, VA
 NAVFACENGCOM - CHES DIV, Code 101 Wash, DC; Code 402 (D Scheeseley) Washington, DC; Code 403 (H. DeVoe) Wash, DC; Code 405 Wash, DC; Code FPO-1 Wash, DC; Code FPO-11P, Wash, DC; Code FPO-1E, Wash, DC; Contracts, ROICC, Annapolis MD; FPO-1 (Spencer) Wash, DC; FPO-1 Wash, DC
 NAVFACENGCOM - LANT DIV, Code 10A, Norfolk VA; Eur. BR Deputy Dir, Naples Italy; European Branch, New York; RDT&ELO 102, Norfolk VA
 NAVFACENGCOM - NORTH DIV, (Boretsky) Philadelphia, PA; CO, Code 09P (LCDR A.J. Stewart); Code 1028, RDT&ELO, Philadelphia PA; Code 111 (Castranovo) Philadelphia, PA; Code 114 (A. Rhoads); Design Div. (R. Masino), Philadelphia PA; ROICC, Contracts, Crane IN
 NAVFACENGCOM - PAC DIV, (Kyi) Code 101, Pearl Harbor, HI; Code 2011 Pearl Harbor, HI; Code 402, RDT&E, Pearl Harbor HI; Commander, Pearl Harbor, HI
 NAVFACENGCOM - SOUTH DIV, Code 90, RDT&ELO, Charleston SC; ROICC (LCDR R. Moeller), Contracts, Corpus Christi TX
 NAVFACENGCOM - WEST DIV, 102; 112; AROICC, Contracts, Twentynine Palms CA; Code 04B San Bruno, CA; 09P20 San Bruno, CA; RDT&ELO Code 2011 San Bruno, CA
 NAVFACENGCOM CONTRACT AROICC, Point Mugu CA; AROICC, Quantico, VA; Code 05, TRIDENT, Bremerton WA; Dir, Eng. Div., Exmouth, Australia; Eng Div dir, Southwest Pac, Manila, PI; OICC, Southwest Pac, Manila, PI; OICC/ROICC, Balboa Canal Zone; ROICC AF Guam; ROICC LANT DIV., Norfolk VA; ROICC, Diego Garcia Island; ROICC, Keflavik, Iceland; ROICC, Pacific, San Bruno CA
 NAVMAG SCE, Guam
 NAVMIRO OIC, Philadelphia PA
 NAVNUPWRU MUSE DET Code NPU-30 Port Hueneme, CA
 NAVOCEANO Code 1600 Bay St. Louis, MS; Code 3432 (J. DePalma), Bay St. Louis MS
 NAVOCEANSYSCEN Code 41, San Diego, CA; Code 4473 Bayside Library, San Diego, CA; Code 52 (H. Talkington) San Diego CA; Code 5204 (J. Stachiw), San Diego, CA; Code 5214 (H. Wheeler), San Diego CA; Code 5221 (R. Jones) San Diego CA; Code 5311 San Diego, CA; Code 6700, San Diego, CA; Research Lib., San Diego CA; Tech. Library, Code 447
 NAVORDSTA PWO, Louisville KY
 NAVPETOFF Code 30, Alexandria VA
 NAVPGSCOL D. Lepper, Monterey CA; E. Thornton, Monterey CA
 NAVPHIBASE C O ACB ONE San Diego CA; CO, ACB 2 Norfolk, VA; COMNAVBEACHGRU TWO Norfolk VA; Code S3T, Norfolk VA; Dir, Amphib, Warfare Brd Staff, Norfolk, VA; Harbor Clearance Unit Two, Little Creek, VA
 NAVRADREFAC PWO, Kami Seya Japan
 NAVREGMEDCEN Code 3041, Memphis, Millington TN; PWO Newport RI; PWO Portsmouth, VA; SCE (D. Kaye), SCE San Diego, CA; SCE, Camp Pendleton CA; SCE, Guam; SCE, Oakland CA
 NAVSCOLCECOFF C35 Port Hueneme, CA; CO, Code C44A Port Hueneme, CA
 NAVSEASYSYSCOM Code 00C-DG DiGeorge, Washington, DC; Code 0325, Program Mgr, Washington, DC; Code OOC (LT R. MacDougall), Washington DC; Code OOC-D, Washington, DC; Code PMS 395 A 3, Washington, DC; Code PMS 395 A2, Washington, DC; Code SEA OOC Washington, DC, PMS-395 A1, Washington, DC; PMS-395, Washington, DC
 NAVSEC (J. Reagan), Washington DC; Code 6034 (Library), Washington DC; Code 6156D, Washington, DC; Code 6157D, Washington, DC
 NAVSECGRUACT Facil. OIL, Galeta Is. Canal Zone; PWO, Adak AK; PWO, Edzell Scotland; PWO, Puerto Rico; PWO, Torri Sta. Okinawa; Security Oftr, Winter Harbor ME
 NAVSHIPREFAC Library, Guam; SCE Subic Bay
 NAVSHIPYD; Code 202.4, Long Beach CA; Code 202.5 (Library) Puget Sound, Bremerton WA; Code 280,

Mare Is., Vallejo, CA; Code 380. (Woodruff) Norfolk, Portsmouth, VA; Code 400, Puget Sound; Code 404 (L. J. Riccio), Norfolk, Portsmouth VA; Code 410, Mare Is., Vallejo CA; Code 440 Portsmouth NH; Code 440, Norfolk; Code 440, Puget Sound, Bremerton WA; Code 450, Charleston SC; L. D. Vivian, Library, Portsmouth NH; PWD (Code 400), Philadelphia PA; PWO, Mare Is., PWO, Puget Sound; SCT, Pearl Harbor HI; Salvage Supt, Phila., PA; Tech Library, Vallejo, CA
 NAVSTA AROICC, Brooklyn NY; CO Naval Station, Mayport FL; CO Roosevelt Roads P.R. Puerto Rico; CO, Brooklyn NY; Code 4, 12 Marine Corps Dist., Treasure Is., San Francisco CA; Dir Mech Engr, Gtmo. Engr. Dir., Rota Spain, Long Beach, CA; Maint. Cont. Div., Guantanamo Bay Cuba; Maint. Div. Dir Code 531, Rodman Canal Zone; PWD (L. J. P. M. Motolenich), Puerto Rico; PWO Midway Island, PWO, Guantanamo Bay Cuba, PWO, Keflavik Iceland; PWO, Mayport FL; ROICC Rota Spain, ROICC, Rota Spain; SCE, Guam, SCE, San Diego CA; SCE, Subic Bay, R.P. Security Offr., San Francisco, CA; Utilities Engr Offr. (A.S. Ritchie), Rota Spain
 NAVSUBASE Bangor, Bremerton, WA; SCE, Pearl Harbor HI
 NAVSUPACT CO, Seattle WA; Code 413, Seattle WA; LTJG McGarrath, SEC, Vallejo, CA; Plan Engr. Div., Naples Italy
 NAVSUREWPCEN PWO, White Oak, Silver Spring, MD
 NAVTECHIRACEN SCE, Pensacola FL
 NAVWPNCEN Code 2636 (W. Bonner), China Lake CA; PWO (Code 26) China Lake CA; ROICC (Code 702), China Lake CA
 NAVWPNEVALFAC Sec Offr, Kirtland AFB, NM; Technical Library, Albuquerque NM
 NAVWPNSA (Clebak) Colts Neck, NJ; Code 092, Colts Neck NJ; Maint. Control Dir., Yorktown VA
 NAVWPNSA PW Office (Code 09C1) Yorktown, VA
 NAVWPNSA PWO, Seal Beach CA
 NAVWPNSUPPCEN Code 09 Crane IN
 NCBU 405 OIC, San Diego, CA
 NCBC Code 10 Davisville, RI; Code 155, Port Hueneme CA; Code 156, Port Hueneme, CA; Code 400, Gulfport MS; PW Engrg, Gulfport MS; PWO (Code 80) Port Hueneme, CA; PWO, Davisville RI
 NCBU 411 OIC, Norfolk VA
 NCR 20, Commander; FWD 30th CDR Diego Garcia Island
 NCSO BAHRAIN Security Offr, Bahrain
 NMCB 5, Operations Dept., 74, CO, Forty, CO; THREE, Operations Offr.
 NOAA Library, Rockville, MD
 NORDA Code 410 Bay St. Louis, MS; Code 440 (Ocean Resch Offr) Bay St. Louis MS; Code 500, Bay St. Louis, MS
 NRI, Code 8400 Washington, DC; Code 8441 (R.A. Skop), Washington DC; Rosenthal, Code 8440, Wash. DC
 NSC Code 541 (Wynne), Norfolk VA
 NSD SCE, Subic Bay, R.P.
 NTC Commander Orlando, FL; OICC, CBU-401, Great Lakes II
 NUCLEAR REGULATORY COMMISSION T.C. Johnson, Washington, DC
 NUSC Code 131 New London, CT; Code FA123 (R.S. Mc...), New London CT; Code S332, B-80 (J. Wilcox), Code SB 331 (Brown), Newport RI; Code FA131 (G. D. La Cruz), New London CT
 OCEANAV Mangmt Info Div., Arlington VA
 OCEANSYSTANT LT AR, Giancola, Norfolk VA
 OFFICE SECRETARY OF DEFENSE ASD (MRA&L) Code CSS CC Washington, DC
 ONR (Dr. F. A. Silva) Arlington, VA; Central Regional Office, Boston, MA; Code 221, Arlington VA; Code 481, Arlington VA; Code 481, Bay St. Louis, MS; Code 700F Arlington VA; Dr. A. Fauler, Pasadena CA
 PACMISRANFAC CO, Kekaha HI
 PHIBCB 1 P&E, Coronado, CA
 PMTC Code 3144, Point Mugu, CA; Code 3331 (S. Opatowsky) Point Mugu, CA; Code 4253.3, Point Mugu, CA; FOD Mobile Unit, Point Mugu, CA; Pat. Counsel, Point Mugu CA
 PWC (Lt. E. S. Agonoy) Pensacola, FL; ACE Office (LTJG St. Germain) Norfolk VA; CO Norfolk VA; CO, (Code 10), Oakland, CA; CO, Great Lakes II; Code 10, Great Lakes, II; Code 110, Oakland, CA; Code 120, Oakland CA; Code 120C, (Library) San Diego, CA; Code 128, Guam; Code 154, Great Lakes, II; Code 200, Great Lakes II; Code 200, Guam; Code 220 Oakland, CA; Code 220.1, Norfolk VA; Code 30C, San Diego, CA; Code 400, Great Lakes, II; Code 400, Oakland, CA; Code 400, Pearl Harbor, HI; Code 400, San Diego, CA; Code 420, Great Lakes, II; Code 420, Oakland, CA; Code 505A (H. Wheeler), Code 600, Great Lakes, II; Code 601, Oakland, CA; Code 610, San Diego CA; Code 700, Great Lakes, II; Code

700, San Diego, CA; THG J.L. McClane, Yokosuka, Japan, Library, Subic Bay, R.P., Utilities Officer,
Guam, NO (Code 20) Oakland, CA
SPCC PWO (Code 120) Mechanicsburg PA
UCT TWO OIC, Norfolk, VA, OIC, Port Hueneue CA
US MERCHANT MARINE ACADEMY Kings Point, NY (Reprint Custodian)
US DEPT OF INTERIOR Bureau of Land MNGMNT - Code 733 (J.L. Sullivan) Wash, DC
US GEOLOGICAL SURVEY Off Marine Geology, Pitelekt, Reston VA
US NATIONAL MARINE FISHERIES SERVICE Highlands NY (Sandy Hook Lab-Library)
US NAVAL FORCES Korea (ENJ-P&O)
USAF SCHOOL OF AEROSPACE MEDICINE Hyperbaric Medicine Div, Brooks AFB, TX
USCG (G-ECV) Washington Dc; (GMP-3 USP 82) Washington Dc; (Smith), Washington, DC; G-1 OF-461 (L.
Dowd), Washington DC
USCG R&D CENTER CO Groton, CT, D. Motherway, Groton CT; Tech. Dir. Groton, CT
USDA Forest Products Lab, Madison WI; Forest Products Lab. (R. DeGroot), Madison WI; Forest Service,
Bowers, Atlanta, GA, Forest Service, San Dimas, CA
USU COM (ECJ41-LO), Wright, Stuttgart, GE
USNA Civil Engr Dept (R. Erchyl) Annapolis MD; Ocean Sys. Eng Dept (Dr. Monney) Annapolis, MD; PWD
Engr. Div. (C. Bradford) Annapolis MD; PWO Annapolis MD
AMERICAN CONCRETE INSTITUTE Detroit MI (Library)
AMERICAN UNIVERSITY Washington DC (M. Norton)
CALIF. DEPT OF NAVIGATION & OCEAN DEV. Sacramento, CA (G. Armstrong)
CALIF. MARITIME ACADEMY Vallejo, CA (Library)
CALIFORNIA INSTITUTE OF TECHNOLOGY Pasadena CA (Keck Ref. Rm)
CALIFORNIA STATE UNIVERSITY LONG BEACH, CA (CHELAPATH); LONG BEACH, CA (YEN)
CATHOLIC UNIV. Mech Engr Dept, Prof. Niedzwecki, Wash., DC
COLORADO STATE UNIV., FOOTHILL CAMPUS Fort Collins (Nelson)
CORNELL UNIVERSITY Ithaca NY (Serials Dept, Engr Lib.)
DAMES & MOORE LIBRARY LOS ANGELES, CA
DUKE UNIV MEDICAL CENTER B. Muga, Durham NC; DURHAM, NC (VESIC)
FLORIDA ATLANTIC UNIVERSITY Boca Raton FL (W. Hartt); Boca Raton FL (W. Tessin); Boca Raton,
FL (McAllister)
FLORIDA TECHNOLOGICAL UNIVERSITY ORLANDO, FL (HARTMAN)
GEORGIA INSTITUTE OF TECHNOLOGY (J.T. R. Johnson) Atlanta, GA
INSTITUTE OF MARINE SCIENCES Morehead City NC (Director)
IOWA STATE UNIVERSITY Ames IA (CE Dept, Handy)
WOODS HOLE OCEANOGRAPHIC INST. Woods Hole MA (Winget)
LEHIGH UNIVERSITY BETHLEHEM, PA (MARINE GEOTECHNICAL LAB., RICHARDS); Bethlehem
PA (Fritz Engr. Lab No. 1; Beedle), Bethlehem PA (Linderman Lib. No 30, Flecksteiner)
MARITIME ACADEMY CASTINE, ME (LIBRARY)
MICHIGAN TECHNOLOGICAL UNIVERSITY Houghton, MI (Haas)
MIT Cambridge MA, Cambridge MA (Rm 10-500, Tech. Reports, Engr. Lab.); Cambridge, MA (Harleman)
NAH ACADEMY OF ENG. ALEXANDRIA, VA (SEARLE, JR.)
NEW MEXICO SOLAR ENERGY INST. Dr. Zwiibel Las Cruces NM
NY CITY COMMUNITY COLLEGE BROOKLYN, NY (LIBRARY)
OREGON STATE UNIVERSITY (CE Dept Grace) Corvallis, OR, CORVALLIS, OR (CE DEPT, BELL);
CORVALLIS, OR (CE DEPT, HICKS); Corvallis OR (School of Oceanography)
PENNSYLVANIA STATE UNIVERSITY STATE COLLEGE, PA (SNYDER), UNIVERSITY PARK, PA
(GOTOISKI)
PURDUE UNIVERSITY Lafayette IN (Leonards); Lafayette, IN (Altschaeffl); Lafayette, IN (CE Engr. Lib)
SAN DIEGO STATE UNIV. I. Noorany San Diego, CA
SCRIPPS INSTITUTE OF OCEANOGRAPHY LA JOLLA, CA (ADAMS); San Diego, CA (Marina Phy. Lab
Spies)
SEATTLE U Prof. Schwaegler Seattle WA
SOUTHWEST RSCH INST King, San Antonio, TX, R. DeHart, San Antonio TX
STANFORD UNIVERSITY Engr Lib, Stanford CA
STATE UNIV. OF NEW YORK Buffalo, NY, Fort Schuyler, NY (Longobardi)
TEXAS A&M UNIVERSITY College Station TX (CE Dept, Herbich); W.B. Ledbetter College Station, TX
UNIVERSITY OF ALASKA Marine Science Inst. College, AK

UNIVERSITY OF CALIFORNIA BERKELEY, CA (CE DEPT. GERWICK); BERKELEY, CA (CE DEPT. MITCHELL); Berkeley CA (B. Bresler); Berkeley CA (Dept of Naval Arch.); Berkeley CA (Pearson); DAVIS, CA (CE DEPT. TAYLOR); La Jolla CA (Acq. Dept. Lib. C-075A); M. Duncan, Berkeley CA; SAN DIEGO, CA, LA JOLLA, CA (SEROCK)
 UNIVERSITY OF CONNECTICUT Groton CT (Inst. Marine Sci. Library)
 UNIVERSITY OF DELAWARE Newark, DE (Dept of Civil Engineering, Chesson)
 UNIVERSITY OF HAWAII HONOLULU, HI (SCIENCE AND TECH. DIV.), Ocean Engrng Dept
 UNIVERSITY OF ILLINOIS Metz Ref Rm, Urbana IL, URBANA, IL (DAVISSON), URBANA, IL (LIBRARY); URBANA, IL (NEWMARK); Urbana IL (CE Dept, W. Gamble)
 UNIVERSITY OF MASSACHUSETTS (Heronemus), Amherst MA CE Dept
 UNIVERSITY OF MICHIGAN Ann Arbor MI (Richart)
 UNIVERSITY OF NEBRASKA-LINCOLN Lincoln, NE (Ross Ice Shell Proj.)
 UNIVERSITY OF NEW HAMPSHIRE DURHAM, NH (LAVOIE)
 UNIVERSITY OF NEW MEXICO J. Nielson-Engr Maths & Civil Sys Div., Albuquerque NM
 UNIVERSITY OF NOTRE DAME Katona, Notre Dame, IN
 UNIVERSITY OF PENNSYLVANIA PHILADELPHIA, PA (SCHOOL OF ENGR & APPLIED SCIENCE, ROLL)
 UNIVERSITY OF RHODE ISLAND KINGSTON, RI (PAZIS); Narragansett RI (Pell Marine Sci. Lib.)
 UNIVERSITY OF SO. CALIFORNIA Univ So. Calif
 UNIVERSITY OF TEXAS Inst. Marine Sci (Library), Port Arkansas TX
 UNIVERSITY OF TEXAS AT AUSTIN AUSTIN, TX (THOMPSON); Austin, TX (Breen)
 UNIVERSITY OF WASHINGTON Seattle WA (M. Sherif); Dept of Civil Engr (Dr. Mattock), Seattle WA; SEATTLE, WA (APPLIED PHYSICS LAB); SEATTLE, WA (MERCHANT); SEATTLE, WA (OCEAN ENG RSCH LAB, GRAY); SEATTLE, WA (PACIFIC MARINE ENVIRON. LAB., HALPERN), Seattle WA (E. Linger); Seattle, WA Transportation, Construction & Geom. Div
 UNIVERSITY OF WISCONSIN Milwaukee WI (Ctr of Great Lakes Studies)
 VIRGINIA INST. OF MARINE SCI, Gloucester Point VA (Library)
 AGBABIAN ASSOC. C. Bagge, El Segundo CA
 ALFRED A. YEE & ASSOC. Honolulu HI
 AMETEK Offshore Res. & Engr Div
 AMSCO Dr. R. McCoy, Erie, PA
 ARCAIR CO. D. Young, Lancaster OH
 ARVID GRANT OLYMPIA, WA
 ATLANTIC RICHFIELD CO. DALLAS, TX (SMITH)
 BATTELLE-COLUMBUS LABS (D. Hackman) Columbus, OH
 BECHTEL CORP. SAN FRANCISCO, CA (PHELPS)
 BETHLEHEM STEEL CO. Dismuke, Bethlehem, PA
 BOUW KAMP INC Berkeley
 BRAND INDUS SERV INC. J. Buehler, Hacienda Heights CA
 BRITISH EMBASSY Sci. & Tech. Dept. (J. McAuley), Washington DC
 BROWN & CALDWELL E M Saunders Walnut Creek, CA
 BROWN & ROOT Houston TX (D. Ward)
 CANADA Can-Dive Services (English) North Vancouver; Library, Calgary, Alberta; Lockheed Petro. Serv. Ltd., New Westminster B.C.; Lockheed Petrol. Srv. Ltd., New Westminster BC; Mem Univ Newfoundland (Chari), St Johns; Nova Scotia Rsch Found. Corp. Dartmouth, Nova Scotia; Surveyor, Nenninger & Chenevert Inc., Montreal; Trans-Mnt Oil Pipe Lone Corp. Vancouver, BC Canada; Warnock Hersey Prof. Srv Ltd, La Sale, Quebec
 CHEMED CORP Lake Zurich IL (Dearborn Chem. Div.Lib.)
 CHEVRON OIL FIELD RESEARCH CO. LA HABRA, CA (BROOKS)
 COLUMBIA GULF TRANSMISSION CO. HOUSTON, TX (ENG. LIB.)
 CONCRETE TECHNOLOGY CORP. TACOMA, WA (ANDERSON)
 CONTINENTAL OIL CO O. Maxson, Ponca City, OK
 DILLINGHAM PRECAST F. McHale, Honolulu HI
 DIXIE DIVING CENTER Decatur, GA
 EVALUATION ASSOC. INC KING OF PRUSSIA, PA (FEDELE)
 EXXON PRODUCTION RESEARCH CO Houston TX (A. Butler Jr); Houston, TX (Chao)
 FORD, BACON & DAVIS, INC. New York (Library)
 FRANCE Dr. Dutertre, Boulogne; L. Pliskin, Paris; P. Jensen, Boulogne; Roger LaCroix, Paris

GENERAL DYNAMICS Elec. Boat Div., Environ. Engr. (H. Wallman), Groton, CT
 GEOTECHNICAL ENGINEERS INC., Winchester, MA (Paulding)
 GIDDEN CO., STRONGSVILLE, OH (RSCH LIB)
 GOULD INC., Shady Side, MD (Ches. Inst. Div., W. Paul)
 GRUMMAN AEROSPACE CORP., Bethpage, NY (Tech. Info. Ctr.)
 HALLEY & ALDRICH, INC., Cambridge, MA (Aldrich, Jr.)
 HUGHES AIRCRAFT, Culver City, CA (Tech. Doc. Ctr.)
 ITALY M., Canon, Milan, Sergio, Tattom, Milano, Torino (I. Levi)
 JAMES CO., R. Gurdley, Orlando, FL
 KENNETH TAYLOR ASSOC., CORAOPOLIS, PA (LIBRARY)
 KOREA Korea Rsch. Inst. Ship & Ocean (B. Chon), Seoul
 LAMONT DOHERTY GEOLOGICAL OBSERV., Palisades, NY (McCoy), Palisades, NY (Schwartz)
 LIN OFFSHORE ENGRG. P. Chow, San Francisco, CA
 LOCKHEED MISSILES & SPACE CO., INC., 1, Trimble, Sunnyvale, CA, Sunnyvale, CA (Ryniewicz)
 Sunnyvale, CA (K. E. Kruger)
 LOCKHEED OCEAN LABORATORY, San Diego, CA (H. Simpson), San Diego, CA (Springer)
 MARATHON OIL CO., Houston, TX
 MARINE CONCRETE STRUCTURES INC., MELAIRIE, LA (INGRAHAM)
 MCCLELLAND ENGINEERS INC., Houston, TX (B. McClelland)
 McDONNELL AIRCRAFT CO., Dept. 501 (R. H. Layman), St. Louis, MO
 MEXICO R. Cardenas
 MOBILE PIPE LINE CO., DALLAS, TX MGR. OF ENGR. (NOACK)
 MOFFATT & NICHOL ENGINEERS (R. Palmer), Long Beach, CA
 MUESER, RUTLEDGE, WENTWORTH AND JOHNSTON, NEW YORK (RICHARDS)
 NEW ZEALAND New Zealand Concrete Research Assoc. (Librarian), Porirua
 NEWPORT NEWS SHIPBLDG. & DRYDOCK CO., Newport News, VA (Tech. Lib.)
 NORWAY A. Torum, Trondheim; DET NORSKE VERITAS (Library), Oslo; DET NORSKE VERITAS
 (Roren), Oslo; T. Foss, Oslo; T. Creed, Ski, Norwegian Tech. Univ. (Brandtzaeg), Trondheim
 OCEAN ENGINEERS SAUSALITO, CA (RYNECKI)
 OCEAN RESOURCE ENG. INC., HOUSTON, TX (ANDERSON)
 PACIFIC MARINE TECHNOLOGY, Duval, WA (Wagner)
 PORTLAND CEMENT ASSOC., SKOKIE, IL (CORLEY, SKOKIE, IL (KILGER), Skokie, IL (Rsch & Dev
 Lab, Lib.)
 PRESCON CORP., TOWSON, MD (KEETER)
 R. J. BROWN ASSOC. (McKeehan), Houston, TX
 RAND CORP., Santa Monica, CA (A. Laupa)
 RAYMOND INTERNATIONAL INC., 1, Colle. Soil Tech. Dept., Pennsauken, NJ
 RIVERSIDE CEMENT CO., Riverside, CA (W. Smith)
 SANDIA LABORATORIES Library Div., Livermore, CA; Seabed Progress Div. 4536 (D. Talbert), Albuquerque
 NM
 SCHUPACK ASSOC. SO., NORWALK, CT (SCHUPACK)
 SEAFOOD LABORATORY, MOREHEAD CITY, NC (LIBRARY)
 SEATECH CORP., MIAMI, FL (PERONI)
 SHELL DEVELOPMENT CO., Houston, TX (C. Sellars Jr.), Houston, TX (E. Doyle)
 SHELL OIL CO., HOUSTON, TX (MARSHALL), Houston, TX (R. de Castongreney), T. Boaz, Houston, TX
 SWEDEN Cement & Concrete Research Inst., Stockholm; GeoTech. Inst., VBB (Library), Stockholm
 TECHNICAL COATINGS CO., Oakmont, PA (Library)
 TIDEWATER CONSTR. CO., Norfolk, VA (Fowler)
 TRW SYSTEMS, CLEVELAND, OH (ENG. LIB.); REDONDO BEACH, CA (DAI)
 UNION CARBIDE CORP., R. J. Martell, Boston, MA
 UNITED KINGDOM A. Denton, London; Cement & Concrete Assoc. Wexham Springs, Slough, Bucks, D. Lee,
 London, D. New, G. Maunsell & Partners, London; J. Derrington, London; Library, Bristol; R. Browne,
 Southall, Middlesex; R. Rudham, Oxfordshire; Shaw & Hatton (F. Hansen), London; Taylor, Woodrow
 Constr. (014P), Southall, Middlesex; Taylor, Woodrow Constr. (Smith), Southall, Middlesex; Univ. of Bristol
 (R. Morgan), Bristol
 WESTINGHOUSE ELECTRIC CORP., Annapolis, MD (Oceanic Div. Lib., Bryan), Library, Pittsburgh, PA
 WESTINTRUCORP., Egerton, Oxnard, CA
 WISS, JANNEY, EISTNER, & ASSOC., Northbrook, IL (D. W. Pfeifer)

WM CLAPP LABS - BATTELLE DUXBURY, MA (LIBRARY); Duxbury, MA (Richards)
WOODWARD-CLYDE CONSULTANTS (A Harrigan) San Francisco; PLYMOUTH MEETING PA (CROSS,
III)

AL SMOOIS Los Angeles, CA
ANTON FEDESKO Bronxville NY
BRAHIZ La Jolla, CA
BUTLOCK La Canada
ERVIN, DOUG Belmont, CA
LAYTON Redmond, WA
R F BESIER Old Saybrook CT
SMITH Gulfport, MS
I W MERMET Washington DC
WM TALBOT Orange CA

