


AD-A137 422 INTEGRATED COMPUTER-AIDED MANUFACTURING (ICAM) 1/2
ARCHITECTURE PART 3 VOLUME. (U) SOFTECH INC WALTHAM MA
S SMITH ET AL. SEP 83 FTR110410000U
UNCLASSIFIED AFWAL-TR-82-4063-VOL-2 F33615-80-C-5109 F/G 9/2 NL

The main body of the document is a large grid of blacked-out redacted content. The grid consists of 12 columns and 10 rows of rectangular cells. The top-left cell of the grid contains a small white letter 'c'. All other cells in the grid are completely blacked out, obscuring any text or data that might have been present. The grid is positioned below the header information and occupies most of the page's area.




MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AFWAL-TR-82-4063

VOLUME II

AD A 137422



**INTEGRATED COMPUTER-AIDED MANUFACTURING (ICAM)
ARCHITECTURE PART III
VOLUME II - PROCEDURES**


SofTech, Inc.
460 Totten Pond Road
Waltham, MA 02154

September 1983

Final Report for September 1980 - October 1982

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

MATERIALS LABORATORY
AIR FORCE WRIGHT AERONAUTICAL LABORATORIES
AIR FORCE SYSTEMS COMMAND
WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433



DTIC FILE COPY


84 01 31 043

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.


This report has been reviewed by the Office of Public Affairs (ASD/PA) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.


RICHARD R. PRESTON, Captain, USAF
Project Manager
Computer Integrated Manufacturing Branch
Manufacturing Technology Division

23 Dec 1983
Approval Date

FOR THE COMMANDER


NATHAN G. TUPPER
Chief
Computer Integrated Manufacturing Branch
Manufacturing Technology Division

23 Dec 1983
Approval Date

"If your address has changed, if you wish to be removed from our mailing list, or if the addressee is no longer employed by your organization, please notify AFWAL/MLTC, Wright-Patterson AFB, Ohio 45433 to help us maintain a current mailing list."

Copies of this report should not be returned unless return is required by security considerations, contractual obligations, or notice on a specific document.

UNCLASSIFIED

FTR110410000U
08 September 1983

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM															
1. REPORT NUMBER AFWAL-TR-82-4063 Volume II	2. GOVT ACCESSION NO. A137222	3. RECIPIENT'S CATALOG NUMBER															
4. TITLE and Subtitle INTEGRATED COMPUTER-AIDED MANUFACTURING (ICAM) ARCHITECTURE PART III/Volume II - Procedures	5. TYPE OF REPORT & PERIOD COVERED Final - September 1980 through June 1982																
	6. PERFORMING ORG REPORT NUMBER 1080-31																
7. AUTHOR(s) S. Smith, SofTech B. Davis, SofTech R. Heine, Rockwell	C. Martin, DACOM	8. CONTRACT OR GRANT NUMBER(s) F33615-80-C-5109															
9. PERFORMING ORGANIZATION NAME AND ADDRESS SofTech, Inc. 460 Totten Pond Road Waltham, MA 02154	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Project Priority 1104																
11. CONTROLLING OFFICE NAME AND ADDRESS Materials Laboratory (AFWAL/MLTC) AF Wright Aeronautical Laboratories (AFSC) Wright-Patterson AFB, OH 45433	12. REPORT DATE September, 1983																
	13. NUMBER OF PAGES 81																
14. MONITORING AGENCY NAME & ADDRESS, if different from Controlling Office Same as Block 11	15. SECURITY CLASS. (of this report) UNCLASSIFIED																
	15a. DECLASSIFICATION, DOWNGRADING SCHEDULE																
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.																	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)																	
18. SUPPLEMENTARY NOTES																	
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) <table border="0"> <tr> <td>Manufacturing Architecture</td> <td>ICAM</td> <td>MFG1</td> </tr> <tr> <td>Model of Manufacturing</td> <td>IDEF</td> <td>MFG01 Glossary</td> </tr> <tr> <td>Integrated Computer-Aided Manufacturing</td> <td>MFG0</td> <td></td> </tr> <tr> <td>Subsystem Integration</td> <td>DESIGN0</td> <td></td> </tr> <tr> <td>Technology Transfer</td> <td>DESIGN1</td> <td></td> </tr> </table>			Manufacturing Architecture	ICAM	MFG1	Model of Manufacturing	IDEF	MFG01 Glossary	Integrated Computer-Aided Manufacturing	MFG0		Subsystem Integration	DESIGN0		Technology Transfer	DESIGN1	
Manufacturing Architecture	ICAM	MFG1															
Model of Manufacturing	IDEF	MFG01 Glossary															
Integrated Computer-Aided Manufacturing	MFG0																
Subsystem Integration	DESIGN0																
Technology Transfer	DESIGN1																
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <p>The Integrated Computer Aided Manufacturing (ICAM) Architecture Part III was initiated to maintain and update the existing manufacturing architecture as well as develop training courses to assist in the transition of IDEF applications, concepts and procedures to other Air Force programs. This volume details the Arrow Trace Procedure, IDEF Integration Procedure and IDEF Integration Procedure.</p>																	

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

This report is presented in the following eight volumes:

1. Volume I - Architecture Part III Accomplishments
2. Volume II - Procedures
3. Volume III - Composite Function Model of "Design Product" (DES0)
4. Volume IV - Composite Information Model of "Design Product" (DES1)
5. Volume V - Composite Function Model of "Manufacture Product" (MFG0)
6. Volume VI - Composite Information Model of "Manufacture Product" (MFG1)
7. Volume VII - MFG01 Glossary
8. Volume VIII - Technology Transfer

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

FOREWORD

This technical report covers the work performed under Air Force Contract #F33615-80-C-5109, "ICAM ARCHITECTURE, PART III," covering the period of September 1980 through October 1982. The contract is sponsored by the Computer Integrated Manufacturing Branch, Manufacturing Technology Division, Materials Laboratory, Air Force Wright Aeronautical Laboratories, Air Force Systems Command, Wright-Patterson Air Force Base, direction of Capt Richard R. Preston. Previous phases were administered under the technical direction of Capt Steven R. LeClair.

Bette Davis is the SofTech Program Manager. The other contributors to this document are as follows:

D. Appleton Company
Rockwell International
SofTech, Inc
SofTech, Inc
SofTech, Inc

Chuck Martin
Richard Heine
Bette Davis
Stan Smith
William St. John



SEARCHED _____
SERIALIZED _____
INDEXED _____
FILED _____
By _____
DISTRICT _____
AVAILABLE _____
1st _____
AI




TABLE OF CONTENTS

<u>Section</u>		<u>Page</u>
1	SCOPE 1-1	
	1.1 Identification	1-1
	1.2 Background	1-1
	1.3 Functional Description of Document	1-4
2	REQUIREMENTS	2-1
	2.1 IDEF0 Integration	2-1
	2.2 Arrow Trace	2-1
	2.3 IDEF1 Integration	2-2
3	SHORTENED IDEF0 INTEGRATION PROCEDURE	3-1
	3.1 Introduction	3-1
	3.2 Basic Concepts	3-3
	3.3 Subsystem Developer Deliverables to the Integration Procedures	3-4
	3.3.1 Inputs from the Subsystem Developer	3-4
	3.3.2 Identifying Subsystems0 Support of System0	3-5
	3.4 Procedure Outputs	3-7
	3.4.1 Output Resulting from the Integration Process	3-7
	3.5 Integration of "AS IS" Subsystem	3-13
	3.5.1 Identification of Subsystem External Arrows	3-13
	3.5.2 Summing the Supported Nodes of System0	3-13

TABLE OF CONTENTS (Continued)

<u>Section</u>	<u>Page</u>
3.5.3 Maintenance and Summing of the Integration Matrix Form	3-17
3.5.4 Checking Text and Glossary	3-18
3.5.5 Comparison of External Arrows	3-21
3.5.6 Exception Reporting	3-21
3.5.7 Update of MFGØ	3-21
3.6 Integrating a Subsystem Model Containing Generic Functions	3-23
4 ARROW TRACE PROCEDURE	4-1
4.1 Introduction	4-1
4.2 The General Arrow Trace Procedure	4-1
4.3 The Detailed Trace	4-2
4.3.1 Trace Origin	4-6
4.3.1.1 Case 1: Label Change	4-6
4.3.1.2 Case 2: Trace Leads to a Box	4-7
4.3.1.3 Case 3: Tunneled Arrow	4-8
4.3.1.4 Case 4: Boundary Arrow	4-8
4.3.1.5 Error in Trace	4-9
4.4.1 Trace Target	4-9
4.4.1.1 Case 1: Label Change	4-10
4.4.1.2 Case 2: Trace Leads to Box	4-11
4.4.1.3 Tunneled Arrow	4-11
4.4.1.4 Boundary Arrow	4-11

TABLE OF CONTENTS (Continued)

Section	Page
4.5 Examples from MFGØ Arrow Trace	4-11
4.5.1 Label Changes	4-12
4.5.2 Trace Leads to a Box	4-12
4.5.3 Tunneled Arrow	4-12
4.5.4 Boundary Arrow	4-12
5 IDEF ₁ INTEGRATION PROCEDURE	5-1
5.1 Introduction	5-1
5.2 Phase Zero	5-3
5.3 Phase One	5-6
5.4 Phase Two	5-11
5.5 Phase Three	5-16
5.6 Phase Four	5-24
5.7 Conclusion	5-26

SECTION 1
SCOPE

1.1 Identification

This volume documents the new IDEF procedures developed since June of 1981. Later volumes of this report present models of the functions or the information used in aerospace design and manufacture. Those models have been modified, extended or improved using the procedures documented herein.

This volume describes the procedures used in evolving the Architecture of Manufacturing and design as they currently exist. It does not present the models which make up the architecture.

Sections 3 and 4 of this volume replaces Appendix B of AFWAL-TR-81-4023, Volume III, "Integration using Architecture" published in June of 1981 as part of the ICAM Architecture Part II, it is additionally, an expansion to AFWAL-TR-81-4023, Volume IV "Function Modeling Manual."

Section 5 of this volume is an adjunct to Volume V Information Modeling Manual of the same 1981 report.

This Volume documents work performed under ICAM Project Priority 1104 - ICAM Architecture of Manufacturing Part III.

1.2 Background

The use of the IDEF methodologies on ICAM projects, Air Force Technology Modernization (Tech Mod) programs and similar DoD modernization programs has resulted in an overall need for cost effective and standardized procedures dealing with model integration and validation. This need was first formally addressed during the ICAM Architecture Part II Project in which the Function Model of "Manufacture Product" MFGP was integrated with two subsystem models. The procedure used and the results obtained are documented in AFWAL-TR-81-4023, Volume III "Integration Using Architecture."

Through these early integration efforts and through experience gained using the architecture models in conjunction with Tech Mod Programs, recommendations for improvements and additions to these procedures were made by developers and users.

Therefore the ICAM Architecture Part III Project established three new procedures aimed at reducing both the costs and time required for integration of subsystem models and validation of resulting composite models. These new procedures are documented in this volume.

1.3 Functional Description of Document

This volume (II) documents procedures used in the development of the architecture of design and manufacture. That architecture appears in other volumes of this report: Volumes III-DES0, IV-DES1, V-MFG0, VI-MFG1.

This volume is intended as a guide for the development of IDEF0 models by manufacturing analysts and industrial engineers involved in the integration of new manufacturing and computer system technology into the production environment. It provides a common baseline for communication and decision making during the "Understanding the Problem" phase of such projects. It can be used by management and engineer's to identify the areas impacted by proposed changes and introduction of new technologies.

Experience, from current Technology Modernization Programs, has shown that the function model MFG0 can serve as either a guide for model development or be annotated to provide a company specific architecture.

SECTION 2 REQUIREMENTS

2.1 IDEF0 Integration

During the period in which the architecture of design and manufacturing was developed, several subsystem architectures were developed. These included MCMM (Manufacturing Control and Material Management), and SMC (Sheet Metal Center), and QA (Quality Assurance).

The SMC and MCMM subsystem IDEF0 models were originally related to the composite IDEF0 model of manufacturing (MFG0) using the procedure documented by Appendix B of AFWAL-TR-81-4023, Volume III "Integration Using Architecture" published in June of 1981. Their support of MFG0 was then documented using the procedure given in Section 3 of that volume. The integration QA0 into MFG0 and DES0 followed the procedure of Section 3 of this report in its entirety.

The original procedure is completely valid. The new procedure was developed to provide the documentation of support arrows on the IDEF0 composite view and to provide a less cumbersome method while retaining most of the benefits of the original procedure. The main purpose of the new procedure was to reduce the time and manhours expended on integration efforts.

2.2 Arrow Trace

As part of the integration of subsystems into the Manufacturing Architecture (Subsystem0 into MFG0), a more complete form of arrow definition known as an "arrow trace" was developed and applied to MFG0. This new procedure incorporates the formerly developed glossary definitions of arrow labels, adding the following additional information to the textual definitions to validate and verify consistency in arrow data:

- A list of synonymous terms used for the data carried on the arrow.
- A list of source functions which generate the data carried on the arrow.
- A list of target functions which utilize the data carried on the arrow.
- A list of the sub-parts (origin components) comprising the data carried in the arrow, as shown by the arrow branching and joining structure.
- The name of the more inclusive data item or items (usage components) which contain the data carried on the arrow, as shown by the arrow branching and joining structure.

This procedure has been needed in the application of the integration procedure in order to document the complete impact of a subsystem on the total Manufacturing Architecture. Also, the arrow tracing procedure has been found to be helpful in pointing out modeling errors and inconsistencies in the arrow structures, such as inconsistent use of arrow labels.

2.3 IDEF1 Integration

The IDEF1 integration procedures were developed to meet a need equivalent to that met by the IDEF0 integration procedures.

The procedures were used to extend the IDEF1, model of manufacture (MFG1).

The subsystems integrated were Integrated Center (ICENT), Integrated Planning System (IPS) and Quality Assurance (QA).

SECTION 3
SHORTENED IDEF0 INTEGRATION PROCEDURE

3.1 Introduction

The shortened IDEF0 integration procedure discussed in this document is a specific phase in an integration process which is intended as an on-going aid to the developers and potential users of newly developed subsystems. The complete process is portrayed in Figure 3-1.

The complete process consists of three phases:

1. Scoping
2. Integration of the "AS IS" subsystem model
3. Integration of the "TO BE" subsystem model

Phase one, which precedes the phase discussed in this procedure, provides for a general scoping of the subsystem developers task. Before development of a new subsystem is initiated, the nodes in the existing System0 to be replaced or supported by the subsystem are identified. This list of nodes provides the contracting office and the developer with a clear specification of the scope of development to be undertaken.

The list of nodes defines the area to be further documented by the developer's "As Is" model.

The definition of any node may be further refined by:

- further detailing or decomposing of the node
- identifying that specific arrows are added, deleted or changed in the context of the node.

Phase two, which this procedure discusses -- when the subsystem developer has completed an "AS IS" model -- specifies a comparison of functions and external interfaces between the subsystem model and the existing "AS IS" System0. The comparison is not exhaustive, and discrepancies noted need not be corrected immediately. The list of discrepancies is used as a guide by the subsystem developer in developing his "TO BE" specifications and by the integration team for review at the next level of integration effort.




Figure 3-1. Shortened IDEF0 Integration Procedure

In the final phase, after this procedure is completed and when the subsystem developer has completed a "TO BE" IDEF0 specification of his subsystem, the comparison of functions and interfaces is repeated with greater rigor and is extended to an identification and consideration of functions which are related to, but not included in, the subsystem. Such functions are considered so as to obtain greater precision and rigor in the specification of Subsystem0 to System0 interfaces. Analysis of the interfaces may indicate a need to change areas of the architecture outside the subsystem to accommodate revised needs or outputs resulting from subsystem installation.

This final phase uses both as-is and to-be versions of System0 since new subsystems must meet two integration criteria. That is, the new subsystem must be useful in factories as they exist today and must also fit smoothly into an image ("TO BE" model) of the updated and integrated factory of tomorrow.

It is within this total integration scenario that this procedure is designed to operate.

Figure 3-1 shows an overview of the total process just described. This illustrates the ultimate purpose and intended outputs of the process of which this procedure is a part. The portions of the process covered by this procedure deal with "AS IS" models and are the primary part of Phase II.

3.2 Basic Concepts

In its simplest form, integration using IDEF0 would involve the replacement of a function represented by a single IDEF0 box by another IDEF0 box. For such replacement to be accepted,

- The new system must be able to use the same information now being supplied to the function.
- The new system must be able to supply the same information now being supplied by the function.
- There must be agreement that the processing performed within the new system is at least equivalent to the processing within the existing system.

The first requirement could be checked by reviewing the input and control arrows of the new and of the old IDEF0 box. The second requirement could be checked by reviewing output arrows. The third requirement could be checked by a discussion of the two box labels. Review of the box labels could be supported by examining any diagrams which detailed the two simple boxes. The procedure in the remainder of this report deals with the requirements just presented, but applies them to the more complex situation which normally exists.

In practice, the parts of an existing system to be replaced by a new subsystem rarely appear as a single box in the architecture of the existing system. Also, differences in implementation methods, terminology or in grouping of data into pipelines may cause difficulty when IDEF0 arrows are compared between models. This latter difficulty could occur even when only one box from each system is being examined.

3.3 Subsystem Developer Deliverables to the Integration Procedure

3.3.1 Inputs from the Subsystem Developer

The subsystem developer is responsible for providing:

Initial Input

- a) Subsystem Statement of Work to be performed.
- b) A textual description of the project including:
 - An expanded discussion of the purpose and viewpoint of the model
 - A summary of the types of improvements which will be sought during the development of the subsystem (see Figure 3-3).
- c) A matrix showing, for each lowest level box in the "AS IS" subsystem IDEF0 model (Subsystem0) the node or nodes of System0 which it supports. The form used is illustrated in Figure 3-2. Preparation of the form by the subsystem developer is discussed more fully in paragraph 3.3.2.
- d) Copies of the final "AS IS" IDEF0 models created during the development of the subsystem. The IDEF0 model must include:
 - A node diagram
 - The complete hierarchy of diagrams
 - Related FEO's
 - Texts for all diagrams
 - Glossary covering box names and arrow labels whose meaning is not self-evident.

System Matrix (Pre-Process)

System Name Subsystem Name	System Matrix (Pre-Process)										A445 (Name) Total	Exception
	A111 (Name)	A112 (Name)	A113 (Name)	A114 (Name)	A115 (Name)	A116 (Name)	A117 (Name)	A118 (Name)	A119 (Name)	A120 (Name)		
A121 - (Name)			⊙								1	A121
A122 - (Name)											0	A122
A123 - (Name)			⊙								1	A123
⋮												
A421 - (Name)			⊙	⊙							2	A421
A422 - (Name)	⊙										1	A422
⋮												
Total	0	1	0	2	1	1	0	...				

Data indicate subsystem support for system function

Figure 3-2. Completed Integration Matrix

- e) Responses to all exceptions raised by the integration team during the ongoing integration effort.

3.3.2 Identifying Subsystem₀ Support of System₀

This step is carried out by the subsystem developer. For each box in Subsystem₀ which is not decomposed,

- 1) Analyze the Subsystem₀ diagram, text, and glossary relating to each "lowest-level" Node Number.
- 2) Review the Node Diagram and individual diagrams for the System₀, to locate a node which performs a function similar to the Subsystem₀ function.
- 3) Search for any additional matching nodes in the System₀ until all nodes have been reviewed.
- 4) Read and study the System₀ diagrams in light of the matches made in Steps 2 and 3, including the "parent" diagrams of System₀ matching nodes as well as any glossary and text.

PURPOSE: This model will be reviewed with system analysts to define ways in which computers could assist in some of the duties of a typical foreman in an aerospace manufacturing company. It therefore stresses the view of a typical foreman of his current activities with all contradictory and irritating factors shown. The presence of the foreman to perform the functions is assumed, but concerns for personnel hiring, training, etc., and for obtaining equipment and facility maintenance are not included. The model will be annotated with mechanism arrows to show which functions will appear in the next--functional--spec of a computer system.

VIEWPOINT: The view of the professional foreman is assumed. Any machine is assumed to be generic as are employees, moves, budgets, etc. The existence and functioning of the department in a physical sense is shown at or above the A-1 level only. A-0 and lower diagrams deal with messages from and messages to the foreman's environment.

CONTEXT: This project will develop computer software to be run on a minicomputer dedicated to each foreman. The computer will be used to track cell load at the operation level, the assignment and expected availability of each operator, set-up man, and machine and the status of material handling equipment. Based on this knowledge, the program will compute the result of various options considered by the foreman and will store the results of his decision. The system will operate in real time and will give notice of upcoming or missed milestones. The program will track cell inventory. Links will be available for later networking of the minicomputers to provide for coordination from a center control program.

Figure 3-3. Summary of Improvements

- 5) Record each match identified in Steps 2 and 3 by entering a dot (.) on the intersection of the appropriate row and column of the Integration Matrix Form.
- 6) Identify any adjustment in context needed to show what parts of the box are supported. Assume for example, that the decomposition of the supported box appearing as item (a) in Figure 3-4 would look like item (b) of Figure 3-4. Then the environment must be redefined to agree with item (c) of Figure 3-4 which now only displays the supported output labelled "p." The output "n" has been dropped because it is not within the context supported by the subsystem mechanism arrows.




Figure 3-4.


The maintenance and revision of this form after it is submitted is the responsibility of the integration team. The procedure for this maintenance and revision is discussed in paragraph 3.5.3.

3.4 Procedure Outputs

3.4.1 Output Resulting from the Integration Process

An Integration Kit will be created as a result of applying the integration procedures to the inputs described in paragraph 3.3.1; the kit will be comprised of the following:

- 1) An Overview, consisting of a description of the purpose, viewpoint, context, assumptions, source documents, and conclusions made by the integrator.




2) A Completed Subsystem Integration Matrix

A Subsystem Integration Matrix form will be completed for the Subsystem \emptyset , as it integrates with the System \emptyset . This is an updated version of the form provided by the subsystem developer and shown in Figure 3. It is discussed further in paragraph 3.5.3.

A complex, dense grid representing a Subsystem Integration Matrix. It features a diagonal line in the top-left corner and numerous columns and rows of data points. The grid is filled with small, illegible text and symbols, likely representing the integration points between various subsystems and the system as a whole.

3) A Summary Version of the Matrix

This is the same form as Item 2. It is marked to show groups of nodes which are analyzed together rather than individually. For example a single box might be analyzed without attention to the separate boxes composing the diagram which details the single box.



4) A copy of Subsystem \emptyset Identifying Outside Arrows

A copy of the Subsystem \emptyset with all arrows which descend from arrows on A- \emptyset or from tunnelled arrows are highlighted using wide arrows. Figure 3-5 illustrates a diagram from such a model.

5) A Summary Model of the System \emptyset Nodes Considered

This is a standard IDEF \emptyset model (lacking text and glossary) but consisting of FEO's (For Exposition Only) so that:

- less than 3 boxes are allowed on a diagram.
- extensive notes are provided and standard box numbers and DRE rules are waved to encourage notations explaining the structure of the model.
- highlighting of "external" arrows as seen in Figure 3-5 is used.

The procedure for producing this model is given in paragraph 3.5.2. Figure 3-6 shows a sample diagram from such a model.

This type of model is discussed further in paragraph 3.5.1.




Figure 3-5. Subsystem Identifying Outside Arrows




Figure 3-6. Standard IDEF0 Model

6) Text Comparison of Nodes Considered

For each node (or group of nodes) identified in Item 3 a discussion of the comparison of node titles, texts, glossaries and external arrows is developed. This part of the document, and the graphic material which may accompany it are discussed in paragraphs 3.5.4, 3.5.5 and 3.5.6.

7) Exception Report

The Exception Report contains an explanation for each numbered exception item which appears on the Integration Matrix or in the Text Comparison. The exceptions are numbered and described chronologically, using text plus copies of System \emptyset or Subsystem \emptyset diagrams as necessary to illustrate the exception item. Exceptions include arrow naming discrepancies, differences in glossary term usage and non-matching external arrow identification between related system and subsystem nodes.

The Exception Report may contain a Recommendations Section at the end of each Exception Report item. These recommendations may include:

- Recommendations for further System \emptyset decomposition.
- Recommendations for additional System \emptyset arrows, where Subsystem \emptyset arrow attributes could not be found.
- Recommendations for modifications or corrections.

8) An updated MFG \emptyset

The integration team will provide new diagrams for all MFG \emptyset diagrams which contain nodes supported by the new subsystem, or which are "parents", "grandparents" etc. of such diagrams. The supported boxes will carry a support arrow labeled subsys only or, for boxes with only one supporting subsystem, will read subsys/subsystem name. The team will maintain and deliver a node list type matrix (see Figure 3-7) to summarize the supporting subsystems. Each check in this matrix will represent one or more dots in the integration matrix of the subsystem indicated. By referring to that subsystem matrix, the reader can determine precisely which subsystem nodes support the CV node in which he is interested.

NODE IN CV MODEL	SUBSYSTEM				
	ABC	DEF	GHI	XYZ	ETC.
A0	✓	✓	✓	✓	✓
A1	✓	✓			
A11		✓			
A111		✓			
A112		✓			
A113					
A12	✓	✓			
A121	✓				
A122	✓	✓			
A123		✓			
A13	✓				
A131					
A132	✓				
A133	✓				
A2	✓	✓	✓		✓
A21	✓		✓		✓
etc.					

Figure 3-7. Architecture-Subsystem Integration Matrix

3.5 Integration of "AS IS" Subsystems

This section discusses the procedures for integration beginning with the delivery of the Integration Matrix by the subsystem developer who has completed an "AS IS" Subsystem \emptyset . The section deals with the efforts of the integration team, a group which brings to the analysis an industry perspective of System \emptyset and Subsystem \emptyset .

3.5.1 Identification of Subsystem External Arrows

Since integration is concerned with the external interfaces of a subsystem, not with its inner workings, this phase of integration considers only those arrows which terminate outside the subsystem. Examination of arrows which start and end within the subsystem occurs only during the more detailed examination which occurs during integration of the Subsystem \emptyset "TO BE" model. The procedure, which is carried out by the integration team, begins by highlighting all arrows on Subsystem \emptyset /A- \emptyset . Arrows on A \emptyset are then highlighted if they carry either an ICOM from one of the highlighted arrows or parentheses in place of an ICOM. This procedure is followed throughout the model until all diagrams have been considered. Figure 3-8 shows a parent diagram and the diagram which details one of its boxes.

The highlighting of arrows depends only on tunnelling and on highlighting of arrows on the parent. Discrepancies in arrow naming are noted for exception reports, (See paragraph 3.5.6) but are not otherwise traced. The use of this form of the model is discussed in paragraph 3.5.5.

3.5.2 Summing the Supported Nodes of System \emptyset

In this step, the nodes of System \emptyset which are supported by Subsystem \emptyset are grouped into a coherent model. This grouping is performed bottom up. APPENDIX A shows a sample output of this procedure.





Figure 3-8. Parent Diagram with Detail

The summary is carried out for two reasons:

- To provide an overview of the topic in order to:
 - Provide top-down understanding
 - Highlight and focus on any pre-existing problems or discrepancies.
- To segregate 'internal' arrows and 'external' arrows for different treatment.

The procedure consists of the following steps:

- 1) All supported boxes are highlighted, and their interface arrows are adjusted to meet the changes noted by the subsystem developer.
- 2) On diagrams with more than one supported box, non-supported boxes are marked out (actually deleted for final reports). All arrows which do not touch supported boxes are marked out. Remaining arrows which touch non-supported boxes become external arrows. See Figure 3-9.





Figure 3-9. Removal of Unsupported Box

- 3) For diagrams with a single supported box, the same result is obtained by treating the arrows around the box as external arrows.
- 4) Parent diagrams of processed diagrams are treated in two ways:
 - a) Diagrams with a single child diagram which is supported are labeled as "channel diagrams." This indicates that the processing of the next higher diagram will be carried out by looking at the next lower diagram.



Box 2 of this diagram is surrounded by the same arrows as to Box 23. Reshaping of Diagram 2 is not necessary.

- b) On diagrams with more than one supported child, the arrows around each parent box are relabeled, deleted, or added to until they match the external arrows of the child. The box which the above figure details would have controls labeled "b" and "d", inputs of "a" and "e" and outputs "c" and "f". The supported nodes at the next lower level (or even lower levels if reasonable) are listed under the parent box in place of the usual DRE. For Figure 3-9, nodes one and three would be listed on the parent. Boxes whose child diagrams have no supported nodes, and the arrows touching those boxes, are treated as were those in Step 2. This step often requires creation of a new diagram. The old diagram is marked "redrawn" and left as a documenting FEO of the redrawn diagram. Original box numbers are used. See Summary/A0 in APPENDIX A.

- 5) When a single diagram (A0) level is reached, the process reverses. In the top down pass, two steps are executed:
 - New ICOM's are noted (or old ones confirmed) to check the process. In doing this, "channel" diagrams may be skipped.
 - The arrows which are now external to the model (as discussed in paragraph 3.4.2) are highlighted.
- 6) The processed diagrams are assigned:
 - a new model name
 - a FEO number in addition to the basic node number.

Appendix A shows a working level in the preparation of such a model. The boxes supported are those across the top of Figure 3-10.

3.5.3 Maintenance and Summing of the Integration Matrix Form

The integration team, upon receipt of the Integration Matrix Form (see paragraph 3.4.1) will total the dots in all rows and columns. An exception occurs when no System0 node can be found which matches a Subsystem0 node, or if more than one such node is found. In these cases, a chronological Exception Number will be entered into the Exception Column (adjacent to the Subsystem0 Node Number column) on the Integration Matrix form (right-most column). Paragraph 3.5.7 discusses the exception report further.

In addition, revisions of the Integration Matrix Form may result from the analysis conducted in paragraphs 3.5.4 and 3.5.5. These revisions are the responsibility of the Integration Team.

Finally, the summary System0 model from paragraph 3.5.2 and examination of the Matrix itself will lead to decisions to group nodes for further study in paragraphs 3.5.4 and 3.5.5. This occurs where:

- 1) One Subsystem0 node supports several related System0 nodes.
- 2) One System0 node is supported by several Subsystem0 nodes.
- 3) A limited group of Subsystem0 nodes support a limited group of System0 nodes.

Figure 3-10 shows four conditions which may exist:

- 1) At Note 1, one box (Subsystem/All) supports 3 closely related boxes. The comparison needs to be made only between System/A3 and Subsystem/All. Individual consideration of System/A31, System/A32 and System/A33 is not required.
- 2) At Note 2, several subsystem boxes support a single box (System/All). In this case, the summing occurs in the Subsystem model; Subsystem/A3 is compared to System/All.
- 3) At Note 3, a limited group of Subsystem boxes support a limited group of System boxes. Such cases require individual analysis. Usually, summing of all boxes at each end is possible but the integration team may decide to sum over lesser groups or, occasionally, not at all.
- 4) At Note 4, a single box supports a single box and no summary need be made.

Figure 3-11 shows an integration matrix marked to show nodes which will be summed before comparison of supported and supporting nodes. The note marks on Figure 3-11 refer to the type numbers above. No occurrences of type 2 appear in the example. Note that some of the noted groupings do not meet the pure classifications given above.

The development of these groupings is guided by examining the output of paragraph 3.5.2. The groupings in turn guide considerations described in paragraphs 3.5.4 and 3.5.5. Several iterations of tentative groupings and revisions are to be expected.

3.5.4 Checking Text and Glossary

For each SystemØ node or group of nodes identified by executing paragraph 3.4.4, the integration team will prepare an Integration Textual Description, based upon the function model texts for each group of boxes.




Figure 3-10. Four Conditions.

SUBSYSTEM NODE (MCM/A)	SYSTEM NODE (CV/A)											6120-490000	
	702	701	11	1185	55	610	621	622	611	620	621		
61111 - Determine Tooling Requirements												1	61111
61112 - Update Job Status												1	61112
61113 - Verify and Check Validation and Tools												1	61113
61114 - Order Tools												1	61114
61115 - Request Material												1	61115
61116 - Order Prints												1	61116
61121 - Process Work Package												1	61121
61122 - Update Job Status												1	61122
61123 - Control Tool Move												1	61123
61124 - Control Temp. Stg. of Tools												3	61124
61125 - Verify Tools												1	61125
61126 - Request Material												1	61126
61131 - Verify Comments												1	61131
61132 - Review Work Station Load												1	61132
61133 - Verify Job Status & Location												1	61133
61134 - Update Job Status												1	61134
61135 - Request Corrective Action												1	61135
61136 - Order Tools												1	61136
61141 - Verify Compl. of Previous Op. Step												1	61141
61142 - Process Stop Order												1	61142
61143 - Control Moves												1	61143
61144 - Verify and Check Validation on Tools												1	61144
61145 - Order Prints												1	61145
61146 - Update Job Status												1	61146
61148 - Update Job Location												1	61148
61151 - Control Store												2	61151
61152 - Control Retrieval												1	61152
611531 - Post Transactions												1	611531
611532 - Verify or Correct Record Counts												1	611532
61211 - Identify Job to be Produced												1	61211
61212 - Verify Material Availability												1	61212
61213 - Develop Operation Plan												1	61213
61221 - Add Job to Station Load												1	61221
61222 - Adjust Job Priority in Load												1	61222
61223 - Remove Job from Station Load												1	61223
61224 - Maintain Station Load												1	61224
61231 - Det. Res. Operator & Verify Material/Pkg.												1	61231
61232 - Assign Operator to Spec. Mach.												1	61232
61233 - Assign Work to Spec. Mach.												1	61233
61234 - Issue Job Move Request												1	61234
61241 - Collect Control Data												1	61241
61242 - Store Control Data												1	61242
61243 - Communicate Control Data												1	61243
61251 - Measure Schedule Realization												1	61251
61252 - Measure Age of Job at Station												1	61252
61253 - Measure Operator Performance												1	61253
61254 - Measure Change in Station Labor Performance												1	61254
61255 - Measure Machine and Tool Performance												1	61255
61256 - Measure Operation												1	61256
613 - Comn. S.M. Center Performance												1	613
TOTAL	11	8	1	1	1	1	1	1	1	1	1	1	7

Figure 3-11. Annotated Intersection Matrix.

The textual description will include a description of the exceptions if any, which are noted between the use of terms on the SystemØ and SubsystemØ diagrams and an Activity Analysis textual description of the activity differences (see Figure 3-12), including those functions that are included in the SystemØ boxes which are not included in the SubsystemØ boxes, and vice versa. These descriptions will be included, to present any similarity/difference noted by the integrator, not to elaborate or otherwise describe elements of SystemØ or SubsystemØ. Each exception will be classified as either critical, major or minor.

3.5.5 Comparison of External Arrows

For each SystemØ node or group of nodes identified by executing Section 6.5 (TO BE REPLACED WITH CORRECT NUMBER), the integration team will prepare a comparison of external arrows. All external arrows reaching or leaving each group of nodes (SystemØ and SubsystemØ) are cross referenced.

Any SystemØ arrows for which an acceptable match is not found are noted for exception reporting (see paragraph 3.5.6).

3.5.6 Exception Reporting

As each question or problem is encountered (see paragraphs 3.5.3; 3.5.4; 3.5.5 and 3.5.6), it is assigned a chronological number. The integration team maintains:

- A central file containing documentation for each exception.
- An index of all exceptions and an index of exceptions which the team considers open.
- A brief description of each open exception. These can be assembled at any time to provide a documentation of project status somewhat more extensive than that provided by the index of active exceptions.

3.5.7 Update of MFGØ

The MFG model is annotated to show which boxes receive some level of support. To avoid clutter, the model diagrams do not reflect all supporting subsystems directly. However any box which is supported itself or which has a "descendant" box which is supported, shows a support arrow (see Figure 3-13) marked "subsys". If only one subsystem supports the box, the subsystem is identified. The specific subsystems involved will be documented by an Architecture-Subsystem Integration Matrix (see Figure 3-11).




Figure 3-12. Integration Textual Description




Figure 3-13. Supported Box

When one subsystem reports that it supports a lowest level node supported by one or more other subsystems, the integration team will examine the interface between the subsystems. If the subsystems are clearly compatible, as when an output of one is an input to the other, no further action is required.

If interfaces between the subsystems are not clear, an exception will be added to the exception list for each of the subsystems.

3.6 Integrating a Subsystem Model Containing Generic Functions

The process of integrating a Subsystem \emptyset which contains a split into multiple generic functions is analogous to the previous Section 7 description except that it includes a preliminary step of creating a "summary FEO" of all generic functions, and then using the FEO for integration of the Subsystem \emptyset with the System \emptyset .

Preparing and Using a Summary FEO

For each group of generic functions in the Subsystem \emptyset , create an IDEFO FEO diagram which summarizes the activities portrayed by all generic functions in the group. Use the boxes of this FEO as the lowest-level Subsystem \emptyset Nodes on the Matrix form, instead of the actual Subsystem \emptyset nodes. Reference the node numbers with an "F" preceding the FEO box number, to indicate a generic function reference (e.g., "A123F1").

To be precise about each generic function integration, an Integration Matrix will be developed for each generic function to show how the function integrates with the FEO, and the FEO boxes supported by the generic function will be annotated with support arrows. In other words, the basic integration procedure will be applied to the FEO and generic function-models just as they are applied to the System \emptyset and the Subsystem \emptyset . Thus, the main integration effort shows generic integration, with specific details traceable via the FEO's second level of detail.

In other cases, a subsystem may perform one or more generic functions which are widely used. For example, a Group Technology system may provide for recovery of a part given its group characteristics. This ability might be useful at many points in manufacturing. In this case, a single summary box (or several, one for each of several functions) will be checked at many points in System \emptyset .

SECTION 4
ARROW TRACE PROCEDURE

4.1 Introduction

As part of the integration of subsystems into the Manufacturing Architecture (SubsystemØ into MFGØ), a more complete form of arrow definition known as an "arrow trace" was developed and applied to MFGØ. This new procedure incorporates the formerly developed glossary definitions of arrow labels, adding the following additional information to the textual definitions:

- A list of synonymous terms used for the data carried on the arrow.
- A list of source functions which generate the data carried on the arrow.
- A list of target functions which utilize the data carried on the arrow.
- A list of the sub-parts (origin components) comprising the data carried on the arrow, as shown by the arrow branching and joining structure.
- The name of the more inclusive data item or items (usage components) which contain the data carried on the arrow, as shown by the arrow branching and joining structure.

This more complete set of information has been deemed necessary in applying the integration procedure in order to document the complete impact of a subsystem on the total Manufacturing Architecture. Also, the arrow tracing procedure has been found to be helpful in pointing out modeling errors and inconsistencies in the arrow structures, such as inconsistent use of arrow labels.

NOTE: This procedure has been written with the assumption that the reader is familiar with the IDEF1 methodology.

4.2 The General Arrow Trace Procedure

In general, the Arrow Trace procedure traces the path of each arrow in the model to find the origin(s) and target(s) of an arrow. Before proceeding, a familiarity of the terminology used in the context of "tracing arrows" is required.

Arrow - A directed line segment having a specific label.

Origin - A function (box) which creates a specific arrow and/or the point at which a specific arrow first appears in a model.

Target - A function in which an arrow finally enters and/or the point at which an arrow label changes.

Origin Component - Arrows which join together to make-up the arrow being traced and/or an arrow whose name changed to that of the arrow being traced.

Usage Component - An arrow which is the result of the traced arrow's name change.

ICOM Code - The code that corresponds to the origin of the arrow.

The arrow trace begins by selecting an arrow. The person performing the arrow trace (the tracer) traces the origin(s), then the target(s).

The diagram showing the arrow being traced is then examined. Each time the arrow is shown entering or leaving a function (box), that function is examined to see if it has a decomposition diagram. If not, the function is listed as a source (leaving) or target (entering). If a decomposition diagram exists, the decomposition diagram is examined to find the continuation of the arrow path, and the trace continues.

If the trace procedure encounters an arrow which is open-ended (it does not enter or leave a box on the diagram being examined), the ICOM code of this "boundary arrow" is used to locate the arrow on the "parent" diagram, and the trace continues.

The most complex interaction occurs when an arrow is shown branching or joining. If the branches are not labeled differently from the main arrow path, this indicates multiple sources or targets. If the branches are labeled differently from the main arrow path, this indicates that the main data item is comprised of the sub-parts shown in the branches. In either case, the trace must continue until all sources or targets are identified.

4.3 The Detailed Trace

The above "general procedure" introduces the major arrow tracing concepts. The detailed procedure, described below and depicted in a flow diagram (Figure 4-1), presents the complete procedure, showing all possible situations encountered and the steps to be performed in each situation. The Arrow Trace Form is included as Figure 4-2 along with several examples (Figures 4-14, 4-15, 4-16, and 4-18) of completed forms resulting from the MFGØ tracing effort.

ARROW TRACE PROCEDURE
ROCKWELL VIEW

2-20-81
S. NEGRETTE




Figure 4-1. Arrow Trace Procedure

ST 252	USED AT:	AUTHOR:	ARCHITECTURE:	TASK I TEAM	DATE:	CONTEXT:
		PROJECT:	TASK I OPTION	REV:	DATE	
NOTES: 1 2 3 4 5 6 7 8 9 10		<input checked="" type="checkbox"/>	WORKING	READER		
		<input type="checkbox"/>	DRAFT			
		<input type="checkbox"/>	RECOMMENDED			
		<input type="checkbox"/>	PUBLICATION			
TOOM DEFINITION		TARGET(S)				
ORIGIN COMPONENT(S)		USAGE COMPONENT(S)				
MODE: (TOOM CODE)	TITLE:	NUMBER:				

Figure 4-2. Arrow Trace Form

At any instant, the goal of the trace is either to locate the origin(s) and target(s) of the selected arrow. Note that, since a single arrow may show multiple origins and targets, using the branch/join arrow structures of IDEF (see Figure 4-3), this will require a forward and backward trace of each branch to complete the arrow trace on a single arrow.




Figure 4-3. Example of Multiple Sources and Targets of an Arrow

For example, if arrow "A" (Figure 4-3) were being traced, Box 2 would be an origin and the origin trace would have to be continued in the decomposition of Box 1. Similarly, Box 5 would be a target and the target trace would have to be continued in the decomposition of Boxes 3 and 4. A method of keeping track of the branch being traced and the branches to be traced is left to the person performing the arrow trace.

The arrow trace begins by selecting an arrow. The procedure continues by tracing (1) origin(s), and (2) target(s) of the arrow. In each trace, at least one of four primary cases will be encountered (see Section 4.3.1) and are listed below.

1. Arrow has a label change.
2. Trace leads to a box.
3. Arrow is tunneled.
4. Arrow is a "Boundary Arrow."

Each case requires a decision and an appropriate action. These will be discussed in detail. Notice the branch/join does not require a decision. Each branch must be traced to complete the procedure for an arrow.

4.3.1 Trace Origin (Figure 4.1, Box 2)

To trace the origin(s) of an arrow, the selected arrow should be followed in the direction of the tail, i.e., in a backward direction. Following this course, at least one of the cases listed above will be encountered. Each case is considered in detail below.

4.3.1.1 Case 1: Label Change (Figure 4-1, Box 2.2)

When a trace leads to a label change, the tracer must decide if the new label is appropriate. If the new label is appropriate, then the change must be documented on the Arrow Trace Form (Figure 4-2). This documentation requires the following steps. (Figure 4-1, Boxes 2.4 and 2.5)

1. Record ICOM Code and name of the new arrow as an "origin component" on the Arrow Trace Form.
2. Record the ICOM code of the arrow being traced (subject arrow) at the first occurrence of the arrow; i.e., that point at which the label changed.

In Figure 4-4, the arrow labeled "C" is the subject arrow. Notice that in tracing "C" backward, the label changes to "A" and "B." If these are appropriate changes, then the output arrows, "A" and "B," are listed as "origin components." The ICOM code of the control arrow "C" is then recorded on the Arrow Trace Form.

If the new label is not appropriate, then the tracer must recommend a revision to the model. A list of recommended revisions should be compiled containing reference to position in the model and explanations of the changes.

When the recommended change is that a different new label be used, the tracer continues the documentation as described by the previous example.




Figure 4-4. Example of Case 1: Label Change, Appropriate

When the recommendation is that there be no label change, then the tracer only needs to continue the trace.

In Figure 4-5, arrow "C" is the subject arrow. The label change from "C" to "B" is deemed inappropriate. The decision is that the label should be "D" rather than "B." This label change is then documented in the same manner as described in steps 1 and 2 of this section.

The label change from "C" to "A" in Figure 4-5 may also be inappropriate, i.e., the label should remain "C." In this case, the recommendation should be documented and the procedure continued from Box 2.1 of Figure 4-1.

4.3.1.2 Case 2: Trace Leads to a Box (Figure 4-1, Box 2.9)

When the arrow trace leads to a box, the box must be examined for decomposition. If the box decomposes, the tracer simply continues the trace in the child diagram. If the box does not decompose, then that box is considered an origin. The ICOM code of the arrow, at the point of contact with the box, is recorded under ICOM code on the Arrow Trace Form.




Figure 4-5. Example of Case 1: Label Change, Inappropriate

In Figure 4-6, "A" is the subject arrow. Tracing "A" backward leads to box one. If box one decomposes, the tracer locates the child diagram of box one and continues the procedure in that diagram. If box one does not decompose, then it is considered an origin of arrow "A" and the ICOM code of "A" at the point of contact with box one is entered under ICOM code on the Arrow Trace Form.

4.3.1.3 Case 3: Tunneled Arrow (Figure 4-1, Box 2.13)


When the subject arrow is tunneled, the ICOM code is obtained at the point the arrow first appears in the model.

In Figure 4-7, arrows "A" and "B" would not be referenced in the parent or child diagrams respectively. The ICOM codes for each arrow would be taken from their points of contact with box one.

4.3.1.4 Case 4. Boundary Arrow (Figure 4-1, Box 2.14)

If the subject arrow is a boundary arrow, then the tracer must continue the trace in the parent diagram.

If this box decomposes,
continue trace in child.



If box 1 does not decompose,
it is an origin.

Figure 4-6. Example of Case 2: Trace Leads to a Box




Figure 4-7. Example of Case 3: Tunneled Arrow

4.3.1.5 Error in Trace (Figure 4-1, Box 2.16)


If tracing an arrow does not lead to any of the four cases described, then the tracer has made an error and should begin the trace over.

4.4.1 Trace Target (Figure 4-1, Box 3)

The logic and procedure for tracing the target(s) of an arrow are basically the same. A major portion of the differences is in the documentation. Only the differences will be addressed in the remaining sections of this procedure.

4.4.1.1 Case 1: Label Change (Figure 4-1, Box 3.2)

Decisions in this case are identical to those in Section 4.3.1.1. Differences in the procedure occur in the documentation required when the label change is appropriate. The ICOM code of the new arrow is recorded as a "target" on the Arrow Trace Form. The label change is then referenced by adding a footnote (parenthesized digit) to the target ICOM code. The new label is then documented using the corresponding footnote number under "usage component" on the Arrow Trace Form. An example of this documentation is presented in Figure 4-8 below.



A1 Diagram

Portion of Arrow Trace Form

Figure 4-8. Target Trace Label Change Documentation

The figure above depicts an "A1" diagram in which arrow "A" is the subject arrow. The arrow's label appropriately changes to "B" and "C." Arrows "B" and "C" must then be identified as "usage components" on the Arrow Trace Form. This is done by listing their footnoted ICOM codes under "targets" and their labels with corresponding footnote numbers under "usage components."

4.4.1.2 Case 2: Trace Leads to Box (Figure 4-1, Box 3.10)

If the box decomposes, the trace is continued in the child diagram. If the box does not decompose, then the ICOM code of the arrow at the entry point to the box is listed as a "target" on the Arrow Trace Form (see Figure 4-9).




Figure 4-9. Example: Arrow Trace (Target) Leads to Box

4.4.1.3 Tunneled Arrow (Figure 4-1, Box 3.14)

If the arrow is tunneled at the entry to a box, the ICOM code of the arrow at that point is listed as a "target." Notice it does not matter if the box decomposes since the tunneled arrow will not appear on the child diagram.

If the arrow is tunneled at the boundary of the diagram, then no action is required. The arrow has no target at that point.

4.4.1.4 Boundary Arrow (Figure 4-1, Box 3.15)

If the subject arrow is a boundary, then the tracer must continue the trace in the parent diagram.

4.5 Examples from MFGØ Arrow Trace

This section presents selected examples from the MFGØ Arrow Trace. References will be made to previous sections of this procedure and the appropriate following figures in an effort to provide practical examples of this procedure.

4.5.1 Label Changes (reference paragraphs 4.3.1.1 and 4.4.1.1)

The trace numbers used in this example are from the MFGØ model and are intended to identify specific arrows on specific diagrams. The format key for these trace numbers is interpreted as follows:

Axxx.BAN

- Axxx - identifies node in MFGØ
- B - identifies the Box on that diagram
- A - identifies ICOM Arrow type
- N - identifies the relative Number of the arrow.

Figure 4-10 is a sample diagram from MFGØ. In tracing the origin of the arrow labeled "job sequence analysis," notice that the label changes to "production sequence." Figure 4-13 shows "A132.102 production sequence" as an origin component and the ICOM Code "A132.211" listed for "job sequence analysis."

Tracing the target labeled "production sequence" in Figure 4-10 also leads to the label change to "job sequence analysis." Figure 4-12 shows "A132.211" listed as a target (with footnote) and the new label (footnoted), "job sequence analysis," under usage component.

4.5.2 Trace Leads to a Box (reference paragraphs 4.3.1.2 and 4.4.1.2)

The arrow labeled "kit plan" in Figure 4-10 is an example of an arrow trace (both target and origin) which leads to a box. Tracing the origin of "kit plan" yields the ICOM code "A132.202" as shown in Figure 4-11. Tracing the origin yields "A132.311" as a target.

4.5.3 Tunneled Arrow (reference paragraphs 4.3.1.3 and 4.4.1.3)

In Figure 4-14, the arrow labeled "WBS & drawing tree" is an example of a tunneled arrow. The appropriate documentation is shown on Figure 4-15.

4.5.4 Boundary Arrow (reference paragraphs 4.3.1.4 and 4.4.1.4)

Arrows labeled "line assembly and installation plan" and "resource plans" on Figure 4-10, are examples of boundary arrows.

RECOMMENDED




Figure 4-10. Develop Line Assembly & Installation Sequence

ICOM DEFINITION	TARGET(S) A132.311	
ORIGIN COMPONENT(S)	USAGE COMPONENT(S)	
MODE: (ICOM CODE) A132.202	TITLE: KIT PLAN	NUMBER:

Figure 4-11. Kit Plan

<p>TARGET(S) A132.211 (1) A132.312</p> <p>USAGE COMPONENT(S) (1) Job sequence analysis</p>	<p>ICOM DEFINITION</p> <p>ORIGIN COMPONENT(S)</p>
<p>NUMBER:</p>	<p>MODE: (ICOM CODE) A132_102</p> <p>TITLE: PRODUCTION STATEMENT</p>

Figure 4-12. Production Sequence

ICOM DEFINITION ORIGIN COMPONENT(S) A132.102 Production Sequence	TARGET(S) A132.211 USAGE COMPONENT(S)	
MODE: (ICOM CODE) A132. 211	TITLE: .JOB SEQUENCE ANALYSIS	NUMBER:

Figure 4-13. Job Sequence Analysis

RECOMMENDED




Figure 4-14. Develop Detail Parts Sequence

TARGET(S) A1341.111	USAGE COMPONENT(S)
NUMBER:	ORIGIN COMPONENT(S)
ICOM DEFINITION	TITLE: WBS 6 DRAWING TREE
MODE: (ICOM CODE) A134.111	NUMBER:

Figure 4-15. WBS & Drawing Tree

SECTION 5
IDEF1 INTEGRATION PROCEDURE

5.1 Introduction

This procedure is designed to serve as a reference guide for the combining of two or more IDEF1 information models into a single information model. The concepts used to facilitate the combining of IDEF1 information models are described and depicted in the various examples throughout this manual. This procedure is designed to be a working reference for the experienced information modeler.

This procedure assumes that the integration modeler has a working knowledge of IDEF1 information modeling methodology and has experience in building multiple IDEF1 information models.

The procedure is based on two assumptions regarding the quality of the models to be used in the integration process. These assumptions are: 1) the models correctly apply the IDEF1 methodologies, and 2) the models accurately reflect the factory views they represent. The quality of the source models will have an impact on the ease with which the models can be integrated. Models which do not correctly apply the IDEF1 methodology or do not accurately reflect the environments they represent can cause the resulting integrated model to lack credibility.

The modeler must also guard against any inadvertent changes to the views of the source models, as a result of the integration process. This can occur rather easily and the modeler should refer to the source models frequently during the integration process to ensure that the integrated model maintains the source model views.

The modeling team should consist of modelers and reviewers who represent the various source models. A team established in this way will provide additional guarantees that the source model views are maintained in the integrated model.

In the course of integrating IDEF1 information models, the modeler may find that, between the source models being integrated, there exist no common entity classes. As a result, "bridges" will have to be built between the models and therefore, new entity classes will result.

New entity classes may also be created from resolutions of discrepancies that arise as a result of the varying views of the models being integrated. The resolution of these discrepancies will be dealt with in the sections that follow.

Any number of IDEF1 information models can be integrated using this procedure. However, the more models being integrated, the more involved the record keeping becomes to provide traceability back to the source models.

This procedure utilizes a five phase approach to the development of an integrated model. This approach is consistent with the five phase development of an IDEF1 information model. The documentation produced by this procedure also parallels the IDEF1 information modeling methodology. The differences, due to the nature of the integration process, will become evident from the discussion that follows. The five phases for developing an integrated model are as follows:

Phase Zero

Phase Zero documents the context of the integrated model. In this phase, the scope of the integrated model is defined, its objectives are stated, and the source data identified.

Phase One

In Phase One, the objective is to identify and define the candidate entity classes to be used in the integrated modeling effort.

Phase Two

In Phase Two, the initial relation classes between the candidate entity classes will be identified.

Phase Three

In Phase Three, the key classes for each of the entity classes in the integrated model will be identified and defined.

Phase Four

In Phase Four, the integrated model will be populated with its non-key attribute classes.

The result of the integration process will be a new model which will reflect the combined views of all of the source models. It is of utmost importance that the integrated model accurately represent the views of the various source models and that the components of the source models are able to be identified within the context of the completed integrated model. Maintaining this approach will ensure maximum usability of the model to the enterprise.

5.2 Phase Zero

The integrated information model must be described and defined in terms of both its ambitions and its limitations. This will be accomplished through a statement of the strategic objective and definition of the scope of the integrated model. The strategic objective consists of two elements. These elements are a statement of purpose and a statement of viewpoint. It is likely that the models to be integrated will have been developed from different viewpoints with differing strategic objectives. For the resulting integrated model to be meaningful, a strategic objective must be synthesized that will accurately reflect the strategic objectives of the source models without changing their intent. This "synthesis of viewpoint" will be evident throughout this procedure and is an integral part of the integration process. An example of a synthesized strategic objective for an integrated model is provided in Figure 5-1.

<u>STRATEGIC OBJECTIVE</u>		
PURPOSE: TO INTEGRATE THE IPS FACTORY VIEWS FROM GENERAL DYNAMICS, NORTHROP AIRCRAFT DIVISION AND ROCKWELL INTERNATIONAL INTO AN INTEGRATED PLANNING SYSTEM COMPOSITE VIEW.		
VIEWPOINT: FUNCTIONAL MANAGEMENT OF OPERATIONS		
NO. PD/T1	TITLE STRATEGIC OBJECTIVE	NUMBER

Figure 5-1 Strategic Objective

The scope of the source models will likewise have been developed to satisfy a specific factory view. A scope must be established for the integrated model that will satisfy the scopes of the various source models. One way to establish the scope of the integrated model is to view the problem domain of the source models from an IDEF0 perspective. An analysis of this IDEF0 perspective will then help clearly establish the scope and context of the integrated model. An example of an IDEF1 integrated model scope viewed from the IDEF0 perspective is provided in Figure 5-2.

To provide traceability of data used in the integration process, a source material log (SML) and a source data list (SDL) are constructed. Source material in this context will be the various source models which are to be integrated. The source material log lists all the source models used to create the integrated model. An example of this source material log is provided in Figure 5-3.




Figure 5-2. IFS Composite View Scope

SOURCE DATA NO.	SOURCE DATA NAME	SOURCE MATERIAL CROSS REFERENCE	COMMENTS
SD-1	Section Activity	SM1-E501	
SD-2	Sched Activity Complete Date	SM1-AC17	
SD-3	Sched Activity Start Date	SM1-AC18	
SD-4	Flow Span of Assembly	SM1-AC23	
SD-5	Line Position	SM1-AC126	
SD-6	Major Assembly Break	SM1-AC127	
SD-7	Configurated Item	SM1-E519	
SD-8	Material	SM1-E505 SM2-E33	
SD-9	Raw Material	SM3-E49	
SD-10	Material Specification	SM1-AC10 SM2-A28 SM3-A35	
SD-11	Part Number/Raw Material Code	SM11-AC155	

NUMBER: _____ TITLE: SOURCE DATA LIST NUMBER: _____

Figure 5-4. Source Data List

To summarize, the objective of Phase Zero is a clearly established set of products which include:

Strategic Objective Definition

- Purpose
- Viewpoint
- Context

Scope and Viewpoint

Source Material Log (SML)

Source Data List (SDL)

Author Conventions

5.3 Phase One

The objective of Phase One is to identify and define the entity classes from the source models that will be included in the integrated model. These candidate entity classes are drawn from the Source Data List constructed in Phase Zero. It is during this identification process that the issue of source model entity class commonality or redundancy, partially identified in Phase Zero, is addressed.

The process of identifying the entity classes for inclusion in the integrated model is as follows: One of the source models to be integrated is chosen as a baseline model. The selection of the baseline model is strictly arbitrary. Its purpose is to provide a starting point. Each of the entity classes in the remaining models is compared with the baseline model. Where an identical or similar entity class definition exists between the models, the affected entity classes become candidates for combining into a single integrated entity class. The key point is commonality or similarity (defined as "commonality of intent") of the definitions. Commonality or similarity of entity class names alone may be misleading because of differing source model viewpoints and differing factory view usage of terms (i.e., two factory views using the same term but with different definitions). This commonality of entity class definitions from the source models represents "overlap" between the models.

For each group of common or "overlap" entity classes, a single entity class name and definition is synthesized which most accurately reflects the viewpoint and strategic objective of the integrated model. The resulting entity class name may not be identical to any of the source model entity class names from which it originated, but it must reflect the meaning of the originating source entity classes. An example of the entity class name and definition synthesis is provided in Figure 5-5.




Figure 5-5. Integrated Entity Class Development

A glossary page is prepared for each entity class synthesized. The entity class names which were not used for the integrated entity class name, may be used, where appropriate, as synonyms for the integrated entity class name and are also listed on the glossary page. (Figure 5-6)

The entity classes for which no commonality existed are now examined for relevancy to the viewpoint and strategic objective of the integrated model. Glossary pages are prepared for each of the remaining entity classes identified as being within the scope of the integrated model. Those candidate entity classes falling outside the integrated model scope are eliminated from the integrated model. The eliminated entity classes are listed on a text page, along with their source data list (SDL) identifiers, and a statement explaining the reason(s) for non-inclusion in the integrated model. (Figure 5-7).

The candidate entity classes which survive the above process form the Entity Class Pool for the integrated model. The surviving entity classes are recorded on the Entity Class Pool Form (Figure 5-8), and new entity class numbers assigned.

ENTITY CLASS NAME:	Drawing				
ENTITY CLASS LABEL:	Drawing				
ENTITY CLASS DEFINITION:	A graphical representation of an object which reflects its geometric configuration, dimensions and construction (form, fit and function).				
ENTITY CLASS SYNONYMS:	Blueprint Engineering Drawing Brownline				
NO.:	E614	TITLE:	ENTITY CLASS DEFINITION: DRAWING	NUMBER:	

Figure 5-6. Entity Class Definition: Drawing

ENTITY CLASSES NOT USED IN INTEGRATED VIEW			
NO.	ENTITY CLASS NAME	SOURCE	REASON
564	Activity Plan	NAD	Replaced by material, manpower, tooling, facilities, quality assurance and equipment plans.
566	Resource	NAD	Not specific enough.
574	Plan Constraint	NAD	Not specific enough.
577	End-Item Resource	NAD	Not specific enough.
24	Building	R1	Outside of scope.
18	Shift	R1	Outside of scope.
49	Dept. Operating Period	R1	Outside of scope.
29	Split	R1	Outside of scope.
53	Tool Order	GD/FW	Appeared to be duplication.
57	Type-Version Ship Project	GD/FW	Appeared to be duplication
61	Selected Operation	GD/FW	Outside of scope

NO. 01/X8 TITLE ENTITY CLASSES NOT USED IN INTEGRATED VIEW NUMBER

Figure 5-7. Entity Class Not Used in Integrated View

USED BY		AUTHOR	DATE	WORKING	READER	DATE	CONTEXT
		C. Martin/A. Nowlin	8/20/81	<input checked="" type="checkbox"/>			
		PROJECT [PSCV]	REV.	<input type="checkbox"/>	<input type="checkbox"/>		
		NOTES 1 2 3 4 5 6 7 8 9 10		<input type="checkbox"/>	<input type="checkbox"/>		
NO. NO.	ENTITY CLASS NAME	SOURCE DATA I.D. NO.	NO. NO.	ENTITY CLASS NAME	SOURCE DATA I.D. NO.		
E-1	Section Activity	SD-1	E-18	Basic Assumptions Memorandum	SD-112		
E-2	Configured Item	SD-7	E-19	Activity Policy	SD-116		
E-3	Material	SD-8,9	E-20	Configuration Baseline	SD-119,120		
E-4	Design Effectivity	SD-12	E-21	End Item	SD-125		
E-5	Statement of Work	SD-18	E-22	Planned Mfg. Operation	SD-132,133,134		
E-6	Sales Contract	SD-41	E-23	Material Plan	SD-136		
E-7	Engineering Change Req'st.	SD-52,53	E-24	Manpower Plan	SD-148		
E-8	Eng. Change Proposal	SD-59	E-25	Tooling Plan	SD-149		
E-9	Engineering Order	SD-61,62,63	E-26	Facilities Plan	SD-150		
E-10	Approved Engrn. Order	SD-65	E-27	Quality Assurance Plan	SD-151		
E-11	Drawing	SD-68,70	E-28	Equipment Plan	SD-152		
E-12	Part	SD-71,72	E-29	Manufacturing Project Plan	SD-153		
E-13	Component Part	SD-95,96	E-30	Preliminary Design Concept	SD-154		
E-14	Section	SD-97	E-31	Process Plan	SD-161,162,163		
E-15	WBS Item	SD-100	E-32	Milestone	SD-165		
E-16	Test Requirement	SD-103	E-33	Contract Tool	SD-175,176		
E-17	Contract Requirement	SD-107	E-34	Account	SD-178		

NO. 01/X TITLE ENTITY CLASS POOL NUMBER

Figure 5-8. Entity Class Pool

An entity class source model cross reference is now prepared. This cross reference provides traceability for each integrated entity class to its originating source model(s). An example of this source model entity class cross reference is provided in Figure 5-9.

At appropriate points during Phase One, kits are structured and circulated for review and comment.

A Phase One Kit will typically consist of the following:

- Kit Cover Sheet
- Entity Class Pool
- Source Model Entity Class Cross Reference
- 15-20 New Entity Class Definition Pages Per Kit

Review time for each kit should not exceed one or two hours.

E.C. NO.	ENTITY CLASS NAME/COMMENT COMPOSITE	E.C. NO.	ENTITY CLASS NAME NAD	E.C. NO.	ENTITY CLASS NAME RI	E.C. NO.	ENTITY CLASS NAME GR/EM
E1C	Section Activity	E501	Section Activity				
E2C	Configurated Item	E519	Configurated Item				
E3C	Material	E505	Material	E33	Material	E49	Raw Material
E4C	* * * Not Used * * *						
E5C	Statement of Work	E533	Statement of Work				
E6C	Sales Contract ("Sales" added to distinguish from Purchase Contract)	E520	Contract	E21	Contract	E38	Contract
E7C	Engineering Change Request	E521	Drawing Change Request			E22	Engineering Change Request
E8C	Engineering Change Proposal					E50	Engineering Change Proposal
E9C	Engineering Order			E32	Engineering Order	E21	Engineering Release
E10C	Approved Engineering Order					E23	Engineering Change Notice
E11C	Drawing	E525	Drawing	E71	Approved Engineering Order		
E12C	Part--(By definition an Assembly could be a part)	E536	Part	E36	Drawing	E20	Engineering Drawing
E13C	Component Part	E552	Assembly	E28	Part Type	E1	Part
E14C	Section	E578	Detail Part	E550	Component Part		
E15C	Work Breakdown Structure Item	E544	Section	E6	Work Breakdown Structure Item		

NOON: TITLE: ENTITY CLASS NAME CROSS REFERENCE NUMBER:

Figure 5-9. Entity Class Name Cross Reference

In summary, Phase One produces the following products for the integrated model:

- Entity Class Pool
- Entity Class Definitions
- Entity Class Source Model Cross Reference
- Phase One Kit(s)

5.4 Phase Two

The objective of phase two in integrated model development is the identification and definition of relation classes and relation class labels. The relation classes to be used in the integrated model are those in the source models which apply to the integrated entity classes identified in phase one. Rough (pencil) drafts of entity class diagrams (with an entity class box only) are constructed for each entity class in the integrated model. (Figure 5-10) The relation classes, along with their respective labels, from each source model entity class is applied to its integrated entity class counterpart. The rough draft integrated entity class diagrams are updated to reflect the relation classes and labels represented in the source models. (Figure 5-11)




Figure 5-10. Entity Class Diagram: Department




Figure 5-11. Entity Class Diagram: Department

In the "overlap" area of the integrated model, conflicting relation class syntax and/or conflicting relation class labels (meaning) may occur because of the differing viewpoints of the source models. FEOs (For Exposition Only) (called refinement alternative FEOs) are constructed that offer alternatives to the conflicting views (Figure 5-12). Actual resolution of these conflicting viewpoints will be accomplished later on in Phase Three.

Triads (three entity classes related directly to each other) may also occur due to differing viewpoints of the source models. FEOs are constructed to illustrate "triads" that result from the integrated process, along with suggested refinements. (Figure 5-13) Triads are resolved through the Phase Two kit review cycle.

Glossary pages are prepared for those relation class definitions, appearing in the source models, that are appropriate to the integrated model. New relation class definitions resulting from the integration process are also incorporated into the integrated model and documented on glossary pages as appropriate.




Figure 5-12. Refinement Alternative FEO: Conflicting Syntax




Figure 5-13. Triad "FEO"

The entity class diagrams are now formalized and the entity class node cross reference constructed. (Figure 5-14). The entity class node cross reference provides an easily usable index to the relation classes contained in the integrated model.

Source model "views" (projections) from the integrated model can now be constructed. These source model views (Figure 5-15) allow each source model to be seen in the context of the integrated model. A source model view is constructed by replacing each source model entity class with its integrated entity class. Any changes to relation class(es) and labels are also shown. These source model views help to validate the structure and semantic intent of the integrated model.

At appropriate points in Phase Two, kits are prepared for review and comment. A typical Phase Two kit should contain from thirty to fifty pages of new material. It should require no more than one or two hours for review. A Phase Two kit will consist of the following:

- Kit Cover Sheet
- Source Model Entity Class Cross Reference
- Source Model Views

SUBJECT ENTITY CLASS LABEL		R. C.	RELATED ENTITY CLASS LABEL		RELATION CLASS LABEL
NO.	LABEL		NO.	LABEL	
29C	MFG PROJECT PLAN	→	SALES CONTRACT	6C	IS BASIS FOR
		—◇	TEST REQUIREMENT	16C	SPECIFIES
		—◇	RESOURCE PLAN	93C	CONTAINS
30C	PRELIM DESIGN CONCEPT	—◇	SALES CONTRACT	6C	RESULTS IN
31C	PROCESS PLAN	—◇	APPRD ENGRN ORDER	10C	AUTHORIZES
		—◇	PLANNER	54C	DEVELOPS
		—◇	WORK PACKAGE	48C	IS BASIS FOR
		—◇	PART	12C	MANUFACTURE IS DESCRIBED BY
		—◇	PLANNED MFG OPER	22C	IS COMPRISED OF
32C	MILESTONE	—◇	STATION CALLOUT	83CD	SELECTS
		—◇	SECTION ACTIVITY	1C	ESTABLISHES ACTIVITY DATES FOR
		—◇	CONTRACT REQ'MT	17C	ESTABLISHES PARAMETERS FOR
		—◇	WBS ITEM	15C	IS COMPRISED OF
		—◇	RESOURCE NEED	94C	PROVIDES DATES FOR
33C	CONTRACT TOOL	—◇	DEL'Y SCHED ITEM	92C	CONTAINS
		—◇	RESCHED MILESTONE	52CD	IS
		—◇	SALES CONTRACT	6C	OWNS
NODE P2/	TITLE	RELATED ENTITY CLASS NODE CROSS REFERENCE			NUMBER

Figure 5-14. Related Entity Class Node Cross Reference




Figure 5-15. Rockwell A2 View of Composite Model (Page 1)

- Node Cross Reference
- Reference Only Entity Class Definitions
- Entity Class Sets (20-30 pages per kit) consisting of:
 - Subject Entity Class Definition
 - Subject Entity Class Diagram
 - Relation Class Definitions (as required)
 - Reference/Refinement FEOs

To summarize, the objective of Phase Two is to produce the following products.

- Source Model Views (of the integrated model)
- Entity Class Diagrams
- Entity Class Node Cross Reference

- Relation Class Definitions (as appropriate)
- Refinement Alternative FEOs (as appropriate)
- Phase Two Kits

5.5 Phase Three

In Phase Three, the Attribute Class Pool is established, key attribute class(es) are assigned to each entity class in the integrated model, and key class migration occurs.

Using the previously selected baseline model as a starting point, the attribute class definitions of the source models are compared with the baseline model for commonality. Where an identical or similar attribute class definition exists between the models, the affected attribute classes are candidates for combining into a single integrated attribute class. The key point is commonality or similarity (defined as "commonality of intent") of attribute class definition. Commonality or similarity of attribute class names may be misleading because of differing source model viewpoints and differing factory view usage of terms (i.e., two factory view using the same term, but with different definitions).

For each group of "common" attribute class definitions, a single attribute class name and definition is synthesized for the integrated model. The resulting attribute class name may not be identical to any of the source model attribute class names from which it originated, but it must reflect the meaning and intent of the source attribute classes. An example of an integrated attribute class name and definition synthesis is provided in Figure 5-16. A glossary page is prepared for each attribute class synthesized. (Figure 5-17)

Attribute class names which were not used for integrated attribute class name(s) may be used, where appropriate, as synonyms for the integrated attribute class name. These synonyms are listed on the glossary page.

The remaining attribute classes are examined for relevancy to the viewpoint and strategic objective of the integrated model, and their applicability to the integrated entity classes. Those candidate attribute classes which fall outside the scope of the integrated model (based in part on the eliminated entity classes from Phase One) are eliminated. The eliminated attribute classes are listed on a text page (with their source data list [SDL] identifier) stating the reasons for non-inclusion in the integrated model. (Figure 5-18). The candidate attribute classes which survive, together with the synthesized attribute classes form the Attribute Class Pool, and are recorded on the Attribute Class Pool Form (Figure 5-19). A new attribute class number is assigned to each member of the Integrated Model Attribute Class Pool.




Figure 5-16. Integrated Attribute Class Development

KEY CLASS(ES): ENGINEERING CHANGE REQUEST NO.				
ATTRIBUTE CLASS NAME	ATTRIBUTE CLASS LABEL	ATTRIB. CLASS ID NO.	ATTRIBUTE CLASS DEFINITION	ATTRIBUTE CLASS SYNONYM(S)
ENGINEERING CHANGE REQUEST NUMBER			A unique identifier which identifies each individual instance of an engineering change request.	
MODE: P3/E 354 (G1)		TITLE: ATTRIBUTE CLASS DEFINITIONS: ENGINEERING CHANGE REQUEST		NUMBER:

Figure 5-17. Attribute Class Definitions: Engineering Change Request

ATTRIBUTE CLASSES NOT USED IN INTEGRATED MODEL			
A.C. NO	ATTRIBUTE CLASS NAME	SOURCE	REASON
A15	Building Number	RI	Outside Scope of Integrated Model
A64	Building Location	RI	Outside Scope of Integrated Model
53	Tool Order Number	GD/PW	Duplicate
A4	Shift Number	RI	Outside Scope of Integrated Model

MODEL: _____ TITLE: ATTRIBUTE CLASSES NOT USED IN INTEGRATED MODEL NUMBER: _____

Figure 5-18. Attribute Classes Not Used In Integrated Model

ATTRIBUTE CLASS		SOURCE DATA	ATTRIBUTE CLASS		SOURCE DATA
I.C. NO.	NAME	I.C. NO.	I.C. NO.	NAME	I.C. NO.
A-1	Material Specification	SD-10	A-18	Engineering Change Proposal Number	SD-60
A-2	Contract Number	SD-42	A-19	Section Number	SD-220
A-3	Engineering Change Request Number	SD-54	A-20	Work Breakdown Structure Item Number	SD-101
A-4	Engineering Order Number	SD-62	A-21	Flag Note Number	SD-104
A-5	Drawing Number	SD-67	A-22	Paragraph Number	SD-108
A-6	Part Number	SD-80	A-23	Project Number	SD-155
A-7	Configuration Baseline Number	SD-121	A-24	Account Number	SD-235
A-8	End Item Serial Number	SD-126	A-25	Schedule Change Request Number	SD-179
A-9	Line Number	SD-135	A-26	Schedule Change Authorization Revision Number	SD-198
A-10	Process Plan Number	SD-164	A-27	Program Name	SD-182
A-11	Milestone Description	SD-166	A-28	Project Number	SD-236
A-12	Contract Tool Number	SD-177	A-29	Type Version Ship Number	SD-217
A-13	Equipment Description	SD-200	A-30	Bill of Material Item Number	SD-240
A-14	Department Number	SD-201	A-31	Planning Parts List Item Number	SD-251
A-15	Station Number	SD-195	A-32	Cutting Specification Identification	SD-256
A-16	Activity Name	SD-186	A-33	Visual Aid Identification	SD-259
A-17	Change Number	SD-215	A-34	Configured Item Serial Number	SD-3

MODEL: P3/1 TITLE: ATTRIBUTE CLASS POOL NUMBER: _____

Figure 5-19. Attribute Class Pool

The attribute class source model cross reference is now prepared. This cross reference provides traceability for each integrated attribute class back to its originating attribute class(es) in the source models. An example of an attribute class source model cross reference is provided in Figure 5-20.

The next activity in Phase Three is the assignment of key classes to each entity class in the integrated model. Using the source models as a guide, assign key classes to the integrated entity classes which: A) are fully independent, and B) are not an "overlap" or synthesized entity class. The entity classes which are "overlap" entity classes will have their key classes determined during key class migration.

Key classes are assigned to each of the non-"overlap" integrated entity classes by comparing the attribute classes used as key class(es) for the source model entity class, to the attribute class(es) in the integrated Attribute Class Pool. The integrated attribute class(es) which correspond to the source attribute class(es) are selected as the key class(es) of the integrated entity class.

AC NO.	ATTRIBUTE CLASS NAME/COMMENT COMPOSITE	AC NO.	ATTRIBUTE CLASS NAME NAD	AC NO.	ATTRIBUTE CLASS NAME RI	AC NO.	ATTRIBUTE CLASS NAME SD/FW
A1C	Material Specification	AC10	Material Specification Number	A28	Material Specification	A35	Material Specification Number
A2C	Contract Number	AC03	Contract Number	A19	Contract Number	A38	Contract Number
A1C	Engineering Change Request Number	AC14	Drawing Change Request Number			A22	Engineering Change Request Number
A4C	Engineering Order Number			A13	Engineering Order Number	A21	Engineering Release Number
						A23	Engineering Change Notice Number
A5C	Drawing Number	AC05	Drawing Number	A25	Drawing Number	A20	Drawing Number
A6C	Part Number	AC04	Dash Number	A17	Part Number	A1	Part Number
A7C	Configuration Baseline Number	AC08	End Item Drawing Number	A14	Configuration Baseline Number		
A8C	End Item Serial Number			A20	Unit Number		
A9C	Line Number	AC11	Method Category	A10	Line Number	A27	Manufacturing Instruction Number
A10C	Process Plan Number			A8	Scan Number		
A11C	Milestone Description	AC76	Published Schedule Number	A18	Milestone Description		
MODEL		TITLE		ATTRIBUTE CLASS NAME CROSS REFERENCE		NUMBER	

Figure 5-20. Attribute Class Name Cross Reference

As the key classes are assigned, they are noted on pencil draft attribute class diagrams. (Figure 5-21) All key class members must pass the "no null," "no repeat criteria." (Ref. IDEF1 manual) Those attribute classes which fail the "no null" and "no repeat" criteria typically result in the creation of new entity classes to satisfy the IDEF1 methodology requirement of unique identification. The "new" entity classes which result are added to the Entity Class Pool, entity class numbers assigned, and glossary pages (definitions) are prepared.

The next step is key class migration. One role the migration of key classes serves is to validate the assigned relation classes. Before key class migration can begin, conflicting syntax identified in Phase Two is resolved. The modeler(s) should choose the syntax which best satisfies the intent of the integrated model. The result of this decision is documented by FEOs for review during the Phase Three kit review cycle. Multiple (non-synonymous) relation classes are left in place at this stage. These will be resolved through the key class migration process.

Key class migration is initiated from the fully independent, non-overlapped integrated entity classes, and progresses to the other integrated entity classes in accordance with IDEF1 methodology.




Figure 5-21. Attribute Class Diagram: Department

At some point in the key class migration process, the modeler will be confronted with an "overlap" entity class. In all likelihood, for these 'overlap' entity classes the key class structure(s) from the source model(s) will be different in each model, so the appropriate integrated key class(es) for these "overlap" integrated entity classes will have to be synthesized. The key class assignment process for these 'overlap' entity classes is as follows: A comparison between the source model key class members and the integrated model attribute class pool is made. The attribute class(es) most closely meeting the needs of the key class(es) for the "overlap" integrated entity class is selected. The key class(es) selected may or may not be the same as the key class(es) from the originating source model entity classes. The selection is based on the scope and viewpoint of the integrated model, and on meeting the semantic intent of the source models.

Multiple (non-synonymous) relation classes are resolved as follows: For those entity classes which have more than one relation class, the inheriting entity class is examined to determine if multiple occurrences of the inherited attribute class are required to identify the entity class. If concurrent multiple occurrences of any attribute classes are required to identify each instance of the entity class and maintain its semantic intent, then the multiple relation classes are retained. If concurrent multiple occurrences are not required, then one or more relation class and relation class label is probably not required and should be eliminated. Where a relation class or relation class label is eliminated, FEOs are constructed to document the reasons for selecting the surviving relation class and relation class label.

As the key classes are migrated, appropriate entries are made on the pencil drafts of the attribute class (Phase Three) diagrams. (Figure 5-21) When all key classes have been developed and migrated, the formal attribute class diagrams (Figure 5-22) are constructed from the pencil drafts.

During the key class migration process, refinement FEOs are constructed as appropriate (along with text where required) to document any structure changes required in the model from its Phase Two representation.

The source model views (projections) from Phase Two are revised to reflect any changes resulting from the Phase Two review cycle and the Phase Three key class assignments and key class migration.




Figure 5-22. Attribute Class Diagram: Department

An Attribute Class/Entity Class Index is constructed. This index lists each attribute class used in the integrated model, its owner entity class and the inheriting entity class(es) and if the attribute class is: 1) owned key class (OK); 2) inherited key class (IK); 3) owned non-key (O); or 4) inherited non-key (I). An example is shown in Figure 5-23.

As appropriate in Phase Three, kits are prepared for review and comment. A typical Phase Three review kit will consist of materials from the following list:

- Kit Cover Sheet
- Strategic Objective
- Source Model Views
- Entity Class Pool
- Source Model Entity Class Cross Reference
- Entity Class Node Cross Reference

ATTRIBUTE CLASS		OWNER ENTITY CLASS		INHERITING ENTITY CLASS		USE CODE
NO.	NAME	NO.	NAME	NO.	NAME	
14	Account Number	34	Account	70	Fab Lot Sub Account	OK
16	Activity Name	5	Statement of Work	19	Activity Policy	OK
				59	Method Use	I
				61	Released Engr. Drawing	I
				93	Resource Plan	I
				1	Section Activity	IS
30	BOM Item No.	43	Bill of Material Item			OK
17	Change No.	5	Statement of Work			OK
				19	Activity Policy	OK
				59	Method Use	OK
				81	Release Engr. Drawing	I
				93	Resource Plan	I
				1	Section Activity	IS
7	Configuration Baseline No.	20	Configuration Baseline	101	Dwr. Applic. to Basln.	IF
				21	End Item	I
34	Configured Item Serial No.	2	Configured Item			OK
2	Contract No.	6	Contract			OK
				19	Activity Policy	OK
				19	Activity Policy	I
NO.:	TITLE:	ATTRIBUTE CLASS/ENTITY CLASS INDEX		NUMBER:		

Figure 5-23. Attribute Class/Entity Class Index

- Attribute Class Pool
- Source Model Attribute Class Cross Reference
- Attribute Class/Entity Class Index
- Entity Class Sets, each of which may consist of:
 - One subject Attribute Class diagram
 - Subject Entity Class definition
 - Some number of Relation Class definitions applicable to the subject Entity Class
 - Attribute Class Definitions (for owned Key Class members)
 - Refinement Alternative FEOs

A typical Phase Three kit should contain between 30 and 50 pages of material. It should require no more than one or two hours to review.

To summarize, Phase Three produces the following products.

- Attribute Class Pool
- Attribute Class Cross Reference
- Key Attribute Class Identification
- Key Attribute Class Definitions
- Attribute Class Diagrams
- Attribute Class/Entity Class Index
- Revised Source Model Views
- Refinement Alternative FEOs

5.6 Phase Four

In Phase Four, the integrated model is populated with its non-key attribute classes. Phase Four focuses attention on the attribute classes which were not utilized as members of a key class in Phase Three. The source models are used to provide guidance for the population of the non-key attribute classes.

The attribute classes not used as key classes in Phase Three are assigned to an integrated entity class based on their usage in the related source model entity class. (Figure 5-24). The assignment of non-key attribute classes to integrated entity classes may not correspond directly to the source models, because the scope and viewpoint of the integrated model may differ from the source models. The assignment of non-key attribute classes to the integrated entity classes must maintain, however, the semantic intent of the source models. The assignment in most cases will be obvious and should present no difficulty.

As each attribute class is assigned to an integrated entity class, the "no-null," and "no-repeat" rules are applied. Refinements are made as necessary in accordance with IDEF₁ methodology to resolve the "no-null" and "no-repeat" violations. New integrated entity classes which emerge as a result of refinement of the "no-null" and "no-repeat" rule violations are added to the Entity Class Pool and source model entity class cross reference, attribute class diagrams are constructed, and source model projections updated as required.




Figure 5-24. Attribute Class Diagram: Department

When population of the integrated entity classes with non-key attribute classes is completed, the Attribute Class/Entity Class Index is updated to document ownership of the non-key attributes.

As appropriate in Phase Four, kits are prepared for review and comment. The contents of a Phase Four kit will be essentially identical to the Phase Three review kits, but the content will reflect the distribution of non-key attribute classes, and any structural changes resulting from Phase Four refinement. Phase Four kits consist of materials from the following list:

- Kit Cover Sheet
- Strategic Objective
- Revised Source Model Views
- Revised Entity Class Pool
- Revised Source Model Entity Class Cross Reference
- Revised Entity Class Node Cross Reference

- Revised Attribute Class/Entity Class Index
- Revised Entity Class Sets, each of which may consist of:
 - One refined subject attribute class diagram
 - Subject entity class definition
 - Some number of relation class definitions applicable to the subject entity class
 - Refinement alternative FEOs
- Revised/Refined Attribute Class Definitions (Key and Non-Key Attribute Classes)

A typical Phase Four kit should contain between 30 and 50 pages of material. It should require no more than one or two hours for review.


In summary, Phase Four, rather than producing an appreciable quantity of new material, concentrates on the further delineation of already established materials.

5.7 Conclusion

With the completion of Phase Four of this process, an integrated information model will have been produced. If the methodology has been adhered to throughout the model's development, the integrated model will represent a stable, integrated, information structure from the source models from which it originated can be "projected" in their revised form. This new "integrated" model provides a stable foundation for the future integration of additional information into the enterprise information structure.

FTR110410000U
08 September 1983

APPENDIX A
SUMMARY SYSTEM 0



USED AT: _____ AUTHOR: _____ PROJECT: _____ DATE: _____

WORKING	READER	DATE
DRAFT		
RECOMMENDED		
PUBLICATION		

CONTEXT: _____


NOTES: 1 2 3 4 5 6 7 8 9 10

NUMBER: _____


TITLE: Control Manufacture of Product

NODE: SUMMARY/A0F1

PUBLICATION



PUBLICATION



USED AT:	AUTHOR: PROJECT:	DATE: REV:	WORKING	READER	DATE	CONTEXT:
			DRAFT			
			RECOMMENDED			
			PUBLICATION			

NOTES:	1	2	3	4	5	6	7	8	9	10
---------------	---	---	---	---	---	---	---	---	---	----


The flowchart illustrates the process flow between two main components:

- CONTROL (A31):**
 - Inputs: Request for Change in Planning (I1), Eng. Release Change Orders (I2), Schedules Budgets (C2).
 - Outputs: Status, Costs (O3), Assignments (A31).
- DEVELOP DETAILED INSTRUCTIONS (A3345):**
 - Inputs: C1 Work To Be Done, C3 Part & Tool Set Up, C3 Tool Ident. Tool Specs.
 - Output: Detailed Fab. Step Instructions (O1).
- DEVELOP DETAILED INSTRUCTIONS (A3345) also receives:**
 - Input from CONTROL (A31) labeled "Assignments".
 - Input from "Completion Reports" (A34).
- DEVELOP DETAILED INSTRUCTIONS (A3345) outputs:**
 - Detailed Fab. Step Instructions (O1).
 - Detailing Problems (O2).

Legend: 1 Actually from A34


MODE: SUMMARY / A 3F1	TITLE: PLAN PRODUCTION	NUMBER:
---------------------------------	----------------------------------	----------------

PUBLICATION




NODE MFG/A3 F2 TITLE PLAN PRODUCTION NUMBER

PUBLICATION




THIS IS A "CHANNEL" DIAGRAM

PUBLICATION




THIS IS A "CHANNEL" DIAGRAM

PUBLICATION



PUBLICATION




NOTE

MFG/A5F1


UNIT

OBTAIN MANUFACTURING MATERIALS

NUMBER




PUBLICATION



MI G/A6 F2	TITLE	PRODUCE PRODUCT	NUMBER
------------	-------	-----------------	--------

THIS DIAGRAM REDRAWN

PUBLICATION




NUMBER

TITLE CONTROL PRODUCTION ORDERS

SUMMARY /A61F1

MODE

PUBLICATION



NUMBER	
TITLE	STORE ITEMS AND TOOLS
SUMMARY /A622F1	

AD-A137 422

INTEGRATED COMPUTER-AIDED MANUFACTURING (ICAM)
ARCHITECTURE PART 3 VOLUME. (U) SOFTECH INC WALTHAM MA
S SMITH ET AL. SEP 83 FTR110410000U

2/2


UNCLASSIFIED

AFWAL-TR-82-4063-VOL-2 F33615-80-C-5109

F/G 9/2


NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

PUBLICATION




NUMBER


TITLE GATHER ITEMS & TOOLS

NODE SUMMARY/A623F1

PUBLICATION




PUBLICATION



NODE: MFG/A63 F1 TITLE: PERFORM PHYSICAL PRODUCTION NUMBER

THIS IS A "CHANNEL" DIAGRAM ONLY

PUBLICATION



END

FILMED

02 - 84

DTIC