

HD-A138 434

MECHANICAL FACE SEAL TECHNOLOGY: A LITERATURE SURVEY
(U) DAVID W TAYLOR NAVAL SHIP RESEARCH AND DEVELOPMENT
CENTER BETHESDA MD N T SIDES FEB 84 DTNSRDC-84/004


1/1

UNCLASSIFIED

F/G 11/1

NL





12

DTNSRDC-84/004

**DAVID W. TAYLOR NAVAL SHIP
RESEARCH AND DEVELOPMENT CENTER**

Bethesda, Maryland 20884



AD A138434

MECHANICAL FACE SEAL TECHNOLOGY: A LITERATURE SURVEY

by

N.T. Sides

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

SHIP MATERIALS ENGINEERING DEPARTMENT
RESEARCH AND DEVELOPMENT REPORT

DTIC
ELECTED
MAR 01 1984

February 1984

DTNSRDC-84/004

DTIC FILE COPY

MECHANICAL FACE SEAL TECHNOLOGY: A LITERATURE SURVEY

84 03 01 01

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

(Block 20 continued)

S The difficulties in modeling seal performance are emphasized. Indeed, it is remarkable and encouraging that several of the models developed do predict face seal performance with some degree of accuracy.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

TABLE OF CONTENTS

	Page
FIGURE.	111
ABSTRACT.	1
ADMINISTRATIVE INFORMATION.	1
INTRODUCTION.	1
GENERAL FACE SEAL DESIGN AND FIELD EXPERIENCE	3
VIBRATION AND DYNAMICS.	4
CAVITATION.	5
WAVINESS.	5
PHASE CHANGE.	6
THERMAL EFFECTS	7
MATERIALS	8
CONCLUSIONS	9
REFERENCES.	11

FIGURE

1 - Existing Propeller Shaft Seal Design.	2
---	---



Accession For	
NTIS GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Special
A-1	

ABSTRACT

A literature survey was conducted to review and evaluate the state of the art in mechanical face seal technology. The survey is part of a study to develop the capability of designing improved seals for Navy use. Sixty-eight references are cited and discussed. The report is subdivided into several sections, each embracing a general physical aspect of face seal operation. The difficulties in modeling seal performance are emphasized. Indeed, it is remarkable and encouraging that several of the models developed do predict face seal performance with some degree of accuracy.

ADMINISTRATIVE INFORMATION

This report covers work conducted under the SSN 688 Shaft Seal Improved Life Program under Program Element 63569N, Task Area S1257 SL001, and Work Unit 2723-606.

INTRODUCTION

Mechanical face seals find numerous applications in naval machinery, for example on the propeller shaft and in all the fluid-handling pumps. When a seal fails, repair is usually costly in terms of lost time and direct costs. Thus, improved seal life and reliability would be of significant benefit to the Navy.

The immediate objective of the present work was to review the state of the art in mechanical shaft seal technology. The ultimate goal is to develop the capability of designing seals with longer life and greater reliability.

Mechanical face seals consist of two annular rings rotating relative to each other and pressed together by spring and fluid pressures (see Figure 1). The idea is to maintain a small gap between the ring faces such that leakage is kept very low but a definite lubricant film is provided.

Although the fundamentals of operation of mechanical face seals have only been seriously addressed in the last two decades, important advances in the understanding of seal operation have been made during that time. Despite these advances, however, seal performance remains a hit-or-miss proposition. A seal may perform for a very long time with virtually no leakage or wear, while another will fail completely in very short order under seemingly identical working conditions. In general, seals for specific applications can be designed to perform reliably, although




Figure 1 - Existing Propeller Shaft Seal Design

there are numerous applications where satisfactory operation has not been possible. The problem is that because the mechanics of seal operation are still not thoroughly understood, the designer cannot anticipate the seal's performance as a function of its design parameters. In spite of the numerous theoretical models developed over the years, no fundamental theoretical basis is available to prescribe a seal design that will result in predictable performance. Improvements to date have resulted from the application of elementary theoretical models combined with trial and error from previous experience.

This report, which examines the literature available on the subject of mechanical face seals, was limited to work performed from 1970 to the present and focuses on actual seals or seal-like geometry. Thus, work on fluid-film bearings was excluded despite the similarities to seals in their theoretical treatment. Each section of this report loosely relates to a specific area of concentration, although significant overlap occurs in the subjects discussed. Many literature surveys have been written on seals, and they are referenced where applicable.

The literature search originated with the National Aeronautics and Space Administration (NASA) data banks and the DIALOG information retrieval services. The data sources queried were then expanded to include the major technical societies such as the American Society of Mechanical Engineers (ASME); the American Society of Lubrication Engineers (ASLE); the British Hydromechanics Research Association (BHRA); and the technical journals such as Wear, Lubrication Engineering, Tribology International, and others.

GENERAL FACE SEAL DESIGN AND FIELD EXPERIENCE

The British Hydromechanics Research Association published several bibliographies containing citations from their data base on the general and specific aspects of seal design. The performance of dynamic seals was discussed in terms of frictional forces, as were the methods of lubrication and wear resistance and the procedures to test and measure them.^{1*} Consideration was given to antifriction behavior, improved materials, lubricant effects, accelerated model wear testing, and waviness effects of tilt and coning.² General applications for seals and patent literature were discussed³ and extremely high-pressure applications were reviewed.⁴

*A complete list of references appears on page 11.

Metcalf⁵ examined seal failures in Canadian nuclear reactor pumps, and he described the experience gained from these failures relating to inadequate lapping, inelasticity, erosion, corrosion, abrasion, adhesion, surface fatigue, cavitation, thermocracking, seal ring breakage, and static seal failure. Ludwig and Greiner^{6,7} described basic assembly configurations, their advantages and shortcomings, and their applications. They related lubrication mechanisms to seal operation and discussed hydrodynamic and hydrostatic effects. Nau and Rowles⁸ wrote a computer program to aid in seal design. The program accounts for surface topography, interfacial fluid dynamics, cavitation, self-generated heat, and thermal and mechanical distortion. Buck⁹ developed a methodology to evaluate seal designs or applications based on observations of maintenance data representing over 130 pump years of service. Seal life was correlated to three dimensionless parameters.

Martinson¹⁰ discussed the development of a large diameter, high-pressure seal for nuclear reactor service. He also described the final seal design configuration in detail and included computer modeling techniques, materials, seal design and operating parameters, and results of special development tests. Recently, Metcalfe¹¹ reviewed seal-related equipment used in the nuclear power industry, highlighting its novel or useful features and the understanding gained from its use. Summers-Smith¹² analyzed maintenance data for centrifugal pump seals in a petrochemical plant. Results suggested that pressure is generated in the lubricant film as a consequence of surface waviness. A major factor of early seal failure was the inability to generate the correct face profile during the initial stages of running.

VIBRATION AND DYNAMICS

An extensive literature review was conducted recently by Etsion.¹³ He divided the review into three sections. The first relates to experimental observations of seal vibration, the second to investigations of dynamic properties of seal elements, and the third to theoretical dynamic analyses of mechanical face seals. Several relevant papers have been published since that time. Green and Etsion¹⁴ calculated stiffness and damping coefficients of the seal fluid film for three degrees of freedom using small perturbation of the ring from its equilibrium position and compared the results with those of other analyses. Childs¹⁵ also derived

dynamic coefficients for high-pressure seals and compared them to other published results. In a companion paper,¹⁶ he developed a finite length solution procedure based on Hirs' turbulent lubrication model. The model gave reasonable results with no swirl present, but failed when swirl was introduced. Dhagat et al.¹⁷ studied the response of a hydrodynamic seal to a specified initial disturbance. They numerically integrated the linearized and the nonlinear equation of motion for lateral oscillations of the seal.

CAVITATION

The subject of cavitation in face seals was recently reviewed by Nau.¹⁸ He summarized past work and presented an analytical model to calculate film cavitation boundaries. Kistler et al.¹⁹ conducted an experiment simulating cavitation in submarine stern-tube seals. Cavitation bubbles were observed and several analytical models were studied. The physical parameters influencing bubble growth and collapse were identified. Ikeuchi and Mori²⁰ adopted a different numerical technique, whereby the mass continuity is preserved in a ruptured film, thus allowing the cavitation boundary to be determined. They showed that load capacity rises with cavitation. In a companion paper,²¹ the authors showed that inward pumping was induced by cavitation and film thickness variation. They concluded that leakage is independent of cavitation unless radial forces are applied to the cavities.

WAVINESS

Lebeck²² found that concentrated drive forces are the largest contributors to waviness. He developed general equations for ring deflection based on curved-beam theory and found that second and odd value harmonics are generally predominant. He also developed a mixed lubrication model²³ to predict the effects of longitudinal roughness and waviness on lubricant behavior and found that most of the load was supported by hydrodynamic pressure. The model was refined²⁴ to consider the contribution of mechanical and hydrostatic pressures, and of thermal rotation. The results showed a strong influence of thermal rotation on initial seal performance and wear. Subsequently, a test machine capable of imposing waviness on a seal ring was described.²⁵ The waviness was moved slowly relative to the ring under rotation to preclude localized wear, which greatly reduced friction and wear. Waviness and tilt then were varied²⁶ to optimize friction and wear for a given leakage. The geometry of the seal is therefore dictated by the optimum design

developed. Lebeck's mixed lubrication model was further refined²⁷ to consider waviness amplitude, surface roughness, asperity contact, hydrodynamic and hydrostatic pressures, and fluid cavitation:

A numerical method of solution was presented by Young and Lebeck,²⁸ who obtained experimental data and compared it to the mixed lubrication model. Good agreement was reported for initial torque and leakage as a function of initial taper. While predicted equilibrium thermal taper (as a function of torque for a balance ratio of 1.0) was in good agreement with experimental results, the agreement was not so good for a balance ratio of 0.75. Based on previous tests,²⁵ Lebeck proposed a wavy seal design for a submarine application.²⁹ Ruddy et al.³⁰ analyzed the effects of a two-period waviness on both the face and the seat. They obtained a closed-loop cyclic solution of a two-dimensional Reynold's equation including squeeze film effects. The waviness amplitude was found to be an order of magnitude less than that measured on seals that have successfully operated in service.³¹ Peng and Cheng³² investigated flow between a rotating and a stationary disk with concentric waviness. They solved the Navier-Stokes equations using a perturbation scheme and concluded that the disk with single negative sine waviness results in minimum leakage and torque at a given wave amplitude.

PHASE CHANGE

The hypothesis that a phase change may take place as the liquid flows between the mating seal rings was first proposed in the work of Orcutt.³³ Hughes et al.³⁴ studied the phenomenon almost a decade later. They concluded that boiling occurs, particularly when the liquid nears saturation conditions; that the main reason for boiling is the flashing which occurs as the pressure decreases across the seal's radius; and that stability criteria exist under boiling conditions. The model was extended to isothermal and adiabatic cases and solved numerically in a follow-up paper.³⁵ Turbulent two-phase flow, with heat addition due to rotational dissipation and the effects of centrifugal inertia, was considered next.³⁶ A general theory was presented for quasi-steady operation. Lebeck³⁷ emphasized a mixed friction hydrostatic seal model where both mechanical contact and phase change effects were considered. He showed that phase change resulted in a greater load support by fluid-film pressure than either an all-liquid or an all-gas seal and concluded that operation at a higher temperature reduces seal wear rate and friction.

Will³⁸ conducted experimental tests that supported Lebeck's theoretical work. Kuzma³⁹ analyzed a grooved seal to determine the location and shape of the liquid-gas interface. Barnard and Weir⁴⁰ examined seals that operated successfully in an oil refinery. They observed three concentric rings across the seal faces and hypothesized that the gas-band conditions approach the critical temperature and pressure of the sealed fluid. They correlated actual and computed track dimensions.

THERMAL EFFECTS

Black⁴¹ solved the equations of thermoelasticity in a three-dimensional, axisymmetric space. He obtained a pressure-velocity relation based on the analytical stress values. Chin-Hsiu⁴² solved the temperature fields and deformations numerically for both the seal and mating rings. He found the mechanical deformation to be small compared to the thermal deformation. Lebeck⁴³ developed deflection equations which included both thermal and mechanical loading and combined them with a wear equation. He formulated a mathematical model that predicted the limits of stable operation and later modified some of the assumptions made in the model⁴⁴ such that results agreed with those of Burton et al.⁴⁵ Banerjee and Burton⁴⁶ conducted experiments on hydrodynamic seals at thermal equilibrium conditions, comparing changes in waviness and mean film thickness to theoretical predictions of thermal growth of waviness. Wu and Burton⁴⁷ developed a model to explain the coupled inertial/thermoelastic instability observed experimentally by Banerjee.⁴⁸ Netzel⁴⁹ reviewed field and laboratory results with respect to the development of thermoelastic instabilities at the seal interface and reported the effect that interface cooling has on the surface disturbances. Kilaparti⁵⁰ studied the thermoelastic instability problem by breaking it into subproblems and obtaining a solution for each case. Effects of material properties on critical speed and of critical speed at the onset of instability were presented analytically. Suganami et al.⁵¹ formulated a model to predict the oval deformation of a seal ring due to hot spots and the rotation of the oval shape relative to the hot spots. Experimental results were presented to confirm the model predictions. Kennedy et al.^{52,53} investigated thermocracking on a cobalt-based superalloy seal ring and proposed a mechanism for initiation and propagation of microcracks that agreed with microscopic observations. A contact probe was built to determine the number, size, location, and surface temperature of contact patches over a range of seal velocities. The size and

temperature of the contact was found to be influenced by the operating velocity and by the thermal, elastic, and wear properties of the seal materials.

MATERIALS

Merrick⁵⁴ characterized interfacial wear reactions of pure nickel and nickel 20 atomic percent molybdenum. Hard facing alloys were weld-deposited on Inconel 625 coupons in a study by Vreeland et al.⁵⁵ A special cermet, developed for possible use as a wearing surface, showed excellent wear and corrosion-resistance properties. Lohou⁵⁶ discussed a new version of silicon-carbide (SiC-S) as applied to water-injection pumps. Echtenkamp⁵⁷ compared the properties of tungsten and titanium carbides with other materials. Lashway⁵⁸ reviewed the commercial forms of silicon-carbide with respect to the manufacturing processes, resultant properties, and impact on seal performance. Lagerquist and Sandvick⁵⁹ developed a new type of corrosion-resistant cemented carbide that maintained the physical and mechanical properties of the base alloy by adding chromium and molybdenum to tungsten carbide/nickel grades. These additives stabilize the metallic binder phase both mechanically and electromechanically without affecting the carbide phase.

Effertz and Fichte⁶⁰ examined seal failures in large reactor water pumps and concluded that material loss from the tungsten-carbide rings with nickel or cobalt binders followed the dissolution of these binders. They recommended the use of a NiCrMo binder, the use of SiC rings, or the use of synthetic resins in place of Sb impregnation. Dziedzic⁶¹ presented experimental data to compare the corrosion, thermal shock, and wear resistance of siliconized graphite and SiC with that of carbon graphite for nuclear service pumps. Paxton et al.⁶² ran a carbon seal ring against hard carbon, fused alumina, tungsten carbide, silicon-carbide, and silicon-carbide-coated graphite in water. They found that SiC run against hard carbon produced the most stable coefficient of friction. Earlier, Paxton and Strugala⁶³ ranked carbon impregnated with silver, babbitt, bronze, copper, antimony, and resin against 85% sintered aluminum oxide. The resin-impregnated carbon had the lowest wear rate. Ya⁶⁴ examined the phenomenon of selective material transfer in which specific components of one element of a friction pair are transferred to the other when in contact with a liquid dielectric. Beck⁶⁵ presented a theory of electrochemical corrosion caused by accelerating fluid through a gap. The flow generates electrokinetic streaming current, which causes the corrosion. Hirano and Sakai⁶⁶

demonstrated reduced friction, wear, and leakage by chain matching. This effect, which is considered to play a predominant role in thin film lubrication, appears when numbers of carbon atoms of a solvent and an additive coincide.

Tribe⁶⁷ characterized and assessed a wide variety of seal materials and discussed a variety of failure mechanisms. Labus⁶⁸ investigated the following seal materials: carbon, aluminae ceramics, siliconized carbons, silicon carbide, cast iron, and tungsten carbide. He established that speed was the dominant factor, with pressure and temperature having secondary effects.

CONCLUSIONS

The difficulties in formulating an encompassing (Universal) seal operating model become obvious. The mechanical face seal is a complex system in which many physical phenomena coexist and interact such that their contributions are impossible to consider separately. Mathematically, the large number of coupled equations is unwieldy in any kind of closed-form solution. Combining these equations into a single model without solving them would be a formidable task in itself. All of the authors cited addressed one or more physical aspect. Some formulated an approximate model that either neglected other physical phenomena or made simplifying assumptions about them, which renders the outcome predictably incomplete. However, the models are valid for a specific range of operation under specific constraints. Others attempted to combine one or more existing models, with mixed success, but experimental data are still lacking. Most of the existing data are generated from an attempt to highlight the theoretical model developed. As such, these data find little applicability in supporting another author's model, which may require parameters not measured by the original researcher. Difficulty also arises because seal performance cannot be scaled. A small seal can operate successfully while a larger one, using the same geometry and materials and operating under identical conditions and loads, can fail. This makes comparisons between different sizes of seals difficult.

It is a remarkable achievement nonetheless to find that several models were developed that do indeed predict seal operation with some degree of accuracy. Steady progress is being made in understanding the underlying principles of seal operation, as evidenced by the increased sophistication of the most recent models.

REFERENCES

1. "Lubrication and Wear Resistance of Dynamic Seals," (Citations from the Brit. Hydromechanics Res. Assoc. Fluid Engineering Data Base), Nat. Tech. Inf. Service, Springfield, VA, Report 885646 PB82-856584, p. 161 (Dec 1981).
2. "Mechanical Face Seal: Lubrication and Wear Resistance," (Citations from the Brit. Hydromechanics Res. Assoc. Fluid Eng. Data Base), Nat. Tech. Inf. Service, Springfield, VA, Report 967362 PB83-861179, p. 204 (Feb 1983).
3. "Shaft Seals," (Citations from the Brit. Hydromechanics Res. Assoc. Fluid Eng. Base), Nat. Tech. Inf. Service, Springfield, VA, Report 967368 PB83-861245, p. 287 (Feb 1983).
4. "High Pressure Seals and Sealants," (Citations from the Brit. Hydromechanics Res. Assoc. Fluid Eng. Data Base), Nat. Tech. Inf. Service, Service, Springfield, VA, Report 967353 PB83-861088, p. 135 (Feb 1983).
5. Metcalfe, R., "End Face Seals in High Pressure Water, Learning from Those Failures," Am. Soc. Lubrication Eng. Paper 75-LC-1B-1 prepared for joint Am. Soc. Lubricating Eng./Am. Soc. Mech. Eng. Lubrication Conf., Miami Beach, FL (21-23 Oct 1975).
6. Ludwig, L.P. and H.F. Greiner, "Design Considerations in Mechanical Face Seals for Improved Performance. 1: Basic Configurations," Nat. Aeronautics Space Admin. Report NASA-TM-73735; E-9298-1, p. 20 (1977).
7. Ludwig, L.P. and H.F. Greiner, "Design Considerations in Mechanical Face Seals for Improved Performance. 2: Lubrication," Nat. Aeronautics Space Admin. Report NASA-TM-73736; E-9298-2, p. 20 (1977).
8. Nau, B.S. and R.T. Rowles, "A Computational Tool for Mechanical Seal Design," Proc. Adv. Group Aerospace Res. Dev. Propulsion and Energetics Panel Meeting on Seal Technology, United Kingdom (6-7 Apr 1978). AGARD Conf. Proc. No. 237.

9. Buck, G.S., "A Methodology for Design and Application of Mechanical Seals," Am. Soc. Lubrication Eng. Trans. Vol. 23, No. 3, pp. 244-252 (1979).
10. Martinson, A.R., "Design, Development and Testing of Large Diameter, High Pressure Seals for Nuclear-Reactor, Primary-Coolant Pumps - A Challenge to the Pump Manufacturer," Lubrication Eng., Vol. 36, No. 6, pp. 325-340 (Jun 1980).
11. Metcalfe, R. and R.D. Watson, "Equipment for Development of Better End-Face Seals - A Progress Review," Lubrication Eng., Vol. 39, No. 5, pp. 275-284 (May 1983).
12. Summers-Smith, D., "Performance of Mechanical Seals in Centrifugal Process Pumps," 9th Internat. Conf. on Fluid Sealing, Paper 1 (1981).
13. Etsion, I., "A Review of Mechanical Face Seal Dynamics," The Shock and Vibration Digest, Vol. 14, No. 3, p. 14 (Mar 1982).
14. Green, I. and I. Etsion, "Fluid Film Dynamic Coefficients in Mechanical Face Seals," Trans. Am. Soc. Mech. Eng., Vol. 105, pp. 297-301 (Apr 1983).
15. Childs, D.W., "Dynamic Analysis of Turbulent Annular Seals Based on Hirs' Lubrication Equation," Am. Soc. Mech. Eng. Paper 82-LUB-41 (1982).
16. Childs, D.W., "Finite-Length Solutions for Rotodynamic Coefficients of Turbulent Annular Seals," Am. Soc. Mech. Eng. Paper 82-LUB-42 (1982).
17. Dhagat, S.K., R. Sinhasan, and D.V. Singh, "The Non-Linear Response of Hydrodynamic Seals," Wear, Vol. 82, pp. 153-165 (1 Nov 1982).
18. Nau, B.S., "Observations and Analysis of Mechanical Seal Film Characteristics," Trans. Am. Soc. Mech. Eng., J. Lubrication Tech., Vol. 102, pp. 341-349 (July 1980).
19. Kistler, A.L., H.S. Chang, K. Nivatvongs, and I. Ozakat, "Cavitation Phenomenon in Face Seals," Northwestern University Department of Mechanical and Nuclear Engineering Contract N00014-79-C-0007 (15 Jul 1977).

20. Ikeuchi, K. and H. Mori, "Hydrodynamic Lubrication in Seals with Cavitation - 1. Effect of Cavity Pressure on Lubricating Film," J. Soc. Mech. Eng., Vol. 25, No. 204, pp. 1002-1007 (Jun 1982).

21. Ikeuchi, K. and H. Mori, "Hydrodynamic Lubrication in Seals with Cavitation - 2. Effect of Cavity Pressure on Leakage," J. Soc. Mech. Eng., Vol. 25, No. 204, pp. 1008-1013 (Jun 1982).

22. Lebeck, A.O., "Mechanical Loading - A Primary Source of Waviness in Mechanical Face Seals," Am. Soc. Lubrication Eng. Trans., Vol. 20, No.3, pp. 195-208 (1976).

23. Lebeck, A.O., "A Study of Mixed Lubrication in Contacting Mechanical Face Seals," Proc., 4th Leeds-Lyon Symposium on Tribology, Lyon, France (Sep 1977).

24. Lebeck, A.O., "Mixed Friction Hydrostatic Mechanical Face Seal Model with Thermal Rotation and Wear," Am. Soc. Lubrication Eng. Trans., Vol. 23, No. 4, pp. 375-387 (Oct 1980).

25. Lebeck, A.O., "Test Apparatus for Measuring the Effects of Waviness in Mechanical Face Seals," Am. Soc. Lubrication Eng. Trans., Vol. 24, No. 3, pp. 371-378 (Jul 1981).

26. Lebeck, A.O., "Design of an Optimum Moving Wave and Tilt Mechanical Face Seal for Liquid Applications," Brit. Hydromechanics Res. Assoc. Fluid Engineering, Paper E2, pp. 163-184 (1981).

27. Lebeck, A.O., "Hydrodynamic Lubrication in Wavy Contacting Face Seals - A Two-Dimensional Model," Am. Soc. Mech. Eng., J. Lubrication Tech., Vol. 103, pp. 578-586 (Oct 1981).

28. Young, L.A. and A.O. Lebeck, "Experimental Evaluation of a Mixed Friction Hydrostatic Mechanical Face Seal Model Considering Radial Taper, Thermal Taper, and Wear," Transactions Am. Soc. Mech. Eng., J. Lubrication Tech., Vol. 104, pp. 439-448 (Oct 1982).

29. Lebeck, A.O., L.A. Young, K.L. Wong, and J. Knowlton, "Application of the Wavy Mechanical Face Seal to Submarine Seal Design," Defense Tech. Inf. Center Report Bibliography AD-A125-810, p. 220 (Jul 1982).

30. Ruddy, A.V., D. Dowson, and C.M. Taylor, "The Prediction of Film Thickness in a Mechanical Face Seal with Circumferential Waviness on Both the Face and the Seat," J. Mech. Eng. Sci., Vol. 24, No. 1, pp. 37-43 (1982).

31. Ruddy, A.V. and D. Summers-Smith, "Mechanism of Film Generation in Mechanical Face Seals," Tribology Int., Vol. 15, No. 4, pp. 227-231 (Aug 1982).

32. Peng, W.W. and L.C. Cheng, "Effects of Concentric Surface Waviness on Leakage Between Rotating Disks," In: Fluid Mechanics of Mechanical Seals: Proc. of the Winter Annual Meeting, Phoenix, AZ, (14-19 Nov 1982). (A83-18046-37) New York, Amer. Soc. Mech. Eng., p. 121-28 (1872).

33. Orcutt, F.K., "An Investigation of the Operation and Failure of Mechanical Face Seals," Am. Soc. Mech. Eng., J. Lubrication Tech., Vol. 91, No. 4, pp. 713-725 (Oct 1969).

34. Hughes, W.F., N.S. Winowic, M.J. Birchall, and W.D. Kennedy, "Phase Change in Liquid Face Seals," Am. Soc. Mech. Eng., J. Lubrication Tech., Vol. 100 pp. 74-80 (Jan 1978).

35. Hughes, W.F. and N.H. Chang, "Phase Change in Liquid Face Seals II - Isothermal and Adiabatic Bounds with Real Fluids," Am. Soc. Mech. Eng., J. Lubrication, Vol. 102, pp. 350-359 (Jul 1980).

36. Hughes, W.F. and R.M. Beeler, "Turbulent Two-Phase Flow in Ring and Face Seals," Brit. Hydromechanics Res. Assoc., Fluid Eng. Paper E3, pp. 185-202 (1981).

37. Lebeck, A.O., "Mixed Friction Hydrostatic Face Seal Model with Phase Change," Am. Soc. Mech. Eng., J. Lubrication Tech., Vol. 102, pp. 133-138 Apr 1980).

38. Will, T.P., Jr., "Experimental Observations of a Face Contact Mechanical Shaft Seal Operating on Water," Lubrication Eng., Vol. 38, No. 12, pp. 767-772 (Dec 1982).

39. Kuzma, D.C., "The Liquid-Gas Interface in Grooved Face Seals," In: Fluid Mechanics of Mechanical Seals: Proc. of the Winter Annual Meeting, Phoenix, AZ (Nov 14-19 1982). (A83-1804606-37) New York, Am. Soc. Mech. Engrs. pp. 13-20 (1982) 14-19 1982)

40. Barnard, P.C., and R.S.L. Weir, "A Theory for Mechanical Seal Face Thermodynamics," 8th International Conference on Fluid Sealing, Brit. Hydromechanics. Res. Assoc. Fluid Eng., Paper H1 (Sep 1978).

41. Blach, A.E., "Thermoelastic Behavior of Sealing Rings for Mechanical Seals," 6th Internat. Conf. on Fluid Sealing, Brit. Hydromechanics Res. Assoc., Paper D3, pp. 29-38 (1973).

42. Chin-Hsiu, L., "Thermal Deformation in a Mechanical Face Seal," Am. Soc. Lubrication Eng. Trans., Vol. 19, No. 2, pp. 146-152 (1976).

43. Lebeck, A.O., "Theory of Thermoelastic Instability of Rotating Rings in Sliding Contact with Wear," Am. Soc. Mech. Eng., Trans. J. Lubrication Tech. pp. 277-285 (Apr 1976).

44. Lebeck, A.O., "Effect of Ring Deflection and Heat Transfer on the Thermoelastic Instability of Rotating Face Seals," Wear, Vol. 59, No. 1, pp. 121-133 (1980).

45. Burton, R.A., V. Nerlikar, and S.R. Kilaparti, "Thermoelastic Instability in a Seal-Like Configuration," Wear, Vol. 24, pp. 177-188 (1973).

46. Banerjee, B.N. and R.A. Burton, "Experimental Studies in Thermoelastic Effects in Hydrodynamically Lubricated Face Seals," Am. Soc. Mech. Eng., Trans, J. Lubrication Tech., Vol. 101, pp. 275-282 (Jul 1979).

47. Wu, Y.T. and R.A. Burton, "Thermoelastic and Dynamic Phenomenon in Seals," Am. Soc. Mech. Eng. Paper 80-C2/Lub-9 (Sep 1978).
48. Banerjee, B.N. and R.A. Burton, "An Instability for Parallel Sliding of Solid Surfaces Separated by a Viscous Liquid Film," Trans. Am. Soc. Mech. Eng., J. Lubrication Tech. Vol. 98, pp. 157-166 (Jan 1976).
49. Netzel, J.P., "Surface Disturbances in Mechanical Face Seals from Thermoelastic Instability," Am. Soc. Lubrication Eng. Preprint 80-AM-63-1.
50. Kilaparti, S.R., "Thermoelastic Instability in a Seal-Like Configuration," (Ph.D. Thesis) Northwestern University Microfilm Order 8124923 (1981).
51. Suganami, T., T. Mosuda, N. Oishi, and T. Shimazu, "Study on Thermal Behavior of Large Seal Ring," Trans. Am. Soc. Mech. Eng., J. Lubrication Tech., Vol. 104, No. 4, pp. 449-454 (1982).
52. Kennedy, F.E., Jr. and S.A. Karpe, "Thermocracking of a Mechanical Face Seal," Wear, Vol. 79, pp. 21-36 (15 Jun 1982).
53. Kennedy, F.E., Jr. et al, "Factors Influencing Thermomechanical Failure of Face Seals II," Nat. Tech. Inf. Service 967423 AD-A124 189/2 (Jan 1983).
54. Merrick, E.A., "A Study of Wear Reactions on Mechanical Face Seals of Nickel and Nickel-20 Atom Percent Molybdenum Alloys," Tennessee University Report ME-73-T57-15, Contract N00014-68-A-0144 (Mar 1973).
55. Vreeland, D.C., B.B. Miller, and J. Carroll, "Development of Materials Resistant to Wear and Corrosion for Mechanical Face Seal Applications," Naval Ship Research & Development Report 4299 (Nov 1974).
56. Lohou, J., "Mechanical Seals for Water Injection Pumps - A New Hard Face Material," Lubrication Eng. Vol. 34, No. 6, pp. 320-326 (Jun 1978).
57. Echtenkamp, A.L., "Combating Corrosion/Wear with the Hard Carbide Alloys," Am. Soc. Lubrication Eng. Preprint 78-LC-3C-2 (1978).

58. Lashway, R.W., "Silicon Carbide for Mechanical Shaft Seals," Brit. Hydromechanics Res. Assoc. Fluid Eng., Paper A4 (1981).

59. Lagerquist, M. and A.B. Sandvick, "Corrosion Resistant Cemented Carbide Grades for Mechanical Seals," Brit. Hydromechanics Res. Assoc., Fluid Eng., Paper A2 (1981).

60. Effertz, P.H. and W. Fichte, "Selective Corrosion in Axial Hydrodynamic Controlled Leakage Shaft Seals Made from Carbide/Carbon in Ultrafine, Conditioned Power Station Water - Water Cooled Reactors," Translated from Der Maschinenschaden, Vol. 54, No. 4, pp. 113-123 (1982).

61. Dziedzic, J., "Siliconized Graphite and Silicon Carbide as Face Materials for Mechanical Seals in 12% Boric Acid - Nuclear Service," Lubrication Eng., Vol. 36, No. 11, pp. 643-651 (Nov 1980).

62. Paxton, R.R. and H.T. Hulburt, "Rubbing Friction in Radial Face Seals," Lubrication Eng., Vol. 36, No. 2, pp. 89-97 (Feb 1980).

63. Paxton, R.R. and E.W. Strugala, "Wear Rates of Impregnated Carbons Sealing Warm Water," Am. Soc. Lubrication Eng. Preprint 73-AM-6E-1 (Aug 1973).

64. Ya, S.A., "Mechanism of Selective Transfer," Soviet Material Sci., Vol. 15, No. 1, pp. 429-444 (Jan-Feb 1979).

65. Beck, T.R., "Zeta Corrosion of Mechanical Seals," Preprint for Annual Meeting, Am. Soc. Mech. Eng., Phoenix, AZ (Nov 1982).

66. Hirano, F. and T. Sakai, "The Chain Matching Effect on Performance of Mechanical Seals," Brit. Hydromechanics Res. Assoc., Paper XI (1981). (1981).

67. Tribe, F.J., "Seawater-Lubricated Mechanical Seals and Bearings, Associated Material Problems," Lubrication Eng., Vol. 39, No. 5, pp. 292-299 (1983).

68. Labus, T.J., "The Influence of Rubbing Materials and Operating Conditions on the Power Dissipated by Mechanical Seals," Am. Soc. Lubrication Eng. Preprint ASLE Preprint 80-AM-6B-3 (1980).

INITIAL DISTRIBUTION

Copies

3 NRL Code 617D
 2 (Dr. J. Murday)
 1 (Dr. R. Mowery)

15 NAVSEA
 2 SEA 05R14 (Dr. H.
 Vanderveldt)
 2 SEA 05R32 (J. DeCorpo)
 5 SEA 56X43 (R. Graham)
 2 SEA 996
 2 PMS 393 (C. Kresge)
 2 PMS 396 (C. Mussen and
 M. McBride)

12 DTIC

CENTER DISTRIBUTION

Copies	Code	Name
1	272	E. Quandt, Jr.
1	272A	A. Smookler
1	2723	B. Neild, Jr.
1	28	J. Belt
1	2809	A. Malec
1	283	H. Singerman
5	2832	J. Dray
10	2832	T. Sides
10	5211.1	Reports Dist.
1	522.1	TIC
1	522.2	TIC
2	5231	Office Services

DTNSRDC ISSUES THREE TYPES OF REPORTS

1. DTNSRDC REPORTS, A FORMAL SERIES, CONTAIN INFORMATION OF PERMANENT TECHNICAL VALUE. THEY CARRY A CONSECUTIVE NUMERICAL IDENTIFICATION REGARDLESS OF THEIR CLASSIFICATION OR THE ORIGINATING DEPARTMENT.

2. DEPARTMENTAL REPORTS, A SEMIFORMAL SERIES, CONTAIN INFORMATION OF A PRELIMINARY, TEMPORARY, OR PROPRIETARY NATURE OR OF LIMITED INTEREST OR SIGNIFICANCE. THEY CARRY A DEPARTMENTAL ALPHANUMERICAL IDENTIFICATION.

3. TECHNICAL MEMORANDA, AN INFORMAL SERIES, CONTAIN TECHNICAL DOCUMENTATION OF LIMITED USE AND INTEREST. THEY ARE PRIMARILY WORKING PAPERS INTENDED FOR INTERNAL USE. THEY CARRY AN IDENTIFYING NUMBER WHICH INDICATES THEIR TYPE AND THE NUMERICAL CODE OF THE ORIGINATING DEPARTMENT. ANY DISTRIBUTION OUTSIDE DTNSRDC MUST BE APPROVED BY THE HEAD OF THE ORIGINATING DEPARTMENT ON A CASE-BY-CASE BASIS.

FILME

4-84