

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE					
1a. REPORT SECURITY CLASSIFICATION Unclassified		1b. RESTRICTIVE MARKINGS None			
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.			
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) NORDA Report 90		5. MONITORING ORGANIZATION REPORT NUMBER(S) NORDA Report 90			
6. NAME OF PERFORMING ORGANIZATION Naval Ocean Research and Development Activity		7a. NAME OF MONITORING ORGANIZATION Naval Ocean Research and Development Activity			
6c. ADDRESS (City, State, and ZIP Code) Ocean Science Directorate NSTL, Mississippi 39529-5004		7b. ADDRESS (City, State, and ZIP Code) Ocean Science Directorate NSTL, Mississippi 39529-5004			
8a. NAME OF FUNDING/SPONSORING ORGANIZATION Naval Ocean Research and Development Activity	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
8c. ADDRESS (City, State, and ZIP Code) Ocean Science Directorate NSTL, Mississippi 39529-5004					
10. SOURCE OF FUNDING NOS.		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT NO.
		61153N			
11. TITLE (Include Security Classification) A Towed Instrument Vehicle for Deep Ocean Sampling					
12. PERSONAL AUTHOR(S) C. R. Rein, D. A. Wiesenburg, and D. M. Lavoie					
13a. TYPE OF REPORT Final		13b. TIME COVERED From _____ To _____		14. DATE OF REPORT (Yr., Mo., Day) January 1985	
15. PAGE COUNT 48					
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) Towed instrument vehicle, oceanographic sampling		
FIELD	GROUP	SUB. GR.			
19. ABSTRACT (Continue on reverse if necessary and identify by block number) A vehicle that can take instrumentation into the ocean while being towed by a surface craft has been built. The vehicle body is a flooded, 8-foot-long cylinder stabilized at the tail and depressed by a short wing. Most of the structural loads are borne by four full-length radius plates. These plates divide the cylindrical body lengthwise into four wet compartments that have quadrant cross sections. Each quadrant can hold instrument payloads as large as five and one-half inches in diameter. Each quadrant can be uncovered independently to service the payload. These features are improvements over previous designs for carrying an assortment of payloads. Construction cost was only \$3200. Design criteria, details of the construction, and results of an initial tow test of the towed body are presented.					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☒ DTIC USERS ☐			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL D. A. Wiesenburg			22b. TELEPHONE NUMBER (Include Area Code) (601) 688-5491		22c. OFFICE SYMBOL Code 333

// Naval Ocean Research and Development Activity.

NSTL, Mississippi 39529

NORDA Report 90

January 1985



A Towed Instrument Vehicle for Deep Ocean Sampling

Final Report

Charles R. Rein

Ocean Technology Division
Ocean Acoustics and Technology Directorate

Denis A. Wiesenburger

Dennis M. Lavoie

Oceanography Division
Ocean Science Directorate

Foreword

Studies of horizontal variability in the ocean require the capability to sample on much shorter length scales than can be accomplished with a series of vertical stations. A towed instrument package is needed to make those horizontal measurements. Thus, there is a recurring need in oceanography for towed vehicles to carry instrumentation below the ocean surface. Usually these vehicles have been designed to perform a specific task. The vehicle described here is the result of an effort to produce a towed vehicle design that can accommodate a wider variety and a greater quantity of instrumentation than can earlier designs, and is also simple to construct and maintain. The vehicle design presented here requires only commonly available materials and simple machining. The simplicity of the design allows for easy modification to satisfy the special requirements of many potential users.



R. P. Onorati, Captain, USN
Commanding Officer, NORDA

Executive summary

A vehicle that can take instrumentation into the ocean while being towed by a surface craft has been built. The vehicle body is a flooded, 8-foot-long cylinder stabilized at the tail and depressed by a short wing. Most of the structural loads are borne by four full-length radius plates. These plates divide the cylindrical body lengthwise into four wet compartments that have quadrant cross sections. Each quadrant can hold instrument payloads as large as 5½ inches in diameter. Each quadrant can be uncovered independently to service the payload. These features are improvements over previous designs for carrying an assortment of payloads. Construction cost was only \$3200. Design criteria, details of the construction, and results of an initial tow test of the towed body are presented.

Acknowledgments

The authors wish to acknowledge Mr. David C. Young who assembled the towed vehicle from the component parts and provided useful suggestions during design modification. We also thank Mr. Patrick J. Setser, Dr. Norman L. Guinasso, and Dr. David R. Schink of Texas A&M University for providing details of the design and towing characteristics of the Texas A&M winged fish. This project was funded by the Naval Ocean Research and Development Activity under Program Element 61153N, Herbert Epert, Jr., program manager.

Contents

Illustrations and tables	iv
Introduction	1
Previous tow vehicles	1
Batfish	1
Fathom Oceanology oceanographic towed fish	2
Texas A&M winged fish	2
TUPS fish design considerations	2
Tow test	5
Conclusions	5
References	6
Drawings	7

Illustrations and tables

Illustrations

- Figure 1. Photograph of the assembled towed vehicle, supported on a wooden stand. 3
- Figure 2. Rear view of the towed vehicle showing the quadrant cross sections formed by the radius plates. 4
- Figure 3. Photograph of the nose and forward section with a skin panel removed to reveal the large holes in the radius plates, which allow communication between the longitudinal quadrants. 4
- Figure 4. Schematic diagram of the tow test experimental configuration. 5

Table

- Table 1. Tow test results with empty vehicle. 5

Drawings

84-333-01-001	TUPS towed body envelope.	7
84-333-01-100	Nose subassembly.	9
84-333-01-101	End bracket, nose plate.	11
84-333-01-102	Nose.	13
84-333-01-200	Fuselage subassembly.	15
84-333-01-201	Radius plate.	17
84-333-01-202	Interior angle, exterior angle.	19
84-333-01-203	Skin.	21
84-333-01-300	Wing subassembly.	23
84-333-01-301	Wing.	25
84-333-01-302	Wing mounts, anchor tie.	27
84-333-01-303	Wing and stabilizer anchors, wing and stabilizer hangers.	29
84-333-01-400	Tail subassembly.	31
84-333-01-401	Vertical fin.	33
84-333-01-402	Stabilizer.	35
84-333-01-403	Fin mount.	37
84-333-01-404	Stabilizer mounts.	39

A towed instrument vehicle for deep ocean sampling

Introduction

Oceanographers began by studying general ocean basin characteristics using a few water samples and have progressed to studying smaller scale features that require greater sampling densities. Observations of various parameters with depth began with determinations of salinity and temperature using water sample bottles and reversing thermometers, which could be hung on a wire and tripped at discrete depths. The advent of devices (CTDs) for continuously measuring depth distributions of temperature and conductivity led to an increased understanding of the smaller scale vertical features. Biologists and chemists were still faced with obtaining discrete water samples to make their measurements. Submersible pumps attached to CTD units, combined with fluorometers or transmissometers, have allowed the collection of almost continuous vertical profiles for some chemical and biological parameters (e.g., chlorophyll and micronutrients).

Detailed analysis of horizontal distributions in the surface ocean, however, has been notoriously difficult due to the high data densities required to determine a coherent picture of the ocean surface. Studies of horizontal variations have often been undertaken simply by spacing hydrocast or CTD stations closely along a transect line and contouring the data between the stations. In dynamic ocean areas, however, the variability of temperature and salinity, as well as chemical and biological parameters, occurs on horizontal length scales much shorter than can be studied with standard hydrocasting techniques. A new sampling strategy was needed to obtain the sample density required to study dynamic upper ocean processes. This strategy involves use of a towed instrumented vehicle that can be operated continuously in surface waters (down to 200 m) while the towing vessel is under way at speeds of up to 12 knots. Several such systems have been constructed in the past. A few have combined in situ instrumentation with a submersible pump in the tow vehicle to pump water to the deck of the ship for onboard chemical and biological analyses. A towed instrumented pumping system is highly desirable in providing the flexibility to meet analytical needs that cannot be achieved with electronic sensors alone.

This report describes the design and testing of the towing vehicle developed by the Naval Ocean Research and Development Activity (NORDA) as part of a towed under-water pumping system (TUPS). This system will be used initially by NORDA scientists in a program to study the dynamic chemical and physical processes often observed in ocean frontal areas. The versatility of this tow vehicle will make it useful to many future research projects.

Previous tow vehicles

Before design was begun on the tow vehicle described here, several existing tow vehicle designs were evaluated with respect to our system requirements. Our design criteria demanded that the tow fish be relatively lightweight, have a large internal volume for assorted instrumentation, and have the instruments easily accessible. Special consideration was given to the need to accommodate a large-diameter tow cable required for pumping water from depth. Although many tow fish were considered, only three were evaluated in detail. Their design concepts and reason for their exclusion are presented in the following sections.

Batfish

The "Batfish" programmable towed body (manufactured by Guildline Instruments, Smith Falls, Ontario, Canada) has been used quite successfully by oceanographers at Bedford Institute of Oceanography. Herman (1977) and Herman and Denman (1977) provided excellent examples of how it can be effectively used to study near-surface chlorophyll variations. Dessureault (1976) provided a detailed description of the system and its operation.

The Batfish is 4.4 ft long and 3.1 ft high, the wing span is 4.1 ft, and weight in air is 176 lb. The body is constructed of reinforced fiberglass, stainless steel, and aluminum. Payload capability is 50 lb. The Batfish obtains downward depression from a hydraulically actuated hydroplane that is controlled by a shipboard deck unit. The Batfish is towed with an electromechanical towing cable. The tow body can be programmed to "fly" a predetermined profile or to maintain a constant depth. Cost of the Batfish is approximately \$45,000.

A major advantage of the Batfish is the ability to program it to undulate along a sawtooth pattern in a vertical plane when towed from a moving ship. The sawtooth cycle length can be as short as 0.3 km in surface waters, which makes it suitable for studying oceanographic features on the scale from 1 to 10 km.

The Batfish was excluded because it had a small payload capability and had never been configured with the large-diameter (one-inch) cable needed for a pumping system. While the ability to undulate the tow body is highly desirable, the loss of payload capability was overriding. We also desired a tow vehicle design that had been proven to work with a deep-towed pumping system. The Batfish met neither of these requirements.

Fathom Oceanology oceanographic towed fish

The oceanographic towed fish (manufactured by Fathom Oceanology Limited, Port Credit, Ontario, Canada) is a streamlined, multipurpose tow vehicle. This towed fish has been used successfully in towed pumping systems by Texaco Oil Company and later by Texas A&M University (Wiesenburg and Schink, 1978).

The Fathom towed fish is 5.0 ft long, has a 1.5 ft diameter and a weight in air (50% ballast) of 980 lb. Lead plates are used for ballast. The frame is constructed of high-strength aluminum and is covered with high-impact ABS plastic or polycarbonate shells. The Fathom fish has rear fins and stabilizers and adjustable trim tabs. Payload volume is 5.2 ft³.

The Fathom towed fish achieves downward depression from lead ballast weights bolted into the upper half of the fish. The fish, without instruments, weighs 84 lb. With the maximum 50% lead ballast, a maximum weight of 1000 lb is attained. Since the Fathom towed fish has no dynamic control, the depth of the towed fish is determined by the length of cable deployed. Cost of the Fathom towed fish is approximately \$12,000 (1980 price).

Three factors led to the exclusion of the Fathom fish for our purposes. The 1000-lb weight (without instruments) is too heavy to launch and retrieve safely at sea without a specially designed launching cradle. Our launching requirements excluded such a device. Also, the instrument payload volume was too small. Finally, the instruments on the Fathom fish are mounted in the bottom half of the fish. This configuration makes instrument access difficult without the Fathom launching cradle.

Texas A&M winged fish

An underwater tow vehicle was designed and constructed at Texas A&M University with funding from

the Office of Naval Research (Contracts N00014-75-C-0537 and N00014-80-C-0113). Their fish was used in a deep-towed pumping system to explore changes in chemical and biological properties in near-surface waters.

The Texas A&M fish is 3.9 ft long and 2.1 ft high; weight in air is 110 lb. The fish body is cylindrical (diameter of 1.0 ft) and is constructed from an aluminum pipe with internal ribs to support the tow point and a removable upper section for instrument installation. The Texas A&M fish achieves downward depression from a wing (dimensions—1.0 ft x 3.4 ft) angled at 8° to the body, which gives the fish an effective weight of 500 lb at a speed of 10 knots. The winged fish was designed with critical advice from Reece Folb and Richard Knutson of the Towed System Branch, David W. Taylor Naval Ship Research and Development Center. Setser et al. (1983) briefly describe the Texas A&M winged fish and provide examples of its utility in studying nutrient and chlorophyll variations in the Atlantic Ocean off the U.S. east coast.

For our purposes, the winged fish designed by Texas A&M University had several advantages over both the Batfish and the Fathom Oceanology tow vehicle. The dynamic depression allowed the winged fish to be much lighter and easier to handle than the Fathom tow vehicle. The payload volume of the Texas A&M fish was also larger than that of the Batfish, although it was still too small for our needs.

A major drawback to the Texas A&M fish is the difficulty in accessing the installed instrumentation. The skin of the fish (walls of the aluminum pipe) is used to provide the structural integrity of the vehicle. The instruments are also attached to the fish skin with mounting brackets. To access the lower instruments, upper instruments must be removed. Our design criteria dictated access to any instrument without having to disturb others. For this reason, as well as the small size, the Texas A&M fish design could not be used exactly. The tow vehicle that we designed employs many design concepts used in the Texas A&M fish, but incorporates several unique features that make it more flexible to use and simpler to fabricate and maintain.

TUPS fish design considerations

The TUPS vehicle design was affected by many conflicting requirements. The vehicle must be capable of tow speeds to 12 knots and depths to 200 m. The vehicle envelope should be similar to that of proven towed bodies (see previous section) and be easy to fabricate and maintain, but capable of carrying up to 20 linear feet of payload

as large as 5½ inches in diameter. It is undesirable to have to move any item of payload to gain access to another. Included in the payload are an electric motor and pump, which must have a seawater inlet near the nose and various optical sensors with special field-of-view requirements. Provision for reasonable seawater flow past other sensors in the body is also required.

The outside diameter of the fuselage is 14.25 inches with an overall length of 8 ft, 3 inches. The wingspan is 4 ft with a 16-inch chord. The rationale for the parts configuration of the vehicle will be explained in nose-to-tail order. Drawings that describe the vehicle envelope, assemblies, and details of the parts are appended. Pictures of the assembled tow vehicle are shown in Figures 1, 2, and 3.

The nose (Drawing #84-333-01-102) is made of lead in anticipation of the body being tail heavy. Although the weight and balance information for the vehicle and payload were unknown when fabrication started, we knew that the tow point would be approximately one-third of the vehicle length behind the nose, and that the tow point and the centers of buoyancy and gravity should be nearly on the same vertical line. Making the nose of lead with a weight of 80 lb will, therefore, almost surely decrease the problem of adding balance weights forward for proper trim when the vehicle is being readied for deployment. Also the pump and motor, relatively heavy payload items, will be positioned in the lower quadrant forward to help move the center of gravity forward and down. In addition, the longitudinal position of the tow point can be adjusted to aid in balancing the vehicle. The final adjust-

ment will be made by adding weights and perhaps syntactic flotation. The center hole in the nose is large enough to allow forward penetration by the pump inlet and permits flow of seawater through the vehicle.

The nose plate (Drawing #84-333-01-101) provides anchorage for the nose attachment bolts and temporary alignment support for the nose by means of a shoulder on its periphery. The end brackets (Drawing #84-333-01-101) join the nose plate to the four radius plates (Drawing #84-333-01-201) which, together with the interior and exterior angles, are the spine of the vehicle. The radius plates are symmetrical such that either end can be placed forward. The larger holes in the plates provide for communication between the longitudinal quadrants. The interior angles (Drawing #84-333-01-202) permit joining of the inner edges of the radius plates near the center line of the vehicle. They are identical but not symmetrical in the manner of the radius plates. Their orientation by pairs on the radius plates prevents interference of their mounting bolts. The exterior angles (Drawing #84-333-01-202) permit joining of the outer edges of the radius plates with the skin panels. The exterior angles are through-bolted to the radius plates but contain threaded inserts to receive the screws that fasten the skin panels. The skin panels (Drawing #84-333-01-203) are intended to be the only parts that are normally removed for service to the payload. They are fastened with hex-head screws instead of flat-head screws so that precise location of the mounting holes is not necessary. The upper quadrant is necessarily covered by two pieces of skin because of the wing mounts, but each of the other quadrants is covered with a single panel




Figure 1. Photograph of the assembled towed vehicle, supported on a wooden stand.




Figure 2. Rear view of the towed vehicle showing the quadrant cross sections formed by the radius plates.

that should not be further divided. These panels are structural members that resist longitudinal bending of the vehicle, especially near the tow point.

The wing (Drawing #84-333-01-301) is made of 1/4-inch plate and is mounted with a negative angle of attack of 8°. The leading and trailing edges are beveled on the under-

side to provide an approximately foil-shaped cross section to enhance the downward force produced. The wing tips are perforated to reduce the tip vortices, as well as to provide attachment points for taglines. The wing is attached by three bolts to each of its mounts (Drawing #84-333-01-302). The three sets of holes in the wing and three sets of holes in the mount provide for nine different positions of the wing on the body. The tow point is also attached to the wing, ideally at the same longitudinal position as the center of (downward) lift. This configuration avoids the problem of transmitting the wing forces through the body and makes trimming the vehicle easier, but there must be enough service loop in the cable and hose under the tow point to accommodate the various wing positions. The wing mounts are attached to hangers (Drawing #84-333-01-303), which are, in turn, attached to anchors (Drawing #84-333-01-303) bolted to the radius plates. The hanger and anchors on the left side are mirror images of their counterparts on the right side. If they are each rotated 180° about their vertical axes and moved to the opposite side of the body, new positions for the wing mounts are created. This effectively doubles the number of possible positions of the wing to 18. The anchors in the lower three quadrants are used to distribute the gravitational and inertial forces on the vehicle to all four radius




Figure 3. Photograph of the nose and forward section with a skin panel removed to reveal the large holes in the radius plates, which allow communication between the longitudinal quadrants.

plates. To achieve this, and to maintain the 90° angle between the radius plates, they must be connected by anchor ties (Drawing #84-333-01-302). The skin panels are curved into a pre-buckled configuration and cannot serve as rigid connectors to resist circumferential forces.

The horizontal stabilizer (Drawing #84-333-01-402) is mounted in essentially the same manner as the wing except that the anchors (Drawing #84-333-01-303), hangers (Drawing #84-333-01-303), and mounts (Drawing #84-333-01-404) are made of lighter angles and the angle of attack is zero. The vertical fin (Drawing #84-333-01-401) is joined to the stabilizer by two angles (Drawing #84-333-01-403). The longitudinal position of the vertical fin is adjustable. It is mounted below the fuselage to help orient the vehicle during launch.

Fabricating the TUPS fish from the detailed drawings was done in two parts. The fuselage (radius plates and skin panels) was manufactured and assembled by Jurisch Engineering, Slidell, Louisiana. The nose, wing, and tail subassemblies were fabricated by Cuevas Machine Shop, Perkinston, Mississippi. The tow vehicle was assembled by Mr. David C. Young of NORDA.

Tow test

The first tow test of the TUPS vehicle was conducted at the U.S. Geological Survey Test Tank at NSTL, Mississippi, in October 1984. The tank dimensions are 12 ft x 12 ft x 450 ft. The vehicle contained no internal attitude instrumentation or payload, but the tow line angle and tension were measured. The tow forces were transmitted through a 3-inch-diameter ball centered 5-1/3 inches behind the leading edge of the wing. The tow test configuration is shown schematically in Figure 4.




Figure 4. Schematic diagram of the tow test experimental configuration.

The purposes of the tow test were to determine if vehicle stability difficulties would be likely and to bracket the speed and force characteristics of the vehicle. The test results are shown in Table 1. The vehicle appeared to be extremely stable. Further tow tests were postponed until after the installation of payload.

Conclusions

The cylindrical, four-compartment, winged tow vehicle described here meets our needs for a towed research vehicle significantly better than previous designs. The vehicle is extremely stable. Each of the four separate compartments is capable of holding a 5 1/2-inch-diameter cylindrical payload. Each quadrant is individually accessible, and the flat radius plates make instrument attachment

Table 1. Tow test results with empty vehicle.

Run Number ^{a,b}	Speed (knots)	Tow Cable Angle, θ (degrees)	Load Cell Tension ^c (pounds)	Vertical Component of Load Cell Tension ^d (pounds)	Vertical Component of Hydrodynamic Forces (pounds)	Drag Force (pounds)
1	3	7	320	320	80	40
2	6	18	550	520	280	170
3	9	26	910	810	570	410
4	3	7	300	300	60	40
5	6	17	520	500	260	150
6	9	26	880	790	550	390

^aRun numbers 1-3, vehicle attitude in water at zero velocity, 10.9° nose down. Leading edge of wing 64 cm aft of skin-nose plate interface.

^bRun numbers 4-6, vehicle attitude in water at zero velocity, 2.8° nose up. Leading edge of wing 59 cm aft of skin-nose plate interface.

^cForce measurement error +10 lb, -0 lb.

^dVehicle weight in water is 240 lbs.

simple. The angled wing gives sufficient downward depression (550 lb at 9 knots) to tow at considerable depth without having to heavily ballast the vehicle. Fabrication cost of the NORDA TUPS fish (\$3200, 1984 price) is significantly less than either of the commercially available tow vehicles that were evaluated.

References


Dessureault, J. G. (1976). "Batfish": A Depth Controllable Towed Body for Collecting Oceanographic Data. *Ocean Engineering*, v. 3, pp. 99-111.

Herman, A. W. (1977). *In Situ Chlorophyll and Plankton Measurements with the Batfish Vehicle*. MTS-IEEE Oceans 77 Conference Record, v. 2, pp. 39D.



Herman, A. W. and K. L. Denman (1977). Rapid Underway Profiling of Chlorophyll with an In Situ Fluorometer Mounted on a "Batfish" Vehicle. *Deep-Sea Research*, v. 24, pp. 385-397.

Setser, P. J., N. L. Guinasso, Jr., N. L. Condra, D. A. Wiesenburg, and D. R. Schink (1983). A Deep-Towed Pumping System for Continuous Underway Sampling. *Environmental Science and Technology*, v. 17, pp. 47-49.


Wiesenburg, D. A. and D. R. Schink (1978). *Use of the Texas A&M Deep Towed Pumping System in the Gulf of Mexico Aboard the R/V GYRE during Cruise 77-G-14, 3-7 December 1984*. Report 78-4-T, Department of Oceanography, Texas A&M University, College Station, Texas, 32 pp.





NOTE
 INTERIOR DIVIDED INTO 7" RADIUS
 QUADRANTS QUARTER CIRCLE
 SKIN PANELS CAN BE REMOVED
 INDIVIDUALLY
 ADJUSTABLE POSITION OF WING
 IS ADJUSTABLE
 WING AND STABILIZER ROOTS
 PARTIALLY OBSTRUCT ADJACENT
 QUADRANTS



4	24-332-01-400 TAIL SUB-ASSEMBLY
3	24-332-01-300 WING SUB-ASSEMBLY
2	24-332-01-200 FUSELAGE SUB-ASSEMBLY
1	24-332-01-100 NOSE SUB-ASSEMBLY
END NO REFERENCE REFERENCE TITLE	
C.R. REIN NORDA	
26 APRIL 1954 TIPS	
TIPS TOWED BODY ENVELOPE	
DRAWING NO 24-333-01-201	
SCALE 1/2"=1'	






1/4 x 1/4 x 1 6061-T6 ALUM ANGLE



MAKE SIXTEEN


FULL SCALE.

2. END BRACKET




3. NOSE PLATE

WAKE ONE ALUMINUM 6061-T6
SCALE 1/2" = 1"




DIMENSIONS IN INCHES
TOLERANCES X ± 0.000
XY ± 0.015
ANGLE ± 01°

C.B. REIN	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY	
	NSTL, MISSISSIPPI 39529	
	TUPS	END BRACKET, NOSE PLATE
	84-333-01-101	



1 NOSE





DIMENSIONS IN INCHES



TOLERANCES .X ± 0.002
.14 ± 0.015
SCALE = 1"

MAKE ONE MATERIAL, LEAD
SCALE 1/2 = 1"

C.B. SEIN 1/10/60	NAVAL RESEARCH DEVELOPMENT ACTIVITY NRL MISSISSIPPI 38523	
TUPS	NCSE	
34-333-01-102		



6	1/4" X 1/4" SCREW	SSCS	25-3000 SELF LOCKING SCREW HEX HEAD	64
5	1/4" X 1/4" SCREW	SSCS	1" 1/4" HEX HEAD SCREW	80
4	1/4" X 1/4" SCREW	SSCS	1/4" X 1/4" 24-333-DI-202	4
3	RADIUS PLATE	1/4" X 1/4"	24-333-DI-201	4
2	INTERIOR ANGLE	1/4" X 1/4"	24-333-DI-200	4
1	EXTERIOR ANGLE	1/4" X 1/4"	24-333-DI-200	4
10	WAVE	MATERIAL	SSCS	REFERENCE, NOTES
NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY				
NGT, MISSISSIPPI 39529				
TYPE		FUSELAGE SUB-ASSEMBLY		
1		34-333-DI-200	1/2" X 1"	




DIMENSIONS IN INCHES


TOLERANCES D.X. ± 0.050
S.X. ± 0.015
FRACTIONS $\pm 1/64$

MATERIAL: ALUM. 6061-T6

C.R. REIN 20 JAN 68	NAVAL OCEAN RESEARCH AND DEVELOPMENT ACTIVITY	
	NSTL, MISSISSIPPI 39520	
	TUPS	RADIUS PLATE
84-333-01-201		



1 EXTERIOR ANGLE




2 INTERIOR ANGLE

DIMENSIONS IN INCHES
TOLERANCES 0X, ±0.050
0Y, ±0.015
FRKT ± 1/16

1/4 x 1/4 x 1, 6061-T6 ANGLE

CR. REM. IN. 21/24/8		NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY NSTL, MISSISSIPPI 39529	
TUPS		INTERIOR ANGLE, EXTERIOR ANGLE	
		84-333-01-202	



DIMENSIONS IN INCHES
TOLERANCES DX ± 0.060
DY ± 0.015
FRAC. $\pm 1/16$
ANGLE $\pm 0.1^\circ$




1. SKIN QUADRANT. 1/2 SCALE

MANUFACTURE SKIN QUADRANT
BLANK AS SHOWN BELOW THEN BREAK OR
ROLL TO 10" I.D. AND BREAK 1"
ALONG LONG EDGES AS SHOWN
LONG EDGES SHOULD BE FLAT ON
EXTERIOR ANGLES WHEN ASSEMBLED



C.R. REIN IN	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY	
	MSTL, MISSISSIPPI 39529	
	TUPS	SKIN
	84-333-01-203	




84-333-01-203



17	FASTEN 5 TO RADUS PLATE TO 7	1/2 x 3/8 x 1/4 L HEX HD CRES BOLTS, NUTS, LK WASHERS	2
15	FASTEN 5 TO RADUS PLATES	1/2 x 3/8 x 1/4 L HEX HD CRES BOLTS, NUTS, LK WASHERS	2
16	FASTEN 4 TO 5	1/2 x 3/8 x 1/4 L HEX HD CRES BOLTS, NUTS, LK WASHERS	2
16	FASTEN 5 TO 7	1/2 x 3/8 x 1/4 L HEX HD CRES BOLTS, NUTS, LK WASHERS	2
16	FASTEN 3 TO 7	1/2 x 3/8 x 1/4 L HEX HD CRES BOLTS, NUTS, LK WASHERS	4
16	FASTEN 2 TO 13	1/2 x 3/8 x 1/4 L HEX HD CRES BOLTS, NUTS, LK WASHERS	4
15	FASTEN 1 TO 2	1/2 x 3/8 x 1/4 L HEX HD CRES BOLTS, NUTS, LK WASHERS	6
19	84-333-01-303	RIGHT AFT WING HANGER	1
13	84-333-01-303	RIGHT FORWARD WING HANGER	1
11	84-333-01-303	LEFT AFT WING HANGER	1
10	84-333-01-303	LEFT FORWARD WING HANGER	1
7	84-333-01-303	RIGHT WING ANCHOR	6
5	84-333-01-303	LEFT WING ANCHOR	6
4	84-333-01-302	ANCHOR TIE	4
3	84-333-01-302	LEFT WING MOUNT	1
2	84-333-01-302	RIGHT WING MOUNT	1
1	84-333-01-301	HING	1
ITEM REFERENCE & NOTES			2/11



C.R.REIN	NAVAL OCEAN RESEARCH & DEVELOPMENT ACT. 7		
	NSTL, MISSISSIPPI 33529		
	TUPS WING SUB-ASSEMBLY		
	84-333-01-300		
	A=1"		




MAKE ONE
ALUM. 6061-T6

DIMENSIONS IN INCHES


TOLEANCES
DIA. = 0.005
HOLE = 0.005
FILL = 0.005
ANGLE = 0.005

G.R. REIN.	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY	
	NSTL, MISSISSIPPI 38520	
	TUPS	WING
	84-333-01-301	




3"x3"x1/2" ANGLE SHOWN

5. MAKE SIX 3"x3"x1/2" ANGLE ALUM 6061-T6
6. MAKE TWO 3"x3"x1/4" ANGLE ALUM 6061-T6




5. LEFT WING ANCHOR
6. RIGHT TAIL ANCHOR




9. MAKE TWO; X=6.0, Y=0.85 3"x3"x1/4" ANGLE ALUM 6061-T6
10. MAKE ONE; X=6.4, Y=1.25 3"x3"x1/2" " " "
11. MAKE ONE; X=7.5, Y=2.75 3"x3"x1/2" " " "

3"x3"x1/2" ANGLE SHOWN




9. RIGHT TAIL HANGER
10. LEFT FORWARD WING HANGER
11. LEFT AFT WING HANGER




3"x3"x1/4" ANGLE SHOWN

7. MAKE SIX 3"x3"x1/4" ANGLE
8. MAKE TWO 3"x3"x1/4" ANGLE
ALUM 6061-T6




7. RIGHT WING ANCHOR
8. LEFT TAIL ANCHOR




3"x3"x1/2" ANGLE SHOWN

12. MAKE TWO; X=6.0, Y=0.85 3"x3"x1/4" ANGLE
13. MAKE ONE; X=6.4, Y=1.25 3"x3"x1/2" ANGLE
14. MAKE ONE; X=7.5, Y=2.75 3"x3"x1/2" ANGLE
MATERIAL ALUM 6061-T6




12. LEFT TAIL HANGER
13. RIGHT FORWARD WING HANGER
14. RIGHT AFT WING HANGER

DIMENSIONS IN INCHES	
TOLERANCES	0.X ± 0.050
	0.XX ± 0.015
	FRACT. = 1/16"
	ANGLE, 1/2"
SCALE 1"=1"	
C. R. REIN COMAR 1984	
NAVAL OCEAN RESEARCH AND DEVELOPMENT ACTIVITY	
XSTL MISSISSIPPI 39520	
WING, STABILIZER ANCHORS AND HANGERS	
84-333-01-303	




12	FASTEN 5/8-10 PRIME BOLT, 1/2-1/2 HEX HD CRES BOLTS, NUTS, LK WASHERS	2
11	FASTEN 5/8-10 IDP, 1/2-1/2 IDP, 1/2-1/2 HD HD CRES EXTS, NUTS, LK WASHERS	2
13	FASTEN 5/8-10 IDP, 1/2-1/2 IDP, 1/2-1/2 HD HD CRES BOLTS, NUTS, LK WASHERS	2
12	51-333-01-303 LEFT TAIL HANGER	2
11	FASTEN 2 1/2-303, 1/2-303, 1/2-303 HD HD CRES BOLTS, NUTS, LK WASHERS	4
10	FASTEN 2 1/2-303, 1/2-303, 1/2-303 HD HD CRES BOLTS, NUTS, LK WASHERS	4
9	51-333-01-303 RIGHT TAIL HANGER	2
8	51-333-01-303 LEFT TAIL HANGER	2
7	FASTEN 2 1/2-303, 1/2-303, 1/2-303 HD HD CRES BOLTS, NUTS, LK WASHERS	3
6	51-333-01-303 RIGHT TAIL ANCHOR	2
5	51-333-01-404 RIGHT STABILIZER MOUNT	1
4	51-333-01-404 LEFT STABILIZER MOUNT	1
3	51-333-01-903 FIN MOUNT	2
2	51-333-01-402 STABILIZER	2
1	51-333-01-401 VERTICAL FIN	2
ITEM REFERENCE AND NOTES		

G.B.B.EIN	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY	
	HSTL, MISSISSIPPI 33529	
	TUPS	TAIL SUB-ASSEMBLY
	84-333-01-400	



31




MAKE ONE
ALUMINUM 6061-T6


1_VERTICAL FIN

DIMENSIONS IN INCHES
TOLERANCES D.X. ± 0.050
D.X. ± 0.015
FRCT. = 1/64
ANGLE $\pm 1/2^\circ$

C.R.REIN	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY	
	NSTL, MISSISSIPPI 39529	
	TUPS	VERTICAL FIN
	84-333-01-401	
	2" = 1"	




2. STABILIZER



DIMENSIONS IN INCHES
TOLERANCES 0.1 ± 0.005
HOLE ± 0.015
FRAC $\pm 1/16$
ANGLE $\pm 1/2^\circ$

G. R. REIN 5 APRIL 84	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY NSTL, MISSISSIPPI 39529	
	TUPS	STABILIZER
	84-333-01-402	
	1/2" = 1"	




MAKE TWO
2"x2"x1/4" ANGLE
ALUM 6061-T6


DIMENSIONS IN INCHES
TOLERANCES $0.X \pm 0.050$
 $0.XX \pm 0.015$
FRACT. $\pm 1/64$

3. FIN MOUNT



C. R. REIN 4 APRIL '84	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY NSTL, MISSISSIPPI 38529	
	TUPS	FIN MOUNT
	84-333-01-103	
	1" = 1"	




MAKE ONE
2"x2"x1/4" ANGLE
ALUM. 6061-T6




4 LEFT STABILIZER MOUNT



MAKE ONE
2"x2"x1/4" ANGLE
ALUM. 6061-T6



5 RIGHT STABILIZER MOUNT



DIMENSIONS IN INCHES
TOLERANCES DX ±0.050
DX ±0.015
FRACT. ±1/64

C.R. REIN 4 APRIL 81	NAVAL OCEAN RESEARCH & DEVELOPMENT ACTIVITY	
	N6TL, MISSISSIPPI 39529	
	TUPS	STABILIZER MOUNTS
	84-333-01-101	
1-1		

Distribution List

Department of the Navy
Asst Secretary of the Navy
(Research Engineering & System)
Washington DC 20350

Commanding Officer
Naval Ocean R & D Activity
ATTN: Codes 100/111/112
NSTL MS 39529

Department of the Navy
Chief of Naval Operations
ATTN: OP-951
Washington DC 20350

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 113
NSTL MS 39529

Department of the Navy
Chief of Naval Operations
ATTN: OP-952
Washington DC 20350

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 125L
NSTL MS 39529

Department of the Navy
Chief of Naval Operations
ATTN: OP-987
Washington DC 20350

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 125ED
NSTL MS 39529

Department of the Navy
Chief of Naval Material
Washington DC 20360

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 110
NSTL MS 39529

Commander
Naval Air Development Center
Warminster PA 18974

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 105
NSTL MS 39529

Commander
Naval Air Systems Command
Headquarters
Washington DC 20361

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 115
NSTL MS 39529

Commanding Officer
Naval Coastal Systems Center
Panama City FL 32407

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 200
NSTL MS 39529

Commander
Naval Electronic Systems Com
Headquarters
Washington DC 20360

Commanding Officer
Naval Ocean R & D Activity
ATTN: Code 300
NSTL MS 39529

Commanding Officer
Naval Environmental Prediction
Research Facility
Monterey CA 93940

Commanding Officer
Naval Research Laboratory
Washington DC 20375

Commander
Naval Facilities Eng Command
Headquarters
200 Stovall Street
Alexandria VA 22332

Commander
Naval Oceanography Command
NSTL MS 39529

Commanding Officer
Fleet Numerical Ocean Cen
Monterey CA 93940

Commanding Officer
Naval Oceanographic Office
NSTL MS 39522

Commander
Naval Ocean Systems Center
San Diego CA 92152

Commanding Officer
ONR Branch Office LONDON
Box 39
FPO New York 09510

Officer in Charge
Office of Naval Research
Detachment, Pasadena
1030 E. Green Street
Pasadena CA 91106

Commander
Naval Sea System Command
Headquarters
Washington DC 20362

Commander
D W Taylor Naval Ship R & D Cen
Bethesda MD 20084

Commander
Naval Surface Weapons Center
Dahlgren VA 22448

Commanding Officer
Naval Underwater Systems Center
ATTN: NEW LONDON LAB
Newport RI 02841

Superintendent
Naval Postgraduate School
Monterey CA 93940

Project Manager
Chief of Naval Material
Department of the Navy
Washington DC 20360

Department of the Navy
Deputy Chief of Naval Material
for Laboratories
Rm 866 Crystal Plaza Five
Washington DC 20360

Officer in Charge
Naval Underwater Sys Gen Det
New London Laboratory
New London CT 06320

Defense Technical Info Cen
Cameron Station
Alexandria VA 22314

Director
Chief of Naval Research
ONR Code 420
NSTL MS 39529

Director, Liaison Office
Naval Ocean R & D Activity
800 N. Quincy Street
Ballston Tower #1
Arlington VA 22217

Department of the Navy
Office of Naval Research
ATTN: Code 102
800 N. Quincy Street
Arlington VA 22217

Director
Woods Hole Oceanographic Inst
86-96 Water St.
Woods Hole MA 02543

Director
University of California
Scripps Institute of Oceanography
P. O. Box 6049
San Diego CA 92106

Working Collection
Texas A & M University
Department of Oceanography
College Station TX 77843

U218736