



MICROCOPY RESOLUTION TEST CHART NATIONAL BUREAU OF STANDARDS-1963-A

AAMRL-TR-85-049

.

PROGRAMMING A MULTIPLE-ORIFICE HYDRAULIC DECELERATOR

CARL G. TOLER

AD-A159 428

JUNE 1985

FILE COPY

310

Approved for public release; distribution unlimited.

HARRY G. ARMSTRONG AEROSPACE MEDICAL RESEARCH LABORATORY AEROSPACE MEDICAL DIVISION AIR FORCE SYSTEMS COMMAND WRIGHT-PATTERSON AIR FORCE BASE, OHIO 45433

SEP 3 0 1985



•

.

ROTICES

When US Generations, denotings, specifications, or other data are used for any purpose other than a definitely related flowingsent precuritional operation, the Government thereby incurs no responsibility nor any objective produces and the fact that the Government may have formulated, furnished, or in any user administ the self drawings, specifications, or other data, is not to be regarded by implication or observing discussion to manufacture, use, or self any patented investion that may in any way be related thereto.

Please do not request copies of this report from Air Force Asrospace Medical Research Laboratory. Additional copies may be purchased from:

> National Technical Information Service 5285 Port Royal Road Springfield, Virginia 22161

Federal Government agencies and their contractors registered with Defense Technical Information Center should direct requests for copies of this report to:

> Defense Technical Information Center Cameron Station Alexandria, Virginia 22314

TECHNICAL REVIEW AND APPROVAL

AAMR1-TR-85-049

This report has been reviewed by the Office of Public Affairs (PA) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication.

FOR THE COMMANDER

Hennin E. von Gie ha

HENNINGE. WON GIERKE, Dr Ing Director Biodynamics and Bioengineering Division Air Force Aerospace Medical Research Laboratory

	REPORT DOCUME	ENTATION PAG	E		
18 REPORT SECURITY CLASSIFICATION		15. RESTRICTIVE N	ARKINGS		
2 SECURITY CLASSIFICATION AUTHORITY	·	3. DISTRIBUTION	VAILABILITY O	FREPORT	··· ···
		Approved	for public	release; di	stributi
20. DECLASSIFICATION/DOWNGRADING SCHE	DULE	unlimited	•		
4. PERFORMING ORGANIZATION REPORT NUM	MBER (\$)	5. MONITORING OF	GANIZATION R	EPORT NUMBER	b) _
AAMRL-TR-85-049			TOBING OBCAN	247100	
Harry G. Armstrong Aerospace	(<i>if applicable</i>)	A. TOME OF MONI	I UNING UNGAN		
Medical Research Laboratory	AAMRL/BBP				
Sc. ADDRESS (City, State and ZIP Code)		7b. ADDRESS (City,	State and ZIP Cod	le)	
Wright-Patterson Air Force Bas	e OH 45433-6573				
S. NAME OF FUNDING/SPONSORING	B. OFFICE SYMBOL	9. PROCUREMENT	INSTRUMENT ID	ENTIFICATION N	UMBER
Protection Branch					
RE ADDRESS (City State and 71P Code)	I MARKL/DDP	10. SOURCE OF FU			
		PROGRAM	PROJECT	TASK	WORK
Wright-Patterson Air Force Bas	e OH 45433-6573	ELEMENT NO.	NO.	NO.	NO
11. TITLE (Include Security Clamification) Droom	amming A	622025	7931	21	
Multiple-Orifice Hydraulic Dec	elerator (11)		1231		
12. PERSONAL AUTHOR(S)		<u> </u>	••••••••••••••••••••••••••••••••••••••		
Mu Caul O Talau					
<u>mr. Carl_G. Ioler</u>					
Mr. Carl G. Joler 13a TYPE OF REPORT	COVERED	14. DATE OF REPO	RT (Yr., Mo., Dey) 15. PAGE (OUNT
Mr. Lari G. Joier 13. Type of Report 13. Time 1 Fina] FROM Ma 16. SUPPLEMENTARY NOTATION	соvered <u>r 78 </u> то <u>Feb 85</u>	14. DATE OF REPO June 1985	RT (Yr., Mo., Dey) 15. PAGE 30	:OUNT
Mr. Carl G. IOTEr 13a TYPE OF REPORT 13b TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES	сочелер <u>r 78</u> то <u>Feb 85</u> Тів. subject телмя (с	14. DATE OF REPO June 1985	RT (Yr., Mo., Day	(/y by block numbe	20UNT
Mr. Lari G. Joier 13a Type of Report 13b. TIME Fina] FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR.	covered <u>r 78</u> то <u>Feb 85</u> 18. subject тенмя (с Biodynamic Impact	14. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test	eccentry and ident ulic Decele Facility	15. PAGE 30 30	
Mr. Lari G. Joier 13a. Type of Report 13b. TIME Fina] From Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR.	covered <u>r 78 то Feb 85</u> is.subject термя (c Biodynamic Impact	14. DATE OF REPO June 1985 Continue on reverse I/ n S Hydra Test	RT (Yr., Mo., Day eccessory and ident ulic Decele Facility	15. PAGE (30 30 (/y by block number ator	7)
MT. Lari G. Joier 13. TYPE OF REPORT 13. TYPE OF REPORT 13. TIME Fina] FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary of The AAMRL Horizontal Deceleration)	covered <u>r 78</u> то <u>Feb 85</u> 18. SUBJECT ТЕРМЯ (C Biodynamic Impact nd identify by block numbe tion Facility is	14. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test	ecomory and identi ulic Decele Facility uct experim	15. PAGE (30 17y by block number ator	r)
MT. Lari G. Joler 13a. TYPE OF REPORT 13b. TIME Fina] FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ASSTRACT (Continue on reverse if necessary ar The AAMRL Horizontal Decelerat the development of design critical	COVERED <u>r 78</u> to <u>Feb 85</u> 18. SUBJECT TERMS (C Biodynamic Impact Impact identify by block numbe tion Facility is teria for aircre	14. DATE OF REPO June 1985 Continue on reverse if n 's Hydra Test '' used to cond w personnel p	eccessory and ident ulic Decele Facility uct experim rotection.	(/y by block number erator ental resea The hydrau	rch for
MT. Lari G. Joler 13a. TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary or The AAMRL Horizontal Decelerat the development of design critication	COVERED <u>r 78 to Feb 85</u> 18. SUBJECT TERMS (C Biodynamic Impact Impact Ind identify by block number tion Facility is teria for aircrein r-filled cylinder	14. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test "used to conde w personnel p r. A piston i	ecomery and ident ulic Decele Facility uct experim rotection. mounted on	15. PAGE (30 30 17 by block number erator ental resea The hydrau the front o	rch for f a
MT. Lari G. JOIEr 13a. TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary ar The AAMRL Horizontal Decelerat the development of design critication device is a water deceleration sled ruptures a	COVERED <u>r 78 to Feb 85</u> 18. SUBJECT TERMS (C Biodynamic Impact Impact identify by block number tion Facility is teria for aircref r-filled cylinder frangible diaphr	It. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test "used to conde w personnel p r. A piston i agm positione	economy and identi ulic Decele Facility uct experim rotection. mounted on d at the op	(15. PAGE 30 30 (17) by block number erator ental resea The hydrau the front o ening of th	rch for lic f a e
MT. Carl G. JOIET 13a TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water of the development of design critical deceleration sled ruptures a cylinder and displaces the water of the development of design critical deceleration sled ruptures a cylinder and displaces the water of the development of the cylinder and displaces the water of the cylinder and displaces the cylinder and	COVERED <u>r 78</u> to Feb 85 18. SUBJECT TERMS (C Biodynamic Impact Impact 16 identify by block number tion Facility is teria for aircrear r-filled cylinder frangible diaphr ter in the cylin	14. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test "used to conde w personnel p r. A piston i agm positione der through t	eccentry and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple	is page 30 30 1/y by block number ator ental resea The hydrau the front o ening of th orifices.	"" rch for lic f a e As the
MT. Lari G. Joler 13a TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water state of the ustor the u	COVERED <u>r 78</u> to Feb 85 18. SUBJECT TERMS (C Biodynamic Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact I	2000 1985 2000 1985	econory and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby	is page 30 if y by block number rator pental resea The hydrau the front o ening of th orifices. decreasing	rch for lic f a e As the the
MT. Lari G. IOTET 13a. TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary are the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water are the development of the state of the water applied to the physical state	COVERED <u>r 78 to Feb 85</u> 18. SUBJECT TERMS (C Biodynamic Impact Impact Indidentify by block number tion Facility is teria for aircred r-filled cylinder frangible diaphr ter in the cylin nder it closes o to escape. Berny of fluid flow fil	24. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test "used to conde w personnel p r. A piston i agm positione der through t ff the orific oulli's conset n the cylinde	ecomery and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby rvation-of-	is page 30 30 if y by block number ator ental resea The hydrau the front o ening of the orifices. decreasing energy equa	rch for lic f a e As the the
Mr. Carl G. Joler 13a TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary are the development of design crist deceleration device is a water deceleration sled ruptures a cylinder and displaces the wat piston travels along the cylination are the water applied to the physical state to be determined as a function	COVERED <u>r 78 to Feb 85</u> 18. SUBJECT TERMS (C Biodynamic Impact 19. Identify by block number tion Facility is teria for aircref r-filled cylinder frangible diaphr ter in the cylin nder it closes o to escape. Berny of fluid flow in n of the piston	It. DATE OF REPO June 1985 Continue on reverse if n is Hydra Test "used to conde w personnel p r. A piston i agm positione der through t ff the orific oulli's consen n the cylinder cross-section	ar (Yr. Mo. Dey convery and identi- ulic Decele Facility uct experime rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area. ar	is page 30 if y by block number rator ental resea The hydrau the front o ening of the orifices. decreasing energy equa the orific celeration	" rch for lic f a e As the the tion was e area
Mr. Carl G. Joler 13a TYPE OF REPORT 13b. TIME Fina] FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the slipering state	COVERED <u>r 78 to Feb 85</u> 18. SUBJECT TERMS (C Biodynamic Impact Impact 16 identify by block number tion Facility is teria for aircrea r-filled cylinder frangible diaphr ter in the cylin nder it closes o to escape. Bernin of fluid flow i n of the piston ed. A computer	in the cylinder in the	eccentry and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to	is page 30 15 page 30 16 page 17 by block number erator the front of the front of ening of the orifices. decreasing energy equa the orific celeration, determine	rch for lic f a e As the the tion was e area
Mr. Carl G. JOIEr 13a TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary as The AAMRL Horizontal Deceleration device is a water deceleration device is a water deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the slaappropriate plug orifice and	COVERED <u>r 78 to Feb 85</u> <u>18. SUBJECT TERMS (C</u> Biodynamic Impact <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impa</u>	in the cylinder for the cylinder continue on reverse if n is Hydra Test "used to cond w personnel p r. A piston i agm positione der through the ff the orific oulli's conset n the cylinder cross-section program was d uce desired ag	eccentry and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration	is page 30 1/y by block number ental resea The hydrau the front o ening of th orifices. decreasing energy equa the orific celeration, determine -time profi	rch for lic f a As the the tion was e area the les.
Mr. Lari G. Joler 13a TYPE OF REPORT 13b. TIME Final FROM Ma 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the sl appropriate plug orifice and The program corrects for the comparison the cylinder of the sl appropriate plug orifice and the physical state comparison the cylinder of the sl appropriate plug orifice and the program corrects for the comparison the cylinder of the sl appropriate plug orifice and the program corrects for the cylinder of the sl appropriate plug orifice and the program corrects for the cylinder of the sl appropriate plug orifice and the program corrects for the cylinder of the sl appropriate plug orifice and the program corrects for the cylinder of the sl appropriate plug orifice and the program corrects for the cylinder of the sl appropriate plug orifice and the plug orifice and the program corrects for the cylinder of the sl approprime cylinder	COVERED <u>r 78</u> to Feb 85 18. SUBJECT TERMS (C Biodynamic Impact Impact refiled cylinder frangible diaphr ter in the cylin nder it closes o to escape. Berne of fluid flow i n of the piston ed. A computer location to prod energy loss due	2. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test "used to conde w personnel p r. A piston i agm positioned der through t ff the orific oulli's conset n the cylinded cross-section program was de uce desired ac to the vena-ce	eccentry and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of	is page 30 1/y by block number erator pental resea The hydrau the front o ening of th orifices. decreasing energy equa the orific celeration, determine -time profi each plug.	rch for lic f a As the the tion was e area the les. Data
MT. Lari G. IOTET 13a TYPE OF REPORT 13b. TIME Final 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary of The AAMRL Horizontal Decelerat the development of design critic deceleration device is a water deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the sl appropriate plug orifice and The program corrects for the from several tests were used	COVERED <u>r 78 to Feb 85</u> <u>is subject terms (C</u> Biodynamic Impact <u>ind identify by block number</u> tion Facility is teria for aircret r-filled cylinder frangible diaphr ter in the cylin nder it closes of to escape. Bernin of fluid flow if n of the piston ed. A computer location to prod energy loss due to determine a co	It. DATE OF REPO June 1985 Continue on reverse if n s Hydra Test "used to conde w personnel per r. A piston i agm positione der through the ff the orifice oulli's consen n the cylinder cross-section program was de uce desired ac to the <u>vena-ce</u> orrection coe	area, ac events and identive active experime rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of fficient fo	is page 30 30 if y by block number ator ental resea The hydrau the front o ening of th orifices. decreasing energy equa the orific celeration, determine -time profi each plug. r other los	rch for lic f a e As the tion was e area the les. Data ses,
MT. Lari G. IOTET 13a TYPE OF REPORT 13b. TIME Final 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP 19. ABSTRACT (Continue on reverse if necessary at the development of design critic deceleration device is a water deceleration sled ruptures a cylinder and displaces the wat piston travels along the cylinder and displaces the wat piston travels along the cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the sl appropriate plug orifice and The program corrects for the from several tests were used such as those attributable to	COVERED <u>r 78</u> to Feb 85 Biodynamic Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact Impact	In the cylinder for the cylinder or the cylinder or the cylinder or the cylinder or the cylinder or the cylinder cross-section program was du uce desired at to the vena-co orrection coer and surface re	ar (Yr. Mo. Dey cornery and identi- ulic Decele Facility uct experime rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of fficient fo pughness. a	is page 30 if y by block number ator ental resea The hydrau the front o ening of th orifices. decreasing energy equa the orific celeration, determine -time profi each plug. r other los s a lumped	rch for lic f a e As the the tion was e area the les. Data ses, quantity
MT. Lari G. IDIET 13a TYPE OF REPORT 13b. TIME Final 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the sl appropriate plug orifice and The program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the program corrects for the of the sl appropriate plug orifice and the plug orifice and the program corrects for the of the sl appropriate plug orifice and the	Is. SUBJECT TERMS (C Biodynamic Impact Impact Impact Impact Indidentify by block numbe tion Facility is teria for aircre r-filled cylinde frangible diaphr ter in the cylin nder it closes o to escape. Berny of fluid flow i n of the piston ed. A computer location to prod energy loss due to determine a cu conduit length	It. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test "used to conde w personnel p r. A piston i agm positioned der through t ff the orific oulli's conse n the cylinder cross-section program was d uce desired at to the <u>vena-cc</u> orrection coe and <u>surface re</u>	eccessory and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of fficient fo <u>bughness.</u> a URITY CLASSIFI	is page 30 if y by block number rator pental resea The hydrau the front o ening of the orifices. decreasing energy equa the orific celeration, determine -time profi each plug. r other los s a lumped CATION	rch for lic f a e As the tion was e area the les. Data ses, quantity
MT. Lari G. IDIET 13a TYPE OF REPORT 13b. TIME Final 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the wat piston travels along the cylinavailable area for the water applied to the physical state to be determined as a function velocity and weight of the slippropriate plug orifice and The program corrects for the from several tests were used such as those attributable to 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT (CONTINUED)	Is. SUBJECT TERMS (C Biodynamic Impact Impact Impact Impact Impact Impact Impact Impact Impact Ind identify by block numbe tion Facility is teria for aircre r-filled cylinde frangible diaphr ter in the cylin nder it closes o to escape. Berne of fluid flow i n of the piston ed. A computer location to prod energy loss due to determine a co conduit length Impact	in the cylinder for the cylinder or the cylinder or the cylinder or the cylinder or the cylinder or the cylinder cross-section program was do uce desired and to the <u>vena-cc</u> or the <u>vena-cc</u> or corection coe and <u>surface re</u> Unclassifi	eccentry and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of fficient fo oughness. a UNITY CLASSIFI ed	Is page 30 15 page 30 17 by block number Part or Part	rch for lic f a e As the tion was e area the les. Data ses, quantity
MT. Lari G. IOTET 13a TYPE OF REPORT 13b. TIME Final 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP 19. ABSTRACT (Continue on reverse if recemery at the development of design critication device is a water deceleration device is a water deceleration sled ruptures a cylinder and displaces the wat piston travels along the cylination area for the water applied to the physical state to be determined as a function velocity and weight of the slip appropriate plug orifice and The program corrects for the from several tests were used such as those attributable to 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT (CONSIDEL INDIVIDUAL	COVERED <u>r 78</u> <u>to</u> <u>Feb 85</u> <u>Biodynamic</u> <u>Biodynamic</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impact</u> <u>Impac</u>	It. DATE OF REPO June 1985 Continue on reverse if n S Hydra Test "used to conde w personnel p r. A piston i agm positione der through ti ff the orific oulli's conset n the cylinde cross-section program was d uce desired at to the <u>vena-cc</u> orrection coe and <u>surface re</u> 21. ABSTRACT SEC Unclassifi	AT (Yr. Mo. Dey correctly and identi- ulic Decele Facility uct experime rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of fficient fo oughness. a URITY CLASSIFI ed UMBER ode?	is page 30 if y by block number rator ental resea The hydrau the front o ening of th orifices. decreasing energy equa the orific celeration, determine -time profi each plug. r other los <u>s a lumped</u> CATION	rch for lic f a e As the tion was e area the les. Data ses, guantity
MT. Lari G. IDIET 13a. TYPE OF REPORT 13b. TIME Final 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the slippropriate plug orifice and The program corrects for the of the slippropriate plug orifice and the program corrects for the cylipsuch as those attributable to 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT (Continue on reverse Structure) 19. ABSTRACT (Continue on reverse if necessary and the development of design critical state to deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the slippropriate plug orifice and The program corrects for the of from several tests were used such as those attributable to 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT (Continue on corrects for the from several for the cylip on the cyl	COVERED <u>r 78</u> <u>to</u> <u>Feb 85</u> lia. SUBJECT TERMS (C Biodynamic Impact Impact r filled cylinder frangible diaphr ter in the cylin nder it closes o to escape. Berne of fluid flow i n of the piston ed. A computer location to prod energy loss due to determine a cu <u>conduit length</u> E otic USERS □	14. DATE OF REPO June 1985 Continue on reverse if n is Hydra Test "used to conde w personnel p r. A piston i agm positione der through t ff the orific oulli's conset n the cylinder cross-section program was de uce desired as to the <u>vena-cc</u> orrection coe and <u>surface re</u> 21. ABSTRACT SEC Unclassifi 22b. TELEPHONE N. (Jnclude Area C. (513) 255-31	eccessery and ident ulic Decele Facility uct experim rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of fficient fo oughness. a UNITY CLASSIFI ed	15. PAGE 30 17. by block number Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prator Prat	rch for lic f a e As the tion was e area the les. Data ses, quantity
MT. Lari G. IDIET 13a. TYPE OF REPORT 13b. TIME Final 16. SUPPLEMENTARY NOTATION 17. COSATI CODES FIELD GROUP SUB. GR. 19. ABSTRACT (Continue on reverse if necessary and the development of design critical deceleration device is a water deceleration sled ruptures a cylinder and displaces the water applied to the physical state to be determined as a function velocity and weight of the sl appropriate plug orifice and The program corrects for the of from several tests were used such as those attributable to 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT (Continue on reverse for the form several tests were used such as those attributable to 22a. NAME OF RESPONSIBLE INDIVIDUAL Mr. Carl G. TOLER	COVERED <u>r 78</u> to Feb 85 18. SUBJECT TERMS (C Biodynamic Impact Impact Impact Impact Indidentify by block number tion Facility is teria for aircred frangible diaphr ter in the cylinder frangible diaphr ter in the cylinder in the cylinder frangible diaphr ter in the cylinder for fluid flow in n of the piston ed. A computer location to prod energy loss due to determine a cu conduit length NOT EDITION OF 1 JAN 73	14. DATE OF REPO June 1985 Continue on reverse if n 's Hydra Test 'used to conde w personnel pi r. A piston i agm positione der through the ff the orific oulli's consen n the cylinder cross-section program was de uce desired at to the <u>vena-cc</u> orrection coe and <u>surface re</u> 21. ABSTRACT SEC Unclassifi 22b. TELEPHONEN (Include Ared Cl (513) 255-31 IS OBSOLETE.	AT (Yr. Mo. Dey convery and identi- ulic Decele Facility uct experime rotection. mounted on d at the op he multiple es thereby rvation-of- r, allowing al area, ac eveloped to cceleration ontracta of fficient for outputs and UNBER ode; 23 UNCL	15. PAGE (30 17. by block number erator mental resea The hydrau the front o ening of th orifices. decreasing energy equa the orific celeration, determine -time profi each plug. r other los <u>s a lumped</u> CATION 22c. OFFICE SYN AAMRL/BBP ASSIFIED	rch for lic f a e As the tion was e area the les. Data ses, quantity

and the second state of the se

PREFACE

This report was prepared by the Biomechanical Protection Branch, Biodynamics & Bioengineering Division of the Harry G. Armstrong Aerospace Medical Research Laboratory. This report describes a hydraulic deceleration device, the physical laws governing its operation, and presents an accurate method of determining the correct orifice arrangement to produce desired acceleration-time profiles.

The author wishes to acknowledge the personnel of the Dynalectron Corporation for their support in developing the computer program to produce the desired hydraulic decelerator profile and for the electronic data used in the analysis. The author is grateful to Capt Michael P. Connors and Mr. James W. Brinkley for their technical assistance and guidance in this developmental program. Special thanks is offered to Mrs. Jeni Blake for her administrative support in the preparation of this documentation.

	Accesion for	ļ
	NTIS CRA&I	
	By Drit ib, tion/	
	Availability Codes	
•31c	Dist Avail and/or Special	
and a start	A-1	

a structure in the second of the second of

TABLE OF CONTENTS

ない

		Page No.
	PREFACE TABLE OF CONTENTS LIST OF FIGURES LIST OF TABLES	111 1v V V
1	INTRODUCTION	1
2	MATERIALS AND METHODS	3
	A. Facility B. Physical Phenomenon C. Solution	3 3 8
3	DISCUSSION	13
	APPENDIX A	14
	REFERENCES	24

LIST OF FIGURES

FIGUR	Ε	PAGE NO.
1	HORIZONTAL DECELERATION FACILITY	2
2	HYDRAULIC DECELERATION DEVICE	4
3	SIDE SECTIONAL VIEW AND END VIEW OF THE HYDRAULIC DECELERATION DEVICE	5
4	ACCELERATION AND VELOCITY VERSUS DISPLACEMENT FOR TEST 1441	9
5	ACTUAL VERSUS THEORETICAL ORIFICE AREA	11
6	ACTUAL AND THEORETICAL ACCELERATION PROFILE FOR TEST 2040	12

TABLE

The states the second second

1111111

LIST OF TABLES

PAGE NO.

7

1 CONTRACTION COEFFICIENT VERSUS AREA RATIO

INTRODUCTION

The mission of the Biomechanical Protection Branch includes development of design criteria for crew protection against transient acceleration and measurement of the interaction between the dynamic response of the human body and protection systems during acceleration. This technology is acquired for application to the design of crew safety systems such as: emergency escape systems, personnel restraint devices, and impact attenuators. One of the facilities used by the Branch to accomplish this mission is the Horizontal Deceleration Facility.

The Horizontal Deceleration Facility is an impact test facility that consists of a launch system, a two-rail track, a sled, and a hydraulic deceleration device. The facility is shown in Figure 1. The launch system is used to gradually accelerate the sled along the horizontal track. The specimen to be tested is mounted on top of the sled. After separation from the launching system, the sled is allowed to free coast along the track for 125 feet. During the free-coast phase the sled velocity may be controlled by means of braking devices mounted on the sled. The primary impact environment is produced at the end of the free-coast phase by the hydraulic deceleration device (Kilian and Brown, 1980).

The hydraulic deceleration device was designed to provide an impact acceleration-time profile which can be altered to meet the requirements of different research programs. Acceleration-time profiles are produced by the resisting force on the end of a piston mounted on the front of the sled. During the impact event the piston displaces water through the orifices arranged in a spiral pattern along the cylinder of the hydraulic deceleration device. The sizes of the orifices can be changed to control the acceleration-time profile. Changing the configuration of the hydraulic deceleration device for different acceleration profiles has proved to be time consuming and expensive due to the amount of trial and error associated with the current method of configuring the device. The same method was used to configure the Daisy Decelerator (Chandler, 1967). Several tests are usually required before the desired acceleration-time profile is obtained. Therefore, the objective of this study was to develop a more accurate and efficient means of establishing correct orifice configurations for the hydraulic deceleration device.

MATERIALS AND METHODS

FACILITY

The hydraulic deceleration device, shown in Figure 2, consists of a waterfilled cylinder, a reservoir which surrounds the cylinder, and structural members to transmit forces to a reaction mass. The cylinder is constructed of a series of seven blocks, 8 inches in length. The blocks are bored to mate with a five-foot long piston that is mounted on the front of an impact sled. The piston is seven inches in diameter with 0.010 inch radial clearance in the cylinder. Each block has a series of 33 threaded 1 1/8 inch-diameter holes to receive plugs with orifice areas ranging from 0.010 to 0.994 in². The spacing between the centers of consecutive plugs is 0.187 inch along the longitudinal axis to create a spiral arrangement of the orifices along the cylinder. Larger transition plugs are mounted between each block with orifice areas ranging from 0.161 to 3.976 in².

Before each test a frangible diaphragm constructed of polyethylene film is fixed to the opening of the cylinder and the hydraulic deceleration device is filled with water. As the sled approaches the hydraulic deceleration device, the piston ruptures the diaphragm and forces the water out through the orifices. The orifices act as throttling valves restricting the flow, thereby creating a back pressure on the face of the piston. The pressure on the face of the piston decelerates the sled. Since the orifices are arranged in a spiral pattern along the cyliner, the sled acceleration can be programmed as a function of displacement along the hydraulic deceleration device.

PHYSICAL PHENOMENON

The action of the piston in the cylinder is much like a piston pump. The force applied to the piston is from the momentum of the sled. As the piston travels along the bore of the cylinder, the orifices are closed off. Thus, the orifice area available for the water to flow is continuously decreased. Figure 3 shows side and end views of the hydraulic deceleration device illustrating the arrangement of the orifice plugs with the piston partially inserted into the cylinder.

If the assumption is made that steady flow of a frictionless, incompressible fluid is occurring along a streamline, then Bernoulli's conservation-ofenergy equation can be applied to describe the physical state of the fluid (Streeter, 1958).

$$z + \frac{P}{\gamma} + \frac{V^2}{2g} = C \qquad (1)$$



ويرجعه والمرجع والمراجع والمرجع والمرج

FIGURE 3. SIDE SECTIONAL VIEW AND END VIEW OF THE HYDRAULIC DECELERATION DEVICE

where A_0 is the sum of all the orifice areas not passed by the piston. Substituting equations 3 and 4 in equation 2, the equation of state is defined as:

$$\frac{W_{s}G_{s}}{A_{R}\gamma} + \frac{V_{s}^{2}}{2g} = \frac{V_{s}^{2}A_{R}^{2}}{2gA_{0}^{2}} + H_{L}$$
(5)

In the analysis of fluid flow in a pipeline, several sources are present to contribute to the energy loss, H_L . One source is friction, defined as:

$$f_{2Dg}^{L_{e} V^{2}}$$
(6)

where f is a dimensionless term representing the relative roughness; L_e is the equivalent length of the conduit; and D is the diameter. This loss effect is difficult to determine analytically and is best determined experimentally. This is impractical to do for all the orifices. Another source is the loss at the entrance to a pipeline from a reservoir. This applies to the entrance of each plug and usually varies between $0.05V^2/2g$ to $0.5V^2/2g$, depending on the squareness of the edge of the opening. A third source of energy loss is due to a sudden contraction in a pipeline. This occurs at the base of each plug where the opening is suddenly decreased from the diameter of the plug to the smaller diameter of the orifice in the plug. The contraction coefficient for water flow in a pipeline is known as a function of the area ratio and is presented in Table 1.

Table 1. CONTRACTION COEFFICIENT VERSUS AREA RATIO

A ₂ /A ₁	-	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
Cc	-	0.624	.632	.643	.659	.681	.712	.755	.813	.892	1.00

The energy loss due to the contraction is defined as:

$$h_{c} = (1/C_{c} - 1)^{2} \frac{V_{c}^{2}}{2g}$$
(7)

Substituting h_C for H_L in equation 5 and rearranging terms, then Bernoulli's equation becomes:

$$\frac{A_0}{\sqrt{(1/C_c - 1)^2 + 1}} = \frac{A_R}{\sqrt{(2gW_sG_s/A_RV_s^2 + 1)}}$$
(8)



FIGURE 4. ACCELERATION AND VELOCITY VERSUS DISPLACEMENT FOR TEST 1441

9





DISCUSSION

The hydraulic deceleration orifice profile can be determined by the application of Bernoulli's conservation-of-energy equation to the physical state of fluid flow during the impact event. Energy losses due to the <u>vena-contracta</u> of each orifice was included in the calculation of the required orifice area. Losses due to friction and square edged orifices were determined as a lumped parameter based upon impact test results. This procedure of determining the hydraulic deceleration profile has been used for a recent test program and has proven very accurate.

Several sources of perturbations, not covered in this report, exist which can affect the acceleration profiles obtained during impact. One is the piston striking the alignment bearing prior to entering the hydraulic deceleration device. This has occasionally produced short-duration pulses of various amplitudes at the beginning of the impact profile. The clearance between the sled glide pads and the rails allows the sled to vibrate between the rails during impact, which appears as noise on the acceleration profile. The dynamic interaction between the test subject and seat, especially during low-amplitude long-duration profiles, may also alter the pulse shape.



PARAMETERS

W - SLED WEIGHT (POUNDD)
$P_{S} = PROFILE SOURCE - 1, 2, 3, 4, 5, 6$
D _T = DATA TIME INCREMENT (SEC)
A_{M}^{\pm} data peak acc. (g)
B = DATA PULSE WIDTH (SEC)
VT = TOTAL VELOCITY CHANCE (FT/SEC)
$S_{T}^{=}$ TOTAL DISPLACEMENT (FT)
T = INSTANTANEOUS TIME (SEC)
$V_i = INSTANTANEOUS VELOCITY (FT/SEC)$
S = INSTANTANEOUS DISP. (INCH)
0 = INSTANTANEOUS ORIFICE AREA (SQ. IN.)
$A_{i} = INSTANTANEOUS ACC. (FT/SEC2)$
C = CORRECTION COEFFICIENT
T_{p} = RISE TIME (SEC.)
T _F = FALL TIME (SEC.)
I_{T} = TIME SOURCE 0,1
D = DISTANCE TO PLUG (IN)
P_n , $P_i = PLUG IDENTIFICATION$
B = PLUG ORIFICE AREA (SQ. IN.)
L ₁ = PLUG LOCATION
C_= PLUG EFFECTIVE AREA (SQ.IN.)
R = TOTAL EFFECTIVE AREA (SQ.IN.)

TO LEAD AND THE PARTY IN THE CONTRACT PROPERTY DESCRIPTION OF THE PARTY OF THE PART



COURCE ENGLANCE







DATA							
n	P _n	8,	C _n				
1	1	\$.94 4	Ø.944				
2	3	J.681	9 .713				
5	31	Ø. 352	#.0#1				
5	32	Ø.328	d .371				
6	4	Ø.215	J.248				
7	33	Ø.159	9.184				
8	8	9.193	Ø.129				
9	34	9.909 g g g	9.9 93				
11	26	9.933	J.J . J .				
12	25	Ø.Ø35	9.941				
13	34	Ø.927	Ø.932				
14	36	Ø.Ø17	9.929				
15	37	Ø.998	g.91g				
10	9 41	3 076	2 976				
18	43	2.726	2.853				
19	42	1.898	1.996				
29	431	1.313	1.485				
21	44	9.864	Ø.994				
22	432	9.636	9.737				
23	433	J.499	g. 30p				
25	434	Ø. 332	Ø. 386				
26	416	Ø.212	Ø.248				
27	429	\$.167	J.196				
28	425	9.137	9.16 1				
29	4	p	p				



END

10-85

DTIC