

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

AD-A181 466

DTIC FILE COPY

2

NAVAL POSTGRADUATE SCHOOL

Monterey, California



DTIC
SELECTED
JUN 19 1987
S E D

THESIS

COST ANALYSIS FOR AIRCRAFT SYSTEM TEST AND
EVALUATION: EMPIRICAL SURVEY DATA STRUCTURING
AND PARAMETRIC MODELING, VOLUME II

by

William J. Foster

and

Walter J. Moore Jr.

March 1987

Thesis Advisor:

Tung X. Bui

Approved for public release; distribution is unlimited

A181466

REPORT DOCUMENTATION PAGE

1a REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b RESTRICTIVE MARKINGS	
2a SECURITY CLASSIFICATION AUTHORITY		3 DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited	
2b DECLASSIFICATION/DOWNGRADING SCHEDULE			
4 PERFORMING ORGANIZATION REPORT NUMBER(S)		5 MONITORING ORGANIZATION REPORT NUMBER(S)	
6a NAME OF PERFORMING ORGANIZATION Naval Postgraduate School	6b OFFICE SYMBOL (if applicable) 54	7a NAME OF MONITORING ORGANIZATION Naval Postgraduate School	
6c ADDRESS (City, State, and ZIP Code) Monterey, California 93940-5000		7b ADDRESS (City, State, and ZIP Code) Monterey, California 93940-5000	
8a NAME OF FUNDING/SPONSORING ORGANIZATION Naval Air Systems Command	8b OFFICE SYMBOL (if applicable) AIR-5243	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c ADDRESS (City, State, and ZIP Code) Jefferson Plaza 2 Washington D.C. 20361		10 SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO	PROJECT NO
		TASK NO	WORK UNIT ACCESSION NO
11 TITLE (Include Security Classification) COST ANALYSIS FOR AIRCRAFT SYSTEM TEST AND EVALUATION: EMPIRICAL SURVEY DATA STRUCTURING AND PARAMETRIC MODELING, VOLUME II			
12 PERSONAL AUTHOR(S) Foster, William J. and Moore, Walter J. Jr.			
13a TYPE OF REPORT Master's Thesis	13b TIME COVERED FROM _____ TO _____	14 DATE OF REPORT (Year, Month, Day) March 1987	15 PAGE COUNT 256
16 SUPPLEMENTARY NOTATION			
17 COSATI CODES		18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	Aircraft, Financial Management, Materiel Acquisition	
	SUB-GROUP		
19 ABSTRACT (Continue on reverse if necessary and identify by block number)			
<p>There is an increasing requirement from high levels within the Government that the Navy's aircraft cost estimators and analysts provide explicit estimates for the sub-elements of Aircraft System Test and Evaluation (AST&E) efforts. The data required to produce more accurate and detailed estimates represent lower levels in the Aircraft Work Breakdown Structure (WBS) than previously available. This is a two volume thesis. Volume I examines the WBS and Contractor Cost Data Reporting (CCDR) system with a description of current reporting practices and implementation shortcomings. Recommended courses of action to improve reporting requirements and thereby improve data quality and cost estimates</p>			
20 DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS		21 ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a NAME OF RESPONSIBLE INDIVIDUAL Tung X. Bui		22b TELEPHONE (Include Area Code) 646-2639	22c OFFICE SYMBOL 54Bd

(19. continued)

are proposed. Major cost drivers for AST&E, from both the perspective of Defense Contractors and Military Flight Test Centers, are discussed. Beginning in Volume II, a relational data base system is introduced to more easily evaluate AST&E cost elements and physical/performance characteristics. A Contractor Flight Test Cost estimating relationship (CER) is developed through step-wise multiple regression analysis of data gathered from Defense Contractors and Naval Air Systems Command (NAVAIR).

Approved for public release; distribution is unlimited

Cost Analysis for Aircraft System Test and Evaluation:
Empirical Survey, Data Structuring and Parametric Modeling
Volume II

by

William J. Foster
Major, United States Marine Corps
B.A., Washington State University, 1972

and

Walter J. Moore Jr.
Lieutenant, United States Naval Reserve
B.S., University of San Francisco, 1981

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN INFORMATION SYSTEMS

from the

NAVAL POSTGRADUATE SCHOOL
March 1987

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

Authors:

William J. Foster

William J. Foster

W. J. Moore Jr.

Walter J. Moore Jr.



Approved by:

Tung X. Bui

Tung X. Bui, Thesis Advisor

T. Sivasankaran

T. Sivasankaran, Second Reader

Willis R. Greer, Jr.

Willis R. Greer, Jr., Chairman,
Department of Administrative Sciences

Kneale T. Marshall

Kneale T. Marshall, Dean of
Information and Policy Sciences

ABSTRACT

There is an increasing requirement from high levels within the Government that the Navy's aircraft cost estimators and analysts provide explicit estimates for the sub-elements of Aircraft System Test and Evaluation (AST&E) efforts. The data required to produce more accurate and detailed estimates represent lower levels in the Aircraft Work Breakdown Structure (WBS) than previously available. This is a two volume thesis. Volume I examines the WBS and Contractor Cost Data Reporting (CCDR) system with a description of current reporting practices and implementation shortcomings. Recommended courses of action to improve reporting requirements and thereby improve data quality and cost estimates are proposed. Major cost drivers for AST&E, from both the perspective of Defense Contractors and Military Flight Test Centers, are discussed. Beginning in (Volume II), a relational data base system is introduced to more easily evaluate AST&E cost elements and physical/performance characteristics. A Contractor Flight Test cost estimating relationship (CER) is developed through step-wise multiple regression analysis of data gathered from Defense Contractors and Naval Air Systems Command (NAVAIR).

This document is a thesis by [unclear] on the subject of [unclear] requirements, parameters, and [unclear]

TABLE OF CONTENTS

I.	SURVEY OF CURRENT DATA AND STRUCTURE.....	8
A.	INTRODUCTION.....	8
B.	DESCRIPTION BY CONTRACTOR.....	8
1.	Boeing.....	8
2.	Rockwell International, Columbus.....	11
3.	Fairchild Aircraft.....	11
4.	Grumman Aerospace Corporation.....	11
5.	Rockwell International, Los Angeles.....	12
6.	LTV Aerospace and Defense.....	12
7.	General Dynamics Corporation.....	13
8.	McDonnell Douglas Corporation.....	14
9.	Lockheed Georgia Company.....	14
10.	Lockheed California Company.....	16
11.	Naval Air Test Center.....	16
12.	Air Force Test Flight Center.....	16
13.	NAVAIR.....	17
C.	SUMMARY.....	18
II.	A SURVEY OF PARAMETRIC TECHNIQUES FOR ESTIMATING COST OF AIRCRAFT SYSTEMS.....	19
A.	INTRODUCTION.....	19
B.	PARAMETRIC COST ESTIMATION STUDIES.....	20
1.	Planning Research Corporation (PRC R-547-A) April 1967.....	20
2.	RAND (R-761-PR) February 1972.....	22
3.	J. Watson Noah Associates (FR-103-USN) September 1973.....	24

4.	RAND (R-1693-1-PA&E) May 1975.....	27
5.	RAND (R-1854-PR) March 1976.....	31
6.	TRW Defense and Space Systems Group (ASD-TR-80-5025) September 1980.....	32
7.	RAND (N-1685-AF) March 1981.....	34
C.	SUMMARY.....	35
III.	DEVELOPMENT OF DATA BASE.....	38
A.	REQUIREMENTS FOR BUILDING DATA BASE SYSTEM FOR T & E.....	38
1.	Current Data Base.....	38
2.	Need for Data Manipulation.....	38
3.	Need for Standardization.....	39
B.	DESIGN AND IMPLEMENTATION.....	39
C.	DATA BASE UTILIZATION AND BENEFITS.....	41
IV.	DATA ANALYSIS OF SYSTEM TEST AND EVALUATION.....	43
A.	DISCUSSION OF DATA STRUCTURES.....	43
1.	Dependent Variables.....	43
2.	Independent Variables.....	44
3.	Statistical Analysis Data Format.....	45
B.	EVALUATION OF DATA.....	46
1.	Statistical Value of the Data.....	46
C.	ANALYSIS OF COST DRIVERS.....	47
D.	DEVELOPMENT OF COST DRIVER MODELS.....	48
1.	Contractor Flight Test Total Labor Hours....	49
a.	Weight and Speed Variables.....	50
b.	Consideration of Other Variables.....	51
2.	Contractor Flight Test Engineering Hours....	53

a.	Weight and Speed Variables.....	53
b.	Consideration of Other Variables.....	54
E.	SUMMARY.....	55
V.	CONCLUSION.....	56
A.	SUMMARY OF RESULTS.....	56
1.	Propositions for a better implementation of the CCDR.....	56
2.	Elicitation of experts' opinion to identify the most important cost-drivers in System Test and Evaluation.....	57
3.	Survey of Current Data and Structure Main- tained by Defense Contractors & Military Institutions.....	58
4.	Survey of Parametric Techniques for Estimat- ing Cost of Aircraft Systems.....	58
5.	Development of a Cost Estimation Relational Data Base System.....	59
6.	Development of New Parametric Cost Estima- tion Models.....	60
B.	SUGGESTIONS FOR FURTHER RESEARCH.....	60
APPENDIX A:	DATA DICTIONARY.....	62
APPENDIX B:	PROGRAMS.....	66
APPENDIX C:	DATA STRUCTURES.....	111
APPENDIX D:	USER'S MANUAL.....	114
APPENDIX E:	REPORTS.....	135
APPENDIX F:	ONE WAY ANALYSIS OF VARIANCE.....	114
APPENDIX G:	REGRESSION ANALYSIS.....	184
LIST OF REFERENCES.....		250
BIBLIOGRAPHY.....		251
INITIAL DISTRIBUTION LIST.....		253

I. SURVEY OF CURRENT DATA AND STRUCTURE

A. INTRODUCTION

All companies interviewed provided data in some form or another. Some data were better and more complete than others. Not all aircraft data requested were provided. Various reasons were given, including, (i) data too old and not available or would not be of use; (ii) aircraft were commercial derivatives and flight test data not applicable; or (iii) data were for internal use only. A synopsis of the data received, by company, is included below. This summary includes: the type of aircraft reported against, how much data was given, what form the data was in, and a short overview of the companies data collection methods.

B. DESCRIPTION BY CONTRACTOR

1. Boeing

Boeing's initial data include a breakdown of the B-52 and the KC-135 aircraft. Flight Test, Wind Tunnel Test, Static Test, Fatigue test, Flight hours, Wind Tunnel Occupancy Hours and other data were provided. The flight test data were time phased. In the case of the B-52, only block 1 aircraft were time phased, available from 1952 through 1958 in six-month intervals. With the KC 135 six-month interval data blocks 1 through 4 aircraft were

included ranging from 1953 through 1959. For wind tunnel static and fatigue test, only data for the B-52 were provided. Flight test hours were provided by serial number, and wind tunnel occupancy hours were given for both B-52 and KC-135. Other data include the B-52 prototypes flight test and mockup hours. Other KC-135 data include other block 1 data, i.e., maintenance trainers, support equipment, static test, wind tunnel test, airframe and structure ground test, avionics ground test, other ground test, other system test, class I M/U, class II M/U, and class III M/U. Graphs were plotted in the section on wind tunnel occupancy to show the time phased usage of the wind tunnel. Additional Flight test and Wind Tunnel data on the KC-135-1, XB-52, YB-52 and YC-14 were provided.

All the data given was stored in a historical data base within the company owned and developed called Executive Information System (EIS). This system is a matrix-type structure with cost elements and programs forming the parents with many children, matched against the Work Breakdown Structure (WBS) down to the fifth level elements (see Figure 1-1). All cost data is from the official company accounting system and auditable to work in progress ledgers. Data can be retrieved per user desired reports or formats in tabular or graphic display (i.e., total man-hours by cost element (CE), detailed manhours (CE/WBS),

EIS Data Base Matrix




Figure 1-1. EIS Data Base Matrix

time-spread cumulative unit cost, and program and product data). Boeing also has a current on-line system to handle ongoing projects. Once these projects are completed, the information is transferred to the historical data base.

2. Rockwell International, Columbus

Rockwell Columbus provided data on the A-5A, OV-10 and the T-2. Data included total hours and dollars for Contractor Flight Test, Wind Tunnel, Static and Fatigue Test. Contractor Flight Test and Wind Tunnel were not broken down into any sub-elements; Static and Fatigue Test did not include the Engineering hours for the article test. Flight hours are time phased. Engineering and manufacturing hours are the only hours reported.

It was not understood whether or not Rockwell has an computerized data base. If they do, it is not likely real time since definitions are not standard through the company.

3. Fairchild Aircraft

Fairchild provided data on the F-105. Information was given on engineering paper and looked to be a copy of the total records kept of the aircraft. Fairchild does not have a data base. All records are apparently kept by hand. Like Rockwell, the definitions are not standard company wide.

4. Grumman Aerospace Corporation

Grumman provided data on the F-14. Initially, cost data only were provided. Later, a detailed breakdown of the

system test and evaluation for Contractor Flight, Static, Wind Tunnel, and Fatigue test were offered, together with a Test to Cost Study performed by the Flight Test Department which included extensive information relating to the F-14 and other aircraft.

Grumman has a data base and a standard accounting system. Data are structured down to Level 9 of the WBS in the data base. Grumman uses the contract dictionary down to Level 5 or 6. Data below Levels 5 and 6 are defined by Grumman's Planning and Controls section. The company's definitions are standardized.

5. Rockwell International, Los Angeles

Only cost data on the B-1 were provided by Rockwell L.A.. Cumulative system test hours were made available for Static Test and Fatigue Test. These hours were broken down by unit number.

Rockwell has a computer data base accounting system. During the interview, they did not share any detail on its level of information. We were referred to the Air Force system project office for all our data requests. We were only provided dollar figures on the CCDR required reports.

6. LTV Aerospace and Defense

LTV delivered data on A-7, TA-7, XC-142A, F-8U and as a sub-contractor, S-3A and C-17. Of these, statistics on the A-7 and the TA-7 were abundant. Flight hours were time phased starting in September 1965 for the A-7 and December

1976 for the TA-7. Labor hours were divided into engineering and manufacturing, and reported for Instrumentation, Flight Test Spin Program, Night and Delivery, and Misc. For the TA-7, labor hours were not divided between engineering and manufacturing. Total hours were reported against the same items as the A-7 except for an additional item reporting category of General Flight Support.

The company's financial management department maintains the WBS to the third level. The Work Management System is a system listing by task and correlates to WBS sub-tasks. LTV does not currently have a data base that allows for retrieval of historical data by cost element. Work is in progress to implement such a data base system.

7. General Dynamics Corporation

General Dynamics provided data on the YF-16, F-111, F-16 and the B-58. Data included hours and dollars for Direct Labor Hours, Administration, Engineering, Tooling, Manufacturing, Mod and Test, Electric Fabrication Center, Q.A. and Production Support. Only dollar figures were reported for Overhead, Material and Subcontract, Material Burden, Other Direct Charges and General and Administrative Expense. In addition, a Program Overview was given along with Aircraft Characteristics, Program Unique Features, Schedule Data, and WBS Definitions.

General Dynamics maintains a company-wide MIS with matrix translation to input individual project cost data. This system captures actual cost data with dollars normalized to a midpoint for the cost period. The internal data base is used to establish cost estimation relationships.

8. McDonnell Douglas Corporation

McDonnell Douglas provided a schedule for the Static Airframe, Fatigue Airframe, and Fatigue Test Article development. They also provided a historical F/TF-15 Category I Flight Test Plan, but no data was released.

WBS accounting is kept at one level below contract requirements. If contract is at Level 3, internal records will be maintained at Level 4. Their current data base maintains information at the following levels:

- Job order--large component level
- Item level--segregates major tasks (i.e., fatigue testing)
- Cost code--sub-task of item level (i.e., forward fuselage side panel).

Cost accounting is standardized company wide in a corporate data base system used by McDonnell Douglas with each sector of the company records are maintained separately in sub-groups for specialized information.

9. Lockheed Georgia Company

Lockheed released data on the C-5, C-141 and a limited amount on the C-130. The C-5 data was broken down

by Production Manhours, Engineering Manhours, Tooling Manhours, and Material Dollars. In addition, a description of the WBS used on the C-5 was provided. The C-141 data was broken down by Engineering Manhours, Tooling Manhours, and Material Dollars. A WBS description and a test and update highlights chart was provided. The limited data on the C-130 included total flight hours, number of months from 1st flight to completion of tests, and average flight hours per month.

Cost items are tracked by work order, subdivided into major class, minor class, and suffix. Suffix data has been used by different divisions of Lockheed Georgia for their own data tracking, complicating insertion of lower level cost elements into a standard company database. The work order information generally follows the work breakdown structure format. The accounting and record keeping department utilizes Boeing's information system shell to support the internal data structures. The Tops (terminal on-line pricing system) will work with the Glides (GELAC Integrated Data Bank Estimating System) system for cost estimating and analysis. As this system is fully implemented, the outer ring or system shell will be standardized company-wide. The inner ring will be tailored for departmental use. Due to differences in past job order tracking, a significant amount of time has been spent in standardizing cost data. For government contracts, they use

the Sentinel system (Cost schedule control system) to track CCDR reporting requirements only. This was the basic system previously used to track work order information.

10. Lockheed California Company

Lockheed California provided data on the S-3A, this data was given in hours and dollars. Data was provided for the majority of the requested categories. Flight hours were provided by aircraft. Engineering hours were further broken down into subcategories of the WBS.

Cost items are tracked the same as with Lockheed Georgia except that an on line data base is expected to be operational in the near future. At present, historical test data is maintained separately for each major program and not standardized company wide.

11. Naval Air Test Center

It was intentional not to gather data from the Naval Air Test Center. However, some information on an accounting system that is to be introduced in March 1987 were made available. This system is called STAFS (Standard Automated Financial System). It is not used as a real time data base and will not provide real time access to System Test and Evaluation type data.

12. Air Force Test Flight Center

The Air Force Test Center provided data on the B1-B, F-15 and the F-16. Units (hours); actual and estimated, dollars; estimated total, actual total, estimated

reimbursable and actual reimbursable were reported for job order numbers. Cost-centers were broken down by JON (job order numbers), PIN (product identification number), REN (resource identification number), and EEIC (elementary element identification code).

This test center is unique in that it is a Combined Test Facility. Contractors and the test center share data collected on System Test and Evaluation aircraft. Contractors do their testing on site using the Test Centers facilities.

The Air Force Test Flight Center uses an accounting system called MISTE (Management Information System for Test and Evaluation). This system tracks and updates the test data according to the JON, PIN, REN, and EEIC numbers. It also provides the capability to create reports, standard and nonstandard.

13. NAVAIR

Additional information was provided by NAVAIR. This data was on the S-3A aircraft and came from the NAVAIR data base where the CCDR report information is held. The data was time phased in six-month intervals, standardized and reported against the WBS. This information was used as a tool to evaluate the other S-3A data.

C. SUMMARY

All data furnished can be used, however for the initial analysis, only test labor hours, as opposed to dollars, are appropriate. Therefore Rockwell's cost data will not be utilized. Also the data contributed by the Air Force Test Flight Center is not appropriate because of the inability to distinguish between Contractor Flight Test and Operational Flight Test.

Data furnished by the contractors need to be standardized and compared to the individual companies' CCDR reports held at NAVAIR before they can be used for statistical purposes. Once this task is accomplished, the data could be ready for analysis. However to facilitate the analysis process, the data should be re-arranged in a cohesive and consistent framework. This could be accomplished by developing a data base structure where data could be maintained. This would also facilitate the ease of use as well as the analysis.

II. A SURVEY OF PARAMETRIC TECHNIQUES FOR ESTIMATING COST OF AIRCRAFT SYSTEMS

A. INTRODUCTION

A parametric equation which is derived from theoretical considerations is called a model. The parameters occurring in a model usually represent quantities that have physical significance. The validity of a model rests on the procedures used to obtain values of the parameters, e.g., estimators that not only fit the data well, but also come, on the average, close to the true values and do not vary excessively from one set of experiments to the next. The process of determining parameter values with these statistical considerations in mind is termed model estimation. The utility of parametric estimation models has been effectively applied to several branches of science. (BARD, 1974, pp. 15-16) These parametric techniques are also applicable to the area of cost estimation.

Parametric cost estimating, when applied to aircraft systems, primarily utilizes physical and performance characteristics, as well as costs of previously procured items to identify the anticipated costs for a new system. A combination of system parameters, such as physical dimensions, weight, speed, etc., can be related to the total system cost. Relationships can be established in the form of mathematical equations and are referred to as Cost

Estimating Relationships (CERs). Cost elements, such as labor hours, are chosen as the dependent variable in a CER. System parameters are evaluated as independent variables in the relationship. These parametric methods can be applied to individual segments of a system life cycle or estimations can be aggregated to reflect a composite--resulting in total system cost. In the acquisition of aircraft systems, parametric cost estimating lends itself readily to developing relationships before the details of design are certain. Cost comparisons on alternative designs can also be evaluated early in the preliminary design stage as varying parameters of system cost are tested. Parametric cost estimating is a possible tool, provided accurate and sufficient data is available to evaluate the aircraft physical characteristics, performance tradeoffs, and cost impact alternatives.

Several research studies have applied parametric cost estimating methods to develop models for aircraft systems. Included are two studies that focus on software and avionics estimating methods.

B. PARAMETRIC COST ESTIMATION STUDIES

1. Planning Research Corporation (PRC R-547-A) April 1967

An early excursion into estimating airframe development and production costs was attempted by the Planning Research Corporation (PRC). The study centered on

developing suitable techniques for use in program planning, cost-effectiveness studies, and evaluation of contractor proposals. This model consisted of three separate cost elements: direct manufacturing labor, manufacturing materials, and engineering and tooling (aggregated as a single element). Tooling and engineering costs were combined in order to separate recurring and nonrecurring costs for these two categories. (Sanchez, 1967, p. I-1) The model was developed by stepwise regression on a sample of forty-one propeller driven and turbojet aircraft dating from as early as 1940. Aircraft characteristics used as independent variables included speed, weight, and functions of these (e.g., speed squared). Production program characteristics included quantity produced, delivery rate, and a weight growth factor. Contractor discontinuity variables were used to represent differences in accounting practices. Time-related characteristics expressed changes in the technological state-of-the-art from 1940.

Separate estimating equations were developed for each cost element at production unit quantities of 10, 30, 100 and 300. These estimates were then used to derive cost-quantity curves to enable cost estimation for a desired quantity of production. Graphed on a logarithmic scale, the four units of production estimate points were analyzed with best fit straight line through the vertical axis. This log-linear functional form was used to provide an estimate

for a single unit of production. Twelve equations were developed, four for each cost element across the levels of production, to derive three cost estimating curves. The evaluation of separate levels of production allowed for derivation of a learning curve to be expressed in unit costs. This provided for a more uniform procedure to be applied for aggregating cost elements into total costs. (Sanchez, 1967, p. I-6)

The study did not develop separate cost equations for prototype and production aircraft. The sample data utilized a wide variety of aircraft types, period of development and production, and range of manufacturing technology.

2. RAND (R-761-PR) February 1972

This report provided a set of relationships for estimating costs of military aircraft airframes in a long-range planning context. The relationships included costs of development and production with a separate set of CER equations for prototype aircraft development. The cost elements used in developing these relationships included engineering, development support, flight test operations, tooling, manufacturing labor, manufacturing material, and quality control. (Levenson, 1972, p. 1)

The relationships were obtained through analysis from data on post-World War II cargo, tanker, fighter, bomber, and trainer aircraft. The aircraft were of aluminum

construction with range in speed from low subsonic to Mach 2.2. The data sample included production programs from ten different defense contractors. The estimating equations were derived by statistical multiple regression techniques. These techniques related costs or man-hours to aircraft physical and performance characteristics and to airframe production quantity. Although other potential equation forms and explanatory variables were considered and tested, exponential regression equations primarily used three independent explanatory variables: aircraft weight, speed and quantity. These three variables provided the most useful relationships for the cost elements evaluated. Little or no predictive improvement was gained by including additional physical and performance variables in determining total airframe costs. (Levenson, 1972, p. 3)

Flight test operations were evaluated as a separate cost element and comprised all costs incurred by the contractor to carry out flight tests except the cost of test aircraft. Flight test operations costs were available for 27 aircraft. Data on several aircraft were not consistent with the majority of the sample. However, because no systematic criterion for rejecting specific aircraft was apparent in the sample, the complete sample was used.

Flight test operations cost was related to speed, weight and number of test aircraft with the resulting equation (Levenson, 1972, p. 14):

$F = .001244 A^{1.160} S^{1.371} Q^{1.281}$
coefficient of correlation (unadjusted) = .97
coefficient of variation = 34 percent

where F = flight test operations cost in 1970 constant
dollars

A = AMPR weight (lb)

S = maximum speed at best altitude

Q = number of flight test airframes

The uncertainty in predicting costs was addressed by this study. Since cost estimation is frequently treated as an attempt to obtain a best single-valued prediction of the cost of a new item, a level of confidence assigned to the cost equation may explain variations between initial predictions and the actual cost outcome. Factors that account for these variations may be analyzed to assess this confidence. Three primary sources of cost estimation uncertainty occurring in aircraft systems acquisition were indicated as:

1. Changes requested by the customer
2. Difficulties encountered by the contractor
3. Statistical uncertainty inherent in the estimating method--e.g., uncertainty due to failure to include all of the relevant independent variables, uncertainty due to inherent randomness in the process being modeled.

The study maintained that the effectiveness of a parametric cost model could only be analyzed with respect to the third source of uncertainty. The effects of the first two sources

of uncertainty on the validity of a model could possibly be observed by analyzing the planned weight and speed against actual weight and speed of the finished aircraft in the regression model. (Levenson, 1972, p. 33)

3. J. Watson Noah Associates (FR-103-USN) September 1973

The original intent of this report was to examine aircraft Research and Development costs and derive cost relationships for their estimation. Due to the difficulty in isolating historic R & D costs, production costs were also examined.

Data from thirty-five aircraft systems were included in the research study. Airframe cost elements included engineering, tooling and manufacturing labor, and materials costs. The costs were divided into non-recurring and recurring costs. The non-recurring costs included primarily much of what is considered as Research, Test, Development and Evaluation.

These cost estimating relationships were developed using multiple regression analysis through several logical steps. First, a large number of variables in different combinations and functional forms were screened. An examination of conventional regression statistics resulted in the elimination of several alternatives. The preferred CER was developed and a prediction interval computed. The equation was then used to predict known costs for one or

more aircraft which had been temporarily excluded from the data base as a form of validation and verification. If these results proved satisfactory, then all of the observations were included in the CER development and the coefficients were reestimated. (Noah, 1973, pp. 44-45)

The following candidate variables for non-recurring airframe costs were selected:

S = Maximum Speed

A = AMPR Weight

R = Ratio of gross takeoff (GTO) weight to AMPR weight

T = Technology Index

D = Complexity Dummy

Aeronautical Manufacturers' Planning Report (AMPR) weight provided a standard for consistent evaluation. Maximum speed was used for an aircraft's best altitude. Gross takeoff weight represents design gross weight for an aircraft's primary mission. The technology index variable explained the changes which occurred in airframe manufacturing technology through time trends. The complexity dummy variable was included because the CERs underestimated the costs of four aircraft (F-102, F-106, B-58 and F-111). The use of the dummy variable was justified for these aircraft due to mission or performance parameters which required significantly new and complex technology. (Noah, 1973, pp. 47-48)

The non-recurring airframe costs relationship, derived through regression analysis, resulted in the following CER predictor:

$$\text{Cost} = -5.945 + .00663 S + .05138 T - 1.4071 R + 6.74926 D$$

(6.43) (1.645) (3.18) (7.54)

$$N = 32$$

$$R^2 = .847$$

Numbers shown in parentheses are t-ratios expressed in absolute value. All logarithms are understood to be to the base 'e'. (Noah, 1973, p. 66-67)

Cost estimation relationships for separate elements of airframe non-recurring total costs were not developed in this model.

The significance of avionics cost in aircraft system development with a current lack of avionics CERs to estimate either development or production costs was addressed in this study. Avionics CER development had not been successful up until that time due to poor data availability and quality. The study recommended categorization and reporting of avionics costs by function through required contractor cost reports.

4. RAND (R-1693-1-PA&E) May 1975

The cost estimation model developed in the 1972 RAND study (R-761-PR) elicited user concern centering on three perceived shortcomings of the model: (1) the only two major explanatory variables were weight and speed; (2) all aircraft were lumped together rather than treated as

separate classes; and (3) no provision was made for taking into account changes in airframe structural materials and manufacturing methods. (Large, 1975, p. 2) As information on several new aircraft became available, the Office of the Assistant Secretary of Defense -Program Analysis and Evaluation (OSD-PA&E) sponsored a new RAND study to address these problems. The study plan called for:

1. Review of airframe data in the RAND files to ensure accuracy and consistency of definition and acquisition data on new aircraft
2. Consideration of additional explanatory variables that would make the model better able to deal with characteristics peculiar to individual aircraft, e.g., variable-geometry wing, oversize fuselage
3. Examination of the cost impact of major changes in manufacturing technology over time and of the use of different structural materials. (Large, 1975, p. 2)

In the time available, all questions concerning data consistency were not resolved. Their search for other explanatory variables that would improve the accuracy of estimates were less fruitful than they hoped. The variations in cost that were not explained by weight and speed were not explained by any other objective indexes that they could find. Since the data sample consisted largely of aluminum aircraft, the shift to other materials such as steel, titanium, and composites raises a question about the value of equations derived from that sample for estimating the cost of future aircraft. Some qualitative considerations were addressed concerning a statistical

analysis trend toward higher material costs and reduced manufacturing man-hours.

The estimation model developed was similar to other RAND models in that it allowed estimates to be made of individual cost elements. The study contends that results obtained from individual cost estimates are comparable to the accuracy achieved by estimating at the total program level recommended by the 1973 Noah study (FR-103-USN).

An attempt to analyze the data sample by aircraft type (bombers, fighters, cargo aircraft, etc.) was addressed. Despite the intuitive appeal of stratifying the sample in that way, two factors discouraged this approach. First, when the data were plotted, no natural boundaries appeared. Trainers were mixed with fighters, fighters with bombers, and bombers with cargo aircraft since many category types were similar in both weight and speed. Second, the sample size for individual aircraft types was too small to be representative except in the case of fighters. They held that in cost estimation, as is usually the case, the new aircraft will be substantially different from the historical data base and it is better to have a larger group of more diverse aircraft as a data sample.

Numerous explanatory variables that could impact aircraft development cost were evaluated. Seventeen separate physical characteristics were considered as possible variables for analysis. Other factors influencing

program cost were explored: **schedule, management, funding, state-of-the-art advance, availability of labor, investment in capital tools, and time.** However, these factors were considered to be inconsistent and not appropriate to a parametric cost model based on data from a wide assortment of programs insensitive to small changes. (Large, 1975, p. 14)

Utilizing a stepwise least-squares procedure, the explanatory variables were evaluated. The most statistically significant characteristics and dependable predictors of cost remained **weight and speed.** (Large, 1975, p. v)

Flight test costs were also addressed in this study as a separate cost element. The independent variables found to be significant here, other than weight and speed, were the **number of flight-test aircraft** and a **dummy variable** to distinguish between cargo aircraft and all other types. The rationale for the dummy variable focused on added cost of instrumenting the test aircraft as an important portion of flight-test cost. Thus, cost should increase as the number of aircraft increases. Cargo aircraft supposedly require less flight testing than fighters and bombers due to a relative complexity factor, so cargo aircraft flight test costs would be lower. The flight test estimating equation was presented as follows (Large, 1975, pp. 36-37):

where FT = Flight Test Cost (1973 \$ in Thousands)

Wt = Airframe Unit Weight (lb)

Speed = Maximum Speed (kn)

N = Number of Test Aircraft

DV = Dummy Variable (2 - Cargo, 1 - All others)

$$FT = .13(Wt)^{.71} \quad (Speed)^{.59} \quad (N)^{.72} \quad (DV)^{-1.56}$$

(.99) (.92) (.99) (.99)

$$R^2 = .81$$

The number under each independent variable is the level of significance of that variable.

The study provided a suggested direction for future research emphasizing not only deterministic physical and performance characteristics but also trying to understand the influence of program differences. Factors such as **schedule, experience, efficiency, economic conditions, labor scarcities**, and all other contractor and governmental concerns do have a cost impact on each individual aircraft system acquisition. (Large, 1975, pp. 53-54)

5. RAND (R-1854-PR) March 1976

This report described the development of a substantially revised RAND computer model, DAPCA III (Development and Procurement Costs of Aircraft), which superceded the previous version reported in RAND report R-761-PR. This model is based partially on airframe methodology described in R-1693-1-PA&E with all airframe costs calculated as functions of airframe unit weight and

maximum speed at best altitude. Other explanatory variables found to be significant were time of first flight for manufacturing labor and for manufacturing materials, and the dummy variable for cargo or non-cargo aircraft in flight test cost. (Boren, 1976, p. 2)

No cost estimation relationships were developed for avionics packages to be included in the total system cost. Avionics development cost was entered into this model only as a throughput. Estimations for follow-on avionics packages were adjusted to follow a 95% learning curve factor since the package usually consisted of old as well as new equipment.

6. TRW Defense and Space Systems Group (ASD-TR-80-5025) September 1980

This study does not address the acquisition of the total aircraft system, rather it focuses on the software cost analysis and estimating procedures of avionics operational flight programs (OFP). It assumes limited knowledge of the software product in the early planning phases, increased knowledge before the release of the Request For Proposal (RFP), and more complete knowledge at the time of proposal evaluation and source selection. (Wolverton, 1980, p. 1) Several cost estimating methodologies and alternatives were provided to support and evaluate the validity of an initial cost estimate.

The study reviewed five traditional approaches to software cost estimation. The approaches described were

top-down, similarities and differences, ratio, standards, and bottom-up estimating. It was recommended that two approaches should always be used in order to cross-check one against the other. This provided a systematic basis that would account for any observed difference in the total cost.

Four cost estimating models, that could be utilized for initial estimates or cross-checking, were described by purpose, input, computational procedures, and output. These models, believed to be most useful, included: Boeing Computer Services Cost Model, IBM Walston-Felix Cost Model, Putnam's Software Life Cycle Cost Model, and RCA PRICE Software Cost Model. These parametric estimation models predominantly use a combination of the following inputs: units of delivered source statements, lines of source code, number of source instructions, type of software to be developed, programming language and programmer skill, programming techniques, labor cost, available manpower or similar type descriptors. Utilizing various parametric techniques, the models provides cost estimation information in the form of man-month requirements, project duration, development cost, time phasing of effort, and sensitivity analysis to adjusted input variables.

The study recommends that each separate cost estimate be verified through comparison with an alternate prediction method.

7. RAND (N-1685-AF) March 1981

This research project was directed at providing cost estimating methods and relationships for both whole avionics suites and individual avionics systems for combat aircraft. The study centered on a sample of 17 combat aircraft and the avionics equipment installed in each. Possible explanatory variables were selected based upon interview inputs from defense contractors. Multivariate regression analysis techniques were used to evaluate potential CERs for both whole suites and individual avionics systems.

The explanatory variables determined to be most statistically significant for the avionics suites were:

1. Aircraft Empty Weight
2. Avionics Suite Weight
3. System Power Requirements (kilovoltamperes)
4. Avionics Suite Volume
5. Year of First Flight (technology variable)
6. All-weather capability dummy variable.

Four individual cost estimating relationship equations were developed based upon aircraft characteristics, avionics suite weight, avionics suite volume, and avionics suite power requirements. (Dryden, 1981, pp. v-vi)

Analysis of individual avionics systems, broken down into 11 functional groups, did not yield cost estimating relationships that were as robust as those provided for a whole avionics suite. This grouping provided relatively

homogeneous subsamples with potential estimating relationships based on weight, volume and power variables. A technology variable added little to the effectiveness of tested relationships with an undesirable amount of unexplained variance remaining.

A major problem expressed in this study was the difficulty in capturing and representing the rapid change characterizing the electronics technology of avionics. Advances in that technology have consistently led to the accomplishment of more individual functions per unit size of avionics equipment. To meet increasing mission requirements, more functions have been included in the design of avionics suites with an overall increase in total cost. (Dryden, 1981, p. 2)

C. SUMMARY

The studies discussed in this chapter were developed to provide parametric cost estimating models for both development of total aircraft systems and separate cost elements of those systems. The models describing airframe costs were developed as long ago as 1967. Avionics and software costs have emerged as growing elements in the acquisition of new aircraft systems. All of these cost models were developed through multiple stepwise regression using various size databases. The statistical samples were updated and evaluated with newer aircraft designs as

manufacturing methods and materials also changed. Despite the difference in samples and statistical approaches each study used for estimation, the two primary aircraft characteristics or variables/drivers for airframe cost remained weight and speed. Comparing airframe design alternatives for a new aircraft system, cost and performance tradeoffs could not be readily identified by using current estimation models unless weight and speed are significant factors in the analysis. Figure 2-1 compares four airframe cost studies by identifying cost elements and independent aircraft characteristic variables. Other physical and performance characteristics provided the most easily quantifiable descriptors of an aircraft system but did not yield the statistical qualities required to be considered for inclusion in an accurate cost model.

The need for identification of more reliable independent variables, that would provide statistical stability for cost estimation, was a salient issue addressed in these research studies. The structure and implementation of acquisition record keeping systems to provide the depth and accuracy of cost data for analysis was also considered an important focal point.

	A	B	C	D	
DEPENDENT VARIABLES					
Aircraft Recurring Cost				X	
Aircraft Non-recurring Cost				X	
Development Support Cost			X		
Engineering/Tooling Cost		X			
Flight Test Cost	X			X	
Manufacturing Labor Cost		X			
Manufacturing Materials Cost		X	X		
Quality Control Cost		X			
Tooling Cost			X		
Total Cost				X	
Engineering Hours					X
Manufacturing Hours					X
Quality Control Hours				X	
Tooling Hours					X
INDEPENDENT VARIABLES					
Cargo Dummy				X	
Quantity		X	X		X
Speed	X	X	X	X	
Time/Complexity	X		X		
Weight	X	X	X	X	
STUDIES					
A.	PRC R-547A (1967)				
B.	RAND R-761-PR (1972)				
C.	NOAH FR-103-USN (1973)				
D.	RAND R-1693-PA&E (1975)				

Figure 2-1. Dependent/Independent Variables Developed For Aircraft Cost Estimating Models

III. DEVELOPMENT OF DATA BASE

A. REQUIREMENTS FOR BUILDING DATA BASE SYSTEM FOR T & E

1. Current Data Base

The system currently employed at NAVAIR is on three VAX-780's. This system does not facilitate either easy access to, amendment of, or rapid manipulation of the stored data due to heavy use by all branches of NAVAIR. The need for separate applications and more natural access to the data became evident in discussions with the sponsor. This need must also be filled by a system that is MS-DOS compatible that will integrate with their current on-line applications and other projected applications. The discussion in the next two sections suggests that a relational database would best fit the purpose of this study. A relational DBMS provides more timely information, better data integrity, data independence, better data management, and economies of scale. (Kroenke, 1983, p. 17)

2. Need for Data Manipulation

Constructing a data base would be greatly simplified if the only requirements were to estimate total program cost or total development and total production costs. For long-range planning studies, estimates at such aggregated levels may suffice, but they are of little use in understanding why a new program is estimated to cost a certain amount. An analyst often wants to be able to compare major cost drivers

with their counterparts to determine whether they seem reasonable and to make adjustments wherever indicated by special characteristics of the proposed aircraft (Large, 1975, p. 8), or to make design or programmatic decisions involving tradeoffs at low levels of detail. These ad hoc inquiries necessitated a tailored data base applications program that could be easily manipulated and readily interfaced into a separate statistical analysis software package such as Statsgraphic, version 2.1 or later.

3. Need for Standardization

Achieving a perfectly consistent data base when the data have been compiled by so many different contractors is extremely difficult because accounting practices differ so greatly among companies. (Large, 1975, p. 7) Thoroughly reviewing the data supplied by the contractors (levels below the required CCDR reports) and comparing them to archival data, available through NAVAIR (CCDR reports), allowed for some standardization and normalization (see Appendix A, DATA DICTIONARY). Upon completion of this step, it then becomes necessary to select an appropriate data base package for the tailored design and implementation.

B. DESIGN AND IMPLEMENTATION

Given that the data base would be used in a Local Area Network (LAN) MIS office environment, a desk top-based DBMS with advanced user interface and full transfer capabilities to the VAX-780s would be ideal. Several excellent relational data base shells are available commercially.

dBase III+ was selected for its application parameters, user friendliness and availability of technical support. The research indicated that the basic relational composition of the data base required the ability to combine aircraft specifications and test data in many different configurations as depicted in the Bachman Diagram of the logical system (Figure 3-1).




Figure 3-1. Bachman Diagram

The data was broken down at the third normal form (3NF) using the aircraft model as the key attribute. A number of predefined procedures (see Appendix B, PROGRAMS) for the manipulation of the data were compiled and a hierarchical chart was developed to enable visualization of the interrelationships of those procedures (Figure 3-2).




Figure 3-2. Basic Hierarchy Chart

Further decomposition led to the hierarchy depicted in Figure 3-3. The thirty-one (31) attributes and their structure (see Appendix C, DATA STRUCTURES) used in the programs evolved from this decomposition.

C. DATA BASE UTILIZATION AND BENEFITS

A User's Manual (see Appendix D, USER'S MANUAL) was developed to enhance the maintenance and portability of the applications programs. When a new aircraft is to be developed, all the available data can be inserted into the data base. Corrections to existing data as well as deletion of outdated data or entire records have also been simplified. Perhaps the major benefit of the program is its ability to merge files based on any attribute or sub-sets of attributes the analyst wishes to examine. Ad hoc queries can be processed and the analyst can review the report in a printed form (see Appendix E, REPORTS) as well as entering this newly created file into Statsgraphic, a statistical software package, to expedite the analysis process.




Figure 3-3. Hierarchy Chart

IV. DATA ANALYSIS OF SYSTEM TEST AND EVALUATION

A. DISCUSSION OF DATA STRUCTURES

As discussed in Chapter I, the data received were broken down into two basic categories, dependent and independent variables. These two types of variables are further described below. Appendix C (DATA STRUCTURE) lists all these variables as they are grouped into categories in the data base.

1. Dependent Variables

In the analysis process, we are trying to determine a relationship between the physical and performance characteristics of an aircraft and its test costs. The System Test and Evaluation data requested from the Defense Contractors and NAVAIR focused on direct labor hours. Direct labor hours have proven consistent in evaluating costs without regard to inflationary dollar values. Engineering, manufacturing, tooling, quality control, logistic support and total direct labor hours for the Work Breakdown Structure sub-elements of Contractor Flight Test, Static Test, Fatigue Test and Wind Tunnel Test are used as dependent variables for analysis. Standardized Work Breakdown Structure definitions of these direct labor hour cost elements as provided in Volume I, Chapter III.

2. Independent Variables

Data on aircraft physical and performance specifications are provided by Defense Contractors, NAVAIR, Aircraft Cost Handbooks (Noah, 1973; Day, 1982) and Jane's All the Worlds Aircraft reference series (1948 to present). This reference material allows an initial grouping of independent variables for estimation. The potential variables are chosen based on the availability of data, identification as proven cost drivers in previous research and expert recommendations (i.e., contractors, NAVAIR and Flight Test Centers). These specifications are separated into the following sub-categories:

- a. Characteristics -
 - Number of Crew
 - Date of First Flight
 - Aircraft Wetted Area
 - Fuselage Volume
 - Wing Loading
 - Carrier Capable
 - Number of Avionics Boxes
 - Number of Engines
 - Number of Store Stations
 - Thrust

- b. Ratios/Factors -
 - Limit Load Factor
 - Ultimate Load Factor
 - Empty Weight Divided by
Structure Weight

Empty Weight Divided by _____

Aircraft Volume

Gross Takeoff Weight Divided by

Structure Weight

c. Weight -

Structure Weight

Airframe Unit Weight

Empty Weight

Gross Takeoff Weight

Uninstalled Avionics Weight

Installed Avionics Weight

Maximum Structural Store Weight.

d. Performance -

Maximum Speed at Optimum Alt

Maximum Speed at Sea Level

Cruise Speed

Combat Ceiling

Service Ceiling

Combat Radius

The complete data structure listing of both the dependent and independent variables are contained in Appendix C (DATA STRUCTURE).

3. Statistical Analysis Data Format

Multiple linear and non linear regression were performed. The process started by developing correlation matrices and then selecting initial independent variables with the highest correlation relating to the dependent variables and low inter-variable correlation with other

independent variables. The regression procedure fits a model relating one dependent variable to one or more independent variables by minimizing the sum of the squares of the residuals for the fitted line. Linear, multiplicative and exponential models were used. In the multiplicative and exponential models, the dependent variable is first transformed by taking its natural logarithms. Then, the model parameters are estimated. The results are then plotted using the fitted lines.

B. EVALUATION OF DATA

1. Statistical Value of the Data

The data available for analysis are given in Appendix D. During the screening process, it was determined that only Engineering hours and Total hours cost elements within the Contractor Flight Test WBS sub-category contained sufficient data points to permit statistically valid analysis. Although much of the Static Test, Fatigue Test and Wind Tunnel Test data were consistent and complete for several aircraft, there were not enough data reported in these sub-categories to lend statistical significance for the use of these cost elements as dependent variables.

The data representing both dependent and independent variables were entered into a data base to facilitate analysis and grouping of the data. The specific data points available for analysis in this study are represented in

Appendix E. Due to the proprietary nature of the data, the presence of data is represented by an 'XX' corresponding to a the applicable cost element or physical/performance characteristic.

NAVAIR supplied standardized data from historical records. This data was used to validated some of the labor hours provided by Defense Contractors. Not all of this data was able to be standardized as discussed in Chapter I. However, it was determined that this data should be included so that initial analysis could be conducted with the largest possible sample size. It is envisioned that NAVAIR will continue further collection and standardization of this data so that more definitive statistical analysis can be accomplished as data becomes available.

C. ANALYSIS OF COST DRIVERS

As independent variables were initially evaluated for consideration as cost drivers, a one-sample analysis was performed to indicate data consistency (Statgraphics, 1986 p. 11-2). A histogram plot of variables with greater than ten data points was developed. This enabled an analysis of both data groupings and variable comparison of physical/performance characteristics. The resulting one-sample analysis and histograms are contained in Appendix F.

All of the independent variables were considered for potential analysis. Several were evaluated as not having

sufficient data points required for successful multiple regression techniques. The following cost drivers were considered to have the most significant impact for cost estimation modeling: Number of Crew (CREW), Date of First Flight (FF), Wing Loading (WL), Carrier Qualified (CQ), Number of Engines (ENG), Thrust, Empty Weight Divided by Structure Weight (WEOWS or WE/WS), Gross Takeoff Weight Divided by Structure Weight (GTOWOWS or GTOW/WS), Structure Weight (WS), Empty Weight (WE), Gross Takeoff Weight (GTOW), Uninstalled Avionics Weight (WAVU), Installed Avionics Weight (WAVI), Maximum Speed at Optimum Altitude (VMAXA), Maximum Speed at Sea Level (VMAXS), Cruise Speed (VCRUISE), Combat Ceiling (CBCEIL), Service Ceiling (SERCEIL) and combinations of the above.

D. DEVELOPMENT OF COST DRIVER MODELS

Both stepwise least-squares procedures and single step multiple regression techniques were used to determine the best cost driver models. All of the potential independent variables were tested with respect to dependent variables of Contractor Flight Test Engineering and Total direct labor hours. During the initial regression, a F-ratio of 4.0 was used as a threshold for inclusion of independent variables in the equation. Past historical studies showed that certain particular variables were not determined to influence the cost (Rand, 1975, p.16). However, we

eliminated the independent variables based solely on their statistical insignificance. The multiple-regression package used calculates the usual statistical measures of fit and provides plots of the fit. This package eliminates observations with missing data points thereby decreasing the sample size for analysis. These results are shown with the development of each equation in APPENDIX G. In selecting preferred equations, a high coefficient of determination (R^2), the F statistic for tests concerning the equality of the independent variables standard deviations, and the independent T values are the basis for variables initially being included in the regression. Both linear and logarithmic regression were used. Although logarithmic regression minimizes relative errors, some extremely valuable linear equations were found which had as good if not better statistical significance.

1. Contractor Flight Test Total Labor Hours

a. Weight and Speed Variables

The independent variables initially used with the Total Hours cost element were selected from the outcomes of previous studies and expert opinion, in this area, focusing on aircraft weight and speed. All variables of weight and speed, including ratios of both, were evaluated as potential cost drivers. It was found that the non-availability of complete data created a wide variation in the outcomes of the analysis. With a large sample size, the

statistical significance of the equation was less than that of one with a small sample size.

Utilizing only two independent variables--weight and speed--the following log-linear equation resulted:

EQUATION 1 (Refer to pp. 184, 185)

$$\text{TOTALHRS} = -1.64 (\text{VMAXA})^{1.67} (\text{WEOWS})^{-2.89}$$

$$R^2 = .59$$

$$F\text{-Ratio} = 11.56$$

19 Observations

Utilizing stepwise regression, including all the weight, speed and weight ratio variables, the most conclusive relationship developed, resulting in the following log-linear equation and relating statistics:

EQUATION 2 (Refer to pp. 186, 187)

$$\text{TOTALHRS} = -10.89 (\text{WS})^{.99} (\text{VMAXS})^{1.47}$$

$$R^2 = .95$$

$$F\text{-Ratio} = 69$$

10 Observations including: A-10, A-4, A-5, A-6,
F-14, F-15, F-4, F/A-18, S-3, T-38

Both of these relationships are statistically sound. What also must be considered is the observation size which was reduced by the inclusion of other independent variables with less data availability.

b. Consideration of Other Variables

As the other potential cost drivers were also considered, several variables emerged as being consistently reliable. These included characteristics, performance and avionics weight factors. Interestingly, avionics weight emerged as particularly significant independent variable when used as a percentage factor of either Aircraft Structure Weight (WS) or Empty Weight (WE). This component provided a sizing factor for avionics that provided an easy comparison across all types of aircraft. The integration of avionics accounts for a large number of direct labor hours in the Contractor Flight Test effort. This allows for consideration of avionics as an important cost driver. In the past, avionics was overlooked. It was only considered as a portion of total airframe weight.

With these variables considered, the analysis yielded the following estimated equation:

EQUATION 3 (Refer to pp. 196, 197)

$$\text{TOTALHRS} = -6726.84 + 2.33 (\text{VMAXA}) + 35.22 (\text{WL})$$

$$+ 97.29 (\text{WE/WAVI}) + .13 (\text{WE})$$

$$R^2 = .95$$

$$F\text{-Ratio} = 36.4$$

12 Observations

As more physical and performance characteristics were introduced, the sample size evaluated through stepwise multiple regression decreased again due to missing data

points. This small sample size consisted of a more homogeneous grouping of aircraft by type and weight (<100,000 lbs.). The evaluation of this sample grouping with more independent variables yielded a statistically significant result. The following was obtained from the analysis:

EQUATION 4 (Refer to pp. 220, 221)

$$\text{TOTALHRS} = 6.87 (\text{VMAXA})^{.70} (\text{WS/WAVI})^{18.75} (\text{WAVU})^{2.43} (\text{GTOW})^{-17.03} (\text{GTOW/WS})^{17.13}$$

$$R^2 = .98$$

$$\text{F-Ratio} = 62.1$$

11 Observations

EQUATION 5 (Refer to pp. 222, 223)

$$\text{TOTALHRS} = -6.32 (\text{VMAXA})^{.82} (\text{WS/WAVI})^{1.12}$$

$$R^2 = .92$$

$$\text{F-Ratio} = 57.1$$

13 Observations

EQUATION 6 (Refer to pp. 224, 225)

$$\text{TOTALHRS} = -6765.36 + 2.34 (\text{VMAXA}) + 30.94 (\text{WL}) + 101.32 (\text{WS/WAVI}) + 0.15 (\text{WE})$$

$$R^2 = .95$$

$$\text{F-Ratio} = 41.5$$

13 Observations

2. Contractor Flight Test Engineering Hours

a. Weight and Speed Variables

The independent variables used with the Engineering direct labor hours cost element were selected with the same criteria and constraints as in Total Hours.

Utilizing only two independent variables--weight and speed--the following log-linear equation were derived:

EQUATION 7 (Refer to pp. 230, 231)

$$\text{ENGHRS} = 0.23 (\text{VMAXA})^{1.29} (\text{WEOWS})^{-2.67}$$

$$R^2 = .48$$

$$\text{F-Ratio} = 6.8$$

18 Observations

Utilizing stepwise regression, including all the weight, speed and weight ratio variables, the most conclusive relationship emerged, resulting in the following linear equations and related statistics:

EQUATION 8 (Refer to pp. 232, 233)

$$\text{ENGHRS} = -664.71 + 0.23 (\text{WS}) + 1.73 (\text{VMAXA}) - 0.04 (\text{GTOW})$$

$$R^2 = .91$$

$$\text{F-Ratio} = 25.02$$

11 Observations including: A-10, A-4, A-5, A-6,
AV-8B, F-14, F-15, F-4, F/A-18, S-3, T-38.

Both of these relationships are statistically valid with the considerations as mentioned with Total Hours.

b. Consideration of Other Variables

The same independent variables used in Total Hours were evaluated. With these variables considered, the following relationship of cost drivers yielded the following results:

EQUATION 9 (Refer to pp. 236, 237)

$$\text{ENGHRS} = 165.13 + 3.21 (\text{VMAXA}) + 67.20 (\text{FF}) \\ - 2143.66 (\text{THRUST/WE})$$

$$R^2 = .71$$

$$\text{F-Ratio} = 10.6$$

17 Observations

A smaller sample size of aircraft with Gross Takeoff Weight less than 100,000 lbs. resulted in the following analysis:

EQUATION 10 (Refer to pp. 242, 243)

$$\text{ENGHRS} = - 574.34 + 0.72 (\text{VMAXA}) + 7.85 (\text{WL}) \\ + 29.2 (\text{WS/WAVI}) + 0.37 (\text{WAVU}) + 0.22 (\text{WE}) \\ - 0.07 (\text{GTOW}) - 18.22 (\text{FF}) - 706.75 (\text{CREW})$$

$$R^2 = .998$$

$$\text{F-Ratio} = 170.17$$

11 Observations including: A-10, A-4, A-5, A-6, AV-8B, F-14, F-15, F-4, F/A-18, S-3, T-38.

EQUATION 11 (Refer to pp. 244, 245)

$$\text{ENGHRS} = 1.1 (\text{VMAXA})^{.89} (\text{WS/WAVI})^{2.24} (\text{GTOW})^{-1.52}$$

$$R^2 = .79$$

$$\text{F-Ratio} = 12.7$$

14 Observations

E. SUMMARY

Contractor Flight Test Total direct labor hours proved to be a more stable dependent variable than Engineering direct labor hours. The best cost drivers were determined using a sample size with Gross Takeoff Weight restricted to less than 100,000 lbs. In most relationships, the avionics weight percentage factor emerged as particularly significant independent variable.

No best cost model can be recommended at this point due to lack of data causing variance in observation size between cost estimating relationships.

V. SUMMARY

The purpose of this research was to review the current cost estimating structure in Aircraft Systems Test and Evaluation and provide better cost estimation models, with particular emphasis on Contractor Flight Test elements.

A. SUMMARY OF RESULTS

As a result of extensive field investigation, data collection, database design and implementation and parametric modeling, the major findings of this research are enumerated below:

1. Propositions for a better implementation of the CCDR

The Contractor cost Data Reporting (CCDR) system was established to provide the DOD with continual ability to develop and use valid cost estimates (Chapter II, Volume I). However, from a cost estimation standpoint, current practices of the CCDR system suffer from numerous shortcomings. First, CCDR reports have often been inconsistent across contractors due to ambiguity in defining cost elements. Second, dual source and sub-contracts are more than frequently granted. Contractors habitually cannot, or do not want to cooperate with other contractors. Third, cost data have not been reported regularly enough for time-series analysis.

This research proposed a number of courses of action that could at least correct some of these shortcomings for more meaningful and accurate data analysis: (1) factor the Work Breakdown Structure (WBS) into lower levels, (2) provide time-phased data reporting, and (3) implement a well-defined CCDR data base system (Chapter III, Volume I). Furthermore, this study suggested an eventual restructurization of the WBS by revising the hierarchy of the WBS elements.

2. Elicitation of experts' opinion to identify the most important cost-drivers in System Test and Evaluation

Past scientific studies have primarily considered weight, speed and the number of aircraft as the most statistically significant cost estimators. Due to technological innovations, other cost drivers have recently emerged. This study conducted a nation-wide field investigation. The following factors were identified as essential cost drivers: mission, aircraft weight, aircraft speed, avionics complexity, software, power supplies, data reduction, number of test aircraft, delivery schedule, joint contractor/ military testing and political environment (Chapter V, Volume I).

The interviews with defense contractors and military test centers also resulted in numerous recommendations for improvement of the current process of System Test and Evaluation. Among these, the following strategies have triggered substantial interest: (1) use of simulation in

software testing, (2) use of structured analysis and design methodology to develop software, (3) implementation of distributed systems using parallel process, (4) development of more efficient power units to reduce weight and volume of avionics of aircraft, (5) reduction of the required number of test aircraft, and (6) delivery of aircraft in a block (phase program). In addition, in a longer perspective, further studies are necessary to determine if joint testing is producing the highest quality and most cost-efficient aircraft.

3. Survey of Current Data and Structure Maintained by Defense Contractors and Military Institutions

As an effort to gather data for cost modeling, this research gathered data from defense contractors and military test centers. Data were provided by Boeing, Rockwell International at Columbus, Fairchild, Grumman Aerospace Corporation, Rockwell International at Los Angeles, LTV Aerospace and Defense, General Dynamics, McDonnell Douglas, Lockheed Georgia, Lockheed California, the Naval Air Test Center, the Air Force Test Flight Center, and NAVAIR. It was found that some data were better and more complete than others. It was also found that some data requested could not be obtained (Chapter I, Volume II).

4. Survey of Parametric Techniques for Estimating Cost of Aircraft Systems

Avionics and software costs have emerged as growing elements in the acquisition of new aircraft systems.

Despite the difference in samples and statistical approaches each study used for estimation, the two primary aircraft characteristics or variables/drivers for airframe cost remained weight and speed.

The need for identification of more reliable independent variables, that would provide statistical stability for cost estimation, was a salient issue addressed in these econometric estimations. The structure and implementation of acquisition record keeping systems to provide the depth and accuracy of cost data for analysis were also considered an important focal point.

5. Development of a Cost Estimation Relational Data Base System

The current NAVAIR system does not facilitate either easy access to, amendment of, or rapid manipulation of the stored data for cost estimation due to heavy use by all branches of NAVAIR. The need for separate applications and more natural access to the data became evident in discussions with the sponsor. This need must also be filled by a system that is MS-DOS compatible and will integrate with current on-line applications and other projected applications.

Given that the data base would be used in a Local Area Network (LAN) MIS office environment, a desk top-based DBMS with advanced user interface and full transfer capabilities to the VAX-780s would be ideal was implemented using dBase III Plus (Chapter III, Volume II).

6. Development of New Parametric Cost Estimation Models

Contractor Flight Test Total direct labor hours proved to be a more stable dependent variable than Engineering direct labor hours. The best cost drivers were determined using a sample size with Gross Takeoff Weight restricted to less than 100,000 lbs. In most relationships, the avionics weight percentage factor emerged as a particularly significant independent variable (Chapter IV, Volume II).

B. SUGGESTIONS FOR FUTURE RESEARCH

The conclusions developed through the statistical analysis are extensions and improvements on the previous studies cited. As more data are collected, standardized and inputted the equations developed should increase in accuracy. The rapidly changing "state of the art" in avionics and its commensurate effects on cost estimation and analysis of aircraft systems that have been previously identified, continues to be of concern. This effect on cost estimation will not be solved until a method of collection of engineering and total hours in the WBS and CCDR is adopted at lower levels than previously used. This paucity of data hampered this research and undoubtedly will hamper future research and consequently the accuracy of estimation on proposed aircraft. The groundwork had been laid, this takes that groundwork but one step further. It is hoped

that this thesis will be of value to both the public and private sectors. The challenge to future research lies in the adoption of measures to insure clarity across both contractor and government lines. Then, precision and accuracy can be insured.

APPENDIX A: DATA DICTIONARY

AIRCRAFT	=	MODEL + MISSION + MFG
AVBX	=	Number of avionics boxes in aircraft system
AWA	=	Aircraft wetted area
CBT_CEIL	=	Maximum rated combat ceiling
CBT_RADIUS	=	Radius of operation for combat purposes in miles
CHAR	=	MODEL + CREW + FIRST_FLT + AWA + VOL + WL + CQ + AVBX + ENG + SSTA + THRUST
CREW	=	Number of crew members
CQ	=	Is the aircraft carrier qualified
ENG	=	Number of engines
ENGHR	=	Number of engineering hours spent on flight testing
FATIGUE	=	MODEL + FTMOS + FTHRS + FENGHRS + FMFGHRS + FTOOLHR + FQCHRS + FILSHRS + FTOTHR
FENGHRS	=	Number of engineering hours spent on fatigue testing
FILSHRS	=	Number of integrated logistic support hours spent on fatigue testing
FIRST_FLT	=	Date of first flight since 1952
FLIGHT	=	MODEL + FLTHRS + TEVTS + ENGHR + MFGHR + TOOLHR + QCHR + ILSHR + TOTHR
FLTHRS	=	Number of hours the aircraft spent in actual flight testing
FMFGHRS	=	Number of manufacturing hours spent on fatigue testing
FQCHRS	=	Number of quality control hours spent on fatigue testing
FTHRS	=	Number of hours the aircraft spent in actual fatigue testing

FTMOS = Number of months the aircraft underwent fatigue testing
FTOOLHR = Number of tooling hours spent on fatigue testing
FTOTHR = Total number of hours spent on fatigue testing
GTOW = Gross takeoff weight
GTOW/WS = Gross takeoff weight/Structure weight
ILSHR = Number of integrated logistic support hours spent on flight testing
LLF = Load limit factor
MAXWSS = Maximum structure stores weight
MFG = Manufacturer's Name
MFGHR = Number of manufacturing hours spent on flight testing
MISSION = [ASW | Attack | Bomber | Early War | EW
Fighter | Patrol | Recon | Trainer |
Transport]
MODEL = Aircraft's model number
PERFORMA = MODEL + THRUST + VMAXA + VMAXS + VCRUISE +
CBT_CEIL + SER_CEIL + CBT_RADIUS
QCHR = Number of quality control hours spent on flight testing
SENGHRS = Number of engineering hours spent on static testing
SER_CEIL = Maximum rated ceiling
SILSHRS = Number of integrated logistic support hours spent on static testing
SMFGHRS = Number of manufacturing hours spent on static testing
SQCHRS = Number of quality control hours spent on static testing

SSTA = Number of aircraft store stations

STATIC = MODEL + STMOS + SENGHRS + SMFGHRS + STOOLHR + SQCHRS + SILSHRS + STOTHR

STMOS = Number of months the aircraft underwent static testing

STOOLHR = Number of tooling hours spent on static testing

STOTHR = Total number of hours spent on static testing

TEVTS = Number of separate specific tests performed during the flight testing

THRUST = [Pounds of Thrust | Shaft Horsepower | Horsepower]

TOOLHR = Number of tooling hours spent on flight testing

TOTHR = Total number of hours spent on flight testing

ULF = Unlimited load factor

VCRUISE = Normal cruising speed in knots

VMAXA = Maximum speed at optimum altitude

VMAXS = Maximum speed at sea level

VOL = Fuselage volume

WA = Aircraft unit weight

WAVI = Installed avionics weight

WAVU = Uninstalled avionics weight

WE = Empty weight of the aircraft

WE/VOL = Empty weight/Volume

WE/WS = Empty weight /Structure weight

WEIGHT = MODEL + WS + WA + WE + GTOW + WAVU + WAVI + MAXWSS

WENGHRS = Number of engineering hours spent on wind tunnel testing
WILSHRS = Number of integrated logistic support hours spent on wind tunnel testing
WIND = MODEL + WTMOS + WTHRS + WENGHRS + WMFGHRS + WTOOLHR + WQCHRS + WILSHRS + WTOTHRS
WL = Wing strength measured in pounds per square foot
WMFGHRS = Number of manufacturing hours spent on wind tunnel testing
WQCHRS = Number of quality control hours spent on wind tunnel testing
WS = Structure weight
WTHRS = Number of hours the aircraft spent in actual wind tunnel testing
WTMOS = Number of months the aircraft underwent wind tunnel testing
WTOOLHR = Number of tooling hours spent on wind tunnel testing
WTOTHRS = Total number of hours spent on wind tunnel testing

APPENDIX B: PROGRAMS

* Program...: ADDMOD.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to add models to the basic files.
* Date.....: 12/05/86
* I/O Files: AIRCRAFT.DBF, CHAR.DBF, FATIGUE.DBF, FLIGHT.DBF,
* PERFORMA.DBF, RATIOS.DBF, STATIC.DBF,
* WEIGHT.DBF, WIND.DBF
* Called By: TIGER.PRG, MODMENU.PRG
* Calls Mod: NONE
* Reserved.: selectnum
* Variables: NONE

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

SET COLOR TO GR+/B+
* ---Display menu options, centered on the screen.
* draw menu border and print heading

CLEAR
 USE ADDFILE
 APPEND
 CLEAR

@ 12,22 SAY [ADDING MODELS TO ALL BASIC FILES.....]

 USE AIRCRAFT
 APPEND FROM ADDFILE
 SORT ON MODEL TO TEMPSORT.DBF
 CLOSE ALL
 ERASE AIRCRAFT.DBF
 RENAME TEMPSORT.DBF TO AIRCRAFT.DBF

 USE CHAR
 APPEND FROM ADDFILE
 SORT ON MODEL TO TEMPSORT.DBF
 CLOSE ALL
 ERASE CHAR.DBF
 RENAME TEMPSORT.DBF TO CHAR.DBF

 USE PERFORMA
 APPEND FROM ADDFILE
 SORT ON MODEL TO TEMPSORT.DBF
 CLOSE ALL
 ERASE PERFORMA.DBF
 RENAME TEMPSORT.DBF TO PERFORMA.DBF

USE WEIGHT
APPEND FROM ADDFILE
SORT ON MODEL TO TEMPSORT.DBF
CLOSE ALL
ERASE WEIGHT.DBF
RENAME TEMPSORT.DBF TO WEIGHT.DBF

USE RATIOS
APPEND FROM ADDFILE
SORT ON MODEL TO TEMPSORT.DBF
CLOSE ALL
ERASE RATIOS.DBF
RENAME TEMPSORT.DBF TO RATIOS.DBF

USE FATIGUE
APPEND FROM ADDFILE
SORT ON MODEL TO TEMPSORT.DBF
CLOSE ALL
ERASE FATIGUE.DBF
RENAME TEMPSORT.DBF TO FATIGUE.DBF

USE FLIGHT
APPEND FROM ADDFILE
SORT ON MODEL TO TEMPSORT.DBF
CLOSE ALL
ERASE FLIGHT.DBF
RENAME TEMPSORT.DBF TO FLIGHT.DBF

USE STATIC
APPEND FROM ADDFILE
SORT ON MODEL TO TEMPSORT.DBF
CLOSE ALL
ERASE STATIC.DBF
RENAME TEMPSORT.DBF TO STATIC.DBF

USE WIND
APPEND FROM ADDFILE
SORT ON MODEL TO TEMPSORT.DBF
CLOSE ALL
ERASE WIND.DBF
RENAME TEMPSORT.DBF TO WIND.DBF

* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst

* READ
* SET CONFIRM ON
CLEAR
USE ADDFILE
ZAP

RETURN

* EOF: ADDMOD.PRG

^Z

```

* Program...: BROANY.PRG
* Author....: TUNG'S TIGERS
* Purpose...: Allows the user to browse any current database file
* Date.....: 01/01/80
* I/O Files: Any database file selected by user.
* Called By: TIGER.PRG, BROWMENU.PRG
* Calls Mod: PRINT.PRG
* Reserved.: selectnum
* Variables: NONE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```

DO WHILE .T.
SET COLOR TO GR+/B+
  * ---Display menu options, centered on the screen.
  *   draw menu border and print heading

```

```

CLEAR
@ 2, 0 TO 12,79 DOUBLE
@ 3,15 SAY [B R O W S E   C U R R E N T   F I L E S   M E N U ]
@ 4,1 TO 4,78 DOUBLE
* ---display detail lines
@ 7,31 SAY [1. BROWSE ANY FILE]
@ 8,31 SAY [2. LIST FILES]
@ 10, 31 SAY '0. EXIT'
STORE 0 TO selectnum
@ 12,33 SAY " select      "
@ 12,42 GET selectnum PICTURE "9" RANGE 0,2

```

```

READ

```

```

DO CASE

```

```

  CASE selectnum = 0
    SET TALK ON
    CLEAR ALL
    RETURN

```

```

  CASE selectnum = 1
    * DO BROWSE ANY FILE
    ACCEPT [Enter filename....] to BROFILE
    USE &BROFILE
    GO TOP
    BROWSE
    * SET CONFIRM OFF
    * STORE ' ' TO wait_subst
    * @ 23,0 SAY 'Press any key to continue...' GET wait_subst
    * READ
    * SET CONFIRM ON

```

```
CASE selectnum = 2
* DO LIST FILES
DO PRINT
DIR *.DBF
SET PRINT OFF
SET CONFIRM OFF
STORE ' ' TO wait_subst
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
READ
SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: BROANY.PRG

^Z

```

* Program...: BROBASIC.PRG
* Author...: TUNG'S TIGERS
* Purpose...: This option allows the user to browse the basic data
*             files.
* Date.....: 12/06/86
* I/O Files: AIRCRAFT.DBF, CHAR.DBF, FATIGUE.DBF, FLIGHT.DBF,
*             PERFORMA.DBF, RATIOS.DBF, STATIC.DBF,
*             WEIGHT.DBF, WIND.DBF
* Called By: TIGER.PRG, BROWMENU.PRG
* Calls Mod: NONE
* Reserved.: selectnum
* Variables: NONE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```

DO WHILE .T.

```

```

SET COLOR TO GR+/B+

```

- * ---Display menu options, centered on the screen.
- * draw menu border and print heading

```

CLEAR

```

```

@ 2, 0 TO 19,79 DOUBLE

```

```

@ 3,18 SAY [B R O W S E   B A S I C   F I L E S   M E N U]

```

```

@ 4,1 TO 4,78 DOUBLE

```

```

* ---display detail lines

```

```

@ 7,31 SAY [1. AIRCRAFT]

```

```

@ 8,31 SAY [2. CHARACTERISTICS]

```

```

@ 9,31 SAY [3. PERFORMANCE]

```

```

@ 10,31 SAY [4. RATIOS/FACTORS]

```

```

@ 11,31 SAY [5. WEIGHT]

```

```

@ 12,31 SAY [6. FATIGUE TEST]

```

```

@ 13,31 SAY [7. FLIGHT TEST]

```

```

@ 14,31 SAY [8. STATIC TEST]

```

```

@ 15,31 SAY [9. WIND TUNNEL TEST]

```

```

@ 17, 31 SAY '0. EXIT'

```

```

STORE 0 TO selectnum

```

```

@ 19,33 SAY " select      "

```

```

@ 19,42 GET selectnum PICTURE "9" RANGE 0,9

```

```

READ

```

```

DO CASE

```

```

CASE selectnum = 0

```

```

SET TALK ON

```

```

CLEAR ALL

```

```

RETURN

```

```

CASE selectnum = 1
* DO AIRCRAFT
  USE AIRCRAFT
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 2
* DO CHARACTERISTICS
  USE CHAR
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 3
* DO PERFORMANCE
  USE PERFORMA
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 4
* DO RATIOS/FACTORS
  USE RATIOS
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 5
* DO WEIGHT
  USE WEIGHT
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

```

```
CASE selectnum = 6
* DO FATIGUE TEST
  USE FATIGUE
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON
```

```
CASE selectnum = 7
* DO FLIGHT TEST
  USE FLIGHT
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON
```

```
CASE selectnum = 8
* DO STATIC TEST
  USE STATIC
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON
```

```
CASE selectnum = 9
* DO WIND TUNNEL TEST
  USE WIND
  GO TOP
  BROWSE
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: BROBASIC.PRG

^Z

```

* Program...: BROWMENU.PRG
* Author...: TUNG'S TIGERS
* Purpose...: This option allows the user to select the browse
*             option he wants
* Date.....: 01/01/80
* I/O Files: NONE
* Called By: TIGER.PRG
* Calls Mod: BROBASIC.PRG, BROANY.PRG
* Reserved.: selectnum
* Variables: NONE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```

DO WHILE .T.

```

```

SET COLOR TO GR+/B+

```

```

* ---Display menu options, centered on the screen.
*   draw menu border and print heading

```

```

CLEAR

```

```

@ 2, 0 TO 12,79 DOUBLE

```

```

@ 3,24 SAY [B R O W S E   F I L E S   M E N U]

```

```

@ 4,1 TO 4,78 DOUBLE

```

```

* ---display detail lines

```

```

@ 7,29 SAY [1. BROWSE BASIC FILES]

```

```

@ 8,29 SAY [2. BROWSE ANY FILES]

```

```

@ 10, 29 SAY '0. EXIT'

```

```

STORE 0 TO selectnum

```

```

@ 12,33 SAY " select      "

```

```

@ 12,42 GET selectnum PICTURE "9" RANGE 0,2

```

```

READ

```

```

DO CASE

```

```

CASE selectnum = 0

```

```

    SET TALK ON

```

```

    CLEAR ALL

```

```

    RETURN

```

```

CASE selectnum = 1

```

```

* DO BROWSE BASIC FILES

```

```

    DO BROBASIC

```

```

* SET CONFIRM ON

```

```

* STORE ' ' TO wait_subst

```

```

* @ 23,0 SAY 'Press any key to continue...' GET wait_subst

```

```

* READ

```

```

* SET CONFIRM OFF

```

```
      CASE selectnum = 2
      * DO BROWSE ANY FILES
        DO BROANY
      *   SET CONFIRM OFF
      *   STORE ' ' TO wait_subst
      *   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
      *   READ
      *   SET CONFIRM ON

      ENDCASE

      ENDDO T

      RETURN

      * EOF: BROWMENU.PRG

      ^Z
```

```

* Program...: CQUERYMENU.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to create ad hoc queries.
* Date.....: 12/06/86
* I/O Files: ANY SELECTED BY USER
* Called By: TIGER.PRG
* Calls Mod: PRINT.PRG
* Reserved.: selectnum
* Variables: NONE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+
```

```

* ---Display menu options, centered on the screen.
*   draw menu border and print heading
CLEAR

```

```
@ 2, 0 TO 12,79 DOUBLE
```

```
@ 3,24 SAY [CREATE QUERY MENU]
```

```
@ 4,1 TO 4,78 DOUBLE
```

```
* ---display detail lines
```

```
@ 7,31 SAY [1. CREATE NEW QUERY]
```

```
@ 8,31 SAY [2. LIST QUERY FILES]
```

```
@ 10, 31 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 12,33 SAY " select "
```

```
@ 12,42 GET selectnum PICTURE "9" RANGE 0,2
```

```
READ
```

```
DO CASE
```

```
  CASE selectnum = 0
```

```
    SET TALK ON
```

```
    CLEAR ALL
```

```
    RETURN
```

```
  CASE selectnum = 1
```

```
    * DO CREATE NEW QUERY
```

```
    CREATE QUERY
```

```
    * SET CONFIRM OFF
```

```
    * STORE ' ' TO wait_subst
```

```
    * @ 23,0 SAY 'Press any key to continue...' GET wait_subst
```

```
    * READ
```

```
    * SET CONFIRM ON
```

```
CASE selectnum = 2
* DO LIST QUERY FILES
DO PRINT
DIR *.QRY
SET PRINT OFF
SET CONFIRM OFF
STORE ' ' TO wait_subst
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
READ
SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: CQUERYMENU.PRG

^Z

```

* Program...: CREPORTMENU.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to create ad hoc reports.
* Date.....: 12/06/86
* I/O Files: ANY SELECTED BY USER
* Called By: TIGER.PRG
* Calls Mod: PRINT.PRG
* Reserved.: selectnum
* Variables: NONE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+
```

```
* ---Display menu options, centered on the screen.
```

```
* draw menu border and print heading
```

```
CLEAR
```

```
@ 2, 0 TO 12,79 DOUBLE
```

```
@ 3,23 SAY [C R E A T E   R E P O R T   M E N U]
```

```
@ 4,1 TO 4,78 DOUBLE
```

```
* ---display detail lines
```

```
@ 7,26 SAY [1. CREATE NEW REPORT]
```

```
@ 8,26 SAY [2. LIST EXISTING REPORT FILES]
```

```
@ 10, 26 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 12,33 SAY " select      "
```

```
@ 12,42 GET selectnum PICTURE "9" RANGE 0,2
```

```
READ
```

```
DO CASE
```

```
  CASE selectnum = 0
```

```
    SET TALK ON
```

```
    CLEAR ALL
```

```
    RETURN
```

```
  CASE selectnum = 1
```

```
    * DO CREATE NEW REPORT
```

```
    CREATE REPORT
```

```
    * SET CONFIRM OFF
```

```
    * STORE ' ' TO wait_subst
```

```
    * @ 23,0 SAY 'Press any key to continue...' GET Wait_subst
```

```
    * READ
```

```
    * SET CONFIRM ON
```

```
CASE selectnum = 2
* DO LIST EXISTING REPORT FILES
DO PRINT
DIR *.FRM
SET PRINT OFF
SET CONFIRM OFF
STORE ' ' TO wait_subst
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
READ
SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: CREPORTMENU.PRG

^Z

```

* Program...: DELREC.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to delete records from nine basic files.
* Date.....: 12/05/86
* I/O Files: The nine basic files.
* Called By: TIGER.PRG, MODREC.PRG
* Calls Mod: NONE
* Reserved.: selectnum
* Variables: DEMODEL, WAITPACK

```

```

SET TALK OFF
SET BELL ON
SET STATUS ON
SET ESCAPE ON
SET CONFIRM ON

```

```

DO WHILE .T.
SET COLOR TO W+/R+,GR+/B+,R+
  * ---Display menu options, centered on the screen.
  *   draw menu border and print heading

```

```

CLEAR

```

```

STORE " " TO DELETEMODEL
ACCEPT "ENTER AIRCRAFT MODEL ..." TO DELETEMODEL

```

```

USE AIRCRAFT
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
SET COLOR TO GR+/R+
WAIT [DELETE MARKED AIRCRAFT RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
  PACK
ELSE RECALL ALL
ENDIF

```

```

USE CHAR
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED CHARACTER RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
  PACK
ELSE RECALL ALL
ENDIF

```

```

USE PERFORMA
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED PERFORMANCE RECORDS? (Y/N)] TO
WAITPACK
IF UPPER(WAITPACK)="Y"
  PACK
ELSE RECALL ALL
ENDIF

```

USE RATIOS
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED RATIOS RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
PACK
ELSE RECALL ALL
ENDIF

USE WEIGHT
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED WEIGHT RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
PACK
ELSE RECALL ALL
ENDIF

USE FATIGUE
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED FATIGUE RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
PACK
ELSE RECALL ALL
ENDIF

USE FLIGHT
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED FLIGHT RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
PACK
ELSE RECALL ALL
ENDIF

USE STATIC
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED STATIC RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
PACK
ELSE RECALL ALL
ENDIF

USE WIND
DELETE FOR MODEL=DELETEMODEL
STORE " " TO WAITPACK
WAIT [DELETE MARKED WIND RECORDS? (Y/N)] TO WAITPACK
IF UPPER(WAITPACK)="Y"
PACK
ELSE RECALL ALL
ENDIF

```
*      SET CONFIRM OFF
*      STORE ' ' TO wait_subst
*      @ 23,0 SAY "Press any key to continue..." GET wait_subst
*      READ
*      SET CONFIRM ON
```

CLEAR

RETURN

ENDDO T

* EOF: DELREC.PRG

^Z

```

* Program...: DELRMENU.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Caution user concerning permanently deleting records
* Date.....: 02/20/87
* I/O Files: NONE
* Called By: TIGER.PRG, MODMENU.PRG
* Calls Mod: DELREC.PRG
* Reserved.: selectnum

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+,GR+/R+,R+
```

```

* ---Display menu options, centered on the screen.
*   draw menu border and print heading

```

```
CLEAR
```

```
@ 2, 0 TO 11,79 DOUBLE
```

```
@ 3,27 SAY [D E L E T E   R E C O R D S]
```

```
@ 4,1 TO 4,78 DOUBLE
```

```
* ---display detail lines
```

```
@ 7, 7 SAY [1. YOU ARE ABOUT TO PERMANENTLY DELETE SELECTED]
```

```
@ 7, 55 SAY [RECORDS FROM FILES]
```

```
@ 9, 7 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 11,33 SAY " select      "
```

```
@ 11,42 GET selectnum PICTURE "9" RANGE 0,1
```

```
READ
```

```
DO CASE
```

```
  CASE selectnum = 0
```

```
    SET BELL ON
```

```
    SET TALK ON
```

```
    CLEAR ALL
```

```
    SET COLOR TO GR+/B+,GR+/R+,BG+
```

```
    RETURN
```

```
  CASE selectnum = 1
```

```
    * DO YOU ARE ABOUT TO PERMANENTLY DELETE SELECTED RECORDS
```

```
    * FROM FILES
```

```
    DO DELREC
```

```
    * @ 23,0 SAY 'Press any key to continue...' GET wait_subst
```

```
    * READ
```

```
    * SET CONFIRM ON
```

```
ENDCASE
```

```
ENDDO T
```

```
SET COLOR TO GR+/B+,GR+/R+,BG+
```

```
RETURN
```

```
* EOF: DELRMENU.PRG
```

```
^2
```

```

* Program...: EDITREC.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to edit the nine basic files.
* Date.....: 12/05/86
* I/O Files: AIRCRAFT.DBF, CHAR.DBF, FATIGUE.DBF, FLIGHT.DBF,
*           PERFORMA.DBF, RATIOS.DBF, STATIC.DBF, WEIGHT.DBF,
*           WIND.DBF
* Called By: TIGER.PRG, MODMENU.PRG
* Calls Mod: NONE
* Reserved.: selectnum
* Variables: NONE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```

DO WHILE .T.
SET COLOR TO GR+/B+
* ---Display menu options, centered on the screen.
*   draw menu border and print heading

```

```

CLEAR
@ 2, 0 TO 19,79 DOUBLE
@ 3,25 SAY [E D I T R E C O R D S M E N U]
@ 4,1 TO 4,78 DOUBLE
* ---display detail lines
@ 7,31 SAY [1. AIRCRAFT]
@ 8,31 SAY [2. CHARACTERISTICS]
@ 9,31 SAY [3. PERFORMANCE]
@ 10,31 SAY [4. RATIOS/FACTORS]
@ 11,31 SAY [5. WEIGHT]
@ 12,31 SAY [6. FATIGUE TEST]
@ 13,31 SAY [7. FLIGHT TEST]
@ 14,31 SAY [8. STATIC TEST]
@ 15,31 SAY [9. WIND TUNNEL TEST]
@ 17, 31 SAY '0. EXIT'
STORE 0 TO selectnum
@ 19,33 SAY " select      "
@ 19,42 GET selectnum PICTURE "9" RANGE 0,9
READ

```

```

DO CASE

```

```

CASE selectnum = 0
SET TALK OFF
CLEAR ALL
RETURN

```

```

CASE selectnum = 1
* DO AIRCRAFT
  USE AIRCRAFT
  EDIT
*
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 2
* DO CHARACTERISTICS
  USE CHAR
  EDIT
*
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 3
* DO PERFORMANCE
  USE PERFORMA
  EDIT
*
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 4
* DO RATIOS/FACTORS
  USE RATIOS
  EDIT
*
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

CASE selectnum = 5
* DO WEIGHT
  USE WEIGHT
  EDIT
*
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON

```

```

CASE selectnum = 6
* DO FATIGUE TEST
  USE FATIGUE
  EDIT
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 7
* DO FLIGHT TEST
  USE FLIGHT
  EDIT
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 8
* DO STATIC TEST
  USE STATIC
  EDIT
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 9
* DO WIND TUNNEL TEST
  USE WIND
  EDIT
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

ENDCASE

ENDDO T

RETURN

* EOF: EDITREC.PRG

^Z

```

```

* Program...: JOINFILE.PRG
* Author....: TUNG'S TIGERS
* Purpose...: Allows user to join selected files.
* Date.....: 12/05/86
* I/O Files: Files as selected by user.
* Called By: TIGER.PRG
* Calls Mod: PRINT.PRG
* Reserved.: selectnum
* Variables: FILEONE, FILETWO, NEWFILE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```

DO WHILE .T.

```

```

SET COLOR TO GR+/B+

```

```

* ---Display menu options, centered on the screen.
*   draw menu border and print heading

```

```

CLEAR

```

```

@ 2, 0 TO 13,79 DOUBLE

```

```

@ 3,26 SAY [J O I N   F I L E S   M E N U]

```

```

@ 4,1 TO 4,78 DOUBLE

```

```

* ---display detail lines

```

```

@ 7,29 SAY [1. LIST EXISTING FILES]

```

```

@ 8,29 SAY [2. JOIN FILES]

```

```

@ 9,29 SAY [3. JOIN TO FORM SPECS]

```

```

@ 11, 29 SAY '0. EXIT'

```

```

STORE 0 TO selectnum

```

```

@ 13,33 SAY " select          "

```

```

@ 13,42 GET selectnum PICTURE "9" RANGE 0,3

```

```

READ

```

```

DO CASE

```

```

CASE selectnum = 0

```

```

SET TALK ON

```

```

CLEAR ALL

```

```

RETURN

```

```

CASE selectnum = 1

```

```

* DO LIST EXISTING FILES

```

```

DO PRINT

```

```

DIR *.DBF

```

```

SET PRINT OFF

```

```

SET CONFIRM OFF

```

```

STORE ' ' TO wait_subst

```

```

@ 23,0 SAY 'Press any key to continue...' GET wait_subst

```

```

READ

```

```

SET CONFIRM ON

```

CASE selectnum = 2

* DO JOIN FILES

ACCEPT [Enter filename 1...] TO FILEONE

ACCEPT [Enter filename 2...] TO FILETWO

ACCEPT [Enter new filename...] TO NEWFILE

SELECT A

USE &FILEONE

SELECT B

USE &FILETWO

JOIN WITH &FILEONE TO &NEWFILE FOR MODEL=A->MODEL

CASE selectnum = 3

* DO JOIN TO FORM SPECS

SELECT A

USE CHAR

SELECT B

USE AIRCRAFT

JOIN WITH CHAR TO TJOIN1 FOR MODEL=A->MODEL

SELECT A

USE PERFORMA

SELECT B

USE TJOIN1

JOIN WITH PERFORMA TO TJOIN2 FOR MODEL=A->MODEL

SELECT A

USE RATIOS

SELECT B

USE TJOIN2

JOIN WITH RATIOS TO TJOIN3 FOR MODEL=A->MODEL

SELECT A

USE WEIGHT

SELECT B

USE TJOIN3

JOIN WITH WEIGHT TO TJOIN4 FOR MODEL=A->MODEL

SELECT A

USE FATIGUE

SELECT B

USE TJOIN4

JOIN WITH FATIGUE TO TJOINS FOR MODEL=A->MODEL

SELECT A

USE FLIGHT

SELECT B

USE TJOINS

JOIN WITH FLIGHT TO TJOIN6 FOR MODEL=A->MODEL

```
SELECT A
USE STATIC
SELECT B
USE TJOIN6
JOIN WITH STATIC TO TJOIN7 FOR MODEL=A->MODEL
```

```
ERASE SPECS.DBF
SELECT A
USE WIND
SELECT B
USE TJOIN7
JOIN WITH WIND TO SPECS FOR MODEL=A->MODEL
```

```
CLOSE ALL
```

```
ERASE TJOIN1.DBF
ERASE TJOIN2.DBF
ERASE TJOIN3.DBF
ERASE TJOIN4.DBF
ERASE TJOIN5.DBF
ERASE TJOIN6.DBF
ERASE TJOIN7.DBF
```

```
* SET CONFIRM OFF
* STORE ' ' TO wait_subst
* @ 23,0 SAY 'Press any key to continue...' GET wait_subst
* READ
* SET CONFIRM ON
* SET STATUS ON
```

```
ENDCASE
```

```
ENDDO T
```

```
RETURN
```

```
* EOF: JOINFILE.PRG
```

```
"2
```

- Program...: LISANY.PRG
- Author....: TUNG'S TIGERS
- Purpose...: Allows user to view any selected file's structure.
- Date.....: 01/01/80
- I/O Files: Any files selected by user.
- Called By: TIGER.PRG, LISTMENU.PRG
- Calls Mod: PRINT.PRG
- Reserved.: selectnum
- Variables: LISTNAME

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+
```

- * ---Display menu options, centered on the screen.
- * draw menu border and print heading

```
CLEAR
```

```
@ 2, 0 TO 12,79 DOUBLE
```

```
@ 3,18 SAY [L I S T   A N Y   S T R U C T U R E   M E N U]
```

```
@ 4,1 TO 4,78 DOUBLE
```

- * ---display detail lines

```
@ 7,30 SAY [1. DISPLAY STRUCTURES]
```

```
@ 8,30 SAY [2. LIST FILES]
```

```
@ 10, 30 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 12,33 SAY " select      "
```

```
@ 12,42 GET selectnum PICTURE "9" RANGE 0,2
```

```
READ
```

```
DO CASE
```

```
    CASE selectnum = 0
```

```
        SET TALK ON
```

```
        CLEAR ALL
```

```
        RETURN
```

```
    CASE selectnum = 1
```

- * DO DISPLAY STRUCTURES

```
    ACCEPT [Enter filename...] TO LISTNAME
```

```
    USE &LISTNAME
```

```
    DO PRINT
```

```
    DISPLAY STRUCTURE
```

```
    SET CONFIRM ON
```

```
    STORE ' ' TO wait_subst
```

```
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
```

```
    READ
```

```
    SET CONFIRM ON
```

CASE selectnum = 2

```
* DO LIST FILES
DO PRINT
DIR *.DEF
SET PRINT OFF
SET CONFIRM ON
STORE ' ' TO wait_subst
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
READ
SET CONFIRM OFF
```

ENDCASE

ENDDO T

RETURN

* EOF: LISANY.PRG

^Z

- * Program...: LISBASIC.PRG
- * Author...: TUNG'S TIGERS
- * Purpose...: Allows user to view the structure of the basic files
- * Date.....: 12/06/86
- * I/O Files: The nine basic database files.
- * Called By: TIGER.PRG, LISTMENU.PRG
- * Calls Mod: PRINT.PRG
- * Reserved.: selectnum
- * Variables: NONE

```
SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF
```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+
```

- * ---Display menu options, centered on the screen.
- * draw menu border and print heading

```
CLEAR
```

```
@ 2, 0 TO 19,79 DOUBLE
```

```
@ 3,15 SAY [L I S T B A S I C S T R U C T U R E M E N U]
```

```
@ 4,1 TO 4,78 DOUBLE
```

- * ---display detail lines

```
@ 7,31 SAY [1. AIRCRAFT]
```

```
@ 8,31 SAY [2. CHARACTERISTICS]
```

```
@ 9,31 SAY [3. PERFORMANCE]
```

```
@ 10,31 SAY [4. RATIOS/FACTORS]
```

```
@ 11,31 SAY [5. WEIGHT]
```

```
@ 12,31 SAY [6. FATIGUE TEST]
```

```
@ 13,31 SAY [7. FLIGHT TEST]
```

```
@ 14,31 SAY [8. STATIC TEST]
```

```
@ 15,31 SAY [9. WIND TUNNEL TEST]
```

```
@ 17, 31 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 19,33 SAY " select "
```

```
@ 19,42 GET selectnum PICTURE "9" RANGE 0,9
```

```
READ
```

```
DO CASE
```

```
    CASE selectnum = 0
```

```
        SET TALK ON
```

```
        CLEAR ALL
```

```
        RETURN
```

```
CASE selectnum = 1
* DO AIRCRAFT
  USE AIRCRAFT
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

```
CASE selectnum = 2
* DO CHARACTERISTICS
  USE CHAR
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

```
CASE selectnum = 3
* DO PERFORMANCE
  USE PERFORMA
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

```
CASE selectnum = 4
* DO RATIOS/FACTORS
  USE RATIOS
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

CASE selectnum = 5

```
* DO WEIGHT
  USE WEIGHT
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

CASE selectnum = 6

```
* DO FATIGUE TEST
  USE FATIGUE
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

CASE selectnum = 7

```
* DO FLIGHT TEST
  USE FLIGHT
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

CASE selectnum = 8

```
* DO STATIC TEST
  USE STATIC
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

```
CASE selectnum = 9
* DO WIND TUNNEL TEST
  USE WIND
  DO PRINT
  LIST STRUCTURE
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOP: LISBASIC.PRG

~Z

```

* Program...: LISTMENU.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to view a file's structure.
* Date.....: 01/01/80
* I/O Files: NONE
* Called By: TIGER.PRG
* Calls Mod: LISBASIC.PRG, LISANY.PRG
* Reserved.: selectnum
* Variables: NONE

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF

```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+
```

```

* ---Display menu options, centered on the screen.
*   draw menu border and print heading

```

```
CLEAR
```

```
@ 2, 0 TO 12,79 DOUBLE
```

```
@ 3,22 SAY [L I S T   S T R U C T U R E   M E N U]
```

```
@ 4,1 TO 4,78 DOUBLE
```

```
* ---display detail lines
```

```
@ 7,30 SAY [1. LIST BASIC STRUCTURES]
```

```
@ 8,30 SAY [2. LIST ANY STRUCTURE]
```

```
@ 10, 30 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 12,33 SAY " select      "
```

```
@ 12,42 GET selectnum PICTURE "9" RANGE 0,2
```

```
READ
```

```
DO CASE
```

```
    CASE selectnum = 0
```

```
        SET TALK ON
```

```
        CLEAR ALL
```

```
        RETURN
```

```
    CASE selectnum = 1
```

```
        * DO LIST BASIC STRUCTURES
```

```
        DO LISBASIC
```


```
*       SET CONFIRM OFF
```

```
*       STORE ' ' TO wait_subst
```

```
*       @ 23,0 SAY 'Press any key to continue...' GET wait_subst
```

```
*       READ
```

```
*       SET CONFIRM ON
```

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

```
CASE selectmen = 2
  * DO LIST ANY STRUCTURE
  DO LISANY
  * SET CONFIRM OFF
  * STORE ' ' TO wait_subst
  * @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  * READ
  * SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: LISTMENU.PRG

^s

```

* Program...: MODMENU.PRG
* Author....: TUN'S TIGERS
* Purpose...: Allows user to select type of record modification.
* Date.....: 02/18/87
* I/O Files: NONE
* Called By: TIGER.PRG
* Calls Mod: ADDMOD.PRG, EDITREC.PRG, DELRMENU.PRG
* Reserved.: selectnum
* Variables:

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE OFF
SET CONFIRM OFF

```

```

DO WHILE .T.

```

```

SET COLOR TO GR+/B+

```

```

* ---Display menu options, centered on the screen.
*   draw menu border and print heading

```

```

CLEAR

```

```

@ 2, 0 TO 13,79 DOUBLE

```

```

@ 3,23 SAY [M O D I F Y   R E C O R D S   M E N U]

```

```

@ 4,1 TO 4,78 DOUBLE

```

```

* ---display detail lines

```

```

@ 7,33 SAY [1. ADD AIRCRAFT MODEL]

```

```

@ 8,33 SAY [2. EDIT RECORDS]

```

```

@ 9,33 SAY [3. DELETE RECORDS]

```

```

@ 11, 33 SAY '0. EXIT'

```

```

STORE 0 TO selectnum

```

```

@ 13,33 SAY " select      "

```

```

@ 13,42 GET selectnum PICTURE "9" RANGE 0,3

```

```

READ

```

```

DO CASE

```

```

CASE selectnum = 0

```

```

    SET BELL ON

```

```

    SET TALK ON

```

```

    CLEAR ALL

```

```

    RETURN

```

```

CASE selectnum = 1

```

```

* DO ADD AIRCRAFT MODEL

```

```

    DO ADDMOD

```

```

    SET CONFIRM OFF

```

```

    STORE ' ' TO wait_subst

```

```

    @ 23,0 SAY 'Press any key to continue...' GET wait_subst

```

```

    READ

```

```

    SET CONFIRM ON

```

```
CASE selectnum = 2
* DO EDIT RECORDS
DO EDITREC
SET CONFIRM OFF
STORE ' ' TO wait_subst
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
READ
SET CONFIRM ON
```

```
CASE selectnum = 3
* DO DELETE RECORDS
DO DELRMENU
SET CONFIRM OFF
STORE ' ' TO wait_subst
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
READ
SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: MODMENU.PRG

^Z

* Program...: PRINT.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to send output to printer if desired.
* Date.....: 12/06/86
* I/O Files: NONE
* Called By: BROWANY.PRG, CQUERYMENU.PRG, CREPORTMENU.PRG,
* JOINFILE.PRG, LISBASIC.PRG, LISANY.PRG,
* PRINTANY.PRG, PRINTBASIC.PRG
* Calls Mod: NONE
* Reserved.: selectnum
* Variables: ANSWER

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET ECHO OFF

* Select output media

STORE " " TO ANSWER
WAIT [Direct the output to the printer? (Y/N)] TO ANSWER

IF UPPER(ANSWER)="Y"
 SET PRINT ON
 RETURN
ELSE
 RETURN
ENDIF

* EOF: PRINT.PRG

^Z

- * Program...: PRINTANY.PRG
- * Author....: TUNG'S TIGERS
- * Purpose...: Allows the user to print any report.
- * Date.....: 02/19/87
- * I/O Files: ANY REPORT FILES SELECTED BY USER
- * Called By: TIGER.PRG, PRPTMENU.PRG
- * Calls Mod: PRINT.PRG
- * Reserved.: selectnum
- * Variables:

```
SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE OFF
SET CONFIRM OFF
```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+
```

- * ---Display menu options, centered on the screen.
- * draw menu border and print heading

```
CLEAR
```

```
@ 2, 0 TO 12,79 DOUBLE
```

```
@ 3,20 SAY [P R I N T   A N Y   R E P O R T   M E N U]
```

```
@ 4,1 TO 4,78 DOUBLE
```

- * ---display detail lines

```
@ 7,33 SAY [1. PRINT ANY REPORT]
```

```
@ 8,33 SAY [2. LIST REPORTS]
```

```
@ 10, 33 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 12,33 SAY " select "
```

```
@ 12,42 GET selectnum PICTURE "9" RANGE 0,2
```

```
READ
```

```
DO CASE
```

```
CASE selectnum = 0
```

```
SET BELL ON
```

```
SET TALK ON
```

```
CLEAR ALL
```

```
RETURN
```

```
CASE selectnum = 1
```

- * DO PRINT ANY REPORT

```
ACCEPT [Enter DBF filename...] TO DBFFILE
```

```
ACCEPT [Enter Report Name....] TO RPTFILE
```

```
USE &DBFFILE
```

```
DO PRINT
```

```
REPORT FORM &RPTFILE
```

```
SET PRINTER OFF
```

```
SET CONFIRM OFF
```

```
STORE ' ' TO wait_subst
```

```
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
```

```
REA.
```

```
SET CONFIRM ON
```

```
CASE selectsum = 2
* DO LIST REPORTS
DO PRINT
DIR *.PRN
SET PRINT OFF
SET CONFIRM OFF
STORE ' ' TO wait_subst
@ 23,0 SAY 'Press any key to continue...' GET wait_subst
READ
SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: PRINTANY.PRG

^Z

- * Program...: PRINTBASIC.PRG
- * Author...: TUNG'S TIGERS
- * Purpose...: Allows the user to print any report available.
- * Date.....: 02/19/87
- * I/O Files: AIRCRAFT.DBF, CHAR.DBF, PERFORMA.DBF, RATIOS.DBF,
- * WRIGHT.DBF, FATIGUE.DBF, FLIGHT.DBF, STATIC.DBF,
- * WIND.DBF
- * Called By: TIGER.PRG, PRPTMENU.PRG
- * Calls Mod: PRINT.PRG
- * Reserved.: selectnum
- * Variables:

```
SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE OFF
SET CONFIRM OFF
```

```
DO WHILE .T.
```

```
SET COLOR TO GR+/B+
```

- * ---Display menu options, centered on the screen.
- * draw menu border and print heading

```
CLEAR
```

```
@ 2, 0 TO 19,79 DOUBLE
```

```
@ 3,18 SAY [P R I N T B A S I C R E P O R T M E N U]
```

```
@ 4,1 TO 4,78 DOUBLE
```

- * ---display detail lines

```
@ 7,31 SAY [1. AIRCRAFT]
```

```
@ 8,31 SAY [2. CHARACTERISTICS]
```

```
@ 9,31 SAY [3. PERFORMANCE]
```

```
@ 10,31 SAY [4. RATIOS/FACTORS]
```

```
@ 11,31 SAY [5. WEIGHT]
```

```
@ 12,31 SAY [6. FATIGUE TEST]
```

```
@ 13,31 SAY [7. FLIGHT TEST]
```

```
@ 14,31 SAY [8. STATIC TEST]
```

```
@ 15,31 SAY [9. WIND TEST]
```

```
@ 17,31 SAY '0. EXIT'
```

```
STORE 0 TO selectnum
```

```
@ 19,33 SAY " select "
```

```
@ 19,42 GET selectnum PICTURE "9" RANGE 0,9
```

```
READ
```

```
DO CASE
```

```
CASE selectnum = 0
```

```
SET BELL ON
```

```
SET TALK ON
```

```
CLEAR ALL
```

```
RETURN
```

```

CASE selectnum = 1
* DO AIRCRAFT
  USE AIRCRAFT
  DO PRINT
  REPORT FORM AIRRPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON

CASE selectnum = 2
* DO CHAR
  USE CHAR
  DO PRINT
  REPORT FORM CHARPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON

CASE selectnum = 3
* DO PERFORMANCE
  USE PERFORMA
  DO PRINT
  REPORT FORM PERRPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON

CASE selectnum = 4
* DO RATIOS
  USE RATIOS
  DO PRINT
  REPORT FORM RATRPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON

```

CASE selectnum = 5

```
* DO WEIGHT
  USE WEIGHT
  DO PRINT
  REPORT FORM WGTRPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

CASE selectnum = 6

```
* DO FATIGUE
  USE FATIGUE
  DO PRINT
  REPORT FORM FATRPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

CASE selectnum = 7

```
* DO FLIGHT
  USE FLIGHT
  DO PRINT
  REPORT FORM FLTRPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

CASE selectnum = 8

```
* DO STATIC
  USE STATIC
  DO PRINT
  REPORT FORM STARPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

```
CASE selectnum = 9
* DO WIND
  USE WIND
  DO PRINT
  REPORT FORM WNRPT.FRM
  SET PRINT OFF
  SET CONFIRM OFF
  STORE ' ' TO wait_subst
  @ 23,0 SAY 'Press any key to continue...' GET wait_subst
  READ
  SET CONFIRM ON
```

ENDCASE

ENDDO T

RETURN

* EOF: PRINTBASIC.PRG

^Z

```

* Program...: PRPTMENU.PRG
* Author...: TUNG'S TIGERS
* Purpose...: Allows user to print selected reports
* Date.....: 02/19/87
* I/O Files: NONE
* Called By: TIGER.PRG
* Calls Mod: PRINTBASIC.PRG, PRINTANY.PRG, PRINT.PRG
* Reserved.: selectnum
* Variables:

```

```

SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE OFF
SET CONFIRM OFF

```

```

DO WHILE .T.
SET COLOR TO GR+/B+
  * ---Display menu options, centered on the screen.
  *   draw menu border and print heading
  CLEAR
  @ 2, 0 TO 12,79 DOUBLE
  @ 3,23 SAY [P R I N T   R E P O R T S   M E N U]
  @ 4,1 TO 4,78 DOUBLE
  * ---display detail lines
  @ 7,31 SAY [1. PRINT BASIC REPORTS]
  @ 8,31 SAY [2. PRINT ANY REPORT]
  @ 10, 31 SAY '0. EXIT'
  STORE 0 TO selectnum
  @ 12,33 SAY " select      "
  @ 12,42 GET selectnum PICTURE "9" RANGE 0,2
  READ

```

```

DO CASE

```

```

  CASE selectnum = 0
    SET BELL ON
    SET TALK ON
    CLEAR ALL
    RETURN

```

```

  CASE selectnum = 1
    * DO PRINT BASIC REPORTS
    DO PRINTBASIC
    *   SET CONFIRM OFF
    *   STORE ' ' TO wait_subst
    *   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
    *   READ
    *   SET CONFIRM ON

```

```
CASE selectnum = 2
  * DO PRINT ANY REPORT
  DO PRINTANY
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

ENDCASE

ENDDO T

RETURN

* EOF: PRPTMENU.PRG

^Z
```

```
* Program...: TIGER.PRG
* Author...: TUNG'S TIGERS
* Date.....: 02/18/87
* Purpose...: This program assists the user in the selection of
*             actions to be performed on the database.
* I/O Files: None
* Called by: None
* Calls Mod: BROWMENU.PRG, CREPORTMENU.PRG, CQUERYMENU.PRG,
*            JOINFILE.PRG, LISTMENU.PRG, MODMENU.PRG,
*            PRINTMENU.PRG
* Reserved.: selectnum
* Variables: None
```

```
SET TALK OFF
SET BELL OFF
SET STATUS ON
SET ESCAPE ON
SET CONFIRM OFF
```

```
DO WHILE .T.
SET COLOR TO GR+/B+
* ---Display menu options, centered on the screen.
*   draw menu border and print heading
CLEAR
@ 2, 0 TO 17,79 DOUBLE
@ 3,26 SAY [T I G E R   M A I N   M E N U]
@ 4,1 TO 4,78 DOUBLE
* ---display detail lines
@ 7,32 SAY [1. LIST STRUCTURES]
@ 8,32 SAY [2. BROWSE FILES]
@ 9,32 SAY [3. JOIN FILES]
@ 10,32 SAY [4. MODIFY RECORDS]
@ 11,32 SAY [5. CREATE REPORTS]
@ 12,32 SAY [6. CREATE QUERIES]
@ 13,32 SAY [7. PRINT REPORTS]
@ 15, 32 SAY '0. EXIT'
STORE 0 TO selectnum
@ 17,33 SAY " select      "
@ 17,42 GET selectnum PICTURE "9" RANGE 0,7
READ
```

```
DO CASE
```

```
    CASE selectnum = 0
        SET BELL ON
        SET TALK ON
        CLEAR ALL
        RETURN
```

```

CASE selectnum = 1
* DO LIST STRUCTURES
  DO LISTMENU
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 2
* DO BROUSE FILES
  DO BROWMENU
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 3
* DO JOIN FILES
  DO JOINFILE
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 4
* DO MODIFY RECORDS
  DO MODMENU
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 5
* DO CREATE REPORTS
  DO CREPRTMENU
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

CASE selectnum = 6
* DO CREATE QUERIES
  DO CQUERYMENU
*   SET CONFIRM OFF
*   STORE ' ' TO wait_subst
*   @ 23,0 SAY 'Press any key to continue...' GET wait_subst
*   READ
*   SET CONFIRM ON

```

```
      CASE selectnum = 7
      * DO PRINT REPORTS
      DO PRPTMENU
      * SET CONFIRM OFF
      * STORE ' ' TO wait_subst
      * @ 23,0 SAY 'Press any key to continue...' GET wait_subst
      * READ
      * SET CONFIRM ON

ENDCASE

ENDDO T

SET COLOR TO W+/B+,GR+/R+, BG+

RETURN

* EOF: TIGER.PRG

^Z
```

APPENDIX C: DATA STRUCTURES

Structure for database: C:AIRCRAFT.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	MISSION	Character	10	
3	MFG	Character	20	
** Total **			41	

Structure for database: C:CHAR.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	CREW	Numeric	2	
3	FIRST_FLT	Numeric	5	2
4	AWA	Numeric	4	
5	VOL	Numeric	5	
6	WL	Numeric	5	1
7	CQ	Numeric	1	
8	AVBX	Numeric	2	
9	ENG	Numeric	1	
10	SSTA	Numeric	2	
11	THRUST	Numeric	6	
** Total **			44	

Structure for database: C.PERFORMA.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	VMAXA	Numeric	4	
3	VMAXS	Numeric	3	
4	VCRUISE	Numeric	3	
5	CBT_CEIL	Numeric	5	
6	SER_CEIL	Numeric	6	
7	CBT_RADIUS	Numeric	5	
** Total **			37	

Structure for database: C:RATIOS.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	LLF	Numeric	6	3
3	ULF	Numeric	6	3
4	WE/WS	Numeric	6	4
5	WE/VOL	Numeric	7	4
6	GTOW/WS	Numeric	6	4
** Total **			42	

Structure for database: C:WEIGHT.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field name	Type	Width	Dec
1	MODEL	Character	10	
2	WS	Numeric	6	
3	WA	Numeric	6	
4	WE	Numeric	6	
5	GTOW	Numeric	6	
6	WAVU	Numeric	4	
7	WAVI	Numeric	4	
8	MAXWSS	Numeric	6	
** Total **			49	

Structure for database: C:FATIGUE.dbf

Number of data records: 38

Date of lat update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	FTMOS	Numeric	3	
3	FTHRS	Numeric	6	1
4	FENGHRS	Numeric	6	1
5	FMPGHRS	Numeric	6	1
6	FTOOLHR	Numeric	6	1
7	FQCHRS	Numeric	6	1
8	FILSHRS	Numeric	6	1
9	FTOTHRS	Numeric	6	1
** Total **			56	

Structure for database: C:FLIGHT.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	FLTHRS	Numeric	6	
3	TEVTS	Numeric	6	
4	ENGHR	Numeric	6	1
5	MFGHR	Numeric	6	1
6	TOOLHR	Numeric	6	1
7	QCHR	Numeric	6	1
8	ILSHR	Numeric	6	1
9	TOTHRS	Numeric	6	1
** Total **			59	

Structure for database: C:STATIC.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	STMOS	Numeric	3	
3	SENGHRS	Numeric	6	1
4	SMFGHRS	Numeric	6	1
5	STOOLHR	Numeric	6	1
6	SQCHRS	Numeric	6	1
7	SILSHRS	Numeric	6	1
8	STOTHR	Numeric	6	1
** Total **			50	

Structure for database: C:WIND.dbf

Number of data records: 38

Date of last update : 02/20/87

Field	Field Name	Type	Width	Dec
1	MODEL	Character	10	
2	WTMOS	Numeric	3	
3	WTHRS	Numeric	6	1
4	WENGHRS	Numeric	6	1
5	WMFGHRS	Numeric	6	1
6	WTOOLHR	Numeric	6	1
7	WQCHRS	Numeric	6	1
8	WILSHRS	Numeric	6	1
9	WTOTHR	Numeric	6	1
** Total **			56	

APPENDIX D: USER'S MANUAL

1. PRELIMINARY INFORMATION:

1.0 INTRODUCTION:

This User's Manual is designed to assist the NAVAIR Cost Systems, Research and Methods personnel in the use of the programs. All of the programs used are MENU DRIVEN to make this system as user friendly as possible. This manual is not designed to replace a programmer's guide.

*** This manual presupposes a basic working knowledge of dBASE III+ ASSIST functions. The three asterisks (***) symbol is used as a prompt in this manual to alert the user when the ASSIST function is required to complete the menu option.

1.1 TIGER MAIN MENU:

Allows the user to select what basic actions are to be performed on the database. The selections are:

1. LIST STRUCTURES
2. BROWSE FILES
3. JOIN FILES
4. MODIFY RECORDS
5. CREATE REPORTS
6. CREATE QUERIES
7. PRINT REPORT
0. EXIT (to dBASE III+ ASSIST menu)

1.2 LIST STRUCTURES:

Allows the user to view the structure of a file. The selections are:

1. LIST BASIC STRUCTURES
2. LIST ANY STRUCTURE
0. EXIT (to the TIGER MAIN MENU)

1.2.1 LIST BASIC STRUCTURES:

This option allows the user to view the structure of the basic files. The selections are:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (to the LIST STRUCTURE MENU)

1.2.2 LIST ANY STRUCTURE:

This option allows the user to view the structure of any selected file. The selections are:

1. DISPLAY STRUCTURES
2. LIST FILES
0. EXIT (to the LIST STRUCTURE MENU)

1.3 BROWSE FILES:

When the user selects this option there are three selections available:

1. BROWSE BASIC FILES
2. BROWSE ANY FILES
3. EXIT (to the TIGER MAIN MENU)

1.3.1 BROWSE BASIC FILES:

This option allows the user to view the basic data files. The selections are:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (to the BROWSE FILES MENU)

1.3.2 BROWSE ANY FILES:

Allows the user to view the current data base files.
The selections are:

1. BROWSE ANY FILE
2. LIST FILES
0. EXIT (to the BROWSE FILES MENU)

1.4 JOIN FILES:

When the user selects this option there are four selections available:

1. LIST EXISTING FILES
2. JOIN FILES
3. JOIN TO FORM SPECS
0. EXIT (to the TIGER MAIN MENU)

1.4.1 LIST EXISTING FILES:

Allows the user to view a listing of existing files.

1.4.2 JOIN FILES:

Allows the user to join files on the model field.

1.4.3 JOIN TO FORM SPECS:

Allows the user to join all the current basic files to form a specifications structure to facilitate ad hoc queries.

1.5 MODIFY RECORDS:

When the user selects this option four selections are available:

1. ADD AIRCRAFT MODEL
2. EDIT RECORDS
3. DELETE RECORDS
0. EXIT (to the TIGER MAIN MENU)

1.5.1 ADD AIRCRAFT MODEL:

This program assists the user in adding a new model aircraft to all of the nine basic files concurrently. This also does an automatic sort to place the new aircraft in alpha-numeric order.

1.5.2 EDIT RECORDS:

This program assists the user in editing records in the nine basic files. The selections are:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (to the MODIFY RECORDS MENU)

1.5.3 DELETE RECORDS:

This program assists the user in deleting records from the nine basic files concurrently. In addition, it displays the following selections:

1. YOU ARE ABOUT TO PERMANENTLY DELETE SELECTED RECORDS FROM FILES
0. EXIT (to the MODIFY RECORDS MENU)

1.6 CREATE REPORTS:

Allows the user to create ad hoc reports. The selections are:

1. CREATE NEW REPORT
2. LIST EXISTING REPORT FILES
0. EXIT (to the TIGER MAIN MENU)

1.6.1 CREATE NEW REPORT:

Defaults the user to the dBASE III+ ASSIST menu.

1.6.2 LIST EXISTING REPORT FILES:

Allows the user to view all report files.

1.7 CREATE QUERIES:

Allows the user to create ad hoc query relationships. The selections are:

1. CREATE NEW QUERY
2. LIST QUERY FILES
0. EXIT (to the TIGER MAIN MENU)

1.7.1 CREATE NEW QUERY:

Defaults the user to the dBASE III+ ASSIST menu.

1.7.2 LIST QUERY FILES:

Allows the user view all query files.

1.8 PRINT REPORTS:

Allows the user to print reports that come from the data files. The selections are:

1. PRINT BASIC REPORTS
2. PRINT ANY REPORT
0. EXIT (to the TIGER MAIN MENU)

1.8.1 PRINT BASIC REPORTS:

Allows the user to print the basic reports by inputting a file name.

1.8.2 PRINT ANY REPORT:

Allows the user to print a report based on the primary data files. The selections are:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST.RPT
9. WIND TUNNEL TEST.RPT
0. EXIT (to the PRINT REPORTS MENU)

2.0 INTRODUCTION:

The TIGER data base system is used to provide a relational method to input, access and compare data on the Test and Evaluation cost drivers of military aircraft. This program will allow the user to work with existing files, add data, edit data and delete records from the following nine applicable files:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST

2.1 Procedures:

This program is designed to be operated using dBASE III+ with an IBM-PC and hard disk drive to contain the required files. Ensure the required files are resident on the hard disk drive prior to operation.

1. Commands to perform.
 - a. Type: DBASE (enables the db.exe file).
 - b. Type: DO TIGER or F9 function key (activates main menu).

2.2 TIGER MAIN MENU:

This menu is displayed to provide the user access to the data base and the following options to view and manipulate data:

1. LIST STRUCTURES
2. BROWSE FILES
3. JOIN FILES
4. MODIFY RECORDS
5. CREATE REPORTS
6. CREATE QUERIES
7. PRINT REPORT
0. EXIT (to dBASE III+ ASSIST menu)

2.2.1 SELECTING SUB-MENUS:

Select an option from the TIGER MAIN MENU by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2, 3, 4, 5, 6, 7, or 0 <cr>

3.0 LIST STRUCTURES:

The LIST STRUCTURES menu is displayed when called as an option from the TIGER MAIN MENU. This menu provides the user the opportunity to view and print the structure of a data file with the following selections:

1. LIST BASIC STRUCTURES
2. LIST ANY STRUCTURE
0. EXIT (to the TIGER MAIN MENU)

SELECTING LIST STRUCTURES OPTIONS:

Select an option from the LIST STRUCTURES menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2 or 0 <cr>

3.1 LIST BASIC STRUCTURES:

The LIST BASIC STRUCTURES menu is displayed when called as an option from the LIST STRUCTURES menu. This menu provides the user the opportunity to view and print the structure of the nine basic data files with the following selections:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (exit to the LIST STRUCTURES MENU)

SELECTING DATA FILE OPTIONS:

Select an option from the LIST BASIC STRUCTURES menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2, 3, 4, 5, 6, 7, 8, 9 or 0 <cr>

3.1.1 SELECTED DATA FILES:

These data files are called from the LIST BASIC STRUCTURES menu and allows the user to view and print the structure of the selected data file.

When this option is selected the monitor will query the user:

"Direct this output to the printer? (Y/N)"

If printed copy is desired:

1. Command to perform:
 - a. Type: Y<cr>

If printed copy is not desired:

1. Command to perform:
 - a. Type: N<cr>

After selecting Y/N the list will scroll on the screen and display the requested structure.

RETURN FROM SELECTED DATA FILE OPTION:

To return from viewing a selected data file structure, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.1.2 LIST ANY STRUCTURE:

The LIST ANY STRUCTURE option is called from the LIST STRUCTURES menu and allows the user to view and print the structure of any data file by typing a specific database filename.

1. Commands to perform:
 - a. Type: <filename><cr>

When this option is selected the monitor will query the user:

"Direct this output to the printer? (Y/N)"

If printed copy is desired:

1. Command to perform:
 - a. Type: Y<cr>

If printed copy is not desired:

1. Command to perform:
 - a. Type: N<cr>

After selecting Y/N the listing will scroll on the screen and display the requested structure.

RETURN FROM LIST ANY STRUCTURE OPTION:

To return from viewing a data file, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.2 BROWSE FILES:

The BROWSE FILES menu is displayed when called as an option from the TIGER MAIN MENU. This menu provides the user the opportunity to view but not manipulate applicable files with the following selections:

1. BROWSE BASIC FILES
2. BROWSE ANY FILE
0. EXIT (to the TIGER MAIN MENU)

SELECTING SUB-MENUS:

Select an option from the BROWSE FILES menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2 or 0 <cr>

3.2.1 BROWSE BASIC FILES:

The BROWSE BASIC FILES menu is displayed when called as an option from the BROWSE FILES menu. This menu provides the user the opportunity to view but not manipulate the nine basic data files with the following selections:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (to the BROWSE FILES MENU)

SELECTING DATA FILE OPTIONS:

Select an option from the BROWSE BASIC FILES menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2, 3, 4, 5, 6, 7, 8, 9 or 0 <cr>

3.2.1.1 SELECTED DATA FILES:

These data files are called from the BROWSE BASIC FILE menu and allows the user to view but not manipulate the data contained in the selected file.

RETURN FROM SELECTED DATA FILE OPTION:

To return from browsing a selected data file, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.2.2 BROWSE ANY FILE:

The BROWSE ANY FILE menu is displayed when called as an option from the BROWSE FILES menu. This menu provides the user the opportunity to view but not manipulate any files with the following selections:

1. BROWSE ANY FILE
2. LIST FILES
0. EXIT (to the BROWSE FILES MENU)

SELECTING SUB-MENU OPTIONS:

Select an option from the BROWSE ANY FILE menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2 or 0 <cr>

3.2.2.1 BROWSE ANY FILE:

The BROWSE ANY FILE option is called from the BROWSE ANY FILE menu and allows the user to view a specific database file by typing a specific database filename.

1. Commands to perform:
 - a. Type: <filename><cr>

When this option is selected the monitor will query the user:

"Direct this output to the printer? (Y/N)"

If printed copy is desired:

1. Command to perform:
 - a. Type: Y<cr>

If printed copy is not desired:

1. Command to perform:
 - a. Type: N<cr>

After selecting Y/N the requested file will scroll on the screen.

RETURN FROM BROWSE ANY FILE OPTION:

To return from viewing a database file, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.2.2.2 LIST FILES:

The LIST FILES option is called from the BROWSE ANY FILE menu and allows the user to view a directory listing of current database files.

RETURN FROM DATABASE FILE LISTING OPTION:

To return from viewing a database file listing, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.3 JOIN FILES:

The JOIN FILE menu is displayed when called as an option from the TIGER MAIN MENU. This menu provides the user the opportunity to list existing files and join files with the following selections:

1. LIST EXISTING FILES
2. JOIN FILES
3. JOIN TO FORM SPECS
0. EXIT (to the TIGER MAIN MENU)

3.3.1 LIST EXISTING FILES:

The LIST EXISTING FILES option is called from the JOIN FILE menu and allows the user to view and print a directory listing of existing database files.

When this option is selected the monitor will query the user:

"Direct this output to the printer? (Y/N)"

If printed copy is desired:

1. Command to perform:
 - a. Type: Y<cr>

If printed copy is not desired:

1. Command to perform:
 - a. Type: N<cr>

After selecting Y/N the requested listing will scroll on the screen.

RETURN FROM EXISTING FILES LISTING OPTION:

To return from viewing an existing files listing, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.3.2 JOIN FILES:

The JOIN FILES option is called from the JOIN FILE menu and allows the user to join two selected data files on the MODEL field with a <FILENAME> specified for the new join file.

When this option is selected the monitor will query the user:

"Enter filename 1..."

1. Commands to perform:
 - a. Type: <FILENAME> <cr>

"Enter filename 2..."

1. Commands to perform:
 - a. Type: <FILENAME> <cr>

"Enter new filename..."

1. Commands to perform:
 - a. Type: <FILENAME> <cr>

RETURN FROM JOIN FILES OPTION:

Following entry of the desired filenames, the program will join the desired files and return to the JOIN FILE menu.

3.3.3 JOIN TO FORM SPECS:

The JOIN TO FORM SPECS option is called from the JOIN FILES MENU and allows the user to view and print a specifications structure of the existing database files.

When this option is selected the monitor will query the user:

"Direct this output to the printer? (Y/N)"

If printed copy is desired:

1. Command to perform:
 - a. Type: Y<cr>

If printed copy is not desired:

1. Command to perform:
 - a. Type: N<cr>

After selecting Y/N the requested specifications chart will scroll on the screen.

RETURN FROM JOIN TO FORM SPECS OPTION:

To return from viewing a specifications chart, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.4 MODIFY RECORDS:

When the user selects this option four selections are available:

1. ADD AIRCRAFT MODEL
2. EDIT RECORDS
3. DELETE RECORDS
0. EXIT (to the TIGER MAIN MENU)

3.4.1 ADD AIRCRAFT MODEL:

This program assists the user in adding a new model aircraft to all of the nine basic files concurrently. This also does an automatic sort to place the new aircraft in alpha-numeric order.

When this option is selected the monitor will query the user to input the new model:

1. Command to perform:
 - a. Type: Model<cr>

RETURN FROM ADD AIRCRAFT MODEL OPTION:

To return from adding a new aircraft, the user may type <CTRL - End> which will return the screen to the previous menu.

3.4.2 EDIT RECORDS:

This program assists the user in editing records in the nine basic files. The user must be cautioned: in this selection you will be editing only the file you have selected, you will not edit all the structures simultaneously. In addition, if you edit the model, it will only be edited in the structure selected. In order to ensure continuity among all structures you will have to individually modify the model attribute in the remaining structures. The selections are:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (to the MODIFY RECORDS MENU)

Select an option from the BROWSE BASIC FILES menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2, 3, 4, 5, 6, 7, 8, 9 or 0 <cr>

RETURN FROM EDIT RECORDS OPTION:

To return from editing a record, the user may type <esc> which will save the changes and return the screen to the previous menu.

3.4.3 DELETE RECORDS:

This program assists the user in deleting records from the nine basic files concurrently. It does an automatic pack to ensure the remaining models are maintained in alpha-numeric order. In addition, it displays the following selections:

1. YOU ARE ABOUT TO PERMANENTLY DELETE SELECTED RECORDS FROM FILES
0. EXIT (to the MODIFY RECORDS MENU)

RETURN FROM DELETE RECORDS OPTION:

To return from deleting a record, the user may type <esc> which will return the screen to the previous menu.

3.5 CREATE REPORT:

The CREATE REPORT menu is displayed when called as an option from the TIGER MAIN MENU. This menu provides the user the opportunity to create an ad hoc report or view a listing of existing report files with the following selections:

1. CREATE NEW REPORT
2. LIST EXISTING REPORT FILES
0. EXIT (to the TIGER MAIN MENU)

SELECTING CREATE REPORT OPTIONS:

Select an option from the CREATE REPORT menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2 or 0 <cr>

3.5.1 CREATE NEW REPORT:

The CREATE NEW REPORT option is called from the CREATE REPORT menu and allows the user to create an ad hoc report utilizing the dBASE III+ ASSIST function.

1. Commands to perform:
 - a. Type: 1

*** a. User is directed to the dBASE III+ ASSIST function.

RETURN FROM CREATE NEW REPORT OPTION:

To return from creating an ad hoc report, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.5.2 LIST EXISTING REPORT FILES:

The LIST EXISTING REPORT FILES option is called from the CREATE REPORT menu and allows the user to view a directory listing of existing report files.

RETURN FROM EXISTING REPORT FILES LISTING OPTION:

To return from viewing an existing report files listing, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.6 CREATE QUERIES:

The CREATE QUERIES menu is displayed when called as an option from the TIGER MAIN MENU. This menu provides the user the opportunity to create ad hoc query relationships with the following selectaons:

1. CREATE NEW QUERY
2. LIST QUERY FILES
0. EXIT (to the TIGER MAIN MENU)

SELECTING CREATE QUERIES OPTIONS:

Select an option from the CREATE QUERIES menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2 or 0 <cr>

3.6.1 CREATE NEW QUERY:

The CREATE NEW QUERY option is displayed when called as an option from the CREATE QUERY menu. This option allows the user to create an ad hoc query using the dBASE III+ ASSIST function.

1. Commands to perform:
 - a. Type: 1

*** a. User is directed to the dBASE III+ ASSIST function.

3.6.2 LIST QUERY FILES:

The LIST QUERY FILES option is called from the CREATE QUERY menu and allows the user to view all query files.

RETURN FROM LIST QUERY FILES OPTION:

To return from viewing a query file listing, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.7 PRINT REPORTS:

The PRINT REPORTS menu is displayed when called as an option from the TIGER MAIN MENU. This menu provides the user the opportunity to send to the printer the following selections:

1. PRINT BASIC REPORTS
2. PRINT ANY REPORT
0. EXIT (to the TIGER MAIN MENU)

SELECTING SUB-MENUS:

Select an option from the PRINT REPORTS menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2, 3, or 0 <cr>

3.7.1 PRINT BASIC REPORTS:

The PRINT BASIC REPORTS menu is displayed when called as an option from the TIGER MAIN MENU. This menu provides the user the opportunity to send to the printer nine standard reports with the following selections:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (to the PRINT REPORTS MENU)

SELECTING SUB-MENUS:

Select an option from the PRINT BASIC REPORTS menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2, 3, 4, 5, 6, 7, 8, 9, or 0 <cr>

RETURN FROM PRINT BASIC REPORTS OPTION:

To return from printing a basic report, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.7.2 PRINT ANY REPORT:

Allows the user to print a report based on the primary data files. The selections are:

1. PRINT ANY REPORT
2. LIST REPORTS
0. EXIT (to the PRINT REPORTS MENU)

3.7.2.1 PRINT ANY REPORT:

Allows the user to print a report based on the following selections:

1. AIRCRAFT
2. CHARACTERISTICS
3. PERFORMANCE
4. RATIOS/FACTORS
5. WEIGHT
6. FATIGUE TEST
7. FLIGHT TEST
8. STATIC TEST
9. WIND TUNNEL TEST
0. EXIT (to the PRINT REPORTS MENU)

SELECTING SUB-MENUS:

Select an option from the PRINT ANY REPORTS menu by typing the number of the corresponding option desired.

1. Commands to perform:
 - a. Type: 1, 2, 3, 4, 5, 6, 7, 8, 9, or 0 <cr>

RETURN FROM PRINT ANY REPORTS OPTION:

To return from printing a report, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

3.7.2.2 LIST REPORTS:

Allows the user to view and print the reports that are available.

RETURN FROM LIST REPORTS OPTION:

To return from viewing or printing the available reports, the user may type <esc> which will return the screen to the previous menu.

1. Commands to perform:
 - a. Type: <esc>

APPENDIX E: REPORTS

*** DUE TO THE PROPRIETARY NATURE OF THE DATA THIS THESIS WILL
USE "XX" TO INDICATE WHERE SUCH DATA WAS AVAILABLE AND USED
IN THE DATABASE ***

AIRCRAFT

MODEL	MISSION	MFG
A-10A	XX	XX
A-18	XX	XX
A 4A	XX	XX
A-5A	XX	XX
A-6A	XX	XX
A-7	XX	XX
AV-8B	XX	XX
B-1	XX	XX
B 45C	XX	XX
B-52F	XX	XX
B-52G	XX	XX
B-58A	XX	XX
C-130B	XX	XX
C-130E	XX	XX
C 135A	XX	XX
C-141A	XX	XX
C-5A	XX	XX
E-3A	XX	XX
F-100	XX	XX
F-105	XX	XX
F-111A	XX	XX
F-14A	XX	XX
F-15A	XX	XX
F-16A	XX	XX
F-18	XX	XX
F-4A	XX	XX
F-5	XX	XX
F-84B	XX	XX
F-86D	XX	XX
OV-10	XX	XX
S-3A	XX	XX
T-2	XX	XX
T-38A	XX	XX
T-39	XX	XX
XB-70	XX	XX
YC-130	XX	XX
YC-14	XX	XX
YF 16	XX	XX

FLIGHT TEST DATA

MODEL	PLTHRS	TEVTS	ENGRHR	MFGHR	TOOLHR	QCHR	ILSHR	TOTHR
A-10A			XX	XX	XX	XX		
A-18			XX	XX	XX	XX		
A-4A			XX	XX	XX			XX
A-5A			XX	XX		XX		XX
A-6A			XX	XX	XX	XX		XX
A-7	XX		XX					
AV-8B			XX					
B-1			XX					XX
B-45C								
B-52F			XX					XX
B-52G								
B-58A			XX	XX	XX	XX		XX
C-130B								
C-130E								
C-135A			XX					XX
C-141A	XX		XX					XX
C-5A	XX		XX			XX		XX
E-3A	XX		XX					
F-100								XX
F-105			XX	XX	XX			XX
F-111A	XX		XX	XX	XX	XX		XX
F-14A			XX	XX	XX	XX		XX
F-15A			XX	XX		XX		XX
F-16A	XX		XX	XX	XX	XX		XX
F-18			XX	XX	XX	XX		XX
F-4A			XX	XX		XX		XX
F-5								XX
F-84B								
F-86D								
OV-10			XX	XX				
S-3A	XX		XX	XX	XX	XX		XX
T-2			XX	XX				
T-38A			XX	XX	XX	XX		XX
T-39								XX
XB-70								
YC 130								
YC-14	XX		XX					XX
YF-16	XX		XX	XX	XX	XX		XX

FATIGUE TEST DATA

MODEL	THOS	THRS	ENGERS	MPGERS	TOOLER	QCERS	ILSERS	TOTERS
A-10A			XX					
A-10			XX					
A-4A								
A-5A			XX	XX				
A-6A								
A-7								
AV-8B								
B-1								
B-45C								
B-52P			XX					
B-52G								
B-58A			XX	XX	XX	XX		XX
C-130B								
C-130E								
C-135A								
C-141A			XX					
C-5A			XX	XX	XX	XX		
E-3A								
F-100								
F-105								
F-111A			XX	XX	XX	XX		XX
F-14A			XX	XX	XX	XX		
F-15A								
F-16A			XX	XX	XX	XX		XX
F-18			XX					
F-4A								
F-5								
F-84B								
F-86D								
OV-10			XX	XX				
S-3A			XX	XX	XX			
T-2			XX	XX				
T-38A								
T-39								
XB-70								
YC-130								
YC-14								
YF-16								

STATIC TEST DATA

MODEL	TMOB	EMGHS	MPGHS	TOOLHR	QCHRS	ILSHRS	TOTHS
A-10A		XX					
A-18		XX					
A-4A							
A-5A		XX	XX				
A-6A							
A-7							
AV-0B							
B-1							
B-45C							
B-52F		XX					
B-52G							
B-58A		XX	XX	XX	XX		XX
C-130B							
C-130E							
C-135A							XX
C-141A		XX					
C-5A		XX	XX	XX			
E-3A							
F-100							
F-105							
F-111A		XX	XX	XX	XX		XX
F-14A		XX	XX	XX	XX		
F-15A							
F-16A		XX	XX	XX	XX		
F-18		XX					
F-4A		XX					
F-5							
F-84B							
F-86D							
OV-10		XX	XX				
S-3A		XX	XX	XX			
T-2		XX	XX				
T-38A							
T-39							
XB-70							
YC-130							
YC-14							
YF-16							

WIND TUNNEL TEST DATA

MODEL	TMOS	THRS	ENGHRS	MFGHRS	TOOLHR	QCHRS	ILSHRS	TOTHR
A-10A			XX					
A-18			XX					
A-4A			XX					
A-5A			XX	XX				
A-6A			XX					
A-7								
AV-8B								
B-1								
B-45C								
B-52F			XX					
B-52G								
B-58A			XX		XX	XX		XX
C-130B								
C-130E								
C-135A								XX
C-141A			XX					
C-5A			XX					
E-3A								
F-100								
F-105								
F-111A			XX	XX	XX	XX		XX
F-14A			XX	XX	XX	XX		
F-15A								
F-16A			XX		XX	XX		XX
F-18			XX	XX				
F-4A			XX					
F-5								
F-84B								
F-86D								
OV-10			XX	XX				
S-3A			XX	XX				
T-2								
T-38A			XX					
T-39								
XB-70								
YC-130								
YC-14			XX					
YF-16			XX		XX	XX		XX

AIRCRAFT CHARACTERISTICS

MODEL	CREW	1STFL	AWA	VOL	WL	CQ	AVBX	ENG	SSTA	THRUST
A-10A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
A-18	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
A-4A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
A-5A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
A-6A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
A-7	XX	XX			XX	XX		XX	XX	XX
AV-8B	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
B-1	XX	XX			XX	XX		XX	XX	XX
B-45C	XX									
B-52F	XX	XX			XX	XX		XX	XX	XX
B-52G	XX	XX			XX	XX		XX	XX	XX
B-58A	XX	XX			XX	XX		XX	XX	XX
C-130B	XX	XX			XX	XX		XX	XX	XX
C-130E	XX	XX			XX	XX		XX	XX	XX
C-135A	XX	XX			XX	XX		XX	XX	XX
C-141A	XX	XX			XX	XX		XX	XX	XX
C-5A	XX	XX			XX	XX		XX	XX	XX
E-3A	XX	XX			XX	XX		XX	XX	XX
F-100	XX	XX			XX	XX		XX	XX	XX
F-105	XX	XX			XX	XX		XX	XX	XX
F-111A	XX	XX			XX	XX		XX	XX	XX
F-14A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
F-15A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
F-16A	XX	XX			XX	XX	XX	XX	XX	XX
F-18	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
F-4A	XX	XX	XX		XX	XX	XX	XX	XX	XX
F-5	XX	XX			XX	XX		XX	XX	XX
F-84B	XX	XX			XX	XX		XX	XX	XX
F-86D	XX	XX			XX	XX		XX	XX	XX
OV-10	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
S-3A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
T-2	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
T-38A	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
T-39	XX	XX	XX	XX	XX	XX	XX	XX	XX	XX
XB-70	XX									
YC-130	XX	XX			XX	XX		XX		
YC-14	XX	XX			XX	XX		XX		
YF-16	XX	XX			XX	XX		XX	XX	

AIRCRAFT RATIOS/FACTORS

MODEL	LLF	ULF	WE/WS	WE/VOL	GTOW/WS
A-10A	XX	XX	XX	XX	XX
A-18	XX	XX	XX	XX	XX
A-4A	XX	XX	XX	XX	XX
A-5A	XX	XX	XX	XX	XX
A-6A	XX	XX	XX	XX	XX
A-7	XX	XX	XX	XX	XX
AV-8B	XX	XX	XX	XX	XX
B-1			XX		XX
B-45C			XX		XX
B-52F			XX		XX
B-52G			XX		XX
B-58A			XX		XX
C-130B			XX		XX
C-130E		XX	XX		XX
C-135A			XX		XX
C-141A			XX		XX
C-5A			XX		XX
E-3A			XX		XX
F-100			XX		XX
F-105					
F-111A			XX		XX
F-14A	XX	XX	XX	XX	XX
F-15A	XX	XX	XX	XX	XX
F-16A	XX	XX	XX	XX	XX
F-18	XX	XX	XX	XX	XX
F-4A	XX	XX	XX		XX
F-5					
F-84B		XX	XX		XX
F-86D			XX		XX
OV-10	XX	XX	XX	XX	XX
S-3A	XX	XX	XX	XX	XX
T-2	XX	XX	XX	XX	XX
T-38A	XX	XX	XX	XX	XX
T-39	XX	XX	XX	XX	XX
XB-70			XX		XX
YC-130					XX
YC-14					
YF-16		XX	XX		XX

AIRCRAFT WEIGHT

MODEL	WS	WA	WE	GTOW	WAVU	WAVI	MAXWSS
A-10A	XX	XX	XX	XX	XX	XX	XX
A-18	XX	XX	XX	XX	XX	XX	XX
A-4A	XX	XX	XX	XX	XX	XX	XX
A-5A	XX	XX	XX	XX	XX	XX	
A-6A	XX	XX	XX	XX	XX	XX	XX
A-7	XX	XX	XX	XX	XX	XX	XX
AV-8B	XX	XX	XX	XX	XX	XX	XX
B-1	XX	XX	XX	XX	XX	XX	
B-45C	XX		XX	XX	XX		XX
B-52F	XX		XX	XX	XX	XX	
B-52G	XX	XX	XX	XX	XX	XX	
B-58A	XX	XX	XX	XX	XX	XX	
C-130B	XX	XX	XX	XX	XX	XX	
C-130E	XX		XX	XX	XX	XX	
C-135A	XX		XX	XX	XX		
C-141A	XX		XX	XX	XX	XX	
C-5A	XX	XX	XX	XX	XX	XX	
E-3A	XX	XX	XX	XX	XX	XX	
F-100	XX		XX	XX	XX	XX	
F-105			XX	XX			
F-111A	XX	XX	XX	XX	XX	XX	
F-14A	XX	XX	XX	XX	XX	XX	
F-15A	XX	XX	XX	XX	XX	XX	
F-16A	XX	XX	XX	XX	XX	XX	
F-18	XX	XX	XX	XX	XX	XX	XX
F-4A	XX	XX	XX	XX	XX	XX	XX
F-5			XX	XX			
F-84B	XX		XX	XX	XX		
F-86D	XX	XX	XX	XX	XX	XX	
OV-10	XX	XX	XX	XX	XX	XX	XX
S-3A	XX	XX	XX	XX	XX	XX	XX
T-2	XX	XX	XX	XX	XX	XX	
T-38A	XX	XX	XX	XX	XX	XX	XX
T-39	XX	XX	XX	XX	XX	XX	
XB-70	XX		XX	XX	XX	XX	
YC-130	XX	XX		XX	XX	XX	
YC-14							
YF-16	XX	XX	XX	XX	XX	XX	

AIRCRAFT PERFORMANCE


MODEL	VMAXA	VMAXS	VCruise	CBTCEIL	SERCEIL	CBTRADIUS
A-10A	XX	XX	XX	XX	XX	XX
A-18	XX	XX	XX	XX		XX
A-4A	XX	XX	XX	XX	XX	XX
A-5A	XX	XX	XX	XX	XX	XX
A-6A	XX	XX	XX	XX	XX	XX
A-7	XX	XX	XX	XX	XX	XX
AV-8B	XX	XX	XX			XX
B-1	XX	XX	XX	XX	XX	XX
B-45C		XX			XX	XX
B-52F	XX			XX	XX	XX
B-52G	XX		XX			
B-58A	XX	XX		XX	XX	XX
C-130B	XX		XX			
C-130E	XX	XX	XX		XX	XX
C-135A	XX		XX	XX	XX	XX
C-141A	XX		XX	XX	XX	XX
C-5A	XX		XX	XX	XX	XX
E-3A	XX		XX			
F-100	XX		XX	XX	XX	XX
F-105	XX		XX	XX	XX	XX
F-111A	XX		XX	XX	XX	XX
F-14A	XX	XX	XX		XX	
F-15A	XX	XX	XX		XX	
F-16A	XX	XX			XX	XX
F-18	XX	XX	XX	XX		XX
F-4A	XX	XX	XX	XX	XX	XX
F-5	XX		XX	XX	XX	XX
F-84B	XX	XX	XX	XX	XX	
F-86D	XX				XX	XX
OV-10	XX	XX	XX		XX	
S-3A	XX	XX	XX		XX	XX
T-2	XX	XX	XX			
T-38A	XX	XX	XX	XX	XX	XX
T-39	XX	XX	XX	XX	XX	XX
XB-70						
YC-130						
YC-14						
YF-16						

APPENDIX F: ONE WAY ANALYSIS OF VARIANCE
 One-Sample Analysis Results

Sample Statistics:	Number of Obs.	awa	11
	Average		2118.82
	Variance		561931
	Std. Deviation		749.62
	Median		2217
Confidence Interval for Mean:		95 Percent	
Sample 1		1615.08 2622.55	10 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			

Hypothesis Test for H0: Mean = 0 Computed t statistic = 9.37451
 vs Alt: NE Sig. Level = 2.86391E-5
 at Alpha = 0.05 so reject H0.

Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	Number of Obs.	cbceil	19
	Average		47805.3
	Variance		6.6438E7
	Std. Deviation		8150.95
	Median		46900
Confidence Interval for Mean:		95 Percent	
Sample 1		43875.7 51734.9	18 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			

Hypothesis Test for H0: Mean = 0	Computed t statistic = 25.5649
vs Alt: NE	Sig. Level = 1.33227E-15
at Alpha = 0.05	so reject H0.


Frequency Histogram



One-Sample Analysis Results

Sample Statistics: Number of Obs.	09		
Average	36		
Variance	0.277778		
Std. Deviation	0.206349		
Median	0.454257		
	0		
Confidence Interval for Mean:	95	Percent	
Sample 1	0.124044	0.431512	35 D.F.
Confidence Interval for Variance:	0	Percent	
Sample 1			
Hypothesis Test for H0: Mean = 0	Computed t statistic = 3.669		
vs Alt: NE	Sig. Level = 8.03748E-4		
at Alpha = 0.05	so reject H0.		


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	eng
Number of Obs.	34
Average	2.5
Variance	3.22727
Std. Deviation	1.79646
Median	2
Confidence Interval for Mean:	95 Percent
Sample 1	1.87304 3.12696 33 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	
Hypothesis Test for H0: Mean = 0	Computed t statistic = 8.1145
vs Alt: NE	Sig. Level = 2.2925E-9
at Alpha = 0.05	so reject H0.


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	enghrs
Number of Obs.	25
Average	1350.06
Variance	1.39592E6
Std. Deviation	1181.49
Median	820
Confidence Interval for Mean:	95 Percent
Sample 1	862.244 1837.87 24 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	
Hypothesis Test for H0: Mean = 0	Computed t statistic = 5.71935
vs Alt: NE	Sig. Level = 6.92241E-6
at Alpha = 0.05	so reject H0.

Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	Number of Obs.	ff	31
	Average		11.0458
	Variance		77.5108
	Std. Deviation		8.80402
	Median		8.33
Confidence Interval for Mean:		95 Percent	
Sample 1		7.81571 14.2759	30 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			

Hypothesis Test for H_0 : Mean = 0
 vs H_1 : NE
 at Alpha = 0.05

Computed t statistic = 6.9855
 Sig. Level = 9.22532E-3
 so reject H_0 .

Frequency Histogram




One-Sample Analysis Results


Sample Statistics:	Number of Obs.	gtow	35
	Average		134429
	Variance		3.25712E10
	Std. Deviation		180475
	Median		56000
Confidence Interval for Mean:		95 Percent	
Sample 1		72419 196438	34 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			

Hypothesis Test for H_0 : Mean = 0	Computed t statistic = 4.40666
vs Alt: NE	Sig. Level = 9.95387E-5
at Alpha = 0.05	so reject H_0 .

Frequency Histogram




Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	Number of Obs.	gtow DIVIDE vol		
	Average	10		
	Variance	37.0000		
	Std. Deviation	158.864		
	Median	12.6041		
		36.313		
Confidence Interval for Mean:		95	Percent	
Sample 1		27.9819	46.0197	9 D.F.
Confidence Interval for Variance:		0	Percent	
Sample 1				
Hypothesis Test for H0: Mean = 0		Computed t statistic = 9.2832		
vs Alt: NE		Sig. Level = 6.6219E-6		
at alpha = 0.05		so reject H0.		


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	Number of Obs.	gtow DIVIDE ws	
	Average	29	
	Variance	4.02412	
	Std. Deviation	0.747225	
	Median	0.864422	
Confidence Interval for Mean:		95 Percent	
Sample 1		3.69524 4.35301	28 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			
Hypothesis Test for H0: Mean = 0		Computed t statistic = 25.0694	
vs Alt: NE		Sig. Level = 0	
at Alpha = 0.05		so reject H0.	

Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	11f
Number of Obs.	11
Average	6.77264
Variance	2.0014
Std. Deviation	1.41471
Median	7.333
Confidence Interval for Mean:	95 Percent
Sample 1	5.82197 7.7233 10 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	

Hypothesis Test for H0: Mean = 0	Computed t statistic = 15.8777
vs Alt: NE	Sig. Level = 2.02201E-8
at Alpha = 0.05	so reject H0.

Frequency Histogram



11f

One-Sample Analysis Results


Sample Statistics: Number of Obs.	serceil
Average	25
Variance	41018.8
Std. Deviation :	2.23502E8
Median	14950
	38820

Confidence Interval for Mean:	95 Percent
Sample 1	34846.3 47191.3 24 D.F.

Confidence Interval for Variance:	0 Percent
Sample 1	

Hypothesis Test for H0: Mean = 0	Computed t statistic = 13.7187
vs Alt: NE	Sig. Level = 7.4607E-13
at Alpha = 0.05	so reject H0.


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	Number of Obs.	11	ssd
	Average	0.545455	
	Variance	0.272727	
	Std. Deviation	0.522233	
	Median	1	
Confidence Interval for Mean:	95 Percent		
Sample 1	0.19452 0.896389	10 D.F.	
Confidence Interval for Variance:	0 Percent		
Sample 1			
Hypothesis Test for H0: Mean = 0	Computed t statistic = 3.4641		
vs Alt: NE	Sig. Level = 6.08085E-3		
at Alpha = 0.05	so reject H0.		

Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	Number of Obs.	ssta		11
	Average	ssta		6.36364
	Variance	ssta		11.0545
	Std. Deviation	ssta		3.32484
	Median	ssta		7
Confidence Interval for Mean:		95	Percent	
Sample 1		4.12938	8.59789	10 D.F.
Confidence Interval for Variance:		0	Percent	
Sample 1				

Hypothesis Test for H_0 : Mean = 0 Computed t statistic = 6.34792
vs Alt: NE Sig. Level = 8.37422E-5
at Alpha = 0.05 so reject H_0 .


Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	Number of Obs.	thrust		34
	Average			34756.5
	Variance			1.54224E9
	Std. Deviation			39271.4
	Median			19415
Confidence Interval for Mean:		95	Percent	
Sample 1		21050.8	48462.1	33 D.F.
Confidence Interval for Variance:		0	Percent	
Sample 1				
Hypothesis Test for H0: Mean = 0		Computed t statistic = 5.16059		
vs Alt: NE		Sig. Level = 1.17766E-5		
at Alpha = 0.05		so reject H0.		

Frequency Histogram




Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	Number of Obs.	thrust DIVIDE gtow	
	Average	33	
	Variance	0.391425	
	Std. Deviation	0.0483744	
	Median	0.219942	
		0.345	
Confidence Interval for Mean:	95 Percent		
Sample 1	0.313419 0.469431	32 D.F.	
Confidence Interval for Variance:	0 Percent		
Sample 1			
Hypothesis Test for H0: Mean = 0	Computed t statistic = 10.2235		
vs Alt: NE	Sig. Level = 1.31655E-11		
at Alpha = 0.05	so reject H0.		


Frequency Histogram



One-Sample Analysis Results

<p>Sample Statistics: Number of Obs. 32</p> <p style="padding-left: 20px;">Average 0.826883</p> <p style="padding-left: 20px;">Variance 0.200047</p> <p style="padding-left: 20px;">Std. Deviation 0.447267</p> <p style="padding-left: 20px;">Median 0.703102</p> <p>Confidence Interval for Mean: 95 Percent</p> <p style="padding-left: 20px;">Sample 1 0.665588 0.988177 31 D.F.</p> <p>Confidence Interval for Variance: 0 Percent</p> <p style="padding-left: 20px;">Sample 1</p> <p>Hypothesis Test for H0: Mean = 0 Computed t statistic = 10.4581</p> <p style="padding-left: 40px;">vs Alt: NE Sig. Level = 1.08794E-11</p> <p style="padding-left: 40px;">at Alpha = 0.05 so reject H0.</p>	
---	--

Frequency Histogram




One-Sample Analysis Results


Sample Statistics:	totalhrs
Number of Obs.	23
Average	2827.24
Variance	8.64743E6
Std. Deviation	2940.65
Median	1555
Confidence Interval for Mean:	95 Percent
Sample 1	1555.3 4099.17 22 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	

Hypothesis Test for H0: Mean = 0	Computed t statistic = 4.61087
vs Alt: NE	Sig. Level = 1.35702E-4
at Alpha = 0.05	so reject H0.

Frequency Histogram



Frequency Histogram




One-Sample Analysis Results

<p>Sample Statistics: Number of Obs.</p> <p style="padding-left: 20px;">Average</p> <p style="padding-left: 20px;">Variance</p> <p style="padding-left: 20px;">Std. Deviation</p> <p style="padding-left: 20px;">Median</p> <p>Confidence Interval for Mean:</p> <p style="padding-left: 20px;">Sample 1</p> <p>Confidence Interval for Variance:</p> <p style="padding-left: 20px;">Sample 1</p>	<p>ulf</p> <p>14</p> <p>9.74214</p> <p>6.3674</p> <p>2.52337</p> <p>10.75</p> <p>95 Percent</p> <p>8.26482 11.1995 13 D.F.</p> <p>0 Percent</p>
---	---

<p>Hypothesis Test for H0: Mean = 0</p> <p style="padding-left: 20px;">vs Alt: NE</p> <p style="padding-left: 20px;">at Alpha = 0.05</p>	<p>Computed t statistic = 14.4457</p> <p>Sig. Level = 2.19486E-9</p> <p>so reject H0.</p>
--	---


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	veruise
Number of Obs.	24
Average	437.542
Variance	4698.78
Std. Deviation	68.5477
Median	451.5
Confidence Interval for Mean:	95 Percent
Sample 1	408.59 466.494 23 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	
Hypothesis Test for H0: Mean = 0	Computed t statistic = 31.2703
vs Alt: NE	Sig. Level = 0
at Alpha = 0.05	so reject H0.


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	Number of Obs.	vmaxa		
	Average	27		
	Variance	754.593		
	Std. Deviation	101210		
	Median	318.135		
		602		
Confidence Interval for Mean:		95 Percent		
Sample 1		628.713 880.472	26 D.F.	
Confidence Interval for Variance:		0 Percent		
Sample 1				
Hypothesis Test for H0: Mean = 0		Computed t statistic = 12.3249		
vs Alt: NE		Sig. Level = 2.31348E-12		
at Alpha = 0.05		so reject H0.		


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	Number of Obs.	vmax	15
	Average		600.467
	Variance		17782.1
	Std. Deviation		133.35
	Median		602
Confidence Interval for Mean:		95 Percent	
Sample 1		526.601 674.332	14 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			
Hypothesis Test for H0: Mean = 0		Computed t statistic = 17.4395	
vs Alt: NE		Sig. Level = 6.8257E-11	
at Alpha = 0.05		so reject H0.	


Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	vol
Number of Obs.	10
Average	1370.4
Variance	804927
Std. Deviation	897.177
Median	1163.5
Confidence Interval for Mean:	95 Percent
Sample 1	728.423 2012.38 9 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	
Hypothesis Test for H0: Mean = 0	Computed t statistic = 4.83024
vs Alt: NE	Sig. Level = 9.33589E-4
at Alpha = 0.05	so reject H0.

Frequency Histogram



One-Sample Analysis Results


Sample Statistics:	Number of Obs.	wa	20
	Average		41146
	Variance		4.21295E9
	Std. Deviation		64907.2
	Median		17000.5

Confidence Interval for Mean:	95	Percent	
Sample 1	10761	71530.9	19 I.F.


Confidence Interval for Variance:	0	Percent	
Sample 1			

Hypothesis Test for H0: Mean = 0	Computed t statistic = 2.83497
vs Alt: NE	Sig. Level = 0.0105845
at Alpha = 0.05	so reject H0.

Frequency Histogram




Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	wavi
Number of Obs.	29
Average	2959.28
Variance	2.22048E7
Std. Deviation	4712.2
Median	2016
Confidence Interval for Mean:	95 Percent
Sample 1	1166.43 4752.12 28 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	
Hypothesis Test for H0: Mean = 0	Computed t statistic = 3.3819
vs Alt: NE	Sig. Level = 2.14005E-3
at Alpha = 0.05	so reject H0.

Frequency Histogram



Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	wavu		
Number of Obs.	26		
Average	1595.23		
Variance	1.78913E6		
Std. Deviation	1337.58		
Median	1355		
Confidence Interval for Mean:	95 Percent		
Sample 1	1054.84 2135.62	25 D.F.	
Confidence Interval for Variance:	0 Percent		
Sample 1			

Hypothesis Test for H0: Mean = 0	Computed t statistic = 6.0812
vs Alt: NE	Sig. Level = 2.35225E-6
at Alpha = 0.05	so reject H0.

Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	we
Number of Obs.	34
Average	56357.6
Variance	5.09945E9
Std. Deviation	71410.4
Median	25906
Confidence Interval for Mean:	95 Percent
Sample 1	31435.5 81279.6 33 D.F.


Confidence Interval for Variance:	0 Percent
Sample 1	

Hypothesis Test for H0: Mean = 0	Computed t statistic = 4.60182
vs Alt: NE	Sig. Level = 5.9478E-5
at Alpha = 0.05	so reject H0.

Frequency Histogram




Frequency Histogram



One-Sample Analysis Results

<p>Sample Statistics: Number of Obs. 10 Average 17.563 Variance 17.0068 Std. Deviation 4.12393 Median 16.8659</p> <p>Confidence Interval for Mean: 95 Percent Sample 1 14.6121 20.5139 9 D.F.</p> <p>Confidence Interval for Variance: 95 Percent Sample 1</p> <p>Hypothesis Test for H_0: Mean = 0 Computed t-statistic = 1.314675 vs H_1: NE Sig. Level = 0.26557E-01 at Alpha = 0.05 so reject H_0.</p>	
---	--


Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	Number of Obs.	28	we DIVIDE wavi
	Average	35.2013	
	Variance	1260.87	
	Std. Deviation	35.5087	
	Median	23.8228	
Confidence Interval for Mean:		95 Percent	
Sample 1		21.4293 48.9734	27 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			
Hypothesis Test for H0: Mean = 0		Computed t statistic = 5.2457	
vs Alt: NE		Sig. Level = 1.57472E-5	
at Alpha = 0.05		so reject H0.	


Frequency Histogram



Frequency Histogram




Frequency Histogram



One-Sample Analysis Results

Sample Statistics:	Number of Obs.	32	df
	Average	98.1719	
	Variance	896.013	
	Std. Deviation	29.9335	
	Median	94.95	
Confidence Interval for Mean:		95 Percent	
Sample 1		87.3772 108.967	31 D.F.
Confidence Interval for Variance:		0 Percent	
Sample 1			
Hypothesis Test for H_0 : Mean = 0		Computed t statistic = 16.5526	
vs H_1 : NE		Sig. Level = 0	
at Alpha = 0.05		so reject H_0 .	

Frequency Histogram




One-Sample Analysis Results

Sample Statistics:	Number of Obs.	we DIVIDE ws	28
	Average		1.87446
	Variance		0.070027
	Std. Deviation		0.264626
	Median		1.8928
Confidence Interval for Mean:	Sample 1	95 Percent	1.77183 1.9771 27 D.F.
Confidence Interval for Variance:	Sample 1	0 Percent	

Hypothesis Test for H0: Mean = 0	Computed t statistic = 37.4821
vs Alt: NE	Sig. Level = 0
at Alpha = 0.05	so reject H0.

Frequency Histogram




One-Sample Analysis Results


Sample Statistics:	ws
Number of Obs.	29
Average	40255
Variance	2.94592E9
Std. Deviation	54276.3
Median	17801
Confidence Interval for Mean:	95 Percent
Sample 1	19604.5 60905.5 28 D.F.
Confidence Interval for Variance:	0 Percent
Sample 1	

Hypothesis Test for H0: Mean = 0	Computed t statistic = 3.99401
vs Alt: NE	Sig. Level = 4.27014E-4
at Alpha = 0.05	so reject H0.

Frequency Histogram



Frequency Histogram



APPENDIX G: REGRESSION ANALYSIS

Model fitting results for: LOC totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-1.644169	2.349697	-0.6997	0.4941
LOC vmara	1.674174	0.368939	4.5378	0.0003
LOC vccus	-2.891408	1.030646	-2.8054	0.0127

R-SQ. (ADJ.) = 0.5399 SE = 0.607238 MAE = 0.414662 DurWat = 2.397
 Previously: 0.7060 1683.511947 963.114854 2.596
 19 observations fitted, forecast(s) computed for 5 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	8.52498	2	4.26249	11.5597	.0008
Error	5.89981	16	0.368738		
Total (Corr.)	14.4248	18			


R-squared = 0.590995

R-squared (Adj. for d.f.) = 0.53987

Std. error of est. = 0.607238

Durbin-Watson statistic = 2.39708

Plot of LOG totalhrs



Stepwise Selection for LOG totalhrs

Selection: Forward Maximum steps: 500 F-to-enter: 4.00
 Control: Manual Step: 2 F-to-remove: 4.00

R-squared: .95175 Adjusted: .93797 MSE: 0.0316714 d.f.: 7

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. LOG us	0.98550	88.4172	2. LOG we	.0818	.0404
7. LOG vmaxs	1.46814	34.1405	3. LOG weows	.0978	.0580
			4. LOG vmaxa	.1065	.0688
			5. LOG vcruise	.2166	.2954
			6. LOG gtow	.1600	.1577
			8. LOG gtowows	.1601	.1577

Model fitting results for: LOG totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-10.899863	1.781637	-6.1179	0.0005
LOG us	0.985498	0.104806	9.4030	0.0000
LOG vmaxs	1.468145	0.251266	5.8430	0.0006


R-SQ. (ADJ.) = 0.9380 SE= 0.177965 MAE= 0.132311 DurbinWat= 2.029
 Previously: 0.9380 0.177965 0.132311 2.029
 10 observations fitted, forecast(s) computed for 3 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	4.37345	2	2.18672	69.0440	.0000
Error	0.221700	7	0.0316714		
Total (Corr.)	4.59515	9			

R-squared = 0.951753 Std. error of est. = 0.177965
 R-squared (Adj. for d.f.) = 0.937969 Durbin-Watson statistic = 2.02894

Plot of LOG totalhrs



Model fitting results for: LOG totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-4.78732	3.188752	-1.5013	0.1497
LOG gtow	0.272277	0.142315	1.9132	0.0709
LOG vmaxa	1.415453	0.385744	3.6694	0.0016

R-SQ. (ADJ.) = 0.3906 SE= 0.704933 MAE= 0.523254 DurWat= 2.408
 Previously: 0.0000 0.000000 0.000000 0.000

22 observations fitted. forecasts computed for 5 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	7.68378	2	3.84189	7.73125	.0035
Error	9.44168	19	0.496931		
Total (Corr.)	17.1255	21			


R-squared = 0.448676

R-squared (Adj. for d.f.) = 0.390642

Std. error of est. = 0.704933

Durbin-Watson statistic = 2.40754

Plot of LOG totalhrs



Model fitting results for LSC data.bas

Independent variable	Coefficient	Std. error	T-value	P-value
CONSTANT	-4.002193	3.457228	-1.1576	.254
LSC wt	7.062916	1.864498	3.791	.0007
LSC flow	7.772036	1.478102	5.265	.0001
LSC area	7.062916	1.864498	3.791	.0007

R-squared = .520742
 R-squared (Adj. for d.f.) = .42429

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	7.51159	3	2.50386	5.43279	.00099
Error	6.91320	15	.460880		
Total + Corr.	14.4248	18			


R-squared = 0.520742


R-squared (Adj. for d.f.) = 0.42429

Std. error of est. = 0.678681

Durbin-Watson statistic = 2.34636

Plot of LOG totalhrs





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

Model fitting results for: LOG totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-84.270745	28.941247	-2.9118	0.0141
LOG ws	-4.975196	2.265801	-2.1958	0.0505
LOG we	63.286114	20.602163	3.0718	0.0106
LOG we DIVIDE LOG ws	-64.565417	21.422902	-3.0139	0.0118
LOG vcruise	1.176559	0.947667	1.2415	0.2402

R-SQ. (ADJ.) = 0.3979 SE= 0.571264 MAE= 0.368527 DurbinWat= 1.101
 Previously: 0.0000 0.000000 0.000000 0.000
 16 observations fitted, forecast(s) computed for 4 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	4.54038	4	1.13509	3.47823	.0454
Error	3.58976	11	0.326342		
Total (Corr.)	8.13014	15			

R-squared = 0.558462
 R-squared (Adj. for d.f.) = 0.397903

Std. error of est. = 0.571264
 Durbin-Watson statistic = 1.10092

Plot of LOG totalhrs



Model fitting results for: LOG totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-5.024162	3.147581	-1.5962	0.1269
LOG we	0.318161	0.154253	2.0626	0.0531
LOG vmaxa	1.411488	0.380101	3.7135	0.0015

R-SQ. (ADJ.) = 0.4062 SE= 0.695872 MAE= 0.499345 DurWat= 2.481
 Previously: 0.0000 0.000000 0.000000 0.000

22 observations fitted, forecast(s) computed for 5 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	7.92494	2	3.96247	8.18290	.0027
Error	9.20052	19	0.484238		
Total (Corr.)	17.1255	21			

R-squared = 0.462758
 R-squared (Adj. for d.f.) = 0.406206

Std. error of est. = 0.695872
 Durbin-Watson statistic = 2.48074

Plot of LOG totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-6726.836552	1012.435443	-6.6442	0.0003
vmaxa	2.330642	0.87699	2.6575	0.0326
wl	35.224491	10.321967	3.4126	0.0112
ws DIVIDE wavi	97.288109	23.353698	4.1659	0.0042
we	0.132533	0.037022	3.5799	0.0090

R-SQ. (ADJ.) = 0.9280 SE= 712.704726 MAE= 436.237562 DurbWat= 0.892
 Previously: 0.0000 0.000000 0.000000 0.000
 12 observations fitted, forecast(s) computed for 10 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	74004804.	4	18501201.	36.4234	.0001
Error	3555636.	7	507948.		
Total (Corr.)	77560440.	11			

R-squared = 0.954157
 R-squared (Adj. for d.f.) = 0.92796

Std. error of est. = 712.705
 Durbin-Watson statistic = 0.892229

(X 1000) Plot of totalhrs



Stepwise Selection for totalhrs

Selection: Backward Maximum steps: 500 F-to-enter: 4.00
 Control: Manual Step: 3 F-to-remove: 4.00

R-squared: .94437 Adjusted: .90728 MSE: 973045 d.f.: 9

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. vmaxa	8.14256	83.3816	7. cq	.2576	.5684
2. ws DIVIDE wavi	194.380	20.6772	8. ff RAISE 3	.2691	.6243
3. wavu	2.33100	28.8253	9. serceil	.0949	.0727
4. gtow	-0.02500	42.1519			
5. weows	-13021.5	46.2526			
6. gtowows	909.081	8.3928			

Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	12749.531908	4000.619381	3.1869	0.0111
vmaxa	8.142559	0.891715	9.1314	0.0000
ws DIVIDE wavi	194.379668	42.746922	4.5472	0.0014
wavu	2.331001	0.434166	5.3689	0.0005
gtow	-0.025003	0.003851	-6.4924	0.0001
weows	-1.302149E4	1914.664197	-6.8009	0.0001
gtowows	909.080784	313.797035	2.8970	0.0177


R-SQ. (ADJ.) = 0.9073 SE= 986.430249 MAE= 609.756674 DurWat= 2.240
 Previously: 0.6783 1760.963833 1067.911642 2.201
 16 observations fitted, forecast(s) computed for 2 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	148657177.	6	24776196.	25.4625	.0000
Error	8757402.	9	973045.		
Total (Corr.)	157414578.	15			

R-squared = 0.944367 Stnd. error of est. = 986.43
 R-squared (Adj. for d.f.) = 0.907279 Durbin-Watson statistic = 2.24001

(X 1000) Plot of totalhrs



Stepwise Selection for totalhrs

Selection: Forward
Control: Manual

Maximum steps: 500
Step: 2

F-to-enter: 4.00
F-to-remove: 4.00

R-squared: .92416 Adjusted: .88625 MSE: 677250 d.f.: 10

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. vmaxa	4.96938	32.8124			
2. wl	54.0451	31.5327			
3. ws DIVIDE wavi	156.815	19.1014			
4. gtow	-0.01428	16.8802			
5. wavi	0.87475	8.8128			

Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-9300.697159	1377.000197	-6.7543	0.0001
vmaxa	4.969379	0.867528	5.7282	0.0002
wl	54.045094	9.624444	5.6154	0.0002
ws DIVIDE wavi	156.815223	35.880272	4.3705	0.0014
gtow	-0.01428	0.003476	-4.1085	0.0021
wavi	0.874754	0.294665	2.9686	0.0141

R-SQ. (ADJ.) = 0.8862 SE= 822.951850 MAE= 577.829045 Durblwat= 2.369
 Previously: 0.0000 0.000000 0.000000 0.0000

16 observations fitted, forecast(s) computed for 8 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	F-value
Model	82532342.	5	16506468.	24.3728	.0000
Error	6772497.	10	677250.		
Total (Corr.)	89304839.	15			


R-squared = 0.924164

Std. error of est. = 822.952

R-squared (Adj. for d.f.) = 0.886246

Durbin-Watson statistic = 2.3691

(X 1000) Plot of totalhrs



Stepwise Selection for totalhrs

Selection: Backward
Control: Manual

Maximum steps: 500
Step: 3

F-to-enter: 4.00
F-to-remove: 4.00

R-squared: .74445

Adjusted: .63797

MSE: 3.49019E6

d.f.: 12

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. vmaxa	6.67724	15.9442	5. ff	.0811	.0728
2. wl	46.0690	4.9906	6. gtow	.1020	.1156
3. wavu	2.29306	10.5702	7. we DIVIDE wavi	.3706	1.7509
4. we	-0.04799	7.8223			
8. ws DIVIDE wavi	234.509	9.5858			

Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-1.191286E4	3036.321909	-3.9235	0.0020
vmaxa	6.677243	1.672231	3.9930	0.0018
wl	46.069036	20.622153	2.2340	0.0453
wavu	2.293064	0.7053	3.2512	0.0069
we	-0.047986	0.017157	-2.7968	0.0161
ws DIVIDE wavi	234.508931	75.74366	3.0961	0.0093

R-SQ. (ADJ.) = 0.6380 SE= 1868.205589 MAE= 1131.250970 DurWat= 2.332
 Previously: 0.0000 0.000000 0.000000 0.0000
 18 observations fitted, forecast(s) computed for 4 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	122010310.	5	24402062.	6.99161	.0028
Error	41882305.	12	3490192.		
Total (Corr.)	163892615.	17			


R-squared = 0.744453

Std. error of est. = 1868.21

R-squared (Adj. for d.f.) = 0.637975

Durbin-Watson statistic = 2.33243

(X 1000) Plot of totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-1.147354E4	3148.144654	-3.6445	0.0030
vmaxa	7.064267	1.70583	4.1412	0.0012
wl	42.037725	20.760173	2.0249	0.0639
ws DIVIDE wavi	219.724726	78.772184	2.7894	0.0153
we	-0.048325	0.018965	-2.5482	0.0243
wavi	1.600989	0.552012	2.9003	0.0124

R-SQ. (ADJ.) = 0.6008 SE= 1924.645484 MAE= 1128.024872 Durbwat= 2.794
 Previously: 0.0000 0.000000 0.000000 0.000
 19 observations fitted, forecast(s) computed for 5 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	118866336.	5	23773267.	6.41782	.0033
Error	48155383.	13	3704260.		
Total (Corr.)	167021719.	18			

R-squared = 0.711682
 R-squared (Adj. for d.f.) = 0.60079

Std. error of est. = 1924.65
 Durbin-Watson statistic = 2.79406

(X 1000) Plot of totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-1.07769814	3383.833165	-3.1848	0.0111
vmaxa	7.539102	1.781093	4.2329	0.0022
wl	46.55265	20.553606	2.2649	0.0498
wavu	2.576484	0.800791	3.2174	0.0105
we DIVIDE wavi	-407.440752	172.078252	-2.3678	0.0421
we	-0.243616	0.108182	-2.2519	0.0508
ff	-29.563053	72.889472	-0.4056	0.6945
gtow	0.060143	0.036311	1.6563	0.1320
ws DIVIDE wavi	992.657877	332.812353	2.9826	0.0154

R-SQ. (ADJ.) = 0.7060 SE= 1683.511947 MAE= 963.114854 DurWat= 2.596
 Previously: 0.0000 0.000000 0.000000 0.000
 18 observations fitted, forecast(s) computed for 4 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	138384703.	8	17299088.	6.10331	.0069
Error	25507912.	9	2834212.		
Total (Corr.)	163892615.	17			

R-squared = 0.844362
 R-squared (Adj. for d.f.) = 0.706017

Std. error of est. = 1683.51
 Durbin-Watson statistic = 2.59577

(X 1000) Plot of totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-4966.2844	3144.648299	-1.5793	0.1383
vmaxa	6.003015	2.1484	2.7942	0.0152
wl	32.998473	25.591643	1.2894	0.2197
ws DIVIDE wavi	23.604575	56.384542	0.4186	0.6823
gtow	-0.000798	0.00478	-0.1670	0.8699
oq	-965.452538	1271.433844	-0.7593	0.4612

R-SQ. (ADJ.) = 0.3701 SE= 2417.689738 MAE= 1407.425309 DurbinWat= 2.073
 Previously: 0.0000 0.000000 0.000000 0.000
 19 observations fitted, forecast(s) computed for 5 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	91033811.	5	18206762.	3.11481	.0458
Error	75987908.	13	5845224.		
Total (Corr.)	167021719.	18			


R-squared = 0.545042

R-squared (Adj. for d.f.) = 0.370058

Std. error of est. = 2417.69

Durbin-Watson statistic = 2.07341

(X 1000) Plot of totalhrs



Stepwise Selection for totalhrs

Selection: Backward Maximum steps: 500 F-to-enter: 4.00
 Control: Manual Step: 1 F-to-remove: 4.00

R-squared: .79187 Adjusted: .67834 MSE: 3.10099E6 d.f.: 11

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. vmaxa	6.99089	20.6238	7. cq	.0658	.0435
2. ws DIVIDE wavi	145.229	4.0321			
3. wavu	1.61572	5.0800			
4. gtow	-0.01673	7.3714			
5. weows	-7687.24	7.2815			
6. gtowows	1108.63	4.0873			

Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	4414.960281	6371.611386	0.6929	0.5027
vmaxa	6.990887	1.539388	4.5413	0.0008
ws DIVIDE wavi	145.229295	72.324928	2.0080	0.0698
wavu	1.615719	0.716861	2.2539	0.0456
gtow	-0.016729	0.006162	-2.7150	0.0201
weows	-7687.240688	2848.782698	-2.6984	0.0207
gtowows	1108.633655	548.367505	2.0217	0.0682


R-SQ. (ADJ.) = 0.6783 SE= 1760.963833 MAE= 1067.911642 DurWat= 2.201
 Previously: 0.9073 986.430249 609.756674 2.240
 18 observations fitted, forecast(s) computed for 4 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	129781685.	6	21630281.	6.97527	.0030
Error	34110930.	11	3100994.		
Total (Corr.)	163892615.	17			

R-squared = 0.79187 Std. error of est. = 1760.96
 R-squared (Adj. for d.f.) = 0.678345 Durbin-Watson statistic = 2.20112

(X 1000) Plot of totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-5385.623196	2834.875627	-1.8998	0.0799
vmaxa	5.653046	2.029718	2.7851	0.0155
wl	49.042364	26.462688	1.8533	0.0867
ws DIVIDE wavi	28.888184	51.854799	0.5571	0.5869
gtow	-0.00159	0.0045	-0.3532	0.7296
ff	-104.436616	66.999514	-1.5588	0.1431

R-SQ. (ADJ.) = 0.4457 SE= 2267.861733 MAE= 1349.153035 DurbWat= 2.503
 Previously: 0.0000 0.000000 0.000000 0.000
 19 observations fitted, forecast(s) computed for 5 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	100160160.	5	20032032.	3.89486	.0223
Error	66861559.	13	5143197.		
Total (Corr.)	167021719.	18			


R-squared = 0.599683

R-squared (Adj. for d.f.) = 0.445716

Std. error of est. = 2267.86

Durbin-Watson statistic = 2.50286

(X 1000) Plot of totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-5741.815982	2748.137258	-2.0893	0.0569
vmaxa	5.458323	1.982469	2.7533	0.0164
wl	50.908485	25.537522	1.9935	0.0676
ws DIVIDE wavi	29.270494	50.323741	0.5816	0.5708
gtow	-0.002188	0.004418	-0.4951	0.6288
ff RAISE 2	-3.894643	2.120978	-1.8362	0.0893

R-SQ. (ADJ.) = 0.4776 SE= 2201.647296 MAE= 1240.300951 Durbwat= 2.549
 Previously: 0.0000 0.000000 0.000000 0.0000
 19 observations fitted, forecast(s) computed for 5 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	104007459.	5	20801492.	4.29140	.0159
Error	63014261.	13	4847251.		
Total (Corr.)	167021719.	18			

R-squared = 0.622718
 R-squared (Adj. for d.f.) = 0.47761

Std. error of est. = 2201.65
 Durbin-Watson statistic = 2.5485

(X 1000) Plot of totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-1.008728E4	3137.053076	-3.2155	0.0092
vmaxa	9.338453	1.839435	5.0768	0.0005
wl	28.362929	20.576164	1.3784	0.1981
wavu	1.895789	0.70721	2.6807	0.0231
we DIVIDE wavi	150.108292	46.354616	3.2383	0.0089
we	-0.040676	0.013158	-3.0914	0.0114
thrust DIVIDE gtow	-1.094131E4	3508.578638	-3.1184	0.0109
ff	190.285517	94.305322	2.0178	0.0712

R-SQ. (ADJ.) = 0.7291 SE= 1616.030773 MAE= 902.049649 DurbWat= 2.861
 Previously: 0.0000 0.000000 0.000000 0.000
 18 observations fitted, forecast(s) computed for 4 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	137777061.	7	19682437.	7.53667	.0025
Error	26115555.	10	2611555.		
Total (Corr.)	163892615.	17			

R-squared = 0.840654
 R-squared (Adj. for d.f.) = 0.729113

Std. error of est. = 1616.03
 Durbin-Watson statistic = 2.861

(X 1000) Plot of totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-9813.6704	2863.161766	-3.4276	0.0065
vmaxa	8.694981	1.66529	5.2213	0.0004
wl	33.215811	19.614328	1.6934	0.1212
wavu	2.121268	0.709265	2.9908	0.0136
ws DIVIDE wavi	260.320297	73.636122	3.5352	0.0054
we	-0.055863	0.016039	-3.4830	0.0059
thrust DIVIDE gtow	-8589.128032	3137.092016	-2.7379	0.0209
ff	126.039147	78.127578	1.6132	0.1378

R-SQ. (ADJ.) = 0.7533 SE= 1542.096194 MAE= 867.476921 DurbWat= 2.692
 Previously: 0.0000 0.000000 0.000000 0.000
 18 observations fitted, forecast(s) computed for 4 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	140112009.	7	20016001.	8.41694	.0016
Error	23780607.	10	2378061.		
Total (Corr.)	163892615.	17			


R-squared = 0.854901

R-squared (Adj. for d.f.) = 0.753332

Std. error of est. = 1542.1

Durbin-Watson statistic = 2.69151

(X 1000) Plot of totalhrs



Stepwise Selection for LOG TACAIR.totalhrs

Selection: Backward Control: Manual	Maximum steps: 500 Step: 2	F-to-enter: 4.00 F-to-remove: 4.00			
R-squared: .98415	Adjusted: .96830	MSE: 0.0214077 d.f.: 5			
Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. LOG TACAIR.vmax	0.69923	31.3357	5. LOG TACAIR.weow	.3518	.5649
2. LOG TACAIR.ws/L	18.7550	25.2687	7. LOG TACAIR.serc	.1047	.0443
3. LOG TACAIR.wavu	2.42565	21.5854			
4. LOG TACAIR.gtow	-17.0349	22.1357			
6. LOG TACAIR.gtow	17.1285	21.5176			

Model fitting results for: LOG TACAIR.totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	6.874211	2.94801	2.3318	0.0671
LOG TACAIR.vmax	0.699229	0.124911	5.5978	0.0025
LOG TACAIR.ws/LOG wavi	18.754967	3.730998	5.0268	0.0040
LOG TACAIR.wavu	2.425654	0.522095	4.6460	0.0056
LOG TACAIR.gtow	-17.03489	3.620704	-4.7049	0.0053
LOG TACAIR.gtowows	17.128471	3.692506	4.6387	0.0056

R-SQ. (ADJ.) = 0.9683 SE= 0.146314 MAE= 0.087641 DurbinWat= 2.870
 Previously: 0.0000 0.000000 0.000000 0.0000


11 observations fitted, forecast(s) computed for 5 missing val. of dep. var.

Analysis of Variance for the Full Regression


Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	6.64717	5	1.32943	62.1007	.0002
Error	0.107039	5	0.0214077		
Total (Corr.)	6.75421	10			

R-squared = 0.984152 Std. error of est. = 0.146314
 R-squared (Adj. for d.f.) = 0.968305 Durbin-Watson statistic = 2.8699

Plot of LOG TACAIR.totalhrs



Plot of LOG totalhrs



Stepwise Selection for totalhrs

Selection: Forward	Maximum steps: 500	F-to-enter: 4.00			
Control: Manual	Step: 4	F-to-remove: 4.00			
R-squared: .95398	Adjusted: .93097	MSI: 480629			
		d.f.: 8			
Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. vmaxa	2.33585	7.4979			
2. w1	30.9369	13.6181			
3. ws DIVIDE wavi	101.317	20.9875			
4. we	0.14790	24.1840			

Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-6765.355351	983.580912	-6.8783	0.0001
vmaxa	2.335848	0.853053	2.7382	0.0255
w1	30.936863	8.383352	3.6903	0.0061
ws DIVIDE wavi	101.316795	22.115742	4.5812	0.0018
we	0.147903	0.030076	4.9177	0.0012

R-SQ. (ADJ.) = 0.9310 SE= 693.273796 MAE= 422.562358 DurbWat= 1.256
 Previously: 0.9299 698.587123 417.243790 1.346
 13 observations fitted, forecast(s) computed for 9 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	79705877.	4	19926469.	41.4592	.0000
Error	3845028.	8	480629.		
Total (Corr.)	83550906.	12			

R-squared = 0.95398


R-squared (Adj. for d.f.) = 0.93097

224

Std. error of est. = 693.274

Durbin-Watson statistic = 1.25585

(X 1000) Plot of totalhrs



Model fitting results for: LOG totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-6.339618	1.689781	-3.7517	0.0072
LOG vmaxa	0.775971	0.234725	3.3059	0.0130
LOG w1	0.360059	0.393167	0.9158	0.3902
LOG ws DIVIDE LOG wavi	1.251752	0.559645	2.2367	0.0604
LOG we	0.315797	0.717507	0.4401	0.6731
LOG gtow	-0.476118	0.483354	-0.9850	0.3574


R-SQ. (ADJ.) = 0.9829 SE= 0.277782 MAE= 0.151160 DurbinWat= 2.151
 Previously: 0.9034 0.252306 0.176933 1.817
 13 observations fitted, forecast(s) computed for 9 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	7.36841	5	1.47368	19.0983	.0006
Error	0.540141	7	0.0771631		
Total (Corr.)	7.90855	12			

R-squared = 0.931702 Std. error of est. = 0.277782
 R-squared (Adj. for d.f.) = 0.882917 Durbin-Watson statistic = 2.15053

Plot of LOG totalhrs



Model fitting results for: totalhrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-1696.690309	1845.018323	-0.9196	0.3794
wl	13.233161	19.357693	0.6836	0.5097
we	0.268227	0.136831	1.9603	0.0784
gtow	-0.036665	0.062259	-0.5889	0.5690
ff	-29.825079	61.67896	-0.4836	0.6391
crew	-485.906955	708.258672	-0.6861	0.5083
thrust	-0.0023	0.070846	-0.0325	0.9747

R-SQ. (ADJ.) = 0.6070 SE= 1557.048481 MAE= 848.770571 DurbWat= 3.092
 Previously: 0.0000 0.000000 0.000000 0.000
 17 observations fitted, forecast(s) computed for 7 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	74453699.	6	12408950.	5.11836	.0119
Error	24244000.	10	2424400.		
Total (Corr.)	98697698.	16			


R-squared = 0.754361

R-squared (Adj. for d.f.) = 0.606978

Std. error of est. = 1557.05

Durbin-Watson statistic = 3.09212

(X 1000) Plot of totalhrs



Model fitting results for: LOG NAVAIR.enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	0.231436	2.452182	0.0944	0.9261
LOG NAVAIR.wcows	-2.666201	1.079392	-2.4701	0.0260
LOG NAVAIR.vmaxa	1.285233	0.385039	3.3379	0.0045

R-SQ. (ADJ.) = 0.4073 SE= 0.633723 MAE= 0.441969 DurWat= 2.332
 Previously: 0.6917 0.350327 0.238806 2.077
 18 observations fitted, forecast(s) computed for 6 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	5.49564	2	2.74782	6.84211	.0077
Error	6.02407	15	0.401605		
Total (Corr.)	11.5197	17			


R-squared = 0.477064

R-squared (Adj. for d.f.) = 0.40734

Std. error of est. = 0.633723

Durbin-Watson statistic = 2.33171

Plot of LOG NAVAIR.enghrs



Stepwise Selection for enghrs

Selection: Forward
Control: Manual

Maximum steps: 500
Step: 3

F-to-enter: 4.00
F-to-remove: 4.00

R-squared: .91470

Adjusted: .87814

MSE: 136185

d.f.: 7

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. ws	0.23374	20.4361	2. we	.3010	.5976
3. gtow	-0.04050	7.9813	4. we DIVIDE ws	.0421	.0107
6. vmaxa	1.72672	15.6414	5. gtowows	.6135	3.6217
			7. vmaxs	.3278	.7226
			8. vcruiise	.3501	.8382

Model fitting results for: enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-664.707451	339.993428	-1.9551	0.0915
ws	0.233744	0.051706	4.5206	0.0027
gtow	-0.0405	0.014336	-2.8251	0.0256
vmaxa	1.726718	0.436599	3.9549	0.0055

R-SQ. (ADJ.) = 0.8781 SE= 369.032815 MAE= 246.540949 DurWat= 1.518
 Previously: 0.0000 0.000000 0.000000 0.0000
 11 observations fitted, forecast(s) computed for 2 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	F-value
Model	10222599.	3	3407533.	25.0213	.0004
Error	953297.	7	.136185.		
Total (Corr.)	11175896.	10			


R-squared = 0.914701

Std. error of est. = 369.033

R-squared (Adj. for d.f.) = 0.878144

Durbin-Watson statistic = 1.51797

(X 1000) Plot of enghrs



Stepwise Selection for LOG enghrs

Selection: Forward Maximum steps: 500 F-to-enter: 4.00
 Control: Manual Step: 2 F-to-remove: 4.00

R-squared: .88402 Adjusted: .80669 MSE: 0.0769604 d.f.: 6

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. LOG ws	0.86904	3.6446	4. LOG we	.1578	.1277
2. LOG gtow	-0.53820	1.6251	5. LOG we/LOG ws	.1595	.1305
3. LOG vmaxa	1.31783	9.0148	6. LOG gtowows	.1740	.1561
8. LOG vcruise	-1.33836	2.7475	7. LOG vmaxs	.1116	.0631

Model fitting results for: LOG enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	4.250695	4.13965	1.0268	0.3441
LOG ws	0.869042	0.455213	1.9091	0.1048
LOG gtow	-0.538204	0.422185	-1.2748	0.2495
LOG vmaxa	1.317829	0.438916	3.0025	0.0239
LOG vcruise	-1.338361	0.807433	-1.6576	0.1485

R-SQ. (ADJ.) = 0.8067 SE= 0.277417 MAE= 0.172304 DurWat= 2.479
 Previously: 0.0000 0.000000 0.000000 0.0000

11 observations fitted, forecast(s) computed for 2 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	3.51950	4	0.879874	11.4328	.0057
Error	0.461762	6	0.0769604		
Total (Corr.)	3.98126	10			


R-squared = 0.884016

F-squared (Adj. for d.f.) = 0.806693

Std. error of est. = 0.277417

Durbin-Watson statistic = 2.4788

Plot of LOG enghrs



Stepwise Selection for enghrs

Selection: Forward Maximum steps: 500 F-to-enter: 4.00
 Control: Manual Step: 3 F-to-remove: 4.00

R-squared: .70983 Adjusted: .64287 MSE: 533350 d.f.: 13

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. vmaxa	3.20573	29.0995	2. wl	.2895	1.0974
6. ff	67.1994	5.2112	3. ws DIVIDE wavi	.3199	1.3680
8. thrust DIVIDE w	-2143.66	12.5099	4. wavu	.0179	.0038
			5. stow	.1798	.4008
			7. thrust	.2148	.5805

Model fitting results for: enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	165.128623	571.955487	0.2887	0.7774
vmaxa	3.205728	0.59427	5.3944	0.0001
ff	67.199366	29.437158	2.2828	0.0399
thrust DIVIDE we	-2143.663629	606.079306	-3.5369	0.0036


R-SQ. (ADJ.) = 0.6429 SE= 730.308349 MAE= 510.506300 DurbinWat= 1.611
 Previously: 0.0000 0.000000 0.000000 0.000
 17 observations fitted, forecast(s) computed for 5 missing val. of dep. var.

Analysis of Variance for the Full Regression


Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	16961072.	3	5653691.	10.6003	.0008
Error	6933554.	13	533350.		
Total (Corr.)	23894625.	16			

R-squared = 0.709828 Std. error of est. = 730.308
 R-squared (Adj. for d.f.) = 0.642865 Durbin-Watson statistic = 1.61062

(X 1000) Plot of enghrs



(X 1000) Plot of enghrs



Model fitting results for: LOG NAVAIR.enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-6.801848	3.433679	-1.9809	0.0829
LOG NAVAIR.ws	0.796297	0.190425	4.1817	0.0031
LOG NAVAIR.vmaxs	1.034254	0.494547	2.0913	0.0699

R-SQ. (ADJ.) = 0.6917 SE= 0.350327 MAE= 0.238806 DurbinWat= 2.077
 Previously: 0.9380 0.177965 0.132311 2.029
 11 observations fitted, forecast(s) computed for 3 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	2.99943	2	1.49972	12.2198	.0037
Error	0.981830	8	0.122729		
Total (Corr.)	3.98126	10			


R-squared = 0.753387

R-squared (Adj. for d.f.) = 0.691734

Std. error of est. = 0.350327

Durbin-Watson statistic = 2.07705

Plot of LOG NAVAIR.enghrs



Stepwise Selection for enghrs

Selection: Backward Control: Manual	Maximum steps: 500 Step: 1	F-to-enter: 4.00 F-to-remove: 4.00			
R-squared: .99853	Adjusted: .99266	MSE: 10641.1 d.f.: 2			
Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. vmaxa	0.72158	9.8922	3. we DIVIDE wavi	.1219	.0149
2. wl	7.85314	21.3107			
4. ws DIVIDE wavi	29.1986	7.1067			
5. wavu	0.36939	13.6414			
6. we	0.21610	156.0330			
7. gtow	-0.07261	98.5882			
8. ff	-18.2202	5.8794			
9. crew	-706.749	60.8837			

Model fitting results for: enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-574.336252	430.901101	-1.3329	0.3141
vmaxa	0.721582	0.229424	3.1452	0.0880
wl	7.853144	1.70116	4.6163	0.0439
ws DIVIDE wavi	29.198641	10.952899	2.6658	0.1166
wavu	0.369393	0.100014	3.6934	0.0661
we	0.216104	0.0173	12.4913	0.0063
gtow	-0.072606	0.007312	-9.9292	0.0100
ff	-18.220246	7.514298	-2.4247	0.1362
crew	-706.74891	90.576275	-7.8028	0.0160


R-SQ. (ADJ.) = 0.9927 SE= 103.155852 MAE= 36.385286 DurWat= 3.175
 Previously: 0.9730 197.873714 100.886893 2.678
 11 observations fitted, forecast(s) computed for 6 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	14485948.	8	1810743.	170.165	.0059
Error	21282.3	2	10641.1		
Total (Corr.)	14507230.	10			

R-squared = 0.998533 Std. error of est. = 103.156
 R-squared (Adj. for d.f.) = 0.992665 Durbin-Watson statistic = 3.17494

(X 1000) Plot of enghrs



Stepwise Selection for LOG enghrs

Selection: Forward	Maximum steps: 500	F-to-enter: 4.00			
Control: Manual	Step: 1	F-to-remove: 4.00			
R-squared: .79223	Adjusted: .72990	MSE: 0.148068			
		d.f.: 10			
Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
1. LOG vmaxa	0.88684	7.2676	2. LOG wl	.0419	.0158
3. LOG ws/LOG wavi	2.23734	12.0092	4. LOG wavu	.1411	.1829
6. LOG gtow	-1.51740	5.8557	5. LOG we	.2859	.8014
			7. LOG crew	.3133	.9793
			8. LOG we/LOG wavi	.2886	.8177

Model fitting results for: LOG enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	1.097246	2.630871	0.4171	0.6854
LOG vmaxa	0.886838	0.328965	2.6958	0.0225
LOG ws/LOG wavi	2.237343	0.645617	3.4654	0.0061
LOG gtow	-1.517396	0.62706	-2.4199	0.0361

R-SQ. (ADJ.) = 0.7299 SE= 0.384796 MAE= 0.231345 DurWat= 2.637
 Previously: 0.2515 0.773003 0.487195 2.272
 14 observations fitted, forecast(s) computed for 11 missing val. of dep. var.


Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	5.64600	3	1.88200	12.7104	.0010
Error	1.48068	10	0.148068		
Total (Corr.)	7.12669	13			

R-squared = 0.792234
 R-squared (Adj. for d.f.) = 0.729904

Std. error of est. = 0.384796
 Durbin-Watson statistic = 2.63739

Plot of LOG enghrs



Model fitting results for: enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	-1796.984046	675.352982	-2.6608	0.0324
vmaxa	1.314872	0.662056	1.9860	0.0874
ws DIVIDE wavi	40.676451	25.293659	1.6082	0.1518
we	0.082504	0.0245	3.3675	0.0120

R-SQ. (ADJ.) = 0.8159 SE= 516.828624 MAE= 281.317892 DurWat= 2.817
 Previously: 0.0000 0.000000 0.000000 0.000
 11 observations fitted, forecast(s) computed for 6 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	12637447.	3	4212482.	15.7705	.0017
Error	1869783.	7	267112.		
Total (Corr.)	14507230.	10			


R-squared = 0.871114

Std. error of est. = 516.829

R-squared (Adj. for d.f.) = 0.815877

Durbin-Watson statistic = 2.81673

(X 1000) Plot of enghrs



Stepwise Selection for enghrs

Selection: Forward
Control: Manual

Maximum steps: 500
Step: 3

F-to-enter: 4.00
F-to-remove: 4.00

R-squared: .98651

Adjusted: .97301

MSE: 39154

d.f.: 5

Variables in Model	Coeff.	F-Remove	Variables Not in Model	P.Corr.	F-Enter
2. wl	8.12227	6.5471	1. vmaxa	.3713	.6396
6. we	0.25753	155.5007	3. we DIVIDE wavi	.0171	.0012
7. gtow	-0.08093	55.9442	4. ws DIVIDE wavi	.1100	.0490
8. ff	-31.1604	12.0470	5. wavu	.5678	1.9034
9. crew	-688.305	62.7862			

Model fitting results for: enghrs

Independent variable	coefficient	std. error	t-value	sig.level
CONSTANT	427.599034	286.234759	1.4939	0.1954
wl	8.122269	3.174332	2.5587	0.0507
we	0.25753	0.020652	12.4700	0.0001
gtow	-0.080931	0.01082	-7.4796	0.0007
ff	-31.160437	8.977676	-3.4709	0.0178
crew	-688.304888	86.865819	-7.9238	0.0005

R-SQ. (ADJ.) = 0.9730 SE= 197.873714 MAE= 100.886893 Durbwat= 2.678
 Previously: 0.8159 516.828624 281.317892 2.317
 11 observations fitted, forecast(s) computed for 6 missing val. of dep. var.

Analysis of Variance for the Full Regression

Source	Sum of Squares	DF	Mean Square	F-Ratio	P-value
Model	14311460.	5	2862292.	73.1034	.0001
Error	195770.	5	39154.0		
Total (Corr.)	14507230.	10			


R-squared = 0.986505

R-squared (Adj. for d.f.) = 0.973011

Std. error of est. = 197.874

Durbin-Watson statistic = 2.67847

(X 1000) Plot of enghrs



LIST OF REFERENCES

- Bard, Yonathan. Nonlinear Parameter Estimation. New York, NY: Academic Press, 1974.
- Boren, H. E. Jr. A Computer Model for Estimating Development and Procurement Costs of Aircraft (DAPCA-III). The Rand Corporation Report R-1854-PR, March 1976.
- Day, C. F., Findley, D. P. Aircraft Cost Handbook. J. Watson Noah Inc. Report FR-1834-USAF, December 1982.
- Dryden, J., Britt, T., and Binnings-DePriester, S. An Analysis of Combat Aircraft Avionics Production Costs. The Rand Corporation Note N-1685-AF, March 1981.
- Kroenke, David M. Database Processing: Fundamentals, Design, Implementation. Chicago, IL: Science Research Associates, Inc., 1983.
- Large, Joseph P., Campbell, Harry G., and Cates, David. Parametric Equations for Estimating Aircraft Airframe Costs. The Rand Corporation Report R-1693-PA&E, May 1975.
- Levenson, G. S., Boren, H. E., Tihansky, D. P., and Timson, F. Cost-Estimating Relationships for Aircraft Airframes. The Rand Corporation Report R-761-PR, February 1972.
- Noah, J. W., Daniels, J. M., Day, C. F., and Eskew, H. L. Estimating Aircraft Costs By Parametric Methods. J. Watson Noah Associates, Inc. Report FR-103-USN, September 1973.
- Noah, J. W., et al. Aircraft Cost Handbook. J. Watson Noah Associates, Inc. Report TR-103-USN, July 1973.
- Sanchez, Luis R., and DeiRossi, James A. Methods of Estimating Fixed-Wing Airframe Costs. Planning Research Corporation Report PRC R-547A, April 1967.
- Statistical Graphics Corporation, Statsgraphics 2.1, 1986.
- Wolverton, R. W. Airborne Systems Software Acquisition Engineering Guidebook for Software Cost Analysis and Estimating. TRW Defense and Space Systems Group Report ASD-TR-80-5025, September 1980.

BIBLIOGRAPHY

- Adolph, C. E., and Montgomery, P. Cost-effective Testing of Software Intensive Systems. Paper presented at Society of Flight Test Engineers, Sixteenth Annual Symposium, Seattle WA, August 1985.
- Anderson, Lee G., and Settle, Russell F. Benefit-Cost Analysis; A Practical Guide. Lexington Book, 1974.
- Beck, C. L., and Pfeil, D. L. Airframe RTD&E Cost Estimating: A Justification For and Development of Unique Cost Estimating Relationships According to Aircraft Type. M.S. Thesis, Air Force Institute of Technology, Wright-Patterson Air Force Base, OH, September 1982.
- Bennett, Bruce R. The Use of Parametric Cost Estimating Relationships as They Pertain to Aircraft Airframes; A New Perspective. M.S. Thesis, Naval Postgraduate School, Monterey, CA, March 1980.
- Blecke, Curtis J. Financial Analysis For Decision Making. Englewood Cliffs, NJ: Prentice-Hall, 1966.
- Boehm, Barry W. Software Engineering Economics. Englewood Cliffs, NJ: Prentice-Hall, 1981.
- Clark, Forrest D. Applied Cost Engineering. New York: M. Dekker, 1978.
- Committee For Economic Development, Improving Federal Program Performance: A Statement of National Policy. Washington D. C., 1971.
- Cummins, J. M. Cost Overruns In Defense Procurement, A Problem Of Entrepreneurial Choice Under Uncertainty. Northwestern University, 1973.
- Department of Defense. Contractor Cost Data Reporting System, NAVMAT P-5241. Washington D.C., 1973.
- Department of Defense. Military Standard Work Breakdown Structures For Defense Materiel Items, MIL-STD-881A. Washington D.C., 1975.
- Greenberg, Joel S. "Risk Analysis: Challenge to the Aerospace Decision-Maker." Astronautics & Aeronautics, 12 (1974), 48-57
- Johnston, J. Econometric Methods. New York: McGraw-Hill, 1963.

Livingston, John J. Management Planning And Control, Math Models. New York: McGraw-Hill, 1970.

US Task Force on Reducing Cost of Defense System Acquisition. Design to Cost, Commercial Practices vs. DOD Practice. Washington D.C., 1973.

Yourdon, Edward. Managing the Structured Techniques. New York, NY: Yourdon Inc., 1986.

INITIAL DISTRIBUTION LIST

	No. Copies
1. Defense Technical Information Center Cameron Station Alexandria, Va. 22304-6145	2
2. Library, Code 0142 Naval Postgraduate School Monterey, Ca. 93943-5002	2
3. Air Force Flight Test Center Mrs. Carol Guthrie Code AC Edwards Air Force Base, Ca. 93523	1
4. Boeing Aerospace Company Mr. Henry F. Schwartz M/S 1758 P.O. Box 3707 Seattle, Wa. 98124	1
5. Department of the Air Force Headquarters Aeronautical Systems Division Attn: ACCM - Mr. Daniels Wright-Patterson Air Force Base, Oh. 45433-6503	1
6. Department of the Navy Naval Center for Cost Analysis (NCA-1) Washington, D.C. 20350-1100	1
7. Douglas Aircraft Company Mr. Len Chartier Cl-243 18A-40 3855 Lakewood Blvd. Long Beach, Ca. 90846	1
8. Douglas Aircraft Company Mr. Loren Frye Cl-240 41-80 3855 Lakewood Blvd. Long Beach, Ca. 90846	1
9. Fairchild Republic Company Mr. Stan Granowetter Conklin Street Farmingdale, N.Y. 11735	1

- | | | |
|-----|--|---|
| 10. | Fairchild Republic Company
Mr. Robert Hoffman
Building 55
Conklin Street
Farmingdale, N.Y. 11735 | 1 |
| 11. | General Dynamics Corporation
Mr. John Denheyer
M/Z 1638
P.O. Box 748
Fort Worth, Tx. 76101 | 1 |
| 12. | Grumman Aerospace Corporation
Mr. Jim McDonagh
MS C20-GHQ
Bethpage, N.Y. 11714 | 1 |
| 13. | Lockheed-Georgia Company
Mr. Bob Farmer
Dept. 81-11, Zone 23
86 South Cobb Dr.
Marietta, Ga. 30063 | 1 |
| 14. | Lockheed-California Company
Mr. Phil Finkle
Dept. 81-16, B/66, P/A-1
P.O. Box 551
Burbank, Ca. 91520 | 1 |
| 15. | LTV Aerospace and Defense
Aero Products Division
Mr. Clint Miller
MS 220-70
P.O. Box 225907
Dallas, Tx. 75265 | 1 |
| 16. | McDonnell Aircraft Company
Mr. Raymond Yarck
Dept. 015
P.O. Box 516
St. Louis, Mo. 63166 | 1 |
| 17. | Naval Air Systems Command
Mr. Bob Patterson
AIR-5243
Jefferson Plaza 2
Washington D.C. 20361 | 2 |

18. Naval Air Test Center 1
 Karen Tyson
 Business Resource Department
 Antisubmarine Aircraft Test Directorate
 Patuxent River, Md. 20670-5304
19. Office of Secretary of Defense (PA&E) 2
 Cost Analysis Division (Ms. Asher)
 Room 2D278, Pentagon
 Washington D.C. 20301-1800
20. Rockwell International Corporation 1
 Mr. Gayle Turner
 Bldg. 3
 4300 E. Fifth Ave.
 Columbus, Oh. 43216
21. Rockwell International Corporation 1
 Mr. George Bostater
 Dept 196, 011-ZR09
 P.O. Box 90098
 Los Angeles, Ca. 90009
22. LCDR Robert W. Fannesbeck USN 1
 976 Happy Valley Road
 Pleasanton, Ca. 94566
23. Professor Tung X. Bui, Code 54Bd 2
 Department of Administrative Science
 Naval Postgraduate School
 Monterey, Ca. 93943-5000
24. Major David J. Lee USMC 1
 1506 Smith Street
 McLean, Va. 22101
25. LT W.J. Moore Jr. USNR 1
 NAMO
 Patuxent River, Md. 20670
26. Major William Foster USMC 1
 E202 Amber Drive
 Tacoma, Wa. 98499
27. Professor Taracad R. Sivasankaran, Code 54Sj 1
 Department of Administrative Sciences
 Naval Postgraduate School
 Monterey, Ca. 93943-5000

END

7-87

Ditic