INCL		
UNCL	JARIEL	

٠	•	-	`	

· · · ·					
		• • • • •	DIH	FILE	COPY
4					
	PORT DOCUM	ENTATION PAGE			
		16. RESTRICTIVE MARKI	NGS		
		3. DISTRIBUTION/AVAILA	BILITY OF REPO	RT	
AD-A191 583	·				14 - J
		Approved for public	release; distrib	ution is unlim	lled.
PERFORMING ORGANIZATION REPORT NUMBE	R(S)	5. MONITORING ORGAN	ZATION REPORT	NUMBER(S)	
NAME OF PERFORMING ORGANIZATION	6b. OFFICE SYMBOL (I applicable)	7a. NAME OF MONITORI	NG ORGANIZATI	ON	
Naval Ocean Systems Center	NOSC	Naval Ocean System	ns Center		
San Diego, California 92152-5000		San Diego, Californ	ia 92152-5000		
NAME OF FUNDING/SPONSORING ORGANIZA	TION 86. OFFICE SYMBOL	9. PROCUREMENT INST			
	(If applicable)				
ADDRESS (City, State and ZIP Code)		10. SOURCE OF FUNDIN	G NUMBERS		
· · · · · · · · · · · · · · · · · · ·		PROGRAM ELEMENT NO	PROJECT NO.	TASK NO.	AGENCY ACCESSION NO
		RDDA	MP72	DCA	DN305 117
TITLE (include Security Classification)					
Meteor Burst Communication Buoy Relay	Tests				
PERSONAL AUTHOR(S)					
J.E. Bickel	<u></u>				
J.E. Bickel TYPE OF REPORT I3b. TIME CON Tresentation/Speech	/ERED	14. DATE OF REPORT	(Year, Month, Day)	15. PAGE COL	TIC
J.E. Bickel TYPE OF REPORT 13b. TIME COV <u>Tresentation/Speech</u> FROM Nov SUPPLEMENTARY NOTATION	ERED 1987 TO Nov 1987	14. DATE OF REPORT January 1988	(Year, Month, Day)	15. PAGE COL	TIC
J.E. Bickel TYPE OF REPORT 13b. TIME CON Presentation/Speech FROM Nov SUPPLEMENTARY NOTATION	ЕВЕД 1987 ТО Nov 1987	14. DATE OF REPORT January 1988	(Year, Month, Day)	15. PAGE COL	TIC
J.E. Bickel TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES	TERED 1987 TO Nov 1987 18. SUBJECT TERMS	14. DATE OF REPORT January 1988 (Continue on Amerso I necessary and ic	(Year, Month, Day) Ientiliyby block number)	15. PAGE COL	TIC ECTE R 2 3 1988
J.E. Bickel I. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP SUB-GROUP	TERED 1987 TO Nov 1987 18. SUBJECT TERMS meteor trails ionize	14. DATE OF REPORT January 1988 (Continue on otherse I necessary and it	(Year, Month, Day) tentila by block number)	15. PAGE COL	TIC LECTE R 2 3 1988
J.E. Bickel TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP SUB-GROUP	PERED 1987 TO Nov 1987 18. SUBJECT TERMS meteor trails ionize relay function battery-powered r	14. DATE OF REPORT January 1988 (Continue on offerse Il necessary and ic the state of the state	(Year, Month, Day) tentiliyby block number)	15. PAGE COL	TIC ECTE R 2 3 1988
J.E. Bickel a. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP SUB-GROUP	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS	14. DATE OF REPORT January 1988 (Continue on otherse if necessary and it	(Year, Month, Day) Tentiliyby block number)	15. PAGE DOL	TIC ECTE R 2 3 1988
J.E. Bickel I. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP SUB-GROUP A metage built communications (MBC)	VERED 1987 TO Nov 1987 18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cock number) link is limited	14. DATE OF REPORT January 1988 (Continue on offerse Il necessary and it to St	(Year, Month, Day) Ientifybyblock number)	15. PAGE COL	TIC LECTE R 2 3 1988 C. E
J.E. Bickel a. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP SUB-GROUP AMSTRACT (Continue on reverse if measurey and identity by bill A meteor burst communications (MBC) which meteor trails ionize, which is typica	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cot number) link is limited to approx illy 100km 20km, and	14. DATE OF REPORT January 1988 (Continue on Amore I measury and ic the second	(Yeer, Month, Day) tentily by block number) tiles (nmi). Thi	15. PAGE COL SEL Market State S is due to the	E Physical height
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP SUB-GROUP A meteor burst communications (MBC) which meteor trails ionize, which is typica Longer range communications can be a	VERED 1987 TO Nov 1987 18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cost number) link is limited to approx illy 100km 20km, and schieved by using meteo	14. DATE OF REPORT January 1988 (Continue on Afferse & necessary and it imately 1000 nautical m it to the curvature of the physics relays. Over the	(Year, Month, Day) tentily by block number) tilles (nmi). Thi e arth.	15. PAGE COL SEL	TIC ECTE R 2 3 1988 Ca E physical height
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES 1D GROUP SUB-GROUP A meteor burst communications (MBC) which meteor trails ionize, which is typica Longer range communications can be a nction, but are generally not practical for lo	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cock number) link is limited to approx. lly 100km 20km, and chieved by using meteo ong periods of time if the	14. DATE OF REPORT January 1988 (Continue on officerse Il necessary and it instead imately 1000 nautical m d to the curvature of the r burst relays. Over the ship is required for othe	(Year, Month, Day) fendify by block number) files (nmi). Thi e earth. e oceans, ships er missions. An	15. PAGE COL SEL S is due to the at sea can prother alternat	TIC ECTE R 2 3 1988 C E physical height rovide the relay ive is the use of
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES 1D GROUP SUB-GROUP A meteor burst communications (MBC) which meteor trails ionize, which is typica Longer range communications can be a nction, but are generally not practical for lo loys, which are allowed to drift or are mode	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS control of the second second battery-powered r CONUS control of the second second control of the second second control of the second seco	14. DATE OF REPORT January 1988 (Continue on Averse & necessary and it instead imately 1000 nautical m d to the curvature of the r burst relays. Over the e ship is required for oth the deep ocean bottom.	(Yeer, Month, Day) tentily by block number) tiles (nmi). Thi e earth. e oceans, ships er missions. An	15. PAGE COL SECOND S is due to the at sea can prother alternat	E Physical height rovide the relay ive is the use of
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES 1D GROUP SUB-GROUP A meteor burst communications (MBC) which meteor trails ionize, which is typication Longer range communications can be a nction, but are generally not practical for to toys, which are allowed to drift or are moon This paper describes a relatively large N	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS occ number) link is limited to approx and the seamounts or to ABC relay buoy with rer	14. DATE OF REPORT January 1988 (Continue on Herse I necessary and it is a second seco	(Year, Month, Day) fentity by block number) hiles (nmi). Thi e earth. e oceans, ships er missions. An capability and	15. PAGE COL S is due to the at sea can protect alternat presents the r	TIC ECTE R 2 3 1988 C E physical height rovide the relay ive is the use of esults of a buoy
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES 1D GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary and identify by bi A meteor burst communications (MBC) which meteor trails ionize, which is typica Longer range communications can be a nction, but are generally not practical for to toys, which are allowed to drift or are moot This paper describes a relatively large N Id ship relay test between San Diego, San I eteor burst master and remote station system of the station system of the system	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cot number) link is limited to approx lily 100km 20km, and chieved by using meteo ong periods of time if the ord to seamounts or to MBC relay buoy with rer Francisco, and Hawair m in a buoy and operatin	14. DATE OF REPORT January 1988 (Continue on there I measure and it is a second	(Yeer, Month, Day) tentify by block number) tiles (nmi). Thi e earth. e oceans, ships er missions. An capability and the feasibility of ler buoys are po	15. PAGE COL S is due to the at sea can protect alternat presents the r f mounting a t ssible if neede	TIC ECTE R 2 3 1988 Ca E physical height rovide the relay ive is the use of esults of a buoy pattery-powered of for only a few
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP GROUP GROUP SUB-GROUP A meteor burst communications (MBC) which meteor trails ionize, which is typics Longer range communications can be a nction, but are generally not practical for lo loys, which are allowed to drift or are moc This paper describes a relatively large N Id ship relay test between San Diego, San I eteor burst master and remote station syster ort emergency messages or to act as a re- ccessary.	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS control of the seamounts of the relay function battery-powered r CONUS control of the seamounts and the seamounts of the red to seamounts of to ABC relay buoy with rer Francisco, and Hawaif. m in a buoy and operatin mote station only, oper	14. DATE OF REPORT January 1988 (Continue on Herse I necessary and it imately 1000 nautical m d to the curvature of the r burst relays. Over the e ship is required for oth the deep ocean bottom. note and master station The tests demonstrate to ing it for 6 months. Small rating within range of m	(Yeer, Month, Day) tentifyby block number) tiles (nmi). This e arth. e oceans, ships er missions. An capability and the feasibility of ler buoys are po- naster stations	15. PAGE COL S is due to the at sea can pr nother alternat presents the r f mounting a b ssible if neede so that a large	TIC ECTE R 2 3 1988 CE physical height rovide the relay ive is the use of esults of a buoy pattery-powered of for only a few re battery is not
J.E. Bickei TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES D GROUP GROUP SUB-GROUP AMSTRACT (Continue on reverse i measury and identity by bit A meteor burst communications (MBC) which meteor trails ionize, which is typicat Longer range communications can be a metion, but are generally not practical for lo toys, which are allowed to drift or are more This paper describes a relatively large N d ship relay test between San Diego, San Dietor burst master and remote station syster ort emergency messages or to act as a re- cessary.	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS oct number) link is limited to approx and the subject of time if the ord to seamounts or to ABC relay buoy with rer Francisco, and Hawair ² . min a buoy and operatif mote station only, oper	14. DATE OF REPORT January 1988 (Continue on there if necessary and it is a state of the state of the state of the state of the is to the curvature of the r burst relays. Over the e ship is required for othe the deep ocean bottom. The tests demonstrate to ag it for 6 months. Small ating within range of m	(Year, Month, Day) fendify by block number) ties (nmi). Thi e earth. e oceans, ships er missions. An capability and the feasibility of ler buoys are po naster stations i	15. PAGE COL S is due to the at sea can pr nother alternat presents the r f mounting a b ssible if neede so that a large	TIC ECTE R 2 3 1988 C E physical height rovide the relay ive is the use of esults of a buoy pattery-powered d for only a few je battery is not
J.E. Bickel J.E. Bickel TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES D GROUP SUB-GROUP AMSTRACT (Continue on reverse i necessary and identify by ba A meteor burst communications (MBC) which meteor trails ionize, which is typical Longer range communications can be a notion, but are generally not practical for lo oys, which are allowed to drift or are mood This paper describes a relatively large N d ship relay test between San Diego, San 1 tetor burst master and remote station syster ort emergency messages or to act as a re cessary. During these tests messages were succe rizontally polarized antennas in the seawa	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cot number) link is limited to approx ally 100km 20km, and chieved by using meteo ong periods of time if the ored to seamounts or to ABC relay buoy with rer Francisco, and Hawair m in a buoy and operatir mote station only, oper ssfully relayed between the environment was obs	14. DATE OF REPORT January 1988 (Continue on themes I measure and it imately 1000 nautical m d to the curvature of the r burst relays. Over the e ship is required for oth the deep ocean bottom. The tests demonstrate ing it for 6 months. Small ating within range of m CONUS and Hawaii, an iserved.	(Yeer, Month, Day) tentifyby block number) tiles (nmi). Thi e arth. e oceans, ships er missions. Arr capability and the feasibility of ler buoys are pon haster stations in nd the relative	15. PAGE COL S is due to the at sea can protocolor presents the r f mounting a t ssible if neede so that a larg performance co	TIC ECTE R 2 3 1988 Con E physical height rovide the relay ive is the use of esults of a buoy pattery-powered of for only a few the battery is not
J.E. Bickel TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES D GROUP SUB-GROUP GROUP GROUP SUB-GROUP Ameteor burst communications (MBC) which meteor trails ionize, which is typics Longer range communications can be a anction, but are generally not practical for la oys, which are allowed to drift or are mode This paper describes a relatively large N d ship relay test between San Diego, San I teteor burst master and remote station syste: ort emergency messages or to act as a re- cessary. During these tests messages were succe rizontally polarized antennas in the seawa Brasented at Mateor Pure Communications	18. SUBJECT TERMS meteor trails ionizer relay function battery-powered r CONUS construction battery-powered r construction const	14. DATE OF REPORT January 1988 (Continue on Herse I necessary and it is a state of the state of	(Yeer, Month, Day) tentily by block number) tentily by block number (tentily by block number) tentily by block number) tentily by block number (tentily by block number) tentily	15. PAGE COL S is due to the at sea can pr nother alternat presents the r f mounting a b ssible if neede so that a larg performance co	TIC ECTE R 2 3 1988 C E physical height rovide the relay ive is the use of esults of a buoy battery-powered of for only a few the battery is not of vertically and
J.E. Bickel TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP GROUP SUB-GROUF Ameteor burst communications (MBC) which meteor trails ionize, which is typicat Longer range communications can be a nction, but are generally not practical for lo toys, which are allowed to drift or are mood This paper describes a relatively large N ad ship relay test between San Diego, San Dietor burst master and remote station syster ort emergency messages or to act as a re- scessary. During these tests messages were succe- prizontally polarized antennas in the seawa Presented at Meteor Burst Communication	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS oct number) link is limited to approx. lly 100km 20km, and chieved by using meteo ong periods of time if the ord to seamounts or to ABC relay buoy with rer Francisco, and Hawaif. m in a buoy and operatif mote station only, oper ssfully relayed between the environment was obs- ions (MBC) Symposium	14. DATE OF REPORT January 1988 (Continue on Herse I necessary and it instead	(Year, Month, Day) fentily by block number) fields (nmi). Thi e earth. e oceans, ships er missions. An capability and the feasibility of ler buoys are po- naster stations are nd the relative nd, 4-5 Nov 19	15. PAGE COL S is due to the at sea can pr nother alternat presents the r f mounting a b ssible if neede so that a larg performance co 987.	TIC ECTE R 2 3 1988 Ca E physical height rovide the relay ive is the use of esults of a buoy pattery-powered of for only a few the battery is not of vertically and
J.E. Bickel TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES 1D GROUP SUB-GROUP ABSTRACT (Continue on reverse if necessary and identify by in A meteor burst communications (MBC) which meteor trails ionize, which is typica Longer range communications can be a nction, but are generally not practical for lo ioys, which are allowed to drift or are mood This paper describes a relatively large N id ship relay test between San Diego, San 1 eteor burst master and remote station system iort emergency messages or to act as a re- recessary. During these tests messages were succeor prizontally polarized antennas in the seawa Presented at Meteor Burst Communication	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cot number) link is limited to approx ally 100km 20km, and chieved by using meteo ong periods of time if the ordet to seamounts or to ABC relay buoy with rer Francisco, and Hawair . m in a buoy and operatin mote station only, oper ssfully relayed between ther environment was obs- tions (MBC) Symposium	14. DATE OF REPORT January 1988 (Continue on there I measure and it is a second	(Yeer, Month, Day) tentifyby block number) tiles (nmi). Thi e arth. e oceans, ships er missions. Arr capability and the feasibility of ler buoys are pon haster stations are nd the relative ind, 4-5 Nov 19	15. PAGE COL S is due to the at sea can protocolor presents the r f mounting a b ssible if neede so that a larg performance co 887.	TIC ECTE R 2 3 1988 Con E physical height rovide the relay ive is the use of esults of a buoy battery-powered of for only a few the battery is not of vertically and
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES LD GROUP GROUP SUB-GROUP ABSTRACT (Continue on reverse il necessary and identify by in A meteor burst communications (MBC) which meteor trails ionize, which is typic: Longer range communications can be a nction, but are generally not practical for la toys, which are allowed to drift or are mode This paper describes a relatively large N id ship relay test between San Diego, San I eteor burst master and remote station syste: ort emergency messages or to act as a re- cessary. During these tests messages were succe- prizontally polarized antennas in the seawa Presented at Meteor Burst Communication	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS (CONUS)	14. DATE OF REPORT January 1988 (Continue on Herse I necessary and it is a state of the state of	(Yeer, Month, Day) tentifyby block number) tiles (nmi). Thi e earth. e oceans, ships er missions. An capability and the feasibility of ler buoys are po haster stations and the relative nd, 4-5 Nov 19	15. PAGE COL S is due to the at sea can pr nother alternat presents the r f mounting a b ssible if neede so that a larg performance co 987.	TIC ECTE R 2 3 1988 C E physical height rovide the relay ive is the use of esults of a buoy battery-powered of for only a few te battery is not of vertically and
J.E. Bickel TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES D GROUP GROUP SUB-GROUF SUB-GROUF A meteor burst communications (MBC) which meteor trails ionize, which is typicat Longer range communications can be a nction, but are generally not practical for lo toys, which are allowed to drift or are mood This paper describes a relatively large N ad ship relay test between San Diego, San Dietor burst master and remote station system iort emergency messages or to act as a re- recessary. During these tests messages were succe prizontally polarized antennas in the seawa Presented at Meteor Burst Communication DISTRIBUTION/AVAILABILITY OF ABSTRACT	18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS oct number) link is limited to approx. lly 100km 20km, and chieved by using meteo ong periods of time if the ored to seamounts or to ABC relay buoy with rer Francisco, and Hawaif. m in a buoy and operatif mote station only, oper ssfully relayed between the environment was obs- tions (MBC) Symposium	14. DATE OF REPORT January 1988 (Continue on Herse I necessary and it instead	(Year, Month, Day) fentily by block number) fields (nmi). Thi e earth. e oceans, ships er missions. An capability and the feasibility of ler buoys are po- naster stations are nd the relative ind, 4-5 Nov 19 Y CLASSIFICATION	15. PAGE COL S EL S S S CALL S S S CALL S S S CALL S S S CALL S S S S S S S S S S S S S S S S S S S	TIC ECTE R 2 3 1988 C E physical height rovide the relay ive is the use of esults of a buoy pattery-powered of for only a few the battery is not of vertically and
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES 1D GROUP COSATI CODES 1D GROUP SUB-GROUP AMSTRACT (Continue on reverse if necessary and identify by in A meteor burst communications (MBC) which meteor trails ionize, which is typicat Longer range communications can be a nction, but are generally not practical for in 100ys, which are allowed to drift or are mood This paper describes a relatively large N 1d ship relay test between San Diego, San I eteor burst master and remote station system fort emergency messages or to act as a re- recessary. During these tests messages were succe- prizontally polarized antennas in the seawa Presented at Meteor Burst Communication DISTRIBUTION/AVAILABILITY OF ABSTRACT JUNCLASSIFIED/UNLIMITED X SAME AS R	18. SUBJECT TERMS neteor trails ionizer relay function battery-powered r CONUS cot number) link is limited to approx link is limited to approx cot number) link is limited to approx link is limited to approx cot number) link is limited to approx link is limited to approx cotheved by using meteo org periods of time if the reference to seamounts or to ABC relay buoy with ref Francisco, and Hawair . m in a buoy and operating mote station only, oper ssfully relayed between ter environment was obs ions (MBC) Symposium PT DTIC USERS	14. DATE OF REPORT January 1988 (Continue on Herse I messary and it is a second	(Yeer, Month, Day) tentifyby block number) tiles (nmi). Thi e earth. e oceans, ships er missions. Arr capability and the feasibility of ler buoys are ponaster stations and the relative ind the relative nd, 4-5 Nov 19 Y CLASSIFICATIO	15. PAGE COL Second Strategy S	physical height rovide the relay ive is the use of esults of a buoy battery-powered of for only a few the battery is not of vertically and
J.E. Bickel A. TYPE OF REPORT Presentation/Speech SUPPLEMENTARY NOTATION COSATI CODES 1D GROUP SUB-GROUP COSATI CODES 1D GROUP SUB-GROUP ABSTRACT (Continue on reverse i necessary and identify by is A meteor burst communications (MBC) which meteor trails ionize, which is typic: Longer range communications can be a nction, but are generally not practical for la toys, which are allowed to drift or are mode This paper describes a relatively large N id ship relay test between San Diego, San 1 eteor burst master and remote station system iort emergency messages or to act as a re- icessary. During these tests messages were success presented at Meteor Burst Communication DISTRIBUTION/AVAILABILITY OF ABSTRACT UNCLASSIFIED/UNLIMITED X SAME AS R NAME OF RESPONSIBLE INDIVIDUAL	TO Nov 1987 18. SUBJECT TERMS meteor trails ionize relay function battery-powered r CONUS cot number) link is limited to approx link is limited to seamounts or to MBC relay buoy with rer Francisco, and Hawaif mote station only, oper list environment was obs lons (MBC) Symposium	14. DATE OF REPORT January 1988 (Continue on Amore I measury and it imately 1000 nautical m d to the curvature of the r burst relays. Over the e ship is required for oth the deep ocean bottom. The tests demonstrate to a for 6 months. Small a ting within range of m CONUS and Hawaii, an iserved. The Hagne, Netherland 21. ABSTRACT SECURIT UNCLASSIFIED 22b. TELEPHONE (measure A	(Yeer, Month, Day) tentifyby block number) tiles (nmi). Thi e earth. e oceans, ships er missions. An capability and the feasibility of ler buoys are po haster stations and the relative nd, 4-5 Nov 19 Y CLASSIFICATIO Vew Code)	15. PAGE COL S is due to the at sea can pr nother alternat presents the r f mounting a t ssible if neede so that a larg performance co 987.	TICLECTE R 2 3 1988 C E physical height rovide the relay ive is the use of esults of a buoy pattery-powered d for only a few the battery is not of vertically and

1. METEOR BURST COMMUNICATION BUOY RELAY TESTS

by John E. Bickel Naval Ocean Systems Center San Diego, CA 92152-5000

1.1 INTRODUCTION

A meteor burst communications (MBC) link is limited to approximately 1000 nautical miles (nmi). This is due to the physical height at which meteor trails ionize, which is typically 100 km \pm 20 km, and to the curvature of the earth.

Longer range communications can be achieved by using meteor burst relays. Over the oceans, ships at sea can provide the relay function, but are generally not practical for long periods of time if the ship is required for other missions. Another alternative is the use of buoys, which are allowed to drift or are moored to seamounts or to the deep ocean bottom.

This paper describes a relatively large MBC relay buoy with remote and master station capability and presents the results of a buoy and ship relay

test between San Diego, San Francisco, and Hawaii . The tests demonstrate the feasibility of mounting a battery-powered meteor burst master and remote station system in a buoy and operating it for 6 months. Smaller buoys are possible if needed for only a few short emergency messages or to act as a remote station only, operating within range of master stations so that a large battery is not necessary.

During these tests messages were successfully relayed between CONUS and Hawaii, and the relative performance of vertically and horizontally polarized antennas in the seawater environment was observed.

1.2 BUOY RELAY SYSTEM

An MBC relay buoy was developed and built for deployment in the open ocean that would survive at least 90 days and in sea states of six or more. The buoy system includes the meteor burst communications equipment capable of continuous remote station operation and 2 hours a day master station operation, its antenna, the battery power supply, a switching circuit for remotely selecting redundant MBC equipment and battery-charging circuits, and environmental sensors.

A comprehensive study of possible buoy designs, MBCS buoy antennas, and power supply systems was made before selecting the optimum design.

A surface-following, pendulous spherical buoy, shown in Figure 1, was selected from among several classes of buoys as the most effective at maintaining the vertical stability of the MBCS antenna while providing the necessary reserve buoyancy to insure proper flotation. This buoy consists of a spherical float with a rigid "arm" extending downward to form a "ball-insocket joint" where the float rotates in the ocean support. A ballast weight is suspended from the end of the arm, well below the effective depth of the surface wave motion, to provide a righting moment when the buoy is tilted. A design objective for the buoy was that it maintain the antenna within 10 degrees of vertical for conditions up to and including sea state six. -----

MARCASS DATES SAME TO CONSTRUCT DATES

Constant of the second second

The antenna was a 15-foot-high "J", shown in Figure 2, with characteristics equivalent to a vertical half-wave dipole. Vertical polarization. omnidirectional coverage, and 2.1 dBi of gain were achieved.

The MBC equipment was manufactured by Meteor Communications Corp. (MCC) and had previously been used for various other MBC applications tests. MCC model 540A remote station transceivers and MCC 530 master station transceivers were deployed and used as illustrated in Figure 3. The transmitter of the MCC 540A provided 300 watts of peak RF power. The MCC 530 transmitter provided 500 watts of RF power. Their instantaneous data rates were 4 kbps. Software modifications by MCC for this buoy relay test demonstration were incorporated to provide an automatic message relay capability so that test and information messages were relayed automatically from an MBCS master to remote, to master. to a final remote station destination and acknowledgement returned to the originating master station.

A second MCC MBC system was also deployed which included an MCC model 512 remote station which had been modified to perform as a 33% duty cycle probe-and-listen master station for use on the buoy. However, because of weather and ship schedule problems, it was not tested.

PICK

bility Codes

Special

Dist

COP

The MBCS primary power supply selected was a zinc-air battery 16" x 16" x 62" weighing 450 lb and rated at 1200 ampere-hours. It was used to recharge a lead-acid secondary battery at a 0.7-ampere rate, which provided the short periods of high power drain required by the MBCS transmitter. Its expected voltage variation over a 16-hour test cycle, when powering the MCC 512 master station for 1 hour each day, is shown in Figure 4. The zinc-air battery was recently developed by the U.S. Coast Guard for use on their thousands of aidsto-navigation buoys for up to 2 years each and has proven to be very reliable and optimum for buoy applications.

1.3 TEST PLAN SYNOPSIS

The basic test configuration included the meteor burst stations indicated in Figure 3 and described as follows (the equipment in parentheses was for testing the relay system with the buoy performing as a master station but was not used):

- 1. One ground-based model MCC-530 (and MCC-510) MBCS master station. located at San Diego (NOSC). The antenna was a 5-element Yagi antenna oriented for vertical polarization and directed toward the buoy near San Francisco.
- 2. One ship-based MCC-530 (and 510) master station, located aboard USNS De Steiguer (T-AGOR-12) research ship. During the course of the test, the ship took two cruises to a mid-ocean point between Hawaii on For and CONUS, acting as a master station relay. The ship was also used to deploy and recover the buoy. Two 5-element vertically A&I polarized Yagi antennas were mounted on the ship, one on the bow ł and one near its stern. They were operated simultaneously through iced a power splitter as shown in Figure 5. cation
- 3. Two buoy-mounted model MCC-540A remote station MBCS equipments. (An MCC 512 remote station transceiver, which had been modified to operate as a master station with its transmitter having a 33% duty ition/ cycle, was also on the buoy.) The buoy was moored off the California coast 45 nmi SW of San Francisco. Avail and/or

- 4. One ground-based MCC-540A remote station, located on Mauna Loa (11, 100 feet) on the island of Hawaii. This site elevation extended meteor burst range (100 150 nmi). A 5-element Yagi antenna was directed toward San Francisco.
- 5. One ground-based MCC-540A remote station, located at Stinson Beach, 12 nmi N of San Francisco. This station was originally located on top Mt. Tamalpais near San Francisco, but was moved to Stinson Beach because of rf interference from the entire San Francisco bay area on Mt. Tamalpais. A 3-element Yagi antenna was used at this site.

Soccessi (Seconder) (Seconder) (Seconder)

PUPPER NOT PERMIT

3

Photographs of the buoy and the installations at San Diego, on USNS De Steiguer, and at Stinson Beach, are shown in Figure 6.

The primary testing included two cruises of USNS De Steiguer. These cruises are summarized below:

1.3.1 CRUISE NUMBER ONE

During the first cruise, illustrated in Figure 7, the ship left from Oakland Naval Shipyard on 25 June 1986, and traveled to 37°22'N, 123°09'W, 45 nmi SW of the Golden Gate Bridge, where it deployed the buoy. It then sailed to 30°32'N, 138°09'W, almost midway between the buoy and Hawaii. During this time, the ship was in constant communication with the buoy through line-ofsite (LOS) operation, meteor burst operation, and sporadic E operation, using the MCC 530/540A (master/remote) MBCS equipment; the San Diego master station was communicating with the buoy; and the ship was also listening for Hawaii, achieving the first communication at about 1300 nmi range.

While the ship was at mid-position, it sailed back and forth in a 100nmi pattern, keeping its bow and stern MBCS Yagi antennas pointed to the buoy and Hawaii. Messages were transferred between the ship and Hawaii, and between the ship and buoy. Because of problems with the automatic message generator at San Diego, there were no messages sent from San Diego to Hawaii. Several messages were sent from Hawaii to San Diego. The ship was at midposition for about three days, after which it sailed back to the buoy.

The plan was to remotely switch from the MCC 540A remote system to the MCC 512 remote system on the buoy to allow testing of the buoy battery power system while the buoy was operated as a master station. (The MCC 512 had been modified to function as either a remote station relay requiring as little as 1.5 watts of DC power or as a master station relay requiring as much as 600 watts of DC power.) Because of bad weather and heavy seas, the ship bypassed the buoy returning to Port Heuneme California on 8 July 1986.

1.3.2 CRUISE NUMBER TWO

On cruise number two, illustrated in Figure 8, the ship left Oakland Naval Shipyard on 8 August 1986 at 0300. The ship sailed to the buoy, which had been moored during cruise one. The plan was to recover the buoy and deploy it to a seamount 400 nmi closer to Hawaii, providing more optimum ranges for relay between San Diego, the buoy, the ship, and Hawaii.

Upon arrival at the buoy site, it was found that the buoy tether line had been cut by a passing ship and the MBCS buoy was gone. The crown (tether) buoy was still in place, but had a scrape mark on its side, indicating it had been hit by a green ship. Because of the loss of the buoy, the test plan was changed to allow relay of data from the station located at Stinson Beach near San Francisco to Hawaii via the ship.

During the cruise to mid-position, messages were transferred between the ship and Stinson Beach. Continuous ground wave connectivity (LOS) was measured out to 230 nmi. During the remainder of the cruise, communication was maintained using meteor burst and sporadic E operation. At about 1200 nmi from Hawaii, the first communications from Hawaii were received, apparently due to sporadic E.

The ship arrived at mid-position on August 12th, where it maintained a test pattern of back-and-forth operation over a 50-nmi path for about 3 days. During this period, numerous messages were transferred between Hawaii and Stinson Beach. Although the activity was sporadic, indicating a lot of sporadic E operation, there were periods of meteor activity, and the test did prove the relay concept. At mid-point, the transmission paths were at times in excess of 1000 nmi.

On 15 August 1986, the Yagi antennas on the bow of the USNS De Steiguer and at Stinson Beach were rotated to obtain performance data for horizontal polarization, the shipboard transmitter power delivered 800 watts to only the 5-element Yagi mounted on the bow of the ship, and the ship started its cruise back to Oakland, arriving 18 August. During the return cruise, good meteor activity was recorded between the ship and Stinson Beach.

The equipment buoy was later seen by a naval ship, but efforts to relocate and recover it failed; however MBCS communications between the buoy and San Diego were re-established, even though the location of the buoy was uncertain. This communication continued until 5 February 1987 as the buoy drifted from north of San Diego to about 1000 nmi south. Its fate is not known.

1.4 TEST RESULTS

All test data resulted from operating the MCC 530/540A (master/remote) equipment. The bulk of the MCC 530/540A data consisted of the number of good (verified) receptions of a 72 ms long test message from a remote station (buoy, Stinson Beach, or Hawaii) recorded by the ship's 530 as it sailed to and from the remote stations located in the buoy, at Stinson Beach, or at Hawaii. This provided valuable data on performance versus range over the ocean.

Figures 9 and 10 give the good receptions from the buoy as a function of range. The cyclic variation of good receptions is due to the diurnal variations in meteor rates. The peaks correspond to 0600 local time. Note the ground wave performance extended out to 130 nmi during cruise number one.

During cruise number two, the same data was obtained during communications with the shore-based station at Stinson Beach. This data is plotted in Figures 11 and 12. The ground wave extended to at least 230 nmi. This difference in ground wave range data correlates to the type of antennas used, dipole J-antenna on the buoy and a higher gain 3-element Yagi at Stinson Beach

At the same time, the shore-based MCC 530 at San Diego recorded the same data as it communicated with the buoy, giving information on performance versus time of day. Figure 13 gives the number of "good receptions" received from the buoy at San Diego. Note the diurnal variations in the data. The data was taken during cruise number one. During the second ship cruise, Stinson Beach and Hawaii were entering messages for relay through the ship to each other. A list of the total number of characters relayed through and received at each remote station from the other remote station is summarized in Table 1. Note from this data that a large number of messages were transferred from Stinson Beach to Hawaii; however, a lot of these messages occurred in groups, indicating that sporadic E was the most common propagation medium. Because of the long range (near 1100 nmi), meteor activity was extremely slow, and waiting times were at times measured in hours instead of minutes. These results point to the need for additional relays in the San Francisco/Hawaii link.

1.5 ANALYSIS

A list of the average Rx good counts vs. range is given in Table 2. This data was taken from Figures 9, 10, 11, and 12. These values are from an imaginary curve that averages the diurnal variation which is evident but ignores the extreme values that are assumed to result from sporadic-E. Also listed in Table 2 is the system power factor (PF), which is a function of antenna gains (G_T and G_R), transmitter power (P_T), and receiver threshold (P_R). The differences between the four sets of data are due to the different PF used, i.e.:

Cruise 1 Out - VERTICAL POLARIZATION

Tx Power 250 watts, Omni Rx Ant PF = 176 dB

Cruise 1 In - VERTICAL POLARIZATION

Tx Power 500 watts, Omni Rx Ant PF = 179 dB

Cruise 2 Out - VERTICAL POLARIZATION

Tx Power 250 watts, 3EL Yagi Rx Antenna PF - 179 dB

NG XXXXXI XX

Cruise 2 In - HORIZONTAL POLARIZATION

Tx Power 800 watts, 3EL Yagi Rx Antenna PF = 187 dB

The differences in count roughly follows the standard equation relating meteor count to system power factor or sensitivity, i.e.,

$$\frac{N_1}{N_2} - 10 \exp\left\{\frac{PF_1 - PF_2}{20}\right\}$$

where:

 N_1 - Meteor Rate for System 1

N₂ - Meteor Rate for System 2

 PF_1 - Power Factor for System 1

 PF_2 = Power Factor for System 2

As an example, the daily average Rx good count difference between the first and the fourth plot at 500 miles is about 4:1. This corresponds to a 12-dB difference in system sensitivity. The actual power difference was 11 dB.

Note from the data that the performance drops off with range beyond 700 to 750 nmi. This is especially true for the second half of the second cruise, which used horizontal polarization. This suggests that vertical polarization will perform best at these ranges, probably because the antenna cutback is less for the antenna heights used.

1.6 CONCLUSIONS

The San Francisco/Hawaii link provided marginal performance using one relay (the ship). Unfortunately, the loss of the buoy during the second cruise prevented placing the buoy 400 nmi closer to Hawaii. This would have allowed the test of a two-relay link, which would have undoubtedly improved performance. With this arrangement, message waiting times could be reduced to minutes.

Large, heavy fuel supplies or batteries of limited life are required to provide power for a buoy relay system operating as a master station. However, an MBCS emergency relay network operational concept that partially mitigates this limitation includes implementing combination master/remote station functions in the MBCS equipment operated at each buoy-supported transceiver relay node in the network. This is illustrated by the MBCS network diagrammed in Figure 14. Each of the nodes can function as either an MBCS master station, probing to establish connectivity with a remote station, or as the remote station. ŠUM 202023 "SUMMA" DUDDA" EDMOG VODUM MANNE KANNE KANA DUDDAU DUDAU DUDAU DUDAU DUDAU DUDAU DUDAU

Initially, all stations function continuously as remote stations, prepared to respond with a transmission acknowledging reception of a probing signal. When a message is injected into the network, the node responds by functioning as a master station, probing for a programmed number of minutes or until the message receipt is acknowledged by one or more of the remote stations addressed. The functioning master station may or may not continue to probe until all of the remote stations within range of its transmitted probing signal acknowledge reception of the message. Each station (node) to which the message is passed begins functioning as a master station, probing until the message is passed to yet another combination remote/master station functioning as a remote station closer to the intended final destination of the addressed message. Each station (node) returns to functioning as a remote station when it has no message to relay.

REFERENCES

- 1. NOSC TR 1171, <u>Buoy Relay for a Meteor Burst Communication System Test</u> <u>Report</u>, by J.E. Bickel, T.L. Wright, G.L. Davis, E.A. Thowless, J.F. Theisen of NOSC, and T. Donich of MCC, April 1986.
- NOSC TR 1150, <u>Preliminary Design Options for Meteor Burst Communications</u> <u>Systems Buoy Relays</u>, J.E. Bickel, T.L. Wright, E.A. Thowless, G.L. Davis, G. Pickins (CSC), December 1986.

. Table 1.

 Number of characters relayed through USNS De Steiguer and received at Stinson Beach from Hawaii and at Hawaii from Stinson Beach.

DAY <u>NUMBER</u>	STINSON BEACH RX CHAR	HAWAII RANG	E FROM STINSON BEACH
222	Off	4,544	343-603
223	Off	23,160	614-876
224	2,632 (7 hrs)	88,088	876-977
225	680	6,088	999-950
226	78,088	79,264	998-950
227	19,648	1,120 (8 hrs)	990-800
228	95,920	Off	800-550
229	94,054	Off	550-360

Table 2. List of the daily average (noon) Rx good receptions for 300, 600, 800 nmi ranges (values from Figures 9, 10, 11, and 12).

	I	RANGE, nr	ni			
CRUISE	<u>300</u>	<u>600</u>	<u>800</u>	POL.	<u>PF**</u>	
1 Out	10	10	4	Vert.	176 dB	
l In	15	15	5	Vert.	179 dB	
2 Out	15	15	5	Vert.	179 dB	
2 In	40	40	10	Horz.	187 dB	

**NOTE: PF (db) = $P_T + G_T + G_R - P_R$



and the second second



Figure 3. MBCS equipment deployment for relay tests.



• Figure 4. Expected voltage of the secondary lead-acid battery during a typical test cycle.



.

こうちょうにん () たちなななない) していたい ()

L'ANGE CANADA

PEREFECT

J.

P.2.12025-514

CONTRACTOR PROFILE RECORDED

Figure 5. USNS De Steiguer MBCS Yagi antenna installation.



Photographs of the test installations. Figure 6.

Stinson Beach



USNS De Steiguer







Buoy





Figure 9. Number of good receptions per hour recorded aboard USNS De Steiguer from the buoy during the first half of the first cruise.



Figure 10. Number of good receptions per hour recorded aboard USNS De Steiguer from the buoy during the second half of the first cruise.



Figure 11. Number of good receptions per hour recorded aboard USNS De Steiguer from Stinson Beach during the first half of the second cruise.



Figure 12. Number of good receptions per hour recorded aboard USNS De Steiguer from Stinson Beach during the second half of the second cruise. Horizontally polarized antennas were used.



Figure 13. Typical diurnal variation of the number of good receptions received from the buoy at San Diego during cruise 1.



AND BUCKER AND A DESCRIPTION NAME AND A DESCRIPTION OF A

Part of the

Figure 14. A proposed MBCS strategic connectivity network.