ND-81	91 999	PER	FORMA	STRAT	A HYD	ROGEN EFENS.	PULSE	D ELEC	TROTH	ERHAL INC		1/	1
UNCLAS	SIFIE	AFO	SR-TR-	88-81	96 F49	628-87	-0-00	28	er er	F/8 :	21/3	NL	
					1								
				P.		:	1 4 67 4 7						



1. P. 1. P. 1. P. 1. R. 1. P. 1. 1. 1. 1.

いま ひょうりませ

	MCI INACHITAT		DAGE		
			ARKINGS		
Unclassified DIC					
TE	3. DISTRI	UTION /	AVAILABILITY O	F REPORT	
AD-A191 999 1988		pprov 1st	ed far publi	le release,	
A PERFORMING ORGANIZATION REPORT NUMBER(S)	5. MONITO	DRING C	RGANIZATION	EPORT NUMB	ER(S)
		AF	OSR TR	· 88-	0 ' 9 6
GT-Devices, Inc.	MBOL 7a. NAME (de) USAF, Resear	OF MO AFSC, ch	NITORING ORGA	Office of	f Scientific
C ADDRESS (City, State, and ZIP Code)	75. ADDR	ESS (City	, State, and ZIP	Code)	
Alexandria, VA 22312-2408	Buildi Bollir	ng 41 Ig AFE	.0 3, DC 203	32-6448	
3a. NAME OF FUNDING/SPONSORING 8b. OFFICE SY	MBOL 9. PROCU	EMENT	INSTRUMENT IC	ENTIFICATION	NUMBER
AFOSR	Ā. F4962	0-87-	·C-0028		
BC. ADDRESS (City, State, and ZIP Code)	10. SOURC	E OF FI	UNDING NUMBER	RS	
Scarca Th	- ELEMENT	NO.	PROJECT NO.	TASK NO.	WORK UNIT
	(.110)	RF	ふみつれ	AL	
11. TITLE (Include Security Classification)		<u> </u>	<u></u>		
Performance of a Hydrogen Pulsed Electr	othermal Thru	ster	(SDI)		
2. PERSONAL AUTHOR(S) Rodney L. Burton. Shvke A. Golds	tein and Shih	-Yina	Wang		<u> </u>
13a. TYPE OF REPORT 13b. TIME COVERED	14. DATE O	F REPOR	IT (Year, Month,	Day) 15. PA	GE COUNT
FINAL REPORT FROM 87/01/12087/	U//12 Septe	mber	28, 1987		4/ ·
	· •				
	TEDNAS /Constant		if	d idensif t	
17. COSATI CODES 18. SUBJECT	TERMS (Continue on	reverse pulse	if necessary an	d identify by l	Nock number)
17. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 1 Iniquid h	TERMS (Continue on propulsion, lydrogen prope	reverse pulse llant	if necessary and ed electrot	d identify by l hermal pro	block number) opulsion,
17. COSATI CODES FIELD GROUP SUB-GROUP Electric liquid h	TERMS (Continue on propulsion, ydrogen prope	reverse pulse llant	if necessary and ed electrot	d identify by l hermal pro	work number) opulsion,
17. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 19. ABSTRACT (Continue on reverse if necessary and identify by	TERMS (Continue on propulsion, ydrogen prope block number)	reverse pulse llant	if necessary and ed electrot	d identify by b hermal pro	block number) opulsion,
17. COSATI CODES FIELD GROUP SUB-GROUP 18. SUBJECT Electric liquid h 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to co	reverse pulse llant etern	if necessary and ed electrot	d identify by b hermal pro chnical fe	whock number) opulsion,
I7. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 19. ABSURACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase Of measuring the performance of a pulsed e of measuring the performance of a 5 kW thruste	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal er is presente	reverse pulse llant etern thru	if necessary and ed electrot	didentify by b hermal pro chnical fe quid hydro e capacit:	plock number) opulsion, easibility ogen ive pulse
17. COSATI CODES FIELD GROUP SUB-GROUP 18. SUBJECT Electric liquid h 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c lectrothermal r is presente stics, nozzle	reverse pulse llant eterm thru d, ir	if necessary and ed electrot	d identify by b hermal pro chnical fe quid hydro e capacit d predicte	easibility ogen ive pulse ed specific
17. COSATI CODES FIELD GROUP SUB-GROUP 18. SUBJECT Electric liquid h 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal er is presente stics, nozzle liscussed whic nozzle	etern thru d, ir	if necessary and ed electrot	d identify by b hermal pro chnical fe quid hydro e capacit d predicte lves the p	easibility open ive pulse ed specific problem of
I7. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 19. ABSURACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase Inis report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded It is concluded	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal r is presente stics, nozzle liscussed whic nozzle. Afte that a Phase	reverse pulse llant thru d, ir perf h tre r an II te	if necessary and ed electrot is the tent is ter on line cluding the formance and eats and so investigat	d identify by b hermal pro chnical fe quid hydro e capacit d predicte lves the p ion of teo concentrat	easibility open ive pulse ed specific problem of chniques for te on
I7.COSATI CODES18. SUBJECTFIELDGROUPSUB-GROUPElectric19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phaseof measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal r is presente stics, nozzle iscussed whic nozzle. After that a Phase gen testing sh	eterm thru d, ir perf h tre II te ould	if necessary and ed electrot	d identify by b hermal pro chnical fe quid hydro e capacit d predicte lves the p ion of teo concentrat ed to Phas	block number) opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES FIELD GROUP SUB-GROUP 18. SUBJECT Electric liquid h 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal stics, nozzle iscussed whic nozzle. After that a Phase gen testing sh	reverse pulse llant thru d, ir perf h tre r an II te ould	if necessary and ed electrot ster on line cluding the formance and ats and so investigat be postpon	d identify by b hermal pro quid hydro e capacit d predicte lves the p ion of teo concentrat ed to Phas	wock number) opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES FIELD GROUP SUB-GROUP I a subject FIELD GROUP SUB-GROUP I a subject of a continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog Meywords:	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal r is presente stics, nozzle iscussed whic nozzle. Afte that a Phase yen testing sh	reverse pulse llant thru d, ir perf h tre r an II te ould	if necessary and ed electrot	d identify by b hermal pro chnical fe quid hydro e capacit d predicte lves the p ion of teo concentrat ed to Phas	block number) opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES FIELD GROUP SUB-GROUP 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog *equoreds:	TERMS (Continue on propulsion, dydrogen proper- block number) Teffort to c electrothermal stics, nozzle discussed whice nozzle. After that a Phase gen testing sh	reverse pulse llant thru d, ir perf h tre r an II te ould	if necessary and ed electrot	d identify by b hermal pro quid hydro e capacit d predicte lves the p ion of teo concentrat ed to Phas	wock number) opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES FIELD GROUP SUB-GROUP 18. SUBJECT Electric liquid h 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog Mequords:	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal stics, nozzle iscussed whic nozzle. Afte that a Phase yen testing sh	reverse pulse llant thru d, ir perf h tre r an II te ould	if necessary and ed electrot	d identify by b hermal pro chnical fo quid hydro e capacit d predicto lves the p ion of teo concentrat ed to Phas	block number) opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog *equords: 20. DISTRIBUTION/AVAILABILITY OF ABSTRACT DUNCLASSIFIED/UNLIMITED	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal stics, nozzle iscussed whic nozzle. Afte that a Phase yen testing sh	reverse pulse llant thru d, ir perf h tre r an II te ould	if necessary and ed electrot intendent of the ster on line cluding the commance and so investigat est and so investigat be postpon	chnical fe quid hydro e capacit d predicte lves the p ion of teo concentrat ed to Phas	Wock number) opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog "equords" 20. DISTRIBUTION / AVAILABILITY OF ABSTRACT DUNCLASSIFIED/UNLIMITED ENSAME AS RPT 222. NAME OF RESPONSIBLE INDIVIDUAL Rodney L. Burton Drictan	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal er is presente stics, nozzle fiscussed whic nozzle. Afte that a Phase yen testing sh 21 ABSTR UT 226 TECEP (703)	reverse pulse ilant thru d, ir perf h tre r an II te could	if necessary and ed electrot	chnical fe quid hydro e capacit d predicto lves the p ion of teo concentrated to Phase CATION	easibility opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog ************************************	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal er is presente stics, nozzle iscussed whic nozzle. Afte that a Phase yen testing sh 21. ABSTR UT 22b. TELEP (703) e used until exhauste	reverse pulse llant thru d, ir perf h tre r an II te ould	if necessary and ed electrot	chnical fe quid hydro e capacit d predicte lves the p ion of teo concentrat ed to Phase CATION	easibility opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.
17. COSATI CODES 18. SUBJECT FIELD GROUP SUB-GROUP Electric 19. ABSTRACT (Continue on reverse if necessary and identify by Inis report describes an SBIR Phase 19. ABSTRACT (Continue on reverse if necessary and identify by This report describes an SBIR Phase of measuring the performance of a pulsed e propellant. The design/of a 5 kW thruste forming network, arc discharge characteri impulse and thrust. A/thermal model is d liquid hydrogen boiling in the injection handling liquid hydrogen it is concluded water and/or hydrazine, and liquid hydrog *equords: 20. DISTRIBUTION / AVAILABILITY OF ABSTRACT DUNCLASSIFIED/UNLIMITED ENSAME AS RPT 222. NAME OF RESPONSIBLE INDIVIDUAL Rodney L. Burton DT FORM 1473, 84 MAR B3 APR edition may be All other edition All other edition	TERMS (Continue on propulsion, ydrogen prope block number) Teffort to c electrothermal er is presente stics, nozzle fiscussed whic nozzle. Afte that a Phase yen testing sh 21 ABSTR UT 22b. TELEP (703) e used until exhauste ons are obsolete.	reverse pulse llant thru d, ir perf h tre r an II te ould	if necessary and ed electrot is the tensor on line is ter on line cluding the formance and eats and so investigat est should be postpon	chnical fe quid hydro e capacit d predicte lves the p ion of teo concentrat ed to Phase CATION e) 22c. OFFICE CLASSIFICATION assified	easibility opulsion, easibility ogen ive pulse ed specific problem of chniques for te on se III.

(

0

PERFORMANCE OF A HYDROGEN

PULSED ELECTROTHERMAL THRUSTER

Strategic Defense Initiative Organization Innovative Science and Technology SBIR Phase I

Final Report

AFOSR-TR- 88-0196

GT - Devices

88 2 29 149

5705A General Washington Drive

Alexandria, VA 22312

(703) 642-8150

PERFORMANCE OF A HYDROGEN

PULSED ELECTROTHERMAL THRUSTER

Strategic Defense Initiative Organization Innovative Science and Technology SBIR Phase I

Final Report

AFOSR Contract No: F49620-87-C-0028DEF

01/30/87 - 07/30/87

Performed by:

Ø

Ô

5

10

GT-Devices, Inc. 5705A General Washington Drive Alexandria, VA 22312-2408

Principal Investigator:

Rodney L. Burton

Report Date:

September 28, 1987

Submitted to:

Air Force Office of Scientific Research AFOSR/NA Bolling Air Force Base, DC 20332

Contract Technical Monitor:

Dr. Mitat Birkan

i

Accesson For	
NTIS GRA&I U DTIC TAB III Unimponed II Julian at a	•
By Distribute (
Alex table ty included	
Dist Aural deor A-1	P4

Keess she with the second second

TABLE OF CONTENTS

Ρ	a	g	e
•	-	Э.	-

1.4572.234

2222244

Title Page	i
DD Form 1473	ii
Table of Contents	iii
I. Introduction	1
II. Design of a Liquid Hydrogen PET Thruster	9
III. Feasibility of LH2 Laboratory Testing	21
IV. Conclusions for a Phase II SBIR Program	29

A. Appendices

¢

8

1

0

Ø

•

Ò

A.

Ð

1.	Statement of Phase II Proposal Submittal	31
2.	Rocket Research Company Commitment Letter	33
3.	Woodland Cryogenics, Inc. Study	35
4.	AEDC Aerospace Chamber (10V)	40

I. INTRODUCTION

This report provides an overview of a Phase I SBIR effort to determine the feasibility of performing liquid hydrogen performance tests on the pulsed electrothermal (PET) thruster in a laboratory environment. As part of this effort, the thruster was designed and its performance predicted.

۲

S.

Ð

It has been well established that electric propulsion has an important role to play for SDIO in space. The high specific impulse capability of electric thrusters has been demonstrated by electrothermal, electromagnetic and electrostatic devices possessing I_{sp} 's in the 500 to 5000 second range. In this section we derive the appropriate range for SDIO missions, and demonstrate that the pulsed electrothermal (PET) thruster proposed here has significant advantages for these missions.

What types of missions are best suited to electric thrusters, where they can perform a task which simply cannot be economically accomplished by chemical rockets? There are two types. The first type is a mission with a tight mass budget, e.g. a space-based radar which must be launched from the space shuttle and transferred to a higher parking orbit. Depending on the required orbit transfer, it may not be possible to accomplish the mission chemically and stay within the shuttle payload limit. In this case a high I_{sp} electric system can be used to achieve orbit transfer and minimize propellant consumption [1]. Because the thrust time increases as I_{sp}^2 , the mass savings are ultimately dictated by the maximum allowable thrust time. For example, a 5000 sec electrostatic thruster may maximize on-orbit mass, but might require 400 days to complete the transfer. Therefore a 1000 second system might be preferable to reduce thrust time.

AMAMA SAMAMA PARANA PARANA PARANA PARANA PARANA PARANA PARANA PARANA PARANA PARANA

The second type of missions well suited to electric propulsion are those with high characteristic velocity V, conducted by reusable spacecraft. Examples of this type of mission are:

- 1. Transfer a satellite to GEO and return, or return a second satellite for maintenance, using an OTV.
- 2. Maneuver a battle station in a constantly changing orbit to avoid "space mines" and ASAT systems.

^[1] Burton, R.L., Goldstein, S.A., Hilko, B.K., Tidman, D.A., and Winsor, N.K., "Proposed System Design for a 20 kW Pulsed Electrothermal Thruster," AIAA Paper 84-1387, AIAA/SAE/ASME 20th Joint Propulsion Conference, Cincinnati, OH, June 11-13, 1984.

3. Transfer new battle stations or surveillance satellites into a constellation to build up the constellation or to replace spacecraft unexpectedly lost by malfunctions.

These missions are characterized by a requirement to move the maximum mass in the shortest possible time, in a reusable mode. An approach to finding the optimum I_{sp} for these missions is to define a payload rate [2]

Payload rate = PR =
$$\frac{m_{pay}/m_o}{t_+}$$

where t_t is the thrust time. By maximizing PR, maximum use is gotten out of the spacecraft.

The payload rate PR is given approximately by the nondimensional expression:

TANKAN "ZASANA" NASAAT RAMANI PANANA "PANANA" PANANA "PANANA" PANANA

$$\alpha(\Delta V)^{2} PR = 2ne^{-\frac{2\Delta V}{g I}} \left(1 - \frac{\Delta V}{g I}\right) \left(\frac{\Delta V}{g I}\right)^{2}$$

where $\alpha[kg/w]$ is the power supply specific mass and η is the electric propulsion system efficiency. This expression has a maximum value for $\Delta V/gI_{sp}$ between 0 and 1. The optimum I_{sp} to maximize PR is given by the condition:

$$e^{-\Delta V/g I} sp \left(1 - \frac{\Delta V}{g I_{sp}}\right) = m_p/m_o$$

where $m_{\rm p}/m_{\rm o}$ is the power supply mass fraction. This equation is plotted in Fig. 1.

Figure 1 shows the following:

Ø

10

зŋ,

1. An I_{SP} of 500-3000 seconds is required for a wide range of missions from ΔV = 4-12 km/sec and power supply fractions m_D/m_O of 0 to 50%.

2. Payload mass fraction is a unique function of power supply mass fraction m_p/m_o . Payload fraction is approximately 35% for mp/mo up to 30%, even at a high mission ΔV of 12 km/sec and above.

[2]Free, B., "Use of SP-100 Nuclear Power Supply for Electric Propulsion," Scionics, Inc., Tech, Rpt. STR No. 686, June 6, 1986.



3. At mission ΔV 's below 4 km/sec, the payload mass fraction for a 400 sec chemical system is higher than electric, so chemical is preferred over electric to the left of the dashed curve.

4. An I_{sp} of above 3000 seconds is only useful for very high ΔV 's, well above 12 km/sec.

We now discuss the availability of electric thrusters in the 500-3000 second range, which is the desirable range for high payload rate as shown in Fig. 1. Electric thrusters have been under development since the early 1960's, and the performance status is shown in Fig. 2, which shows system efficiency versus I_{sp} for various thruster types. Beginning with the ion thrusters, the efficiency is above 80% at 5000 seconds, but falls off rapidly below 3000 seconds. This is a reflection of the constant energy cost that must be paid for each ion, which becomes a large (and unrecoverable) fraction of the energy below 3000 seconds.

Electrothermal thrusters (e.g. arcjet, Fig. 2) also produce ions, but unlike electrostatic ion thrusters can in principle recover their ion production costs in a nozzle, provided that nozzle recombination rates are sufficiently high to approach equilibrium. The recombination rates for the arcjet are not sufficiently high, as is reflected in the arcjet curve (Fig. 2), which shows a sharp dropoff in efficiency as the $I_{\rm SP}$ approaches 1000 seconds. This drop is directly related to the low recombination rate at the arcjet operating pressure of 1-2 atmospheres.

In order to recover the ionization energy and some of the dissociation energy in an electrothermal thruster, the recombination rate is raised by raising the plasma pressure; an effective remedy because the recombination rate varies as the square of the density [3]. Suppose that the pressure is raised by a factor of approximately 10^3 , and the plasma energy is therefore raised by the same amount. To avoid raising the power level, which would seriously ablate the discharge chamber surfaces, the thruster is operated in a pulsed mode with a duty cycle of approximately 10^{-3} , which keeps the power throughput constant. This has the effect of bringing a kilowatt-level thruster into the megawatt range of peak power. The effect on efficiency is shown for H₂O and H₂ in Fig. 2, which indicates that efficiencies in the 80% range can be achieved with the H₂ at 2500 seconds, and 60% can be achieved with H₂O at 1500 seconds.

[3] Book, D.L., "Plasma Physics," Chap. 18 in <u>Physics Vade</u> <u>Mecum</u>," H.L. Anderson, ed., Am. Inst. of Phys., New York, 1981, p. 271.

ΥË,



Pulsed Electrothermal (PET) Thruster Description

0

01

۰ð

140

GT-Devices has been developing [4-7] the propulsion concept called pulsed electrothermal or PET. The system is shown in Fig. 3 in its simplest form. A power supply continuously charges an electric energy store, while liquid propellant is fed into a thrust chamber. The energy store then repetitively discharges electrical energy into the thrust chamber to create thrust impulses.

GTD PULSED ELECTROTHERMAL PROPULSION



Figure 3

propellant

At first glance this system seems needlessly complicated, since the energy could be fed continuously to the thrust chamber to produce continuous thrust. This is in fact done in the

[4]Burton, R.L., Goldstein, S.A., Hilko, B.K., Tidman, D.A., and Winsor, N.K., "Investigation of a Pulsed Electrothermal Thruster," Final Report No. NASA CR-168266, NASA-Lewis Research Center, October 1, 1983.

[5]Burton, R.L., Goldstein, S.A., Hilko, B.K., Tidman, D.A., and Winsor, N.K., "Investigation of a Pulsed Electrothermal Thruster System," Final Report on NASA CR-174768, NASA-Lewis Research Center, October 31, 1984.

[6]Burton, R.L., Fleischer, D., Goldstein, S.A., Tidman, D.A., and Winsor, N.K., "Investigation of a Repetitive Pulsed Electrothermal Thruster, Final Report No. NASA CR-179464, NASA-Lewis Research Center, August 21, 1986.

[7]Burton, R.L., P.I., "Performance of a Hydrogen Pulsed Electrothermal Thruster," SBIR Phase I, AFOSR Contract No. F49620-87-C-0028, 1/30/87 - 7/30/87.

ILETTER "EXAMPLE AND "EXAMPLE TEXTER 222252

hydrogen arcjet, but the efficiency decreases rapidly because of frozen flow losses above $I_{sp} = 1000$ seconds as shown in Fig. 2. The pulsed system not only increases the efficiency, but permits operation out to 3000 seconds (Fig. 2). This startling improvement in performance is serendipitously caused by a fundamental change in the physics of the nozzle expansion process, coupled with lower temperature operation, both of which substantially reduce the energy lost to ionization and dissociation in the exhaust. Our experimental measurements [6] have verified this performance improvement for water, and we predict an even greater improvement for hydrogen as shown in Fig. 2.

•

0

Q,

Δ.

Ą,

Q,

A PET propulsion system is shown schematically in Fig. 4. A full-wave rectifier charges a capacitive PFN which is directly connected to the electrodes. Simultaneously, a small quantity of propellant is injected into the chamber in liquid form. When the voltage is sufficiently high, breakdown occurs through the propellant vapor, and energy is efficiently transferred to the propellant, which has 99% of the circuit resistance. The propellant is heated to about 500 atm and 14,000°K, and expands through the nozzle, exhausting at a low temperature. The ionization energy is low, so that the efficiency of the thruster is therefore quite high.



Figure 4

A pulsed system can be operated at an arbitrarily high power level, and hence pressure level, as long as the pulse length is sufficiently short that the electrodes and insulators do not

erode. It is straightforward to scale PET propulsion over a wide thrust range by varying the energy per pulse and the pulse rate.

The pulsed electrothermal thruster curves in Fig. 2 show two data points, which are estimated performance levels from preliminary tests on H₂O, conducted with considerable excess propellant flow at a (high) background pressure of 10-20 torr. It is the main purpose of the proposed effort to provide proper pulsed electrothermal thrust performance data, by conducting thrust stand tests on two or more propellants with a high propellant utilization efficiency.

DEPENDENCE ERECTED

It is important that realistic operating conditions exist during the performance tests. Simultaneously, it is required that:

1. The background pressure is sufficiently low to provide accurate exhaust velocity measurements and an ambient pressure considerably less than nozzle exit pressure.

2. Plasma conditions are such that the thruster does not erode or ablate.

3. The propellant is suitable for the 500-3000 second range, and the utilization efficiency is 50% or greater.

4. The performance measurements are accomplished with an accuracy of 2% or better.

Achievement of the above conditions and experimental results will establish that the PET thruster is capable of the performance required for high $I_{\rm SP}$, minimum trip time missions for SDIO.

Phase I Effort

5

14

0

6

3

â

GT-Devices has recently completed the Phase I SBIR effort on performance of a liquid hydrogen PET thruster[7]. The two primary objectives were the design of a liquid hydrogen thruster and a determination of the feasibility of operating with LH₂ in the laboratory. A description of these two tasks and the conclusions reached form the body of this report.

II. DESIGN OF A LIQUID HYDROGEN PET THRUSTER

The design of the liquid hydrogen pulsed electrothermal thruster consists of three major elements:

1

6

0

0

3

Ø

ų,

Ŵ

1

- A. Calculation of discharge parameters and pulse forming network.
- B. Calculation of exhaust conditions, including frozen flow.
- C. Thermal modeling of thruster, including boiling of liquid hydrogen prior to injection.

The thruster design is shown in Figure 5. Some of the hardware, such as a mount system and radiation shielding, is not included in this design.

Discharge Parameters, Pulse Forming Network, and Ideal Performance

Calculation of discharge parameters and pulse forming network follows a zero-D model used successfully at GT-Devices [4-6]. For this model, the discharge power is equated to the enthalpy flux of evaporated propellant, where the temperature is calculated self-consistently using a form of the Spitzer equation [8], modified for electron-neutral collisions [9]. The arc plasma is the load for a matched PFN, and the calculation is assumed to be quasi-steady.

The entire calculation is conveniently performed on LOTUS, and the present design is shown below:

[8]L. Spitzer, Jr., "Physics of Fully Ionized Gases," 2nd Ed., Interscience Publishers, 1962, pp 136-143.

[9]D. A. Tidman, et.al., "A Rail Gun Plasma Armature Model," Tech. Note GTD86-3, March 1986.



ALLELES SALESSE NOVERAL SALESSE VALUE SALESSE DAVAGE DAVASAL DAVASAL DAVASAL

2222223

7.200.00



2

4

. ا

'G

10

Revision date Electrothermal Model for PET LH2PET Sep 22.1987 This model calculates conditions in a bore being driven by electrothermal plasma sources, or "lightbulbs," and coupled to a æ supersonic nozzle. I. Calculation of the conditions in the lightbulbs. Lightbulb plasma parameters are calculated from the formulary. Equations in the formulary are presented as a function of current. In the model below the current is solved self-consistently from: ٤. Vo = I(Zpfn + Rext + R(I))where R(I) is derived from the formulary by eliminating Tev. One then gets an approximate quadratic equation of the form: Y*Y + B*Y - Vo/(Zpfn + Rext) = 0where $Y = I^{2}.5$ and B is a constant. The value of B is given by: B =((.0194)*.94*1*Sp²(8/11)*S²(3/11))/(Zpfn+Rext)/d²(13/11)/G where Sp is the Spitzer term Zlnlambda(1+2nueo/nuei), S is the area enhancement factor, d is the capillary diameter and G is the 18 volume factor. The variable 1 is the capillary length and for two lightbulbs in series is the sum of the two lengths. The .94 factor is 4(kA) raised to the -(1/22) power. ENTER? 3.50 Capillary length, cm. Ε Capillary diameter, cm, at 1 kilobar 0.45 Ε Number of capillaries. 1 or 2. 1.00 Ε Spitzer factor, Zlnlambda(1+2nueo/nuei) 8.00 Ε Area enhancement factor, S 2.00 Ε Volume factor. G 1.00 Ε Impedance of pulse forming network, Zpfn, milliohms Resistance of external circuit, Rext, milliohms Ε 900 3 F Ε Capacitance of pfn, microfarads 8.00 Pulse length, microseconds, 2CZpfn 14.40 Breakdown field, volts/cm 700 Ε Charging voltage, Vo. kV 2.45 PFN energy stored, J 24.01 System average power, kW Ε 5.00 Pulse rate, pps 208 Constant B 1.00 X Current in capillary, kA 1.50 Capillary resistance, milliohms, total 735 PFN transfer efficiency, $4RZ/(R+Z)^2$ 0.99 Second half cycle voltage, kV 0.25

PERSONAL WAY

RECEIPTING INSTAND

Capillary power, megawatts, total Capillary temperature, eV and deg K, Tl	1.64 1.14	13276
In order to calculate pressure, information must be for the speed of sound and gamma, available from gra	pe entered aphs or table	s.
Material in capillary. Molecular weight, STP	hydrogen 2.0	E E
Speed of sound at capillary temperature, km/sec Specific heat ratio, gamma Throat area contraction ratio Mach number (assumed sonic) Pressure, average, atm	11.90 1.28 0.45 0.89 100	E E E
Pressure, stagnation, atm Pressure, sonic, atm	128 71	
Characteristic venting time, microseconds Pulse length, microseconds	5.54 14.40	
Enthalpy, kJ/gm, from tables Ideal thrust impulse bit, mN-sec	615.00 1.35	E
Ideal exhaust velocity, km/sec Ideal specific impulse, sec	35.07 3579	
Ideal thrust efficiency, eta Ideal thrust to power ratio T/P, N/kW	1.00 0.057	

х

5.255554 (1

THE WAY AND A

Calculate the insulator wall heating, assuming blackbody radiation at the capillary temperature during the pulse, using the relation $dT = alpha*Tev^2 4*tp^2.5$

where alpha is a property of the insulator material. Typical values of alpha at high temps are 1.0 for SiC, 1.2 for BN and 1.4 for Si3N4. Melt temperatures in deg. C are 2500 for SiC, 3000 for BN and 1900 for Si3N4.

Also calculate the temperature rise due to convection for phi = 1.5. The MTF data give dT/alpha values of 3530 for SiC, 2530 for BN and 3003 for Si3N4. Handbook values are 2500, 2500 and 1360.

Insulator alpha Insulator temperature rise, delta T, deg K.	1.40 911	E
Delta T convective at the throat, deg K. Total delta T, radiative plus convective, deg K	311 1222	
Total dT/alpha	873	

The above calculation shows a capillary length of 3.50 cm and a capillary diameter of .45 cm. The PFN impedance is 900 milliohms, and the capillary resistance is 735 milliohms, which is essentially a perfect match. This high impedance guarantees that less than 1% of the stored energy is lost in the 3 milliohm external resistance.

The pulse rate is pushed as high as possible to 208 pulses per second at 5 kW. The stored energy is then 24.0 J/pulse, the breakdown voltage is 2.45 kV, and the PFN capacitance is 8.00 microfarads. The pulse length is then 14.4 microseconds, which is longer than the characteristic venting time of 5.54microseconds.

Instantaneous power is 1.64 MW at 1.14 eV (13,300 deg. K), and the hydrogen sound speed is, from the Sesame Tables [10], 11.9km/sec at a specific heat ratio of 1.28. The average pressure is calculated from the propellant mass evaporation rate and choked conditions at the entrance to the supersonic nozzle to be 100atm. This pressure is significantly above that of a DC arcjet, but is also significantly below the pressure capability of a capillary discharge from a mechanical standpoint.

The enthalpy from the charts (Fig. 6) [11] is 615 kJ/gm, which if fully expanded gives an ideal specific impulse of 3580 seconds, and an ideal thrust to power ratio of .057 N/kW. At 5 kW, the ideal thrust would then be 0.28 N.

The above LOTUS calculation also shows a calculation for insulator temperature rise, for an "alpha" factor of 1.4 for silicon nitride ceramic. The total calculated temperature rise is 1200 deg K, which requires an initial wall temperature of 700 deg K or less to stay below the Si3N4 melt temperature. This calculation is conservative, because the peak insulator temperature rise of 911 deg K does not occur simultaneously with the convective delta T of 311 deg K. The assumed pulse conditions therefore appear to provide a small margin against insulator ablation.

Frozen Flow Performance

6

R.

12

1

62

S

0

The frozen flow performance is estimated from a simple model. Under discharge chamber conditions of 100 atm and 13,300 deg K the hydrogen is fully dissociated and 2% ionized (Fig. 6). We calculate the conditions for recombination of hydrogen atoms and then argue that since the resulting exhaust flow is mostly [10] SESAME Equation of State Library, Report LASL-79-62, Los Alamos Scientific Laboratory, Los Alamos, NM.

[11] "Mollier Chart for Hydrogen," AFOSR Contract AF 49(638)-54





Ð

but not completely dissociated, the ionization energy in the exhaust is negligible compared to the dissociation energy.

The hydrogen starts from rest and accelerates to a maximum velocity of 25 km/sec. For a 10 cm long nozzle, a rough estimate of the nozzle residence time is \approx 5 microseconds. From the model of Zel'dovich and Raizer [12], the recombination rate of atomic hydrogen is given by

$$\frac{1}{n_{\rm H}}\frac{{\rm d}n_{\rm H}}{{\rm d}t}\approx -2\,\sigma\,\overline{v}\,V_{\rm H_2}\,n_{\rm H}^2$$

where

30

6

Ø,

3

ΨŬ

 $\sigma = \text{scattering cross section} \approx 12 \times 10^{-16} \text{ cm}^2$ $V_{H2} = \text{volume of H}_2 \text{ molecule} \approx 1.1 \times 10^{-23} \text{ cm}^3$ $\overline{v} = \text{mean velocity, } (8\text{kT}/\pi\text{M}_{\text{H}})^{1/2} = 1.56 \times 10^6 \text{ cm/sec @ 1 eV}$ $n_{\text{H}} = \text{atomic density} = 6 \times 10^{19}/\text{cm}^3 \text{ @ 100 atm, 1 eV}$

This equation displays the important result that the percentage reduction in ny scales as ny². Operation of the PET dimuster at high pressure therefore greatly aids the recombination process.

The characteristic recombination time from the above equation is

$$t_{r} = \frac{1}{2\sigma \overline{v} V_{H_{2}} n_{H}^{2}}$$

At 100 atm and 1 eV, tr = 6.7 x 10^{-9} sec, which is so short compared to the flow time that the hydrogen is in local thermal equilibrium. The density at which tr becomes longer than the 5 microsecond flow time is nH \approx 2.2 x 10^{18} , which corresponds to a pressure of about 1.8 atm and a temperature of about .44 eV (5200 deg K).

Under these conditions the hydrogen is about 93% dissociated (see Fig. 6), with an energy of 310 kJ and an enthalpy extraction of 305 kJ/gm. Were the nozzle to be truncated at this point, the efficiency would be 50% and the specific impulse would be 2520 seconds. We approximate the flow from this point as monatomic

^[12]Zel'dovich and Raizer, "Physics of Shock Waves and High-Temperature Hydrodynamic Phenomena," Vol I, Academic Press, NY, 1966. p.364 ff.

hydrogen, and calculate the density at which the hydrogen freezes in translation.

Translational freezing occurs when the mean free path becomes large, say 1 cm. This density is approximately $10^{15}/\text{cm}^3$, which for adiabatic flow of a perfect monatomic hydrogen gas with $\gamma=5/3$ corresponds to a drop in temperature from 5200 deg K to 30° K, which says that the translational energy does not freeze. [This is not true in practice because of the nozzle boundary layer.]

The design area ratio is 500:1. This ratio will inviscidly achieve Mach 20 with a monatomic gas, extracting over 99% of the translational enthalpy. This extracted enthalpy amounts to 107 kJ/gm, which when added to the initial 305 kJ/gm gives 412 kJ/gm extracted. The remaining 203 kJ/gm [615-412] is the dissociation energy of the hydrogen. The thruster efficiency is then

$$\eta = \frac{412}{615} = .67$$

The thruster specific impulse $\sqrt{2\Delta H}/g$ is

 $I_{SD} = 2930$ seconds

The thrust to power ratio $2\eta/gI_{sp}$ is

T/P = .0467 N/kW

This design provides slightly more specific impulse and slightly less efficiency than was initially proposed, but provides a benchmark design against which 70-75% efficiency can be achieved at 2500 seconds.

Thruster Thermal Design

60

Ŵ,

50

10

Rocket Research Company, Redmond, WA was hired to develop a liquid hydrogen PET thermal model. The principle concern was development of a design to prevent boiling of liquid hydrogen in the injection tube, and a satisfactory design was achieved.

The thruster design is shown in Figure 5. The primary components are listed in Table I below:

		iquiu nyui	ogen rei infuscei	components
<u>No.</u>	Components	<u>Material</u>	ODxIDxL, cm	Comments
1.	LH ₂ Plenum	347 SS	1.1 x 0.8 x 5.0)
2.	Nozzle Seal	Carbon	2.3 x 0.5 x .10)
3.	Injection Tube	347 SS	0.5 x .45 x 8.0) k=.10 [W/cm ^o K]
4.	Injection Orifice	Macor	0.7 x .01 x 0.8	k=.017 [₩/cmºK]
5.	Insulator	SizNa	4.0 x .45 x 7.3	8 k=.25 [W/cm ^o K]
6.	Nozzle Electrode	W-alloy	2.3 x .50 x .95	5 k=.94 [W/cm°K]
7.	Nozzle	brass	8.5 x 1.3 x 10.	4 A/A*=250
8.	Nozzle Mount	copper	6.1 x 3.0 x 1.5	5 k=3.8 [W/cm ^o K]
9.	Fin Radiator	copper	17 x 6.1 x 1.0	400 cm^2
10.	Compression Sleeve	4340 STL	6.1 x 4.0 x 7.8	8 k=.50 [W/cm ^o K]
11.	Retainer	Macor	6.1 x 1.7 x 1.5	5 k=.017 [W/cmºK]
12.	Injection Electrode	W-alloy	2.7 x 0.7 x 2.0) k=.94 [W/cm ^o K]
13.	Gas H ₂ Plenum	347 SŠ	2.1 x 1.1 x 5.0)
14.	HV Seal	Macor	4.0 x 2.7 x 0.5	5 rated 5 kV
15	Injection Tube Seal	Carbon		

TABLE I. Liquid Hydrogen PET Thruster Components

Ð

Ŷ

\$

10

Sr

1Ø

4

1

6

S.S.S.S.S.

12 20347 R.o +.004369.7 VET VECEAR 10 . BAR (69) ED. CONDUCTIVITY (BTU/FT HR °F) (207) 8 8.00 0080 63) 6 CONDITION UNKNOWN (71) O (<u><u></u>]+</u> 2 2 8.00-.00803T-3.50E (GT-DEMES) 0 -400 -300 -200 - 100 0 LIQUIP H2 - 424°F TEMPERATURE (°F)

B.7.v

THERMAL CONDUCTIVITY OF 347 STAINLESS STEEL

REP (207) (SEE AGOVE):

10

ø

04

1Ø

N,

 $H^{\mu}_{\mu\nu}$

-

Y.S. Touloukian et al :: THERMOPHYSICAL PROPERTIES RESEARCH CENTER DATA BOOK, Vol 1, Ch. 1, June, 1966.

Figure 7

18

SSSS - SSSSS - SSSSS



Thermal analysis was performed by a finite element radiation and conduction model. Heat is allowed to flow through material conduction paths between elements or by surface radiation to the surrounding environment, assumed to be at 293 deg K. Thermal conductivities were generally assumed to be constant, the lone exception being the injection tube, designed of 347 SS. For this material k drops by a factor 8 between room temperature and liquid hydrogen temperature of 20 deg K, so that k was expressed as an analytic function of temperature (Fig. 7)[13]. The elements used are shown in Figure 8.

Figure 8 also shows some of the principle calculated temperatures. The LH₂ is shown to start at 20.0 deg K, reaching 30.2 deg K before injection. Boiling can be prevented by maintaining the hydrogen at a pressure at 10 atm up to the injection orifice (Item 4, Fig. 5). Some of the hydrogen will then flash to vapor in the discharge capillary, but the effect of this on performance has not been analyzed.

The steady temperatures of the radiator (Item 9) and the nozzle (Item 7) were also calculated, and are shown in Figure 8. Based on these temperatures, total radiation to the environment is 365 watts, which represents a loss to the system which must be supplied electrically. This radiated loss has the effect of reducing the efficiency from .67 to .62.

The thermal analysis predicts that the 5 kW liquid hydrogen PET thruster would appear significantly different from an arcjet at the same power. Peak temperature of the radiator is only 550 deg. K, so that it would not radiate in the visible. This characteristic also makes the PET thruster hospitable to sensors located in the vicinity of the device.

[13]"Cryogenic Materials Data Handbook," Vol. I, Sections A, B, C, Air Force Systems Command, Wright-Patterson Air Force Base, OH, NTIS AD713619. July, 1970.

III. FEASIBILITY OF LIQUID HYDROGEN LABORATORY TESTS

Although small quantities of liquid hydrogen are required for testing a 5 kW PET thruster, the preparation of a laboratory liquid hydrogen facility is a non-trivial task. At the design condition of .23 N thrust and 2930 seconds specific impulse, the mass flow rate of LH₂ is 8.0 milligrams/second, and the volume flow rate is .11 cm³/sec. Several approaches were investigated for laboratory testing of PET with this LH₂ flow requirement.

Dewar System

G

ŵ

The dewar system is the first choice, because it is the least expensive, and permits tests of any duration by replenishing the dewar during the test. The dewar system (Fig. 9) uses a liquid nitrogen pre-cooling system and a liquid hydrogen system, which consists of a dewar, transfer line and phase separator. [The LN₂ system is not shown in Fig. 9] The phase separator is located close to the thruster, and uses gravity to insure that only liquid phase hydrogen enters the thruster plenum (Item 1, Fig. 5). The separated gas is ducted to a cooling jacket surrounding the plenum (Item 13, Fig. 5) and is then ejected into the laboratory safety system.

In order to cool the system initially, the system mass is first cooled to 77° K, using LN₂. The LH₂ is used to cool down to 20° K. The system mass is not known exactly, but it will be in the 5-10 kg range. A rough estimate of the quantity of LH₂ required per kg for cooling is derived for an average specific heat of 300 J/kg-deg K, a temperature drop of 57 deg K, and a heat of evaporation of 31 kJ/liter. Thus .55 liters of LH₂ are required for cool-down, so 3-6 liters are required for a 5-10 kg system, an acceptable amount.

Once cooled, LH₂ is required for thruster operation. The LH₂ quantity for 5 kW thruster operation is .11 cm³/sec or 0.4 liters/hour. Since the thruster takes 1.4 hours for 10^6 pulses, relatively little LH₂ is required to run the thruster, except for the longest tests. The longest test requirement would probably be 10^8 pulses, which would require 140 hours and 56 liters, easily tolerated by a dewar system. Even a 50 kW thruster could be tested by this technique, since a standard pressurized LH₂ cylinder holds 170 liters, and can be refilled during a test.

Liquid hydrogen is transferred from the dewar under pressure to the thruster through a vacuum-jacketed transfer line. The design of a typical line for helium [and hydrogen] is shown in Figure 10, as available from CRYO Industries of America. Inc.





The phase separator (Fig. 9) uses gravity to extract hydrogen vapor from the fluid, which flows to the thruster, shown with thrust axis vertical. The cold vapor is ducted to a plenum jacket surrounding the LH₂ plenum. Additional thermal insulation in the forum of radiation shielding and jacketing will be required, but is not included in this design.

The most difficult requirement to satisfy on the liquid hydrogen system is safety. On large LH₂ systems, no valves are allowed inside a building for safety reasons, which requires that 100 m or so of transfer line be cooled. The problems of greatest concern are:

- a) Accidental spillage and fire
- b) Leakage of pressurized hydrogen and fire
- c) Purging and disposition of vacuum pump exhaust
- d) Hoods and ventilation system for hydrogen gas
- e) Accidental spillage on human skin.

The solution of each of these areas is possible, and requires great care and experience with cryogenics and in particular with LH2. No attempt was made to estimate safety-related costs, but they are certainly significant.

Refrigerator System

1

Ð

Ú,

3

2

Q,

Ð

The refrigerator system, in which LH₂ is made at the thruster from gaseous hydrogen, is significantly safer than the dewar system, because the problem of LH₂ spillage does not exist. The basic system is shown in Figure 11.

For hydrogen, the heat which must be extracted to condense from 77 deg K is 1200 J/gm. For a 5 kW thruster, the equivalent refrigeration power is 9.8 W. This can be supplied by a small closed cycle refrigerator, e.g. the Air Products CS-208L shown in Figure 12. This refrigerator is too small, however, to provide the cool-down requirements of the system. A 10 kg system would require approximately 160 kJ, so a two hour cool-down would require an average of 22 watts. Even though the refrigerator efficiency and power is higher at 77 deg. K a larger refrigerator than the CS-208L would be required.

A solution to this problem is to provide a large (say 100 kg) block of copper, which is cooled to the LH2 freezing point of 14 deg. K. The total heat capacity of the block from 14 deg K to 20 deg K is then 180 kJ, which can provide the 160 kJ required for cool-down. A small 10 W refrigerator can then be used, running continuously. Note that a typical cost for a 10 W refrigerator is \$16k, whereas a 25 W refrigerator is about \$25k.



GOUGO ...

MARCHONGROUNDRUNGHUNGHUNG

DISPLEX® CLOSED CYCLE REFRIGERATION SYSTEMS

0

0

8

-

10

10

10

ð,

30

()t



7

JUSSENSE DEPENDENCE

NATIONAL SECOND PARAMETERS DESCRIPTION

PERSONA RECENTED

26

Although the refrigerator system is safer than the dewar system, there are still important safety considerations related to gaseous hydrogen. These safety issues, items b-d above, require design and modification to any laboratory not already equipped to handle toxic or combustible gases.

Existing Facilities for LH2

Although technically feasible, the time and cost for designing, procuring and learning to operate a new liquid hydrogen facility are large for an SBIR Phase II program. An alternative is to use an existing facility, which could provide not only the LH₂, but also the vacuum tanks and equipment required for PET thruster testing.

One such facility is the 10V Aerospace Chamber at the Arnold Engineering Development Center, Arnold Air Force Station, TN 14. The description of the 10V facility is reproduced in Appendix A-4 of this report, which shows that 5 kW PET thruster testing can be performed in this facility.

A visit was made [5/27/87] to AEDC to see the 10V facility and discuss LH₂ operation with Dr. Allan B. Bailey of Calspan. PET requirements were thoroughly discussed, and there is confidence that an experiment could be performed at AEDC on the 10V. Operating at 10 atm pressure could prove to be a problem, however. Besides LH₂, LN₂ and LHe are available. AEDC has expertise in transfer line fabrication, LH₂ handling, and also in the testing of small rocket thrusters using a variety of diagnostics. AEDC has made an ROM estimate of 12-22 K as the cost of safety analysis plus hardware to permit LH₂ operation. Other costs would include a power supply, a tank cooling system, and GT-Devices travel costs for testing, in addition to AEDC testing fees.

Phase II R&D for PET Thruster Scientific and Technical Feasibility

The most critical issue facing the liquid hydrogen PET thruster is the LH₂ injection and arc breakdown process. As discussed above, hydrogen boiling must be prevented in the injection tube, which can be prevented by proper design, particularly the use of a ceramic injection nozzle. This design must be verified by experiment. The second major issue is the evaporation of the injected liquid in the discharge chamber, which must be accomplished on a microsecond time scale.

14"Test Facilities Handbook" (Twelfth Edition), Arnold Engineering Development Center, Arnold Air Force Station, TN, March 1984. The details of the liquid/vapor heating process for LH2 subjected to a megawatt-level electric discharge depend on the injector design. Drop size and wall interactions will strongly influence the evaporation time. This critical area is currently being investigated at GT-Devices under an AFOSR-funded 36 month experimental program to investigate the arc heating of water sprays spectroscopically. The results of this investigation will aid in understanding of the LH2 injection process.

One of the related questions to the injection process is that of propellant utilization, i.e., how much propellant must actually be injected to hold the discharge temperature at the design level. Any excess propellant has the effect of reducing specific impulse. While it is believed that high (over 80%) utilization factors can be achieved, this remains to be demonstrated.

Chemical reactions between hydrogen and the thruster electrodes are an important issue. Total pulse time for a long (10^8 pulses) mission is approximately 10^3 seconds, so it is hoped that chemical reactions can be minimized by the proper choice of materials. The solution to this problem must be demonstrated by experiment.

Finally, the performance (thrust and specific impulse) must be measured. While the calculations of the heating and exhaust processes provided in this report are believed to be a fair representation of the actual situation, the issue can only be resolved by experimental test.

Summary of LH₂ Feasibility

Q.

ŵ

Three approaches were investigated; dewar, closed cycle refrigerator and the AEDC 10V aerospace chamber. Startup costs and startup time are lowest for the AEDC option. This option requires GT-Devices offsite personnel, but this would be a requirement in any case unless high vacuum facilities were constructed at GT-Devices. Testing at AEDC therefore seems to be the best solution investigated.

The refrigerator option should be rejected. It suffers from high equipment costs, which are not offset by the savings in safety requirements. The flexibility and low initial cost of the dewar system makes this system the second choice after AEDC.

IV. CONCLUSIONS RELEVANT TO A PHASE II SBIR PROGRAM

Ô

1

 \mathbf{D}

Ð

The purpose of the Phase I program was to design a liquid hydrogen PET thruster and determine the feasibility of liquid hydrogen testing for Phase II.

The design analysis indicates that the LH₂ PET would be a 62% efficient thruster at 2930 seconds, performance significantly higher than other types of thrusters (Fig. 12). Operation at higher pressures and lower temperatures, if it can be achieved, would raise the system efficiency to the 75% level at 2000 seconds.

The current history of space operations strongly suggests that propellants other than liquid hydrogen, particularly water and hydrazine, will have a role to play in space before LH2 becomes available. As far as the PET thruster is concerned, it may be well to establish water and hydrazine performance before liquid hydrogen, since the former can still perform in an interesting specific range above 1000 seconds.

Performance measurements on PET will require testing at a laboratory facility capable of high vacuum not available at GT-Devices. Initial testing on water can be performed at GT-Devices inexpensively at modest tank pressures.

It is concluded that Phase II of this PET performance effort should be broadened to include water, hydrazine and liquid hydrogen propellants, and this has been proposed as indicated in Appendices A-1 and A-2.



APPENDIX A - 1

(

Q

10

W.

Q

3

0

3

8

Ø

1000000000

PARAMAN PROPERTY



5705A General Washington Drive Alexandria, VA 22312 (703) 642-8150 11 September 1987

66

6

ð

8

Ð

Ms. Linda Marie Kendrick Contract Specialist 3350 (LMK) NASA Lewis Research Center Cleveland, Ohio 44135

Dear Ms. Kendrick:

GT-Devices is pleased to submit the enclosed SDIO SBIR Phase II proposal GTD-93, "Performance of a Pulsed Electrothermal Thruster with Water, Hydrazine and Liquid Hydrogen."

Phase I of this effort was performed under AFOSR Contract F49620-87-C-0028DEF. After Phase I, Leonard H. Caveny of SDIO/IST agreed to assign responsibility for technical evaluation of this Phase II proposal to NASA-Lewis, under the direction of David C. Byers, Chief, Auxiliary, Propulsion Branch.

We are aware that the SBIR program gives special consideration to proposals demonstrating non-Federal capital commitments for Phase III activities. We are pleased to say that Rocket Research Company, Redmond, WA, has made such a commitment for this Phase II effort, and has promised a growing commitment based on successful results in Phase II. This commitment takes the form of 1) equipment purchases 2) facilities modifications, and 3) the performance of Task 4 of this proposal (fuel cart) at no cost to the contract. Rocket Research Co. has agreed to do this in order to stay within the SBIR funding eligibility requirements, and to demonstrate their company's commitment to this vital program. Rocket Research Company's letter of commitment is enclosed in this proposal.

If you have any questions of a technical nature, please call Rodney L. Burton at the above number. Other questions may be referred to me.

Sincerely,

E Luclow AREAN

Marian E. Ludlow Contracts Administrator

Enclosure

cc: R. L. Burton, D. A. Tidman, S. A. Goldstein
D. C. Byers - NASA-Lewis
L. H. Caveny - SDIO/IST
W. W. Smith, R. J. Cassady, B. W. Schmitz ~ RRC

APPENDIX A - 2

8

¢ ¢

11441 WILLOWS RD N.E. P.O. BOX 97009 REDMOND, WA 98073-9709 (206) 885-5000 TWX 910-449-2861

8

3

ħČ:

Ś

1

53

48

ð?

Olin ROCKET RESEARCH COMPANY

DEFENSE SYSTEMS GROUP

September 9, 1987 Ref. No. 3100-87-169

Dr. R. L. Burton Director of Space Applications GT Devices 5705A General Washington Drive Alexandria, VA 22312

Dear Dr. Burton,

Rocket Research Company (RRC) is pleased to have the opportunity to cooperatively pursue the development of the Pulsed Electrothermal Thruster (PET) with GT Devices. The PET performance regime and adaptability to many propellants compliments the range of electric thrusters currently being pursued by RRC. This SBIR provides the opportunity to prove performance feasibility of this important new thruster concept and as such has generated a company commitment to support this effort.

RRC is modifying an on-going electric propulsion capital improvement effort to accommodate the particular testing requirements of the PET. As part of this capital improvement, RRC will provide a fuel cart capable of running N_2H_4 or H_2O , will modify a new vacuum chamber to allow vertical firing of the PET, and will provide adequate instrumentation, data recording, power, and pumping capacity for the proposed PET test. If the proposed feasibility test is successful and applications for this thruster become more defined, RRC's commitment in this area will continue to grow. Again, RRC is pleased to work with GT Devices and focus its experience base and talent on a successful Phase II effort.

Sincerely yours,

B. W. Schmitz

Vice President, Engineering and Technology

BWS/km#54



Liquid Hydrogen Experimental Project for G T Devices Inc.

April 20, 1987

Project Director: Dr. Rodney L. Burton Director of Experimental Research

Furpose: To determine the feasibility of suppling Hydrogen as a liquid fuel to a experimental booster motor at a rate of 1 Gram per minute.

Physical layout: The motor will be placed on a vacuum chamber in a way so as to allow the discharge from the motor to enter the chamber. This is to simulate operation in a vacuum such as outer space.

The fuel will be supplied from a inlet at the top of the motor which will be in a vertical position on the top of the vacuum chamber, and this fuel must be a liquid saturated a 1 pound per square inch gauge.

DATA RELATED TO HYDROGEN

Conversion data:

80

00

10

X

31

5

2

÷

6

÷.

		wei	ight	nt gas		liquid	
		Lb.	Kg	SCF	Nm3	Gal	L
1	pound	1.0	0.4536	192	5.047	1.6928	6.408
1	kilogram	2.205	1.0	423.3	11.126	3.733	14.128
1	SCF Gas	0.005209	0.002363	1.0	0.02628	0.00882	0.03339
1	Nm3 Gas	0.19815	0.08988	38.04	1.0	0.3355	1.2699
1	Gal lig.	0.5906	0.2679	113.41	2.981	1.0	3.785
1	L liq.	0.15604	0.07078	29.99	0.7881	0.2642	1.0

Notes: standard cubic foot gas measured at 1 atomosphere and 70'F.

Nm3 gas measured at 1 atomsphere and 0'C.

Liquid measured at 1 atmosphere and boiling temperature.

Hydrogen gas values expressed in the stable condition 75% ortho, 25% para.

Equilibrium Hydrogen is commonly referred to as para-Hydrogen and is 2% ortho-Hydrogen.

Hydrogen liquid values expressed in the stable para condition.

All values rounded to nearest 4/5 significant numbers.

All values are consistent with standards adopted by the Compressed Bas Association on June 19.1962. The following is the Hydrogen material data for refrigerated liquid which is synonymous with the terms liquid Hydrogen, Para Hydrogen, and liquified Hydrogen.

D.O.T. identity number; 1333-74-0

D.O.T. hazard class: FLAMMABLE GAS

Chemical family: Cryogenic Flamable inorganic

Volumetrics: One volume of liquid Hydrogen at its boiling point and atomspheric pressure will vaporize into approximately 850 volumes of gaseous Hydrogen at 70'F (21.1'C) and 1 atmosphere.

HEALTH HAZARD DATA:

8

Ø

33

Hydrogen is defined as a simple asphyxiant. Oxygen levels should be maintained at a greater than 18 Molar percent at normal atmospheric pressure which is equivalent to a partial pressure of 135 MM Hg. (ACGIH,1985-86). Inhalation of high concentrations of Hydrogen so as to exclude an adequate supply of oxygen to the lungs causes dizziness, deeper breathing due to air hunger causes possible nausea and eventual unconsciousness. Contact with the cryogenic liquid can cause tissue freezing or frostbite on dermal contact or if splashed in the eyes. Hydrogen is inactive biologically and essentially nontoxic.

Prompt medical attention is mandatory in all cases of overexposure to Hydrogen. Rescue personnel should be equipped with self-contained breathing apparatus and be cognizant of exteme fire and explosion hazard.

PHYSICAL DATA: Hydrogen is flammable over a very wide range in air and should be considered a hazardous mixture when other liquids, solids, or gases are introduced.

BOILING FOINT: -423'F (-252.8'C)

VAPOR PRESSURE: 070'F(21.1'C): above the critical temp. of -399.8'F

LIQUID DENSITY AT BOILING POINT: 4.43 Lb/Ft3 (70.96Kg/M3)

GAS DENSITY AT 70'F AND 1 ATM: .0052

SOLUBILITY IN H20: very slight

EVAPORATION RATE: 99.9+% volatile

FREEZING POINT: -434.6'F (-259.2'C)

SPECIFIC GRAVITY: (AIR=1) @70'F (21.1'C)= .069

APPERANCE: Clear, colorless, odorless liquid

AUTO IGNITION TEMP.: 1058'F (570'C)

FLAMMABLE LIMITS % X VOLUME: LEL 4 UEL 74.5

NOTE: Earth-ground and bond all lines and equipment associated with the Hydrogen system. All electrical equipment should be non-sparking or explosion proof. Liquid Hydrogen cylinders should be used only in well ventilated areas of non-combustible construction and in accordance with the manufacturer's instructions. This type cylinder must always be kept in an upright position. Specialized hand trucks are needed for movement of this type cylinder.

6 .

The feasibility of this project is possible using the above stated safety and data guide lines.

The supply control for the liquid Hydrogen can be operated from a temp. sensor type control or a liquid flow control. Either type will supply the quality liquid required. This will be used along with vacuum insulated piping, special controls and equipment required to supply liquid to the motor. Serious considerations must be given to the safety of this project as it relates to the test area, supply of liquid Hydrogen and Oxygen sources. We are sure that some type of modification must be done in the test area to provide adequate ventilation due to the nature of the liquids and gases and their wide range of flammability.

With out additional data we can not expand on the physical layout which would explain the detail of the liquid Hydrogen installation with related equipment. There are two ways to supply the liquid to this project, and we feel that the smallest amount of liquid Hydrogen on test site would be the safest. To supply the test stand we would suggest that a small dewar be used to supply the phase seperator which in turn supply the inlet to the motor and provide a liquid source saturated at one atmosphere. Care must be taken to properly vent the phase seperator as a volume of Hydrogen gas must be vented at this point to assure the liquid is at the quality required. The dewar can be removed and refilled from a liquid source such as a liquid cylinder. This refilling process must be done at a remote and safe site. The liquid cylinder contains approx. 45 gallons of liquid Hydrogen which could be pressurized as high as 150 P.S.I.G. and adequate ventilation is required for the refill process.

The basic differance between a liquid dewar and a liquid cylinder is in the design and coding of the units. The dewar is an insulated container designed to hold liquids for a short period of time at atmospheric pressures and cryogenic temperature. The liquid cylinder is A.S.M.E. coded at a pressure and designed to hold larger amounts of cryogenic liquid under pressures higher than atmospheric for longer periods of time. The condition of the liquid will change as the pressure rises in the liquid container. The control for the liquid Hydrogen must be done after the phase seperator as the volumetrics change. I would suggest that a control flow orfice be used to allow the liquid flow to be changed as desired during testing the motor. The control orfice can be designed several ways depending on the accuracy and response required. One possible way to build this control is to design a fixed orfice with a metering valve up stream which will allow the flow to the orfice to be adjusted. The entire liquid flow operation can be monitored through liquid pressure and temperature sensors which can be manually or automatically controlled.

The general layout and operation of the liquid Hydrogen supply will be done as follows.

1. The dewar will be filled from a larger liquid source such as a liquid cylinder.

2. The dewar will then be positioned on the test stand and a supply of Hydrogen gas will be applied to the unit which will cause the liquid to be forced at low pressure into the phase seperator.

3. The phase seperator will reduce the heat from the liquid and allow the cooled liquid to flow into a small reserve which will feed the motor. At this point the flow control equipment will be installed to adjust the flow.

4. the entire Hydrogen supply system should be shrouded in a Nitrogen gas blanket. This will assure that the supply sustem will remain inert and free from Dxygen impingement. The Nitrogen blanket will improve the safety of the system.

The cost involved with the liquid Hydrogen supply is difficult to assess but a qualified estimation of the total cost would be in the \$35,000.00 range. This estimate is with the understanding that all the equipment is of a prototype design that requires special handling.

In closing, any experimental project involving liquid Hydrogen can be dangerous if not properly controlled. This project is feasible only if the safety control is strictly adhered to and the liquid volumes are maintained at the lowest possible levels.

Thank you for the interest in Woodland Cryogenics, our products, and services. We look foward to the continuation of this and other projects in which we can provide this type of service.

Yours Truly

Jan Sta

Ú.

ð

20

Hudson Payne Sales Mgr. Woodland Crogenics Inc.

39

PARAGRAPH 01CARTP20



APPENDIX A - 4

8

3

1%

٧Č

ю

64

÷

N

Ð

PART 10 Aerospace Chamber (10V)

10.1 GENERAL DESCRIPTION

dî,

A

ß

Š

10

8

10

Ð

10

æ

The Aerospace Chamber (10V) (Fig. 10.1) is designed for low density aerodynamic studies and testing of small rocket engines under space vacuum conditions.



Fig. 10.1 View of the Aerospace Chamber (10V)

The stainless steel chamber, located in the Developmental Chamber Area in the Engineering Laboratory Building, is 10 ft in diameter and 20 ft long. Chamber pumpdown is accomplished with a 730-cfm roughing pump, a 140-cfm forepump, and a 6-in. diffusion pump. The chamber is equipped with an internal cryogenic system designed for high efficiency vacuum pumping of aerodynamic test streams and rocket exhaust products. The cryogenic system consists of a 77°K liquidnitrogen-cooled high capture liner, 20°K gaseoushelium-cooled surfaces and 4.2°K liquid-heliumcooled surfaces.

The unique capabilities of this chamber make it suitable for (1) aerodynamic testing of items, such as drag measurements on satellite configurations and high altitude air sampling probes, in the transition and free molecular flow regimes, and (2) determining the performance and effects of small rocket engines operaing in the space environment, including jet plume studies.

10.2 PERFORMANCE

10.2.1 AERODYNAMIC TESTING

The low denisty aerodynamic testing configuration is shown in Fig. 10.2. The nozzles are cooled with liquid nitrogen to reduce boundary layer thickness. A resistance heater allows operation at reservoir temperatures up to 1000°K at Mach numbers from 2 to 7.

Typical performance characteristics of this chamber as an aerodynamic facility are shown in Figs. 10.3a and b. Uniform flow core diameters up to 50 cm can be obtained. The run time, using nitrogen varies from a few minutes at a mass flow of 40 gm/sec to hours at mass flows less than 3 gm/sec. Molecular mean free path lengths of slightly more than 2 in. can be obtained at the nozzle exit plane.

10.2.2 SPACE PROPULSION TESTING

The space propulsion testing configuration is shown in Fig. 10.4. Free expansion on the jet plume is made possible by the high capture rate of the exhaust gases on the chamber cryogenic surfaces.

The performance of the chamber for rocket engine testing is shown in Fig. 10.5. The actual test conditions which can be achieved within the performance range shown are a function of the propellants used and the resultant exhaust products—the lower the hydrogen content, the lower the chamber ambient pressure.



- 64

- 6

Ø

١¢

Q

ĝ

0

¢,

10

(ii

8

000005556

Fig. 10.2 Aerospace Chamber (10V) Operating as Low Density Aerodynamic Facility





10.2



Fig. 10.4 Aerospace Chamber (10V) Operating as a Space Propulsion Test Facility

*

ŵ

10

Ŷ

0



Fig. 10.5 Performance of Aerospace Chamber (10V) for Space Propulsion Testing

10.3

NUMBER NAMES N

MARKARKA NAMADAN

ELLER TURNER

