

DTIC FILE COPY

①

AD-A199 216

PORT DOCUMENTATION PAGE

2b. DECLASSIFICATION/DOWNGRADING SCHEDULE		1b. RESTRICTIVE MARKINGS	
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.	
6a. NAME OF PERFORMING ORGANIZATION Naval Ocean Systems Center	6b. OFFICE SYMBOL (if applicable) NOSC	7a. NAME OF MONITORING ORGANIZATION Naval Ocean Systems Center	
6c. ADDRESS (City, State and ZIP Code) San Diego, CA 92152-5000		7b. ADDRESS (City, State and ZIP Code) San Diego, CA 92152-5000	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (if applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State and ZIP Code)		10. SOURCE OF FUNDING NUMBERS	
		PROGRAM ELEMENT NO.	PROJECT NO.
			TASK NO.
			AGENCY ACCESSION NO.
			XV36
11. TITLE (include Security Classification) FIBER-OPTIC PRIMARY DIVING TETHER			
12. PERSONAL AUTHOR(S)			
13a. TYPE OF REPORT Presentation/speech	13b. TIME COVERED FROM Mar 1988 TO Mar 1988	14. DATE OF REPORT (Year, Month, Day) August 1988	15. PAGE COUNT
16. SUPPLEMENTARY NOTATION			
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	
19. ABSTRACT (Continue on reverse if necessary and identify by block number) Diving operations require a clear, reliable communications link between surface support personnel and the diver. The electrical umbilicals presently used are heavy and cumbersome or require an external strength member. These cumbersome tethers hinder the diver's ability to accomplish search, inspection, repair or maintenance tasks.			
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a. NAME OF RESPONSIBLE PERSON S. R. Terwilliger		22b. TELEPHONE (Include Area Code) (808) 257-1607	22c. OFFICE SYMBOL Code 534

Presented at the DoD Fiber Optics Conference, 22-25 March, McLean, VA.

DTIC
ELECTE
SEP 07 1988
S E D

DD FORM 1473, 84 JAN

83 APR EDITION MAY BE USED UNTIL EXHAUSTED
ALL OTHER EDITIONS ARE OBSOLETE

88 9 6 242

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE

THE CONFERENCE RECORD

DOD FIBER OPTICS CONFERENCE '88

March 22-25, 1988
McLean Hilton Hotel
McLean, Virginia

Sponsored by

The Tri-Service Fiber Optics Coordinating Committee

and

The Armed Forces Communications and Electronics Association

in Cooperation With

The Department of Energy

and

The Office of the Under Secretary of Defense, Acquisition
(Research and Advanced Technology) Electronics System



Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

FIBER-OPTIC PRIMARY DIVING TETHER

STEVEN R. TERWILLIGER, Project Engineer

NAVAL OCEAN SYSTEMS CENTER, Hawaii Laboratory

Diving operations require a clear, reliable communications link between surface support personnel and the diver. The electrical umbilicals presently used are heavy and cumbersome or require an external strength member. These cumbersome tethers hinder the diver's ability to accomplish search, inspection, repair or maintenance tasks.

Use of fiber optics in combination with synthetic strength members have been used to overcome many of the problems inherent to existing communication cables. These materials allow a reduction in cable weight, diameter, and electromagnetic signature while maintaining the tensile strength required in diving tethers. The combination of high-quality communications and increased diver mobility significantly improves safety and the ability of a diver to complete a task.

A system was developed to demonstrate the role fiber optics can play in diving communications. The system (figure 1) provided for round-robin voice and video data transmission between multiple divers and the surface and interfaced to fleet equipment with no modification to that equipment. The system can be reconfigured depending on mission requirements.




Figure 1. Fitted and observed survival curves for the 1997-1998 season.

The optomechanical cable contains an outer armor and jacket over a jacketed core (figure 2). The jacketed core is composed of three armored optics: graded-index (multimode) fibers, each individually Kevlar armored and jacketed. This jacketed core is then armored with the primary Kevlar strength-member and jacketed.




Figure 2 1-400 488R data: comparison of the two experimental conditions

The cable design permits the outer armor to be strength terminated at the diver's waist while passing the core through to the optical connector on the junction box. The optical connector on the junction box was a multi-pass, expanded-beam connector with internal strain relief manufactured by Litton Veam.

Tests were performed to evaluate the cable's performance when subjected to mechanical and environmental stresses. The tests indicate the cable performs well under severe loading and bending conditions.

2

Tensile-Load test results showed an average break strength of 1665 pounds (termination influenced) compared with a design break strength of 2000 lbs. Constructional stretch was 0.35 percent and the strain at 500 pounds was 0.8 percent. Tensile tests on three armored-optic samples resulted in an average ultimate strength of 250 pounds.

The Tensile-Attenuation test measured the change in optical attenuation in a long length of cable under cyclic tension. Attenuation measurements were taken at 100 pound intervals up to 500 pounds and a final reading at 750 pounds during tension cycles. Over three tension cycles, the excess attenuation caused by this tension loading was less than 0.8 dB (0.85 um wavelength) in any fiber.

Bend-Attenuation tests were used to evaluate the effects of bending over a sheave on optical transmission. Excess attenuation was never greater than 2.8 dB (0.85 um wavelength) over any size sheave. Transmission was only lost when the cable was kinked.

The optomechanical cable is approximately the same diameter as the electrical umbilical it replaced and it has a strength member. The cable contains three fibers; two fibers were used for telemetry (simplex communication) leaving the third fiber for future system expansion. With a 750 pound safe lift rating (2x safety factor), the cable can be married into an existing surface-supply diving tether or act along as the primary diving tether.

Acknowledgements: Funds for this project were provided by the Navy Science Assistance Program.

Biographical Data: Steven Terwilliger is an ocean systems engineer with the Advanced Systems Division, Naval Ocean Systems Center, Hawaii Laboratory. Mr. Terwilliger graduated summa cum laude with degrees in Ocean and Electronics technology from the Florida Institute of Technology in 1980. He has been working in the areas of fiber-optics, ROV and diving support technologies since 1982.