

AD-A211 794

N00014-88-K-0354


Discriminating Rigid from Nonrigid Motion

Myron L. Braunstein
Donald D. Hoffman
Frank E. Pollick

(9) Studies in the Cognitive Sciences, 51
July 1989

Department of Cognitive Sciences
University of California, Irvine
Irvine, California, 92717

Accession For	
NTIS CRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	



This research was supported by Office of Naval Research Contract N00014-88-K-0354, National Science Foundation Grants BNS-8819565 and IRI-8700924, and DOD Grant N00014-87-G-0135. We would like to thank Bruce Bennett, Jill Nicola, Chetan Prakash, and Whitman Richards for helpful discussions, Laura Bertin for programming assistance, George Andersen for comments on an earlier draft of this paper, and Lionel Shapiro for conducting a series of experiments preliminary to those reported here. The earlier series of experiments was reported in "Minimum Points and Views for the Detection of Rigid Structures," October 1987.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No 0704-0188

1a REPORT SECURITY CLASSIFICATION Unclassified			1b RESTRICTIVE MARKINGS N. A.		
2a SECURITY CLASSIFICATION AUTHORITY N. A.			3 DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release; distribution unlimited.		
2b DECLASSIFICATION / DOWNGRADING SCHEDULE N. A.					
4 PERFORMING ORGANIZATION REPORT NUMBER(S) 51 (Studies in the Cognitive Sciences)			5 MONITORING ORGANIZATION REPORT NUMBER(S) Same		
6a NAME OF PERFORMING ORGANIZATION University of California- Irvine		6b OFFICE SYMBOL (if applicable)	7a NAME OF MONITORING ORGANIZATION Office of Naval Research		
6c ADDRESS (City, State, and ZIP Code) Department of Cognitive Sciences Irvine, CA 92717			7b ADDRESS (City, State, and ZIP Code) 800 N. Quincy Street Arlington, VA 22217-5000		
8a NAME OF FUNDING / SPONSORING ORGANIZATION Office of Naval Research		8b OFFICE SYMBOL (if applicable) Code 1142PS	9 PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER N00014-88-K-0354		
8c ADDRESS (City, State, and ZIP Code) 800 N. Quincy Street Arlington, VA 22217-5000			10 SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO 61153N 42	PROJECT NO RR04209	TASK NO RR0420901
					WORK UNIT ACCESSION NO 4424219
11 TITLE (Include Security Classification) (U) Discriminating Rigid from Nonrigid Motion					
12 PERSONAL AUTHOR(S) Braunstein, Myron L. Hoffman, Donald D. Pollick, Frank E.					
13a TYPE OF REPORT Technical		13b TIME COVERED FROM 88/08/01 TO 91/07/31		14 DATE OF REPORT (Year, Month, Day) 89/07/31	
15 PAGE COUNT 26					
16 SUPPLEMENTARY NOTATION					
17 COSATI CODES			18 SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	depth, images, motion, orthographic, rigidity, vision, rotation, structure, three-dimensional, perception, <i>Human observers, Visual perception</i>		
19 ABSTRACT (Continue on reverse if necessary and identify by block number) Theoretical investigations of structure from motion have demonstrated that an ideal observer can discriminate rigid from nonrigid motion from two views of as few as four points. We report three experiments that demonstrate similar abilities in human observers: In one experiment 4 of 6 subjects made this discrimination from two views of four points; the remaining subjects required five points. Accuracy in discriminating rigid from nonrigid motion depended on the amount of nonrigidity in the nonrigid structure. Our measure of nonrigidity was based on the variance of the interpoint distances over views. The ability to detect a rigid group dropped sharply as "noise" points (points not part of the rigid group) were added to the display. We conclude that human observers do extremely well in discriminating between nonrigid and fully rigid motion, but do quite poorly at segregating points in a display on the basis of rigidity. Key words:					
20 DISTRIBUTION / AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS			21 ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a NAME OF RESPONSIBLE INDIVIDUAL H. Hawkins			22b TELEPHONE (Include Area Code) (202) 696-4323		22c OFFICE SYMBOL Code 1142PS

SECURITY CLASSIFICATION OF THIS PAGE

Contents

Abstract	iv
1. Introduction	1
1.1 Theoretical Developments	2
2. Experiment 1	4
2.1 Method	5
2.1.1 Subjects.	5
2.1.2 Design.	5
2.1.3 Stimuli.	5
2.1.4 Apparatus.	6
2.2 Procedure	6
2.3 Results	7
3. Experiment 2	8
3.1 Method	9
3.1.1 Subjects.	9
3.1.2 Design.	9
3.1.3 Stimuli.	9
3.2 Procedure	11
3.3 Results	11
4. Experiment 3	12
4.1 Method	13
4.1.1 Subjects.	13
4.1.2 Design.	13
4.1.3 Stimuli.	13
4.2 Procedure	13
4.3 Results	14
5. Discussion	17
References	20

Abstract

Theoretical investigations of structure from motion have demonstrated that an ideal observer can discriminate rigid from nonrigid motion from two views of as few as four points. We report three experiments that demonstrate similar abilities in human observers: In one experiment 4 of 6 subjects made this discrimination from two views of four points; the remaining subjects required five points. Accuracy in discriminating rigid from nonrigid motion depended on the amount of nonrigidity in the nonrigid structure. Our measure of nonrigidity was based on the variance of the interpoint distances over views. The ability to detect a rigid group dropped sharply as "noise" points (points not part of the rigid group) were added to the display. We conclude that human observers do extremely well in discriminating between nonrigid and fully rigid motion, but do quite poorly at segregating points in a display on the basis of rigidity.

1. Introduction

Human observers report seeing three-dimensional (3D) relationships in certain changing two-dimensional (2D) images, e.g., images that represent projections of rotating solid objects (Wallach & O'Connell, 1953) or projections of rotating patterns of dots (Braunstein, 1962; Green, 1961). There has been recent interest in the minimum numbers of points and views for which subjects can make accurate judgments about 3D structure from 2D images. This interest stems in part from theoretical analyses of the minimum conditions under which an ideal observer can infer 3D structure from 2D coordinates. In this paper we relate psychophysical data to theoretical analyses for a particular judgment: discriminating rigid from nonrigid motion.¹

Lappin, Doner, & Kottas (1980) studied the ability of subjects to judge 3D relationships on the basis of only two views. They added noise to polar projections of rotating rigid spheres by varying the number of points that were in correspondence between the views. They concluded that two views were sufficient for discriminating between different levels of noise applied to rigid structures. Braunstein, Hoffman, Shapiro, Andersen, & Bennett (1987) asked subjects to discriminate between same and different rigid structures on the basis of 2-6 views of 2-5 points. They found that human performance exceeded theoretical expectations, although some of the accuracy may have resulted from subjects exploiting the correlation that exists between 3D and 2D interpoint distances: 2D interpoint distances tend to be more similar for two projections of the same 3D object than for two projections based on different 3D objects.

Todd (1988) has provided further evidence that two views are sufficient for distinguishing between rigid and nonrigid motion. He had subjects rate the rigidity of the depicted motion for two, four or eight views of 14 connected line segments. The nonrigid displays were created by having each line segment end point rotate about an axis whose position and orientation with respect to the picture plane was selected at random. The mean ratings given by subjects for nonrigid and rigid displays were at opposite ends of a five-point rating scale. This clear discrimination between rigid and nonrigid displays did not increase with views, possibly because the effect had already reached a ceiling in the two-view condition.

In research concerned specifically with testing the applicability of Ullman's (1979) theorem to human observers, Petersik (1987) studied discrimination of rigid from nonrigid motion in displays consisting of three views of four points. This study used only rotations about a vertical axis. Nonrigid motion was produced by taking rigid displays and displacing points horizontally or vertically in the 2D projection. This method, however, does not provide a clear indication of a subject's ability to discriminate rigid from nonrigid motion. When nonrigid displays are produced by perturbing the 2D trajectories of points in a rigid display, it may be possible to

¹Points move rigidly if all of their three-dimensional interpoint distances remain constant over time.

distinguish between rigid and nonrigid displays on the basis of the trajectories of individual points. The most obvious case is that of a parallel projection of dots rotating about a vertical axis with a perturbation inserted in the vertical direction. All of the unperturbed trajectories are horizontal lines; any perturbed trajectories in the nonrigid display may be detected merely because they deviate from horizontal lines. It is important that any task involving discriminations between rigid and nonrigid motion should require subjects to use relationships between points; the trajectories of individual points should not be discriminable between rigid and nonrigid displays.

1.1 Theoretical Developments

Theoretical investigations of structure from motion have proceeded in two directions. In the first, investigators have developed specific theorems, stating specific conditions in which image motion can be given a three-dimensional interpretation. In the second, investigators have developed a general framework, within which the specific theorems can be seen as special cases. In this section we briefly review the progress on specific theorems. A discussion of the general framework is beyond the scope of this paper, and may be found elsewhere (Bennett & Hoffman, 1988; Bennett, Hoffman, & Prakash, 1989). We then discuss the distinction between detecting and recovering rigid structures in motion, a distinction critical to the experimental work we present.

The specific theorems can be distinguished, for convenience, along three dimensions: constraints, projection, and temporal mode. Constraints are required due to the fundamental ambiguity of structure from motion, viz., any given dynamical image, no matter how rich in features or extended in time, has not just one three-dimensional interpretation but, in principle, infinitely many. A dynamic two-dimensional image does not, by itself and without further constraints, specify a unique three-dimensional interpretation; it does not because the components of motion and position along the lines of sight are lost in projection. So if, for example, one collected the data output by a video camera, it would not make sense to ask, without further constraints, what is *the* three-dimensional interpretation of that data. For this reason each theorem employs some constraint.

The constraints employed so far can be grouped into two categories: rigid and nonrigid motion. The constraint of rigid motion has been proposed by many perceptual psychologists (Gibson & Gibson, 1957; Green, 1961; Hay 1966; Johansson, 1975; Ullman, 1979; Wallach & O'Connell, 1953). The idea is that, of all possible three-dimensional interpretations of dynamic two-dimensional images, the rigid interpretations should be among the ones preferred. Kruppa (1913), building on work of Chasles (1855), first stated rigorously conditions in which image motion can be given a three-dimensional interpretation using a constraint of rigidity. Kruppa's result and others (Faugeras & Maybank, 1989; Huang & Lee, in press;

Longuet-Higgins & Prazdny, 1980; Ullman, 1979), allow arbitrary rigid motions. Other results have restricted the type of rigid motion: rotation about the vertical axis (Longuet-Higgins, 1982); rotation about an arbitrary fixed-axis (Bobick, 1986; Hoffman & Bennett, 1986; Webb & Aggarwal, 1981); rotation at a constant angular velocity (Hoffman & Bennett, 1985; 1986); and rotation in a single plane (Hoffman & Flinchbaugh, 1982). Nonrigid motion has been less studied (Bennett & Hoffman, 1985; Grzywacz & Hildreth, 1987; Koenderink & van Doorn, 1986; Ullman, 1984).

The projections employed in the theorems are two: orthographic and perspective. In orthographic projection the distance of an object from the imaging surface has no effect on its image. If one uses cartesian coordinates (x,y,z) such that coordinates x and y lie in the imaging plane and z is orthogonal, then orthographic projection is the map $(x,y,z) \mapsto (x,y)$. In perspective projection the distance of an object from the imaging surface does have an effect on its image, with greater distance leading to a smaller image. A simple model of this is given by the map $(x,y,z) \mapsto (x/z, y/z)$. Some analyses use a combination of orthographic and perspective projections, as in Ullman's (1979) "polar-parallel" projection.

The temporal modes employed are two: discrete and continuous. Discrete time analyses treat motion much like a video camera does--as a sequence of frames (Hoffman & Flinchbaugh, 1982; Huang & Lee, in press; Longuet-Higgins, 1982; Ullman, 1979). Continuous time analyses treat motion in terms of vector fields and their spatial and temporal derivatives (Hoffman, 1982; Koenderink & van Doorn, 1975, 1976, 1981; Longuet-Higgins & Prazdny, 1980; Waxman & Wohn, 1987). Again, combinations of these temporal modes are possible, though not common (Bobick, 1986).

We now consider one structure-from-motion theorem in modest detail--as an example of this line of investigation, and as an aid to understanding the distinction between detection and recovery. Bennett, Hoffman, Nicola, and Prakash (1989) prove the following result. Suppose that four points are moving in space. Suppose that one is given two distinct orthographic views of the points. And suppose that, between the two views, the four points move rigidly and are noncoplanar. Then the two views contain sufficient information to restrict the possible rigid interpretations to a one-parameter family. Moreover, if the four points do *not* move rigidly between the views then, almost surely (Lebesgue measure), the views have no possible rigid interpretation (this last statement was proved by Ullman (1977)).

We can now make clear, with the aid of this example theorem, the distinction between detection and recovery of a structure in motion. Informally, to *detect* rigid structures is to discriminate successfully between those image data (here, those two views of four points) that have rigid interpretations from those that do not; to *recover* rigid structures is to assign a rigid interpretation to each set of image data that is compatible with a rigid interpretation. Detection is necessary for recovery, but not vice versa. In our example theorem, two views of four points are sufficient to detect rigid structures, but once detection has occurred there is still an

uncountable set of rigid interpretations that could be assigned. Rigidity alone, under these conditions, is an insufficient constraint to pick out one interpretation from this uncountable collection. Hence one cannot, under these conditions, recover a rigid structure.

The example theorem states that for two views of any four moving points it is theoretically possible to determine whether or not those points could lie on a rigid structure. Our first objective in the present study was to determine whether human observers can discriminate rigid from nonrigid structures at this minimum combination of points and views. A finding that human observers can make this discrimination on the basis of two views of four points would provide support for the hypothesis that human observers can exploit a rigidity constraint. Our second objective in this research was to examine the robustness of this discrimination as noise is added to a rigid display. To do this we measured the reduction in accuracy of this discrimination when points that were not part of the rigid structure were added to the display.

The first experiment was intended to demonstrate that rigid structures can be discriminated from nonrigid structures at the theoretical minimum level of two views of four points. The second experiment studied how increasing the number of views affects accuracy of this discrimination. The third experiment studied how the detection of rigid structures is affected by adding points that were not part of the rigid structure. This addresses a fundamental question: whether a rigidity constraint is likely to be useful in human vision for segregating rigid from nonrigid motion, so that 3D structure can be recovered for those points that are moving rigidly.

2. Experiment 1

The principal objective of the first experiment was to establish that subjects can discriminate rigid from nonrigid structures on the basis of two distinct views of as few as four points. The discriminability of rigid and nonrigid structures depends of course on the set of nonrigid structures that are used in the "noise" trials. As we noted earlier, the nonrigid trials must be generated in a way that does not allow discrimination between rigid and nonrigid displays on the basis of the motions of individual points. This precludes the use of random motions in the nonrigid displays and of methods in which the 2D trajectories of moving points are perturbed. Instead, both the rigid and nonrigid displays should be generated from the same individual dot motions. This suggests two methods of generating nonrigid displays, methods which can be used separately or in combination. The first assigns a different angular velocity to each point in the nonrigid displays, but has all points rotating about the same axis. The second assigns the same angular velocity to each point, but has each point rotate about a different axis. We chose the latter method because the first produces a relationship between 2D and 3D nonrigidity, viz.,

greater 2D nonrigidity for the displays that are nonrigid in 3D. (The measure of 2D nonrigidity that we used is described in the Stimuli section.) Producing 3D nonrigidity by varying the axis of rotation, as in the latter method, does not result in a consistent relationship between 2D and 3D nonrigidity.

2.1 Method

2.1.1 Subjects. The subjects were four undergraduate students, one graduate student, and one staff member, who were paid for their participation. Acuity of at least 20/40 (Snellen eye chart) was required in the eye used throughout the experiment. Three of the undergraduate students were run without feedback. These subjects had no knowledge of the purposes of the experiment. The remaining subjects were run with feedback. One of these subjects was the third author; the other two were generally familiar with the purposes of the experiment.

2.1.2 Design. We examined two independent variables: the number of points in a simulated object and the presence or absence of feedback. The number of points was 4, 5, or 6. Each subject responded to 80 signal trials and 80 noise trials at each of the three levels of points.

2.1.3 Stimuli. A stimulus display consisted of two views of four, five, or six light-green dots, changing position against a dark background. The two views represented a sequence of orthographic projections of points undergoing rotations in three dimensions. Initial point positions were selected at random within the volume of a sphere. The axes of rotation were determined as follows: A total of 272 points were placed at approximately equal distances on the surface of a sphere. (This was done using a three frequency dodecahedron approximation. See Pugh, 1986.) A set of potential axes of rotation was defined by connecting each of these points to the center of the sphere, with the constraint that the slant angle of each axis (relative to the viewing direction) fell within the range 45° - 90° . There were 34 axes that met this constraint. For *rigid* displays, all points in the display rotated about the same axis (which was randomly selected from the set of 34 axes). For *nonrigid* displays, each point rotated about a different axis, each randomly selected without replacement from the set of 34 axes. The angle of rotation about each axis was selected from a uniform distribution over integer values between 6° and 18° .

Displays were used in the experiment only if they met three criteria: (a) nearest neighbor correspondence, (b) minimum 2D motion, and (c) minimum 3D spacing. The nearest neighbor criterion required the 2D position of each point in each view to be closer to the 2D position of that point in the other view than to the position of any other point in the other view. The minimum 2D motion criterion required that each point move between views a distance of at least 5% of the radius of the generating sphere. The minimum 3D spacing criterion required all pairs of points, in any given view, to be separated by at least 5% of the radius of the generating sphere. These three criteria were imposed to help assure (a) correct

correspondence matching, (b) clearly visible motion of all points, and (c) clear separation of all points.

We developed a measure of 2D nonrigidity to determine whether the 2D projections of *nonrigid* displays were less rigid than the 2D projections of *rigid* displays. First, we computed the variance, across views, of the projected interpoint distances of each pair of points in a display. Then we computed the mean of these variances across pairs. This mean gave the measure of nonrigidity in the 2D projection. An analysis of variance (ANOVA) was conducted on the stimulus displays, using the measure of 2D nonrigidity for each randomly generated display as the dependent variable. The independent variables were 3D rigid vs. 3D nonrigid displays and number of points. The 2D nonrigidity did not differ significantly for the rigid and nonrigid displays, $F(1,79) < 1$. The main effects of number of points on 2D nonrigidity, and the interaction, were also not significant.

The SOA between views was 400 msec. In order to allow sufficient time for subjects to make a judgment, the two views were repeated until the subject responded, up to a maximum of 60 sec.

2.1.4 Apparatus. The stimuli were presented on a Hewlett-Packard Model 1321B X-Y Display with a P-31 phosphor, under the control of a PDP 11/83 computer. The maximum projected diameter of each simulated object occupied 821 plotting positions on the screen and subtended a visual angle of 2° . Points were refreshed at a rate of 17.5 Hz. The dot and background luminances at the screen were approximately 5 and 0.02 cd/m², respectively. Subjects viewed the displays through a tube that limited the field of view to a circular area 7.9° in diameter. A 0.5 neutral-density filter was inserted in the tube to remove any apparent traces on the CRT. The eye-to-screen distance was 1.7 m.

A metal and plastic model consisting of four white spheres rigidly connected by thin black rods was used to instruct the subjects. The subjects responded by pressing one of two switches, one labeled "rigid" and the other "nonrigid." The responses (and response latencies) were recorded by the PDP 11/83.

2.2 Procedure

Each subject participated in one practice session followed by four experimental sessions. Each session began with 9 practice trials followed by a random sequence of 120 trials, consisting of 20 signal and 20 noise trials at each of the three point levels. The trials were presented in three blocks of 43 trials each. There was a 2-sec delay between each trial and a 1-min rest period between each block.

Subjects were instructed to press the "rigid" switch if the display consisted of a group of dots that was moving rigidly and to press the "nonrigid" switch otherwise. A group of dots was defined as moving rigidly if "the distance from any dot to any other dot remains the same, no matter how the group is moved." The model was

used to demonstrate the rigid group condition. Subjects who were to receive feedback were told that a single tone would indicate a correct response and that two tones would indicate an incorrect response. The room was darkened 2 min before the trials began.

2.3 Results

A signal detection paradigm (Green & Swets, 1966) was used to analyze the results, with the trials containing a rigid group serving as signal trials. (We consider some of the implications of this definition of signal trials in the Discussion section.) A d' measure was computed for each subject and stimulus condition, using the proportion of "rigid group" responses on signal (3D rigid display) trials as the hit rate and the proportion of "rigid group" responses on noise (no rigid group) trials as the false alarm rate. Each d' was based on 160 trials, half of which were signal trials.

The significance of the d' scores was calculated for each subject and number of points, using Marascuilo's (1970, pp. 238-240) one-signal significance test. Table 1 lists these d' values. Of a total of 18 d' s (six subjects, three numbers of points) 14 were significantly different from zero ($p < .05$). For feedback subjects, 8 (of a total of 9) were significant. For nonfeedback subjects, 6 (of a total of 9) were significant. The d' s for all feedback subjects and for one nonfeedback subject were significant at two views of four points. The d' s for all subjects were significant at two views of five points. The mean d' s for the subjects given feedback was higher than for those not given feedback (0.84 vs. 0.67) and lower for four points (0.51) than for five and six points (0.90 and 0.85), but these differences were not statistically significant.

A measure of 3D nonrigidity was developed to determine whether the amount of 3D nonrigidity in the noise displays affected the d' results. This measure was the mean across pairs of points of the variances of the 3D interpoint distances across views. (Specifically, let $\mathbf{p}_{ij} = (x_{ij}, y_{ij}, z_{ij})$ denote the position in space of point i in view j . Let d_{iij} be the 3D distance between $\mathbf{p}_{ij}$ and $\mathbf{p}_{i'j}$. Let σ_{iij}^2 be the variance of d_{iij} over all views j . Then our 3D nonrigidity measure is the mean of the σ_{iij}^2 for all distinct i and i' .) The nonrigid displays were separated into two categories--*high* and *low* 3D nonrigidity--according to whether nonrigidity was greater than or less than the median value. The proportion of false alarms was calculated separately for each category. The proportion of correct responses for the entire rigid group was used to calculate the hit rate. This provided separate measures of d' for nonrigid displays with low and high amounts of nonrigidity. Fifteen (of 18) d' s were significantly different from zero when the high nonrigidity displays were used in calculating the false alarm rate and eight (of 18) were significantly different from zero when the low nonrigidity displays were used. The d' values were higher for the high nonrigidity displays than for the low nonrigidity displays in 16 of 18 comparisons (6 subjects x 3 numbers of points). The mean d' s for the high nonrigidity and low nonrigidity displays were 0.99 and 0.54, respectively.

Table 1
d' Scores in Experiment 1

Subject	Number of Points		
	4	5	6
Feedback			
Group			
F	0.865*	1.235*	1.635*
A	0.550*	0.735*	0.280
T	0.505*	0.800*	0.925*
No			
Feedback			
Group			
G	0.345	0.715*	1.060*
L	0.475*	1.210*	0.805*
O	0.290	0.705*	0.405

* $p < .05$

These results indicate that human observers can discriminate rigid from nonrigid structures at or near the minimum level at which this discrimination is theoretically possible: two views of four points. (This is the minimum level if one assumes orthographic projection and if no constraints other than rigidity are applied.) The discriminability of rigid from nonrigid motion depends on the nonrigidity in the noise trials, as reflected in our 3D nonrigidity measure.

3. Experiment 2

Experiment 2 examines accuracy in the four-point condition as the number of views increases. Previous studies present mixed results for the effects of number of views on judgments related to recovery of 3D structure and discrimination of rigid from nonrigid motion. Doner, Lappin, and Perfetto (1984) found increased accuracy with increasing numbers of views in discriminations between different

levels of spatio-temporal correlation in polar projections of rotating dot spheres. Braunstein et al. (1987) found increasing accuracy with increasing numbers of views in discriminations between same and different 3D structures. On the other hand, Todd (1988) found no increase in the discriminability of rigid from nonrigid structures as the number of views was increased beyond two. Theoretically, two views does contain sufficient information for discriminating rigid from nonrigid structures (Bennett, Hoffman, Nicola, & Prakash, 1989; Ullman, 1977), but a third view is required before a specific rigid structure can be recovered (Ullman, 1979). It is possible that human observers are more accurate in discriminating rigid from nonrigid motion when there is sufficient information to recover a specific structure. If this were the case an increase in accuracy should be expected in the three-view over the two-view condition.

Number of views, however, cannot be studied in isolation. Only two of the following three variables can be held constant as the number of views is varied: (a) rate of presentation of the views, (b) amount of rotation between views, and (c) total amount of rotation in the sequence of views. We chose to hold the first two variables constant and allow the total amount of rotation to vary with number of views. For our nonrigid displays, this resulted in an increase in our measure of 3D nonrigidity with increasing numbers of views. It is thus possible that an increase in d' with increasing views could be attributed to an increase in nonrigidity in the noise trials (suggested by Todd, personal communication, May 1, 1989). If the effect of number of views is due to the increase in 3D nonrigidity in the noise trials, we would expect that (a) d' will increase steadily with increasing numbers of views; and (b) the increase in d' will result from a decrease in the false alarm rate rather than an increase in the hit rate.

3.1 Method

3.1.1 Subjects. The subjects were four of the six subjects who had served in Experiment 1. Two subjects had received feedback in Experiment 1 and two had not.

3.1.2 Design. We examined two independent variables: number of views (2, 3, 4, 5, or 6) and SOA (66 ms or 400 ms). (Two levels were used because Todd, Akerstrom, Reichel, and Hayes, 1988, found an interaction between number of views and SOA in determining ratings of rigidity.) All displays contained four points. Each subject responded to 60 signal trials and 60 noise trials at each of the ten combinations of SOA and number of views.

3.1.3 Stimuli. The method of generating the stimuli was the same as that used in Experiment 1 with the following exceptions. The SOAs were 66 ms and 400 ms. The refresh rate for both SOAs was 15 Hz. The angles of rotation were randomly selected from a uniform distribution over integer values between 5° and 9° . For rigid displays having more than two views, a new axis of rotation was randomly

Table 2
d' Scores in Experiment 2

SOA	Subject	Number of Views				
		2	3	4	5	6
66 ms						
	F	0.905*	1.075*	1.530*	1.620*	2.030*
	A	0.200	0.390	0.460*	1.190*	1.315*
	G	0.000	0.260	1.315*	1.470*	1.575*
	L	0.490	1.630*	1.210*	1.810*	1.295*
400 ms						
	F	1.190*	1.520*	2.225*	2.300*	3.035*
	A	0.670*	0.860*	1.110*	1.165*	1.745*
	G	0.715*	1.120*	1.400*	1.045*	1.460*
	L	0.825*	1.330*	1.620*	1.420*	2.495*

* $p < .05$

selected for each additional view. For nonrigid displays having more than two views, a new axis of rotation was selected for each point in each additional view.

An ANOVA was conducted on the stimulus displays, using the 2D nonrigidity measure as the dependent variable. The independent variables were 3D rigidity, SOA, and number of views. The 2D nonrigidity was significantly different for the 3D rigid and 3D nonrigid displays, $F(1,59) = 10.8$, $p < .01$. The 2D nonrigidity measure increased significantly with number of views, $F(4,236) = 178.3$, $p < .01$. There were no other significant effects or interactions. The significant effect of 3D nonrigidity indicates that it was theoretically possible for subjects to discriminate 3D rigid from 3D nonrigid displays on the basis of 2D nonrigidity. This seems unlikely, however, as the variance in the 2D nonrigidity measure accounted for by 3D nonrigidity was 0.3%, compared to 38.2% accounted for by number of views. The means of the 2D nonrigidity measures were .0053 for the 3D rigid displays and .0058 for the 3D nonrigid displays. The means for the displays with 2-6 views were .0012, .0029, .0053, .0077, and .0107, respectively. The units are squared distances in a unit sphere.

3.2 Procedure

Each subject participated in one practice session followed by 10 experimental sessions. Each session began with 9 practice trials followed by a random sequence of 120 trials, consisting of 12 signal and 12 noise trials at each of the 5 view levels. The trials were presented in three blocks of 43 trials each. Half the experimental sessions were at the short SOA, the other half at the long SOA. The order of SOA was alternated between sessions with half the subjects beginning with the long SOA and the other half beginning with the short SOA. The procedure was otherwise the same as in Experiment 1.

3.3 Results

A d' was computed for each subject and stimulus condition (Table 2). For the short SOA 15 of the 20 d' s were significantly different from zero, $p < 0.05$. Of the five that were not significant, three were at the 2 view level and two were at the 3 view level. For the long SOA all 20 d' s were significantly different from zero ($p < 0.05$).

A two-way ANOVA was conducted with SOA and number of views as the independent variables. There were two significant effects. The main effect of SOA, $F(1,3) = 16.83$, $p < 0.05$, $\omega^2 = 0.08$, showed an increase in d' with longer SOA (1.46 vs. 1.09). The main effect of number of views, $F(4,12) = 29.16$, $p < 0.01$, $\omega^2 = 0.44$, showed an increase in d' with greater numbers of views. Post hoc comparisons (Tukey's HSD test) showed significant differences for 2 views vs. 3, 4, 5, and 6 views; 3 views vs. 5 and 6 views; and 4 views vs. 6 views.

As in Experiment 1, d' s were calculated with the nonrigid displays divided into high and low 3D nonrigidity subgroups. For the high nonrigidity displays 36 of 40 d' s were significantly different from zero with a mean d' of 1.50. For the low nonrigidity displays 29 of 40 were significantly different from zero with a mean d' of 1.07. The d' values were greater for the high nonrigidity displays than for the low nonrigidity displays in 37 of 40 comparisons (4 subjects $\times$ 2 SOA's $\times$ 5 numbers of views).

The relationship between number of views and 3D nonrigidity, d' , hit rate, and false alarm rate is shown in Figure 1. The 3D nonrigidity measure increased with number of views. There was a corresponding decrease in the false alarm rate. The hit rate remained constant, indicating that the increase in d' was due to a decrease in the false alarm rate. This is the pattern of results that would be expected if the effect of number of views was due to the increase in the 3D nonrigidity that occurred with increasing numbers of views. This provides a further indication of subjects' sensitivity to variations in 3D nonrigidity and confirms the usefulness of the 3D nonrigidity measure as a predictor of performance in discriminating rigid from nonrigid motion.




Figure 1. d' , 3D nonrigidity, proportion of hits, and proportion of false alarms as functions of the number of views (Experiment 2). (In order to use the same abscissa values for d' and the 3D nonrigidity measure, the nonrigidity measure is multiplied by 1000 in this figure and in Figures 2 and 3.)

4. Experiment 3

Two orthographic views of four points are theoretically sufficient to determine whether or not a 3D motion is rigid (Bennett, Hoffman, Nicola, & Prakash, 1989; Ullman, 1977), and the results of Experiments 1 and 2 indicate that subjects can make this discrimination at these minimum levels of points and views. For displays containing more than four points, the same theoretical analysis can be used to determine whether a display contains any subset of four points that is moving rigidly. It is important to know whether subjects can also determine whether rigid motion is present under these conditions; the usefulness of a rigidity constraint would be severely limited if such a constraint could be applied only when all moving elements were part of the same rigid structure. Experiment 3 included displays in which four points were moving rigidly but which, in addition, had from one to four points that were not part of the rigid structure. The subject's task, rather than indicating whether the observed structure was rigid or nonrigid as in Experiments 1 and 2, was to determine whether the display contained at least four points that moved together rigidly.

4.1 Method

4.1.1 Subjects. The subjects were three of the four subjects from Experiment 2 and one graduate student who had not served in Experiments 1 or 2. Three of the subjects were naive as to the purposes of the experiment; one subject was the third author. As a precondition for participating in this experiment, each subject was required to achieve a d' of 1.2 or better in a screening session in which they responded to 100 trials of 12 views of 4 points. This criterion assured that subjects were performing, on trials with no noise points, at a level comparable to performance in Experiment 2. One of the four subjects failed to meet the criterion in the first screening session but succeeded in doing so in a second screening session.

4.1.2 Design. We examined two independent variables: number of views (2, 3, 4, or 12) and number of noise points (0, 1, 2, 3, or 4). Each subject responded to 60 signal trials and 60 noise trials at each of the 20 combinations of number of views and noise points.

4.1.3 Stimuli. The method of generating the stimuli was the same as that used in Experiments 1 and 2, with the following exceptions: The 2D minimum motion criteria for a display had to be met for each point for at least one transition between views rather than for all transitions. This change was made because of difficulty in generating 12-view displays that satisfied the more stringent criterion. Also, there was a change of two parameters: SOA and range of rotation angle for transitions. Two SOAs were used, 80 ms and 240 ms. (These were selected on the basis of Todd's observations, personal communication November 1988, and our own observations of the SOAs required for perception of smooth motion for two-view and multiple-view displays.) The refresh rate for both SOAs was 12.5 Hz. The long SOAs were used for the two view displays and the short SOA for the 3, 4 and 12 view displays. The angles of rotation were randomly selected from a uniform distribution of integer values between 5° and 7° . The larger rotation angles used in the previous experiments were eliminated because they appeared to interfere with the perception of smooth motion at the 80-ms SOA.

An ANOVA was conducted on the 2D nonrigidity measure, with 3D rigidity, number of views, and number of noise points as the independent variables. The only significant effect was the main effect of number of views, $F(3,177) = 1510.0$, $p < .01$. The means for 2, 3, 4, and 12 views were 0.0009, 0.0019, 0.0029, and 0.0133.

4.2 Procedure

Each subject participated in one or more screening sessions (described above), one practice session, and 24 experimental sessions. Each experimental session began with 5 practice trials followed by a random sequence of 100 trials, consisting of 10 signal and 10 noise trials at each of the 5 noise point levels. The trials were presented in three blocks of 35 trials each. There were 6 sessions at each

of the 4 levels of number of views. The number of views across the 24 sessions was in the order 12, 4, 3, 2, 2, 3, 4, and 12 views, repeated three times.

As in Experiment 1 there was a 2 sec delay between each trial and a 1 min rest period between each block. The subjects were instructed to press the "rigid" switch if the display contained a group of dots that was moved together rigidly and to press the "nonrigid" switch otherwise. A group of dots was defined as moving together rigidly if "at least four dots maintain constant distances from each other regardless of how the entire group moves."

4.3 Results

A d' was computed for each subject and stimulus condition (Table 3). Of 80 d' 's, 48 were significantly different from zero, $p < 0.05$. For 0 noise points 15 (of 16) d' 's were significantly different from zero. For 4 noise points 7 (of 16) d' 's were significantly different from zero.

The independent variables in the ANOVA were number of noise points and number of views. There were two significant effects. The main effect of number of noise points, $F(4,12) = 26.79$, $p < 0.01$, $\omega^2 = 0.34$, showed a decrease in d' with more noise points. The mean d' values for 0, 1, 2, 3, and 4 noise points were 0.97, 0.54, 0.45, 0.37, and 0.40, respectively. Post hoc comparisons showed only the differences between 0 noise points and nonzero noise point conditions to be significant. The main effect of number of views, $F(3,9) = 10.43$, $p < 0.01$, $\omega^2 = 0.21$, showed an increase in d' with greater numbers of views. The mean d' 's for 2, 3, 4, and 12 views were 0.34, 0.52, 0.49, and 0.84, respectively. Post hoc comparisons showed only the differences between 12 views and smaller numbers of views to be significant.

In the previous experiments we examined the relationship between accuracy of discrimination and a measure of 3D nonrigidity for the noise trials. For those experiments the 3D nonrigidity for the signal trials was always zero. In Experiment 3, 3D nonrigidity increased for the signal trials as additional noise points were added. It is likely that discriminability in this experiment was based on a relationship between 3D nonrigidity in the signal trials and 3D nonrigidity in the noise trials. We examined two obvious relationships: the ratio of the nonrigidity measure (signal trials/noise trials) and the difference in the measure (noise trials - signal trials). The correlations with d' , across the 20 combinations of views and noise points, were -.65 for the ratio measure and .87 for the difference measure. We therefore present the difference measure in Figures 2 and 3. Figure 2 shows the effects of number of noise points on d' and on the difference between noise and signal trials in 3D nonrigidity. The hit rate and false alarm rate are also shown. Figure 3 presents these effects as the number of views increases from 2 to 12. These results suggest that the difference in nonrigidity, or some related quantity, accounts both for the effects of points and for the effects of views. These effects are due primarily to changes in the false alarm rate.

Table 3
d' Scores in Experiment 3

Number of Views	Subject	Number of Noise Points				
		0	1	2	3	4
2	F	0.740*	0.420	0.170	0.125	0.645*
	M	0.300	0.545*	0.000	-0.135	0.000
	G	0.695*	0.320	0.895*	0.000	0.105
	L	0.740*	0.380	0.555*	-0.045	0.305
3	F	1.200*	0.815*	0.725*	0.160	0.320
	M	0.630*	0.505*	0.245	0.175	0.090
	G	0.550*	0.445	0.730*	0.490*	0.305
	L	1.045*	0.515*	0.310	0.385	0.715*
4	F	0.950*	0.595*	0.465*	0.415	0.375
	M	1.040*	0.505*	0.260	0.565*	0.530*
	G	0.505*	0.375	-0.205	0.650*	0.510*
	L	0.940*	0.595*	0.275	0.180	0.220
12	F	1.560*	0.850*	0.695*	0.945*	0.815*
	M	2.005*	0.865*	0.870*	0.480*	0.660*
	G	1.345*	0.465*	0.685*	0.660*	0.250
	L	1.330*	0.375	0.550*	0.800*	0.555*

* $p < .05$




Figure 2. d' , difference in 3D nonrigidity (noise nonrigidity - signal nonrigidity), proportion of hits, and proportion of false alarms as functions of the number of noise points in the signal displays (Experiment 3).




Figure 3. d' , difference in 3D nonrigidity (noise nonrigidity - signal nonrigidity), proportion of hits, and proportion of false alarms as functions of the number of views (Experiment 3).

5. Discussion

Human observers can discriminate rigid from nonrigid motion at the minimum level of points and views at which such discrimination is theoretically possible on the basis of a rigidity constraint alone: two views of four points. For discriminations between displays in which all points were either moving rigidly or were rotating about separate axes, accuracy depended on the deviation of the nonrigid displays from rigid motion. Our measure of this deviation, the mean across pairs of points of the variance in the interpoint distance over views, was related to the discriminability of rigid from nonrigid displays. This measure is based on the 3D structure used to generate the displays. The usefulness of this measure is especially interesting in the case of the two-view displays, because the same two view displays can be generated from an infinite number of rigid 3D structures (Bennett, Hoffman, Nicola, & Prakash, 1989).

Increasing the number of points in a rigidly moving group does not lead to a clear increase in accuracy, although there was a nonsignificant increase from four to more than four points. It is certainly possible that an effect of points would be found for larger numbers of points--numbers sufficient to give the configuration a clear shape. Increasing the number of views did increase accuracy of discrimination, but this can be attributed to the increase in nonrigidity of the nonrigid displays. With points rotating about separate axes, the variance of the distances between pairs of points increases with number of views. Our measure of 3D nonrigidity, based on these variances, correlated .985 with d' across the five levels of views.

Although human subjects can discriminate rigid from nonrigid structures at the minimum level of points and views at which this discrimination is theoretically possible, accuracy drops sharply when even one point that is not part of the rigid structure is added to a rigid display. It appears that human observers are not proficient at analyses that require testing subgroups of points to determine whether one subgroup is present that is moving rigidly. (With five points there would be five such subgroups to test. This may not seem to be much of a processing load from a computational viewpoint, but five subgroups involving six distances each in one display may be difficult for human subjects to process.) These results may appear to be in conflict with Ullman's (1979) well known demonstration that two concentric cylinders differing in diameter are easily segregated by the human visual system. This demonstration, however, is not directly comparable to the present stimuli. The demonstration used a large number of points and views rather than the minimal numbers used in the present research. Perhaps more importantly, the motion in the demonstration was rotation about a fixed axis at a constant angular velocity. Bennett and Hoffman (1985) have shown that a fixed-axis constraint is sufficient mathematically for recovering 3D structure from four orthographic views of two points or three orthographic views of four points; a rigidity constraint is not necessary. Demonstrations by Braunstein (1983) and Ramachandran, Cobb, &

Rogers-Ramachandran (1988) also indicate that the perceptual segmentation of two rotating cylinders may not be based entirely on the use of a rigidity constraint.

The sharp drop in accuracy in detecting the presence of a rigid structure when noise points were added to the structure is consistent with Lappin et al.'s (1980) results with larger numbers of dots. In that study accuracy in determining which of two displays had more coherent motion was highest when one of the displays was completely rigid, but dropped sharply when both displays contained nonrigid motion. If the subjects in the present experiments were primarily engaged in detecting nonrigid motion, rather than detecting rigid groups of points, it is not surprising that accuracy would drop sharply when both the signal trials and noise trials included nonrigid motion.

Discrimination between rigid and nonrigid structures, at least on the basis of small numbers of points and views, does not appear to be an easy task for human subjects. Subjective reports indicate that this task requires careful attention. It is possible that the task could be performed with less effort if the nonrigid motions differed even more from the rigid motions. In our displays, the same center of rotation was used for all points whether or not they were part of a rigid structure. Generically, feature points that are moving independently would probably not have the same center of rotation. This probably made discriminations especially difficult in the present study, but this was necessary to prevent a consistent relationship between nonrigidity in the 2D projection and nonrigidity in 3D.

In presenting a signal detection analysis of the present experiments we chose to define displays containing groups of at least four points moving together rigidly as signal displays, and displays lacking such rigid groups as noise displays. Our results suggest that the opposite interpretation may be worth considering. Discrimination of rigid from nonrigid motion may be conceived of as detecting deviations from constant interpoint distances in 3D, that is, detecting nonrigidity. Thus in Experiments 1 and 2 the rigid displays might have been defined as the "noise displays" and the nonrigid displays as the "signal plus noise displays." Increasing the 3D nonrigidity of the nonrigid displays by increasing the number of views in Experiment 2 could then be described as increasing the signal strength, with the expected result of increasing d' . In Experiment 3 subjects may have been discriminating between levels of nonrigidity (i.e., between two levels of signal) rather than detecting rigid groups. Introspective reports suggest that subjects were both looking for rigid groups and looking for deviations from rigidity. The relationship between signal detection concepts and the discrimination of rigid from nonrigid motion would be worth exploring further with additional experimental manipulations.

In conclusion, these experiments reveal that human subjects are surprisingly good at some aspects of analyzing 3D structures and surprisingly poor at others. Human subjects can discriminate rigid from nonrigid motion at exactly the minimum levels of points and views specified by theoretical analyses, suggesting that

such analyses may be of relevance to the study of human vision. But when the task is changed to determining whether a rigid structure is present in noise, performance falls off sharply with even one noise point. We need to look further into the issue of whether a rigidity constraint is useful in perceptual grouping, or whether other constraints must determine grouping before a rigidity constraint can be applied.

References

- Bennett, B., & Hoffman, D. (1985). The computation of structure from fixed axis motion: nonrigid structures. *Biological Cybernetics*, 51, 293-300.
- Bennett B., & Hoffman D. (1988). Perceptual representations: meaning and truth conditions. In S. Schiffer & S. Steele (Eds.), *Cognition and representation* (pp. 87-128). Boulder, CO: Westview Press.
- Bennett, B., Hoffman, D., & Prakash, C. (1989). *Observer Mechanics: A formal theory of perception*. New York: Academic Press.
- Bennett, B., Hoffman, D., Nicola, J., & Prakash, C. (1989). Structure from two orthographic views of rigid motion. *Journal of the Optical Society of America*, A in press.
- Bobick, A. (1986). A hybrid approach to structure from motion. In N. I. Badler & J. K. Tsotsos (Eds.), *Motion: Representation and perception* (pp. 91-109). New York: North-Holland.
- Braunstein, M. L. (1962). Depth perception in rotating dot patterns: Effects of numerosity and perspective. *Journal of Experimental Psychology*, 64, 415-420.
- Braunstein, M. L. (1983, June). *How flexible is the rigidity assumption?* Paper presented at the Second International Conference on Event Perception and Action, Nashville, TN.
- Braunstein, M. L., Hoffman, D. D., Shapiro, L. R., Andersen, G. J., & Bennett, B. M. (1987). Minimum points and views for the recovery of three-dimensional structure. *Journal of Experimental Psychology: Human Perception and Performance*, 13, 335-343.
- Chasles, M. (1855). Question No. 296. *Nouvelles Annales de Mathematiques*, 14, 50.
- Doner, J., Lappin, J. S., & Perfetto, G. (1984). Detection of three-dimensional structure in moving optical patterns. *Journal of Experimental Psychology: Human Perception and Performance*, 10, 1-11.
- Faugeras, O., & Maybank, S. (1989). Motion from point matches: multiplicity of solutions. *Proceedings of the IEEE Workshop on Visual Motion*, 248-255.
- Gibson, J., & Gibson, E. (1957). Continuous perspective transformations and the perception of rigid motion. *Journal of Experimental Psychology*, 54, 129-138.
- Green, B. F., Jr. (1961). Figure coherence in the kinetic depth effect. *Journal of Experimental Psychology*, 62, 272-282.
- Green, D. M., & Swets, J. A. (1966). *Signal Detection Theory and Psychophysics*. New York: Wiley.
- Grzywacz, N., & Hildreth E. (1987). Incremental rigidity scheme for recovering structure from motion: Position-based versus velocity-based formulations. *Journal of the Optical Society of America*, A4, 503-518.
- Hay, C. (1966). Optical motions and space perception: An extension of Gibson's analysis. *Psychological Review*, 73, 550-565.

- Hoffman, D. (1982). Inferring local surface orientation from motion fields. *Journal of the Optical Society of America*, 72, 888-892.
- Hoffman, D., & Bennett, B. (1985). Inferring the relative 3-D positions of two moving points. *Journal of the Optical Society of America*, A2, 350-533.
- Hoffman, D., & Bennett, B. (1986). The computation of structure from fixed-axis motion: rigid structures. *Biological Cybernetics*, 54, 71-83.
- Hoffman, D., & Flinchbaugh, B. (1982). The interpretation of biological motion. *Biological Cybernetics*, 42, 195-204.
- Huang T., & Lee C., (in press). Motion and structure from orthographic projections. *IEEE Transactions on Pattern Analysis and Machine Intelligence*.
- Johansson, G. (1975). Visual motion perception. *Scientific American*, 232(6), 76-88.
- Koenderink, J., & van Doorn, A. (1975). Invariant properties of the motion parallax field due to the movement of rigid bodies relative to an observer. *Optica Acta*, 22, 773-791.
- Koenderink, J. J., & van Doorn, A. J. (1976). Local structure of movement parallax of the plane. *Journal of the Optical Society of America*, 66, 717-723.
- Koenderink, J., & van Doorn, A. (1981). Exterspecific component of the motion parallax field. *Journal of the Optical Society of America*, 71, 953-957.
- Koenderink, J., & van Doorn, A. (1986). Depth and shape from differential perspective in the presence of bending deformations. *Journal of the Optical Society of America*, A3, 242-249.
- Kruppa, E. (1913). Zur Ermittlung eines Objektes aus zwei Perspektiven mit innerer Orientierung. *Akademie der Wissenschaften in Wien: Mathematisch-naturwissenschaftliche Klasse Sitzungsberichte*, 122, 1939-1948.
- Lappin, J. S., Doner, J. F., & Kottas, B. (1980). Minimal conditions for the visual detection of structure and motion in three dimensions. *Science*, 209, 717-719.
- Longuet-Higgins, H. C. (1982). The role of the vertical dimension in stereoscopic vision. *Perception*, 11, 377-386.
- Longuet-Higgins, H. C., & Prazdny, K. (1980). The intersection of moving retinal images. *Proceedings of the Royal Society of London, Series B*, 208, 385-397.
- Marascuilo, L. A. (1970). Extensions of the significance test for one-parameter signal detection hypotheses. *Psychometrika*, 35, 237-243.
- Petersik, J. T., (1987). Recovery of structure from motion: Implications for a performance theory based on the structure-from-motion theorem. *Perception & Psychophysics*, 42, 355-364.
- Pugh, A. (1976). *Polyhedra: A visual approach*. Berkeley, CA: University of California Press.
- Ramachandran, V. S., Cobb, S., & Rogers-Ramachandran, D. (1988). Perception of 3-D structure from motion: The role of velocity gradients and segmentation boundaries. *Perception & Psychophysics*, 44, 390-393.

- Todd, J. T. (1988, November). *Minimal conditions for the perception of structure from motion*. Paper presented at the Twenty-Ninth Annual Meeting, Psychonomic Society, Chicago, IL.
- Todd, J. T., Akerstrom, R. A., Reichel, F. D., & Hayes, W. (1988). Apparent rotation in three-dimensional space: Effects of temporal, spatial, and structural factors. *Perception & Psychophysics*, 43, 179-188.
- Ullman, S. (1977). *The Interpretation of Visual Motion*. Ph.D. Thesis, Massachusetts Institute of Technology.
- Ullman, S. (1979). *The interpretation of visual motion*. Cambridge, MA: MIT Press.
- Ullman, S. (1984). Maximizing rigidity: The incremental recovery of 3-D structure from rigid and nonrigid motion. *Perception*, 13, 255-274.
- Wallach, H., & O'Connell, D. N. (1953). The kinetic depth effect. *Journal of Experimental Psychology*, 45, 205-217.
- Waxman, A., & Wohn, K. (1987). Contour evolution, neighborhood deformation, and image flow: textured surfaces in motion. In W. Richards & S. Ullman (Eds.), *Image Understanding 1985-86* (pp. 72-98). Norwood, NJ: Ablex.
- Webb, J. A., & Aggarwal, J. K. (1981). Visually interpreting the motion of objects in space. *Computer*, 14(8), 40-46.

Studies in the Cognitive Sciences

1. Peter W. Culicover and Michael Rochemont, "Stress and Focus in English" (April 1981).
2. John I. Yellott, Jr., "Seeing Things Inside Out" (July 1981).
3. Peter W. Culicover, "Learnability Explanations and Processing Explanations" (June 1981).
4. Thomas R. Nelson, R. Jacob Leonesio, Arthur P. Shimamura, Robert F. Landwehr and Louis Narens, "Overlearning and the Feeling of Knowing" (July 1981).
5. Myron L. Braunstein, George J. Andersen, and David M. Riefer, "The Use of Occlusion to Resolve Ambiguity in Parallel Projections" (July 1981).
6. W. C. Watt, "Semiotic Systemhood" (August 1981).
7. Kenneth Ralph Stern, "Contour Angle and Linear Perspective Effects on the Perceived Direction of Rotary Motion" (September 1981).
8. V. S. Ramachandran and S. M. Anstis, "Extrapolation of Motion Path in Human Visual Perception" (September 1981).
9. Gerald Patrick Delahunty, "Topics in the Syntax and Semantics of English Cleft Sentences" (In four fascicles) (September 1981).
10. Lynn Nadel, "Cognitive Maps: At the Choice Point Again" (October 1981).
11. V. S. Ramachandran, "Perception of Apparent Movement" (October 1981).
12. Louis Narens and R. Duncan Luce, "How We May Have Been Misled Into Believing in the Interpersonal Comparability of Utility" (February 1982).
13. Robert M. Harnish, Four Lectures on Inferential Pragmatics (in two fascicles) (March 1982).
14. Adrienne Frostholt, William Bennett and Gary Lynch, "Behavioral Abnormalities of Murine Muscular Dystrophy" (April 1982).
15. A. Kimball Romney, "Systemic Culture Patterns and High Concordance Codes" (June 1982).

16. V. S. Ramachandran and S. M. Anstis, "Laws of Perceptual Organization in Multistable Apparent Motion" (November 1982).
17. Tarow Indow and Toshio Watanabe, "Parallel- and Distance-Alleys on Horopter Plane in the Dark" (November 1982).
18. Tarow Indow and Toshio Watanabe, "Parallel--and Distance--Alleys with Moving Points in the Horizontal plane" (November 1982).
19. W. C. Watt, "Signs of the Times" (February 1983).
20. Victorina D. Lefebvre, "Ethical features of the normative hero in Soviet children's literature of 1960s-70s" (February 1983).
21. R. Duncan Luce and Louis Narens, "Symmetry, Scale Types, and Generalizations of Classical Physical Measurement" (February 1983).
22. Lin Chen, "What Are the Units of Figure Perceptual Representation" (February 1983).
23. Rupert Pentweazle, "Architecture, Movies, Cattlebrands, and the Ineffable" (April 1983).
24. George J. Andersen and Myron L. Braunstein, "Induced Self-Motion in Central Vision" (September 1984).
25. A. Kimball Romney, Susan C. Weller, and William H. Batchelder, "Culture as Consensus: A Theory of Culture and Informant Accuracy" (October 1984).
26. W. C. Watt, "The Byblos Matrix" (October 1984).
27. Vladimir A. Lefebvre, "The Golden Section and an Algebraic Model of Ethical Cognition" (November 1984).
28. Tom N. Cornsweet and John I. Yellott, Jr., "Image Processing by Intensity Dependent Spatial Summation" (November 1984).
29. D. D. Hoffman and B. M. Bennett, "The Computation of Structure from Fixed Axis Motion: Rigid Structures" (November 1984).
30. William H. Batchelder and David M. Riefer, "The Statistical Analysis of a Model for Storage and Retrieval Processes in Human Memory" (March 1985).
31. W. C. Watt, "What is the Proper Characterization of the Alphabet? IV: Union" (March 1985).

32. Vladimir A. Lefebvre, "The Fundamental Structures of Human Reflexion" (March 1985).
33. Louis Narens and R. Duncan Luce, "Measurement: The Theory of Numerical Assignments" (April 1985).
34. Louis Narens and R. Duncan Luce, "Measurement, Theory Of" (June 1985).
35. D.D. Hoffman and B.M. Bennett, "Visual Representations: Meaning and Truth Conditions" (July 1985).
36. W. C. Watt, "Vestiges of a Ugaritian Phonological Matrix Embodied in the English Alphabet" (October 1985).
37. Vladimir A. Lefebvre, Victorina D. Lefebvre and Jack Adams-Webber, "Modeling an Experiment on Construing Self and Others" (January 1986).
38. W. C. Watt, "Canons of Alphabetic Change" (February 1986).
39. Hagit Borer and Kenneth Wexler, "The Maturation of Syntax" (March 1986).
40. W. C. Watt, "Sign and Signifex" (April 1986).
41. Myron L. Braunstein, Donald D. Hoffman, Lionel R. Shapiro, George J. Andersen and Bruce M. Bennett, "Minimum Points and Views for the Recovery of Three-Dimensional Structure" (July 1986).
42. David LaBerge and Janice A. Lawry, "Focal Attention in the Identification of Words by Whole and by Parts" (September 1986).
43. David LaBerge and Vincent Brown, "Theory and Measurement of Attentional Operations In Shape Identification" (December 1986)
44. Kimberly A. Jameson, Louis Narens, Keith Goldfarb and Thomas O. Nelson, "The Influence of Subthreshold Priming on Metamemory and Recall" (February, 1987).
45. W.C. Watt, "The Ras Shamra Matrix as a Record of Ancient Phonological Perceptions" (August 1987). (Revised: The Ras Shamra Matrix - March 1988).
46. Myron L. Braunstein, Lionel R. Shapiro, Donald D. Hoffman, Bruce M. Bennett, "Minimum Points and Views for the Detection of Rigid Structures" (October 1987).
47. Edward H. Matthei, "Crossing Boundaries: More Evidence for Phonological Constraints on Early Multi-Word Utterances" (November 1987).
48. A. Kimball Romney, "Quantitative Models, Science and Cumulative Knowledge" (June 1988).

49. W.C. Watt, "Getting Writing Right" (October 1988).
50. W.C. Watt, "666" (February 1989).
51. Myron L. Braunstein, Donald D. Hoffman, Frank E. Pollick,
"Discriminating Rigid from Nonrigid Motion (July 1989).

OFFICE OF NAVAL RESEARCH PERCEPTUAL SCIENCE PROGRAM

Technical Reports Distribution List

Dr. Earl A. Alluisi
OUSD (A)/R&A(E&LS)
Pentagon 3D129
Washington, DC 20301-3080

Dr. Gary Aston-Jones
New York University
Department of Biology
Washington Sq Ctr for NS
New York, NY 10003

Dr. Michael Athans
M. I. T.
Lab for Information and
Decision Systems
Cambridge, MA 02139

Dr. Christopher G. Atkeson
M. I. T.
Artificial Intelligence Lab
545 Technology Square
Cambridge, MA 02139

Dr. Alan D. Baddeley
Director, Appl. Psychol. Unit
Medical Research Council
15 Chaucer Road
Cambridge CB2 2EF
ENGLAND

Prof. James A. Ballas
Department of Psychology
George Mason University
4400 University Drive
Fairfax, VA 22030

Dr. Bruce Barnes
Program Director, Div. Info
National Science Foundation
1800 G Street, N.W.
Washington, DC 20550

Mr. Charles Bates
Director, HE Division
USAF AAMRL/HE
WPAFB, OH 45433

Mr. Norman Beck
Naval Underwater Systems Center
Combat Control Systems Dept
Code 221
Newport, RI 02840

Dr. Emilio Bizzi
M. I. T.
Whitaker College
Cambridge, MA 02139

Dr. Kenneth R. Boff
AAMRL/HL
WPAFB, OH 45433

Mr. Luiz Cabral
Naval Underwater Sys. Ctr.
Bldg. 1171/1
Newport, RI 02841

Cdr. Robert C. Carter, USN
Naval Research Laboratory
Code 5532
Washington, DC 20375-5000

Dr. David Castanon
Alphatech, Inc.
111 Middlesex Turnpike
Burlington, MA 01803

Dr. Marvin S. Cohen
Dec. Sci Consortium, Inc.
1895 Preston White Drive
Suite 300
Reston, VA 22091

Dr. Stanley C. Collyer
Office of Naval Technology
Code 222
800 N. Quincy Street
Arlington, VA 22217-5000

Defense Tech. Info. Center
Cameron Station, Bldg 5
Alexandria, VA 22314
(2 copies)

2.

Prof. Jay Elkerton
University of Michigan
Dept. of I & O Engineering
Center for Ergonomics
1205 Beal Avenue
Ann Arbor, MI 48109-2117

Dr. Robert A. Fleming
Naval Ocean Systems Center
Human Factors Support Grp.
1411 South Fern Street
Arlington, VA 22202-2896

Dr. Alfred R. Fregly
AF Office of Sci. Res.
Life Sciences Directorate
Bldg. 410
Bolling AFB, DC 20332-6448

Dr. Jaocuin Fuster
Univ of Calif - Los Angeles
School of Medicine
760 Westwood Plaza
Los Angeles, CA 90024

Dr. Sherman Gee
Office of Naval Technology
Command & Control Technol.
Code 221
800 N. Quincy Street
Arlington, VA 22217-5000

Dr. Apostolos P. Georgopoulos
Johns Hopkins University
School of Medicine
Department of Neuroscience
Baltimore, MD 21205

Dr. Donald A. Glaser
Univ of California
Dept of Molecular Biology
Berkeley, CA 94720

Mr. Dan Greenwood
Netrologic, Inc.
5080 Shoreham Place
Suite 201
San Diego, CA 92122

Jeffrey Grossman
Naval Ocean Systems Center
Code 4403
Bldg. 334
San Diego, CA 92152-6800

Dr. Thomas E. Hanna
Naval Sub Med Res Lab
Behavioral Sciences Dept
Naval Submarine Base
Groton, CT 06349-5900

Mr. Paul Heckman
Naval Ocean Systems Center
San Diego, CA 92152

Dr. Steven Hillyard
Univ of Calif - San Diego
Department of Neuroscience
La Jolla, CA 92093

Dr. Susan Hockfield
Yale University
School of Medicine
333 Cedar Street
New Haven, CT 06510

Prof. Donald D. Hoffman
U. of California - Irvine
School of Social Sciences
Irvine, CA 92717

Prof. Robin Hogarth
University of Chicago
Grad. School of Business
1101 E. 58th Street
Chicago, IL 60637

Dr. John M. Hollerbach
M. I. T.
Artificial Intelligence Lab
545 Technology Square
Cambridge, MA 02139

Prof. James H. Howard, Jr.
Department of Psychology
Human Performance Lab
Catholic University
Washington, DC 20064

3.

Prof. Robert A. Hummel
New York University
Courant Institute of
Mathematical Sciences
251 Mercer Street
New York, NY 10012

Prof. Douglas E. Hunter
Defense Intelligence College
Washington, DC 20374

Dr. Bonnie E. John
Dept. of Computer Science
Carnegie-Mellon University
Pittsburgh, PA 15213

Dr. Edgar M. Johnson
Technical Director
US Army Research Institute
5001 Eisenhower Avenue
Alexandria, VA 22333-5600

Dr. William B. Johnson
Search Technology, Inc.
4725 Peachtree Corners Circle
Suite 200
Norcross, GA 30092

Capt T. E. Jones, MSC, USN
Aviation Medicine & Human
Performance (Code 404)
Naval Medical R & D Cmd
National Capital Region
Bethesda, MD 21814-5044

Dr. Michael Kaplan,
Director, Office Basic Res
US Army Research Institute
5001 Eisenhower Avenue
Alexandria, VA 22333-5600

Dr. Milton S. Katz
US Army Research Institute
ARIESCO
Box 65
FPO, NY 09510-1500

Dr. Steven W. Keele
University of Oregon
Department of Psychology
Eugene, OR 97403-1219

Dr. J. A. Scott Kelso
Florida Atlantic University
Center for Complex Systems
P. O. Box 3091
Boca Raton, FL 33421-0991

Prof. Roberta Klatzky
Department of Psychology
U. of Calif.-Santa Barbara
Santa Barbara, CA 93106

Prof. David L. Kleinman
Electrical Engineering &
Computer Science Dept.
University of Connecticut
Storrs, CT 06268

Dr. Christof Koch
Calif Inst of Technology
Division of Biology
Pasadena, CA 91125

Dr. Arthur F. Kramer
Department of Psychology
University of Illinois
Champaign, IL 61820

Mr. Keith Kramer
Naval Research Laboratory
Code 5532
Washington, DC 20375-5000

Dr. Robert H. LaMotte
Yale University
School of Medicine
333 Cedar Street
New Haven, CT 06510

Dr. David Le Berge
U. of California - Irvine
Cognitive Sciences Dept.
Irvine, CA 92717

Prof. John Lehoczky
Department of Statistics
Carnegie-Mellon University
Pittsburgh, PA 15213

Mr. I. Lemaire
Naval Ocean Systems Center
Code 09
Engrg. & Computer Science
San Diego, CA 92152

4.

Prof. Alexander Levis
Massachusetts Institute
of Technology
Laboratory of Information
& Decision Systems
Cambridge, MA 02139

Prof. Gregory R. Lockhead
Department of Psychology
Duke University
Durham, NC 27706

Dr. Richard Loutitt
National Science Foundation
Division of Behavioral &
Neural Sciences
1800 G Street, N. W.
Washington, DC 20550

Dr. Robert A. Lufti
Waisman Center
University of Wisconsin
Madison, WI 53706

Dr. John H. R. Maunsell
University of Rochester
Strong Sch of Med & Dent
Box 642
Rochester, NY 14642

Dr. John C. Middlebrooks
University of Florida
Dept. of Neuroscience
Box J-J44, JHMHC
Gainesville, FL 82610

Mr. Harold G. Miller
Technical Director, War
Gaming Department
Naval War College
Newport, RI 02841

Capt. William Moroney, USN
Naval Air Development Ctr.
Code 602
Warminster, PA 18974

Dean of the Academic Dept.
U. S. Naval Academy
Annapolis, MD 21402-5018

Naval Aerospace Medical
Research Laboratory
Sensory Division Code 23
Pensacola, FL 32508

Commanding Officer
Naval Air Systems Command
Crew Station Design
NAVAIR 5313
Washington, DC 20361

Commanding Officer
Naval Biodynamics Lab
Michoud Station
Box 29407
New Orleans, LA 70189

Commanding Officer
Navy Health Research Ctr.
P.O. Box 85122
San Diego, CA 92138

Commanding Officer
Navy Personnel R&D Center
San Diego, CA 92152-6800

Director
Technical Information Div.
Code 2627
Naval Research Laboratory
Washington, DC 20375-5000

US Naval Test Center
Aircrew Systems Branch
Systems Engineering Test
Directorate
Patuxent River, MD 20670

Commanding Officer
Naval Weapons Center
Human Factors Branch
Code 3152
China Lake, CA 93555

Dr. Allen Newell
Dept. of Computer Science
Carnegie-Mellon University
Schenley Park
Pittsburgh, PA 15213

5.

Dr. David Noble
Engineering Res. Associates
8616 Westwood Center Drive
McLean, VA 22180

Dr. Michael Letsky
Office of the Chief of
Naval Operations
OP-01B7
Washington, DC 20350

Office of the Chief of
Naval Operations
OP-933D3
Washington, DC 20350-2000

Office of Naval Research
Special Asst. for Marine
Corps Matters
Code 00MC
800 N. Quincy Street
Arlington, VA 22217-5000

Office of Naval Research
Perceptual Science Program
Code 1142PS
800 N. Quincy Street
Arlington, VA 22217-5000
(3 copies)

Dr. Jesse Orlansky
Inst. for Defense Analyses
1801 N. Beauregard Street
Alexandria, VA 22311

Lt. Dennis McBride, USN
Pacific Missile Test Center
Human Factors Branch
Pt. Mugu, CA 93042

Dr. Howard E. Paschler
Univ of Calif - San Diego
Psychology Department
La Jolla, CA 92093-0001

Prof. John W. Payne
Fuqua School of Business
Ctr. for Decision Studies
Duke University
Durham, NC 27706

Dr. Richard Pew
BBN Laboratories, Inc.
Experimental Psychol. Dept.
70 Fawcett Street
Cambridge, MA 02238

Prof. Tomaso Poggio
Massachusetts Institute
of Technology
Center for Biological
Information Processing
Cambridge, MA 02139

Dr. Michael I. Posner
Washington University
Medical Center
St. Louis, MO 63130

Dr. W. A. Rizzo
Head, Human Factors Div.
Naval Training Systems Ctr
12350 Research Parkway
Orlando, FL 32826-3224

Prof. Scott Robertson
Department of Psychology
Rutgers University
Busch Campus
New Brunswick, NJ 08903

Dr. Lawrence A. Rothblat
George Washington University
Department of Psychology
Rice Hall, 6th Floor
Washington, DC 20052

Dr. William B. Rouse
Search Technology, Inc.
4725 Peachtree Corners Circle
Suite 200
Norcross, GA 30092

Dr. Walter Schneider
University of Pittsburgh
LRDC Bldg.
3939 O'Hara Street
Pittsburgh, PA 15260

Prof. Thomas B. Sheridan
Massachusetts Institute of
Technology
Dept. of Mechanical Engrg.
Cambridge, MA 02139

6.

Dr. Gordon L. Shulman
Department of Neurology
Wash Univ Schl of Medicine
Box 8111
St. Louis, MO 63110

Dr. Randall P. Shumaker
Naval Research Laboratory
Code 5510
US Navy Center for ARAI
Washington, DC 20375-5000

Prof. James A. Simmons
Department of Psychology
Brown University
Providence, RI 02912

Dr. H. Wallace Sinaiko
Manpower Research &
Advisory Services
Smithsonian Institution
801 N. Pitt St. Suite 120
Alexandria, VA 22314-1713

LCdr. Timothy Singer, USN
Naval Air Development Ctr.
Human Factors Engrg. Div.
Warminster, PA 18974

Dr. Paul Slovic
Decision Research, Inc.
1201 Oak Street
Eugene, OR 97401

Dr. Dana L. Small
Naval Ocean Systems Ctr.
Code 33
San Diego, CA 92152-5000

Mr. James G. Smith
Office of Naval Research
Code 121
800 N. Quincy Street
Arlington, VA 22217-5000

Mr. Yale Smith
Rome Air Development Ctr.
RADC/COAD
Griffis AFB, NY 13441-5700

Prof. Harry L. Snyder
Dept of Industrial Engrg.
VPISU
Blacksburg, VA 24061

Capt. Frank Snyder, USN
Naval War College
Operations Department
Newport, RI 02841

Cdr. S. Snyder
Office of Naval Technology
Code 222
800 N. Quincy Street
Arlington, VA 22217-5000

Prof. Michael Sovereign
Naval Postgraduate School
Code 74
Joint C3 Curriculum
Monterey, CA 93943

Mr. Steven L. Speidel
Naval Ocean Systems Ctr
Code 632
San Diego, CA 92152-5000

Dr. George Sperling
New York University
Department of Psychology
6 Washington Place
New York, NY 10003

Mr. Nelson F. Steele
Advanced Res Dev Corp
5457 Twin Knolls Road
Columbia, MD 21035

Prof. Kent A. Stevens
University of Oregon
Dept. of Computer &
Information Sciences
Eugene, OR 97403

Dr. John Tangney
AF Office of Sci. Res.
Life Sciences Directorate
Bldg. 410
Bolling AFB, DC 20332-6448

Prof. Demosthenis Teneketzis
Dept. of Electrical Engrg.
& Computer Science
University of Michigan
Ann Arbor, MI 48109-1109

Dr. James T. Todd
Brandeis University
Psychology Department
Waltham, MA 02254

Dr. Martin A. Tolcott
Decision Science Consortium
1895 Preston White Drive
Suite 300
Reston, VA 22091-4369

Dr. Douglas Towne
U. of Southern California
Behavioral Technology Lab
1845 South Elena Avenue
Fourth Floor
Redondo Beach, CA 90277

Dr. Ronald J. Tusa
Johns Hopkins University
Neurology Department
34th & Charles Place
Baltimore, MD 21218

Dr. Amos Tversky
Stanford University
Dept. of Psychology
Bldg. 420
Stanford, CA 94305

Prof. William R. Uttal
Department of Psychology
Arizona State University
Tempe, AZ 85287-1104

Dr. Harold P. Van Cott
Committee on Human Factors
NAS-National Res. Council
2101 Constitution Ave, N.W.
Washington, DC 20418

Dr. David C. Van Essen
Calif Inst of Technology
Biology Division
1201 E. California Blvd.
Pasadena, CA 91125

Dr. Charles S. Weaver
MAXIM Technologies, Inc.
3000 Patrick Henry Drive
Santa Clara, CA 95054

Dr. John Weisz
Technical Director
US Army Human Engineering
Laboratory
Aberdeen P. G., MD 21005

Dr. Elizabeth M. Wenzel
NASA-Ames Research Center
MS # 239-3
Moffett Field, CA 94035

Dr. Robert Wherry
Analytics, Inc.
2500 Maryland Road
Willow Grove, PA 19090

Dr. Milton A. Whitcomb
NAS-National Res. Council
CHABA
2101 Constitution Ave., N.W.
Washington, DC 20418

Prof. Christopher D. Wickens
Department of Psychology
University of Illinois
Champaign, IL 61801

Dr. Diane Williams
Naval Ocean Systems Ctr
Code 4403
Bldg. 334
San Diego, CA 92152-6800

Dr. Dana Yoerger
Woods Hole Oceanographic
Institution
Woods Hole, MA 02543

Dr. Wayne Zachary
CHI Systems, Inc.
Gwynedd Plaza III
Bethlehem Pike
Spring House, PA 19477