



TR-0294

DTIC

JUL 08 1991

AD

Reports Control Symbol
OSD - 1366

2



AD-A237 624



XTRAN: AN ATMOSPHERIC TRANSMITTANCE CODE
BASED ON XSCALE

April 1991

Ricardo Peña



Approved for public release; distribution unlimited.

US ARMY

LABORATORY COMMAND

91-04093



ATMOSPHERIC SCIENCES LABORATORY
White Sands Missile Range, NM 88002-5501

0

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

Destruction Notice

When this document is no longer needed, destroy it by any method that will prevent disclosure of its contents or reconstruction of the document.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE April 1991	3. REPORT TYPE AND DATES COVERED Final		
4. TITLE AND SUBTITLE XTRAN: AN ATMOSPHERIC TRANSMITTANCE CODE BASED ON XSCALE		5. FUNDING NUMBERS TA 62784AH71		
6. AUTHOR(S) Ricardo Peña				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Atmospheric Sciences Laboratory White Sands Missile Range, NM 88002-5501		8. PERFORMING ORGANIZATION REPORT NUMBER ASL-TR-0294		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Laboratory Command Adelphi, MD 20783-1145		10. SPONSORING/MONITORING AGENCY REPORT NUMBER		
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited		12b. DISTRIBUTION CODE		
13. ABSTRACT (Maximum 200 words) Several Electro-Optical Systems Atmospheric Effects Library modules require the use of XSCALE for calculation of the natural atmospheric transmittance value. XSCALE is a large (over 1600 lines of code) algorithm, which, in some cases, requires other external modules or data files for execution. XTRAN, a comparatively smaller (less than 240 lines) computer code, was developed for use with the KWIK (crosswind integrated concentration) munition expenditure stand-alone versions (SKWIK and IKWIK). XTRAN computes horizontal extinction and transmittance values based on the XSCALE module for visible, near-, mid-, and far-infrared wavelengths by using estimated values of visibility and polynomial regression equations for aerosol extinction as a function of relative humidity. This report shows the usefulness and practicality of the XTRAN code as a horizontal transmittance model.				
14. SUBJECT TERMS atmospheric transmittance, visibility, relative humidity, extinction coefficients, contrast threshold, aerosol		15. NUMBER OF PAGES 33		
		16. PRICE CODE		
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

ACKNOWLEDGMENT

The author acknowledges Dr. Robert Fiegel's assistance in producing XSCALE data for comparison with XTRAN results.

Accession For	
DTIC SPAN	☒
DTIC Tab	☐
Unannounced	☐
Justification	
By	
Distribution	
Availability Codes	
Dist	Avail and/or Special
H-1	

CONTENTS

LIST OF TABLES	6
1. INTRODUCTION	7
2. VISIBILITY AND CONTRAST THRESHOLD VALUES	7
3. EXTINCTION COEFFICIENTS	3
4. TRANSMITTANCE COMPARATIVE CALCULATIONS: XSCALE VERSUS XTRAN	9
5. MUNITION EXPENDITURES CALCULATIONS: SKWIK VERSUS EOSAEL KWIK	11
6. CONCLUSION	14
LITERATURE CITED	15
APPENDIX A. EXTINCTION DATA FOR MARITIME, URBAN, AND RURAL AEROSOLS ..	17
APPENDIX B. EXTINCTION DATA FOR FOG ONE (HEAVY ADVECTION) AND FOG TWO (MODERATE ADVECTION) AEROSOL	21
APPENDIX C. EXTINCTION CALCULATIONS FOR RAIN, FALLING AND BLOWING SNOW	23
APPENDIX D. XTRAN COMPUTER SOURCE CODE IN FORTRAN 77	25
DISTRIBUTION LIST	33

LIST OF TABLES

1. Comparative Transmittance Values Between XSCALE and XTRAN	10
2. Actual and Percent Differences in Munition Expenditures Between SKWIK and KWIK Calculations for Maritime Aerosol	12
3. Actual and Percent Difference in Munition Expenditures Between SKWIK and KWIK Calculations for Urban Aerosol	13
4. Actual and Percent Difference in Munition Expenditures Between SKWIK and KWIK Calculations for Rural Aerosol	14

1. INTRODUCTION

The KWIK (crosswind integrated concentration) smoke munition expenditures algorithm (Peña, 1987) and other models, such as LOWTRAN (Pierluissi et al., 1987) and TARGAC (Davis, 1987), use the natural aerosol transmittance data from the EOSAEL (Electro-Optical Systems Atmospheric Effects Library) module XSCALE (Duncan et al., 1987) for wavelengths of 0.2 to 12.5 μm .

The XTRAN algorithm has been developed in an effort to minimize the amount of computer code that is required to calculate horizontal atmospheric transmittance values. XTRAN contains about 240 lines of FORTRAN 77 code (about one-eighth the size of XSCALE) and computes horizontal extinction and transmittance values for the following adverse weather conditions.

- Haze/fog maritime (arctic and polar) air mass
- Haze/fog urban air mass
- Haze/fog rural (continental polar) air mass
- Fog one (heavy advection)
- Fog two (moderate advection)
- Rain (drizzle)
- Rain (widespread)
- Rain (thunderstorm)
- Snow (falling or blowing) for relative humidity (RH) less than 95 percent only

XTRAN uses estimated values of visibility coupled with polynomial regression analysis for natural aerosol extinction as a function of RH to calculate the horizontal atmospheric transmission through a smoke cloud. The polynomial regression equations are obtained by using aerosol extinction coefficients from the RHDATA file from XSCALE. The code for fog one, fog two, rain (drizzle, widespread, and thunderstorm), and snow is taken from XSCALE. XTRAN's only limitation is its exclusion of snow at greater than 95 percent RH and ice fog condition.

XTRAN is used in SKWIK (a short version of the EOSAEL KWIK model) and IKWIK (inverse KWIK tactical decision aid). Peña (1991) describes the latest personal computer (PC) versions of EOSAEL KWIK, SKWIK, and IKWIK. This report presents the results of a comparative study of the effects of using XTRAN versus XSCALE transmittance data with the KWIK model.

2. VISIBILITY AND CONTRAST THRESHOLD VALUES

Two terms that are widely used together with "visibility" are visual range and meteorological range. All three terms are often used interchangeably; but according to McCartney (1976), visual range is the more useful quantity because it allows for a target/background contrast of less than unity and/or a threshold contrast of more than 2 percent.

Visual range* is defined as

$$R_v = \frac{1}{K_e} \ln \frac{C}{\epsilon} \quad (1)$$

*In this report, the term "visibility" will be used interchangeably with visual range.

where K_e is the extinction coefficient in the visual wavelength band, C is the inherent target contrast against a background (considered to be unity where a black target is against the background), and c is the constant threshold value.

During the Smoke Week VII trials, where live-fired smoke munitions were used, LOVIR (low visibility infrared) transmissometry data were compared with corresponding results from the PRESTO (personal evaluation system for target obscuration) system. Peña (1986) showed that these results indicate that the threshold contrast value was approximately 0.10 for visible and near-infrared wavelengths and 0.05 for mid- and far-infrared wavelengths.

Restating equation (1) for visible and near-infrared wavelengths,

$$R_v = \frac{1}{K_e} \ln \frac{1}{0.10} \quad (2)$$

or

$$K_e = \frac{2.303}{R_v} \quad (3)$$

For mid- and far-infrared wavelengths the extinction coefficient becomes

$$K_e = \frac{3.00}{R_v} \quad (4)$$

3. EXTINCTION COEFFICIENTS

Lower atmospheric aerosol particle sizes are a function of air mass as well as RH. These particles, however, grow with increasing RH. The XSCALE module (Duncan et al., 1987) uses Mie theory to calculate atmospheric absorption and extinction coefficients. The results, found in the RHDATA file, are tabulated for eight RH levels (0, 50, 70, 80, 90, 95, 98, and 99 percent) and 31 wavelengths, ranging from 0.2 to 12.5 μm , for each RH level.

Equations (3) and (4) were modified as follows for visible (0.55 μm) and near-infrared (1.06 μm) and for mid- (3.75 μm) and far-infrared (10.6 μm) wavelengths, respectively.

$$K_e = \frac{2.3}{R_v} K_t \quad (5)$$

$$K_e = \frac{3.00}{R_v} K_t \quad (6)$$

K_t is the corresponding extinction value from the RHDATA file (see appendix A) for the particular aerosol, wavelength, and RH value.

Regression analysis techniques were applied to the K_e extinction values (see appendix A tables A-1 through A-9) for near-, mid-, and far-infrared wavelengths, six RH values (0, 50, 70, 80, 90, and 95 percent) and four values

of visibility (2.3, 10, 20, and 30 km). This technique produced a series of four equations per wavelength band and aerosol type (see appendix C, sub-routine XTRAN) of the form

$$K_{ext} = A + B(RH) + C(RH)^2 + D(RH)^3 \dots \quad (7)$$

Appendix B shows the procedure used to obtain the extinction coefficients for fog one and fog two for 2.3, 10, 20, and 30 km visibility.

Appendix C presents the rain and snow extinction coefficients. Note that the calculations for falling and blowing snow are valid only for RH less than 95 percent.

Appendix D shows the FORTRAN 77 source code for the XTRAN algorithm containing all regression equations and calculations for transmittance.

4. TRANSMITTANCE COMPARATIVE CALCULATIONS: XSCALE VERSUS XTRAN

Comparative calculations of transmittance values using XSCALE and XTRAN were performed on identical meteorological data (line-of-sight visibility, RH, windspeed, temperature, and horizontal slant range) for maritime, urban, and rural aerosol. The visibility values used with XSCALE were 1.5, 10, 15, 20, and 25 km. XTRAN used visibilities of 2.3, 10, 20, and 30 km (see table 1). The XTRAN values of 2.3, 20, and 30 km were used instead of 1.5, 15, and 25 km, in order to determine the sensitivity of visibility estimates used in calculating transmittance values.

Table 1 shows the comparative calculations of maritime, urban, and rural aerosol transmittance values for visible, near-, mid-, and far-infrared wavelengths. Horizontal slant ranges of 1.0 and 2.0 km were used in all three aerosol calculations. The numbers in parentheses for visibility represent the values used by the XTRAN algorithm. In the same manner, the transmittance values calculated by XTRAN are also shown in parentheses. The visible transmittance column in table 1 shows only one set of numbers because there was no difference between the XSCALE and XTRAN calculations for this wavelength.

Since XSCALE uses the threshold contrast value of 0.02 for all wavelengths and XTRAN (and also KWIK) uses 0.10 for visible and near-infrared and 0.05 for mid- and far-infrared wavelengths (as explained above), it was necessary to apply an adjustment factor to the XSCALE transmittance values to make them comparable to the XTRAN calculated values. The following relationships were used.

For visible and near-infrared wavelengths

$$T_{vn} = (T_{xscale})^{0.5887} \quad (8)$$

and for mid- and far-infrared wavelengths

$$T_{mf} = (T_{xscale})^{0.76577} \quad (9)$$

where T_{xscale} is the transmittance value calculated by XSCALE for a particular wavelength. The transmittance values calculated by XTRAN for all wavelengths and air masses were derived from the following general expression

$$T = \exp \left[-(S_{\text{rang}} K_e) \right] \quad (10)$$

where S_{rang} is the horizontal slant range in kilometers.

TABLE 1. COMPARATIVE TRANSMITTANCE VALUES BETWEEN XSCALE AND XTRAN

<u>Maritime Aerosol</u>					
Visibility (km)	SRNG (km)	Visible	Near IR	Mid IR	Far IR
1.5 (2.3) *	1.0	.215	.330 (.485) *	.538 (.669) *	.842 (.894) *
10. (10.)	1.0	.794	.846 (.848)	.911 (.908)	.974 (.980)
15. (20.)	2.0	.736	.764 (.825)	.789 (.860)	.940 (.988)
20. (20.)	2.0	.794	.817 (.825)	.837 (.860)	.955 (.988)
25. (30.)	2.0	.832	.850 (.817)	.857 (.864)	.958 (.986)
<u>Urban Aerosol</u>					
1.5 (2.3)	1.0	.215	.486 (.620)	.756 (.830)	.835 (.894)
10. (10.)	1.0	.794	.897 (.896)	.959 (.959)	.973 (.974)
15. (20.)	2.0	.736	.868 (.894)	.947 (.958)	.968 (.976)
20. (20.)	2.0	.794	.899 (.894)	.960 (.958)	.976 (.976)
25. (30.)	2.0	.832	.917 (.927)	.968 (.972)	.982 (.984)
<u>Rural Aerosol</u>					
1.5 (2.3)	1.0	.215	.524 (.654)	.819 (.873)	.852 (.897)
10. (10.)	1.0	.794	.908 (.905)	.970 (.967)	.976 (.976)
15. (20.)	2.0	.736	.876 (.901)	.955 (.963)	.970 (.976)
20. (20.)	2.0	.794	.905 (.901)	.966 (.963)	.977 (.976)
25. (30.)	2.0	.823	.922 (.932)	.937 (.974)	.983 (.984)

*NOTE: XTRAN visibility and transmittance values are shown in parentheses.

5. MUNITION EXPENDITURES COMPARATIVE CALCULATIONS: SKWIK VERSUS EOSAEL KWIK

A second comparison test that was run is shown in tables 2, 3, and 4. These tables show the actual and percent difference in munition expenditures of a series of calculations using identical input data for SKWIK and EOSAEL KWIK for maritime, urban, and rural aerosols. The XTRAN subroutine in SKWIK used 2.3, 10, 20, and 30 km approximations for actual visibility, as shown in these tables. The tables also show positive digits to indicate cases where the number of rounds calculated by SKWIK were in excess (overprediction) of the EOSAEL KWIK calculations and negative digits to indicate the cases where SKWIK underpredicted EOSAEL KWIK. A zero was used to indicate no difference between the computed values. The results are also presented, respectively, as plus, minus, or zero percent difference.

The "worst" case produced by these comparative calculations occurred with maritime aerosol (see table 2), where the SKWIK overprediction was between two and seven rounds (5.0 and 5.3 percent). However, 19 cases out of 24 (79 percent) showed no difference. Table 3 (urban aerosol) showed four cases of two-round overprediction and a total average difference of 1.2 percent (83 percent of the cases showed no difference). Table 4 (rural aerosol) indicated a total average difference (overprediction) of 1.1 percent. However, the maximum overprediction is only two rounds (4.5 percent to 16.6 percent), and 88 percent of the cases were in perfect agreement.

Note that the best agreement in tables 2, 3, and 4 lies in the visible region (perfect agreement) and in the near-infrared wavelengths, where the KWIK model has demonstrated its best munition prediction capabilities. Also, note that most of the differences occur with the lower visibility estimates (1.5 and 6.0 km) but visibilities over 14 km (for urban aerosol) or 24 km (for maritime and rural aerosols) show less sensitivity to visibility estimates. Overall, XTRAN does a very good job, as verified by the data in tables 1, 2, 3, and 4, of estimating the transmittance values used in SKWIK to determine munition expenditures.

TABLE 2. ACTUAL AND PERCENT DIFFERENCE IN MUNITION EXPENDITURES
BETWEEN SKWIK AND KWIK CALCULATIONS FOR MARITIME AEROSOL

	Visible	Near IR	Mid IR	Far IR
Visibility = 1.5 km (estimated as 2.3 km)				
Rounds Diff. :	0	0	+2	+2
Percent Diff.:	0	0	5.0	5.3
Visibility = 6 km (estimated as 10 km)				
Rounds Diff. :	0	0	0	+2
Percent Diff.:	0	0	0	4.3
Visibility = 14 km (estimated as 10 km)				
Rounds Diff. :	0	0	-2	0
Percent Diff.:	0	0	-3.6	0
Visibility = 15 km (estimated as 20 km)				
Rounds Diff. :	0	0	+7	0
Percent Diff.:	0	0	5.1	0
Visibility = 24 km (estimated as 20 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 25 km (estimated as 30 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0

TOTAL AVERAGE DIFFERENCE = 0.67%

TABLE 3. ACTUAL AND PERCENT DIFFERENCE IN MUNITION EXPENDITURES
BETWEEN SKWIK AND KWIK CALCULATIONS FOR URBAN AEROSOL

	Visible	Near IR	Mid IR	Far IR
Visibility = 1.5 km (estimated as 2.3 km)				
Rounds Diff. :	0	+2	+2	+2
Percent Diff.:	0	14.3	4.3	5.0
Visibility = 6 km (estimated as 10 km)				
Rounds Diff. :	0	0	0	+2
Percent Diff.:	0	0	0	4.2
Visibility = 14 km (estimated as 10 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 15 km (estimated as 20 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 24 km (estimated as 20 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 25 km (estimated as 30 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0

TOTAL AVERAGE DIFFERENCE = 1.2%

TABLE 4. ACTUAL AND PERCENT DIFFERENCE IN MUNITION EXPENDITURES BETWEEN SKWIK AND KWIK CALCULATIONS FOR RURAL AEROSOL

	Visible	Near IR	Mid IR	Far IR
Visibility = 1.5 km (estimated as 2.3 km)				
Rounds Diff. :	0	+2	+2	+2
Percent Diff.:	0	16.6	4.5	5.3
Visibility = 6 km (estimated as 10 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 14 km (estimated as 10 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 15 km (estimated as 20 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 24 km (estimated as 20 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0
Visibility = 25 km (estimated as 30 km)				
Rounds Diff. :	0	0	0	0
Percent Diff.:	0	0	0	0

TOTAL AVERAGE DIFFERENCE = 1.1%

6. CONCLUSION

The data presented here show that the XTRAN algorithm can be used with very good accuracy to compute extinction and transmittance values for maritime, urban, and rural aerosols, as well as rain and some snow conditions. The main advantage of XTRAN lies in its practical usefulness because of its size (one-eighth the size of XSCALE) and rapid execution.

LITERATURE CITED

- Davis, J. M., 1987, EOSAEL 87, Volume 29, Target Acquisition Model, TARGAC, ASL-TR-0221-29, U.S. Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM.
- Duncan, L. D., M. A. Seagraves, and M. G. Heaps, 1987, EOSAEL 87, Volume 7, Natural Aerosol Extinction Module XSCALE, ASL-TR-0221-7, U.S. Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM.
- McCartney, E. J., 1976, Optics of the Atmosphere, John Wiley and Sons, Incorporated, NY.
- Peña, Ricardo, 1986, Smoke Munition Expenditures: FM 6-40 Versus KWIK Model, ASL-TR-0206, U.S. Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM.
- Peña, R., 1987, EOSAEL 87, Volume 13, A Munition Expenditures Model, KWIK, ASL-TR-0221-13, U.S. Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM.
- Peña, R., 1991, PC Versions of the KWIK Munition Expenditures Model, ASL-TMR-0006, U.S. Army Atmospheric Sciences Laboratory, White Sands Missile Range, NM.
- Pierluissi, J. H., and C. E. Maragoudakis, 1987, EOSAEL 87, Volume 14, Atmospheric Transmittance/Radiance Module LOWTRAN, ASL-TR-0221-14, U.S. Army Sciences Laboratory, White Sands Missile Range, NM.

APPENDIX A. EXTINCTION DATA FOR MARITIME, URBAN, AND RURAL AEROSOLS

1. VISIBLE WAVELENGTH DATA FOR ALL AEROSOL

Visible ($0.55 \mu\text{m}$) extinction data for all air masses for a threshold contrast of 0.10 and visibilities of 2.3, 10, 20, and 30 km is given by equation (5) in the text, and may be restated as

$$K_v = \frac{2.3}{\text{Vis}} K_t \quad (\text{A-1})$$

where K_v is the extinction coefficient for a particular wavelength and visual range Vis, and K_t is the factor for scaling extinction at $0.55 \mu\text{m}$ to extinction at a particular wavelength. K_t values are taken from the RHDATA file and normalized to 1.0000 for visible wavelengths.

Therefore, the extinction coefficients for all aerosols at visible wavelengths ($K_t = 1.0000$) and for 2.3, 10, 20, and 30 km visibility (Vis), respectively, is

$$K_{2.3} = 1.0000 \quad (\text{A-2})$$

$$K_{10} = 0.2300 \quad (\text{A-3})$$

$$K_{20} = 0.1150 \quad (\text{A-4})$$

$$K_{30} = 0.0766 \quad (\text{A-5})$$

2. MARITIME AEROSOL

The following K_v extinction relationships are given for maritime aerosol at near- ($1.06 \mu\text{m}$), mid- ($3.75 \mu\text{m}$), and far-infrared ($10.6 \mu\text{m}$) wavelengths, respectively.

For near-infrared wavelengths and 0.10 threshold contrast value the K_v relationship for maritime aerosol is given by equation (A-1).

For mid- and far-infrared wavelengths and 0.05 threshold contrast value:

$$K_v = \frac{3.00}{\text{Vis}} K_t \quad (\text{A-6})$$

Equations (A-1) and (A-6) were used with the K_t values from the RHDATA file to produce the extinction coefficients for Vis (visibility) values of 2.3, 10, 20, and 30 km. Tables A-1, A-2, and A-3 show maritime aerosol extinction coefficients for the above visibilities at an RH range of 0 to 95 percent for near-, mid-, and far-infrared wavelengths, respectively. Tables A-4, A-5, and A-6 (for urban aerosol) and tables A-7, A-8, and A-9 (for rural aerosol) contain the same type of extinction data as tables A-1, A-2, and A-3.

TABLE A-1. MARITIME AEROSOL EXTINCTION DATA FOR NEAR-INFRARED WAVELENGTHS AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE

RH	K2.3	K10	K20	K30
0	0.70297	0.16168	0.08084	0.05385
50	0.72355	0.16642	0.08321	0.05542
70	0.77089	0.17730	0.08865	0.05905
80	0.87538	0.20134	0.10069	0.06705
90	0.88017	0.20244	0.10122	0.06742
95	0.90693	0.20859	0.10430	0.06947

TABLE A-2. MARITIME AEROSOL EXTINCTION DATA FOR MID-INFRARED WAVELENGTHS AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE

RH	K2.3	K10	K20	K30
0	0.37450	0.08643	0.04321	0.02881
50	0.40370	0.09316	0.04658	0.03105
70	0.49499	0.11423	0.05711	0.03808
80	0.77029	0.17780	0.08888	0.05925
90	0.84009	0.19387	0.09693	0.06462
95	0.95605	0.22063	0.11031	0.07354

TABLE A-3. MARITIME AEROSOL EXTINCTION DATA FOR FAR-INFRARED WAVELENGTHS AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE

RH	K2.3	K10	K20	K30
0	0.10877	0.02510	0.01255	0.00837
50	0.11214	0.02588	0.01294	0.00863
70	0.12687	0.02928	0.01464	0.00976
80	0.19911	0.04595	0.02297	0.01532
90	0.23153	0.05343	0.02672	0.01781
95	0.28782	0.06642	0.03362	0.02214

**TABLE A-4. URBAN AEROSOL EXTINCTION DATA FOR NEAR-INFRARED WAVELENGTHS
AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE**

RH	K2.3	K10	K20	K30
0	0.47095	0.10832	0.05416	0.03607
50	0.47013	0.10813	0.05406	0.03601
70	0.46639	0.10727	0.05363	0.03573
80	0.46253	0.10638	0.05319	0.03543
90	0.46809	0.10766	0.05383	0.03586
95	0.48350	0.11121	0.05560	0.03704

**TABLE A-5. URBAN AEROSOL EXTINCTION DATA FOR MID-INFRARED WAVELENGTHS
AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE**

RH	K2.3	K10	K20	K30
0	0.18200	0.04200	0.02000	0.01400
50	0.18199	0.04199	0.02100	0.01399
70	0.18266	0.04215	0.02108	0.01405
80	0.17632	0.04069	0.02034	0.01356
90	0.17286	0.03989	0.01995	0.01330
95	0.17585	0.04058	0.02029	0.01353

**TABLE A-6. URBAN AEROSOL EXTINCTION DATA FOR FAR-INFRARED WAVELENGTHS AT
2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE**

RH	K2.3	K10	K20	K30
0	0.11774	0.02717	0.01359	0.00906
50	0.11769	0.02716	0.01358	0.00905
70	0.11495	0.02653	0.01326	0.00884
80	0.10433	0.02408	0.01204	0.00803
90	0.09604	0.02216	0.01108	0.00739
95	0.09387	0.02166	0.01083	0.00722

TABLE A-7. RURAL AEROSOL EXTINCTION DATA FOR NEAR-INFRARED WAVELENGTHS AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE

RH	K2.3	K10	K20	K30
0	0.41943	0.09647	0.04823	0.03213
50	0.42015	0.09663	0.04832	0.03218
70	0.42171	0.09699	0.04850	0.03230
80	0.43228	0.09942	0.04971	0.03311
90	0.44207	0.10168	0.05084	0.03386
95	0.45025	0.10356	0.05178	0.03449

TABLE A-8. RURAL AEROSOL EXTINCTION DATA FOR MID-INFRARED WAVELENGTHS AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGE

RH	K2.3	K10	K20	K30
0	0.12943	0.02987	0.01493	0.00956
50	0.13052	0.03012	0.01506	0.01004
70	0.13420	0.03097	0.01548	0.01032
80	0.14958	0.03452	0.01726	0.01151
90	0.14983	0.03457	0.01729	0.01153
95	0.15072	0.03478	0.01739	0.01159

TABLE A-9. RURAL AEROSOL EXTINCTION DATA FOR FAR-INFRARED WAVELENGTHS AT 2.3, 10, 20, AND 30 KM VISIBILITY FOR 0 TO 95% RH RANGES

RH	K2.3	K10	K20	K30
0	0.10499	0.02423	0.01211	0.00808
50	0.10433	0.02408	0.01204	0.00803
70	0.10351	0.02389	0.01194	0.00796
80	0.10014	0.02311	0.01155	0.00770
90	0.09069	0.02093	0.01046	0.00698
95	0.08732	0.02015	0.01008	0.00672

APPENDIX B. EXTINCTION DATA FOR FOG ONE (HEAVY ADVECTION) AND FOG TWO (MODERATE ADVECTION) AEROSOL

Equations (A-1) and (A-6) in appendix A can also be applied to aerosol fog one and fog two for visible, near-, mid-, and far-infrared wavelengths. Since RH is 100 percent for both of these aerosols, the extinction coefficient from the RHDATA file (K_t) will be the same for all visibility ranges within the same wavelength.

1. VISIBLE WAVELENGTHS

Equations (A-2), (A-3), (A-4) and (A-5) in appendix A also apply for fog one and fog two visible ($0.55 \mu\text{m}$) coefficients for 2.3, 10, 20, and 30 km visibilities.

2. FOG ONE EXTINCTION COEFFICIENTS

The following extinction coefficients for near- ($1.06 \mu\text{m}$), mid- ($3.75 \mu\text{m}$), and far-infrared ($10.6 \mu\text{m}$) wavelengths are for visibilities of 2.3 (K2.3), 10 (K10), 20 (K20), and 30 (K30) km.

2.1 Near-Infrared Wavelengths

The following equations are extinction coefficients for near-infrared wavelengths. Equation (A-1) in appendix A was used to produce the extinction values, with $K_t = 1.01750$.

$$K_{2.3} = 1.01750 \quad (\text{B-1})$$

$$K_{10} = 0.23402 \quad (\text{B-2})$$

$$K_{20} = 0.11701 \quad (\text{B-3})$$

$$K_{30} = 0.07801 \quad (\text{B-4})$$

2.2 Mid-Infrared Wavelengths

The extinction coefficients for these wavelengths were derived from equation (A-6) in appendix A, with $K_t = 1.0780$.

$$K_{2.3} = 1.40609 \quad (\text{B-5})$$

$$K_{10} = 0.32340 \quad (\text{B-6})$$

$$K_{20} = 0.16170 \quad (\text{B-7})$$

$$K_{30} = 0.10780 \quad (\text{B-8})$$

2.3 Far-Infrared Wavelengths

Equation (A-6) in appendix A was used to determine the following extinction coefficients, where $K_t = 1.1559$.

$$K_{2.3} = 1.50770 \quad (B-9)$$

$$K_{10} = 0.34677 \quad (B-10)$$

$$K_{20} = 0.17338 \quad (B-11)$$

$$K_{30} = 0.11559 \quad (B-12)$$

3. FOG TWO EXTINCTION COEFFICIENTS

3.1 Near-Infrared Wavelengths

Using equation (A-1) and $K_t = 1.0518$,

$$K_{2.3} = 1.0518 \quad (B-13)$$

$$K_{10} = 0.03155 \quad (B-14)$$

$$K_{20} = 0.12096 \quad (B-15)$$

$$K_{30} = 0.08064 \quad (B-16)$$

3.2 Mid-Infrared Wavelengths

Using equation (A-6) and $K_t = 1.4527$

$$K_{2.3} = 1.89483 \quad (B-17)$$

$$K_{10} = 0.43581 \quad (B-18)$$

$$K_{20} = 0.21791 \quad (B-19)$$

$$K_{30} = 0.14527 \quad (B-20)$$

3.3 Far-Infrared Wavelengths

Using equation (A-6) and $K_t = 2.1601$,

$$K_{2.3} = 2.81752 \quad (B-21)$$

$$K_{10} = 0.64803 \quad (B-22)$$

$$K_{20} = 0.32402 \quad (B-23)$$

$$K_{30} = 0.21601 \quad (B-24)$$

APPENDIX C. EXTINCTION CALCULATIONS FOR RAIN, FALLING AND BLOWING SNOW

1. RAIN EXTINCTION CALCULATIONS

The average rain rate (RNRT) for the three rain categories is given below.

$$\text{Drizzle: RNRT} = 0.5 \text{ mm/h} \quad (\text{C-1})$$

$$\text{Widespread: RNRT} = 5.0 \text{ mm/h} \quad (\text{C-2})$$

$$\text{Thunderstorm: RNRT} = 25.0 \text{ mm/h} \quad (\text{C-3})$$

Rain extinction coefficients for drizzle (Kdr), widespread (Kwd), and thunderstorm (Kth) are derived as

$$K_{dr} = 0.5089 (\text{RNRT})^{0.63} \quad (\text{C-4})$$

$$K_{wd} = 0.3201 (\text{RNRT})^{0.63} \quad (\text{C-5})$$

$$K_{th} = 0.1635 (\text{RNRT})^{0.63} \quad (\text{C-6})$$

2. FALLING AND BLOWING SNOW EXTINCTION (FOR RH < 95 PERCENT)

2.1 Falling snow (windspeed < 5 m/s)

The snow particle radius (RBAR) is dependent on temperature (TEMP), degrees Celsius, as follows.

$$\text{If } \text{TEMP} \leq -15, \quad \text{RBAR} = 100. \quad (\text{C-7})$$

$$\text{If } -15 < \text{TEMP} < 0, \quad \text{RBAR} = (250. + 10.(\text{TEMP})) \quad (\text{C-8})$$

$$\text{If } 0 \leq \text{TEMP} < 2, \quad \text{RBAR} = (250. + 25.(\text{TEMP})) \quad (\text{C-9})$$

$$\text{If } \text{TEMP} \geq 2, \quad \text{RBAR} = 300. \quad (\text{C-10})$$

2.2 Blowing Snow (Windspeed ≥ 5 m/s)

For blowing snow RBAR is set to 100 cm.

The extinction coefficient for falling or blowing snow (RH < 95 percent) is derived from the following expression.

$$K_{sn} = (\exp(-0.88C) + 1)1.96/\text{Vis} \quad (\text{C-11})$$

where

$$C = 1E - 5(2\pi \text{RBAR})\text{RD}/\text{WAVE}/\text{Vis} \quad (\text{C-12})$$

WAVE is the midband wavelength in micrometers (0.55 μm for visible, 1.06 μm for near-, 3.75 μm for mid-, and 10.6 μm for far-infrared) and Vis is the visibility in kilometers. RD, the detector radius, is set to 10 cm.

APPENDIX D. XTRAN COMPUTER SOURCE CODE IN FORTRAN 77

```

C      MAIN PROGRAM XTRAN.FOR
C      * Designed and developed by Ricardo Pena (Penya) 06/06/90.
C      *** XTRAN is a program designed to calculate the atmospheric transmittance
C      due to natural aerosols using the subroutine XTRAN, which is an abre-
C      viated code based on XSCALE. XTRAN determines the atmospheric extinction
C      coefficient EXT. The elevation angle of target from observer with respect
C      to the horizontal is assumed to be zero.
C
C      ** INPUTS      (ALL REAL VALUES)      FORMAT (10X,6F10.3)
C      KEYWORD        COLS.      VARIABLE      DESCRIPTION:
C      -----
C      DATA          1-4              REQUIRED INPUT DATA
C                      11-20      FOG -    ADVERSE WEATHER SELECTION:
C                                          1. = CORRECT FOR HAZ/FOG MARITIME
C                                          (ARCTIC & POLAR) AIR MASS.
C                                          2. = CORRECT FOR HAZ/FOG URBAN
C                                          AIR MASS.
C                                          3. = CORRECT FOR HAZ/FOG RURAL
C                                          (CONTINENTAL POLAR) AIR MASS.
C                                          4. = CORRECT FOR FOG ONE (HEAVY
C                                          ADVECTION).
C                                          5. = CORRECT FOR FOG TWO (MODERATE
C                                          RADIATION).
C                                          6. = CORRECT FOR RAIN (DRIZZLE).
C                                          7. = CORRECT FOR RAIN (WIDESPREAD)
C                                          8. = CORRECT FOR RAIN (THUNDERSTORM).
C                                          9. = CORRECT FOR SNOW (FALLING OR
C                                          BLOWING SNOW) (R. HUM.<95%).
C                      21-30      VS -    LOS VISIBILITY (KM).
C                      31-40      RO -    AMBIENT RELATIVE HUMIDITY (%).
C                      41-50      S3 -    WINDSPEED (METERS/SEC).
C                      51-60      TEMP -  AMBIENT TEMPERATURE (DEG. C).
C                      61-70      SRNG -  SLANT RANGE OF OBSERVER TO TARGET (KM).
C
C      NEXT           1-4              BEGINNING OF EXECUTION FOR MULTIPLE
C                                          DATA SETS.
C
C      DONE           1-4              SIGNIFIES THE LAST OR ONLY DATA SET
C                                          READ. MUST BE THE LAST RECORD READ.
C
C      CHARACTER*4 ID(3),NAME
C      DIMENSION WAVE(4),RV(6)
C      DATA TWOPI/6.283185307/
C      DATA WAVE/0.55, 1.06, 3.75, 10.591/
C      DATA ID/'DATA','NEXT','DONE'/

```



```

C
C READ DATA INPUT:
20  CONTINUE
    READ(7,900) NAME,(RV(K), K=1,6)
    IF (NAME .EQ. ID(1)) GO TO 30
    IF (NAME .EQ. ID(2)) GO TO 50
    IF (NAME .EQ. ID(3)) GO TO 40
30  CONTINUE
    FOG=RV(1)
    IFOG=FOG
    VS=RV(2)
    RO=RV(3)
    S3=RV(4)
    TEMP=RV(5)
    SRNG=RV(6)
    GO TO 20

```

```

C
C LIST INPUTS:
40  CONTINUE
    IDONE =1
50  CONTINUE
    WRITE(6,300)
    WRITE(6,200)
    WRITE(6,350)
    WRITE(6,500)
    WRITE(6,370)
    WRITE(6,600)
    IF( IFOG .EQ. 1) WRITE(6,601)
    IF( IFOG .EQ. 2) WRITE(6,602)
    IF( IFOG .EQ. 3) WRITE(6,603)
    IF( IFOG .EQ. 4) WRITE(6,604)
    IF( IFOG .EQ. 5) WRITE(6,605)
    IF( IFOG .EQ. 6) WRITE(6,606)
    IF( IFOG .EQ. 7) WRITE(6,607)
    IF( IFOG .EQ. 8) WRITE(6,608)
    IF( IFOG .EQ. 9) WRITE(6,609)
    WRITE(6,370)
    WRITE(6,710) VS
    WRITE(6,720) RO
    WRITE(6,730) S3
    WRITE(6,740) TEMP
    WRITE(6,750) SRNG
    WRITE(6,300)

```

```

C * VISIBILITY ADJUSTMENT:
    IF(VS .GE. 25.) VIS=30.
    IF(VS .LT. 25.) VIS=20.
    IF(VS .LT. 15.) VIS=10.
    IF(VS .LT. 6. ) VIS=2.3
    IF(VS .LT. 1. ) VIS=1.0

```

```

C

```

```

C * CALCULATE ATMOSPHERIC EXTINCTION (EXT):
C
DO 100 I=1,4
CALL XTRAN(IFOG,EXT,VS,VIS,R0,WAVE,I,S3,TEMP,TWOPI)
IF(SRNG .GE. VS) THEN
    TRANS=0.0
    GO TO 100
ENDIF
TAU=SRNG*EXT
IF(TAU .LT. 85.) THEN
    TRANS=EXP(-TAU)
ELSE
    TRANS=0.0
ENDIF
TRANS=AMAX1(TRANS,0.00001)
TRANS=AMIN1(TRANS,1.0)
WRITE(6,820) WAVE(I)
WRITE(6,760) EXT
WRITE(6,800) TRANS
WRITE(6,350)
100 CONTINUE
WRITE(6,390)
IF(IDONE .EQ. 1 ) GO TO 999
GO TO 20
C
C * FORMAT STATEMENTS:
200 FORMAT(10X,'ATMOSPHERIC TRANSMITTANCE CALCULATION: ')
300 FORMAT(///)
350 FORMAT(///)
370 FORMAT(1H )
390 FORMAT(1H1)
500 FORMAT(10X,'INPUT PARAMETERS:')
600 FORMAT(10X,'ADVERSE WEATHER CONDITION:')
601 FORMAT(10X,'HAZ/FOG, MARITIME AIR MASS')
602 FORMAT(10X,'HAZ/FOG, URBAN AIR MASS')
603 FORMAT(10X,'HAZ/FOG, RURAL AIR MASS')
604 FORMAT(10X,'FOG ONE, HEAVY ADVECTION')
605 FORMAT(10X,'FOG TWO, MODERATE RADIATION')
606 FORMAT(10X,'RAIN, DRIZZLE')
607 FORMAT(10X,'RAIN, WIDESPREAD')
608 FORMAT(10X,'RAIN, THUNDERSTORM')
609 FORMAT(10X,'SNOW (REL. HUM. < 95%)')
710 FORMAT(10X,'VISIBILITY,KM: ',F5.1)
720 FORMAT(10X,'RELATIVE HUMIDITY, %: ',F5.1)
730 FORMAT(10X,'WINDSPEED, M/S: ',F5.1)
740 FORMAT(10X,'AMBIENT TEMPERATURE, DEG. C: ',F5.1)
750 FORMAT(10X,'SLANT RANGE, KM: ',F5.1)
760 FORMAT(10X,'EXTINCTION COEFFICIENT: ',F8.5)
800 FORMAT(12X,'ATMOSPHERIC TRANSMITTANCE: ',F6.5)
820 FORMAT(10X,'WAVELENGTH, MICROMETERS: ',F6.3)

```

```

900  FORMAT(A4,6X,6F10.3)
999  CONTINUE
      STOP
      END

C
      SUBROUTINE XTRAN (IFOG,EXT,VS,VIS,R0,WAVE,I,S3,TEMP,TWOPI)
C ** SUBROUTINE TO CALCULATE EXTINCTION COEFFICIENTS DUE TO NATURAL
C   AEROSOLS FOR VISIBLE, NEAR IR, MID IR, & FAR IR.      (5/8/90)
C
      DIMENSION WAVE(4)
C * I=1 TO 4 is the index for wavelengths: 0.55, 1.06, 3.75, & 10.591
C
C * VIS=1.0 MEANS THAT THE ACTUAL VISIBILITY (VS) IS LESS THAN ONE KM.
C   THE EXTINCTION VALUE IS NOT CALCULATED FOR THE VIS=1 CASE.
C
      IF(VIS .EQ. 1.0) THEN
          EXT=999.
          GO TO 1000
      ENDIF
      GO TO (100,200,300,400,500,600,600,600,700) IFOG
C * CORRECTION FOR MARITIME AEROSOL (IFOG=1):
100  CONTINUE
      IF(I .EQ. 1) THEN
          EXT=2.303/VS
          GO TO 1000
C * NEAR IR Extinction (10% Threshold Contrast):
      ELSE IF(I .EQ. 2) THEN
          IF(VIS .EQ. 2.3) THEN
              EXT=0.702969+0.434713*R0-0.241279E-01*R0**2+0.489425E-03*
1              R0**3-0.43102547E-05*R0**4+0.13970539E-07*R0**5
          ELSE IF(VIS .EQ. 10.) THEN
              EXT=0.16188842-0.47434827E-03*R0+0.10792305E-04*R0**2
          ELSE IF(VIS .EQ. 20.) THEN
              EXT=0.80943118E-01-0.23695936E-03*R0+0.53943016E-05*R0**2
          ELSE IF(VIS .EQ. 30.) THEN
              EXT=0.53934697E-01-0.16439958E-03*R0+0.36818869E-05*R0**2
          ENDIF
C ** MID IR Extinction (5% Threshold Contrast):
      ELSE IF(I .EQ. 3) THEN
          IF(VIS .EQ. 2.3) THEN
              EXT=0.37449492+0.127212723E+01*R0-0.70787653E-01*R0**2+
1              0.14406625E-02*R0**3-0.12751449E-04*R0**4+0.41612448
2              E-07*R0**5
          ELSE IF(VIS .EQ. 10.) THEN
              EXT=0.86084715E-01+0.24372478E-02*R0-0.84868095E-04*R0**2
1              +0.80744837E-06*R0**3
          ELSE IF(VIS .EQ. 20.) THEN
              EXT=0.4303717E-01+0.12203131E-02*R0-0.42477688E-04*R0**2
2              +0.40400577E-06*R0**3
          ELSE IF(VIS .EQ. 30.) THEN

```

XTRAN 10

```

      EXT=0.30121460E-01-0.86086670E-03*R0+0.14852113E-04*R0**2
    ENDIF
C ** FAR IR Extinction (5% Threshold Contrast):
  ELSE IF(I .EQ. 4) THEN
    IF(VIS .EQ. 2.3) THEN
      EXT=0.10877143-0.36226721E+02*R0+0.24637063E+01*R0**2
1     -0.65918926E-01*R0**3+0.86910543E-03*R0**4-0.56553248
2     E-05*R0**5+0.14548426E-07*R0**6
    ELSE IF(VIS .EQ. 10.) THEN
      EXT=0.25261024E-01-0.64383085E-01*R0+0.28208802E-02*R0**2
1     -0.39837549E-04*R0**3+0.18263068E-06*R0**4
    ELSE IF(VIS .EQ. 20.) THEN
      EXT=0.12630209E-01-0.32088588E-01*R0+0.14060241E-02*R0**2
2     -0.19858198E-04*R0**3+0.91048408E-07*R0**4
    ELSE IF(VIS .EQ. 30.) THEN
      EXT=0.84236782E-02-0.21460595E-01*R0+0.94027692E-03*R0**2
1     -0.13278993E-04*R0**3+0.60876197E-07*R0**4
    ENDIF
  ENDIF
  GO TO 1000
C ** CORRECTION FOR URBAN AEROSOLS (IFOG=2):
200 CONTINUE
  IF(I .EQ. 1) THEN
    EXT=2.303/Vs
    GO TO 1000
C ** NEAR IR (10% Threshold Contrast):
  ELSE IF(I .EQ. 2) THEN
    IF(VIS .EQ. 2.3) THEN
      EXT=0.470469+0.458491E-02*R0-0.138345E-03*R0**2+
1     0.987225E-06*R0**3
    ELSE IF(VIS .EQ. 10.) THEN
      EXT=0.10456311+0.99970964E-04*R0
    ELSE IF(VIS .EQ. 20.) THEN
      EXT=0.52280321E-01+0.49978415E-04*R0
    ELSE IF(VIS .EQ. 30.) THEN
      EXT=0.34820473E-01+0.33340304E-04*R0
    ENDIF
C ** MID IR Extinction (5% Threshold Contrast):
  ELSE IF(I .EQ. 3) THEN
    IF(VIS .EQ. 2.3) THEN
      EXT=0.181672+0.223595E-02*R0-0.649097E-04*R0**2+
1     0.445258E-06*R0**3
    ELSE IF(VIS .EQ. 10.) THEN
      EXT=0.409405E-01+0.246151E-04*R0
    ELSE IF(VIS .EQ. 20.) THEN
      EXT=0.196819E-01+0.214857E-04*R0
    ELSE IF(VIS .EQ. 30.) THEN
      EXT=0.13642567E-01+0.82808624E-05*R0
    ENDIF
C ** FAR IR Extinction (5% Threshold Contrast):

```

XTRAN 20

```

ELSE IF(I .EQ. 4) THEN
  IF(VIS .EQ. 2.3) THEN
    EXT=0.12040912-0.16526281E-03*R0
  ELSE IF(VIS .EQ. 10.) THEN
    EXT=0.27787235E-01-0.38140694E-04*R0
  ELSE IF(VIS .EQ. 20.) THEN
    EXT=0.13896850E-01-0.19114772E-04*R0
  ELSE IF(VIS .EQ. 30.) THEN
    EXT=0.92638688E-02-0.12733592E-04*R0
  ENDIF
ENDIF
GO TO 1000
C ** CORRECTION FOR RURAL AEROSOLS (IFOG=3):
300 CONTINUE
  IF(I .EQ. 1) THEN
    EXT=2.303/V5
    GO TO 1000
  C ** NEAR IR Extinction (10% Threshold Contrast):
    ELSE IF(I .EQ. 2) THEN
      IF(VIS .EQ. 2.3) THEN
        EXT=0.419134+0.297229E-02*R0-0.910602E-04*R0**2+
1          0.693381E-06*R0**3
        ELSE IF(VIS .EQ. 10.) THEN
          EXT=0.92234926E-01+0.14522439E-03*R0
        ELSE IF(VIS .EQ. 20.) THEN
          EXT=0.46116508E-01+0.72625335E-04*R0
        ELSE IF(VIS .EQ. 30.) THEN
          EXT=0.30718057E-01+0.48360044E-04*R0
        ENDIF
      GO TO 1000
    C ** MID IR EXTINCTION (5% Threshold Contrast):
      ELSE IF (I .EQ. 3) THEN
        IF(VIS .EQ. 2.3) THEN
          EXT=0.12900+0.316817E-02*R0-0.970693E-04*R0**2+
1          0.73279779E-06*R0**3
          ELSE IF(VIS .EQ. 10.) THEN
            EXT=0.25575225E-01+0.15271168E-03*R0
          ELSE IF(VIS .EQ. 20.) THEN
            EXT=0.12783289E-01+0.76398985E-04*R0
          ELSE IF(VIS .EQ. 30.) THEN
            EXT=0.82117356E-02+0.54546589E-04*R0
          ENDIF
        C** FAR IR EXTINCTION (5% Threshold Contrast)
          ELSE IF(I .EQ. 4) THEN
            IF(VIS .EQ. 2.3) THEN
              EXT=0.104671+0.200045E-02*R0-0.575152E-04*R0**2+
1              0.385649E-06*R0**3
              ELSE IF(VIS .EQ. 10.) THEN
                EXT=0.23642112E-01+0.55895247E-05*R0
              ELSE IF(VIS .EQ. 20.) THEN

```

XTRAN 30

```

EXT=0.11815846E-01+0.28406062E-05*RO
ELSE IF(VIS .EQ. 30.) THEN
EXT=0.78841036E-02+0.18164473E-05*RO
ENDIF
ENDIF
GO TO 1000
400 CONTINUE
C
C ** EXTINCTION COEFFICIENT FOR FOG ONE (HEAVY ADVECTION): XTRAN 40
C ** RELATIVE HUMIDITY MUST BE 100% FOR FOG ONE. (IFOG=4)
C
IF(IFOG .EQ. 4 .AND. RO .EQ. 100.) THEN
IF(I .EQ. 1) EXT=2.303/VS*1.0000
IF(I .EQ. 2) EXT=2.303/VS*1.0175
IF(I .EQ. 3) EXT=2.996/VS*1.0780
IF(I .EQ. 4) EXT=2.996/VS*1.1559
GO TO 1000
ELSE
EXT=999.
GO TO 1000
ENDIF
500 CONTINUE
C
C ** EXTINCTION COEFFICIENT FOR FOG TWO (MODERATE RADIATION): XTRAN 50
C ** RELATIVE HUMIDITY MUST BE 100% FOR FOG TWO.(IFOG=5)
C
IF(IFOG .EQ. 5 .AND. RO .EQ. 100.) THEN
IF(I .EQ. 1) EXT=2.303/VS*1.0000
IF(I .EQ. 2) EXT=2.303/VS*1.0518
IF(I .EQ. 3) EXT=2.996/VS*1.4527
IF(I .EQ. 4) EXT=2.996/VS*0.21601
GO TO 1000
ELSE
EXT=999.
GO TO 1000
ENDIF
600 CONTINUE
C
C ** EXTINCTION COEFFICIENT (EXT) DUE TO RAIN XTRAN 60
C
C IFOG=6 FOR DRIZZLE; IFOG=7 FOR WIDESPREAD; IFOG=8 FOR THUNDERSTORM.
C ** SET RAIN RATE (RNRT) IN MM/HR:
RNRT=0.
IF(IFOG .EQ. 6) THEN
RNRT=0.5
EXT=0.5089*RNRT**0.63
GO TO 1000
ENDIF
IF(IFOG .EQ. 7) THEN
RNRT=5.0

```

```

        EXT=0.3201*RNRT**0.63
        GO TO 1000
    ENDIF
    IF(IFOG .EQ. 8) THEN
        RNRT=25.
        EXT=0.1635*RNRT**0.63
        GO TO 1000
    ENDIF
700  CONTINUE
C
C ** EXTINCTION COEFFICIENT FOR SNOW (FOR REL. HUM. <95% ONLY)           XTRAN 70
C
C ** IF WINDSPEED < 5 M/S, USE "FALLING SNOW" VALUE FOR SNOW PARTICLE
C    SIZE RBAR. (IFOG=9)
    IF(RO .GT. 95.) THEN
        EXT=999.
        GO TO 1000
    ENDIF
    IF( S3 .LT. 5.) THEN
        IF(TEMP .LE. -15.) RBAR=100.
        IF(TEMP .GT. -15. .AND. TEMP .LT. 0.) RBAR=(250.+10.*TEMP)
        IF(TEMP .GE. 0. .AND. TEMP .LT. 2.) RBAR=(250.+25.*TEMP)
        IF(TEMP .GE. 2.) RBAR=300.
C ** IF WINDSPEED > 5 M/S, USE "BLOWING SNOW" VALUE FOR RBAR.
        ELSE
            RBAR=100.
        ENDIF
        RD=10.
C ** VS IS THE ACTUAL LOS VISIBILITY.
        C=1.E-5*TWOPI*RBAR*RD/WAVE(I)/VS
        EXT=(EXP(-0.88*C)+1.)*1.96/VS
1000 CONTINUE
        RETURN
        END

```

DISTRIBUTION LIST FOR PUBLIC RELEASE

Commandant

U.S. Army Chemical School
ATTN: ATZN-CM-CC (T. Collins)
Fort McClellan, AL 36205

Commander

U.S. Army Aviation Center
ATTN: ATZQ-D-MA (Mr. Oliver N. Heath)
Fort Rucker, AL 36362

Commander

U.S. Army Aviation Center
ATTN: ATZQ-D-MS (Mr. Donald Wagner)
Fort Rucker, AL 36362

NASA/Marshall Space Flight Center
ATTN: ED-43 (Otha H. Vaughan, Jr.)
Huntsville, AL 35812

NASA/Marshall Space Flight Center
Atmospheric Sciences Division
ATTN: Code ED-41 (Dr. George Fichtl)
Huntsville, AL 35812

NASA/Marshall Space Flight Center
Atmospheric Sciences Division
ATTN: Code ED-41
Huntsville, AL 35812

Deputy Commander

U.S. Army Strategic Defense Command
ATTN: (Dr. Julius Q. Lilly)
PO Box 1500
Huntsville, AL 35758

Commander

U.S. Army Missile Command
ATTN: AMSMI-RD-AC-AD (Donald R. Peterson)
Redstone Arsenal, AL 35898-5242

Commander

U.S. Army Missile Command
ATTN: AMSMI-RD-AS-SS (Huey F. Anderson)
Redstone Arsenal, AL 35898-5253

Commander

U.S. Army Missile Command
ATTN: AMSMI-RD-AS-SS (B. Williams)
Redstone Arsenal, AL 35898-5253

Commander

U.S. Army Missile Command
ATTN: AMSMI-RD-DE-SE
(Gordon Lill, Jr.)
Redstone Arsenal, AL 35898-5245

Commander

U.S. Army Missile Command
Redstone Scientific Information Center
ATTN: AMSMI-RD-CS-R/Documents
Redstone Arsenal, AL 35898-5253

Commander

U.S. Army Missile Command
ATTN: AMSMI-RD-TE-F (ASL MET TEAM)
Redstone Arsenal, AL 35898-5253

Commander

U.S. Army Intelligence Center & School
ATTN: ATSI-CD-CB (Mr. Colanto)
Fort Huachuca, AZ 85613-7000

Northrup Corporation

Electro-Mechanical Division
ATTN: Dr. Richard D. Tooley, m/s 7270/Y34
500 East Orangethorpe Avenue
Anaheim, CA 92801-1099

Commander - Code 3331

Naval Weapons Center
ATTN: Dr. Alexis Shlanta
China Lake, CA 93555

Pacific Missile Test Center
Geophysics Division

ATTN: Code 3250-3 (R. de Violini)
Point Mugu, CA 93042-5000

Pacific Missile Test Center
Geophysics Division

ATTN: Code 3253 (Terry E. Battalino)
Point Mugu, CA 93042-5000

Commander
Naval Ocean Systems Center
ATTN: Code 54 (Dr. Juergen Richter)
San Diego, CA 92152-5000

Meteorologist in Charge
Kwajalein Missile Range
P.O. Box 67
APO San Francisco, CA 96555

Library, R-51 Technical Reports
NOAA/ERL
U.S. Department of Commerce
325 S. Broadway
Boulder, CO 80303

Dr. Hans J. Liebe
NTIA/ITS S 3
325 S. Broadway
Boulder, CO 80303

NCAR Library Serials
National Center for Atmos Rsch
P.O. Box 3000
Boulder, CO 80307-3000

Bureau of Reclamantion
ATTN: D:1200
P.O. Box 25007
Denver, CO 80225

Director of Requirements
Deputy Chief of Staff for
Operations and Plans
ATTN: DAMO-RQZ
Washington, DC 20310-0460

Mil Asst for Env Sci of
the Undersecretary of Defense
for Rsch & Engr/R&AT/E&LS
Pentagon - Room 3D129
Washington, DC 20301-3080

Director
Naval Research Laboratory
ATTN: Code 4110 (Dr. Lothar H. Ruhnke)
Washington, DC 20375-5000

HQDA (DEAN-RDM/Dr Gomez)
Washington, DC 20314

Director, Division of Atmospheric Science
National Science Foundation
ATTN: Dr. Eugene W. Bierly
1800 G. Street, N.W.
Washington, DC 20550

Commander
Space and Naval Warfare System Command
ATTN: PMW-145-1G (LT. Painter)
Washington, DC 20362-5100

Naval Training Equipment Center
ATTN: TIC Bldg 2068
Orlando, FL 32813

Commandant
U.S. Army Infantry
ATTN: ATSH-CD-CS-OR (Dr. E. Dutoit)
Fort Benning, GA 30905-5090

USAFETAC/DNE
Scott AFB, IL 62225

Air Weather Service Technical Library
FL4414
Scott AFB, IL 62225-5458

AWS/DOOE
Scott AFB, IL 62225-5008

USAFETAC/DNE
ATTN: Mr. Charles Glauber
Scott AFB, IL 62225-5008

Commander
U.S. Army Combined Arms Combat
Development Activity
ATTN: ATZL-CAW (Lt Col Cullburg)
Fort Leavenworth, KS 66027-5300

Commander
U.S. Army Combined Arms Combat
Development Activity
ATTN: ATZL-CAE (Mr. Beck)
Fort Leavenworth, KS 66027-5300

Commander
U.S. Army Combined Arms Combat
Development Activity
ATTN: ATZL-CAW (Mr. Page)
Fort Leavenworth, KS 66027-5300

Commander
U.S. Army Armor Center and Fort Knox
ATTN: ATZK-CD-ML (Tech Div)
Fort Knox, KY 40121-5215

Air Force Geophysics Laboratory
Hanscom AFB, MA 01731-5000

Commander
Air Force Geophysics Laboratory
ATTN: AFGL/LYP (Rosemary M. Dyer)
Hanscom AFB, MA 01731-5000

Commander
Air Force Geophysics Laboratory
ATTN: LY (Dr. Robert A. McClatchey)
Hanscom AFB, MA 01731-5000

Commander
Air Force Geophysics Laboratory
ATTN: LYA (Dr. M. Kraus)
Hanscom AFB, MA 01731-5000

Raytheon Company
Dr. Charles M. Sonnenschein
Equipment Division
528 Boston Post Road
Sudbury, MA 01776
Mail Stop 1K9

Director
U.S. Army Materiel Systems
Analysis Activity
ATTN: AMXSY-MP (H. Cohen)
Aberdeen Proving Ground, MD 21005-5071

Commander
U.S. Army Chemical Rsch, Dev & Engr Center
ATTN: SMCCR-ST (Ronald Pennsyle)
Aberdeen Proving Ground, MD 21010-5423

Commander
U.S. Army Chemical Rsch Dev & Engr
& Engr Center
ATTN: SMCCR-TDT (Mr. Joseph Vervier)
Aberdeen Proving Ground, MD 21010-5423

Project Manager, Smoke/Obscurants
ATTN: AMCPM-SMK-T
(Mr. A. Van de Wal)
Aberdeen Proving Ground, MD 21005-5001

Director
U.S. Army Materiel Sys Analysis Activity
ATTN: AMXSY-GC (Mr. Fred Campbell)
Aberdeen Proving Ground, MD 21005-5071

Director
U.S. Army Materiel Sys Analysis Activity
ATTN: AMXSY-CR (Robert N. Marchetti)
Aberdeen Proving Ground, MD 21005-5071

Director
U.S. Army Materiel Sys Analysis Activity
ATTN: AMXSY-CS (Mr. Brad W. Bradley)
Aberdeen Proving Ground, MD 21005-5071

Commander
U.S. Army Laboratory Command
ATTN: AMSLC-CG
2800 Powder Mill Road
Adelphi, MD 20783-5071

Commander
Headquarters, U.S. Army Laboratory Command
ATTN: AMSLC-CT
2800 Powder Mill Road
Adelphi, MD 20783-1145

Commander
Harry Diamond Laboratories
ATTN: SLCIS-CO
2800 Powder Mill Road
Adelphi, MD 20783-1197

Director
Harry Diamond Laboratories
ATTN: SLCHD-RT-AC (Dr. Z. G. Sztankay)
2800 Powder Mill Road
Adelphi, MD 20783-1197

Air Force Systems Command/WER
Andrews Air Force Base, MD 20334-5000

National Security Agency
ATTN: W21 (Dr. Longbothum)
9800 Savage Road
Fort George G. Meade, MD 20755-6000

Chief
Intel Mat Dev & Spt Ofc
ATTN: DELEW-WL-I
Bldg 4554-D
Fort George G. Meade, MD 20755-6000

Director
Intelligence Materiel Activity
ATTN: AMXMI-M-D
Fort George G. Meade, MD 20755-5315

Officer in Charge
Naval Surface Weapons Center
White Oak Library, Technical Library
Silver Spring, MD 20910-1090

The Environmental Research
Institute of MI
ATTN: IRIA Library
P.O. Box 8618
Ann Arbor, MI 48107-8618

Dr. A. D. Belmont
Meteorology Department
Central Data, Box 1249
Minneapolis, MN 55440-1249

Commander
U.S. Army Research Office
ATTN: DRXRO-GS (Dr. W. A. Flood)
PO Box 12211
Research Triangle Park, NC 27709-2211

Dr. Jerry Davis
Dept of Marine, Earth, and Atmos Sci
P.O. Box 8208
North Carolina State University
Raleigh, NC 27650-8208

Commander
U.S. Army Cold Regions Research
& Engineering Laboratory
ATTN: CRREL-RG (Mr. Robert Redfield)
Hanover, NH 03755-1290

Commander
U.S. Cold Regions Research
& Engineering Laboratory
ATTN: CRREL-RD (Dr. K. F. Sterrett)
Hanover, NH 03755-1290

Commanding Officer
U.S. Army Armament R&D Command
ATTN: DRDAR-TSS, Bldg 59
Dover, NJ 07801

Commanding Officer
U.S. Army Armament R&D Command
ATTN: SMCAR-MSI (Mr. G. H. Waldron)
Dover, NJ 67801-5001

U.S. Army Communications-
Electronics Command
Center for EW/RSTA
ATTN: AMSEL-RD-EW-SP
Fort Monmouth, NJ 07703-5303

Commander
U.S. Army Communications-
Electronics Command
ATTN: AMSEL-EW-D (File Copy)
Fort Monmouth, NJ 07703-5303

Headquarters
U.S. Army Communications-
Electronics Command
ATTN: AMSEL-EW-MD
Fort Monmouth, NJ 07703-5303

Commander
U.S. Army Satellite Comm Agency
ATTN: DRCPM-SC-3
Fort Monmouth, NJ 07703-5303

Director
EW/RSTA Center
ATTN: AMSEL-EW-DR
Fort Monmouth, NJ 07703-5303

USACECOM
Center for EW/RSTA
ATTN: AMSEL-RD-EW-SP
Fort Monmouth, NJ 07703-5303

6585th TG (AFSC)
ATTN: RX (Capt Stein)
Holloman AFB, NM 88330

OLA, 2WS (MAC)
Holloman AFB, NM 88330-5000

AFWL/WE
Kirtland AFB, NM 87117-6008

Commander
U.S. Army White Sands Missile Range
ATTN: STEWS-TE-TL
White Sands Missile Range, NM 88002-5501

Office of the Test Director
Joint Services WO GW CM Test Program
ATTN: DRXDE-TD (Mr. Weldon Findley)
White Sands Missile Range, NM 88002

Director
U.S. Army TRADOC Analysis Command
ATTN: ATRC-WSR (D. Anguiano)
White Sands Missile Range, NM 88002-5502

Director
U.S. Army TRADOC Analysis Command
ATTN: ATRC-WCC (Mr. Louie Dominguez)
White Sands Missile Range, NM 88002-5502

Commander
U.S. Army TRADOC Analysis Command
ATTN: ATRC-W (Dr. D. W. Collier)
White Sands Missile Range, NM 88002-5501

Rome Air Development Center
ATTN: Technical Library (DOL)
Griffiss AFB, NY 13441-5700

Department of the Air Force
7th Squadron
APO, NY 09403

AF Wright Aeronautical Laboratories
Avionics Laboratory
ATTN: AFWAL/AARI (Dr. V. Chimelis)
Wright-Patterson AFB, OH 45433

Commander
U.S. Army Field Artillery School
ATTN: ATSF-F-FD (Mr. Gullion)
Fort Sill, OK 73503-5600

Commandant
U.S. Army Field Artillery School
ATTN: ATSF-TSM-TA-SS (Mr. Charles Tayler)
Fort Sill, OK 73503-5600

Commander
Naval Air Development Center
ATTN: Code 301 (Dr. A. K. Witt 301)
Warminster, PA 18974

Commander
U.S. Army Dugway Proving Ground
ATTN: STEDP-MT-DA-M (Mr. Paul Carlson)
Dugway, UT 84022

Commander
U.S. Army Dugway Proving Ground
ATTN: STEDP-MT-DA-L
Dugway, UT 84022

Commander
U.S. Army Dugway Proving Ground
ATTN: STEDP-MT-DA-T (Dr. W. A. Peterson)
Dugway, UT 84022

Defense Technical Information Center
ATTN: DTIC-FDAC
Cameron Station, Bldg 5
Alexandria, VA 22314

Commanding Officer
U.S. Army Foreign Sci & Tech Center
ATTN: CM
220 7th Street, NE
Charlottesville, VA 22901-5396

Naval Surface Weapons Center
Code G63
Dahlgren, VA 22448-5000

Commander
U.S. Army Operational Test
& Evaluation Agency
ATTN: CSTE-ED (Floyd I. Hill)
5600 Columbia Pike
Falls Church, VA 22041

Commander and Director
U.S. Army Engineer Topographics Lab
ATTN: ETL-GS-LB
Fort Belvoir, VA 22060

Department of the Army
U.S. Army Center for Night Vision &
Electro-Optics Laboratory
ATTN: AMSEL-RD-NV-D (Dr. Rudolf G. Buser)
Fort Belvoir, VA 22060-5677

Director
U.S. Army Center for Vision &
Electro-Optics Laboratory
ATTN: AMSEL-RD-NV-L (Dr. Robert S. Rhode)
Fort Belvoir, VA 22060-5677

Director
U.S. Army Center for Night Vision &
Electro-Optics Laboratory
ATTN: DELNV-VI
Fort Belvoir, VA 22060-5677

Director
U.S. Army Center of Night Vision &
Electro-Optics Laboratory
ASL Fort Belvoir Met Team
ATTN: Mr. Robert Smith
Fort Belvoir, VA 22060-5677

Department of the Air Force
HQ 5 Weather Wing (MAC)
ATTN: 5 WW/DN
Langley Air Force Base, VA 23665-5000

Commander and Director
U.S. Army Engineer Topographics Lab
ATTN: ETLZD (Dr. Gomez)
Fort Belvoir, VA 22060-5546

Commander
Logistics Center
ATTN: ATCL-E
Fort Lee, VA 23801-6000

Commander
USATRADO
ATTN: ATCD-FA
Fort Monroe, VA 23651-5170

Science and Technology
101 Research Drive
Hampton, VA 23666-1340

Commander
U.S. Army Nuclear & Cml Agency
ATTN: MONA-ZB Bldg 2073
Springfield, VA 22150-3198