

AD-A247 936

ICATION PAGE

Form Approved

OMB No. 0704-0188



ed to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE		3. REPORT TYPE AND DATES COVERED	
4. TITLE AND SUBTITLE Analysis of constrained-layer damping of flexural and extensional waves in infinite, fluid-loaded plates				5. FUNDING NUMBERS WU - DN280-003 PE - 61153N TA - RR011-08-42	
6. AUTHOR(S) Pieter S. Dubbelday				DTIC ELECT	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory Underwater Sound Reference Detachment P.O. Box 568337 Orlando, FL 32856-8837				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Research 800 N. Quincy Street Arlington, VA 22217-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This study contains a mathematical analysis of constrained-layer damping (CLD) in plates of infinite extent, with an emphasis on the physical understanding of some special features, including fluid loading. Previous work is expanded to cover extensional waves. Some essential aspects of fluid loading may be understood by applying thin-plate theory. Therefore, thin-plate theory of extensional waves in a fluid-loaded plate was developed as a counterpart to that for flexural waves. The description and examples of CLD follow three models: the first is an extension of Kerwin's 1959 model, the second a hybrid model for which the base plate is treated by exact elasticity theory, and finally a fully exact model for all three layers. Examples and comparisons are given.					
14. SUBJECT TERMS Constrained-layer damping Extensional waves Fluid-covered thin plate theory Plate-fluid interaction				15. NUMBER OF PAGES 6	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCL	18. SECURITY CLASSIFICATION OF THIS PAGE UNCL	19. SECURITY CLASSIFICATION OF ABSTRACT UNCL	20. LIMITATION OF ABSTRACT UL		

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines** to meet **optical scanning requirements**.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

Block 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement. Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*).

Blocks 17. - 19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

ANALYSIS OF CONSTRAINED-LAYER DAMPING OF FLEXURAL AND
EXTENSIONAL WAVES IN INFINITE, FLUID-LOADED PLATES

Pieter S. Dubbelday
Naval Research Laboratory, USRD
P.O. Box 568339
Orlando, FL, 32856-8339
U.S.A.

Corrected version of article in the
Proceedings of the Second International Congress on
RECENT DEVELOPMENTS IN AIR- AND STRUCTURE-BORNE
SOUND AND VIBRATION

March 4-6, 1992, Vol 1, pp.151-156
Auburn University, U.S.A.
Edited by Malcolm J. Crocker and P.K. Raju

Accession For	
DTIC GRA&I	☒
DTIC TAB	☐
Unannounced	☐
Justification	
By	
Distribution/	
Availability Codes	
Avail and/or	
Special	
A-1	

92 3 23 150

92-07386



ANALYSIS OF CONSTRAINED-LAYER DAMPING OF FLEXURAL AND EXTENSIONAL WAVES IN INFINITE, FLUID-LOADED PLATES

Pieter S. Dubbelday
Naval Research Laboratory, USRD
P.O. Box 568339
Orlando, FL, 32856-8339
U.S.A.

ABSTRACT

This study contains a mathematical analysis of constrained-layer damping (CLD) in plates of infinite extent, with an emphasis on the physical understanding of some special features, including fluid loading. Previous work is expanded to cover extensional waves. Some essential aspects of fluid loading may be understood by applying thin-plate theory. Therefore thin-plate theory of extensional waves in a fluid-loaded plate was developed as a counterpart to that for flexural waves. The description and examples of CLD follow three models: the first is an extension of Kerwin's 1959 model, the second is a hybrid model for which the base plate is treated by exact elasticity theory, and finally a fully exact model for all three layers. Examples and comparisons are given.

NOMENCLATURE

c_p	extensional wave speed for thin base plate	i	index of layers: 1-base plate, 2-elastomer, 3-constraining layer
c_d	dilatational wave speed in base plate material	k	wavenumber in plate, $k = k' - i\alpha$
c_3	extensional wave speed for thin constraining layer	k_o	wavenumber in medium
c_o	wavespeed in medium	q^s	$= \sigma_+ + \sigma_-$
d_i	$= h_i/2$; h_i -layer thickness	w	displacement perpendicular to plate
E_i	Young's modulus for three layers	α	attenuation coefficient
E_i^e	extensional modulus for three layers; $E^e = E/(1-\nu^2)$	ν_i	Poisson's ratio for three layers
F	fluid-loading parameter	ρ_i	density of three layers

G_2	complex shear modulus of elastomer, $G_2 = G_2' (1+i\beta)$	ρ_0	density of medium
g	complex shear parameter, $= G_2 / (k'^2 E_3^e h_2 h_3)$, $g = g' (1+i\beta)$	$\sigma_{+,-}$	stresses at opposite sides of plate
r	$= 3/4$ for flexural, $= 1/2$ for extensional waves	τ	$= [(k/k_0)^2 - 1]^{1/2}$
		ω_c	characteristic frequency for extensional waves in fluid-loaded plate
		Ω	dimensionless frequency, $\Omega = \omega/\omega_c$

INTRODUCTION

The principle of constrained-layer damping of acoustic waves consists of attaching a thin elastomer layer with high viscoelastic loss plus a stiff covering layer to a bar, plate, or structure. This stiff layer forces the elastomer into shear, with concomitant large loss, as compared with purely extensional loss in the elastomer without cover layer. Although the loss tangent of the shear modulus G is almost the same as the loss tangent in the Young's modulus E , the energy loss in the constrained layer is of the order $1/kh_2$ of that in an unconstrained layer.

This physical explanation of the effect is represented in a classical paper by E.M. Kerwin [1]. His model gives good results within the given restrictions: flexural waves at low frequency in a main plate with thin additional layers. Extensional waves are not considered, and fluid loading is not readily introduced.

In order to retain the advantage of Kerwin's model of providing an explicit algebraic expression for the attenuation coefficient in terms of geometric and elastic parameters, the model was extended and compared with more exact formulations, a "hybrid" model and an exact model [2,3].

In this study the analysis is extended to cover extensional waves. Since flexural waves were discussed in previous publications [2,3], only some of their features will be mentioned here. For most combinations of plate and medium, the flexural wave speed in the plate, which increases from zero at zero frequency, reaches a value equal to the speed in the medium, at a certain frequency. Thus one distinguishes radiating and non-radiating ("subsonic") waves in the plate. This phenomenon does not occur for extensional waves in most cases.

HIERARCHY OF MODELS

In the case of flexural waves in a fluid-loaded plate, physical insight was obtained by using thin-plate theory. A parallel thin-plate theory for extensional waves in a fluid-loaded plate is presented. The formalism for extensional waves in terms of the hybrid model and fully exact model is the same as for flexural waves.

The extended Kerwin model includes extensional waves. It is represented by the following expression,

$$\alpha/k' = (r\beta) \frac{E_3^e h_3}{E_1^e h_1} \frac{g' [1 - (c/c_3)^2]^2}{[1 - (c/c_3)^2 + g']^2 + \beta^2 g'^2} \quad (1)$$

The following outline lists the three models for constrained layer damping used in the examples, with their characteristic properties.

1. Extended Kerwin model
 - a. Flexural or extensional waves
 - b. Inertia of constraining layer
 - c. Complex shear parameter
 - d. Wave speed from thick-plate theory
2. Hybrid model
 - a. Exact elasticity theory for base plate
 - b. Other two layers as in Kerwin
 - c. Flexural and extensional waves
 - d. With or without fluid loading
3. Exact model
 - a. Exact theory for all layers
 - b. Flexural and extensional waves
 - c. With or without fluid loading

In all the following examples of the analysis the base plate and additional layers have physical and geometric parameters as listed in table I. The (complex) shear modulus of the elastomer is assumed independent of frequency, in order to emphasize the mechanical aspects of the technique without viscoelastic effects.

THIN-PLATE THEORY FOR EXTENSIONAL WAVES IN FLUID-LOADED PLATE

Thin plate theory for flexural waves in a fluid-loaded plate may be found in Ref.[4]. It appeared difficult to derive an analogous expression for extensional waves directly. Therefore the problem was approached as follows.

One starts from the structural equations for waves in plates obtained from exact elasticity theory by integrating and averaging along the direction perpendicular to the plate. From this, one may derive a thick-plate theory for extensional waves [5]. Fluid loading is represented by the sum of the stresses at both sides of the plate, given as $q^s = \sigma_+ + \sigma_-$. Thin-plate theory follows by dropping terms containing the factor (kd) . (In this section all quantities refer to the base plate.) The result is equivalent to adding a fluid-loading term F to the familiar equation for extensional waves in a plate,

$$[E/(1-\nu^2)] \partial^2 w / \partial x^2 + F = \rho \partial^2 w / \partial t^2, \quad (2)$$

where F is given by

$$F = [1 - (c/c_d)^2] (kd)^2 q^s / (2d). \quad (3)$$

Assuming a harmonic wave, with space and time dependence expressed by $\exp i(\omega t - kx)$, where the x -coordinate is in the direction of the wave parallel to the plate's surface, and introducing a new variable τ by $k^2 = k_o^2 (1 + \tau^2)$, Eq.(2) is replaced by an algebraic equation in terms of τ . For fluid loading on both sides one has $q^s = 2 \omega^2 \rho_o w / (k_o \tau)$ and Eq.(2) becomes

$$\tau^3 - \Omega \tau^2 + \tau [1 - (c_o/c_p)^2] - \Omega [1 - (c_o/c_d)^2] = 0, \quad (4)$$

where a characteristic frequency ω_c and a corresponding dimensionless frequency Ω are introduced by $\omega_c = (\rho/\rho_o) c_p^2 / (c_o d)$ and $\Omega = \omega/\omega_c$.

The characteristic frequency ω_c for brass in water is 1.36×10^6 rad/s, and thus for the frequency region where thin-plate theory may be applied, the non-dimensional frequency Ω is very small. As a consequence there exists a small real root, for small Ω , namely

$$\tau \sim \Omega \frac{1 - (c_o/c_d)^2}{1 - (c_o/c_p)^2} \quad (5)$$

This root corresponds to a non-radiating wave in the plate, with a constant speed slightly less than the speed in the medium, (for low frequency).

By division, one determines the quadratic equation for the two remaining complex conjugate roots,

$$\tau^2 + a\tau + b = 0, \quad (6)$$

$$\text{where } a = \Omega \frac{(c_o/c_p)^2 - (c_o/c_d)^2}{1 - (c_o/c_p)^2} \quad \text{and } b = 1 - (c_o/c_p)^2$$

One of these gives a wave number with positive attenuation constant a .

In Fig. 1 a comparison is shown of the relative attenuation a/k' , according to thin-plate theory and to exact elasticity theory, first for two-sided fluid loading. Although the boundary conditions for extensional waves cannot be satisfied for one-sided fluid loading without additional flexural waves, one might take half the value of q^s as given before, and carry this through the analysis. The results in Fig. 1 show that the attenuation for one-sided fluid-loading thus computed does not compare well with the exact-elasticity result.

CONSTRAINED PLATE IN VACUUM

In Fig. 2, a threefold comparison is shown for the relative attenuation constant for extensional waves propagating in a constrained plate, without fluid loading, for three models. The sharp dip in attenuation near 15 kHz is due to an "equivoluminal mode", whereby the tangential velocity component at the faces of the plate is zero, thus no shear exists in the elastomer layer. Of course this feature does not show up in the extended Kerwin model.

FLUID-LOADED, CONSTRAINED PLATE

Flexural waves

Various typical features for damping of flexural waves by radiation and viscoelastic effects may be seen in Fig. 3. One sees that in the high-frequency range the total attenuation is mostly due to radiation. In the middle range the attenuation is due to viscoelastic damping in the elastomer. At the low frequency end a feature appears of high damping due to radiation. It may be pointed out that this is a consequence of the infinite extent of the plate; for finite plates this "radiation" would not be expected to be found in the farfield. See Ref. [3] for further details.

Extensional waves

In Fig.4, a comparison is shown for the relative attenuation constant as a function of frequency for a constrained plate loaded by fluid on both sides, on the side of the added layers, and on the opposite side, computed by exact elasticity theory. One sees that for a large frequency region there is not much difference between the curves, except for a factor of two between the double-sided and one-sided fluid loading. At the low frequency end the curves for the two cases part, while at the high frequency side two of the curves converge and the third one follows a different path. If one compares this figure with Fig.1, one sees that the damping due to the elastomer layer does not make much difference in the total attenuation, except for a different structure at the high-frequency end.

In all the various configurations for extensional waves studied here, there is little variation of the phase speed from that for a single, unloaded plate. This is quite different from the behavior of the phase speed for flexural waves at high frequencies [3].

REFERENCES

1. E.M. Kerwin, "Damping of flexural waves by a constrained viscoelastic layer", J.Acoust.Soc.Am. 31, 1959, 952-962.
2. P.S. Dubbelday and L. V. Fausett, "Constrained-layer model investigation based on exact elasticity theory", J.Acoust.Soc.Am. 80, 1986, 1097-1102.
3. P.S. Dubbelday, "Constrained-layer damping analysis for flexural waves in infinite fluid-loaded plates", J.Acoust.Soc.Am. 90, 1991, 1475-1487.
4. M.C. Junger and D. Feit, Sound, Structures, and Their Interaction, MIT, Cambridge, 2nd ed., 1986, Secs. 8.1 and 8.2
5. P.S. Dubbelday, "Contribution of antisymmetric and symmetric waves to the reflection of sound in a fluid by a thick, homogeneous plate", NRL Memo. Rep. 4312, Naval Research Laboratory, Orlando, FL, 1980.

ACKNOWLEDGEMENT

This work was supported by the Office of Naval Research.

TABLE I. Material and geometric parameters and derived quantities.

Base plate, brass		Elastomer layer (hypothetical)	
$h_1 = 10$ cm	$E_1 = 104$ GPa	$h_2 = 1.24$ mm	$\rho_2 = 1100$ kg/m ³
$\nu_1 = 0.37$	$\rho_1 = 8500$ kg/m ³	$G_2 = 10$ MPa	$\beta = 1.0$
$G_1 = 38$ GPa	$c_p = 3765$ m/s	Bulk modulus = 1.0 GPa	
$\omega_c = 1.63$ Mrad/s		Constraining layer, aluminum	
Fluid, water		$h_3 = 2.48$ mm	$E_3 = 71$ GPa
$\rho_o = 998$ kg/m ³	$c_o = 1481$ m/s	$\nu_3 = 0.33$	$\rho_3 = 2700$ kg/m ³




Figure 1. Extensional wave; single, fluid-loaded plate. Fluid on:
1-both sides; a-exact b-thin plate
2-one side; a-exact b-thin plate




Figure 2. Extensional wave; constrained plate in vacuum. Model:
1-exact; 2-hybrid; 3-extended Kerwin




Figure 3. Flexural wave; exact model.
1-constrained plate, water on elastomer side; 2-single plate, water on one side; 3-constrained plate in vacuum




Figure 4. Extensional wave, constrained plate. 1-water on both sides; 2-water on elastomer side; 3-water on opposite side. Exact model.