AL-TP-1992-0034

ARMSTRONG

LABORATORY

AD-A255 785



THERMAL STRESS IN U.S. AIR FORCE OPERATIONS

Sarah A. Nunneley

CREW SYSTEMS DIRECTORATE Brooks Air Force Base, TX 78235-5000

August 1992

Final Technical Paper for Period 1 April 1990 - 31 March 1992

Approved for public release; distribution is unlimited.



037

9 21

92

92-25545 422891 , p8

AIR FORCE MATERIEL COMMAND BROOKS AIR FORCE BASE, TEXAS 78235-5000 -

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely Government-related procurement, the United States Government incurs no responsibility or any obligation whatsoever. The fact that the Government may have formulated or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication, or otherwise in any manner construed, as licensing the holder or any other person or corporation; or as conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

The voluntary, fully informed consent of the subjects used in this research was obtained as required by AFR 169-3.

The Office of Public Affairs has reviewed this report, and it is releasable to the National Technical Information Service, where it will be available to the general public, including foreign nationals.

This report has been reviewed and is approved for publication.

SARAH A. NUNNELEY, M

Project Scientist

RICHARD L. MILLER, Ph.D. Chief, Crew Technology Division

William 7 Storm

WILLIAM F. STORM, Ph.D. Chief, Sustained Operations Branch

REPORT DOCUMENTATION PAGE			Form Approved OTAB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA, 2202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE August 1992	3. REPORT TYPE AN Final I Apr	D DATES COVERED 90 - 31 Mar 92	
Thermal Stress in U.S. Air Force Operations			5. FUNDING NUMBERS PE - 62202F PR - 7930 TA - 14	
6. AUTHOR(S)			WU - 04	
Sarah A. Nunneley				
7. PERFORMING ORGANIZATION NAME Armstrong Laboratory Crew Systems Directo Brooks Air Force Bas	(5) AND ADDRESS(ES) rate e, TX 78235-500()	8. PERFORMING ORGANIZATION REPORT NUMBER AL-TP-1992-0034	
9. SPONSORING / MONITORING AGENCY	Y NAME(S) AND ADDRESS(ES)	10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION / AVAILABILITY STA Approved for public	TEMENT release; distril	oution is	12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Topics include issue	es raised by dep dance, real-time	loyment to the	Porcion Culf	
clothing effects on	human thermorego	e heat stress lation. A bi	monitors, and bliography is	
14. SUBJECT TERMS Thermal Stress Heat	human thermoregy Phys: Conv	e heat stress ilation. A bi iology ergence	15. NUMBER OF PAGES 10 16. PRICE CODE	
14. SUBJECT TERMS Thermal Stress Heat Heat Stress Monitori 17. SECURITY CLASSIFICATION 18.	human thermoregy Phys: .ng System SECURITY CLASSIFICATION OF THIS PAGE	ilation. A bi ilation. A bi iology ergence	15. NUMBER OF PAGES 10 16. PRICE CODE	

•

.

Standaru	0	~ ~ ~	o pret	-
Prescribed by	ANSI	Std	239-18	
298-102				

THERMAL STRESS IN U.S. AIR FORCE OPERATIONS

Issues Raised by Deployment to the Persian Gulf

Activities related to Desert Shield and Desert Storm produced a high level of interest in heat stress and heat injury to personnel in U.S. Air Force (USAF) operations. Queries focused on required water intake, the possible need for electrolyte supplementation, and the use of work-rest cycles to prevent heat casualties. Advice on prevention of heat casualties was formulated as a "lesson plan" for Physiological Training Officers and was then revised and forwarded to the USAF Surgeon General's office for issue to flight surgeons. These documents were then modified in the light of operational experience and served as the basis for Air Standardization Coordinating Committee Working Party 61 Proposed Advisory Publication 61/114L, Prevention of Heat Casualties during Air Operations in Hot Weather.

A detailed review of climatic data for the Persian Gulf was undertaken to insure that aeromedical guidance was appropriate to actual climatic conditions. Meteorological data were requested from the USAF Environmental Technical Applications Center (ETAC), Scott AFB, Illinois. ETAC provided Operational Climatic Data Summaries for sites as follows: Iraq (6), Israel (4), Jordan (4), Saudi Arabia (10), other locations along the Persian Gulf (8), and one on the Indian Ocean. Special summaries were extracted from the ETAC data base for the following places: Baghdad, Iraq; Riyadh, Saudi Arabia; Kuwait; Dhahran, Saudi Arabia; Sharjah, Oman; and Salalah, Oman. The following variables were analyzed for the six sites: Heat and humidity; Wet Bulb Globe Temperature (WBGT); nightly minimum dry bulb temperature (Tdb); cumulative heat stress (mean degree-hours above 20 °C). The data showed that heat poses potentially serious problems for flying operations for half the year (May through October), and the nature of the heat stress varies widely from extreme, dry heat (>110 °F, 10 % relative humidity (RH)) at Riyadh to more moderate but humid heat (88 °F, 70% RH) at Salalah. Detailed results were formulated as a technical note. Climatic Heat Stress in the Persian Gulf.

Aircrew Heat Stress

Preliminary data were obtained regarding the cooling capacity of the airventilated head and vest units of the Tactical Life Support System (TLSS). This ensemble includes chemical protection, extended-coverage G-trousers, and assisted pressure breathing for protection from altitude and acceleration. The original design included a

1

liquid-cooled garment, which has now been replaced with an air distribution vest worn between the undershirt and the flight suit. Environmental conditions in our experiments were Tdb=28 °C and black globe temperature=35 °C. The subject wore thermistors on the thigh, torso, head and forehead. He walked on a level treadmill for 10 min, then sat for 20 min, repeating the cycle three times. The first 30-min cycle was used to equilibrate the subject to the warm conditions, following which the ventilating air flow was turned on. The following configurations were tested: 1) Control (demist air only), 2) TLSS head ventilation (no vest), and 3) TLSS Head-Vest with vest flow set to 8 or 15 cfm. Thermal comfort data were collected at the end of each 30-min period during the experiment. Results indicated that ventilation with ambient air provides some relief from moderate heat stress, but that higher air flow is not helpful if the blower system raises inlet temperature.

Aircrew Heat Stress Guidance

Experience with the Fighter Index of Thermal Stress (FITS) indicated the need for a more comprehensive index of heat stress for a wide range of aviation scenarios. The general concept is for an open-ended, semi-quantitative scale which can be used to assess the cumulative effects of heat stress over a series of missions. Due to current emphasis on chemical defense scenarios, the initial version was developed for chemical defense clothing and is documented under Work Unit 2729 04 04.

Real-time Heat Stress Monitors

During the summer of 1990, our laboratory conducted informal trials of two noninvasive systems for monitoring heat stress responses. One was a commercially available radio pill with associated antenna and digital recorder; the system was found to have problems with quality control and signal acquisition that rendered it unsatisfactory for either laboratory or field use at this time. The other product used a single chest strap which incorporated electrocardiogram leads and an insulated skin thermistor (estimated core), and required input of subject age group and clothing type. Signals were recorded on a belt-mounted unit which set off "warning" and "cease work" alarms at limits. Comparison with classical measurements of heart rate and rectal temperature (Tre) in nude and heavily clothed working subjects showed that the estimated core temperature varied with external conditions.

Clothing Effects on Human Thermoregulation

It has been stated that personnel working in impermeable protective clothing will have to stop when skin temperature equals or exceeds Tre because this "convergence" implies that physical collapse is imminent. The available data base included 42 experiments in hot environments (Tdb= 29-35 °C) which produced convergence. Subjects continued work for up to 45 min after Tsk \geq Tre, and 29 subjects (70 %) continued work to classical limits (Tre=39 °C and/or HR=HRmax). We conclude that convergence is not an adequate indicator of heat tolerance limits.

Bibliography

Nunneley SA. Climatic heat stress in the Persian Gulf. AL/CFTO Technical Note, 17 January, 1991; 4 pp.

Nunneley SA. Thermal stress and injury. In Fundamentals of Aerospace Medicine, 2nd Edition, edited by B.L. DeHart. Philadelphia: Lea and Febiger (in press), 1991; 27 pp.

Nunneley SA, Bomalaski SH, Antuñano MJ. Thermal convergence is not an endpoint in clothing studies. Aviat. Space Environ. Med. 1991; 62:471 (abstract).

Nunneley SA, Antuñano MJ, Bomalaski SH. Thermal convergence fails to predict heat tolerance limits. Aviat. Space Environ. Med. (in press), 1992; 10 pp.

Nunneley SA, Young AJ, Sowood PJ, Frim J, Kaufman JW. Prevention of heat casualties during air operations in hot weather. ASCC Working Party 61, Proposed Advisory Publication 61/114L, 1990.

Acce	ssion For	
NTIS DTIC Unan Just	GRAAI TAB nownced ification	
By Dist Avai	ribution/	
Dist A-1	Avail and Special	or

3

DTIC QUALITY INSPECTED 3