

AD-A258 282



ARMY RESEARCH LABORATORY



System Checkout of the  
155-mm Short-Barreled Howitzer  
Using Telemetry Projectiles

C. Ruth  
J. Colburn  
J. Tuerk  
J. Bowen  
J. Hewitt  
A. Koszoru

ARL-MR-8

November 1992



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

92-30865



598

## NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

**REPORT DOCUMENTATION PAGE**Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE November 1992	3. REPORT TYPE AND DATES COVERED Final, 1 Jul - 31 Jul 91	
4. TITLE AND SUBTITLE System Checkout of the 155-mm Short-Barreled Howitzer Using Telemetry Projectiles			5. FUNDING NUMBERS PR: 1L162618AH80	
6. AUTHOR(S) C. Ruth, J. Colburn, J. Tuerk, J. Bowen, J. Hewitt, and A. Koszoru				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WT-PE Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-OP-CI-B (Tech Lib) Aberdeen Proving Ground, MD 21005-5066			10. SPONSORING/MONITORING AGENCY REPORT NUMBER  ARL-MR-8	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Firings were conducted in a unique 155-mm short-barreled howitzer to check out the structural integrity of the redesigned support mounts for the weapon. The howitzer system was designed to be advantageous in acquiring pressure and acceleration data from instrumentation onboard the projectile by using simple hardware techniques with no intricate projectile redesign or expensive telemetry components. Data from the firings is presented both on the telemetry and the system integrity.				
14. SUBJECT TERMS howitzers; interior ballistics; telemetry; pressure data; acceleration data; modified howitzers			15. NUMBER OF PAGES 32	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

INTENTIONALLY LEFT BLANK.

# TABLE OF CONTENTS

	<u>Page</u>
LIST OF FIGURES .....	v
ACKNOWLEDGMENTS .....	vii
PREFACE .....	ix
1. INTRODUCTION .....	1
2. TEST COMPONENTS .....	2
2.1 Fixture Construction and Assembly .....	2
2.2 Projectile Design and Gage Mounting Techniques .....	3
2.3 Ammunition Components .....	4
3. RESULTS AND CONCLUSIONS .....	4
4. REFERENCES .....	19
DISTRIBUTION LIST .....	21

UNCLASSIFIED & UNCONTROLLED

<b>Accession For</b>	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

INTENTIONALLY LEFT BLANK.

108-1010-1010  
108-1010-1010  
108-1010-1010  
108-1010-1010  
108-1010-1010  
108-1010-1010  
108-1010-1010  
108-1010-1010  
108-1010-1010  
108-1010-1010

## LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.	Modified 155-mm Short-Barreled Howitzer .....	7
2.	Modified 155-mm Howitzer Tube .....	8
3.	Housing Assemblies for Telemetry Components .....	9
4.	Spindle Pressure and Doppler Radar, Zone 5 .....	10
5.	Onboard Base Pressure and Doppler Radar, Zone 5 .....	11
6.	Onboard Acceleration and Doppler Radar, Zone 5 .....	12
7.	Spindle Pressure and Doppler Radar, Zone 8 .....	13
8.	Onboard Base Pressure and Doppler Radar, Zone 8 .....	14
9.	Onboard Acceleration and Doppler Radar, Zone 8 .....	15
10.	Resistive Pressure vs. Inbore Travel, Zone 5 .....	16
11.	Resistive Pressure vs. Inbore Travel, Zone 8 .....	17

**INTENTIONALLY LEFT BLANK.**



## ACKNOWLEDGMENTS

The authors wish to express their gratitude for the assistance provided by T. Rosenberger, U.S. Army Ballistic Research Laboratory, Interior Ballistics Division, and D. Meier, Dynamic Science Inc., in the test setup and data acquisition phase.

INTENTIONALLY LEFT BLANK.

## PREFACE

The U.S. Army Ballistic Research Laboratory was deactivated on 30 September 1992 and subsequently became a part of the U.S. Army Research Laboratory (ARL) on 1 October 1992.

INTENTIONALLY LEFT BLANK.

## 1. INTRODUCTION

An ongoing and important function of the Interior Ballistics Division (IBD), U.S. Army Ballistic Research Laboratory (BRL), is to provide accurate simulations of the interior ballistic performance of weapon systems (Baer and Frankle 1962). Using the experimental performance measured during a gun firing, an uncomplicated lumped-parameter code such as the IBHVG2 (Anderson and Fickie 1987) can be used to predict nominal values of projectile displacement, velocity, acceleration, and pressure data for slight changes in projectile weight, charge weight, propellant web, parasitics, etc.

With the increasing complexity of both projectile design and propellant formulation and geometry, ballistic simulations have to more accurately predict the interior ballistic performance. In the past, poorly defined parameters such as burning rates and resistance-to-motion were manipulated until satisfactory simulations were achieved. With more complex codes, these parameters have to be accurately determined through experiments.

Initial results on quantifying resistance to projectile motion (resistive pressure) and the governing logic and equations have been documented (Ruth and Evans 1983) at BRL using a specially constructed short-barreled howitzer. The advantages of such a system were reduced muzzle velocity, making projectile and onboard projectile instrumentation easier to recover; easy access to the nose of the projectile for hard-wire instrumentation; simple electronics with hard-wire telemetry; and no intricate nose scoop for collecting the wire from the gun bore. As noted in Ruth and Evans (1983), the resistive pressure can be defined and calculated by using the data from interior ballistics measurements as indicated below:

$$P_f = P_b - \frac{(w \cdot a)}{(g \cdot A)}, \quad (1)$$

where  $P_f$  = Engraving and resistive pressure  
 $P_b$  = Pressure acting on base of the projectile  
 $a$  = Acceleration of the projectile  
 $A$  = Cross-sectional area of the bore  
 $w$  = Projectile weight  
 $g$  = Acceleration due to gravity.

and from the Lagrangian correction for base pressure knowing breech pressure,

$$P_b = P / (1 + c/2w) , \quad (2)$$

where  $P$  = Breech pressure  
 $c$  = Propellant weight  
 $w$  = Projectile weight .

If one measures the base pressure directly using telemetry, the above assumption for calculating base pressure does not have to be made, and a more accurate representation of the resistive profile can be obtained.

In order to expand the understanding of propellant burning during the ignition and early combustion phase for new concepts in propellant design, a 155-mm short-barreled howitzer, similar in concept to the aforementioned 105-mm howitzer, was designed and constructed at BRL. During initial experiments, the howitzer mount was damaged because of higher than expected chamber pressures (pressure continued to rise after projectile exited from tube and was transversing finger support mounts) and possible structural (hidden) flaws in the steel. Repeated firings apparently weakened the side support struts connecting the howitzer to the recoil system. After a redesign and repair was done, the howitzer was field-tested for system structural compatibility.

To enlarge upon the 105-mm howitzer database (Ruth and Evans 1983), a very simple hard-wire telemetry system was devised for the checkout firings of the redesigned howitzer in an attempt to gain onboard data in a projectile fired from a higher velocity 155-mm system. Both the 105-mm and 155-mm systems were similar in that the projectile extended out the front of the gun bore so as to simplify hard-wire telemetry hookups. Although the telemetry hookups in the 155-mm projectiles were fairly fragile for these acceleration loads, the inexpensive setup and the onboard data that might be recorded justified the attempt to record the onboard pressure and acceleration data.

## 2. TEST COMPONENTS

2.1 Fixture Construction and Assembly. The modified 155-mm M185 howitzer tube used for launching projectiles; the method for attaching the tube to the modified M155 howitzer tube so that a

standard M174 recoil mechanism could be used; the technique for measuring onboard pressure and acceleration during early projectile motion; as well as the method of recovering expelled, extinguished propellant after ignition and early combustion for chemical and physical analysis were all BRL innovations. Fabrication of the component parts for the howitzer and gun interfaces was done at the U.S. Army Combat Systems Test Activity (CSTA) machine shop.

A diagram of the 155-mm short-barreled howitzer is shown in Figure 1. Projectile travel was about 100 mm rather than the 5,098 mm in a standard howitzer. Assembly of this unique weapon was accomplished in several stages (refer to Figure 1 to match components to the following letters in parentheses). First, the breech and shortened tube from a standard M185 howitzer (A) were threaded into a unique breech ring assembly (B) which was in turn welded to a M155 tube (C) by a steel interface union (D). The distance (E) between the breech of the 155-mm tube and the rear plate of the steel interface union was long enough to allow any 155-mm projectile to be loaded into the short-barreled howitzer. The rear plate of the interface union (D) was connected to an adapter (F) which slipped over the bore of the 155-mm howitzer (C). The instrumented projectile (G) when seated in the howitzer had its noseplate and forward ogive outside of the gun tube, thereby minimizing hard-wired hookup complexities. By using this system, the 155-mm short-barreled howitzer could be fired using the standard recoil of a M174 mounted in the upper carriage from a 155-mm M59 gun. Excessive muzzle blast from the weapon was well in front of the recoil and equilibrator systems and would thus cause no structural damage.

The shortened M185 howitzer tube was instrumented at three locations with Kistler 607C3 pressure gages as shown in the schematic of Figure 2. Gages were located in the breech spindle, two each (P1 and Pr), two each (P3l and P3r) at 13.0 cm from the rear face of the tube (RFT); two each (P4l and P4r) at 13.4 cm from the RFT; and one each (P5) at 13.8 cm from the RFT. To accurately measure ignition delay and record data online, the standard lanyard-operated, spring-driven firing pin was replaced by a gas-activated firing pin (Rocchio, Hartman, and Gerri 1979). The gas necessary to drive the modified firing pin into the M82 percussion primer was obtained from an M52A3B1 electric detonation cap.

**2.2 Projectile Design and Gage Mounting Technique.** Two inert 155-mm M101 projectiles were modified by sawing them approximately 36 cm from the base of the projectile into two sections. The interior hemispherical base surface of each projectile was then machined to a flat, cylindrical surface for mounting the hard-wire telemetry assembly. After machining, drilling, and threading the projectile base

for mounting bolts to hold the telemetry assembly, the two parts of each projectile were welded back together.

The telemetry packages consisted of a housing assembly containing two piezoelectric transducers. Each of the housing assemblies was fabricated in three parts (see Figure 3 to match components to the following letters in parentheses). The pressure section (A) contained a pressure gage (B) mounted to measure the projectile base pressure as well as the mounting assembly to attach this section to the projectile body with the mounting bolts. The PCB pressure transducers used for the two tests were Model 109-M31 set for a top step of 140 MPa and Model 109M19 with a top step of 275 MPa. The acceleration section (C), which was threaded to the pressure section, contained an acceleration gage (D) isolated from hot propellant gases. In addition, a steel plug (E) was threaded to the top of the acceleration cavity to protect the gage from the projectile filler material. The PCB Piezotronics accelerators used for the two tests (Model 305A03) were set for a top step of 10,000 G's (98.2 km/s/s). The electrical leads from the pressure and acceleration gages were threaded through holes drilled in the two assembly sections. The leads were loosely looped in the body of the projectile and then threaded through a hole drilled in a wire capture scoop. Prior to threading the capture scoop into the fuze adapter, the projectiles were filled with high-temperature wax so that each projectile would match the weight of current HE rounds. The telemetry wires on the outside of the projectile were tied to a lug on the capture scoop to prevent them from being pulled free from the gages in the projectile. During firing setup, this data link was drawn taut forward of the projectile and secured to the radar reflector stand mounted directly in front of the howitzer. This technique aligned the telemetry wires with the axis of the howitzer during firing and hopefully would allow the projectile scoop to preserve the data link during the interior ballistic cycle.

2.3 Ammunition Components. For the two firings in this test, a low-pressure M4A2 Zone 5 charge and a high-pressure M203 Zone 8 charge were used. The main reason for using these two zoned charges was to completely check the design strength of the modified gun. It was realized that these acceleration loads would stress the limits of the hard-wire telemetry link and possibly destroy the data links early in the ballistic cycle.

### 3. RESULTS AND CONCLUSIONS

The short-barreled 155-mm howitzer was test-fired at two different rates-of-loading using the M4A2 Zone 5 and M203 Zone 8 charges. No adverse effects to the redesigned mounting structure supporting



the 155-mm short howitzer to the 155-mm standard howitzer were observed, and the system is again functional for ongoing research experiments in the BRL. Although the inexpensive hard-wire data links for obtaining base pressure and accelerometer functioned for both charge loadings, the links broke very early in the ballistic cycle for both charges.

The results of the two firings are noted in Table 1. Plots of spindle pressure and Doppler radar, onboard base pressure and Doppler radar, and onboard acceleration and Doppler radar, all as a function of time, are shown for the Zone 5 firing in Figures 4–6, respectively. For the Zone 8 firing, the same series of plots are shown in Figures 7–9, respectively.

For the Zone 5 charge, peak spindle pressure was 70 MPa at 102 ms. The telemetry data links for both onboard projectile pressure and acceleration did not survive the entire interior ballistic cycle. Onboard base pressure was 52 MPa and spindle pressure was 65 MPa when the data link broke. During the engraving cycle for the metallic rotating band, an initial acceleration peak of 3.9 km/s/s was observed at approximately 1 cm of projectile motion. As the projectile went through the engraving process, the acceleration rapidly decayed to zero acceleration at approximately 1 cm of travel. After engraving was completed, the acceleration rapidly increased. At an acceleration of 14.7 km/s/s, the data link broke. Using the Equations 1 and 2, and setting the resistive pressure ( $P_r$ ) to zero, a "no loss" maximum acceleration can be calculated. This calculated acceleration (30.6 km/s/s) assumes no energy was expended in the engraving of the rotating band or bore friction between the band and gun bore and would be higher than the measured peak onboard acceleration.

For the Zone 8 firings, heat from propellant gases affected most of the gages as noted by the baseline returns below the zero baseline. If the heat occurred late into the ballistic cycle, the maximum peak pressure would not be affected. Onboard base pressure reached 40 MPa before the data link broke. During the engraving cycle, an initial acceleration peak of 15.7 km/s/s occurred just as the projectile seated itself into the forcing cone. As it moved through the forcing cone, there was a peak engraving load of 15.72 km/s/s with a momentary pause just after engraving. Then the acceleration increased rapidly to a peak of 41.2 km/s/s before the data link broke. Again, this was much less than the calculated "no loss" acceleration of 113.5 km/s/s.

Using the onboard pressure-time and acceleration-time data from the online data acquisition and Equations 1 and 2, a resistive pressure-vs.-displacement plot can be generated at both zone levels, as

Table 1. Projectile, Charge, and Firing Data

	Round 1	Round 2
Projectile Weight (kg)	44.01	44.01
Charge Type	M4A2, Zone 5	M203, Zone 8
Gage Position	Pressure (MPa) [Time] (ms)	Pressure (MPa) [Time] (ms)
Spindle (left)	74 [100.9]	301 [48.2]
Spindle (right)	70 [100.9]	298 [48.2]
P3 (left)	67 [100.5]	220 [47.9] <sup>c</sup>
P3 (right)	65 [100.5]	235 [47.9] <sup>c</sup>
P4 (left)	66 [100.5]	235 [47.9] <sup>c</sup>
P4 (right)	66 [100.5]	235 [47.9] <sup>c</sup>
P5	67 [100.5]	240 [47.9]
Peak Base Pressure before telemetry link was lost	50 [98.8]	40 [47.8]
Acceleration (km/s/s)	—	—
Onboard peak engraving	3.9 [94.8] <sup>a</sup>	15.7 [45] <sup>a</sup>
Peak acceleration before telemetry link was lost	14.7 [98.5]	41.2 [46]
No loss (calculated)	30.6 [100] <sup>b</sup>	113.5 [48.2] <sup>b</sup>
Muzzle Velocity (m/s)	—	—

<sup>a</sup> Value of onboard peak acceleration during rotating band engraving (see plots).

<sup>b</sup> Value of calculated peak acceleration using peak spindle pressure, gun, and projectile inputs from the formula given in the text.

<sup>c</sup> Plots indicate heat to these pressure gages at some time in the ballistic cycle.

shown in Figures 10 and 11. Although the telemetry data links are broken early in the ballistic cycle, the peak engraving pressure and some of the resistive pressure is detailed. Both the character and level of the curves are in agreement with the data generated from data (Evans 1985) telemetered from full-up gun firings.




Figure 1. Modified 155-mm Short-Barreled Howitzer.




Figure 2. Modified 155-mm Howitzer Tube.




Figure 3. Housing Assemblies for Telemetry Components.




Figure 4. Spindle Pressure and Doppler Radar, Zone 5.




Figure 5. Onboard Base Pressure and Doppler Radar, Zone 5.




Figure 6. Onboard Acceleration and Doppler Radar, Zone 5.






Figure 7. Spindle Pressure and Doppler Radar, Zone 8.




Figure 8. Onboard Base Pressure and Doppler Radar, Zone 8.




Figure 9. Onboard Acceleration and Doppler Radar, Zone 8.




Figure 10. Resistive Pressure vs. Inbore Travel, Zone 5.




Figure 11. Resistive Pressure vs. Inbore Travel, Zone 8.

INTENTIONALLY LEFT BLANK.

#### 4. REFERENCES

- Anderson, R. D., and K. D. Fickie. "IBHVG2 - A User's Guide." BRL-TR-2829, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, July 1987.
- Baer, P. G., and J. M. Frankle. "The Simulation of Interior Ballistic Performance of Guns by Digital Computer Program." BRL-TR-1183, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, December 1962.
- Evans, J. W. "Measurement of Interior Ballistic Performance Using FM/FM Radio Telemetry Techniques." BRL-TR-2699, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, December 1985.
- Rocchio, J. J., R. A. Hartman, and N. J. Gerri. "An Electric Primer-Operated Firing Pin Actuator for Large Caliber Guns." BRL-TR-02897, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, January 1979.
- Ruth, C. R., and J. W. Evans. "A Short-Barreled 105-mm Howitzer for Interior Ballistic Studies." BRL-MR-03238, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, January 1983.

**INTENTIONALLY LEFT BLANK.**



<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	1	Commander U.S. Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander U.S. Army Materiel Command ATTN: AMCAM 5001 Eisenhower Ave. Alexandria, VA 22333-0001	1	Commander U.S. Army Tank-Automotive Command ATTN: ASQNC-TAC-DIT (Technical Information Center) Warren, MI 48397-5000
1	Director U.S. Army Research Laboratory ATTN: AMSRL-D 2800 Powder Mill Rd. Adelphi, MD 20783-1145	1	Director U.S. Army TRADOC Analysis Command ATTN: ATRC-WSR White Sands Missile Range, NM 88002-5502
1	Director U.S. Army Research Laboratory ATTN: AMSRL-OP-CI-A, Tech Publishing 2800 Powder Mill Rd. Adelphi, MD 20783-1145	1	Commandant U.S. Army Field Artillery School ATTN: ATSF-CSI Ft. Sill, OK 73503-5000
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-IMI-I Picatinny Arsenal, NJ 07806-5000	(Class. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000	(Unclas. only) 1	Commandant U.S. Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
1	Director Benet Weapons Laboratory U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050	1	WL/MNOI Eglin AFB, FL 32542-5000  <u>Aberdeen Proving Ground</u>
(Unclas. only) 1	Commander U.S. Army Rock Island Arsenal ATTN: SMCRI-TL/Technical Library Rock Island, IL 61299-5000	2	Dir, USAMSA ATTN: AMXSY-D AMXSY-MP, H. Cohen
1	Director U.S. Army Aviation Research and Technology Activity ATTN: SAVRT-R (Library) M/S 219-3 Ames Research Center Moffett Field, CA 94035-1000	1	Cdr, USATECOM ATTN: AMSTE-TC
		1	Dir, ERDEC ATTN: SCBRD-RT
		1	Cdr, CBDA ATTN: AMSCB-CI
		1	Dir, USARL ATTN: AMSRL-SL-I
		10	Dir, USARL ATTN: AMSRL-OP-CI-B (Tech Lib)

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	C.I.A. 01R/DB/Standard Washington, DC 20505	14	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-AEE SMCAR-AEE-B, A. Beardell D. Downs S. Einstein S. Westley S. Bernstein J. Rutkowski B. Brodman R. Cirincione A. Grabowsky P. Hui J. O'Reilly P. O'Reilly SMCAR-AES, S. Kaplowitz, Bldg. 321 Picatinny Arsenal, NJ 07806-5000
1	Director U.S. Army Ballistic Missile Defense Systems Command Advanced Technology Center P. O. Box 1500 Huntsville, AL 35807-3801		
1	Chairman DOD Explosives Safety Board Room 856-C Hoffman Bldg. 1 2461 Eisenhower Ave. Alexandria, VA 22331-0600		
1	Department of the Army Office of the Product Manager 155mm Howitzer, M109A6, Paladin ATTN: SFAE-AR-HIP-IP, Mr. R. De Kleine Picatinny Arsenal, NJ 07806-5000	1	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-HFM, E. Barrieres Picatinny Arsenal, NJ 07806-5000
2	Commander Production Base Modernization Agency U.S. Army Armament Research, Development, and Engineering Center ATTN: AMSMC-PBM, A. Siklosi AMSMC-PBM-E, L. Laibson Picatinny Arsenal, NJ 07806-5000	1	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-FSA-T, M. Salsbury Picatinny Arsenal, NJ 07806-5000
3	PEO-Armaments Project Manager Tank Main Armament Systems ATTN: AMCPM-TMA/K. Russell AMCPM-TMA-105 AMCPM-TMA-120, C. Roller Picatinny Arsenal, NJ 07806-5000	1	Commander, USACECOM R&D Technical Library ATTN: ASQNC-ELC-IS-L-R, Myer Center Fort Monmouth, NJ 07703-5301
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-CCD, D. Spring SMCAR-CCH-V, C. Mandala Picatinny Arsenal, NJ 07806-5000	1	Commander U.S. Army Harry Diamond Laboratories ATTN: SLCHD-TA-L 2800 Powder Mill Rd. Adelphi, MD 20783-1145
		1	Commandant U.S. Army Aviation School ATTN: Aviation Agency Fort Rucker, AL 36360

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Program Manager U.S. Army Tank-Automotive Command ATTN: AMCPM-ABMS, T. Dean (2 cps) Warren, MI 48092-2498
1	Program Manager U.S. Army Tank-Automotive Command Fighting Vehicles Systems ATTN: SFAE-ASM-BV Warren, MI 48092-2498
1	Project Manager Abrams Tank System ATTN: SFAE-ASM-AB Warren, MI 48397-5000
1	Director HQ, TRAC RPD ATTN: ATCD-MA Fort Monroe, VA 23651-5143
2	Director U.S. Army Materials Technology Laboratory ATTN: SLCMT-ATL (2 cps) Watertown, MA 02172-0001
1	Commander U.S. Army Research Office ATTN: Technical Library P.O. Box 12211 Research Triangle Park, NC 27709-2211
1	Commander U.S. Army Belvoir Research and Development Center ATTN: STRBE-WC Fort Belvoir, VA 22060-5006
1	Director U.S. Army TRAC-Ft. Lee ATTN: ATRC-L, Mr. Cameron Fort Lee, VA 23801-6140
1	Commandant U.S. Army Command and General Staff College Fort Leavenworth, KS 66027

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Commandant U.S. Army Special Warfare School ATTN: Rev and Trng Lit Div Fort Bragg, NC 28307
3	Commander Radford Army Ammunition Plant ATTN: SMCAR-QA/HI LIB (3 cps) Radford, VA 24141-0298
1	Commander U.S. Army Foreign Science and Technology Center ATTN: AMXST-MC-3 220 Seventh Street, NE Charlottesville, VA 22901-5396
2	Commander Naval Sea Systems Command ATTN: SEA 62R SEA 64 Washington, DC 20362-5101
1	Commander Naval Air Systems Command ATTN: AIR-954-Technical Library Washington, DC 20360
1	Naval Research Laboratory Technical Library Washington, DC 20375
2	Commandant U.S. Army Field Artillery Center and School ATTN: ATSF-CO-MW, E. Dublisky (2 cps) Fort Sill, OK 73503-5600
1	Office of Naval Research ATTN: Code 473, R. S. Miller 800 N. Quincy Street Arlington, VA 22217-9999
3	Commandant U.S. Army Armor School ATTN: ATZK-CD-MS, M. Falkovitch (3 cps) Armor Agency Fort Knox, KY 40121-5215

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Commander U.S. Naval Surface Warfare Center ATTN: J. P. Consaga C. Gotzmer Indian Head, MD 20640-5000
4	Commander Naval Surface Warfare Center ATTN: Code 730 Code R-13, K. Kim R. Bernecker H. Sandusky Silver Spring, MD 20903-5000
2	Commanding Officer Naval Underwater Systems Center ATTN: Code 5B331, R. S. Lazar Technical Library Newport, RI 02840
1	Director Benet Weapons Laboratories ATTN: SMCAR-CCB-RA, G. P. O'Hara Watervliet, NY 12189-4050
4	Commander Dahlgren Division Naval Surface Warfare Center ATTN: Code G30, Guns and Munitions Division Code G301, D. Wilson Code G32, Gun Systems Branch Code E23, Technical Library Dahlgren, VA 22448-5000
3	Commander Naval Weapons Center ATTN: Code 388, C. F. Price Code 3895, T. Parr Information Science Division China Lake, CA 93555-6001
1	OSD/SDIO/IST ATTN: Dr. Len Caveny Pentagon Washington, DC 20301-7100

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
3	Commander Indian Head Division Naval Surface Warfare Center ATTN: Code 610, T. C. Smith K. Rice Technical Library Indian Head, MD 20640-5035
1	OLAC PL/TSTL ATTN: D. Shiplett Edwards AFB, CA 93523-5000
1	AFATL/DLYV Eglin AFB, FL 32542-5000
1	AFATL/DLXP Eglin AFB, FL 32542-5000
1	AFATL/DLJE Eglin AFB, FL 32542-5000
1	AFELM, The Rand Corporation ATTN: Library D 1700 Main Street Santa Monica, CA 90401-3297
3	AAI Corporation ATTN: J. Hebert J. Frankle D. Cleveland P.O. Box 126 Hunt Valley, MD 21030-0126
3	AL/LSCF ATTN: J. Levine L. Quinn T. Edwards Edwards AFB, CA 93523-5000
3	ARMTEC Defense Products Company ATTN: S. J. Dyer N. S. Cielik Tech Library 85-901 Avenue 53 Coachella, CA 92236
1	AVCO Everett Research Laboratory ATTN: D. Stuckler 2385 Revere Beach Parkway Everett, MA 02149-5936

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	CPIA - JHU ATTN: Harry J. Hoffman 10630 Little Patuxent Parkway, Suite 202 Columbia, MD 21044-3200
1	General Electric Company Tactical Systems Department ATTN: J. Mandzy 100 Plastics Ave. Pittsfield, MA 01201-3698
1	IITRI ATTN: M. J. Klein 10 W. 35th Street Chicago, IL 60616-3799
1	Hercules, Inc. Allegheny Ballistics Laboratory ATTN: William B. Walkup P.O. Box 210 Rocket Center, WV 26726
1	Hercules, Inc. Radford Army Ammunition Plant ATTN: E. Hibshman Radford, VA 24141-0299
1	Hercules, Inc. Hercules Plaza ATTN: B. M. Riggleman Wilmington, DE 19894
3	Director Lawrence Livermore National Laboratory ATTN: L-355, A. Buckingham M. Finger L-324, M. Constantino P.O. Box 808 Livermore, CA 94550-0622
1	Olin Corporation Badger Army Ammunition Plant ATTN: F. E. Wolf Baraboo, WI 53913

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
3	Olin Ordnance ATTN: E. J. Kirschke A. F. Gonzalez D. W. Worthington P.O. Box 222 St. Marks, FL 32355-0222
1	Olin Ordnance ATTN: H. A. McElroy 10101 9th Street, North St. Petersburg, FL 33716
1	Paul Gough Associates, Inc. ATTN: Dr. Paul S. Gough 1048 South Street Portsmouth, NH 03801-5423
1	Physics International Library ATTN: H. Wayne Wampler P.O. Box 5010 San Leandro, CA 94577-0599
1	Princeton Combustion Research Laboratories, Inc. ATTN: Dr. Martin Summerfield Princeton Corporate Plaza 11 Deerpark Dr., Bldg. IV, Suite 119 Monmouth Junction, NJ 08852
2	Rockwell International Rocketdyne Division ATTN: BA08, J.E. Flanagan J. Gray 6633 Canoga Ave. Canoga Park, CA 91303-2703
1	Sverdrup Technology, Inc. ATTN: Dr. John Deur 2001 Aerospace Parkway Brook Park, OH 44142
2	Thiokol Corporation Elkton Division ATTN: R. Biddle Technical Library P.O. Box 241 Elkton, MD 21921-0241

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Veritay Technology, Inc. ATTN: E. Fisher 4845 Millersport Highway East Amherst, NY 14501-0305	3	Georgia Institute of Technology School of Aerospace Engineering ATTN: B.T. Zim E. Price W.C. Strahle Atlanta, GA 30332
1	Universal Propulsion Company ATTN: H. J. McSpadden 25401 North Central Ave. Phoenix, AZ 85027-7837	1	Institute of Gas Technology ATTN: D. Gidaspow 3424 S. State Street Chicago, IL 60616-3896
1	Battelle ATTN: TACTEC Library, J.N. Huggins 505 King Ave. Columbus, OH 43201-2693	1	The Johns Hopkins University/CPIA ATTN: T. Christian 10630 Little Patuxent Parkway, Suite 202 Columbia, MD 21044-3200
1	Brigham Young University Department of Chemical Engineering ATTN: M. Beckstead Provo, UT 84601	1	Massachusetts Institute of Technology Department of Mechanical Engineering ATTN: T. Toong 77 Massachusetts Ave. Cambridge, MA 02139-4307
1	California Institute of Technology 204 Karman Laboratory Main Stop 301-46 ATTN: F.E.C. Culick 1201 E. California Street Pasadena, CA 91109	1	Pennsylvania State University Department of Mechanical Engineering ATTN: V. Yang University Park, PA 16802-7501
1	California Institute of Technology Jet Propulsion Laboratory ATTN: L. D. Strand, MS 125-224 4800 Oak Grove Drive Pasadena, CA 91109-8099	1	Pennsylvania State University Department of Mechanical Engineering ATTN: K. Kuo University Park, PA 16802-7501
1	University of Illinois Department of Mechanical/Industrial Engineering ATTN: H. Krier 144 MEB; 1206 N. Green Street Urbana, IL 61801-2978	1	Pennsylvania State University Assistant Professor Department of Mechanical Engineering ATTN: Dr. Stefan T. Thynell 219 Hallowell Building University Park, PA 16802-7501
1	University of Massachusetts Department of Mechanical Engineering ATTN: K. Jakus Amherst, MA 01002-0014	1	Pennsylvania State University Director, Gas Dynamics Laboratory Department of Mechanical Engineering ATTN: Dr. Gary S. Settles 303 Mechanical Engineering Building University Park, PA 16802-7501
1	University of Minnesota Department of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55414-3368		

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	SRI International Propulsion Sciences Division ATTN: Technical Library 333 Ravenwood Ave. Menlo Park, CA 94025-3493	1	Washington State University Department of Mechanical Engineering ATTN: C. T. Crowe Pullman, WA 99163-5201
1	Rensselaer Polytechnic Institute Department of Mathematics Troy, NY 12181	1	Alliant Techsystems, Inc. ATTN: Robert E. Tompkins 7225 Northland Dr. Brooklyn Park, MN 55428
2	Director Los Alamos Scientific Laboratory ATTN: T3, D. Butler M. Division, B. Craig P.O. Box 1663 Los Alamos, NM 87544	1	Alliant Techsystems, Inc. ATTN: J. Kennedy 7225 Northland Drive Brooklyn Park, MN 55428
1	General Applied Sciences Laboratory ATTN: J. Erdos 77 Raynor Ave. Ronkonkama, NY 11779-6649	1	Science Applications, Inc. ATTN: R. B. Edelman 23146 Cumorah Crest Drive Woodland Hills, CA 91364-3710
1	Battelle PNL ATTN: Mr. Mark Garnich P.O. Box 999 Richland, WA 99352	1	Battelle ATTN: Mr. Victor Levin 505 King Ave. Columbus, OH 43201-2693
1	Stevens Institute of Technology Davidson Laboratory ATTN: R. McAlevy III Castle Point Station Hoboken, NJ 07030-5907	1	Allegheny Ballistics Laboratory Propulsion Technology Department Hercules Aerospace Company ATTN: Mr. Thomas F. Farabaugh P.O. Box 210 Rocket Center, WV 26726
1	Rutgers University Department of Mechanical and Aerospace Engineering ATTN: S. Temkin University Heights Campus New Brunswick, NJ 08903	1	MBR Research Inc. ATTN: Dr. Moshe Ben-Reuven 601 Ewing St., Suite C-22 Princeton, NJ 08540
1	University of Southern California Mechanical Engineering Department ATTN: OHE200, M. Gerstein Los Angeles, CA 90089-5199		<u>Aberdeen Proving Ground</u>
1	University of Utah Department of Chemical Engineering ATTN: A. Baer Salt Lake City, UT 84112-1194	1	Cdr, USACSTA ATTN: STECS-PO, R. Hendricksen

INTENTIONALLY LEFT BLANK.



## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number ARL-MR-8 Date of Report November 1992
2. Date Report Received \_\_\_\_\_
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_
6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD  
ADDRESS

\_\_\_\_\_  
Organization


\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

DEPARTMENT OF THE ARMY



OFFICIAL BUSINESS

**BUSINESS REPLY MAIL**  
FIRST CLASS PERMIT No 0001, APG, MD

Postage will be paid by addressee

NO POSTAGE  
NECESSARY  
IF MAILED  
IN THE  
UNITED STATES



Director  
U.S. Army Research Laboratory  
ATTN: AMSRL-OP-CI-B (Tech Lib)  
Aberdeen Proving Ground, MD 21005-5066