

AD-A279 118



NBS CIRCULAR 556

①

N-35385

# Thermal Conductivity of Metals and Alloys at Low Temperatures

**COPY 4**

## A Review of the Literature

**DTIC**  
**S** ELECTE **D**  
MAY 09 1994  
**F**

**LIBRARY COPY**

FEB 13 1957

LE [REDACTED]  
CLEV [REDACTED]

This document has been approved for public release and sale; its distribution is unlimited.

**UNITED STATES DEPARTMENT OF COMMERCE**

**NATIONAL BUREAU OF STANDARDS**

94-13744



1208

**94 5 05 188**

## **PERIODICALS OF THE NATIONAL BUREAU OF STANDARDS**

The National Bureau of Standards is engaged in fundamental and applied research in physics, chemistry, mathematics, and engineering. Projects are conducted in thirteen fields: electricity, optics and metrology, heat and power, atomic and radiation physics, chemistry, mechanics, organic and fibrous materials, metallurgy, mineral products, building technology, applied mathematics, electronics, and radio propagation. The Bureau has custody of the national standards of measurement and conducts research leading to the improvement of scientific and engineering standards and of techniques and methods of measurement. Testing methods and instruments are developed; physical constants and properties of materials are determined; and technical processes are investigated.

### **JOURNAL OF RESEARCH**

The Journal presents research papers by authorities in the specialized fields of physics, mathematics, chemistry, and engineering. Complete details of the work are presented, including laboratory data, experimental procedures, and theoretical and mathematical analysis. Annual subscription: domestic, \$5.50; foreign, \$6.75.

### **TECHNICAL NEWS BULLETIN**

Summaries of current research at the National Bureau of Standards are published each month in the Technical News Bulletin. The articles are brief, with emphasis on the results of research, chosen on the basis of their scientific or technologic importance. Lists of all Bureau publications during the preceding month are given, including Research Papers, Handbooks, Applied Mathematics Series, Applied Mathematics Series, Building Materials and Structures Reports, Miscellaneous Publications, and Circulars. Each issue contains 12 or more two-column pages; illustrated. Annual subscription: domestic, \$1.00; foreign, \$1.35.

### **BASIC RADIO PROPAGATION PREDICTIONS**

The Predictions provide the information necessary for calculating the best frequencies for communication between any two points in the world at any time during the given month. The data are important to all users of long-range radio communications and navigation, including broadcasting, airline, steamship, and wireless services, as well as to investigators of radio propagation and ionosphere. Each issue, covering a period of one month, is released three months in advance and contains 16 large pages, including pertinent charts, drawings, and tables. Annual subscription: domestic, \$1.00; foreign, \$1.25.

---

~~Order all publications from the Superintendent of Documents  
U. S. Government Printing Office, Washington 25, D. C.~~

# Thermal Conductivity of Metals and Alloys at Low Temperatures

## A Review of the Literature

Robert L. Powell and William A. Blanpied



Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

National Bureau of Standards Circular 556

Issued September 1, 1954

## Preface

Accurate data on the thermal conductivity of materials of construction at low temperatures are essential in the design of cyrogenic equipment. Such data on pure metals also have important applications in basic physics.

This Circular is issued to satisfy the need for a complete and authoritative compilation of the useful data on thermal conductivity at low temperatures given in the widely scattered and extensive literature on the subject. Although the Circular is not primarily a critical compilation, the text indicates a method that might be used in choosing between conflicting data.

It will be noted that there are wide unexplored regions; much experimental work remains to be done. It is hoped, therefore, that this Circular will stimulate additional measurements and indicate the areas in which data are most needed.

A. V. ASTIN, *Director.*

C-14338

## Contents

Preface .....	III
1. Introduction .....	1
1.1. Scope and arrangement.....	1
2. Figures and tables.....	2
2.1. List .....	2
2.2. Metallic elements .....	3
2.3. Alloys and commercial metals.....	38
2.4. Dielectric crystals .....	56
3. Bibliography .....	64

# Thermal Conductivity of Metals and Alloys at Low Temperatures

## A Review of the Literature<sup>†</sup>

Robert L. Powell and William A. Blanpied\*

An extensive compilation is given of the measured values of thermal conductivity for metals and alloys from room temperature down to approximately 0° K. The more extensive and important data are plotted in 48 graphs. The tables and graphs for the metallic elements and alloys are essentially complete for literature reference from 1900 to early 1954. For comparison, several graphs and tables are given for some representative dielectrics.

### 1. Introduction

#### 1.1. Scope and Arrangement

The thermal conductivity values of three types of solids are presented: (1) metallic elements, (2) alloys, and (3) dielectrics. Very little discussion is presented on the qualitative theories or significance of the various experiments. Recent articles, as indicated under each material, usually will contain comments on these aspects of conductivity. Under "metallic elements," the materials are arranged by periodic groups, beginning with the alkali metals. Under "alloys," the materials are arranged in this same manner by major component. In group 3, several dielectrics are included for comparison. A list of the figures and tables is given in section 2.1.

The professional abstract and leading research journals were searched for references dating from 1900 to the spring of 1954. It is felt that the compilation is complete for the metals and essentially complete for the alloys, but only a few representative references are given for the dielectrics. Conductivity values were collected for the temperature range approximately 0° to 300° K. Many of the references contain information for room temperature only, and conductivity values from these are given in the tables only.

The letters at the left end of the curves are a code to the names of the authors. The symbols at the right end of the curves indicate the material tested. Conductivity values in the graphs and tables are given in units of watts

per centimeter degree Kelvin (except for a few, which are in milliwatts per centimeter degree Kelvin). A table of conversion factors is given. Arrows on the bottom of the graphs indicate the normal boiling points of helium, hydrogen, and nitrogen, and the melting point of ice, respectively. A bibliography (nearly all dated after 1900) is included at the end of the Circular. It is shown in the tables when other properties of the samples have been measured, such as electrical resistance, thermal electromotive force, and specific heat, which are symbolized by R, emf, and C<sub>p</sub>, respectively.

The units in the tables and graphs are usually watts per centimeter degree Kelvin. These may be converted to other systems of units by use of the following factors:

To convert to—	Multiply by—
Cal/cm deg K	0.239
Btu/ft hr deg F	57.8
Btu in/ft <sup>2</sup> hr deg F	693

The preparation of this Circular required the assistance and cooperation of many. Foremost among them was Charles A. Meizner, who plotted most of the graphs and analyzed some of the original research papers. The cooperation of the many authors and manufacturers who supplied reprints of their articles and manuals for use in this study is acknowledged.

<sup>†</sup>This work was supported by funds from the U. S. Atomic Energy Commission.

\*Present address: Yale University, New Haven, Conn.

## 2. Figures and Tables

### 2.1. List

#### METALLIC ELEMENTS

Material	Figures		Tables (page)
	Number	Page	
Aluminum	3, 3a	8, 9	8
Antimony	20	36	36
Beryllium	2	6	6
Bismuth	20	36	36, 37
Cadmium	15, 14a	27, 26	26
Carbon (graphite)	17	30	30
Cerium	21	37	37
Cobalt	8, 9	16, 17	17
Copper	11, 11a	20, 21	20, 21
Gallium	16	29	29
Germanium	18, 19a	31, 35	31
Gold	13, 12a	24, 23	24
Indium	16	29	29
Iridium	10, 10a	18, 19	19
Iron	8, 9	16, 17	16
Lanthanum	--	--	9
Lead	19, 19a	34, 35	34
Lithium	1	5	5
Magnesium	2, 2a	6, 7	6, 7
Manganese	7	14	15
Mercury	15, 15a	27, 28	27
Molybdenum	6, 6a	12, 13	12
Nickel	8, 9	16, 17	17
Niobium	5	11	11
Paladium	10, 10a	18, 19	18
Platinum	10, 10a	18, 19	19
Potassium	1	5	5
Rhodium	10, 10a	18, 19	18
Silicon	--	--	30
Silver	12, 12a	22, 23	22
Sodium	1	5	5
Tantalum	5	11	11
Tellurium	21	37	37
Thallium	16	29	29
Tin	18, 18a, 18b	31, 32, 33	32
Titanium	4	10	10
Tungsten	6, 6a	12, 13	12, 13
Uranium	21	37	37
Vanadium	5	11	11
Zinc	14, 14a	25, 26	25
Zirconium	4	10	10

#### ALLOYS

Material	Figures		Tables (page)
	Number	Page	
Alkali metal	--	--	38
Aluminum	22	40	39, 40, 41
Antimony	29	54	55
Beryllium	--	--	38
Bismuth	29, 29a	54, 55	55
Cadmium	29	54	53
Chromium	--	--	42
Copper	27, 29a	49, 55	48, 49, 50, 51
Copper-nickel	28, 29a	51, 55	51, 52
Gold	26	47	52, 53
Indium	29, 29a	54, 55	53
Iron:			
Carbon steel	23, 24	43, 44	42
Deoxidized steels	24	44	45
Silicon steels	--	--	43
Corrosion resisting steels	23, 24	43, 44	43, 44, 45
Lead	29, 29a	54, 55	54
Magnesium	2a	7	38, 39
Mercury	--	--	53
Nickel	25	46	45, 46
Palladium	26	47	47
Platinum	26	47	47, 48
Silver	26	47	52
Thallium	29, 29a	54, 55	53
Tin	18a, b	32, 33	53
Titanium	29	54	41
Tungsten	--	--	41
Zinc	--	--	53

#### DIELECTRICS

Beryllia	32	60	60
Diamond	30, 30a	57, 58	57
Disordered dielectrics	33, 33a	62, 63	62
Ionic crystals	32, 32a	60, 61	60
Miscellaneous	--	--	56
Quartz	31, 30a	59, 58	59
Sapphire	30, 30a, 32	57, 58, 60	57

## 2.2. Metallic Elements

The variations of the thermal conductivities of metallic elements with temperature are given in figures 1 to 21. The main figures (those without a or b) have the higher temperature curves; usually the temperature range 4° to 300° K. When there is sufficient data in the liquid-helium range, there is a supplementary graph for the range from approximately 0° to 5° or 10° K. The graphs are arranged by periodic groups, beginning with the alkali metals. A summary table is included for each graph, giving for each element a list of references to research papers on the thermal conductivity of the element. The first column contains the chemical symbol and the property or composition identification on the curves if the data for the author reference are plotted on the graph.

Not all the available data are plotted on graphs. If measurements were made at only 1 or 2 temperatures, representative conductivity values are usually given in the "Remarks" column in the corresponding table. When several authors report values that are nearly identical, the report that was published first is usually represented on the graph. There are exceptions to this when the results of a later author are more accurate or more extensive. In most graphs, where there are more than one curve for a given element, the graph showing the highest conductivity is considered most likely to be representative of that of the pure material. The higher values are associated with the more pure material, adequate annealing, and large crystal size.

In the commonly accepted theory for the conductivity of metals, there are two mechanisms for the conduction of heat. In pure metals nearly all of the energy transfer is by electrons. In dielectrics, there is also a transport of energy


by the lattice vibrations. However, the relative contribution of this latter mechanism is insignificant except for alloys, impure metals, and the semimetals like bismuth. The transfer of energy by electrons is impeded by several scattering mechanisms. At temperatures above about 20° K the main scattering agent is the metallic lattice itself. Below that temperature the scattering due to impurity centers and lattice defects becomes increasingly more important. In the temperature range from several degrees to about 40° K, the conductivity of a pure metal may be expressed closely by the equation

$$1/k = \alpha T^2 + \beta T^{-1}.$$

The term  $\alpha T^2$  is characteristic of the lattice of the metal being investigated; the term  $\beta T^{-1}$  represents the scattering due to impurities. The latter term is related to the residual electrical resistance. Experimental values for  $\alpha$  and  $\beta$  are given in the tables when the authors include these values in their research reports.

Several physical and chemical properties of the sample affect the conductivity directly. As the purity of the material is increased, the conductivity maximum rises and is shifted toward lower temperatures. The thermal resistance caused by impurities is not additive—small changes in purity can cause very large changes in the conductivity near the maximum. At higher temperatures, however, the effect is not as important. Cold-working and hardening reduce the conductivity and for that reason, other things being equal, the annealed samples will have a higher conductivity. For some single crystals the conductivity depends upon the direction of heat flow. For several metals that are anisotropic, curves are given for various crystal orientations.





**LITHIUM**


Curve	Sample source and analysis	Remarks	Reference
Me.....	Kahlbaum; "very pure".	Cold-worked; handled in CO <sub>2</sub> atmosphere; R.	W. Meissner (1920).
Bi.....		Extruded and mounted in glass tubes; cycled thermally; R.	C. C. Bidwell (1926b, 1925, 1926a).

**POTASSIUM**

Ho.....	Eimer and Amend; "very pure", free of Fe, Ca, Mg, Al, trace of Na, by chemical analysis.	Melted in vacuum; cast in glass under vacuum; R.	J. W. Hornbeck (1913).
---------	--	--	------------------------

**SODIUM**

Curve	Sample source and analysis	Remarks	Reference
.....	Eimer and Amend; "very pure"; free of Fe, Ca, Mg, Al, and K by chemical analysis.	Melted in vacuum; cast in glass under vacuum; obtained $k=1.34$ at 5.7°C, 1.33 at 21.0°C; R.	J. W. Hornbeck (1913).
Bi.....		Extruded and mounted in glass tubes; cycled thermally; R.	C. C. Bidwell (1926b, 1925, 1926a).
B.McD. 2.	British Thomson-Houston; 0.01 to 0.1% Ca and Al.	Melted, cast in vacuum; cast into soft glass; R.	R. Berman and D. K. C. MacDonald (1951).
B.McD. 2	Philips; trace of Ag.	Melted, cast in vacuum; cast into soft glass; R.	R. Berman and D. K. C. MacDonald (1951).




**BERYLLIUM**

**MAGNESIUM**


Curve	Sample source and analysis	Remarks	Reference
Le.....	Beryllium Co. Am.; comm. pure; traces of Al, Mn, Cr, Fe, Si, and Mg; total impurity 1/2%.	Physical imperfections noted; R, Cp, and emf.	E. J. Lewis (1929).
G. Ad.....	Degussa Co.; "high purity".	Residual resistance 1% of R <sub>273</sub> ; single crystal with heat flow parallel to hexagonal axis; studied effect of magnetic field on R and k.	E. Grüneisen and H. Adenstedt (1938).
G. Er.....	do.....	Same; except rod axis perpendicular to hexagonal axis; binary lateral axis inclined to rod axis by 2°, 12° and 30°; showed anisotropy.	E. Grüneisen and H.-D. Erfling (1940).
Er. G.....	do.....	Same as G. Ad.....	H.-D. Erfling and E. Grüneisen (1942).

Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	k=1.57 at 0°C; R.....	L. Lorens (1881a).
.....	do.....	k=1.72 at 0°C. 2.0 at 80°K; R.....	J. Staebler (1929).
.....	do.....	k=1.72 at 0°C, 1.87 at 80°K; R.....	W. Mannchen (1931).
.....	do.....	k=1.60 at 18°C; R.....	R. Kikuchi (1932).
M. R.....	Johnson, Matthey; 99.95% pure.	Equation $\alpha=10.6 \times 10^{-4}$ , $\beta=1.25$ .	K. Mendelssohn and H. M. Rosenberg. (1952a).
.....	do.....	Equation $\alpha=8.6 \times 10^{-5}$ , $\beta=1.05$ .	H. M. Rosenberg (1954a).
S.....	Dow; manganese impurities as marked on graph.	R.....	E. G. Sharkoff (1952, 1953ab).



**MAGNESIUM (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
K. S. W. 1	Johnson, Matthey; 99.98% purity; .013% Fe, .0023% Mn, .0013% Pb, trace of Si, Cu, Ag, Ca, Na.	Cold-drawn.....	W. R. G. Kemp, A. K. Sreedhar, and G. K. White (1953).
K. S. W. 2	.....do.....	Annealed in vacuum 3 hr at 350°C.	Do.
K. S. W. 3	.....do.....	Same treatment as number 2.....	Do.
R.....	Johnson, Matthey; 99.95% pure; .03% Mn, .0075% Fe, .004% Al.	Annealed 6 hr in vacuum at 500°C; equation $\alpha = 8.5 \times 10^{-4}$ , $\beta = 1.05$ .	H. M. Rosenberg (1954b).




ALUMINUM  
FIGURE 3

ALUMINUM

ALUMINUM (Cont'd)


Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	Low value of $k=1.43$ at $0^\circ\text{C}$ ; R.....	L. Lorenz (1881a).
.....	0.5% Fe, 0.4% Cu.	$k=2.01$ at $18^\circ\text{C}$ ; R, Cp.....	W. Jaeger and H. Diesselhorst (1900).
L.....	Johnson, Matthey; 99% pure.	Lathe turned from larger sample, density of 2.70.	C. H. Lees (1908).
.....	Commercial.....	$k=1.93$ at $0^\circ\text{C}$ , 1.90 at $85^\circ\text{K}$ , 1.59 at $21.4^\circ\text{K}$ .	R. Schott (1916).
.....	.....	Measured the effect of torsion on the thermal and electrical conductivity.	J. E. Calthrop (1926).
.....	5 samples ranging from pure to technical.	Measured at $20^\circ$ and $80^\circ\text{K}$ ; results for purest samples lie just below curve of P. S. J.; studied effect of grain size and crystal boundaries.	E. Grüneisen and E. Goens (1927); E. Grüneisen (1927).
.....	"Pure".....	$k=2.26$ at $0^\circ\text{C}$ , 2.55 at $89^\circ\text{K}$ ; R.....	J. Staebler (1929).
.....	do.....	$k=2.26$ at $0^\circ\text{C}$ , 2.56 at $80^\circ\text{K}$ ; also measured R.	W. Mannchen (1931).
.....	Approx. 99.7% pure; technically pure.	Two samples gave values at $0^\circ\text{C}$ of $k=2.26$ .	A. Eucken and H. Warrentrup (1935).
N.....	Hadfield's.....	Brinell hardness of 17.....	J. de Nobel (1951).

Curve	Sample source and analysis	Remarks	Reference
A. W. S. 1	Alcoa; 99.996% pure, .001% Mg, .001% Si, .0006% Fe, .0004% Cu, .004% Na.	Single crystal; residual electrical resistance of $1.19 \times 10^{-3} R_{273}$ ; $\alpha=2.7 \times 10^{-5}$ , $\beta=7.04$ .	R. A. Andrews, R. T. Webber, and D. A. Spohr (1951).
A. W. S. 2	.....do.....	Single crystal, $R=1.48 \times 10^{-3} R_{273}$ ; $\alpha=2.72 \times 10^{-5}$ , $\beta=6.06$ .	Do.
A. W. S. 3	Johnson, Matthey; 99.995% pure; .002% Mg, .001% Si, .0005% Fe, .0005% Cu, trace of Na.	Polycrystalline rod; residual resistance of $2.14 \times 10^{-3} R_{273}$ ; $\alpha=2.72 \times 10^{-5}$ , $\beta=4.05$ .	Do.
P. S. J.....	Alcoa; 99.99% pure.	Cold-drawn.....	R. W. Powers, D. Schwartz, and H. L. Johnston (1951).
M. R.....	Johnson, Matthey; 99.994% pure.	Annealed polycrystal; $\alpha=2.2 \times 10^{-5}$ , $\beta=2.3$ .	K. Mendelssohn and H. M. Rosenberg (1952a).
.....	.....	Polycrystalline; superconducting state; representative values were .07 at $0.8^\circ\text{K}$ , .015 at $0.65^\circ\text{K}$ , .007 at $0.37^\circ\text{K}$ .	K. Mendelssohn and C. A. Renton (1953).
R.....	.....	$\alpha=3.2 \times 10^{-5}$ , $\beta=0.23$ .....	H. M. Rosenberg (1954a).



**LANTHANUM**

Curve	Sample source and analysis	Remarks	Reference
.....	.....	$k = T/740$ between about 2° and 20°K	H. M. Rosenberg (1954a).




**TITANIUM**

Curve	Sample source and analysis	Remarks	Reference
.....	Comm. pure.....	Abstract only, $k=0.20$ at $273^{\circ}\text{K}$ , $0.21$ at $195^{\circ}\text{K}$ , $0.18$ at $90^{\circ}\text{K}$ , $0.12$ at $20^{\circ}\text{K}$ .	C. J. Rigney and L. I. Bochstahler (1951).
M. R. 1...	Assoc. Elect. Ind. Res. Lab. England; 99.9% pure.	Unannealed; $\beta=290$ .....	K. Mendelsohn and H. M. Rosenberg (1952b).
M. R. 2...	Same source; 99.99% pure.	Annealed; $\beta=170$ .....	Do.
R.....	.....	Single crystal; conductivity constant from $50^{\circ}$ to $100^{\circ}\text{K}$ ; $\alpha=454 \times 10^{-5}$ , $\beta=82$ .	H. M. Rosenberg (1954a).

**ZIRCONIUM**

Curve	Sample source and analysis	Remarks	Reference
M. R.....	Johnson, Matthey; 98% pure.	Annealed; $\alpha=130 \times 10^{-5}$ , $\beta=76$ ..	K. Mendelsohn and H. M. Rosenberg (1952b).
R.....	.....	$\alpha=125 \times 10^{-5}$ , $\beta=34$ .....	H. M. Rosenberg (1954a).



**VANADIUM**


Curve	Sample source and analysis	Remarks	Reference
R.....		In both normal and superconducting states.	H. M. Rosenberg (1954a).

**TANTALUM**

Curve	Sample source and analysis	Remarks	Reference
.....		$k=0.54$ at $17^{\circ}\text{C}$ .....	T. Barratt and R. M. Winter (1926).
.....	Fansteel, 99.9% pure.	$k=0.36$ at $0^{\circ}\text{C}$ .....	M. Cox (1943).
.....		Measured ratio of conductivity in superconducting and normal states.	C. V. Heer and J. G. Daunt (1949).
.....		do.....	J. K. Hulm (1949).
M. O.....	99.95% pure.....	Measured in both normal and superconducting states.	K. Mendelssohn and J. L. Olsen (1950a).
Hu.....	Hilger; 0.1% impurities.	Polycrystalline; impurities in solid solution; measured effect of magnetic field; both normal and superconducting states.	J. K. Hulm (1950).
M. R.....	Johnson, Matthey; 99.98% purity.	Measured both normal and superconducting states; $\beta=27$ .	K. Mendelssohn and H. M. Rosenberg (1952b).
.....	do.....	Measured superconducting state below $1^{\circ}\text{K}$ .	K. Mendelssohn and C. A. Renton (1953).
R.....	do.....	Continued M. R. curve to higher temperatures; $\alpha=79 \times 10^{-4}$ , $\beta=25$ .	H. M. Rosenberg (1954a).

**NIOBIUM**

Curve	Sample source and analysis	Remarks	Reference
M. O.....	Hilger; "high purity".	In both normal and superconducting states; studied effect of magnetic field.	K. Mendelssohn and J. L. Olsen (1950a).
M. E.....	Johnson, Matthey; 99.99% pure.	In both normal and superconducting states; up to $22^{\circ}\text{K}$ .	K. Mendelssohn and H. M. Rosenberg (1952b).
R.....		Continuation to temperatures above $22^{\circ}\text{K}$ .	H. M. Rosenberg (1954a).
.....	Same as M. R.	Superconducting state below $1^{\circ}\text{K}$ .	K. Mendelssohn and C. A. Renton (1953).



TUNGSTEN  
MOLYBDENUM  
FIGURE 6


**MOLYBDENUM**

Curve	Sample source and analysis	Remarks	Reference
		$k=1.45$ at $17^{\circ}\text{C}$ .	T. Barratt and R. M. Winter (1925).
	Philips; "very pure".	Annealed at $900^{\circ}\text{C}$ ; $k=1.44$ at $0^{\circ}\text{C}$ ; R.	W. G. Kannaluk (1931).
	Gen. Elec.	Annealed at $220^{\circ}\text{C}$ ; $k=1.32$ at $0^{\circ}\text{C}$ ; R.	Do.
Ka	.05% Bi, Cd; .01% Al, Ge; Sn, Ti, V, W; .001% Co, Cu, Pt, Rh; trace of C.	R.	W. G. Kannaluk (1933).
M. R.	Johnson, Matthey; 99.95% pure.	$\alpha=7.5 \times 10^{-3}$ , $\beta=8.7$	K. Mendelssohn and H. M. Rosenberg (1952b).
R.	do.	Continued above work to $100^{\circ}\text{K}$ .	H. M. Rosenberg (1954a).

**TUNGSTEN**


Curve	Sample source and analysis	Remarks	Reference
	Heraeus	$k=1.6$ at $0^{\circ}\text{C}$ .	S. Weber (1917).
		$k=2$ at $17^{\circ}\text{C}$ .	T. Barratt and R. M. Winter (1925).
	Osram; impure.	Single crystal; $k=1.83$ at $83^{\circ}\text{K}$ , $1.80$ at $21^{\circ}\text{K}$ .	E. Grüneisen and E. Goens (1927).
G. Go.	Philips; "very pure".	Single crystal.	Do.
	Gen. Elec.	One sample annealed at $220^{\circ}\text{C}$ , $k=1.64$ at $0^{\circ}\text{C}$ ; another sample annealed at $1300^{\circ}\text{C}$ , $k=1.66$ at $18^{\circ}\text{C}$ .	W. G. Kannaluk (1931).
Ka	Phillips	Single crystals, only higher values plotted.	W. G. Kannaluk (1933).
Br. H.	Philips		H. Bremmer and W. J. de Haas (1936).





**TUNGSTEN (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
.....	Gen. Elec.....	$k=1.66$ at $0^{\circ}\text{C}$ .....	I. Langmuir and J. B. Taylor (1936).
.....	.....	At $78^{\circ}$ , $194^{\circ}$ , $273^{\circ}\text{K}$ , approx. same results as Kannaluk (1933).	W. C. Michels and M. Cox (1936).
G. A.....	Same as G. Go. above.	Studied effect of magnetic field and anisotropy.	E. Grüneisen and H. Adenstedt (1937).
H. N.....	Phillips.....	Single crystal; residual resistance of $4 \times 10^{-4} R_{273}$ ; measured effect of magnetic field on $k$ and $R$ .	W. J. de Haas and J. de Nobel (1938).
G. A.....	Same as G. Go...	Single crystals; graph results are for a sample with rod axis parallel to [010] crystal axis; for another crystal with rod axis parallel to [100] axis, $k=22.2$ at $21^{\circ}\text{K}$ ; $R$ .	E. Grüneisen and H. Adenstedt (1938).
.....	Gen. Elec.....	$k=1.93$ at $77^{\circ}\text{K}$ , $1.87$ at $90^{\circ}\text{K}$ , and $1.69$ at $0^{\circ}\text{C}$ .	M. Cox (1943)
.....	Same as H. N. above.	Extended the measurements to higher magnetic fields.	J. de Nobel (1949).
M. R.....	Johnson, Matthey; 99.99% pure.	Annealed; $\alpha=10.2 \times 10^{-4}$ , $\beta=5.9$ .	K. Mendelssohn and H. M. Rosenberg (1952b).
R.....	.....	$\alpha=9.3 \times 10^{-4}$ , $\beta=5.8$ .....	H. M. Rosenberg (1954a).




**MANGANESE**

Curve	Sample source and analysis	Remarks	Reference
.....	.....	$k = 0.05$ at $83^\circ\text{K}$ for the $\beta$ phase..	H. Reddemann (1935).
M. R. ....	Johnson, Matthey; 99.99% pure.	Annealed; $\beta = 1200$ .....	K. Mendelsohn and H. M. Rosenberg (1952b).

**SUPPLEMENTARY DATA**

Curve	Sample source and analysis	Remarks	Reference




**IRON**

Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	$k=0.70$ at $0^{\circ}\text{C}$ .....	L. Lorens (1881a).
.....	"Pure"; .1% C, .06% Mn, .02% Si, .05% Cu, .03% P, .03% S.....	$k=0.72$ at $18^{\circ}\text{C}$ .....	E. Grüneisen (1900).
.....	0.1% C+metals	Also measured $R, C_p, \text{emf}; k=0.67$ at $18^{\circ}\text{C}$ .....	W. Jaeger and H. Diesselhorst (1900).
.....	Krupp; .1% C, .2% Si, .1% Mn.....	Also measured $R, C_p, \text{emf}; k=0.60$ at $18^{\circ}\text{C}$ .....	Do.
L.....	99.42% pure; .1% C, .15% Mn, .13% Si.....	Wrought iron.....	C. H. Lees (1908).
.....	.....	Electrolytic; two rods with average grain sizes of $1 \times 10^{-1}$ and $6 \times 10^{-2}$ cm; $k=0.94$ and $0.90$ , respectively, at $0^{\circ}\text{C}$ ; $k=1.84$ and $1.83$ at $80^{\circ}\text{K}$ .....	A. Eucken and K. Dittich (1927).
.....	Heraeus.....	Electrolytic; average grain size $2 \times 10^{-2}$ cm; $k=0.82$ at $0^{\circ}\text{C}$ and $1.17$ at $80^{\circ}\text{K}$ .....	Do.
G. Go.....	"Double refined".....	Tempered; electrolytic.....	E. Grüneisen and E. Goens (1927).

**IRON (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
.....	"Technically pure".....	Two samples untempered; electrolytic; $k=1.36$ and $0.91$ at $83^{\circ}\text{K}$ , $3.01$ and $0.5$ at $21^{\circ}\text{K}$ .....	E. Grüneisen and E. Goens (1927).
.....	"Pure".....	Electrolytic; $k=0.77$ at $16^{\circ}\text{C}$ .....	R. Kikuchi (1932).
.....	Armeo; .01% C, .02% Mn, .006% P, .026% S, .06% Ca, .02% Si.....	$k=0.7$ at $0^{\circ}\text{C}$ , $0.72$ at $195^{\circ}\text{K}$ , $0.94$ at $90^{\circ}\text{K}$ .....	W. G. Kannaluk (1933).
.....	"Pure".....	Between $3^{\circ}$ and $20^{\circ}\text{K}$ , the values fall just below the curve marked M. R. ....	J. Karweil and K. Schäfer (1939).
.....	Hadfield; 99.93% pure.....	Forged; $k=0.9$ at $90^{\circ}\text{K}$ , maximum of $1.3$ at $52^{\circ}\text{K}$ , $0.5$ at $15^{\circ}\text{K}$ .....	J. de Nobel (1951).
P. Z. J.....	Johnson, Matthey; 99.99% pure.....	.....	R. W. Powers, J. B. Ziegler, and H. L. Johnston (1951a).
M. R.....	Johnson, Matthey; 99.99% pure.....	$\alpha=18 \times 10^{-5}, \beta=9.5$ .....	K. Mendelssohn and H. M. Rosenberg (1952b).
R.....	.....	$\alpha=10.2 \times 10^{-5}, \beta=9.6$ .....	H. M. Rosenberg (1954a).




**NICKEL**

Curve	Sample source and analysis	Remarks	Reference
.....	Basse and Selve; impure.	$k=0.60$ at $18^{\circ}\text{C}$ ; R, $C_p$ , emf. ....	W. Jaeger and H. Dieselhorst (1900).
L.....	Johnson, Matthey; 99% pure.	Lathe turned; density 8.80.....	C. H. Lees (1908).
.....	Heraeus.....	Drawn rod; $k=0.84$ at $0^{\circ}\text{C}$ , 1.11 at $80^{\circ}\text{K}$ .	A. Eucken and K. Dittrich (1927).
P.S.J.....	Int. Nickel; comm. pure.	.....	R. W. Powers, D. Schwartz, and H. L. Johnston (1951).
.....	99.4% pure.....	Forged; approx. same curve as P. S. J. from $93^{\circ}$ to $25^{\circ}\text{K}$ ; at $15^{\circ}\text{K}$ , $k=0.18$ .	J. de Nobel (1951).
M. R.....	Johnson, Matthey; 99.997% pure.	Annealed; $\alpha=22 \times 10^{-5}$ , $\beta=4.4$ ; measured up to $22^{\circ}\text{K}$ .	K. Mendelssohn and H. M. Rosenberg (1952b).
R.....	do.....	Annealed; $\alpha=10.4 \times 10^{-5}$ , $\beta=4.6$ ; measured up to $40^{\circ}\text{K}$ .	H. M. Rosenberg (1954a).

**COBALT**

Curve	Sample source and analysis	Remarks	Reference
R.....	.....	$\alpha=10.5 \times 10^{-5}$ , $\beta=7.9$ .....	H. M. Rosenberg (1954a).




**PALLADIUM**

Curve	Sample source and analysis	Remarks	Reference
.....	"Chem. pure".....	$k=0.7$ at $18^{\circ}\text{C}$ ; R, $C_p$ , emf.....	W. Jaeger and H. Diesselhorst (1900).
.....	.....	$k=0.42$ at $17^{\circ}\text{C}$ for commercial palladium, $0.60$ at $17^{\circ}\text{C}$ for "pure".	T. Barratt and R. M. Winter (1925).
G. Re.....	Heraeus; "pure".	Unannealed; plotted with open circles; R.	E. Grüneisen and H. Reddemann (1934).
G. Re.....	do.....	Cold-drawn; annealed at $380^{\circ}\text{C}$ for two hours; plotted with darkened circles; R.	Do.
M. R.....	Johnson, Matthey; 99.95% pure.	Annealed; $\alpha=64 \times 10^{-5}$ , $\beta=11.7$ .....	K. Mendelsohn and H. M. Rosenberg (1952b).
.....	.....	$\alpha=41 \times 10^{-5}$ , $\beta=11.7$ .....	H. M. Rosenberg (1954a).

**RHODIUM**

Curve	Sample source and analysis	Remarks	Reference
.....	.....	$k=0.88$ at $17^{\circ}\text{C}$ .....	T. Barratt and R. M. Winter (1925).
.....	Heraeus; "pure".	Annealed; $k=2.15$ at $83^{\circ}\text{K}$ , $23.8$ at $21^{\circ}\text{K}$ , R	E. Grüneisen and E. Goens (1927).
M. R.....	Johnson Matthey; 99.95% pure.	$\alpha=22 \times 10^{-5}$ , $\beta=1.4$ .....	K. Mendelsohn and H. M. Rosenberg (1952b).
.....	.....	$\alpha=10.7 \times 10^{-5}$ , $\beta=1.38$ .....	H. M. Rosenberg (1954a).




**PLATINUM**

Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	$k=0.78$ at $18^{\circ}\text{C}$ .....	J. H. Gray (1896).
.....	do.....	$k=0.7$ at $18^{\circ}\text{C}$ ; R, $C_p$ , cmf.....	W. Jaeger and H. Diemelhorst (1900).
Me.....	Heraeus; "very pure".	Drawn; electrically annealed.....	W. Meissner (1915).
.....	do.....	Drawn; electrically annealed; obtained same results as Meissner (1915) at $21^{\circ}$ and $83^{\circ}\text{K}$ ; R.	E. Grüneisen and E. Gooss (1927).
.....	Heraeus; "less pure".	$k=2.96$ at $21^{\circ}\text{K}$ .....	Do.
.....	Heraeus.....	$k=4.25$ at $21^{\circ}\text{K}$ ; measured effect of magnetic field on $k$ , R.	E. Grüneisen and H. Adenstedt (1933).
M. R.....	Johnson, Matthey; 99.999% pure.	$\alpha=43 \times 10^{-5}$ , $\beta=0.40$ .....	K. Mendelssohn and H. M. Rosenberg (1952b).
.....		$\alpha=43 \times 10^{-5}$ , $\beta=0.35$ .....	H. M. Rosenberg (1954a).

**IRIDIUM**

Curve	Sample source and analysis	Remarks	Reference
.....		$k=0.59$ at $17^{\circ}\text{C}$ .....	T. Barratt and R. M. Winter (1935).
M. R.....	Johnson, Matthey; 99.95% pure.	Annealed; $\alpha=3.6 \times 10^{-5}$ , $\beta=0.77$ .	K. Mendelssohn and H. M. Rosenberg (1952b).
R.....		$\alpha=4.6 \times 10^{-5}$ , $\beta=0.75$ .....	H. M. Rosenberg (1954a).




**COPPER**

Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	$k=3$ at $0^{\circ}\text{C}$ .....	L. Lorens (1881a).
.....	.....	One sample had $k=3.6$ at $10^{\circ}\text{C}$ ; the second, $1.3$ at $10^{\circ}\text{C}$ .	J. H. Gray (1895).
.....	"Pure".....	$k=3.9$ at $18^{\circ}\text{C}$ .....	E. Grüneisen (1900).
.....	do.....	$k=3.73$ at $18^{\circ}\text{C}$ ; R, Cp.....	W. Jaeger and H. Diesselhorst (1900).
.....	do.....	$k=3.95$ at $20^{\circ}\text{C}$ .....	W. Schaufelberger (1902).
.....	.....	"Soft drawn, high conductivity"; $k=3.8$ at $27^{\circ}\text{C}$ ; results at $100^{\circ}\text{K}$ are close to the P.S.J. curve.	C. H. Lees (1908).
.....	.....	Electrolytic copper wires; values at $21^{\circ}$ , $91^{\circ}$ and $273^{\circ}$ are close to the W.-1 curve.	W. Meissner (1915).
.....	"Very pure".....	Natural single crystal; results uncertain due to very small size of sample.	R. Schott (1916).
.....	"Tech. pure".....	Approximately on curve of W.-3 down to $22^{\circ}\text{K}$ .	Do.

**COPPER (Cont'd)**


Curve	Sample source and analysis	Remarks	Reference
.....	.....	Measured 18 samples of various crystal structure, purity, and annealing at $21^{\circ}$ and $83^{\circ}\text{K}$ ; R.	E. Grüneisen and E. Goens (1927).
.....	Gen. Elec.....	Single crystal; between $95^{\circ}$ and $300^{\circ}\text{K}$ , the results are close to curve W.-1.	W. G. Kannaluk and T. H. Laby (1928).
.....	.....	Measured 14 different copper samples at $20^{\circ}$ and $90^{\circ}\text{K}$ ; R.	E. Grüneisen and H. Reddemann (1934).
.....	H. Ba.....	.....	W. J. de Haas and T. Biermass (1936).
.....	.....	Studied effect of magnetic field on $k$ , R.	E. Grüneisen and H. Adenstedt (1938).
.....	Al. Mn.....	Johnson, Matthey; free of O; .003% each Ag, Ni, and Pb.	J. F. Allen and E. Mendosa (1947).
.....	P. S. J.....	Am. Brass; "O. F. H. C."	R. W. Powers, D. Schwartz, and H. L. Johnston (1951).





COPPER (Cont'd)

Curve	Sample source and analysis	Remarks	Reference
B. McD.	Johnson, Matthey; .0006% Ag, .0003% Ni, .0004% Pb.	Cold-drawn, then annealed 6 hr at 450°C in helium gas.	R. Berman and D. K. C. MacDonald (1952).
M. R.	Johnson, Matthey; 99.999% pure.	Annealed; $\alpha = 3.2 \times 10^{-4}$ , $\beta = 0.35$ .	K. Mendelsohn and H. M. Rosenberg (1952a).
Ni. Ts.	Gen. Elec.; "comm. high purity".	Polycrystalline wire.	J. Nicol and T. P. Tseng (1953).
W-1.	Johnson, Matthey; 99.999% pure; same as B. MacD.	As cold-drawn; $\alpha = 2.55 \times 10^{-4}$ , $\beta = 1.15$ .	G. K. White (1953c).
W-2.	do.	Annealed in vacuum at 550°C for 3 hours; $\alpha = 2.55 \times 10^{-4}$ , $\beta = 0.21$ .	Do.
W-3.	do.	As cold-drawn; same as W-1.	Do.
R.		$\alpha = 2.5 \times 10^{-4}$ , $\beta = 0.35$ .	H. M. Rosenberg (1954a).




SILVER  
FIGURE 12

SILVER


Curve	Sample source and analysis	Remarks	Reference
.....		Silver wire; $k = 4.02$ at $18^\circ\text{C}$ .....	J. H. Gray (1896).
.....	99.98% pure....	$k = 4.21$ at $18^\circ\text{C}$ ; also measured R, $C_p$ , and emf.	W. Jaeger and H. Dienschhorst (1900).
L.....	Johnson, Matthey; 99.9% pure.	Lathe-turned from a larger rod....	C. H. Lees (1908).
.....		Two silver wires had $k = 4.11$ and $4.04$ at $0^\circ\text{C}$ .	W. G. Kannaluk (1931).
.....	Hilger; trace of Cu, Pb, Bi, Mg, Ca, Na, Si.	At $90^\circ$ , $195^\circ$ , and $273^\circ\text{K}$ values are somewhat higher than those of Lees (1908).	W. G. Kannaluk (1933).
.....		Five rods of silver, varied in composition, annealing, crystal structure. At $20^\circ$ and $90^\circ\text{K}$ pure rods had values close to curve W.-3; R.	E. Grüneisen and H. Reddemann (1934).

SILVER (Cont'd)

Curve	Sample source and analysis	Remarks	Reference
.....	Hönig-schmid....	Annealed; electrolytic; $k = 31.4$ at $21^\circ\text{K}$ ; measured effect of magnetic field on $k$ and R.	E. Grüneisen and H. Adenstedt (1938).
M. R.....	Johnson, Matthey; 99.99% pure.	$\alpha = 9.0 \times 10^{-5}$ , $\beta = 1.6$ .....	K. Mendelssohn and H. M. Rosenberg (1952a).
.....	do.....	Measured effect of magnetic field.	K. Mendelssohn and H. M. Rosenberg (1953).
W. 1-5....	Johnson, Matthey; 99.999% pure.	No. 1 was unannealed; #2, annealed at $650^\circ\text{C}$ , grain size 0.1 mm; #3, cold-drawn; #4, the previous one annealed; #5, a re-run of #4.	G. K. White (1953b).
R.....	Johnson, Matthey.	$\alpha = 5 \times 10^{-5}$ , $\beta = 0.3$ .....	H. M. Rosenberg (1954a).



(See next page for the table on GOLD.)




**GOLD**

Curve	Sample source and analysis	Remarks	Reference
.....	.....	$k=3.14$ at $18^{\circ}\text{C}$ .....	J. H. Gray (1895).
.....	"Pure".....	$k=2.93$ at $18^{\circ}\text{C}$ ; a less pure sample had $k=1.79$ at $18^{\circ}\text{C}$ ; R, $C_p$ , enf. Cold-drawn; annealed.....	W. Jaeger and H. Diesselhorst (1900). W. Meissner (1916).
Me.....	Mylius; 99.999% pure.	$k=2.95$ at $17^{\circ}\text{C}$ .....	T. Barratt and R. M. Winter (1925).
.....	.....	$k=2.98$ at $24^{\circ}\text{C}$ .....	H. Masumoto (1927).
.....	.....	Six samples of various composition, annealing; R. Results for "very pure" gold at $21^{\circ}$ and $83^{\circ}\text{K}$ fall close to curve W.-4.	E. Grüneisen and E. Goens (1927).
.....	.....	$k=3.06$ at $0^{\circ}\text{C}$ .....	W. G. Kannaluk (1931).

**GOLD (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
M. R. ....	Johnson, Matthey; 99.999% pure.	$\alpha=18 \times 10^{-5}$ , $\beta=1.15$ .....	K. Mendelssohn and H. M. Rosenberg (1952a).
W. 1, 2....	Garrett, Davidson, Matthey; 99.9% pure (comm.); Ag, trace of Pt, Fe, Pb, Cu, Sn.	No. 1 sample unannealed; #2, annealed.	G. K. White (1953a).
W. 3, 4, 5..	Johnson, Matthey; 99.999% pure; trace of Ag, Cu; faint trace of Cd, Fe, Mg, Na, Ca, Zn.	No. 3 sample cold-drawn; #4, annealed in vacuum at $700^{\circ}\text{C}$ for 3 hours; #5 was the fourth re-drawn.	Do.
.....	.....	$\alpha=19 \times 10^{-5}$ , $\beta=1.13$ .....	H. M. Rosenberg (1954a).




**ZINC**

**ZINC (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	$k=1.1$ at $18^{\circ}\text{C}$ ; $R, C_p, \text{ emf.}$ .....	W. Jaeger and H. Diemelhorst (1900).
L.....	"Pure redistilled".	Lathe-turned from a cast stick.....	C. H. Lees (1908).
Bi. Le.....	99.993% pure...	Single crystal; also measured polycrystalline samples.	C. C. Bidwell and E. J. Lewis (1929); also E. J. Lewis and C. C. Bidwell (1928).
.....	Kahlbaum.....	$k=1.26$ at $83^{\circ}\text{K}$ and $1.25$ at $0^{\circ}\text{C}$ ....	J. Staebler (1929).
G. Go.....	Kahlbaum; "pure".	Single crystals each with rod axis parallel to main crystal axis. Another sample with axes perpendicular had a conductivity 10% lower.	E. Goens and E. Grüneisen (1932).

Curve	Sample source and analysis	Remarks	Reference
M. R. 1...	Hilger; 99.995% pure.	Polycrystalline; $\alpha = 21 \times 10^{-5}$ , $\beta = 0.4$ .	K. Mendelsohn and H. M. Rosenberg (1952a).
M. R. 2, 3.	Imperial Smelting; 99.997%.	No. 2 had rod axis inclined $80^{\circ}$ to hexagonal crystal axis, $\alpha = 34 \times 10^{-5}$ , $\beta = 0.7$ ; #3, inclined $15^{\circ}$ , $\alpha = 31 \times 10^{-5}$ , $\beta = 0.6$ .	Do.
.....	Same as M. R. 1, 2, 3.	Measured effect of magnetic field..	K. Mendelsohn and H. M. Rosenberg (1953).
.....		$\alpha = 30 \times 10^{-5}$ , $\beta = 0.6$ .....	H. M. Rosenberg (1954a).




(See previous page for the table on ZINC.)

**CADMIUM (Cont'd)**

**CADMIUM**


Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	$k=0.92$ at $0^{\circ}\text{C}$ .....	L. Lorens (1881).
.....	do.....	$k=0.93$ at $18^{\circ}\text{C}$ ; R, Cp, emf.....	W. Jaeger and H. Diesselhorst (1900).
L.....	"Pure redistilled".	Lathe-turned from a cast stick.....	C. H. Lees (1908).
.....	Kahlbaum; "pure".	$k=1.02$ at $273^{\circ}\text{K}$ and $194^{\circ}\text{K}$ , $1.23$ at $83^{\circ}\text{K}$ .	A. Eucken and G. Gehlhoff (1912).
.....	Kahlbaum; "chem. pure".	At $20^{\circ}$ and $273^{\circ}\text{K}$ values fall just below upper curve of Go. G.	R. Schott (1916).

Curve	Sample source and analysis	Remarks	Reference
Go. G. .... II	Kahlbaum; "pure".	Two single crystals, each with main crystal and rod axes parallel.	E. Goens and E. Grüneisen (1932).
Go. G. .... I	do.....	Single crystal with main crystal and rod axes perpendicular.	Do.
.....	Hilger; 99.999% pure.	Measured effect of magnetic field..	K. Mendelssohn and H. M. Rosenberg (1951).
M. R. ....	Hilger; 99.999% pure.	Cast in glass; $\alpha = 140 \times 10^{-5}$ , $\beta = 0.5$ .	K. Mendelssohn and H. M. Rosenberg (1952a).
.....	do.....	Measured effect of magnetic field..	K. Mendelssohn and H. M. Rosenberg (1953).
R. ....	.....	Maximum conductivity of '8 between $4^{\circ}$ and $5^{\circ}\text{K}$ ; $\alpha = 1.2 \times 10^{-5}$ , $\beta = 0.02$ .	H. M. Rosenberg (1954a).




### MERCURY

Curve	Sample source and analysis	Remarks	Reference
On. Ht.		Cp.	H. Kamerlingh Omnes (1914).
		Measured in the liquid state and in solid state near melting.	G. Gehlhof and F. Neumeier (1919).
Re.		Measured ten single crystal rods; fall into four groups. No. 1, rod axis parallel to crystal axis; #2, axes inclined 25°; #3, axes inclined 45°; #4, axes perpendicular.	H. Reddemann (1932).
H. Br.		Measured in both normal and superconducting states.	W. J. de Haas and H. Bremmer (1936).
Hu. 1-5.	Basic rod (#1) from Johnson, Matthey; #2, .002% Cd; #3, .007% Cd; #4, .10% In; #5, .39% In.	Homogeneous solid solutions; polycrystalline, but large crystals; measured in both normal and superconducting state.	J. K. Hulm (1950).
		Measured in the intermediate state near 4°K.	R. T. Webber and D. A. Spohr (1953).



(See previous page for the table on MERCURY.)





**GALLIUM**


**INDIUM**

Curve	Sample source and analysis	Remarks	Reference
R.....		Three single crystals of different orientation; No. 1 $\alpha=160 \times 10^{-5}$ , $\beta=4.7$ ; #2, $\alpha=23 \times 10^{-5}$ , $\beta=0.165$ ; #3, $\alpha=87 \times 10^{-5}$ , $\beta=2.22$ .	H. M. Rosenberg (1954a).

Curve	Sample source and analysis	Remarks	Reference
.....	Hilger.....	Absolute values were not determined.	W. J. de Haas and H. Bremmer (1932a).
Hu.....	Johnson, Matthey; 0.1% impurity.	$\alpha=189 \times 10^{-5}$ , $\beta=1.38$ .....	J. K. Hulm (1950).
.....	Johnson, Matthey.	Single crystal; measured conductivity in intermediate state.	D. P. Detwiler and H. A. Fairbank (1952a, b).
M. R.....	Johnson, Matthey; 99.993% pure.	$\alpha=190 \times 10^{-5}$ , $\beta=0.4$ ; measured in both normal and superconducting state.	K. Mendelssohn and H. M. Rosenberg (1952a).
.....	do.....	Measured effect of magnetic field..	K. Mendelssohn and H. M. Rosenberg (1953).
.....	do.....	Measured conductivity below 1°K; between 0.2° and 0.7°K, conductivity equation was $k=2.5 \times 10^{-2} T^3$ ; $k=.019$ at 0.8°K, .003 at 0.46°K.	K. Mendelssohn and C. A. Renton (1953).
R.....	do.....	$\alpha=185 \times 10^{-5}$ , $\beta=0.35$ for normal state conductivity.	H. M. Rosenberg (1954a).

**THALLIUM**

Curve	Sample source and analysis	Remarks	Reference
.....	Kahlbaum.....	Drawn; $k=0.51$ at 0°C and 0.64 at 80°K.....	A. Eucken and K. Dittrich (1927).
.....	Johnson, Matthey; 99.99% pure.	Annealed; polycrystalline; measured effect of magnetic field.	K. Mendelssohn and H. M. Rosenberg (1953).
.....	do.....	Annealed; polycrystalline; measured conductivity below 1°K; between 0.3° and 0.65°K, conductivity was of form $\ln k=sT$ ; $k=0.2$ at 0.62°K, 0.0015 at 0.3°K.	K. Mendelssohn and C. A. Renton (1953).
R.....	do.....	$\alpha=537 \times 10^{-5}$ , $\beta=0.1$ .....	H. M. Rosenberg (1954a).



**CARBON (Graphite)**


Curve	Sample source and analysis	Remarks	Reference
.....		Pencil lead; density of 2.11 g/cm <sup>3</sup> ; $k=0.15$ at 15°C.	T. Barratt and R. M. Winter (1926).
.....	Acheson graphite.	$k=1.78$ at 122°K, 1.73 at 300°K....	A. P. Cray (1933).
.....	Carbon; 80% petroleum coke, 20% lampblack.	$k=0.016$ at 0°C.....	R. W. Powell, F. H. Schofield (1939).
.....	Acheson graphite.	Two rods gave $k=1.21$ and 1.67 at 0°C.	Do.
.....	National Carbon; Acheson graphite.	For a sample with rod axis parallel to extrusion direction, $k=1.76$ at 0°C, 2.5 at 82°K; for a second sample with rod axis perpendicular to extrusion, $k=1.13$ at 0°C; 1.76 at 82°K.	R. A. Buerschaper (1944).
.....	National Carbon; carbon electrode.	$k=0.06$ at 0°C, 0.01 at 82°K.....	Do.
.....		Measured conductivities of graphite and amorphous carbon.	S. Miruhima and J. Okada (1951).
.....		Measured effect of crystal size....	S. Mrosowski (1952).

**CARBON (Graphite) (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
B. 1-3, 1'-3'	Atomic Energy Res. Establishment.	Artificial graphite rods; very anisotropic; unprimed numbers refer to rods with axes parallel to direction of extrusion; primed numbers refer to rods with axes perpendicular to the extrusion; densities were respectively 1.79, 1.60, and 1.77 g/cm <sup>3</sup> ; crystal sizes 2000, 1000, and 300 Å.	R. Berman (1952).
B. 4, 4'....	Natural graphite.	Density 2.25 g/cm <sup>3</sup> ; crystal size, 2000 Å; unprimed number refers to sample with its rod axis parallel to preferred c-axis; primed number, perpendicular.	Do.
T. W. 1, 2.	National Carbon; graphite.	Densities were 1.70 g/cm <sup>3</sup> ; rod axes were respectively perpendicular and parallel to the preferred c-axis.	W. W. Tyler and A. C. Wilson (1953).
T. W. 3....	Natural graphite.	Molded; density of 1.90; rod axis perpendicular to preferred c-axis.	Do.
T. W. 4....	Lampblack....	Molded; density of 1.65; rod axis parallel to preferred c-axis.	Do.
.....		Abstract only; data not given....	A. W. Smith (1954).

**SILICON**


.....	Impurities of $1 \times 10^{-4}$ percent as shown by Hall effect.	"Filament cut from a crystal pulled in [100] direction;" $k=1.48$ at 0°C, 9 at 80°K, 19.5 at 30°K.	G. W. Hull and T. H. Geballe (1954).
-------	---	--	--------------------------------------



(See next page for table on TIN.)

**GERMANIUM**

Curve	Sample source and analysis	Remarks	Reference
Es. Zi . . . .	"High purity" . .	Cast; higher of two Ge curves on figures 18 and 19a.	I. Estermann and J. E. Zimmerman (1951).
Es. Zi . . . .	0.006 atomic % of Al.	Cast; lower of two Ge curves on figures 18 and 19a.	Do.





TIN

TIN (Cont'd)

Curve	Sample source and analysis	Remarks	Reference
.....	"Pure".....	$k=0.64$ at $0^{\circ}\text{C}$ .....	L. Lorenz (1881).
.....	"Pure" .03% Pb.....	$k=0.61$ at $18^{\circ}\text{C}$ .....	W. Jaeger and H. Diesselhorst (1900).
L.....	Kahlbaum; "pure".....	the turned from a rod.....	C. H. Lees (1908).
.....	.....	Measured the relative change in conductivity at low temperatures, absolute values not given.	W. J. de Haas, S. Aoyama, and H. Bremmer (1931) and W. J. de Haas and H. Bremmer (1931a).
Hu. 1-4....	Johnson, Matthey; No. 1, 99.996% pure; #2, .03% Hg added; #3, .3% Hg added; #4, 4.1% Hg added.	Samples 1-3 were homogeneous solid solutions; #4 was two-phase; both normal and superconducting state measured.	J. K. Hulm (1949, 1950).

Curve	Sample source and analysis	Remarks	Reference
.....	.....	Measured relative change upon becoming superconducting.	C. V. Heer and J. G. Daunt (1949).
Ra. 1, 2....	Chempur; 99.992% pure.	Single crystals with tetragonal axis inclined $85^{\circ}$ to rod axis.	A. Rademakers (1949).
.....	Johnson, Matthey; 99.996% pure.	Measured conductivity in the intermediate state.	D. P. Detwiler, H. A. Fairbank (1952a,b).
.....	Johnson, Matthey; 99.997%.	Single crystal; measured the effect of a magnetic field; for zero field, $k=25.1$ at $4.4^{\circ}\text{K}$ , $19.6$ at $3.0^{\circ}\text{K}$ , $18.0$ at $2.4^{\circ}\text{K}$ , in normal state.	K. Mendelsohn, H. M. Rosenberg (1953).
M. Rn.....	do.....	Single crystal; upper curve in figure 18b; superconducting state.	K. Mendelsohn, C. A. Renton (1953).
M. Rn.....	do.....	Polycrystalline; lower curve on figure 18b; superconducting state.	Do.
R.....	do.....	$\alpha=60 \times 10^{-3}$ , $\beta=0.12$ .....	H. M. Rosenberg (1954a).
Gd. 1-5....	No. 1 and 2, "spect. pure"; #3, 0.3% In; #4 and 5, 3% In.	Polycrystalline; crystal sizes about 1 to 3 mm; cast in glass.	B. B. Goodman (1953).






**LEAD**

**LEAD (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
.....	"Pure"	$k=0.35$ at $0^{\circ}\text{C}$ .	L. Lorens (1881).
.....	do.	$k=0.35$ at $18^{\circ}\text{C}$ .	W. Jaeger and H. Diesselhorst (1900).
.....	.....	$k=0.35$ at $25^{\circ}\text{C}$ , $0.45$ at $90^{\circ}\text{K}$ .	P. Macchia (1907).
L.....	Baxendale; "pure".	Lathe-turned from a bar.	C. H. Lees (1908).
Me.....	Kahlbaum; 99.998% pure.	Cold-drawn.	W. Meissner (1915).
.....	Kahlbaum; "pure".	Results agree with Meissner (1915).	R. Schott (1916).
.....	.....	$k=0.38$ at $12^{\circ}\text{C}$ , $0.36$ at $23^{\circ}\text{C}$ .	T. Pecsalaki (1917).
Bi. Le.....	.....	.....	C. C. Bidwell and E. J. Lewis (1929).
.....	.....	Measured relative temperature variation.	W. J. de Haas and H. Bremmer (1931).
Br. H.....	.....	Measured in both normal and superconducting states.	H. Bremmer and W. J. de Haas (1936).
.....	Hilger; 99.999% pure.	Measured changes in conductivity during superconducting transition.	K. Mendelssohn and R. B. Pontius (1937).


Curve	Sample source and analysis	Remarks	Reference
H. Ra.....	Hilger.	Melted under vacuum; single crystal; in both normal and superconducting states.	W. J. de Haas and H. Rademakers (1940).
Ra.....	do.	Two single crystals.	A. Rademakers (1949).
M. O.....	0.02% Bi.	In both normal and superconducting states.	K. Mendelssohn and J. L. Olsen (1950c).
.....	.....	Studied conductivity in intermediate state.	R. T. Webber and D. A. Spohr (1951).
M. R.....	Tadenc, 99.998% pure.	Single crystal, measured in both normal and superconducting states; normal curve gives $\alpha=325 \times 10^{-4}$ , $\beta=0.10$ ; same curve on graph as H. Ra.; experimental points marked by filled circles.	K. Mendelssohn and H. M. Rosenberg (1952b).
O. Ra.....	.....	Single crystal.	J. L. Olsen and C. A. Renton (1952).
.....	Tadenc.	Measured effect of magnetic field.	K. Mendelssohn and H. M. Rosenberg (1953).
.....	Same as M.R.	$k=25$ at $3.1^{\circ}\text{K}$ , $28$ at $2.7^{\circ}\text{K}$ ; continuation of work of Mendelssohn, Rosenberg (1952b); $\alpha=290 \times 10^{-4}$ , $\beta=0.10$ .	H. M. Rosenberg (1954a).



(For GERMANIUM, see the table under figure 18, page 31.)







**BISMUTH (Cont'd)**

Curve	Sample source and analysis	Remarks	Reference
Re.....	Kahlbaum; "pure".	Rod axis inclined 80° to crystal axis; studied effect of magnetic field; R.	H. Reddemann (1934).
Ro.....		Measured two single crystals, one with rod axis parallel to trigonal crystal axis, one perpendicular.	M. T. Rodine (1934).
H. C. 1, 2, 3.	Hilger; 99.995% pure, trace of silver.	Single crystals; No. 1, rod axis parallel to main crystal axis; #2, rod axis parallel to binary axis; #3, rod axis parallel to bisectrix of binary axes.	W. J. de Haas and W. H. Capel (1934a, b).
		At 83° and 90°K results are close to the ones above; measured effect of magnetic field on <i>k</i> and R.	E. Grüneisen and J. Gielissen (1936).
H. Ge. C...	Hilger; .002% silver, trace of Pb.	Single crystal; rod axis parallel to main crystal axis; measured effect of magnetic field.	W. J. de Haas, A. N. Gerritsen, and W. H. Capel (1936).
		Measured <i>k</i> between 2.3° and 77.4°K.	S. Shalyt (1947).
		Measured effect of magnetic field.	E. Grüneisen, K. Rausch, and K. Weiss (1950).

**TELLURIUM**

Curve	Sample source and analysis	Remarks	Reference
Ca.....	99.999% pure...	No. 1, a single crystal with rod axis parallel to main crystal axis; #2 and #3 are polycrystalline; also measured R, emf.	C. H. Cartwright (1933).

**CERIUM**

R.....		$k = T/900$ from 4° to 20°K.....	H. M. Rosenberg (1954a).
--------	--	----------------------------------	--------------------------

**URANIUM**

T. W. W.....		Quenched; also measured R, emf..	W. W. Tyler, A. C. Wilson, and G. J. Wolga (1952).
M. R.....	Assoc. Elec. Ind Res. Lab.	$\alpha = 750 \times 10^{-5}$ , $\beta = 95$ .....	K. Mendelssohn and H. M. Rosenberg (1952b).
R.....	do.....	$\alpha = 790 \times 10^{-5}$ , $\beta = 93$ .....	H. M. Rosenberg (1954a).

## 2.3 Alloys and Commercial Metals

The values for conductivities of experimental and commercial alloys are given in figures 22 through 29a and in the following tables, arranged according to periodic group of the major component. In several instances a particularly large class of alloys has been separately presented, i. e., copper-nickel alloys. Many of the experimental results are for a limited temperature range, so more of the data are presented in tables than in section 2.2 on metals. This section is also not as complete as section 2.2 because many of the data were published in now unavailable journals or institute reports. As for the preceding tables the following tables contain columns indicating the curve identifying marks, composition, conductivity, remarks, and reference. In addition, they occasionally contain information on trade designation or sym-

bols and manufacturing tempers. The names or numbers and the arrangement within a group are based upon the corresponding arrangements in Metals Handbook.<sup>1</sup> The composition limits for many of the alloys are also taken from the Metals Handbook. The tables listed below, which quote "company or trade manuals", are all based on room-temperature values.

In pure metals the greater part of the energy transfer is by electrons, whereas in alloys the transfer by the lattice vibration is very significant and may be the predominant mode. For that reason the conductivity is not as sensitive to small differences in composition as it is in nearly pure metals. It will be noted in the following graphs that the conductivity curves of alloys with similar compositions are usually parallel to each other and seldom intersect.

<sup>1</sup>Metals Handbook, 1948 ed., Am. Soc. for Metals, Cleveland, Ohio.

### ALKALI METAL ALLOYS

Nominal Composition (%)	Conductivity and remarks	Reference
	w/cm deg K	
Sodium-potassium; 50-50 by atomic percent.	$k = 0.29$ at $-8.9^{\circ}\text{C}$ , $0.30$ at $-10.6^{\circ}\text{C}$ .....	J. W. Hornbeck (1913).

### BERYLLIUM

Commercially pure; Beryllium Co. of America.	See figure 2, under "Metallic Elements".....	E. J. Lewis (1929).
Copper-beryllium	See "Copper Alloys".....	

### MAGNESIUM ALLOYS

0.5 Mn.....	$k = 1.60$ at $273^{\circ}\text{K}$ , $1.34$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	J. Staebler (1929).
0.8 Mn.....	$k = 1.58$ at $273^{\circ}\text{K}$ , $1.22$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
2 Mn.....	$k = 1.18$ at $273^{\circ}\text{K}$ , $0.67$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
3.54 Mn.....	$k = 1.02$ at $273^{\circ}\text{K}$ , $0.57$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
6 Al.....	$k = 0.80$ at $273^{\circ}\text{K}$ , $0.59$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
8 Al.....	$k = 0.65$ at $273^{\circ}\text{K}$ , $0.42$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
12 Al.....	$k = 0.59$ at $273^{\circ}\text{K}$ , $0.33$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
0.7 Si.....	$k = 1.48$ at $273^{\circ}\text{K}$ , $1.10$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
1.5 Si.....	$k = 1.40$ at $273^{\circ}\text{K}$ , $0.95$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
8 Ce.....	$k = 1.25$ at $273^{\circ}\text{K}$ , $1.06$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
12 Ce.....	$k = 1.03$ at $273^{\circ}\text{K}$ , $0.81$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
8 Cu.....	$k = 1.25$ at $273^{\circ}\text{K}$ , $0.88$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
8 Zn.....	$k = 1.19$ at $273^{\circ}\text{K}$ , $0.89$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
8 Cd.....	$k = 1.42$ at $273^{\circ}\text{K}$ , $1.30$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
2 Si, 6 Al.....	$k = 0.69$ at $273^{\circ}\text{K}$ , $0.48$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
2 Si, 8 Al.....	$k = 0.61$ at $273^{\circ}\text{K}$ , $0.38$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
2 Si, 10 Al.....	$k = 0.55$ at $273^{\circ}\text{K}$ , $0.29$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.
2 Si, 12 Al.....	$k = 0.54$ at $273^{\circ}\text{K}$ , $0.28$ at $87^{\circ}\text{K}$ <sup>1</sup> .....	Do.

<sup>1</sup> Chill-cast; also measured R.

### MAGNESIUM ALLOYS (Cont'd)

Nominal Composition (%)	Conductivity and Remarks	Reference
	w/cm deg K	
15 Cu.....	$k = 1.54$ at $273^{\circ}\text{K}$ , $1.51$ at $87^{\circ}\text{K}$ ; chill-cast....	W. Mannchen (1931).
20 Cu, 3 Si.....	$k = 1.08$ at $273^{\circ}\text{K}$ , $0.89$ at $87^{\circ}\text{K}$ ; chill-cast....	Do.
2.2 Ag.....	$k = 1.31$ at $25^{\circ}\text{C}$ <sup>2</sup> .....	R. Kikuchi (1932).
6.0 Ag.....	$k = 1.16$ at $27^{\circ}\text{C}$ <sup>2</sup> .....	Do.
2.1 Al.....	$k = 0.88$ at $27^{\circ}\text{C}$ <sup>2</sup> .....	Do.
4.2 Al.....	$k = 0.69$ at $22^{\circ}\text{C}$ <sup>2</sup> .....	Do.
6.2 Al.....	$k = 0.56$ at $22^{\circ}\text{C}$ <sup>2</sup> .....	Do.
3.2 Al.....	$k = 0.51$ at $18^{\circ}\text{C}$ <sup>2</sup> .....	Do.
10.3 Al.....	$k = 0.45$ at $19^{\circ}\text{C}$ <sup>2</sup> .....	Do.
12.2 Al.....	$k = 0.39$ at $23^{\circ}\text{C}$ <sup>2</sup> .....	Do.
2.4 Cu.....	$k = 1.39$ at $20^{\circ}\text{C}$ <sup>2</sup> .....	Do.
6.3 Cu.....	$k = 1.31$ at $24^{\circ}\text{C}$ <sup>2</sup> .....	Do.
1.9 Ni.....	$k = 1.36$ at $20^{\circ}\text{C}$ <sup>2</sup> .....	Do.
5.8 Ni.....	$k = 1.26$ at $24^{\circ}\text{C}$ <sup>2</sup> .....	Do.
2.2 Sn.....	$k = 1.06$ at $21^{\circ}\text{C}$ <sup>2</sup> .....	Do.
6.4 Sn.....	$k = 0.74$ at $22^{\circ}\text{C}$ <sup>2</sup> .....	Do.
2.1 Zn.....	$k = 1.26$ at $26^{\circ}$ <sup>2</sup> .....	Do.
6.1 Zn.....	$k = 1.09$ at $26^{\circ}\text{C}$ <sup>2</sup> .....	Do.
4 Zn, 0.5 Cu.....	"Elektron" $k = 1.14$ at $26^{\circ}\text{C}$ <sup>2</sup> .....	Do.
4 Al, 1 Zn, 1 Cd, 1 Sn.....	$k = 0.56$ at $22^{\circ}\text{C}$ <sup>2</sup> .....	Do.
6 Al, 3 Zn, 0.4 Cu.....	"Dow metal" $k = 0.61$ at $29^{\circ}\text{C}$ <sup>2</sup> .....	Do.
4 Al, 0.5 Zn, 2 Cd, 1 Sn.....	$k = 0.63$ at $22^{\circ}\text{C}$ <sup>2</sup> .....	Do.
4 Al, 3 Cd, 1 Sn.....	$k = 0.69$ at $22^{\circ}\text{C}$ <sup>2</sup> .....	Do.
4 Al, 2 Cd, 2 Sn.....	$k = 0.56$ at $30^{\circ}\text{C}$ <sup>2</sup> .....	Do.

<sup>2</sup> Vacuum-annealed.

**MAGNESIUM ALLOYS (Cont'd)**  
**COMPANY AND TRADE MANUALS**

ASTM designation	Trade designations	Nominal composition (%)	Conductivity
			w/cm deg K
A 9	Dowmetal A; Maslo AM 241; British DTD 59A, DTD 289, Elektron A8, Elektron A8K.	8 Al, 0.3 Mn	.75
A 10	Dowmetal G; Maslo AM 240; AM-C598; British DTD 259; Elektron VI.	10 Al, 0.1 Mn	.71
AM 80 A		See A 8	
AM 100 A		See A 10	
AZ 31X, A, B	Dowmetal FS-1; Maslo AM-C52S; Whitelight FS-1; British DTD 120A; Elektron AZ 31.	3 Al, 1 Zn, 0.3 Mn	.96
AZ 51 X	Dowmetal JS-1	5 Al, 1 Zn, 0.25 Mn	.88
AZ 61 X, A, B	Dowmetal J-1; Maslo AM-C57S; Whitelight J-1; British DTD 88B, DTD 120A, DTD 259; Elektron AZM.	6 Al, 1 Zn, 0.2 Mn	.80
AZ 63, A	Dowmetal H; Maslo AM 265; British DTD 59A, DTD 289; Elektron AZG.	6 Al, 3 Zn, 0.2 Mn	.75
AZ 80 X, A	Dowmetal 0-1; Maslo AM-C58S; Whitelight 0-1; British DTD 88B; Elektron AZ 855.	8.5 Al, 0.5 Zn, .15 Mn	.75
AZ 91 A, B, C	Dowmetal R, RC; Maslo AM 263; British DTD 136A; Elektron AZ 91.	9 Al, 0.7 Zn, 0.2 Mn	.71
AZ 92, A	Dowmetal C; Maslo AM 260	9 Al, 2 Zn, 0.1 Mn	.71
M 1 A, B	Dowmetal M; Maslo AM403, AM 3S; Whitelight M; British DTD 142, 118, 140A; Elektron AM 503.	1.5 Mn	1.26
	Maslo AM 244	4 Al, 0.2 Mn	0.96
	Dowmetal EK 30A	3 rare earths, 0.35 Zr, 0.3 Zn	.27

**ALUMINUM ALLOYS (Cont'd)**

Composition (%) <sup>1</sup>	Conductivity <sup>1</sup>	State <sup>1</sup>
	w/cm deg K	
5.3 Cu, 0.5 Si, 0.8 Fe, 0.5 Mn, 1.2 Mg. <sup>2</sup>	1.18 1.52	Cast. Annealed.
4.3 Cu, 0.4 Si, 0.9 Fe, 0.6 Mn, 0.4 Mg. <sup>2</sup>	1.22 1.52	Cast. Annealed.
2.5 Cu, 0.4 Si, 0.9 Fe, 1.8 Ni, 0.9 Mg. <sup>2</sup>	1.44 1.63	Cast. Annealed.
4.4 Cu, 0.5 Si, 0.7 Fe, 2.1 Ni, 0.9 Mg. <sup>2</sup>	1.30 1.47	Cast. Annealed.
3.8 Cu, 6.1 Si, 0.9 Fe, 0.6 Mn, 1.6 Mg. <sup>2</sup>	1.00 1.36	Cast. Annealed.
2.7 Cu, 0.4 Si, 0.6 Fe, 12.0 Zn. <sup>2</sup>	1.32 1.33	Cast. Annealed.
2.6 Cu, 0.4 Si, 0.6 Fe, 20.3 Zn. <sup>2</sup>	1.07 1.08	Cast. Annealed.
2.5 Cu, 0.3 Si, 0.8 Fe, 0.5 Mn, 2.6 Zn. <sup>2</sup>	1.26 1.45	Cast. Annealed.
1.9 Cu, 0.1 Si, 1 Fe, 1.5 Mg. <sup>2</sup>	1.57 1.65	Cast. Annealed.
1.8 Cu, 0.4 Si, 0.9 Fe, 0.9 Cr. <sup>2</sup>	1.05 1.09	Cast. Annealed.
1.8 Cu, 0.3 Si, 0.6 Fe, 1 Ni, 1.6 Mg. <sup>2</sup>	1.48 1.65	Cast. Annealed.
11.9 Si, 0.8 Fe. <sup>2</sup>	1.31 1.78	Cast. Annealed.
0.1 Si, 0.6 Fe. <sup>2</sup>	1.86 2.00	Cast. Annealed.
8.1 Cu, 0.4 Si, 0.6 Fe. <sup>2</sup>	1.33 1.32	Quenched. Aged.
5.3 Cu, 0.5 Si, 0.8 Fe, 0.5 Mn, 1.2 Mg. <sup>2</sup>	1.23 1.23	Quenched. Aged.
2.5 Cu, 0.4 Si, 0.9 Fe, 1.8 Ni, 0.9 Mg. <sup>2</sup>	1.38 1.33	Quenched. Aged.
3.8 Cu, 6.1 Si, 0.9 Fe, 0.6 Mn, 1.6 Mg. <sup>2</sup>	1.16 1.14	Quenched. Aged.
2.6 Cu, 0.4 Si, 0.6 Fe, 20.3 Zn. <sup>2</sup>	0.98 0.98	Quenched. Aged.
2.5 Cu, 0.3 Si, 0.9 Fe, 0.5 Mn, 2.6 Zn. <sup>2</sup>	1.32	Quenched.
1.9 Cu, 0.1 Si, 1 Fe, 1.5 Mg. <sup>2</sup>	1.59	Quenched.
1.8 Cu, 0.3 Si, 0.6 Fe, 1.0 Ni, 1.6 Mg. <sup>2</sup>	1.45	Quenched.
5.3 Cu, 0.5 Si, 0.8 Fe, 0.5 Mn, 1.2 Mg. <sup>2</sup>	1.36 1.60	Drawn. Annealed.
4.3 Cu, 0.4 Si, 0.9 Fe, 0.4 Mn, 0.6 Mg. <sup>2</sup>	1.48 1.73	Drawn. Annealed.
11.9 Si, 0.8 Fe. <sup>2</sup>	1.73 1.81	Drawn. Annealed.
0.1 Si, 0.5 Fe. <sup>2</sup>	2.06 2.07	Drawn. Annealed.

**ALUMINUM ALLOYS**


Composition (%)	Conductivity and remarks	Reference
	w/cm deg K	
0.5 Fe, 0.4 Cu	k=2.01 at 18° C.	W. Jaeger and H. Dinselhorst (1900).
Commercial	k=1.93 at 0° C, 1.90 at 85° K, 1.59 at 21.4° K.	R. Schott (1916).
Composition (%) <sup>1</sup>	Conductivity <sup>1</sup>	State <sup>1</sup>
	w/cm deg K	
12.2 Cu, 0.3 Si, 0.6 Fe. <sup>2</sup>	1.24 1.48	Cast. Annealed.
12.2 Cu, 0.2 Si, 0.6 Fe, 1 Mn. <sup>2</sup>	0.93 1.33	Cast. Annealed.
10.5 Cu, 0.3 Si, 0.8 Fe, 1 Ni, 3 Sn. <sup>2</sup>	1.35 1.59	Cast. Annealed.
8.4 Cu, 0.3 Si, 0.7 Fe, 0.7 Mn. <sup>2</sup>	1.02 1.35	Cast. Annealed.
8.1 Cu, 0.4 Si, 0.6 Fe. <sup>2</sup>	1.39 1.67	Cast. Annealed.
6.9 Cu, 0.3 Si, 0.7 Fe, 1.2 Sn. <sup>2</sup>	1.47 1.66	Cast. Annealed.

<sup>1</sup> Results by H. Masumoto (1925) at 27° C.

<sup>2</sup> The samples were chill cast in an iron mold, then annealed for 30 minutes at 450° C.

<sup>3</sup> Chill-cast in an iron mold, annealed, then heated for 30 minutes at about 500° C, quenched in water, and later aged two weeks.

<sup>4</sup> Chill-cast in an iron mold, forged, then cold-drawn to 60% of original diameter, and later annealed for 30 minutes at 500° C.



**ALUMINUM ALLOYS (Cont'd)**

Nominal composition (%)	Conductivity and remarks	Reference
	w/cm deg K	
8 Cu.....	$k=1.32$ at 273°K; $0.88$ at 87°K...	W. Mannchen (1931).
Do.....	$k=1.31$ at 273°K; $0.90$ at 87°K...	Do.
15 Cu.....	$k=1.48$ at 273°K; $.90$ at 87°K...	Do.
8 Mg.....	$k=1.00$ at 273°K; $.73$ at 87°K...	Do.
Do.....	$k=1.05$ at 273°K; $.77$ at 87°K; thermally treated.	Do.
12 Mg.....	$k=0.77$ at 273°K; $.56$ at 87°K...	Do.
14 Mg.....	$k=0.69$ at 273°K; $.44$ at 87°K; thermally treated.	Do.
20 Si.....	$k=1.59$ at 273°; $1.21$ at 87°K; "Alusil".	Do.
4 Cu, 2 Ni, 1.5 Mg; "Y" Alloy".....	$k=1.62$ at 273°K; $1.12$ at 87°K...	Do.
Do.....	$k=1.53$ at 273°K; $1.38$ at 87°K; thermally treated.	Do.
Mg, Mn, Sb; K-S Alloy 245.....	$k=1.07$ at 273°K; $1.00$ at 87°K...	Do.
Mn, Mg, Sb; K-S Alloy 280.....	$k=1.00$ at 273°K; $0.80$ at 87°K...	Do.
Mn, Mg, Sb; K-S Alloy Special.....	$k=1.39$ at 273°K; $1.14$ at 87°K...	Do.
Cu, Mn, Mg; Nelson-Kolben 10.....	$k=1.60$ at 273°K; $1.32$ at 87°K...	Do.
Cu; Nelson-Kolben Vn 1.....	$k=1.43$ at 273°K; $1.18$ at 87°K...	Do.
Cu; Nelson-Kolben.....	$k=1.59$ at 273°K; $1.30$ at 87°K...	Do.
3-5 Cu, 0.5 Mg.....	$k=1.60$ at 273°K; $0.89$ at 87°K...	Do.

**ALUMINUM ALLOYS (Cont'd)**

Curve	Composition (%)	Remarks	Reference
N.-"Dural".....	0.57 Mg, 0.42 Fe, 4.10 Cu, 94.0 Al.	As stamped; "Duraluminium".	J. de Nobel (1951).
P. Z. J.-J51.....	0.29 Cu, 0.56 Mg, 0.02 Mn, 0.56 Fe, 0.30 Si, 0.01 Cr, 0.01 Ti.		R. W. Powers, J. B. Ziegler, and H. L. Johnston (1951).
P. Z. J.-4S.....	0.16 Cu, 1.02 Mg, 1.20 Mn, 0.52 Fe, 0.13 Si, 0.02 Cr, 0.02 Ti.		Do.
P. Z. J.-75S.....	1.5 Cu, 5.5 Zn, 2.5 Mg, 0.2 Mn, 0.3 Cr.		Do.
P. Z. J.-24S.....	4.49 Cu, 0.01 Zn, 1.47 Mg, 0.66 Mn, 0.34 Fe, 0.13 Si, 0.01 Cr, 0.02 Ti.		Do.

**ALUMINUM ALLOYS (Cont'd)**  
**COMPANY AND TRADE MANUALS**

ASTM designation	Trade designation	Nominal compositions (%)	Conductivity	State
			w/cm deg K	
A2	EC 2S; British BS 2L	99.45 Al 99 Al	2.34 2.22 2.18	Annealed. H 18

**WROUGHT ALLOYS**

MI	3S	1.2 Mn	1.93 1.63 1.59 1.55	O H 12 H 14 H 18
	4S	1.2 Mn, 1 Mg	1.63 1.63	O H 38
CP 21	11S; British BS 6L1	5.5 Cu, 0.5 Pb, 0.5 Bi	1.55	T 3
CS 41	14S; British DTD 364	4.4 Cu, 0.8 Si, 0.8 Mn, 0.4 Mg	1.93 1.55 1.21	O T 6 T 4
CM 21	17S; British BS 6L1	4 Cu, 0.5 Mg, 0.5 Mn	1.72 1.21	O T 4
	A 17S	2.5 Cu, 0.3 Mg	1.55	T 4
	18S; British BS 4L25, BS 2L42	4 Cu, 2 Ni, 0.5 Mg	1.93 1.55	O T 61
	B18S	4 Cu, 1.5 Mg, 2.0 Ni	1.93	O
CG 21	24S; British BS2L40, DTD 273	4.5 Cu, 1.5 Mg, 0.6 Mn	1.88 1.21	O T 4
	25S	4.5 Cu, 0.8 Mn, 0.8 Si	1.55 1.93	O T 6
	32S	12.5 Si, 1.0 Mg, 0.9 Cu, 0.9 Ni	1.55 1.38	O T 6
	50S	1.2 Mg	1.93 1.93	O H 38
	C50S	1.3 Mg	1.55	O
	A 51 S	1.0 Si, 0.6 Mg, 0.25 Cr	2.09 1.72	O T 4
GR 1	52S	2.5 Mg, 0.25 Cr	1.38 1.38	O H 38
	53S	1.3 Mg, 0.7 Si, 0.25 Cr	1.72 1.55	O T 4
	56S; British DTD 303	5.2 Mg, 0.1 Mn, 0.1 Cr	1.17 1.09	O H 18
GS 21	61S	1 Mg, 0.6 Si, 0.25 Cu, 0.25 Cr	1.72 1.55	O T 4
	62S	0.25 Cu, 0.6 Si, 1 Mg	1.72 1.55	O T 4
	63S	0.4 Cu, 0.7 Mg	1.93 2.09	T 42 T 5
ZG 42	75S	5.5 Zn, 2.5 Mg, 1.5 Cu, 0.3 Cr, 0.2 Mn	1.21	T 6
	R 301	1 Mg, 0.7 Si, 0.5 Mn	1.93 1.21	O T 4
			1.55	T 6
	R 317	4 Cu, 0.5 Mn, 0.5 Mg, Pb, 0.5 Bi	1.72 1.21	O T 4

**CASTING ALLOYS**

S5	13	12 Si	1.55 to 1.21	
S4	43	5 Si	1.47	Annealed.
SC 2	85	5 Si, 4 Cu	1.17	
	108	4 Cu, 3 Si	1.21 1.47	Cast. Annealed.
SC 8	Allcast	5 Si, 3 Cu	1.05 1.17 1.13 1.38	Cast. Relieved. Aged. T 7
SC 1	A108	5.5 Si, 4.5 Cu	1.42	
	112	7 Cu, 1.7 Zn	1.17 1.47	Annealed.
CS 22	113	7 Cu, 2 Si, 1.7 Zn	1.17 1.47	Annealed.
CS 22	C113	7 Cu, 3.5 Si	1.09	
CG 1	122	10 Cu, 0.2 Mg	1.59 1.30 1.34	T 2 T 61

**ALUMINUM ALLOYS (Cont'd)**  
**COMPANY AND TRADE MANUALS**

ASTM designation	Trade designation	Nominal compositions (%)	Conductivity	State
			w/cm deg K	
SC 41	A 132	12 Si, 2.5 Ni, 1.2 Mg, 0.8 Cu	1.17	T 551
	D 132	9 Si, 3.5 Cu, 0.8 Mg, 0.8 Ni	1.09	T 5
	138	10 Cu, 4 Si, 0.3 Mg	1.05	
CN 21	142	4 Cu, 2 Ni, 1.5 Mg	1.67 1.34 1.51 1.30	T 21 T 571 T 77 T 61
C 1	195	4.5 Cu	1.38 1.47	T 4 T 62
CS 4	B 195	4.5 Cu, 2.5 Si	1.38	T 4
			1.42 to 1.88	T 6
	212	8 Cu, 1.2 Si	1.17	
G 1	214; British DTD 165	3.8 Mg	1.38	Annealed.
	A 214	3.8 Mg, 1.8 Zn	1.34	
	B 214	3.8 Mg, 1.8 Si	1.47	
	F 214	3.8 Mg, 0.5 Si	1.42	
	218	8 Mg	0.96	
	220	10 Mg	.88	T 4
SC 8	319	6 Si, 3.5 Cu	1.13	
	333	9 Si, 3.8 Cu	1.05 1.21 1.17 1.42	F T 5 T 6 T 7
SC 21	355	5 Si, 1.3 Cu, 0.5 Mg	1.67 1.42 1.47 1.63	T 51 T 6 T 61 T 7
SG 1	356	7 Si, 0.3 Mg	1.51 1.67 1.55 1.59 1.63	Chill T 6 T 51 T 6 T 7 Chill T 6
	360, A360	9.5 Si	1.13 to 1.47	
	380, A380	9 Si, 3.5 Cu	0.96 to 1.09	
	384	12 Si, 3.8 Cu	0.96	
	A612	6.5 Zn, 0.7 Mg, 0.5 Cu	.96	
	C 612	6.5 Zn, 0.5 Cu, 0.4 Mg	1.59	
	750	6.5 Sn, 1 Cu, 1.0 Ni	1.80	

**TITANIUM ALLOYS**

Curve	Composition (%)	Conductivity and Remarks	Reference
		w/cm deg K	
	2.8 Cr, 1 Fe	Abstract only; $k = 0.13$ at 273°K, 0.10 at 195°K, 0.06 at 80°K.	C. J. Rigney and L. I. Bockstaber (1951).
Fig. 29; T.W.-Ti.	Rem-Cru Titanium, RC 130-B; 4.7 Mn, 3.99 Al, 0.14 C.	R, emf	W. W. Tyler and A. C. Wilson (1962).

**TUNGSTEN**

Composition	Conductivity and remarks	Reference
	w/cm deg K	
"Impure"	Single crystal; $k = 1.83$ at 83°K, 1.80 at 21°K	E. Gruneisen and E. Goens (1927).

**CHROMIUM  
COMPANY AND TRADE MANUALS**

Composition	Conductivity
Commercial.....	$k=0.67$ at 20°C. w/cm deg K

**IRON**

See figures 8 and 9 under "METALLIC ELEMENTS"

**STEELS**

The tables for steels are arranged into groups where the principal alloying metals are as follows: carbon; silicon; copper, chromium, cobalt, manganese, molybdenum, nickel, tungsten, vanadium; and aluminum.

**CARBON STEELS**

Composition (%)	Conductivity and remarks	Reference
	w/cm deg K	
0.1 C.....	$k=0.67$ at 18°C; wrought iron.....	W. Jaeger and H. Diesselhorst (1900).
1 C.....	$k=0.45$ at 18°C, wrought iron.....	Do.
0.1 C, 0.06 Mn, 0.05 Cu, 0.02 Si, S, 0.03 P.	$k=0.72$ at 18°C.....	E. Grüneisen (1900).
0.57 C, 0.2 Si, 0.1 Mn, 0.04 S, 0.03 Cu, 0.01 P.	$k=0.52$ at 18°C.....	Do.
0.99 C, 0.1 Mn, 0.06 Si, 0.03 S, Cu.	$k=0.51$ at 18°C.....	Do.
1.5 C, 0.2 Mn, 0.05 Si, 0.03 Cu, S, 0.01 P.	$k=0.50$ at 18°C.....	Do.
1 C; "silver steel".....	See figure 23, curve with initial L.....	C. H. Lees (1908).

**CARBON STEELS (Cont'd)**

Composition (%) <sup>1</sup>	Conductivity <sup>1</sup>	State <sup>1</sup>
	w/cm deg K	
0.1 C, 0.4 Mn, 0.02 P, 0.02 S.....	.60	
0.4 C, 0.3 Si, 0.4 Mn, 0.02 P, 0.02 S.....	.44	
0.7 C, 0.2 Si, 0.2 Mn, 0.03 P, 0.02 S.....	.46	
0.9 C, 0.3 Si, 0.2 Mn, 0.03 P, 0.02 S.....	.42	
1.0 C, 0.2 Si, 0.2 Mn, 0.03 P, 0.02 S.....	.42	
1.2 C, 0.3 Si, 0.2 Mn, 0.03 P, 0.02 S.....	.40	
1.5 C, 0.2 Si, 0.2 Mn, 0.03 P, 0.02 S.....	.39	
2.41 C, 0.12 Si, 0.05 Mn, 0.04 P, 0.09 S.....	.32	As cast.
	.33	Annealed 1,000°C, 2 hr.
	.33	6 hr.
	.33	8 hr.

**CARBON STEELS (Cont'd)**

Composition (%) <sup>1</sup>	Conductivity <sup>1</sup>	State <sup>1</sup>
	w/cm deg K	
2.53 C, 0.05 Si, 0.02 Mn, 0.01 P, 0.03 S.....	.31	As cast.
2.67 C, 0.11 Si, 0.02 Mn, 0.03 P, 0.05 S.....	.30	Do.
	.32	1,000°C annealed, 2 hr.
	.32	6 hr.
	.32	8 hr.
3.12 C, 0.06 Si, 0.05 Mn, 0.02 P, 0.06 S.....	.26	As cast.
3.14 C, 0.01 Si, 0.03 Mn, 0.02 P, 0.03 S.....	.26	Do.
3.17 C, 0.21 Si, 0.08 Mn, 0.04 P, 0.06 S.....	.25	Do.
	.26	Annealed 1,000°C, 2 hr.
	.26	6 hr.
	.27	8 hr.
3.53 C, 0.04 Si, 0.05 Mn, 0.01 P, 0.05 S.....	.23	As cast.
3.64 C, 0.16 Si, 0.04 Mn, 0.02 P, 0.02 S.....	.21	Do.
	.23	Annealed 1,000°C, 2 hr.
	.23	6 hr.
	.23	8 hr.
3.93 C, 0.15 Si, 0.04 Mn, 0.02 P, 0.05 S.....	.20	As cast.
3.96 C, 0.2 Si, 0.06 Mn, 0.01 P, 0.02 S.....	.19	As cast.
	.21	Annealed 1,000°C, 2 hr.
	.26	6 hr.
	.50	8 hr.
4.13 C, 0.10 Si, 0.03 Mn, 0.02 P, 0.02 S.....	.18	As cast.
4.26 C, 0.10 Si, 0.03 Mn, 0.02 P, 0.02 S.....	.17	As cast.
4.35 C, 0.35 Si, 0.08 Mn, 0.02 P, 0.02 S.....	.15	Annealed 1,000°C, 2 hr.
4.40 C, 0.34 Si, 0.03 Mn, 0.02 P, 0.08 S.....	.15	As cast.
4.61 C, 0.37 Si, 0.03 Mn, 0.02 P, 0.04 S.....	.17	Annealed 1,000°C, 2 hr.
4.63 C, 0.54 Si, 0.08 Mn, 0.02 P, 0.07 S.....	.13	As cast.
4.63 C, 0.54 Si, 0.08 Mn, 0.02 P, 0.07 S.....	.13	Annealed 1,000°C, 2 hr.
3.82 C, 1.24 Si, 0.09 Mn, 0.01 P, 0.06 S.....	.13	As cast.
3.81 C, 1.96 Si, 0.05 Mn, 0.05 S.....	.20	Annealed 800°C, 1 hr.
	.13	As cast.
	.35	Annealed 800°C, 1 hr.
	.40	Add. annealed 1,000°C
		1 hr.
3.84 C, 1.98 Si, 0.06 Mn, 0.01 S.....	.43	As cast.
	.52	Annealed 800°C, 1 hr.


<sup>1</sup> Results by H. Masumoto (1927) at 25°C.

**CARBON STEELS (Cont'd)**

Curve	Composition (%)	Remarks	Reference
Fig. 24; Mild..	0.14 C, 0.08 Si, 0.07 Mn...	"Mild steel"; heated to 800°C and furnace-cooled.	J. de Nobel (1951).
Fig. 23; P. Z. J.-SAE 1020.	0.33 Mn, 0.18 C, 0.014 Si...		R. W. Powers, J. B. Ziegler, H. L. Johnston (1951a).
Fig. 23; P. Z. J.-SAE 1095.	0.93 C, 0.34 Mn, 0.26 Si, 0.1 Ni, Cr, 0.05 Mo.		Do.

**CARBON STEELS (Cont'd)  
COMPANY AND TRADE MANUALS**

Composition (%)	Conductivity
	w/cm deg K
0.08 C, 0.045 Cr, 0.07 Ni, 0.31 Mn, 0.02 Mo.....	.59
0.23 C, trace Cr, 0.074 Ni, 0.635 Mn, 0.13 Cu.....	.52
0.415 C, trace Cr, 0.063 Ni, 0.643 Mn, 0.12 Cu.....	.52
0.80 C, 0.11 Cr, 0.13 Ni, 0.32 Mn, 0.07 Cu, 0.01 Mo.....	.49
1.22 C, 0.11 Cr, 0.13 Ni, 0.35 Mn, 0.01 Mo, 0.08 Cu.....	.45



Specific references can be found under the type of steel.

**SILICON STEELS**

Composition (%)	Conductivity and remarks	Reference
0.2 Si, 0.1 C, 0.1 Mn, trace of P, S, and Cu.	w/cm deg K $k=0.60$ at 18°C.....	W. Jaeger and H. Diesselhorst (1900).


**CORROSION RESISTING STEELS**

(Copper, chromium, cobalt, manganese, molybdenum, nickel, tungsten, and vanadium)

Curve	Composition (%)	Remarks	Reference
Fig. 23; Kr. Sc.	0.6 Mn, 0.4 C, 0.3 Si, 0.03 S, 0.3 P.	.....	J. Karweil and K. Schäfer (1939).
.....	"Stainless".....	$k=7$ mw/cm deg K at 10°K, 11 at 15°K, 15 at 20°K.	K. R. Wilkinson and J. Wilks (1949).

**CORROSION RESISTING STEELS (Cont'd)**

Curve	Composition (%)	Remarks	Reference
Fig. 24; 2% Ni.	1.92 Ni, 0.72 Mn, 0.21 Si, 0.14 C.	Heated to 800°C and furnace-cooled.	J. de Nobel (1951).
24% Ni.....	24.30 Ni, 6.05 Mn, 1.18 C.	Heated to 1,060°C and water-quenched.	Do.
27% Ni.....	27.30 Ni, 14.6 Cr, 3.5 W, 1.62 Si, 1.34 Mn, 0.44 C.	Heated to 1,000°C and water-quenched, "era/ATV".	Do.
31% Ni.....	31.4 Ni, 0.82 Mn, 0.7 C....	Heated to 800°C and furnace-cooled.	Do. Do.
36% Ni.....	36.17 Ni, 0.92 Mn, 0.16 C, 0.09 Si.	Heated to 1,060°C and water-quenched.	Do.
57% Ni.....	57.5 Ni, 1.31 Mn, 0.34 C, 0.14 Si.	As forged; "A.M.F."	Do.
2% Mn.....	2.23 Mn, 0.41 C, 0.07 Si...	Heated to 800°C and furnace-cooled.	Do.
13% Mn, 1% C.	12.69 Mn, 1.27 C, 0.12 Si...	Heated to 2,000°C and water-quenched, "manganese steel".	Do. Do.
13% Mn.....	12.95 Mn, 0.10 S, 0.12 Si, 0.09 C, 0.06 P.	Heated to 1,000°C and water-quenched.	Do.
39% Mn.....	38.9 Mn, 0.7 Si, 0.2 C, 0.06 S, 0.04 P.	.....do.....	Do.



Specific references can be found under the type of steel.

**CORROSION RESISTING STEELS (Cont'd)**

Curve	Composition (%)	Remarks	Reference
13% Cr.....	13.5 Cr, 0.36 C, 0.22 Si, 0.13 Mn.	Heated to 800°C and furnace-cooled.	J. de Nobel (1951).
13% Cr, quenched.	.....do.....	Heated to 950°C, oil quenched, reheated to 450°C, air-cooled.	Do.
19% Cr.....	18.8 Cr, 8.1 Ni, 0.43 Si, 0.24 Mn, 9.12 C.	Heated to 1,150°C and water-quenched.	Do.
3% Ni.....	2.61 Ni, 0.75 Mo, 0.49 Cr, 0.45 Mn, 0.27 C, 0.11 Si, 0.03 P, 0.01 S.	Heated to 850°C, oil-quenched, reheated to 650°C, water-quenched.	Do.
Fig. 23; P.Z.J.-SAE 4130.	0.99 Cr, 0.52 Mn, 0.33 C, 0.2 Si, Ni, and Mo each.		R. W. Powers, J. B. Ziegler, and H. L. Johnston (1951a).
P. Z. J.-410.....	12.6 Cr, 0.36 Si, 0.32 Mn, 0.12 Ni, 0.09 C, 0.06 Cu, 0.03 N, 0.01 P.		Do.

**CORROSION RESISTING STEELS (Cont'd)**

Curve	Composition (%)	Remarks	Reference
P.Z.J.-347.....	17.88 Cr, 10.28 Ni, 1.24 Mn, 0.85 Nb, 0.57 Si, 0.26 Cu, 0.06 C, 0.03 N, 0.02 P.		R. W. Powers, J. B. Ziegler, and H. L. Johnston (1951a).
P. Z. J.-304.....	18.68 Cr, 8.84 Ni, 1.12 Mn, 0.43 Si, 0.06 Cu, 0.06 C, 0.03 N, 0.02 P.		Do.
Fig. 23; B-Stainless.	7.9 Ni, 18.9 Cr, 1 Ti, 0.7 Si, 0.1 C.	Austenite grains about 0.01 mm across.	R. Berman (1951b).
Fig. 23; Es. Zi.-303.	18 Cr, 9 Ni, 0.15 C.....		I. Estermann and J. E. Zimmerman (1952).
Es. Zi.-347.....	18 Cr, 10 Ni, 0.5 Nb, 0.08 C.		Do.
T.W.-316.....	17 Cr, 12 Ni, 2.5 Mo, 0.1 C.	25% cold reduction..	W. W. Tyler and A. C. Wilson (1952).



**CORROSION RESISTING STEELS (Cont'd)  
COMPANY AND TRADE MANUALS**


AISI No.	Nominal composition (%)	Conductivity w/cm deg K
.....	0.08 C, .045 Cr, .07 Ni, .31 Mn, .02 Mo.....	0.59
.....	0.23 C, trace Cr, .074 Ni, .635 Mn, .13 Cu.....	.52
.....	0.415 C, trace Cr, .063 Ni, .643 Mn, .12 Cu.....	.52
.....	0.325 C, .17 Cr, 3.47 Ni, 0.55 Mn, .09 Cu, .04 Mo.....	.37
.....	0.34 C, 0.78 Cr, 3.53 Ni, 0.55 Mn, .39 Mo, .05 Cu.....	.33
.....	0.315 C, 1.09 Cr, 0.073 Ni, .69 Mn, .012 Mo, .07 Cu.....	.48
.....	0.35 C, .88 Cr, .26 Ni, .59 Mn, .2 Mo, .12 Cu.....	.43
.....	5 Cr, 0.5 Mo.....	.37
.....	1.22 C, 0.03 Cr, .07 Ni, 13.0 Mn, 0.22 Si, .07 Cu.....	.13
.....	0.28 C, trace Cr, 28.37 Ni, 0.89 Mn, .15 Si, .03 Cu.....	.13
.....	0.08 C, 19.11 Cr, 8.14 Ni, 0.37 Mn, .68 Si, .6 W, .03 Cu.....	.16
.....	0.13 C, 12.95 Cr, 0.14 Ni, .25 Mn, .17 Si, .06 Cu, .01 V.....	.27
.....	0.27 C, 13.69 Cr, 0.21 Ni, .28 Mn, .25 W, .02 V.....	.26
.....	0.715 C, 4.26 Cr, 0.067 Ni, .25 Mn, 18.45 W, 1.08 V.....	.25
302	0.14 C, 18 Cr, 9 Ni, 2 Mn.....	.22
303	0.15 C, 18 Cr, 9 Ni, 0.07 P, S, Se each, .6 Zr, Mo each.....	.22
309	0.20 C, 23 Cr, 13 Ni, 2 Mn.....	.19
410	0.15 C, 12.5 Cr.....	.40
418	0.15 C, 13 Cr, 0.07 P, S, Se each, .6 Zr, Mo each.....	.40
420	0.15 C or more, 13 Cr.....	.33
430	0.12 C, 16 Cr.....	.30
440	0.7 C, 17 Cr, 0.75 Mo.....	.25
.....	15 Cr, 35 Ni.....	.13

**NICKEL ALLOYS  
COMPANY AND TRADE MANUALS**

Trade Designation	Nominal composition (%)	Conductivity w/cm deg K
A Nickel.....	99.4 Ni+Co, 0.2 Mn, .15 Fe, .1 Cu, .1 C.....	0.61
D Nickel.....	95 Ni, 4.5 Mn.....	.48
Monel.....	67 Ni, 30 Cu, 1.4 Fe, 1 Mn, 0.15 C, .1 Si.....	.26
K Monel.....	66 Ni, 29 Cu, 2.75 Al, 0.9 Fe, .75 Mn, .5 Si, .15 C.....	.19
Hastelloy A.....	57 Ni, 20 Mo, 20 Fe.....	.17
Hastelloy B.....	62 Ni, 30 Mo, 5 Fe.....	.11
Hastelloy C.....	58 Ni, 17 Mo, 15 Cr, 5 W, 5 Fe.....	.13
Hastelloy D.....	85 Ni, 10 Si, 3 Cu.....	.21
Inconel.....	80 Ni, 14 Cr, 6 Fe.....	.15
Ilhum G.....	58 Ni, 22 Cr, 6 Cu, Mo, Fe each.....	.12
.....	80 Ni, 20 Cr.....	.56
.....	60 Ni, 24 Fe, 16 Cr.....	.14
.....	35 Ni, 50 Fe, 15 Cr.....	.13
Constantan.....	45 Ni, 55 Cu.....	.23

**DEOXIDIZED STEELS  
(Aluminum)**

Curve	Composition (%)	Remarks	Reference
Fig. 24; 4% Al.	4.11 Al, 0.13 Si, 0.08 Mn, 0.03 C, 0.01 S.	Heated to 800°C and furnace-cooled.	J. de Nobel (1951).




**NICKEL ALLOYS (Cont'd)**

Curve	Composition (%)	Conductivity and remarks	Reference
		w/cm deg K	
.....	97.0 Ni, 1.4 Co, 1 Mn, 0.4 Fe.	$k=0.59$ at 18°C.....	W. Jaeger and H. Diesselhorst (1900).
.....	80 Ni, 20 Cr; "nichrome".	$k=0.31$ above room temperature.	R. Kikuchi (1932).
.....	70 Ni, 18 Cr, 12 Fe.	$k=0.28$ above room temperature.	Do.
Fig. 25; Kr. Sc.-Contracid.	60 Ni, 15 Cr, 16 Fe, 7 Mo.		J. Karweil and K. Schäfer (1939).
P.Z.J.-Inconel.	80 Ni, 14 Cr, 6 Fe.		R. W. Powers, J. B. Ziegler, and H. L. Johnston (1951c).
P.Z.J.-Contracid.	60.05 Ni, 14.74 Cr, 15.82 Fe, 7.3 Mo, 2.14 Mn, 0.05 C.		Do.
P.Z.J. Monel.	67 Ni, 30 Cu, 1.4 Fe, 1.0 Mn, 0.15 C, .1 Si, .01 S.	Hot-rolled.....	Do.
P.Z.J. Monel, cold.	.....do.....	Cold-rolled.....	Do.

**NICKEL ALLOYS (Cont'd)**

Curve	Composition (%)	Conductivity and remarks	Reference
		w/cm deg K	
.....	Commercial; 99.4 Ni.....	See Fig. 8 and Nickel Table under "Metallic Elements".	J. de Nobel (1951).
N.-Monel.....	67 Ni, 30.2 Cu.....	As forged.....	Do.
Fig. 24; 57% Ni.	57.5 Ni, 1.31 Mn, 0.34 C, .14 Si; remainder Fe, approx. 40.	As forged.....	Do.
Fig. 25; Es. Zi.-Inconel (drawn).	Inconel.....	Hard-drawn.....	I. Estermann and J. E. Zimmerman (1952).
Es. Zi.-Inconel, #1.	.....do.....	Annealed.....	Do.
Es. Zi.-Inconel, #2.	.....do.....	Hot-rolled.....	Do.
Es.Zi.-Monel.	Monel.....	Hard-drawn.....	Do.
Es.Zi.-Monel, (annealed).	Monel.....	Annealed.....	Do.



**PRECIOUS METAL ALLOYS**

See also the tables given under "SILVER ALLOYS" and "GOLD ALLOYS".

**PALLADIUM ALLOYS**

Composition (%)	Conductivity and remarks	Reference
	w/cm deg K	
90 Pd, 10 Ag.....	$k=0.48$ at 25°C.....	F. A. Schulze (1911).
80 Pd, 20 Ag.....	$k=0.37$ at 25°C.....	Do.
70 Pd, 30 Ag.....	$k=0.32$ at 25°C.....	Do.
60 Pd, 40 Ag.....	$k=0.27$ at 25°C.....	Do.
50 Pd, 50 Ag.....	$k=0.32$ at 25°C.....	Do.
90 Pd, 10 Au.....	$k=0.52$ at 25°C.....	Do.
80 Pd, 20 Au.....	$k=0.42$ at 25°C.....	Do.
70 Pd, 30 Au.....	$k=0.40$ at 25°C.....	Do.
60 Pd, 40 Au.....	$k=0.36$ at 25°C.....	Do.
50 Pd, 50 Au.....	$k=0.36$ at 25°C.....	Do.
90 Pd, 10 Pt.....	$k=0.56$ at 25°C.....	Do.
80 Pd, 20 Pt.....	$k=0.44$ at 25°C.....	Do.
70 Pd, 30 Pt.....	$k=0.40$ at 25°C.....	Do.
60 Pd, 40 Pt.....	$k=0.38$ at 25°C.....	Do.
50 Pd, 50 Pt.....	$k=0.37$ at 25°C.....	Do.

**PALLADIUM ALLOYS (Cont'd)**

Composition (%)	Conductivity and remarks	Reference
	w/cm deg K	
Commercial.....	$k=0.42$ at 17°C.....	T. Barratt and R. M. Winter (1925).
85.5 Pd, 14.5 Cu.....	Polycrystalline; see Fig. 26, "Pd-15% Cu".....	E. Grüneisen and H. Reddemann (1934).
50 Pd, 50 Cu.....	Annealed; see Fig. 26, "Pd-50% Cu".....	Do.
55 Pd, 45 Au.....	Annealed 2 hr. at 800°C; see Fig. 26, "Pd-45% Au".....	Do.

**PLATINUM ALLOYS**

"Impure".....	$k=0.516$ at 18°C.....	W. Jaeger and H. Diesselhorst (1900).
90 Pt, 10 Pd.....	$k=0.43$ at 25°C.....	F. A. Schulze (1911).
80 Pt, 20 Pd.....	$k=0.42$ at 25°C.....	Do.
70 Pt, 30 Pd.....	$k=0.36$ at 25°C.....	Do.
60 Pt, 40 Pd.....	$k=0.34$ at 25°C.....	Do.
50 Pt, 50 Pd.....	$k=0.37$ at 25°C.....	Do.

**PLATINUM ALLOYS (Cont'd)**

Composition (%)	Conductivity and remarks	Reference
	w/cm deg K	
90 Pt, 10 Ir.....	$k=0.31$ at 17°C.....	T. Barratt and R. M. Winter (1925).
85 Pt, 15 Ir.....	$k=0.23$ at 17°C.....	Do.
80 Pt, 20 Ir.....	$k=0.18$ at 17°C.....	Do.
90 Pt, 10 Rh.....	$k=0.30$ at 17°C.....	Do.
96 atomic % Pt, 4 atomic % Au.....	$k=0.46$ at 18°C.....	C. H. Johansson and J. O. Linde (1930).
90 atomic % Pt, 10 atomic % Au.....	$k=0.35$ at 18°C.....	Do.
75 atomic % Pt, 25 atomic % Au.....	$k=0.24$ at 18°C.....	Do.
55 atomic % Pt, 45 atomic % Au.....	$k=0.21$ at 18°C.....	Do.

**COPPER ALLOYS**

See also the "COPPER-NICKEL ALLOY" graph and tables.

Curve	Composition (%)	Conductivity and remarks	Reference
		w/cm deg K	
.....	About 62 Cu, 15 Ni, 22 Zn.....	"Neusilber"; $k=0.29$ at 0°C.....	L. Lorenz (1881).
.....	About 82 Cu, 18 Zn.....	"Red brass"; $k=1.03$ at 0°C.....	Do.
.....	About 65 Cu, 35 Zn.....	"Yellow brass"; $k=0.85$ at 0°C.....	Do.
.....	0.34 P.....	$k=0.95$ at 15°C.....	A. Rietsch (1900).
.....	0.37 P.....	$k=0.61$ at 15°C.....	Do.
.....	1.79 P.....	$k=0.53$ at 15°C.....	Do.
.....	2.08 P.....	$k=0.34$ at 15°C.....	Do.
.....	2.35 P.....	$k=0.27$ at 15°C.....	Do.
.....	5.25 P.....	$k=0.15$ at 15°C.....	Do.
.....	1.04 As.....	$k=1.14$ at 15°C.....	Do.
.....	1.30 As.....	$k=0.83$ at 15°C.....	Do.
.....	2.66 As.....	$k=0.54$ at 15°C.....	Do.
.....	3.00 As.....	$k=0.54$ at 15°C.....	Do.
.....	5.02 As.....	$k=0.20$ at 15°C.....	Do.
.....	85.7 Cu, 7.15 Zn, 6.39 Sn, 0.6 Ni.....	"Red brass"; $k=0.60$ at 18°C.....	W. Jaeger and H. Diesselhorst (1900).
.....	84 Cu, 12 Mn, 4 Ni.....	$k=0.23$ at 18°C.....	Do.
Fig. 27; L-Bram.	70 Cu, 30 Zn.....		C. H. Lees (1908).
Fig. 27; L-Ger. silv.	62 Cu, 22 Zn, 15 Ni.....	"German silver".....	Do.
L-Plat.....	Approx. same as above.....	"Platinoid".....	Do.
L-Manganin.....	84 Cu, 12 Mn, 4 Ni.....	"Manganin".....	Do.
.....	82 Cu, 18 Zn.....	"Red brass"; "fine" crystals; $k=1.27$ at 273°K, 0.66 at 90°K.....	A. Eucken and O. Neumann (1924).
.....	do.....	"Red brass"; "large" crystals; $k=1.20$ at 273°K, 0.65 at 90°K.....	Do.

**COPPER ALLOYS (Cont'd)**


Curve	Composition (%)	Conductivity and remarks	Reference
		w/cm deg K	
Eu. Di.-Cu-50% Mn, 1.	70 Cu, 30 Mn.....	About 48 crystals per centimeter.....	A. Eucken and K. Dittrich (1927).
Eu. Di.-Cu-50% Mn, 2.	do.....	About 112 crystals per centimeter.....	Do.
.....	3 Ag.....	Unannealed; $k=3.57$ at 83° and 21°K.....	E. Grüneisen and E. Goens (1927).
.....	do.....	Annealed 3 hr at 390°C; $k=4.06$ at 83°K, 6.19 at 21°K.....	Do.
Fig. 27; G. Re.-4% Au.	95.5 Cu, 4.5 Au.....	Polycrystalline; unannealed.....	E. Grüneisen and H. Reddemann (1934).
G. Re.-10% Au.	90.3 Cu, 9.7 Au.....	Polycrystalline; unannealed.....	Do.
.....	75.1 Cu, 24.9 Au.....	Quenched from 800°C; $k=0.34$ at 83°K.....	Do.
.....	do.....	Annealed 20 hr at 400°C; $k=0.61$ at 83°K.....	Do.
.....	do.....	Annealed 32 hr at 360°C; $k=0.63$ at 83°K.....	Do.
.....	do.....	Same as above except later annealed 2 hr at 820°C, then quenched; $k=0.23$ at 83°K.....	Do.
G. Re.-25% Au.	do.....	Same as above except later annealed 6 months at room temperature.....	Do.
G. Re.-25% Au, annealed.	do.....	Same as above except additionally annealed 30 hr at 320°C.....	Do.
G. Re.-Cu-50% Au.	49.9 Cu, 50.1 Au.....	Annealed 30 hr at 320°C.....	Do.
G. Re.-Cu-50% Pd.	49.9 Cu, 50.1 Pd.....	Annealed.....	Do.
G. Re.-6% Pd.	93.6 Cu, 6.4 Pd.....	Polycrystalline; unannealed.....	Do.
.....	55 Cu, 45 Pd.....	Annealed; $k=0.67$ at 83°K.....	Do.
G. Re.-45% Pd.	do.....	Annealed 2 hr at 800°C.....	Do.
G. Re.-45% Pd, (annealed).	do.....	Further annealed 30 hr at 320°C.....	Do.

**COPPER ALLOYS (Cont'd)**

Composition (%) <sup>1</sup>	Conductivity <sup>1</sup>
	w/cm deg K
99.986 Cu, 0.0016 Fe, .02 Os.....	3.93 <sup>2</sup>
99.80 Cu, 0.19 Si, .02 Fe.....	2.13 <sup>2</sup>
99.78 Cu, 0.23 Si, .02 Fe.....	1.92 <sup>2</sup>
99.55 Cu, 0.32 Si, .032 Fe.....	1.65 <sup>2</sup>
99.53 Cu, 0.45 Si, .03 Fe.....	1.29 <sup>2</sup>
99.06 Cu, 1.00 Si, 0.03 Fe.....	0.82 <sup>2</sup>
98.09 Cu, 1.98 Si, 0.05 Fe.....	0.51 <sup>2</sup>
96.00 Cu, 3.91 Si, 0.02 Fe.....	0.54 <sup>2</sup>

<sup>1</sup> These values were determined by C. S. Smith (1935) at 20°C. Sometimes the composition percentages add up to more than 100.

<sup>2</sup> The copper-silicon alloys were hot-rolled, cold-drawn and annealed at 700°C and were in the homogeneous  $\alpha$  solid solution.



**COPPER ALLOYS (Cont'd)**

Composition (%) <sup>1</sup>	Conductivity <sup>2</sup> w/cm deg K
99.95 Cu, 0.07 Al, .01 Fe	3.52 <sup>2</sup>
99.77 Cu, 0.22 Al, .01 Fe	2.91 <sup>2</sup>
99.47 Cu, 0.47 Al, .02 Fe	2.35 <sup>2</sup>
99.20 Cu, 0.71 Al, .09 Fe	1.75 <sup>2</sup>
98.08 Cu, 1.89 Al, 0.03 Fe	1.23 <sup>2</sup>
95.25 Cu, 4.61 Al, 0.14 Fe	0.83 <sup>2</sup>
92.15 Cu, 7.72 Al, 0.13 Fe	0.72 <sup>2</sup>
90.56 Cu, 9.37 Al, 0.07 Fe	0.65 <sup>2</sup>
89.88 Cu, 9.90 Al, 0.22 Fe	0.66 <sup>2</sup>
87.76 Cu, 12.15 Al, 0.09 Fe	0.54 <sup>2</sup>
99.94 Cu, 0.07 Mn, .01 Fe, .02 Mg	3.62 <sup>2</sup>
99.88 Cu, 0.14 Mn, .01 Fe, .01 Mg	3.28 <sup>2</sup>
99.55 Cu, 0.43 Mn, .01 Fe, .01 Mg	2.26 <sup>2</sup>
99.05 Cu, 1.05 Mn, 0.01 Fe, .01 Mg	1.50 <sup>2</sup>
98.27 Cu, 1.77 Mn, 0.03 Fe, .01 Mg	1.02 <sup>2</sup>
95.34 Cu, 4.55 Mn, 0.06 Fe, .02 Mg	0.49 <sup>2</sup>
90.25 Cu, 9.53 Mn, 0.18 Fe, .02 Mg, .021 C	0.26 <sup>2</sup>
80.03 Cu, 19.82 Mn, 0.09 Fe, .02 Mg, .035 C	0.15 <sup>2</sup>

<sup>1</sup> These values were determined by C. S. Smith (1935) at 20°C. Sometimes the composition percentages add up to more than 100.

<sup>2</sup> The copper-aluminum alloys were rolled and annealed at 700°C and were in the  $\alpha$  solid solution (except the 12% Al, which was  $\delta$ ).

<sup>3</sup> The copper-manganese alloys were decarburized with magnesium, hot-rolled, and annealed at 700°C.

**COPPER ALLOYS (Cont'd)**

Composition (%) <sup>1</sup>	Conductivity <sup>2</sup> w/cm deg K	State <sup>1</sup>
99.986 Cu, 0.002 Fe, .02 Os	3.94 <sup>2</sup>	
66.24 Cu, 33.72 Zn, 0.03 Pb, .01 Fe, .001 S	1.20 <sup>2</sup>	
96.94 Cu, 3.04 Zn, 0.02 Fe	2.68 <sup>2</sup>	
95.21 Cu, 4.77 Zn, 0.02 Fe	2.42 <sup>2</sup>	
97.49 Cu, 0.06 Fe, .27 Ni, 2.24 Be	0.86 <sup>2</sup>	Quenched.
97.49 Cu, 0.06 Fe, .27 Ni, 2.24 Be	1.03 <sup>2</sup>	Reheated.
97.49 Cu, 0.06 Fe, .27 Ni, 2.24 Be	0.74 <sup>2</sup>	Quenched, cold-drawn.
97.49 Cu, 0.06 Fe, .27 Ni, 2.24 Be	0.82 <sup>2</sup>	Reheated.
97.49 Cu, 0.06 Fe, .27 Ni, 2.24 Be	1.60 <sup>2</sup>	
85.10 Cu, 12.97 Zn, 1.88 Pb, 0.05 Fe	1.08 <sup>2</sup>	
61.85 Cu, 34.79 Zn, 3.29 Pb, 0.07 Fe	1.11 <sup>2</sup>	
65.99 Cu, 29.18 Zn, 4.02 Pb, 0.01 Fe	0.90 <sup>2</sup>	
88.07 Cu, 3.70 Zn, 3.77 Sn, 3.83 Pb, 0.03 Fe	0.56 <sup>2</sup>	
88.08 Cu, 4.09 Zn, 3.76 Sn, 3.80 Pb, 0.02 Fe, .25 P	1.00 <sup>2</sup>	
60.41 Cu, 37.09 Zn, 1.03 Sn, 1.12 Pb, 0.02 Fe, .18 Al, .21 Si	0.30 <sup>2</sup>	Chill-cast.
56.01 Cu, 25.93 Zn, 0.18 Mn, 17.95 Ni, 0.08 Fe, .02 C	.34 <sup>2</sup>	
63.76 Cu, 19.79 Zn, 0.18 Mn, 16.29 Ni, 0.14 Fe	.46 <sup>2</sup>	
65.51 Cu, 23.86 Zn, 0.18 Mn, 10.36 Ni, 0.08 Fe, .01 C	.42 <sup>2</sup>	
59.76 Cu, 29.88 Zn, 0.15 Mn, 10.13 Ni, 0.04 Fe, .04 Mg	.59 <sup>2</sup>	
64.04 Cu, 30.50 Zn, 5.41 Ni, 0.05 Fe		

<sup>1</sup> These values were determined by C. S. Smith (1935) at 20°C. Sometimes the composition percentages add up to more than 100.

<sup>2</sup> The miscellaneous alloys were extensively worked, annealed, and slowly cooled except where noted.

**COPPER ALLOYS (Cont'd)**

Composition (%) <sup>1</sup>	Conductivity <sup>1</sup> w/cm deg K	State <sup>1</sup>
80.08 Cu, 4.98 Ni, 0.08 Fe, 5.11 Al, 0.74 Si	.45	Quenched.
80.08 Cu, 4.98 Ni, 0.08 Fe, 5.11 Al, 0.74 Si	.57	Reheated.
80.08 Cu, 4.98 Ni, 0.08 Fe, 5.11 Al, 0.74 Si	.66	Furnace-cooled.
56.13 Cu, 42.34 Zn, 1.02 Ni, 0.49 Fe	1.14	
80.38 Cu, 0.31 Ni, 0.52 Fe, 38 Sn, 9.41 Al	0.60	
75.79 Cu, 22.22 Zn, 0.01 Fe, 1.98 Al	1.00	
50.35 Cu, 38.36 Zn, 0.12 Mn, 1.06 Fe, 0.98 Sn, .13 Pb.	1.01	
99.654 Cu, 0.03 Fe, .32 Si	1.65	
95.61 Cu, 4.51 Mn, 0.11 Fe	0.46	
99.21 Cu, 0.01 Fe, .01 Si, .85 Cd	3.45	
98.41 Cu, 0.02 Fe, .59 Sn, .02 Si, 1.07 Cd	2.33	
72.49 Cu, 17.76 Zn, 3.34 Mn, 1.78 Fe, 4.44 Al	0.50	
94.00 Cu, 1.03 Mn, 0.08 Fe, 4.68 Si	0.25	Sand-cast.
95.69 Cu, 0.99 Mn, 0.16 Fe, 3.23 Si	0.33	
95.10 Cu, 0.30 Mn, 0.06 Fe, 1.50 Si	0.54	
81.55 Cu, 14.21 Zn, 0.20 Mn, 0.04 Fe, 4.00 Si	0.28	Chill-cast.
95.83 Cu, 1.12 Zn, 0.02 Fe, 3.11 Si	0.37	
78.30 Cu, 0.20 Ni, 8.04 Sn, 13.32 Pb, 0.1 P	0.42	Sand-cast.
87.86 Cu, 3.06 Zn, 0.03 Fe, 8.87 Sn	0.54	Sand-cast.
88.36 Cu, 1.90 Zn, 0.07 Fe, .55 Sn	0.50	Sand-cast.
60.54 Cu, 36.46 Zn, 0.21 Mn, 0.73 Fe, 1.48 Sn, 0.04 Al	0.96	Sand-cast.
99.04 Cu, 0.07 Fe, .9 Cd	2.76	
50.75 Cu, 0.47 Mn, 48.69 Fe, 0.05 Si, .02 C	0.99	

<sup>1</sup> These values were determined by C. S. Smith (1935) at 20°C. Sometimes the composition percentages add up to more than 100.

<sup>2</sup> The miscellaneous alloys were extensively worked, annealed, and slowly cooled except where noted.

**COPPER ALLOYS (Cont'd)**


Curve	Composition (%)	Remarks	Reference
Fig. 27; Kr. S.-Ger. silv.	64 Cu, 20 Zn, 16 Ni	"Neusilber"	J. Karweil and K. Schäfer (1939).
Fig. 27; Kr. Se.-bronz.	46 Cu, 41 Zn, 13 Ni	"Silberbronz"	Do.
Fig. 29a; Al Mn.-Ger. silv.	45.9 Cu, 42.1 Zn, 9.8 Ni, 2.0 Pb, 0.15 Fe, 0.05 Mn.	"German silver"; data fits equation $k=5.3 \times 10^{-4} T^2$ .	J. F. Allen and E. Mendosa (1948).
Fig. 27, Fig. 29a; B.-Ger. silv.	47 Cu, 41 Zn, 9 Ni, 2 Pb.	Mean diameter of crystals was 0.02 mm.	R. Berman (1951b).

**COPPER ALLOYS (Cont'd)  
COMPANY AND TRADE MANUALS**

Name	Nominal Composition (%)	Conductivity w/cm deg K
<b>Coppers:</b>		
Electrolytic Tough Pitch	99.92 Cu, 0.04 O <sub>2</sub>	3.91
Deoxidized	99.94 Cu, 0.02 P	3.39
Oxygen-free high cond.	99.92 Cu	3.93
Silver bearing	99.9 Cu, trace Ag	3.93
Arsenical phosphorized	99.45 Cu, 0.3 As, 0.03 P	1.76
Free cutting	99.4 Cu, 0.6 Te	3.55
Boron deoxidized	99.98 Cu, 0.02 B	3.88
Selenium copper	99.4 Cu, 0.6 Se	3.84
Leaded copper	99.0 Cu, 1.0 Pb	3.84
Chromium copper	99.05 Cu, 0.85 Cr	3.24
Cadmium copper	99.00 Cu, 1.00 Cd	3.44
<b>Brasses:</b>		
Gilding	95 Cu, 5 Zn	2.34
Commercial bronze	90 Cu, 10 Zn	1.88
Bearing bronze	90 Cu, 9.5 Zn, 0.5 Sn	1.73
Commercial bronze	87.5 Cu, 12.5 Zn	1.73
Red brass	85 Cu, 15 Zn	1.59
Low brass	80 Cu, 20 Zn	1.38
Cartridge brass	70 Cu, 30 Zn	1.21
Yellow brass	65 Cu, 35 Zn	1.17
Muntz metal	60 Cu, 40 Zn	1.21

**COPPER ALLOYS (Cont'd)  
COMPANY AND TRADE MANUALS**

Name	Nominal Composition (%)	Conductivity w/cm deg K
<b>Leaded Brasses:</b>		
Leaded commercial bronze	90 Cu, 9.5 Zn, 0.5 Pb	1.80
Leaded commercial bronze	89 Cu, 0.25 Zn, 1.75 Pb	1.80
Commercial bronze	90.25 Cu, 6.9 Zn, 1.75 Pb, 1 Ni	1.40
Low leaded brass	84.5 Cu, 35 Zn, 0.5 Pb	1.17
Low leaded brass	67 Cu, 32.5 Zn, 0.5 Pb	1.16
Medium leaded brass	64.5 Cu, 34.5 Zn, 1.0 Pb	1.17
High leaded brass	62.5 Cu, 35.75 Zn, 1.75 Pb	1.17
High leaded brass	64 Cu, 34 Zn, 2.0 Pb	1.16
Extra high leaded brass	62.5 Cu, 35 Zn, 2.5 Pb	1.17
Free cutting brass	61.5 Cu, 35.5 Zn, 3 Pb	1.17
Leaded Muntz metal	60 Cu, 39.5 Zn, 0.5 Pb	1.21
Free cutting Muntz metal	60.5 Cu, 38.4 Zn, 1.1 Pb	1.17
Forging brass	60 Cu, 38 Zn, 2 Pb	1.17
Architectural bronze	57 Cu, 40 Zn, 3 Pb	1.21
Leaded naval brass	60 Cu, 37.5 Zn, 0.7 to 1.75 Pb, 0.75 Sn	1.17
Leaded tin bearing bronze	87 Cu, 4 Zn, 8 Sn, 1 Pb	0.47
High leaded tin bronze (bushing)	80 Cu, 10 Sn, 10 Pb	0.47
Dairy bronze	64 Cu, 8 Zn, 20 Ni, 4 Pb, 4 Sn	0.23
Leaded nickel brass	60 Cu, 16 Zn, 16 Ni, 5 Pb, 3 Sn	0.27
<b>Special Brasses:</b>		
Admiralty metal	71 Cu, 28 Zn, 1 Sn	1.09
Naval brass	60 Cu, 39.25 Zn, 0.75 Sn	1.17
Manganese bronze	58.5 Cu, 39 Zn, 1.4 Fe, 1 Sn, 0.1 Mn	1.09
Aluminum brass	76 Cu, 22 Zn, 2 Al	1.00
"Ambronze-474"	94.97 Cu, 4.0 Zn, 1.0 Sn, 0.03 P	1.64
"Ambronze-421"	88.00 Cu, 10.0 Zn, 2.0 Sn	1.19
Manganese red brass	85.0 Cu, 14.0 Zn, 1.0 Mn	0.99
Silicon red brass	82.0 Cu, .0 Zn, 1.0 Si	0.67
Trumpet brass	81.0 Cu, 18.0 Zn, 1.0 Sn	1.21
Arsenical admiralty	71.0 Cu, 28.0 Zn, 1.0 Sn, 0.04 As	1.11
Manganese brass	70.0 Cu, 29.0 Zn, 1.0 Mn	0.74
Nickel silver 18%-B	55 Cu, 27 Zn, 18 Ni	0.29
Nickel silver 15%	66 Cu, 19 Zn, 15 Ni	0.35
Leaded nickel silver 12%	65 Cu, 20.7 Zn, 12 Ni, 2 Pb, 0.3 Mn	0.40
Phosphor bronze 5%-A	95 Cu, 5 Sn, trace P	0.80
Phosphor bronze 8%-C	92 Cu, 8 Sn, trace P	0.63
Phosphor bronze 10%-D	90 Cu, 10 Sn, trace P	0.50
Phosphor bronze 1.25%-E	98.75 Cu, 1.25 Sn, trace P	2.05
Phosphor bronze	98.7 Cu, 1.25 Sn, 0.05 P	2.18
Do	98.24 Cu, 1.75 Sn, 0.01 P	1.47
Do	95.95 Cu, 4.0 Sn, 0.05 P	0.81
Do	95.75 Cu, 4.0 Sn, 0.25 P	0.81
Do	95.17 Cu, 4.0 Sn, 0.08 P, 0.5 Fe	0.76
Do	94.75 Cu, 5.0 Sn, 0.25 P	0.81
Do	93.9 Cu, 5.0 Sn, 0.1 P, 1 Pb	0.83
Do	93.7 Cu, 6.0 Sn, 0.3 P	0.57
Do	91.75 Cu, 8.0 Sn, 0.25 P	0.62
Do	89.75 Cu, 10.0 Sn, 0.25 P	0.50
Do	87.90 Cu, 4.0 Sn, 4 Zn, 4 Pb, 0.1 P	0.55
<b>Special Bronzes:</b>		
Silicon bronze A	96 Cu, 3 Si	0.38
Silicon bronze B	97 Cu, 1.5 Si	0.59
"Everdur-1010"	95.8 Cu, 3.1 Si, 1.1 Mn	0.33
"Everdur-1012"	95.6 Cu, 3.0 Si, 1.0 Mn, 0.4 Pb	0.33
"Everdur-1015"	98.25 Cu, 1.5 Si, 0.25 Mn	0.54
"Everdur-1014"	90.75 Cu, 2.0 Si, 7.25 Al	0.45
5% Aluminum bronze	95 Cu, 5 Al	0.83
Do	92 Cu, 8 Al	0.71
10% Aluminum bronze	85 Cu, 10 Al	0.60
Do	82.5 Cu, 10 Al, 5 Ni, 2.5 Fe	0.38
Aluminum silicon bronze	91 Cu, 7 Al, 2 Si	0.38
"Calsun"	95.5 Cu, 2.5 Al, 2.0 Sn	0.87
Chromium copper	99.05 Cu, 0.95 Cr	3.20
"Hitens-961"	99.0 Cu, 1.0 Cd	3.44
"Hitens-965"	98.6 Cu, 0.8 Cd, 0.6 Sn	2.33
Aluminum bronze 89-1-10	89 Cu, 10 Al, 1 Fe	0.65
Aluminum bronze 86-4-10	86 Cu, 10 Al, 4 Fe	0.59
Aluminum bronze	87.5 Cu, 9 Al, 3.5 Fe	0.59



**COPPER ALLOYS (Cont'd)  
COMPANY AND TRADE MANUALS**

Name	Nominal Composition (%)	Conductivity w/cm deg K	State
Beryllium Coppers: Beryllium copper	97 Cu, 2 Be, 0.25	0.84	Solution treated, quenched.
		1.05	As above plus chemically hardened.
		0.84	As above plus cold-rolled.
		0.75	Solution treated, chemically quenched, cold-rolled.
Beryllium alloy 25	2 Be, 0.3 Co, balance Cu	1.21	
Beryllium alloy 165	1.7 Be, 0.3 Co, balance Cu	1.21	
Beryllium alloy 10	0.5 Be, 2.4 Co, balance Cu	2.26	
Beryllium alloy 50	0.4 Be, 1.55 Co, 1.0 Ag, balance Cu	2.22	
Beryllium alloy 20C	2.1 Be, 0.5 Co, balance Cu	1.05	
Beryllium alloy 275C	2.7 Be, 0.5 Co, balance Cu	0.96	
Beryllium alloy 10C	0.6 Be, 2.5 Co, balance Cu	2.13	

**COPPER-NICKEL ALLOYS**  
See also the "COPPER ALLOY" graph and tables.

Curve	Composition (%)	Conductivity and remarks w/cm deg K	Reference
.....	About 62 Cu, 22 Zn, 15 Ni.	"Neusilber"; $k=0.29$ at $0^{\circ}\text{C}$ .	L. Lorenz (1881).
.....	60 Cu, 40 Ni	"Constantan"; $k=0.23$ at $18^{\circ}\text{C}$ .	W. Jaeger and H. Diesselhorst (1900).
.....	54 Cu, 46 Ni	$k=0.21$ at $18^{\circ}\text{C}$ .	E. Grüneisen (1900).
Fig. 27; L-Ger. silv.	62 Cu, 22 Zn, 15 Ni	"German silver"	C. H. Lees (1908).
L-Plat	Approx. same as above.	"Platinoid"	Do.
.....	60 Cu, 40 Ni	"Eureka" or constantan; $k=0.21$ at $17^{\circ}\text{C}$ .	T. Barratt and R. M. Winter (1925).
Fig. 28; Eu-Di-constantan.	60 Cu, 40 Ni	51 crystals per cm; also measured samples with other crystal size.	A. Eucken and K. Dittrich (1927).
.....	1 Ni	$k=1.50$ at $83^{\circ}\text{K}$ , $0.62$ at $21^{\circ}\text{K}$ .	E. Grüneisen and E. Goens (1927).
Fig. 27; Kr. Sc.-Ger. silv.	64 Cu, 16 Ni, 20 Zn	"Neusilber"	J. Karweil and K. Schäfer (1939).

**COPPER-NICKEL ALLOYS (Cont'd)**

Curve	Composition (%)	Conductivity and remarks	Reference
		w/cm deg K	
Fig. 29a; Al. Mn.-Ger. silv.	45.9 Cu, 42.1 Zn, 9.8 Ni, 2.0 Pb, 0.15 Fe, 0.05 Mn.	"German silver"; data fits equation $k = 5.3 \times 10^{-4} T^2$ .	J. F. Allen and E. Mendoza (1948).
.....	63 Cu, 20 Ni, 17 Zn.....	"Nickel-silver"; $k = 25.5$ mw/cm deg at 10°K, 48.5 at 15°K, 71.1 at 20°K.	K. R. Wilkinson and J. Wilks (1949).
.....	70 Cu, 30 Ni.....	"Cupro-nickel"; $k = 20.9$ mw/cm deg at 10°K, 35.8 at 15°K, 50.2 at 20°K.	Do.
Fig. 28; P.Z.J.-constantan.	55 Cu, 45 Ni.....		R. W. Powers, J. B. Ziegler, and H. L. Johnston (1951c).
Fig. 29a; Hu.-Cu-20% Ni.	80 Cu, 20 Ni.....	Also obtained $k = 127$ mw/cm deg at 21.9°K and 79.9 at 16.3°K.	J. K. Hulm (1951).
Fig. 28; B.-Constantan.	60 Cu, 40 Ni.....		R. Berman (1951b).
Figs. 27, 29a; B.-Ger. silv.	47 Cu, 41 Zn, 9 Ni, 2 Pb.	Mean diameter of crystals was 0.02 mm.	Do.
Fig. 27; Es. Zi.-Cu-10% Ni, annealed.	90 Cu, 10 Ni.....	Two samples which were annealed, one a single crystal.	I. Estermann and J. E. Zimmermann (1952).
Es. Zi.-Cu-10% Ni, cold.	do.....	Two samples which were cold-worked.	Do.

**COPPER-NICKEL ALLOYS (Cont'd)**

Composition (%)	Conductivity
	w/cm deg K
99.73 Cu, 0.28 Ni, .01 Fe, .03 Mg.....	3.22 <sup>1, 2</sup>
99.47 Cu, 0.54 Ni, .02 Fe, .04 Mg.....	2.92 <sup>1, 2</sup>
97.94 Cu, 1.97 Ni, 0.02 Fe, .04 Mg.....	1.72 <sup>1, 2</sup>
94.92 Cu, 5.09 Ni, 0.01 Fe, .03 Mg.....	1.00 <sup>1, 2</sup>
89.90 Cu, 10.07 Ni, 0.02 Fe, .03 Mg, .02 C.....	0.62 <sup>1, 2</sup>
84.85 Cu, 15.07 Ni, 0.05 Fe, .01 Mg, .03 Mn.....	0.47 <sup>1, 2</sup>
79.68 Cu, 19.79 Ni, 0.23 Fe, .30 Mg.....	0.36 <sup>1, 2</sup>
69.84 Cu, 30.23 Ni, 0.06 Fe, .06 Mg, .13 Mn.....	0.29 <sup>1, 2</sup>

Composition (%)	Conductivity	State
	w/cm deg K	
64.14 Cu, 18.38 Ni, 0.19 Fe, 17.06 Zn, 0.3 Mn, .02 C.....	0.33 <sup>1, 2</sup>	
63.37 Cu, 19.89 Ni, 0.14 Fe, 8.22 Zn, 3.31 Sn, 5.4 Pb, 0.23 Mn.....	0.28 <sup>1, 2</sup>	Sand-cast.
96.06 Cu, 3.01 Ni, 0.004 Fe, .88 Si.....	0.76 <sup>1, 2</sup>	Quenched.
96.06 Cu, 3.01 Ni, 0.04 Fe, .88 Si.....	1.58 <sup>1, 2</sup>	Reheated.
96.06 Cu, 3.01 Ni, 0.04 Fe, .88 Si.....	1.69 <sup>1, 2</sup>	Furnace-cooled.
74.07 Cu, 19.96 Ni, 0.09 Fe, 5.31 Zn.....	0.39 <sup>1, 2</sup>	
64.5 Cu, 29.44 Ni, 0.07 Fe, 5.69 Zn.....	0.28 <sup>1, 2</sup>	

<sup>1</sup> The values were determined by C. S. Smith, E. W. Palmer (1935) at 20°C. Sometimes the composition percentages add up to more than 100.

<sup>2</sup> The copper-nickel alloys were deoxidized with magnesium, cold-rolled, and annealed at 800°C.

<sup>3</sup> The Miscellaneous alloys were extensively worked, annealed, and slowly cooled except where noted.

**COPPER-NICKEL ALLOYS (Cont'd)  
COMPANY AND TRADE MANUALS**

Name	Nominal composition (%)	Conductivity
		w/cm deg K
Cupro-nickel 30%.....	70 Cu, 30 Ni.....	0.29
Cupro-nickel 10%.....	88.5 Cu, 10 Ni, 1.5 Fe.....	0.47
Nickel silver 18%-A.....	65 Cu, 18 Ni, 17 Zn.....	0.33
Nickel silver 18%-B.....	55 Cu, 18 Ni, 27 Zn.....	0.25
Nickel silver 15%.....	66 Cu, 15 Ni, 19 Zn.....	0.35
Constantan.....	55 Cu, 45 Ni.....	0.23
Dairy bronze.....	64 Cu, 20 Ni, 8 Zn, 4 Pb, 4 Sn.....	0.23
Leaded nickel brass.....	60 Cu, 16 Ni, 16 Zn, 5 Pb, 3 Sn.....	0.27
Leaded nickel silver 12%.....	65 Cu, 12 Ni, 20.7 Zn, 2 Pb, 0.3 Mn.....	0.40

**SILVER ALLOYS**

Curve	Composition (%)	Conductivity and remarks	Reference
		w/cm deg K	
.....	90 Ag, 10 Pd.....	$k = 1.41$ at 25°C.....	F. A. Schulze (1911).
.....	80 Ag, 20 Pd.....	$k = 0.84$ at 25°C.....	Do.
.....	70 Ag, 30 Pd.....	$k = 0.57$ at 25°C.....	Do.
.....	60 Ag, 40 Pd.....	$k = 0.45$ at 25°C.....	Do.
.....	50 Ag, 50 Pd.....	$k = 0.32$ at 25°C.....	Do.
.....	90 Ag, 10 Pt.....	$k = 0.98$ at 25°C.....	Do.
.....	75 Ag, 25 Pt.....	$k = 0.38$ at 25°C.....	Do.
.....	70 Ag, 30 Pt.....	$k = 0.31$ at 25°C.....	Do.
.....	67 Ag, 33 Pt.....	$k = 0.30$ at 25°C.....	Do.
Fig. 26; G. Re.-Ag-0.4% Au.	99.63 Ag, 0.37 Au.....		E. Grüneisen and H. Reddemann (1934).
G. Re.-Ag-25% Au.	75 Ag, 25 Au.....	Single crystal.....	Do.
G. Re.-Au 50% Ag.	50 Ag, 50 Au.....	Single crystal.....	Do.
Po.-Ag Solder.	50 Ag, 15.5 Cu, 16.5 Zn, 18 Cd.....	"Easy-flo"; flame annealed.....	R. L. Powell (1953).

**GOLD ALLOYS**

.....	90 Au, 10 Pd.....	$k = 0.98$ at 25°C.....	F. A. Schulze (1911).
.....	80 Au, 20 Pd.....	$k = 0.59$ at 25°C.....	Do.
.....	70 Au, 30 Pd.....	$k = 0.44$ at 25°C.....	Do.
.....	60 Au, 40 Pd.....	$k = 0.40$ at 25°C.....	Do.
.....	50 Au, 50 Pd.....	$k = 0.36$ at 25°C.....	Do.
.....	90 Au, 10 Pt.....	$k = 0.76$ at 25°C.....	Do.
.....	80 Au, 20 Pt.....	$k = 0.41$ at 25°C.....	Do.
.....	70 Au, 30 Pt.....	$k = 0.30$ at 25°C.....	Do.
.....	60 Au, 40 Pt.....	$k = 0.26$ at 25°C.....	Do.



### GOLD ALLOYS (Cont'd)

Curve	Composition (%)	Conductivity and remarks	Reference
		w/cm deg K	
	92 atomic % Au, 8 atomic % Pt	$k=0.80$ at 18°C	C. H. Johansson and J. O. Linde (1930).
	84 Au, 16 Pt	$k=0.18$ at 18°C	Do.
	68 Au, 32 Pt	$k=0.23$ at 18°C	Do.
	55 Au, 45 Pt	$k=0.21$ at 18°C	Do.
Fig. 26; G. Re.-Au-50% Ag	50 Au, 50 Ag	Single crystal	E. Grüneisen and H. Reddemann (1934).
G. Re.-Au-25% Ag	75 Au, 25 Ag	Single crystal	Do.
G. Re.-Au-26% Cu	73.7 Au, 26.4 Cu	Polycrystalline	Do.
G. Re.-Au-9% Cu	91 Au, 9 Cu	Polycrystalline	Do.
	50.1 Au, 49.9 Cu	Quenched from 800°C; $k=0.193$ at 86°K.	Do.
	do.	Same as above except annealed 22 hr at 360°C; $k=1.28$ at 85°K.	Do.
	do.	Requenched from 800°C; $k=0.23$ at 83°K.	Do.
G. Re.-Au-50% Cu	do.	Annealed 30 hr at 320°C	Do.
G. Re.-Au-9% Pd	91.2 Au, 8.8 Pd	Tempered at 800°C for 2 hr.	Do.
	83 Au, 17 Pd	Annealed 2 hr at 800°C; approx. same curve as "Ag-25% Au".	Do.
	69 Au, 25 Ag, 6 Pt	$k=0.53$ at room temperature.	Trade Manual.

### INDIUM, THALLIUM ALLOYS

	66 Tl, 34 Pb	For a sample with "large" crystals, $k=0.22$ at 273°K, 0.13 at 80°K; for a sample with "small" crystals, $k=0.23$ at 273°K, 0.14 at 80°K.	A. Eucken and K. Dittich (1927).
	67 Tl, 34 Pb by atomic percent.	Measured relative change of thermal conductivity when the alloy became superconductive.	W. J. de Haas and H. Bremmer (1932).
Fig. 29, 29a; Br. H.-In-9% Pb	91.4 In, 8.6 Pb by atomic percent.	Became superconducting at 4.2°K.	H. Bremmer and W. J. de Haas (1936).
Br. H.-Pb-50% In	50 In, 50 Pb by atomic percent.	Became superconducting at 5.54°K.	Do.
Fig. 29a; Hu-In-10% Tl	90 In, 10 Tl by atomic percent.	Single crystal; measured both in the normal and superconducting state; transition temperature about 3.4°K.	J. K. Hulm (1952b).

### ZINC ALLOYS

Trade Designation	Nominal composition (%)	Conductivity
		w/cm deg K
"Zamak-3"	96 Zn, 4 Al, 0.04 Mg	1.13
"Zamak-5"	95 Zn, 4 Al, 1 Cu, 0.04 Mg	1.09
"Zamak-2"	93 Zn, 4 Al, 3 Cu, 0.03 Mg	1.05
Comm. rolled	99.8 Zn, 0.08 Pb	1.09
Do.	99.8 Zn, 0.06 Pb, 0.06 Cd	1.09
Rolled zinc alloy, "Zilloy-15"	98.7 Zn, 1 Cu, 0.01 Mg	1.05

### CADMIUM ALLOYS

Curve	Composition (%)	Remarks	Reference
Fig. 29; Eu. Ge.-Cd-33% Sb	66.7 Cd, 33.3 Sb		A. Eucken and G. Gehloff (1912).
Eu. Ge.-Cd-50% Sb	50 Cd, 50 Sb		Do.

### MERCURY ALLOYS


Composition (%)	Remarks	Reference
98.8 Hg, 1.19 In	Measured ratio of conductivities in normal and superconducting states. See also the graph and table under "Metallic Elements".	J. K. Hulm (1950).

### TIN ALLOYS

Curve	Composition	Remarks	Reference
Figs. 18a, b	Up to 4% mercury	See table under Figs. 18a, b, "Metallic Elements".	J. K. Hulm (1950).
Do.	Up to 3% indium	do.	B. B. Goodman (1953).

### TIN ALLOYS (Cont'd) COMPANY AND TRADE MANUALS

Name	Nominal Composition (%)	Conductivity
		w/cm deg K
Eutectic soft solder	63 Sn, 37 Pb	0.50
Tin foil	92 Sn, 8 Zn	0.59




**LEAD ALLOYS**

Curve	Composition (%)	Remarks	Reference
Fig. 29; Br. H.-Pb-44% Sn.	56 Pb, 44 Sn	Not in solid solution.	H. Bremmer and W. J. de Haas (1936).
	90 Pb, 10 Bi	Measured conductivity in intermediate state and as a function of magnetic field.	K. Mendelssohn and R. B. Pontius (1937).
Fig. 29a; M. O.-Pb-30% Sn.	70 Pb, 30 Sn	Measured in normal and superconductive states.	K. Mendelssohn and J. L. Olsen (1950a).
Fig. 29; M. O.-Pb-0.1% Bi.	99.9 Pb, 0.1 Bi		Do.
M. O.-Pb-10% Bi.	90 Pb, 10 Bi	Note that the thermal conductivity in the superconductive state was higher than in the normal state.	Do.
M. O.-Pb-0.2% Bi.	99.8 Pb, 0.2 Bi	Measured in normal and superconductive states.	K. Mendelssohn and J. L. Olsen (1950e).
M. O.-Pb-0.5% Bi.	99.5 Pb, 0.5 Bi	do.	Do.
Fig. 29a; O.-Pb-30% Bi.	70 Pb, 30 Bi	do.	J. L. Olsen (1952).

**LEAD ALLOYS (Cont'd)**

Name	Nominal composition (%)	Conductivity
		w/cm deg K
Corroding lead	99.73 Pb	0.35
1% antimonial lead	99 Pb, 1 Sb	0.33
Hard lead	96 Pb, 4 Sb	0.31
Do.	94 Pb, 6 Sb	0.29
8% antimonial lead	92 Pb, 8 Sb	0.27
Grid metal	91 Pb, 9 Sb	0.27
5-95 soft solder	95 Pb, 5 Sn	0.36
20-80 soft solder	80 Pb, 20 Sn	0.37
50-50 soft solder	50 Pb, 50 Sn	0.46
Lead base babbitt	80 Pb, 15 Sb, 5 Sn	0.24
Do.	75 Pb, 15 Sb, 10 Sn	0.24



**BISMUTH ALLOYS**

Curve	Composition (%)	Remarks	Reference
Fig. 29; L.-Lip.	50 Bi, 25 Pb, 14 Sn, 11 Cd.	"Lipowitz alloy"	C. H. Lees (1908).
Ge. Ne.-Bi-50% Sb.	50, Bi, 50 Sb.		G. Gehlhoff and F. Neumeier (1913).
Ge. Ne.-Bi-20% Sb.	80 Bi, 20 Sb.		Do.
Ge. Ne.-Bi-13% Sb.	87 Bi, 13 Sb.		Do.
Ge. Ne.-Bi-11% Sb.	89 Bi, 11 Sb.		Do.
Ge. Ne.-Bi-9% Sb.	91 Bi, 9 Sb.		Do.
Fig. 29, 29a; Br. H.-Rose.	50 Bi, 25 Pb, 25 Sn.	"Rose's metal"	H. Bremmer and W. J. de Haas (1936).

**ANTIMONY ALLOYS**


Curve	Composition (%)	Remarks	Reference
Fig. 29; Eu. Ge.-Cd-50% Sb.	50 Sb, 50 Cd.		A. Eucken and G. Gehlhoff (1912).
Eu. Ge.-Sb-48% Cd.	51.7 Sb, 48.3 Cd.		Do.
Eu. Ge.-Sb-33% Cd.	66.7 Sb, 33.3 Cd.	"Very hard"	Do.
Ge. Ne.-Sb-30% Bi.	70 Sb, 30 Bi.		G. Gehlhoff and F. Neumeier (1913a).
Ge. Ne.-Bi-50% Sb.	50 Sb, 50 Bi.		Do.

## 2.4. Dielectric Crystals

This section is not comprehensive but is representative of the dielectrics. There have been few measurements on the conductivity of dielectrics at low temperatures. However, three series of experiments especially worth noting in this short summary are A. Eucken and G. Kuhn (1928), W. J. de Haas and T. Biermasz (in late 1930's), and R. Berman and others of the Clarendon Laboratory at Oxford (1950's).

The following miscellaneous dielectrics were measured by A. Eucken and G. Kuhn (1928) (all percentages are mole percent):

Name	Remarks	Conductivity mw/cm deg K		Name	Remarks	Conductivity mw/cm deg K	
		83° K	273° K			83° K	273° K
Marble.....	Small crystals, 99.9% CaCO <sub>3</sub> ...	42	33	25% KBr,	Pressed at 8,000 atm.....	46	33
Do.....	99.99% CaCO <sub>3</sub> .....	54	38	75% KCl.	..... do.....	80	50
Do.....	Large crystals.....	50	33	10% KBr,	..... do.....	188	71
Calcite.....	Main crystal axis perpendicular to rod axis.	180	46	90% KCl.	..... do.....	17	21
Do.....	Main crystal axis parallel to rod axis.	293	54	50% KCl,	..... do.....	17	13
Sylvite.....	Natural crystal.....	159	75	50% NaCl.	..... do.....	109	25
KCl.....	Pressed at 8,000 atm.....	314	88	Mercuric chloride.	..... do.....	67	25
KCl.....	From a melt.....	402	92	NH <sub>4</sub> Cl.....	..... do.....	33	13
NaCl.....	..... do.....	343	92	NH <sub>4</sub> Br.....	..... do.....	29	21
NaCl.....	Pressed at 8,000 atm.....	251	71	Ba(NO <sub>3</sub> ) <sub>2</sub> .....	..... do.....	25	25
Rock salt.....	..... do.....	180	63	Copper Sulfate.	..... do.....	17	17
Sylvite.....	..... do.....	343	84	Magnesium- sulfate.	..... do.....	13	21
KCl.....	Pressed at 1,250 atm.....	243	75	K <sub>2</sub> (FeCN <sub>6</sub> ).....	Main crystal axis perpendicular to rod axis.	13	21
KCl.....	Pressed at 2,500 atm.....	368	92	Chrom alum.....	..... do.....	17	17
KCl.....	Pressed at 8,900 atm.....	402	96	Potassium alum.	..... do.....	63	264
KBr.....	Pressed at 8,000 atm.....	92	38	Potassium bichromate.	..... do.....	88	84
NaBr.....	..... do.....	50	25	Do.....	Main crystal axis parallel to rod axis.	38	46
KI.....	..... do.....	121	29	Topaz.....	Mineral.....		
KF.....	..... do.....	234	71	Zincblend.....	..... do.....		
NaF.....	..... do.....	519	105	Beryll.....	..... do.....		
RbI.....	..... do.....	59	33	Tourmaline.....	..... do.....		
RbCl.....	..... do.....	29	21				
90% KBr, 10% KCl.	..... do.....	50	29				
75% KBr, 25% KCl.	..... do.....	29	21				
50% KBr, 50% KCl.	..... do.....	25	25				




DIAMOND  
SAPPHIRE  
FIGURE 30


**DIAMOND**

Curve	Remarks	Reference
Fig. 30 and 30a; H.Bz.-D.	In addition to the two curves, they obtained $k=14.3$ at $89^\circ\text{K}$ .	W. J. de Haas and T. Biermasz (1938).
B. S. Z.-D.-1.	Measured the "size effect" in diamond crystals of square cross-section. #1 was 3.9 mm wide, #2 was 3.1 mm wide, #3 was 1.7 mm wide, #4 was 1.1 mm wide. They used a type I stone. All were several centimeters long.	R. Berman, F. E. Simon, and J. M. Ziman (1953).

**SAPPHIRE**


Curve	Remarks	Reference
Figs. 30, 30a; B.-S-1.	Curve S-1; artificial single crystal sapphire (corundum); 6 mm long, diameter of 3 mm; at lowest temperature, $k=2.7 \times 10^{-2} \text{ T}^2$ ; main crystal axis inclined $36^\circ$ to rod axis.	R. Berman (1951).
Figs. 30, 30a; B.-S-2.	Same crystal as above except 1.5 mm diameter.	R. Berman (1952).
Figs. 30, 32; "Alumina".	Sintered alumina; density 3.70 g/cm <sup>3</sup> (95% of single crystal); grain sizes about 5 to 30 microns.	Do.





QUARTZ

Curve	Remarks	Reference
Figs. 31, 30a; H. Bz.	A single crystal with principal axis parallel to rod axis; 5 cm long, 0.3 cm diameter.	W. J. de Haas and T. Biermasz (1935).
H. Bz.-1 . . . .	A single crystal with rod axis perpendicular to principal crystal axis and parallel to bisector of two binary axes; diameter 0.216 cm.	W. J. de Haas and T. Biermasz (1937).
H. Bz.-2 . . . .	Same as above, except diameter 0.454 cm.	W. J. de Haas and T. Biermasz (1938a)
H. Bz.-2A . . . .	Same rod as 2, except diameter ground down to 0.359 cm.	W. J. de Haas and T. Biermasz (1938b).
Fig 31; B-1, 2, 3, 4; H 1, 2, 3, 4, 5, 6, 7, 8.	Single crystal 5 cm long; square cross-section, 5 mm on a side; rod length perpendicular to principal axis; # 1 was without neutron irradiation; # 2 was with 1 unit irradiation; # 3, second additional irradiation of 1.4 units; # 4. third additional irradiation of 16.5 units. The "H" curves were after heating as follows: # 1, 300°C for 8 hrs.; # 2, 400°C for 6 hrs.; # 3, 500°C for 6 hrs.; # 4, 565°C for 6 hrs.; # 5, 540°C for 60 hrs.; # 6, 540°C for 677 hrs.; # 7, 600°C for 1 hr.; # 8, 700°C for 6 hrs.	R. Berman (1951).




### IONIC CRYSTALS


Curve	Remarks	Reference
Fig. 32; H. Bz.-KBr.	Measured a long potassium bromide crystal of approx. 3 cm diameter; the lower branch of the curve near 80°K is for a sample with soldered contacts; the upper, amalgam contacts.	W. J. de Haas and T. Biermasz (1937).
H. Bz.-KCl...	Measured along potassium chloride crystal of square cross-section with a side of 0.252 cm.	Do.
.....	Measured the change in conductivity with change in crystal cross-section for several KCl crystals.	W. J. de Haas and T. Biermasz (1938a).
Fig. 32a; Bj.-CrK Alum.	Measured the conductivity of chromium potassium alum used in magnetic thermometry. Found that the conductivity depended on the rate of cooling of the alum. Curve 1 was for the sample cooled most rapidly.	D. Bijl (1949).
Fig. 32; Si.-NH <sub>4</sub> Cl	.....	C. V. Simson (1951).

### BERYLLIA

Curve	Remarks	Reference
Fig. 32-B. "Beryllia".	Sintered; density 2.94 g/cm <sup>3</sup> (97% of single crystal); crystallites with dimensions between 10 and 40 microns; $k=3.8$ at 90°K.	R. Berman (1952).








**DISORDERED DIELECTRICS**

Curve	Composition	Reference
Fig. 33; St.-Py.	Pyrex glass .....	R. W. B. Stephens (1932).
Fig. 33; Wn.Ws.- Ph.	"Phoenix"; boro-silicate glass .....	K. R. Wilkinson and J. Wilks (1948).
Fig. 33a; Bj.-J.G.20.	Jena Gerate 20 glass .....	D. Bijl (1949).
Bj.-T.....	Thuringian glass .....	Do.
Bj.-J16 III...	Jena 16 III glass .....	Do.
Bj.-M.....	Monax glass .....	Do.
Figs. 33, 33a; B.-Ph.	"Phoenix" glass .....	R. Berman (1951).
B.-Q.....	Quartz glass; upper curve is for a sample rod with approx. 7.5 mm diameter; lower curve, 6 mm diameter.	Do.
B.-Per.....	Perspex plastic.....	Do.



### 3. Bibliography\*

- J. F. Allen and E. Mendoza, Thermal conductivity of copper and German silver at liquid helium temperatures, *Proc. Camb. Phil. Soc.* **44**, 280-288 (1948).
- F. A. Andrews, R. T. Webber, and D. A. Spohr, Thermal conductivities of pure metals at low temperatures, I. Aluminum, *Phys. Rev.* **84**, 994-996 (1951).
- S. S. Ballard, L. S. Combes, and K. A. McCarthy, A comparison of the physical properties of barium fluoride and calcium fluoride, *J. Opt. Soc. Am.* **42**, 684-685 (1952) L.
- T. Barratt and R. M. Winter, Das thermische Leitvermögen von Drähten und Stäben, *Ann. Physik* **77**, 1-15 (1925).
- R. Berman, Thermal conductivity of glasses at low temperatures, *Phys. Rev.* **76**, 315-316 (1949) L.
- R. Berman, The thermal conductivities of some dielectric solids at low temperatures, *Proc. Roy. Soc. (London)* **A208**, 90-108 (1951a).
- R. Berman, The thermal conductivity of some alloys at low temperatures, *Phil. Mag.* **42**, 642-650 (1951b).
- R. Berman, The thermal conductivity of some polycrystalline solids at low temperatures, *Proc. Phys. Soc. (London)* **A65**, 1029-1040 (1952a).
- R. Berman, The thermal conductivity of disordered solids at low temperatures, *Bull. Inst. Int. du Froid, Annexe* 1952-1 (1952b).
- R. Berman, The thermal conductivity of dielectric solids at low temperatures, *Adv. in Physics (Phil. Mag. Supp.)* **2**, 103-140 (1953).
- R. Berman and D. K. C. MacDonald, The thermal and electrical conductivity of sodium at low temperatures, *Proc. Roy. Soc. (London)* **A209**, 368-375 (1951).
- R. Berman and D. K. C. MacDonald, The thermal and electrical conductivity of copper at low temperatures, *Proc. Roy. Soc. (London)* **A211**, 122-128 (1952).
- R. Berman, F. E. Simon, and J. Wilks, Thermal conductivity of dielectric crystals; the "Umklapp" process, *Nature* **168**, 277-280 (1951).
- R. Berman, F. E. Simon, and J. M. Ziman, The thermal conductivity of diamond at low temperatures, *Proc. Roy. Soc. (London)* **A220**, 171-183 (1953).
- C. E. Berry, The effect of an electric field on the thermal conductivity of glass, *J. Chem. Phys.* **13**, 1355-1356 (1949).
- C. C. Bidwell, Thermal conductivity and specific heat of lithium, *Phys. Rev.* **25**, 896 (1925A).
- C. C. Bidwell, Thermal conductivity of lithium, sodium, and lead to  $-250^{\circ}$  C, *Phys. Rev.* **27**, 819 (1926a) A.
- C. C. Bidwell, Thermal conductivity of Li and Na by a modification of the Forbes bar method, *Phys. Rev.* **28**, 584-597 (1926b).
- C. C. Bidwell, A simple relation between thermal conductivity, specific heat and absolute temperature, *Phys. Rev.* **32**, 311-314 (1928).
- C. C. Bidwell, Thermal conductivity of lead and of single and poly crystal zinc, *Phys. Rev.* **33**, 249-251 (1929).
- C. C. Bidwell, Thermal conductivity of metals, *Phys. Rev.* **58**, 561-564 (1940).
- D. Bijl, Some experiments on magnetic thermometry and heat conductivity of chromium potassium alum and glass at low temperatures, *Physica* **4**, 684-693 (1949).
- H. Bremmer and W. J. de Haas, On the conduction of heat by some metals at low temperatures, *Physica* **3**, 672-686 (1936).
- H. Bremmer and W. J. de Haas, On the heat conductivity of superconductivity alloys, *Physica* **3**, 692-704 (1936).
- P. W. Bridgman, Thermal conductivity and thermoelectromotive force of single metal crystals, *Proc. Nat. Acad. Sci.* **11**, 608-612 (1925).
- R. A. Buerschaper, Thermal and electrical conductivity of graphite and carbon at low temperatures, *J. Appl. Phys.* **15**, 452-454 (1944).
- J. E. Calthrop, The effects of torsion on the thermal and electrical conductivities of metals, *Proc. Phys. Soc. (London)* **36**, 168-175 (1924).
- J. E. Calthrop, The effects of torsion upon the thermal and electrical conductivities of aluminum, with special reference to single crystals, *Proc. Phys. Soc. (London)* **38**, 207-214 (1926).
- C. H. Cartwright, Wiedemann-Franz'sche Zahl, Wärmeleitfähigkeit und thermoelektrische Kraft von Tellur, *Ann. Physik* **18**, 656-678 (1933).
- C. S. Chow, The thermal conductivity of some insulating materials at low temperatures, *Proc. Phys. Soc. (London)* **61**, 206-216 (1948).
- W. F. Chubb, The thermal and electrical conductivities of metals and alloys, *Phil. Mag.* **30**, 323-330 (1940).
- J. R. Clarke, On the thermal conductivity of some solid insulators, *Phil. Mag.* **40**, 502-504 (1920).
- M. Cox, Thermal and electrical conductivities of tungsten and tantalum, *Phys. Rev.* **64**, 241-7 (1943).
- A. P. Cray, Thermal conductivity of Acheson graphite, *Phys. Rev.* **4**, 332-333 (1933).
- T. M. Dauphinee, D. G. Ivey, and H. D. Smith, The thermal conductivity of elastomers under stretch and at low temperatures, *Can. J. Research* **A28**, 596-615 (1950).
- D. P. Detwiler and H. A. Fairbank, Thermal conductivity in the intermediate state of pure superconductors, *Phys. Rev.* **86**, 574 (1952a).
- D. P. Detwiler and H. A. Fairbank, The thermal resistivity of superconductors, *Phys. Rev.* **88**, 1049-1052 (1952b).
- J. W. Donaldson, Thermal conductivities of industrial non-ferrous alloys, *J. Inst. Metals* **34**, 43-56 (1925).
- H.-D. Erfling and E. Grüneisen, Weitere Untersuchungen an Berylliumkristallen im transversalem und longitudinalen Magnetfeld, *Ann. Physik* **41**, 89-99 (1942).
- S. Erk, A. Keller and H. Poltz, Über die Wärmeleitfähigkeit von Kunststoffen, *Physik. Z.* **38**, 394-402 (1937).
- I. Estermann and J. E. Zimmerman, Heat conduction in alloys and semi-conductors at low temperatures, *Tech. Report No. 6* (Carnegie Institute of Technology) (June 1951).
- I. Estermann and J. E. Zimmerman, Heat conduction in alloys at low temperatures, *J. Appl. Phys.* **23**, 578-588 (1952).
- A. Eucken, Über die Temperaturabhängigkeit der Wärmeleitfähigkeit fester Nichtmetalle, *Ann. Physik* **34**, 185-221 (1911a).
- A. Eucken, Die Wärmeleitfähigkeit einiger Kristalle bei tiefen Temperaturen, *Verhand. Deutsch. Physik. Gesell.* **13**, 829-835 (1911b).
- A. Eucken, Die Wärmeleitfähigkeit einiger Kristalle bei tiefen Temperaturen, *Physik. Z.* **12**, 1005-1008 (1911c).

\*References followed by A are abstracts; by L, Letters to the Editor.

- A. Eucken, Zur Kenntnis des Wiedemann-Franz'schen Gesetzes, III, Z. physik. Chem. 134, 220-229 (1928).
- A. Eucken and K. Dittrich, Zur Kenntnis des Wiedemann-Franz'schen Gesetzes, II, Z. physik. Chem. 125, 211-228 (1927).
- A. Eucken and G. Gehlhoff, Elektrisches, thermisches Leitvermögen und Wiedemann-Franz'sche Zahl der Antimon-cadmiumlegierungen zwischen 0° und -190° C, Verhand. Deutsch. Physik. Gesell. 14, 169-182 (1912).
- A. Eucken and G. Kuhn, Ergebnisse neuer Messungen der Wärmeleitfähigkeit fester kristallisierter Stoffe bei 0° und -190° C, Z. physik. Chem. 134, 193-219 (1928).
- A. Eucken and O. Neumann, Zur Kenntnis des Wiedemann-Franz'schen Gesetzes, I, Z. physik. Chem. 111, 431-446 (1924).
- A. Eucken and E. Schröder, Das Wärmeleitvermögen einiger verfestigter Flüssigkeiten und Gase (Benzol, Bromwasserstoff, Stickoxydul), Ann. Physik. 36, 609-620 (1939).
- A. Eucken and H. Warrentrup, Eine Apparatur zur Messung der Wärmeleitfähigkeit von Metalblechen, Z. tech. Phys. 16, 99-104 (1935).
- C. G. B. Garrett, The thermal conductivity of potassium chrome alum at temperatures below one degree absolute, Phil. Mag. 41, 621-630 (1950).
- G. Gehlhoff and F. Neumeier, Über die thermischen und elektrischen Eigenschaften der Wismut-Antimon-Legierungen zwischen -190° und +100° C, Verhand. Deutsch. Physik. Gesell. 15, 876-896 (1913a).
- G. Gehlhoff and F. Neumeier, Beiträge zur Kenntnis der thermischen und elektrischen Eigenschaften von gepressten Pulvern aus Antimon, Wismut und Bleiglanz, Verhand. Deutsch. Physik. Gesell. 15, 1069-1081 (1913b).
- G. Gehlhoff and F. Neumeier, Wärmeleitvermögen, elektrisches Leitvermögen, Thermokraft und Wiedemann-Franz'sche Zahl des Quecksilbers zwischen -190° und +150° C, Verhand. Deutsch. Physik. Gesell. 21, 201-217 (1919).
- A. N. Gerritsen, A review of the magnetic properties of Bi, Nederland. Tijdschr. Naturkunde 10, 160-170 (1943).
- E. Giebe, Über die Bestimmung des Wärmeleitvermögens bei tiefen Temperaturen, Verhand. Deutsch. Physik. Gesell. 5, 60-66 (1903).
- E. Goens and E. Grüneisen, Elektrizitäts- und Wärmeleitung in Zink- und Cadmiumkristallen, Ann. Physik 14, 164-180 (1932).
- B. B. Goodman, The thermal conductivity of superconducting tin below 1° K, Proc. Phys. Soc. (London) A66, 217-227 (1953).
- E. Griffiths and G. W. C. Kaye, The measurement of thermal conductivity, Proc. Roy. Soc. (London) A104, 71-98 (1923).
- J. H. Gray, On a method of determining the thermal conductivity of metals, with application to copper, silver, gold and platinum, Phil. Trans. Roy. Soc. (London) A186, 165-186 (1895).
- G. Groetzinger and R. Frey, Versuche über die Änderung des Wärmedurchganges durch Gase ohne elektrisches Moment, durch Flüssigkeiten und feste Körper infolge eines elektrischen Feldes, Physik. Z. 36, 292-297 (1935).
- E. Grüneisen, Ueber die Bestimmung des metallischen Wärmeleitvermögens und über sein Verhältnis zur elektrischen Leitfähigkeit, Ann. Physik. 3, 43-74 (1900).
- E. Grüneisen, Temperaturgesetz des Wärmewiderstandes regulärer Metalle, Z. Physik. 46, 151-159 (1927).
- E. Grüneisen and H. Adenstedt, Anisotropie der Wärmeleitung und Thermokraft regulärer Metalle (Wolfram) im transversalen Magnetfeld bei 20° K, Ann. Physik. 29, 597-604 (1937).
- E. Grüneisen and H. Adenstedt, Einfluss transversaler Magnetfelder auf Elektrizitäts- und Wärmeleitung reiner Metalle bei tiefer Temperatur, Ann. Physik. 31, 714-744 (1938).
- E. Grüneisen and H.-D. Erling, Elektrischer und thermischer Widerstand von Berylliumkristallen im transversalen Magnetfeld, Ann. Physik. 38, 399-420 (1940).
- E. Grüneisen and J. Gieslen, Untersuchungen an Wismutkristallen. I. Wärme- und Elektrizitätsleitung in transversalen Magnetfeldern, Ann. Physik. 26, 449-464 (1936).
- E. Grüneisen and E. Goens, Elektrizitäts- und Wärmeleitung von ein- und vielkristallinen Metallen des regulären Systems, Z. Physik 44, 615-642 (1927).
- E. Grüneisen, K. Rausch, and K. Weiss, Zur Elektrizitäts- und Wärmeleitung von Wismut-Einkristallen im transversalen Magnetfeld, Ann. Physik. 7, 1-17 (1950).
- E. Grüneisen and H. Reddemann, Elektronen- und Gitterleitung beim Wärmefluss in Metallen, Ann. Physik 20, 843-877 (1934).
- W. J. de Haas, S. Aoyama, and H. Bremmer, Thermal conductivity of tin at low temperatures, Comm. Kamerlingh Onnes Lab., Univ. Leiden 19, #214a (1931).
- W. J. de Haas and T. Biermasz, The thermal conductivity of quartz at low temperatures, Physica 2, 673-682 (1935).
- W. J. de Haas and T. Biermasz, Sur la conductibilité thermique aux basses températures, Leiden Communications 22, Supplement No. 82b, 1-13 (1936-1938), reprinted from: Rapports et Communications, No. 24, 7e Congrès International du Froid, la Hague-Amsterdam, juin 1936.
- W. J. de Haas and T. Biermasz, The thermal conductivity of KBr, KCl and SiO<sub>2</sub> at low temperatures, Physica 4, 752-756 (1937).
- W. J. de Haas and T. Biermasz, The thermal conductivity of diamond and potassiumchloride, Physica 5, 47-53 (1938a).
- W. J. de Haas and T. Biermasz, Die Wärmeleitfähigkeit von Kristallen bei tiefen Temperaturen, Physica 5, 320-324 (1938b).
- W. J. de Haas and T. Biermasz, The dependence on thickness of the thermal resistance of crystals at low temperatures, Physica 5, 619-624 (1938c).
- W. J. de Haas and H. Bremmer, Thermal conductivity of lead and tin at low temperatures, Comm. Kamerlingh Onnes Lab., Univ. Leiden, 20, #214 d (1931).
- W. J. de Haas and H. Bremmer, Thermal conductivity of indium at low temperatures, Comm. Kamerlingh Onnes Lab., Univ. of Leiden, 20, #220 b (1932).
- W. J. de Haas and H. Bremmer, The conduction of heat of lead-thallium at low temperatures, Comm. Kamerlingh Onnes Lab., Univ. Leiden, 20, #220 c (1932).
- W. J. de Haas and H. Bremmer, Determination of the heat resistance of mercury at the temperatures obtainable with liquid helium, Physica 3, 687-691 (1936).
- W. J. de Haas and W. H. Capel, A method for the determination of the thermal resistance of metal single crystals at low temperatures, Physica 1, 725-736 (1934a).

- W. J. de Haas and W. H. Capel, The thermal resistance of bismuth single-crystals at low temperatures, *Physica* 1, 929-934 (1934b).
- W. J. de Haas, A. N. Gerritsen, and W. H. Capel, The thermal resistance of bismuth single-crystals at low temperatures and in a magnetic field *Physica* 3, 1143-1158 (1936).
- W. J. de Haas and J. de Nobel, The thermal and the electrical resistance of a tungsten single-crystal at low temperatures and in magnetic fields, *Physica* 5, 449-463 (1938).
- W. J. de Haas and A. Rademakers, The thermal conductivity of lead in the superconducting and normal state, *Physica* 7, 992-1002 (1940).
- C. V. Heer and J. G. Daunt, Heat flow in metals below 1° K and a new method for magnetic cooling, *Phys. Rev.* 76, 854-855 (1949).
- J. W. Hornbeck, Thermal and electrical conductivities of the alkali metals, *Phys. Rev.* 2, 217-240 (1913).
- G. W. Hull and T. H. Geballe, Thermal conductivity of single crystalline silicon, *Bull. Am. Phys. Soc.* 29, 11 (1954) A.
- J. K. Hulm, Thermal conductivity of superconductors, *Nature* 163, 368-369 (1949) L.
- J. K. Hulm, The thermal conductivity of tin, mercury, indium, and tantalum at liquid helium temperatures, *Proc. Roy. Soc. (London)* A204, 98-123 (1950).
- J. K. Hulm, The thermal conductivity of a copper-nickel alloy at low temperature, *Proc. Phys. Soc. (London)* A64, 207-211 (1951).
- J. K. Hulm, Anomalous thermal conductivity of pure metals at low temperatures, *Proc. Phys. Soc. (London)* A65, 227-228 (1952a) L.
- J. K. Hulm, Heat transfer in superconducting alloys, *N.B.S. Circular* 519, 37-42 (1952b).
- J. K. Hulm, Thermal resistivity of mercury in the intermediate state, *Phys. Rev.* 90, 1116 (1953) L.
- R. B. Jacobs and C. Starr, Thermal conductance of metallic contacts, *Rev. Sci. Inst.* 10, 140-141 (1939).
- W. Jaeger and H. Diesselhorst, Wärmeleitung, Elektrizitätsleitung, Wärmecapazität und Thermokraft einiger Metalle, *Wiss. Abhandlung Phys. Techn. Reichsanstalt* 3, 269-424 (1900). (Cataloged under Charlottenburg).
- C. H. Johansson and J. O. Linde, Kristallstruktur, . . . Wärmeleitfähigkeit, . . . des Systems AuPt in Verbindung, *Ann. Physik* 5, 762-792 (1930).
- W. G. Kannaluk, On the thermal conductivity of some metal wires, *Proc. Roy. Soc. (London)* A131, 320-335 (1951).
- W. G. Kannaluk, The thermal and electrical conductivities of several metals between -183° C and 100° C, *Proc. Roy. Soc. (London)* A141, 159-168 (1933).
- W. G. Kannaluk and T. H. Laby, The thermal and the electrical conductivity of a copper crystal at various temperatures, *Proc. Roy. Soc. (London)* A121, 640-653 (1928).
- J. Karweil and K. Schäfer, Die Wärmeleitfähigkeit einiger schlecht leitender Legierungen zwischen 3 und 30° K, *Ann. Physik* 36, 567-577 (1939).
- G. W. C. Kaye and W. F. Higgins, The thermal conductivity of a single crystal of bismuth in a transverse magnetic field, *Phil. Mag.* 8, 1056-1059 (1929).
- G. W. C. Kaye and J. K. Roberts, The thermal conductivities of metal crystals, I. Bismuth, *Proc. Roy. Soc. (London)* A104, 98-114 (1923).
- P. H. Keesom, Heat conductivity of glass at 1.3° K, *Physica* 11, 339-342 (1945).
- W. R. G. Kemp, A. K. Sreedhar, and G. K. White, The thermal conductivity of magnesium at low temperatures, *Proc. Phys. Soc. (London)* A66, 1077-1078 (1953).
- R. Kikuchi, Wärmeleitvermögen und elektrisches Leitvermögen einer Anzahl von Magnesium-Legierungen und ihr Verhalten zum Wiedemann-Franz'schen Gesetz, *Sci. Rep. Tôhoku Imperial Univ. (1st Series)* 21, 585-593 (1932) (Cataloged under Sendai).
- C. Kittel, Interpretation of the thermal conductivity of glasses, *Phys. Rev.* 75, 972-974 (1949).
- M. Kohler, Wärmeleitung der Metalle im starken Magnetfeld, *Ann. Physik* 5, 181-189 (1949).
- S. Konno, On the variation of thermal conductivity during the fusion of metals, *Sci. Rep. Tôhoku Imperial Univ. (1st Series)* 8, 169-179 (1919) (Cataloged under Sendai).
- S. Konno, On the variation of thermal conductivity during the fusion of metals, *Phil. Mag.* 40, 542-552 (1920).
- N. Kurti, B. V. Rollin, and F. Simon, Preliminary experiments on temperature equilibria at very low temperatures, *Physica* 3, 266-274 (1936).
- Landolt-Börnstein *Physikalisch-chemische Tabellen*, Edited by W. A. Roth and K. Scheel (Julius Springer, Berlin) 5th ed., vol. 2, 1923; 5th ed., 1st supplement, vol. 1, 1927; 5th ed., 2d supplement, vol. 2, 1931; 5th ed., 3d supplement, vol. 3, 1936.
- I. Langmuir and J. B. Taylor, The heat conductivity of tungsten and the cooling effects of leads upon filaments at low temperatures, *Phys. Rev.* 50, 68-87 (1936).
- C. H. Lees, Effects of temperature and pressure on the thermal conductivities of solids—Part 1. The effect of temperature on the thermal conductivities of some electrical insulators, *Phil. Trans. Roy. Soc. (London)* A204, 433-466 (1905).
- C. H. Lees, The effects of temperature and pressure on the thermal conductivities of solids—Part 2. The effects of low temperatures on the thermal and electrical conductivities of certain approximately pure metals and alloys, *Phil. Trans. Roy. Soc. (London)* A208, 381-443 (1908).
- C. H. Lees and J. E. Calthrop, The effect of torsion on the thermal and electrical conductivities of metals, *Proc. Phys. Soc. (London)* 35, 225-234 (1923).
- E. J. Lewis, Some thermal and electrical properties of beryllium, *Phys. Rev.* 34, 1575-1587 (1929).
- J. O. Linde, An investigation of the validity of the Wiedemann-Franz-Lorenz law, *Arkiv Fysik* 4, 541-554 (1952).
- L. Lorenz, Ueber das Leitungsvermögen der Metalle für Wärme und Electricität, *Ann. Physik* 13, 422-447 (1881a).
- L. Lorenz, Ueber das Leitungsvermögen der Metalle für Wärme und Electricität, *Ann. Physik* 13, 582-606 (1881b).
- P. Macchia, Thermal conductivity at low temperatures, *Accad. Lincei. Atti.* 16, 507-517 (1907).
- W. Mannchen, Wärmeleitvermögen, elektrisches Leitvermögen und Lorenz'sche Zahl einiger Leichtmetall-Legierungen, *Z. Metallkunde* 23, 193-196 (1931).
- Massachusetts Institute of Technology, Quarterly Progress Reports (October 15, 1952, April 15, 1953, July 15, 1953).
- W. Meissner, Über die thermische und elektrische Leitfähigkeit von Kupfer zwischen 20 und 373° abs., *Verhand. Deutsch. Physik. Gesell.* 16, 262-272 (1914).
- W. Meissner, Thermische und elektrische Leitfähigkeit von Platin zwischen 20 und 373° abs., *Ann. Physik* 47, 1001-1058 (1915).

- W. Meissner, Thermische und elektrische Leitfähigkeit von Lithium zwischen 20 und 373° abs., *Z. Physik* 2, 373-379 (1920).
- H. Masumoto, On the thermal and electrical conductivities of some aluminum alloys, *Sci. Rep. Tōhoku Imperial Univ. (1st Series)* 13, 229-242 (1925) (Cataloged under Sendai).
- H. Masumoto, On the electrical and thermal conductivities of carbon steel and cast iron, *Sci. Rep. Tōhoku Imperial Univ. (1st Series)* 16, 417-435 (1927) (Cataloged under Sendai).
- K. Mendelssohn, Heat conductivity of metals at low temperatures, *Bull. Inst. Int. du Froid, Annexe* 1952-1, 69-79 (1952).
- K. Mendelssohn, Thermal conductivity of superconductors, *Physica* 19, 775-787 (1953).
- K. Mendelssohn and J. L. Olsen, Heat transport in superconductors, *Proc. Phys. Soc. (London)* A63, 2-13 (1950a).
- K. Mendelssohn and J. L. Olsen, Heat flow in superconductive alloys, *Proc. Phys. Soc. (London)* A63, 1182-1183 (1950b).
- K. Mendelssohn and J. L. Olsen, Anomalous heat flow in superconductors, *Phys. Rev.* 80, 859-862 (1950c).
- K. Mendelssohn and R. B. Pontius, Thermal conductivity of supraconductors in a magnetic field, *Phil. Mag.* 24, 777-787 (1937).
- K. Mendelssohn and C. A. Renton, Heat conductivities of superconductive Sn, In, Tl, Ta, Cb, and Al below 1° Kelvin, *Phil. Mag.* (7) 44, 776-781 (1953).
- K. Mendelssohn and H. M. Rosenberg, The thermal conductivity of metals at low temperatures I: The elements of Groups 1, 2 and 3, *Proc. Phys. Soc. (London)* A65, 385-388 (1952a).
- K. Mendelssohn and H. M. Rosenberg, The thermal conductivity of metals at low temperatures II: The transition elements, *Proc. Phys. Soc. (London)* A65, 388-394 (1952b).
- K. Mendelssohn and H. M. Rosenberg, The thermal conductivity of metals in high magnetic fields at low temperatures, *Proc. Roy. Soc. (London)* A218, 190-205 (1953).
- W. C. Michels and M. Cox, The thermal conductivity of tungsten, *Physics* 7, 1953-155 (1936).
- S. Mizushima and J. Okada, Notes on the electrical and thermal conductivities of graphite and amorphous carbon, *Phys. Rev.* 82, 94-95 (1951).
- S. Mrozowski, Thermal conductivity of carbons and graphite, *Phys. Rev.* 86, 251-252 (1952) L.
- J. Nicol and T. P. Tseng, Thermal conductivity of copper between 0.25° K and 4.2° K, *Phys. Rev.* 92, 1062-1063 (1953) L.
- J. de Nobel, Thermal and electrical resistance of a tungsten single crystal at low temperatures and in high magnetic fields, *Physica* 15, 532-540 (1949).
- J. de Nobel, Heat conductivity of steels and a few other metals at low temperatures, 17, 551-562 (1951).
- J. L. Olsen, Heat transport in lead-bismuth alloys, *Proc. Phys. Soc.* A65, 518-532 (1952).
- J. L. Olsen and C. A. Renton, Heat conductivity of superconductive lead below 1° K, *Phil. Mag.* 43, 946-948 (1952).
- J. L. Olsen and H. M. Rosenberg, The thermal conductivity of metals at low temperatures, *Adv. Physics* 2, 28-65 (1953).
- H. K. Onnes and G. Holst, Preliminary determination of the specific heat and of the thermal conductivity of mercury, *Comm. Kamerlingh Onnes Lab., Univ. of Leiden*, No. 142c, 24-33 (1914).
- J. R. Partington, An advanced treatise on physical chemistry (Longmans, Green & Co., Ltd., London, 1952), first edition, vol. 3, pp. 458-561.
- T. Peczalski, Contribution à l'étude de la conductibilité calorifique des solides, *Ann. physique* 7, 185-224 (1917).
- R. L. Powell, The thermal conductivity of "Easy-Flo" silver solder from 20° to 200° K, N.B.S. Report 2609 (1953, 3 pp. (unpublished)).
- R. W. Powell, The electrical resistivity of gallium and some other anisotropic properties of this metal, *Proc. Roy. Soc. (London)* A209, 525-541 (1951).
- R. W. Powers, D. Schwartz, and H. E. Johnston, The thermal conductivity of metals and alloys at low temperatures I. Apparatus for measurements between 25° and 300° K. Data on pure aluminum, OFHC copper and "L" nickel, TR 264-5, Cyrogenics Laboratory, Ohio State University (1951) 22 pp.
- R. W. Powers, J. B. Ziegler, and H. L. Johnston, The thermal conductivity of metals and alloys at low temperatures. II. Data on iron and several steels between 25° and 300° K Influence of alloying constituents, TR 264-6, Cyrogenics Laboratory, Ohio State University (1951a), 17 pp.
- R. W. Powers, J. B. Ziegler, and H. L. Johnston, The thermal conductivity of metals and alloys at low temperatures. III. Data for aluminum alloys between 25° and 300° K, TR 264-7, Cyrogenics Laboratory, Ohio State University (1951b), 10 pp.
- R. W. Powers, J. B. Ziegler, and H. L. Johnston, The thermal conductivity of metals and alloys at low temperatures. IV Data on constantan, monel and contracid between 25° and 300° K, TR 264-8, Cyrogenics Laboratory, Ohio State University (1951c), 11 pp.
- R. W. Quick, C. D. Child, and B. S. Lamphear, Thermal conductivity of copper, *Phys. Rev.* 3, 1-20 (1895).
- A. Rademakers, The thermal conductivity of lead and tin in the superconducting and in the normal state, *Physica* 15, 849-859 (1949).
- K. Rausch, Untersuchungen an Antimon-Einkristallen im transversalen Magnetfeld, *Ann. Physik* 1, 190-206 (1947).
- H. Reddemann, Wärmleitvermögen, Wiedemann-Franz-Lorenzsche Zahl und Thermokraft von Quecksilber-einkristallen, *Ann. Physik* 14, 139-163 (1932).
- H. Reddemann, Änderung der thermischen und elektrischen Leitfähigkeit eines Bi-Einkristallen im Magnetfeld, *Ann. Physik* 20, 441-448 (1934).
- H. Reddemann, Wiedemann-Franzsche Zahl von  $\beta$ -Manganan bei -190° C, *Ann. Physik* 22, 28-30 (1935).
- A. Rietzsch, Über die thermische und elektrische Leitfähigkeit von Kupfer-Phosphor und Kupfer-Arsen, *Ann. Physik* 3, 403-427 (1900).
- C. J. Rigney and L. I. Bockstahler, The thermal conductivity of titanium between 20 and 273° K, *Phys. Rev.* 83, 220 (1951) A.
- M. T. Rodine, Thermal conductivities of bismuth single crystals as influenced by a magnetic field, *Phys. Rev.* 46, 910-916 (1934).
- H. M. Rosenberg, Private Communication (January 1954a).
- H. M. Rosenberg, The thermal and electrical conductivity of magnesium at low temperatures, *Phil. Mag.* 45, 73-79 (1954b).
- A. Schallmach, Heat conductivity of rubber at low temperatures, *Nature* 145, 67 (1940) L.
- A. Schallmach, Heat conductivity of rubber at low temperatures, *Proc. Phys. Soc. (London)* 53, 214-218 (1941).

- W. Schaufelberger, Wärmeleitungsfähigkeit des Kupfers, aus dem stationären und variablen Temperaturzustand bestimmt, und Wärmeleiters, *Ann. Physik* **7**, 589-630 (1902).
- F. H. Schofield, The thermal and electrical conductivities of some pure metals, *Proc. Roy. Soc. (London)* **A107** (1925).
- R. Schott, Über das Wärmeleitvermögen einigen Metalle bei tiefen Temperaturen, *Verhand. Deutsch. Physik. Gesell.* **18**, 27-34 (1916).
- F. A. Schulze, Die Wärmeleitfähigkeit einiger Reihen von Edelmetalllegierungen, *Verhand. Deutsch. Physik. Gesell.* **13**, 856-856 (1911).
- S. Shalyt, The thermal conductivity of bismuth at low temperatures, *J. Phys. (U.S.S.R.)* **8**, 315-316 (1944) L.
- E. G. Sharkoff, Thermal conductivity of magnesium, *Quarterly Progress Report (of Research Lab. of Electronics, M.I.T.)* (October 15, 1952).
- E. G. Sharkoff, Thermal conductivity of magnesium, *Quarterly Progress Report (of Research Lab. of Electronics, M.I.T.)* (April 15, 1953a).
- E. G. Sharkoff, Electrical and thermal conductivity of magnesium, *Quarterly Progress Report (of Research Lab. of Electronics, M.I.T.)* (July 15, 1953b).
- C. V. Simson, Über die Wärmeleitfähigkeit des Ammoniumchlorid im Bereiche seiner II-III-Umwandlung, *Naturwiss.* **38**, 559 (1951).
- A. W. Smith, Thermal conductivity of graphite, North American Aviation, Inc., Downey, California (1954) (Unpublished).
- C. S. Smith and E. W. Palmer, Thermal and electrical conductivities of copper alloys, *Am. Inst. Mining Metal. Eng. Tech. Publ. No. 648* (1935).
- E. H. Sondheimer, The thermal conductivity of metals at low temperatures, *Proc. Phys. Soc. (London)* **A65**, 562-564 (1952) L.
- J. Staebler, Electriche und thermisches Leitvermögen und Wiedemann-Franzche Zahl von Leichtmetallen und Magnesium-legierungen. *Dissertation, April, 1929, Technische Hochschule of Breslau. Published by Doktardruck-Graphisches Institut Paul Funk, Berlin.*
- R. W. B. Stephens, The temperature variation of the thermal conductivity of Pyrex glass, *Phil. Mag.* **14**, 897-914 (1932).
- W. W. Tyler and A. C. Wilson, Jr., Thermal conductivity, electrical resistivity, and thermoelectric power of titanium alloy RC-130-B, *Knolls Atomic Power Laboratory Report 803* (1952) 41 pp.
- W. W. Tyler and A. C. Wilson, Jr., Thermal conductivity, electrical resistivity, and thermoelectric power of graphite, *Phys. Rev.* **89**, 870-875 (1953).
- W. W. Tyler, A. C. Wilson, Jr., and G. J. Wolga, Thermal conductivity, electrical resistivity, and thermoelectric power of uranium, *Knolls Atomic Power Laboratory Report 802* (1952) 25 pp.
- F. J. Webb, K. R. Wilkinson, and J. Wilks, The thermal conductivity of solid helium, *Proc. Roy. Soc. (London)* **A214**, 546-563 (1952).
- F. J. Webb and J. Wilks, The thermal conductivity of solid helium at high densities, *Phil. Mag.* **44**, 663-674 (1953).
- R. T. Webber and D. A. Spohr, Thermal resistivity of superconducting mercury in the intermediate state, *Phys. Rev.* **91**, 414-415 (1953) L.
- S. Weber, . . . des Verhältnisses von Wärmeleitung zur Elektrizitätsleitung . . . des Wolframs, *Ann. Physik* **54**, 165-181 (1917).
- G. K. White, The thermal conductivity of gold at low temperatures, *Proc. Phys. Soc. (London)* **A66**, 559-564 (1953a).
- G. K. White, The thermal conductivity of silver at low temperatures, *Proc. Phys. Soc. (London)* **A66**, 844-845 (1953b) L.
- G. K. White, The thermal and electrical conductivity of copper at low temperatures, *Aust. J. Physics* **6**, 397-404 (1953c).
- K. R. Wilkinson and J. Wilks, Some measurements of heat flow along technical materials in the region 4° to 20° K, *Phys. in Ind.* **26**, 19-20 (1949).
- J. Wilks, The thermal conductivity of ideal dielectric crystals, *Bull. Inst. Int. du Froid, annexe 1952-1* (1952).

BOULDER, COLORADO, July 23, 1954