NAVAL POSTGRADUATE SCHOOL Monterey, California





THESIS

TIME-FREQUENCY DOMAIN DISTRIBUTION AND ITS APPLICATION TO RECIPROCATING MACHINERY ANALYSIS

by

John E. Harding

September 1994

Thesis Advisor:

Young S. Shin

Approved for public release; distribution is unlimited.

19941202 155

DTIC QUALITY INSPECTED 8

de la te

REPORT DOCUMENTATION PAGE

.

Form Approved OMB No. 0704

		· · · · · · · · · · · · · · · · · · ·				
Public reporting burden for this collect searching existing data sources, gatheri regarding this burden estimate or any of headquarters Services, Directorate for I the Office of Management and Budget,	ion of information i ng and maintaining other aspect of this c information Operation Paperwork Reducti	s estimated to average the data needed, and c collection of informatic ons and Reports, 1215 on Project (0704-0188	1 hour per ompleting a on, including Jefferson Da) Washingto	response, includ nd reviewing the suggestions for avis Highway, S on DC 20503.	ling the time f e collection of r reducing this uite 1204, Arb	or reviewing instruction, information. Send comments burden, to Washington lington, VA 22202-4302, and to
1. AGENCY USE ONLY2. REPORT DATE September 19943. REPORT TYPE AND DATES CO Master's Thesis						ND DATES COVERED hesis
4. TITLE AND SUBTITLE: AND ITS APPLICATION (u) 6. AUTHOR(S) Harding	 4. TITLE AND SUBTITLE: TIME-FREQUENCY DOMAIN DISTRIBUTION AND ITS APPLICATION TO RECIPROCATING MACHINERY ANALYSIS (u) 5. FUNDING NUMBERS 					
7. PERFORMING ORGANIZ Naval Postgraduate Schoo Monterey, CA 93943-5000	6. AUTHOR(S) Harding, John E. 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) 8. PERFORMING Naval Postgraduate School ORGANIZATION Monterey, CA 93943-5000 REPORT NUMBER					
9. SPONSORING/MONITOR	ING AGENCY	NAME(S) AND A	ADDRESS	S(ES)	10. SPON AGEN	SORING/MONITORING
11. SUPPLEMENTARY NOT reflect the official policy of	ES The views or position of	s expressed in t the Departmen	his thesi t of Defe	is are those ense or the	e of the au U.S. Go	uthor and do not vernment.
12a. DISTRIBUTION/AVAILABILITY STATEMENT12b. DISTRIBUTION CODEApproved for public release; distribution is unlimited.*A						
13.ABSTRACT Accurate assessment of ship vessels. Current shipboard mac identify possible faults and prof In reciprocating machinery the cases transient. This study prop advanced methods for condition time-frequency domain distribut time-frequency representation, w To simulate faulty conditions, c is proposed Wavelet Analysis w	boboard machiner chinery vibration olem areas. Thi vibration signal poses the use of a monitoring of a tion for the deter vibration data fro constructed artifi vill play a comp	y condition is ess monitoring and d s method has prov- is no longer a stat Pseudo Wigner-V non-stationary and ction of fault locat om two types of re- cial fault signals w lementary role to	ential in in liagnostic ren to be i ionary, er fille Distri transient tion and s eciprocatin vill be intu the Pseude	ncreasing the procedures u inadequate for godic proces bution and in shipboard m everity level. ng air compre- roduced into o Wigner-Vi	e operationa ise frequence or reciprocal s, but is tin ntroduces W achinery. To demor essors will the vibratic lle Distribut	l capability of naval cy domain spectra to ting machinery analysis. ne-dependent and in some Vavelet analysis as two These methods employ a instrate the benefits of a be processed for analysis. on data and analyzed. It tion technique.
14. SUBJECT TERMS Pseudo Wigner-Ville Distr Frequency Spectrum	ibution, Wave	elet Analysis,	Time Do	omain Ana	lysis,	15. NUMBER OF PAGES 138 16. PRICE CODE
17. SECURITY CLASSIFI- CATION OF REPORT Unclassified	17. SECURITY CLASSIFI- CATION OF REPORT18. SECURITY CLASSIFI- CATION OF THIS PAGE19. SECURITY CLASSIFI- CATION OF ABSTRACT20. LIMITATION OF ABSTRACTUnclassifiedUnclassifiedUnclassifiedUL					20. LIMITATION OF ABSTRACT UL
NSN 7540-01-280-5500					Stand	lard Form 298 (Rev. 2-89) Prescribed by ANSI STD 239-18

i

Approved for public release; distribution is unlimited.

Time-Frequency Domain Distribution and Its Application to Reciprocating **Machinery Analysis**

by

John E. Harding Lieutenant, United States Coast Guard B.S., United States Coast Guard Academy, 1987

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN MECHANICAL ENGINEERING

from the

	NAVAL POSTGRADUATE SCHOOL
	September 1994
Author:	
Approved by:	John E. Harding
	Young S. Shin, Thesis Advisor
-	Matthe Killeln
	Matthew D. Kelleher, Chairman
10 ¹⁰⁰	Department of Mechanical Engineering
ATIS TAB DTIC TAB	7
Unain 121cc 10at codes	1
By Districture 11117 Districture 11117 Availability and/or Availability Special	ii
All I	

ABSTRACT

Accurate assessment of shipboard machinery condition is essential in increasing the operational capability of naval vessels. Current shipboard machinery vibration monitoring and diagnostic procedures use frequency domain spectra to identify possible faults and problem areas. This method has proven to be inadequate for reciprocating machinery analysis. In reciprocating machinery the vibration signal is no longer a stationary, ergodic process, but is time-dependent and in some This study proposes the use of Pseudo cases transient. Wigner-Ville Distribution and introduces Wavelet Analysis as two advanced methods for condition monitoring of nonstationary and transient shipboard machinery. These methods employ a time-frequency domain distribution for the detection of fault location and severity level. To demonstrate the benefits of a time-frequency representation, vibration data from two types of reciprocating air compressors will be processed for analysis. To simulate faulty conditions, constructed artificial fault signals will be introduced into the vibration data and analyzed. It is proposed that Wavelet Analysis will play a complementary role to the Pseudo Wigner-Ville Distribuition technique.

iii

TABLE OF CONTENTS

I.	INTRODUCTION					
	A.	GENERAL BACKGROUND 1				
		1. Rational For Maintenance and Monitoring				
		Programs 1				
		2. Current Maintenance and Repair Practices 3				
		3. Predictive Maintenance 5				
	в.	DEVELOPMENT OF VIBRATION ANALYSIS TECHNIQUES				
		FOR RECIPROCATING MACHINES 6				
		1. Current Approach 6				
		2. Proposed Analysis Methods 7				
II.	REC	CIPROCATING MACHINERY ANALYSIS 9				
	A.	DISCUSSION				
	в.	COMPRESSION CYCLE AND MECHANICS OF A				
	RECIPROCATING AIR COMPRESSOR					
		1. Compressor Cycle				
		2. Compressor Timing				
	C.	DATA COLLECTION FOR VIBRATION ANALYSIS 13				
		1. Transducer Placement				
		2. Overview of Reciprocating Vibration				
		Patterns				
III.	TIM	E DOMAIN AND FREQUENCY SPECTRUM REPRESENTATION				
	OF	VIBRATION MEASUREMENT DATA				

	Α.	RECIPROCATING AIR-COMPRESSOR VIBRATION				
		MEASUREMENT DATA				
	в.	DATA ACQUISITION AND PROCESSING				
	C.	TIME DOMAIN AND FREQUENCY SPECTRUM				
		REPRESENTATIONS				
	D.	ARTIFICIAL FAULT SIMULATION 54				
		1. Impulse Disturbance 54				
		2. Transient Vibration Signals 62				
IV.	TIN	E-FREQUENCY DOMAIN REPRESENTATION 68				
	A.	PSEUDO WIGNER-VILLE DISTRIBUTION (PWVD) 68				
		1. History of PWVD				
		2. PWVD of Measured Vibration Data 69				
		3. PWVD of Artificial Fault Simulation 97				
	в.	WAVELET ANALYSIS				
		1. History of Wavelet Analysis 110				
		2. Wavelet Analysis of Artificial Fault				
		Simulation				
v.	CON	CLUSIONS AND RECOMMENDATIONS				
APPEI	NDIX	. MATLAB PROGRAM CODE FOR FFT 116				
LIST	LIST OF REFERENCES					
INIT	INITIAL DISTRIBUTION LIST					

•

v

LIST OF FIGURES

Figure 1:	Breakdown of Machine Data	18
Figure 2:	Vibration Test and Analysis Guide, MID 115	20
Figure 3:	Vibration Test and Analysis Guide, MID 524	22
Figure 4:	MID 115 Vibration Measurement Data	
	Organization	25
Figure 5:	MID 524 Vibration Measurement Data	
	Organization	26
Figure 6:	MID 115 Compressor Component Sampled at	
	750 HZ, Tangential Direction	30
Figure 7:	MID 115 Compressor Component FFT, Sampled	
	at 750HZ, Tangential Direction	31
Figure 8:	MID 115 Compressor Component Sampled at	
	750 HZ, Axial Direction	32
Figure 9:	MID 115 Compressor Component FFT, Sampled	
	at 750HZ, Axial Direction	33
Figure 10:	MID 115 Compressor Component Sampled at	
	750 HZ, Radial Direction	34
Figure 11:	MID 115 Compressor Component FFT, Sampled	
	at 750HZ, Radial Direction	35
Figure 12:	MID 115 Compressor Component Sampled at	
	7500 HZ, Tangential Direction	36
Figure 13:	MID 115 Compressor Component FFT, Sampled	
	at 7500 HZ, Tangential Direction	37

Figure 3	14:	MID 115 Compressor Component Sampled at
		7500 HZ, Axial Direction
Figure 3	15:	MID 115 Compressor Component FFT, Sampled
		at 7500 HZ, Axial Direction
Figure 2	16:	MID 115 Compressor Component Sampled at
		7500 HZ, Radial Direction 40
Figure 2	17:	MID 115 Compressor Component FFT, Sampled
		at 7500 HZ, Radial Direction 41
Figure 1	18:	MID 524 Compressor Component Sampled at
		400 HZ, Tangential Direction 42
Figure 1	19:	MID 524 Compressor Component FFT, Sampled
		at 400 HZ, Tangential Direction 43
Figure 2	20:	MID 524 Compressor Component Sampled at
		400 HZ, Axial Direction
Figure 2	21:	MID 524 Compressor Component FFT, Sampled
		at 400 HZ, Axial Direction 45
Figure 2	22:	MID 524 Compressor Component Sampled at
		400 HZ, Radial Direction 46
Figure 2	23:	MID 524 Compressor Component FFT, Sampled
		at 400 HZ, Radial Direction 47
Figure 2	24:	MID 524 Compressor Component Sampled at
		3950 HZ, Tangential Direction 48
Figure 2	25:	MID 524 Compressor Component FFT, Sampled
		at 3950 HZ, Tangential Direction 49
Figure 2	26:	MID 524 Compressor Component Sampled at
		3950 HZ, Axial Direction 50

Figure	27:	MID 524 Compressor Component FFT, Sampled	
		at 3950 HZ, Axial Direction	51
Figure	28:	MID 524 Compressor Component Sampled at	
		3950 HZ, Radial Direction	52
Figure	29:	MID 524 Compressor Component FFT, Sampled	
		at 3950 HZ, Radial Direction	53
Figure	30:	Artificial Fault Simulation, Tangential	
		Direction	56
Figure	31:	Artificial Fault Simulation FFT, Tangetial	
		Direction	57
Figure	32:	Artificial Fault Simulation, Axial	
		Direction	58
Figure	33:	Artificial Fault Simulation FFT, Axial	
		Direction	59
Figure	34:	Artificial Fault Simulation, Radial	
		Direction	60
Figure	35:	Artificial Fault Simulation FFT, Radial	
		Direction	61
Figure	36:	Typical Transient Vibration, Single Impact	64
Figure	37:	Typical Transient Vibration FFT,	
		Single Impact	65
Figure	38:	Typical Transient Vibration, Dual Impact .	66
Figure	39:	Typical Transient Vibration FFT,	
		Dual Impact	67
Figure	40:	PWVD Results, MID 115 Compressor	
		Sampled at 750 HZ, Tangential Direction	72

- Figure 41: PWVD Contour Map, MID 115 Compressor Sampled at 750 HZ, Tangential Direction . . 73
- Figure 42: PWVD Results, MID 115 Compressor Sampled at 750 HZ, Axial Direction 74
- Figure 43: PWVD Contour Map, MID 115 Compressor Sampled at 750 HZ, Axial Direction 75
- Figure 44: PWVD Results, MID 115 Compressor Sampled at 750 HZ, Radial Direction 76
- Figure 45: PWVD Contour Map, MID 115 Compressor Sampled at 750 HZ, Radial Direction 77
- Figure 46: PWVD Results, MID 115 Compressor Sampled at 7500 HZ, Tangential Direction . 78
- Figure 47: PWVD Contour Map, MID 115 Compressor Sampled at 7500 HZ, Tangential Direction . 79
- Figure 48: PWVD Results, MID 115 Compressor Sampled at 7500 HZ, Axial Direction 80
- Figure 49: PWVD Contour Map, MID 115 Compressor Sampled at 7500 HZ, Axial Direction 81
- Figure 50: PWVD Results, MID 115 Compressor Sampled at 7500 HZ, Radial Direction . . . 82
- Figure 51: PWVD Contour Map, MID 115 Compressor Sampled at 7500 HZ, Radial Direction . . . 83
- Figure 52: PWVD Results, MID 524 Compressor Sampled at 400 HZ, Tangential Direction . . 84
- Figure 53: PWVD Contour Map, MID 524 Compressor Sampled at 400 HZ, Tangential Direction . . 85

ix

Figure 54: PWVD Results, MID 524 Compressor Sampled at 400 HZ, Axial Direction 86 Figure 55: PWVD Contour Map, MID 524 Compressor Sampled at 400 HZ, Axial Direction 87 Figure 56: PWVD Results, MID 524 Compressor Sampled at 400 HZ, Radial Direction . . . 88 Figure 57: PWVD Contour Map, MID 524 Compressor Sampled at 400 HZ, Radial Direction . . . 89 Figure 58: PWVD Results, MID 524 Compressor Sampled at 3950 HZ, Tangential Direction . 90 Figure 59: PWVD Contour Map, MID 524 Compressor Sampled at 3950 HZ, Tangential Direction . 91 Figure 60: PWVD Results, MID 524 Compressor Sampled at 3950 HZ, Axial Direction . . . 92 Figure 61: PWVD Contour Map, MID 524 Compressor Sampled at 3950 HZ, Axial Direction . . . 93 Figure 62: PWVD Results, MID 524 Compressor Sampled at 3950 HZ, Radial Direction . . . 94 Figure 63: PWVD Contour Map, MID 524 Compressor Sampled at 3950 HZ, Radial Direction . . . 95 Figure 64: PWVD Results, Artificial Fault Simulation, Tangential Direction 98 Figure 65: PWVD Contour Map, Artificial Fault Simulation, Tangential Direction 99 Figure 66: PWVD Results, Artificial Fault Simulation, Axial Direction 100

Figure (67:	PWVD Contour Map, Artificial Fault	
		Simulation, Axial Direction	101
Figure 6	68:	PWVD Results, Artificial Fault	
		Simulation, Radial Direction	102
Figure 6	69:	PWVD Contour Map, Artificial Fault	
		Simulation, Radial Direction	103
Figure 7	70:	PWVD Results, Typical Transient	
		Vibration, Single Impact	106
Figure 7	71:	PWVD Contour Map, Typical Transient	
		Vibration, Single Impact	107
Figure 7	72:	PWVD Results, Typical Transient	
		Vibration, Dual Impact	108
Figure 7	73:	PWVD Contour Map, Typical Transient	
		Vibration, Dual Impact	109
Figure 7	74:	Wavelet Transform Results, Artificial	
		Fault Simulation, Tangential Direction .	112
Figure 7	75:	Wavelet Transform Contour Map, Artificial	
		Fault Simulation, Tangential Direction .	113

LIST OF ABBREVIATIONS

	BDC	-	Bottom Dead Center
	DET	-	Detachment
	\mathbf{FFT}	-	Fast Fourier Transform
	HZ	-	Hertz
	MHZ	-	Mega Hertz
	MID	-	Machine Identification Number
	PC	-	Personal Computer
	PERA(CV)	-	Planning and Engineering for Repairs
			and Alterations, aircraft carriers
	PWVD	-	Pseudo Wigner-Ville Distribution
	RMS	-	Root Mean Square
	RPM	-	Revolutions Per Minute
`	TDC	-	Top Dead Center
	VTAG	-	Vibration Testing and Analysis Guide
	WD	_	Wigner Distribution

ACKNOWLEDGEMENT

I would like to express my sincere appreciation to my advisor, Professor Young S. Shin, for his guidance throughout the course of my thesis research. I would also like to thank Dr. Joung J. Kim for his assistance with the computer programs used in this study. Additionally, I would like to thank Mr. Lynn Hampton of NAVSEADET PERA (CV) for providing the machine data.

I dedicate this work to my loving wife Susan, and to my son Steven James.

I. INTRODUCTION

A. GENERAL BACKGROUND

1. Rational For Maintenance and Monitoring Programs

There are many reasons for conducting analysis and assessment of machine operating condition and performance. The principal influence for an organization to accurately assess the operation of its engineering plant is financial. In almost every application, cost is a major driving factor in maintaining equipment in proper operating condition. This practice not only reduces the associated repair time, but ensures optimal performance is achieved. The importance of maintaining equipment at its optimal level is readily apparent in the commercial industry. Costs for equipment operation and repairs are directly linked to a company's profit margin. Simply put, non-operating or poorly operating equipment consume more resources and produce less work. For this reason, many organizations have realized the importance of machinery analysis and some have entire teams dedicated to machine health and condition monitoring.

In military applications where profit margins are not a motivating factor, machinery analysis can still lend itself to the benefit of the organization. This is especially true in surface ship engineering plants [Refs. 1-2]. In the unique application of shipboard engineering plants, there is intense

pressure to ensure machinery and equipment is ready for a particular mission or maneuver, and is available upon demand. Using an aircraft carrier for example, it is readily apparent why there cannot be a delay in response due to equipment malfunction or lack of machine output during aircraft launching or recovering operations. To ensure a prudent response, surface ship engineering plants have designed redundancies. The critical equipment is usually duplicated or has some type of backup system to ensure the required output is continuously delivered.

Because surface ship engineering plants consist of overly redundant systems, optimal performance may not appear to be a worthwhile crusade. As long as a particular system is producing the required output, whether or not it is the most economical or the actual designed output, the demand is being met and therefore it is performing at an acceptable level. The associated input required for this level of operation is seldom a consideration. Machine function is more important then the energy constraints. However, the maintenance time associated with this type of equipment arrangement becomes a significant factor. The duplication and backup of systems increases the number of machinery components requiring support. To assist engineers in the planning, scheduling, and actual performance of maintenance activities for these complex systems, many organizations have adopted varying maintenance practices to manage their engineering plants. Most current

maintenance procedures have fallen under these three types; Preventive Maintenance (also referred to as Planned Maintenance), Casualty Control, and a practice some refer to as Fly to Failure. A brief explanation of each of these practices will be given to emphasize the magnitude of resources, inherent problems, and shortcomings associated with these antiquated practices.

2. Current Maintenance and Repair Practices

In Preventive Maintenance equipment is overhauled based on time (calendar based) and/or usage (operating hours). Plant engineers plan and schedule maintenance regardless of the actual operating condition of the machine. This provides the convenience of predictable logistics support and resource requirements, but it also has many drawbacks. Although this maintenance practices ensures availability, it is very expensive both in actual dollars spent and time available for This practice diverts valuable resources from maintenance. more efficient use, and in today's economic environment, manpower constraints are becoming more strained and less maintenance hours are available. In addition, premature tear downs increase costs and degrade reliability. More often than would be expected, routine open and inspect procedures and unwarranted tear downs result in reassembly problems and failed machinery which had been in good condition prior to undergoing repairs [Ref. 1]. On top of these shortcomings,

many of these same units will have to undergo some type of casualty control measures during operations.

Under Casualty Control procedures, equipment is operated until a fault is detected either by alarm or by decline in performance and then is repaired as required. As long as the equipment is fully functional no other maintenance is performed. It should be noted here that without proper or accurate diagnostics, troubleshooting the fault in the equipment can consume numerous man-hours. Casualty control is usually not used as a primary means to maintain equipment. It is intended for emergency situations to prevent catastrophic failure and degradation of the engineering plant. Mission requirements are usually not severely affected due to the nature of the system design for naval surface ships. However, in the commercial industry where systems may not be as redundant, required output may be severely hampered by the loss of just one piece of gear.

Fly to Failure is probably the least used practice both in commercial industry and in naval surface ship application. Fly to Failure is a concept where equipment is used until complete failure and then replaced. After a faulty condition is first detected, a determination is made as to the significance of the fault and any hazardous conditions that may result by the continued operation of the equipment. Once again without proper and accurate diagnostic procedures any equipment assessment can contain many uncertainties. If a

hazard is determined not to exist to surrounding equipment, personnel, or mission requirements the equipment is allowed to operate until complete failure occurs. In this case equipment is usually monitored but no corrective actions are taken. In some instances naval ships are forced into the fly to failure predicament due to demands on the machinery that are so great as to not allow for proper casualty control.

3. Predictive Maintenance

All of these methods are costly in the realm of manpower, time, and dollar expenditures. With the increasing costs of associated with current maintenance practices and the desire for higher operational availability and extended operating cycles, organizations have sought better ways to manage maintenance requirements. This trend has brought a need to accurately predict and define machinery repairs based on knowledge of system and component performance. One method which provides such information is vibration analysis. Vibration and noise generated by machines is now commonly used to diagnosis machinery conditions, predict failures based on degradation, related and to prevent unexpected wear catastrophic failures [Refs. 1-3]. With accurate assessment of machinery conditions, resources can be more efficiently assigned. In May of 1988 it was published that as many as seven different simultaneous efforts of utilizing vibration measurement and analysis for machinery health determination and maintenance planning existed in the United States surface

Navy program [Ref. 1]. However, a common thread with all of these efforts was the lack of success with the analysis and trending of reciprocating components [Refs. 1-2].

B. DEVELOPMENT OF VIBRATION ANALYSIS TECHNIQUES FOR RECIPROCATING MACHINES

1. Current Approach

Many of the programs developed for surface ships primarily focused the attention on rotating equipment even though reciprocating machinery is a major player in most shipboard engineering plants. Analysis was focused on machine data displayed in the frequency domain. Throughout the commercial industry and specifically in naval surface ship programs, reciprocating machinery has posed additional problems in forming a consensus of opinion as to the validity of applying average data as acceptable criteria [Ref. 1,3]. Averaging data was developed to measure signals in the presence of noise and to measure noise itself. The most common technique used in vibration analysis of machine data is RMS averaging. This averaging technique determines the average magnitude of the signal, ignoring any phase difference that may exist between the spectra. The lack of consensus promoted an unevenness in the analysis of the different types of equipments. Since there was an agreed upon procedure for rotating machinery, that portion of the program marched forward with little consideration for the specific requirements for accurate reciprocating machinery analysis

[Ref. 2]. By approaching the task from one side, analysts developed proven frequency domain techniques for rotating machinery analysis which they then applied to reciprocating machinery. Current shipboard machinery vibration monitoring and diagnostic procedures use this frequency domain spectra to identify possible faults and problem areas.

2. Proposed Analysis Methods

Frequency domain analysis implies that the vibration data is assumed to be stationary and even time independent. This method has proven to be inadequate for reciprocating machinery analysis. In reciprocating machinery the vibration signal is no longer a stationary, ergodic process, but is time-dependent and in some cases transient. These techniques do have value with reciprocating machinery for certain machine components, but they cannot accomplish the total analysis that is required and expected [Ref. 3]. Because of these shortcomings, the surface Navy programs for the analysis of reciprocating machinery have not yielded complete analysis results.

To conduct a total analysis and gain an accurate assessment of the operating condition of a reciprocating machine, advanced analysis techniques need to be employed. Wavelet analysis and Pseudo Wigner-Ville Distribution (PWVD) technique use a time-frequency domain distribution for detection of fault location and severity level and may fill the gap between rotating and reciprocating machinery. By

providing a time-frequency domain distribution the detection of fault locations and severity are based on the signal displacement and timing of the event. Wavelet analysis and PWVD technique are both being explored due to the strong implications that one type of analysis may not cover all possible cases of reciprocation and transient machines. It is proposed that Wavelet analysis will play a complementary role to the PWVD technique.

II. RECIPROCATING MACHINERY ANALYSIS

A. DISCUSSION

To understand how a time-frequency domain distribution analysis can fill the gap between rotating and reciprocation machinery, we must first understand the mechanics of reciprocating machines. The subject of engine vibration can be divided into two categories: vibration of the engine parts relative to each other, called internal vibration, and movement of the engine as a whole, called external vibration [Ref. 4]. With the use of various machinery mounting systems and other isolation techniques, external vibration can be reduced from being a factor in the analysis. That is not to say that external sources will never be a major contributor to machine vibrations, but that external effects will not be studied here. The focus of this investigation has been limited to high-pressure air compressors although it can be equally applied to any reciprocating type machine with few modifications.

As mentioned earlier, there are some benefits of monitoring reciprocating machinery using frequency domain spectra. By viewing the vibration signatures in the frequency domain, information on some of the major components can be gained. The frequency domain should produce indications of crankshaft unbalance, reciprocating unbalance, torsional

unbalance, misalignment, improper gear mesh, and worn or bad bearings. There are other possible components in addition to those listed above that would lend themselves to be analyzed in the frequency domain. The entire frequency span of the machine is related to the rpm of the components. For example, the crankshaft is rotating at a known rpm and establishes the baseline running speed frequency. As the crankshaft makes one revolution, the piston assembly makes two distinct movements. These two distinct movements and the assembly weight is what creates the two times running speed frequency [Ref. 3].

However, reciprocating components such as piston rings, wrist pins, and valves cannot be analyzed in the frequency domain. With frequency domain analysis, the action of these components is lost in noise. In addition, frequencies produced by mechanical faults can not be distinguished from other contributors such as combustion noise, port flow, injection noise and a host of many other factors. The recognition and separation of this noise has left many excellent analysts dismayed [Ref. 3]. For this type of analysis we have to look at timing relationships between mechanical events. Time relates to something that is happening in relationship to the mechanical events or rotational speed or crank-angle position. Knowing how these components act in conjunction with other components of the reciprocating machine, each component frequency can be separated by the use of relative phase comparison measurements

[Ref. 3]. By conducting the analysis in the time-frequency domain, information required to separate component frequencies can be obtained.

B. COMPRESSION CYCLE AND MECHANICS OF A RECIPROCATING AIR COMPRESSOR

1. Compressor Cycle

High pressure air compressors allow mechanical events to be related based on cylinder pressures and crank angle. Just like a two-cycle engine, a compressor repeats its cycle every 360 degrees. Understanding how the cycle of events that happen with a compressor is important in interpreting the data that will be subject to analysis. Simplifying the basic process of a single-stage compressor [Ref. 5], a compressor cycle can be viewed in three steps. Starting in the top dead center (TDC) position where the piston is in the farthest position from the crankshaft, the sequence of events begin. this position the pressure inside the cylinder is In approximately equal to the that of the discharge line. Both the suction valve and discharge valve are closed with the piston in this position.

The second stage of the compressor cycle has the piston assembly drawing back down the cylinder creating a vacuum in the cylinder. The suction valve opens at this point and with the negative pressure gradient between the cylinder and the suction line, gas or air enters the cylinder. Theoretically once the piston reaches bottom dead center (BDC)

the pressure inside the cylinder is the same as that of the suction line and spring action allows the suction valve to close. The piston assembly now begins its movement up or towards TDC starting the final stage of the compressor cycle.

In the final stage of the compressor cycle pressure inside the cylinder increases with the upward movement of the piston assembly and creates a positive pressure gradient between the cylinder and the discharge line. Once the pressure inside the cylinder becomes great enough to overcome the spring tension of the discharge valve, the discharge valve opens and the volume of gas displaces to the discharge line. The displacement of the gas inside the cylinder decreases the pressure required to hold the discharge valve open causing the valve to close. From this point the cycle repeats itself.

2. Compressor Timing

The knowledge of what takes place during the compressor cycle is only a small portion of the information that is needed to establish a relationship between mechanical events. In order to accurately assess the reciprocating components, the compression stage for the cylinder of interest in relation to the vibration signatures taken at a specific point in time in relation to rotational speed must be established. This can be determine based on crank-angle and Piston position can be obtained by knowing crankshaft rpm. the displaced cylinder volume. To calculate displaced cylinder volume, the ratio of the length of the piston

connecting rod and the radius of the circle created by the crank shaft throw to the connecting rod is required [Ref. 5]. Each major timing event within the cylinder is also required. As an example, we need to know when each valve opens and closes in relation to TDC. Obviously for multi-cylinder compressors we would need this information for each cylinder. The compressor manufacturer can provide this information along with other important machine data such as bore, stroke, suction/discharge pressures, cylinder clearance, and rod loading that will be required to conduct a thorough analysis. This study will not discuss all of the analysis required for a complete assessment of a high-pressure air compressor. At this point, identifying frequency components to mechanical events and their relationship in the time-frequency domain is of interest.

C. DATA COLLECTION FOR VIBRATION ANALYSIS

1. Transducer Placement

Understanding what causes specific events to create vibrations at different frequencies, as well as knowing where they should occur in the time trace relative to the crankangle degree, enables one to pinpoint, predict and trend reciprocating machinery. By knowing the crankshaft rpm, crank-angle and cylinder events can easily be converted to time. In order to gather this information it is important that the analysis equipment is setup correctly. Repeatability is extremely important. Since frequency responses of mechanical events of individual cylinders is of interest, placement of the vibration transducers is a governing element. To gather vibration information for the reciprocating components, the transducer should be moved around the cylinder frame to allow the analyst the opportunity to observe the highest response area for different mechanical problems [Ref. 3]. Vibration signals for the rotating components are taken in the same manner as rotating machine analysis - in the axial, tangential, and radial directions of the compressor crankshaft and the drive shaft of the powering unit.

2. Overview of Reciprocating Vibration Patterns

Reciprocating components create distinct vibration patterns which allow them to be separated from machine noise. Looking at each cylinder, vibration signals created by worn valves, atypical valve opening and closing events, worn piston rings, cylinder scoring, and mechanical knocking can be seen. Mechanically driven vibrations such as wrist pin looseness, or piston slap, or even the valve events themselves usually create low frequency vibration. However, there are some mechanical events that create high frequency signals. Examples of a mechanical high frequency might be a scored cylinder liner or rings rubbing along the cylinder walls or through the port area [Ref. 3]. The intensity of a fault condition will determine the amplitude of the vibration pattern. The duration of the vibration signal created by a

fault condition will assist in determining its cause. A timefrequency representation will allow both elements of the data to be displayed simultaneously for accurate assessment of the compressor's operating condition.

There are three basic types of noise that will represent different actions within the cylinder; friction, mechanical knocks, and gas blow. Friction creates high frequency wave forms that are long in duration but in reciprocating machines may not be time-independent. Sharp mechanical impacts create wave forms that will always be timedependent and in some cases transient. As an example, a valve opening event will appear as an impact as the valve opens fully or to the maximum of the stroke. Loose bearings will also create an impact knock at the time of pressure reversal, and when rings go through the port opening or a step in the cylinder wall, a very fast clip or knock will take place. In the case of multiple knocks spaced closely together, the faults may be spring bounce or many rings hitting the same fault as they go by it. Gas blow or vacuum leak patterns are caused by events which increase the velocity of gases or air going over a very small area. Examples that could create this type of pattern include; leaking head gasket, blow-by, and valve opening/closing events. Knowing where the action occurs relationship to the crank-angle degree is key to in interpretation. Again, amplitude of the vibration pattern will depend on the severity of the event.

Once the fault condition can be located, assessed, and diagnosed, the root cause(s) can be traced back and determined. Common problems with valves range from a slight leak to the loss of the valve plate. Valve failure can be caused from wear, impacting, corrosion, or a combination of the three. Valve component wear is often caused by the introduction of foreign materials, incorrect design or modification, or incorrect lubrication. Impacting of the valve plates, seats, and guards may be caused from weak or broken springs as well as excessively strong springs. Piston problems can be caused by incorrect assembly, incorrect machining, improper positioning, as well as broken or leaking rings. Cylinder problems usually result from boring or resizing the cylinder cavity. Detection of inadequate repair and modification type problems can usually be verified by checking the compressor repair history. Regardless of the cause, time-frequency domain analysis will assist in troubleshooting the equipment and expedite the required repairs. The long term benefits of this advance analysis techniques may even be to correct flawed maintenance practices and procedures.

III. TIME DOMAIN AND FREQUENCY SPECTRUM REPRESENTATION OF VIBRATION MEASUREMENT DATA

A. RECIPROCATING AIR-COMPRESSOR VIBRATION MEASUREMENT DATA

Machine data was received from NAVSEA DET PERA(CV) (Planning and Engineering for Repairs and Alterations, aircraft carriers) for two different high-pressure air compressors [Ref. 6]. Each compressor was designated by an assigned Machine Identification (MID) number. The five stage reciprocating high-pressure air compressor was designated MID 115. The six stage reciprocating high-pressure air compressor was designated MID 524. Included in the machine data was a six channel recording of analog vibration measurements, and a Testing and Analysis Guide for each Vibration (VTAG) contained The recorded tape log compressor type. approximately twenty seconds of vibration measurement signals for each data set. Figure 1 shows the breakdown of the machine data that was analyzed during this study. As shown in figure, three recordings were selected for this each compressor type. The recordings captured tri-directional vibration measurement signals for the driving unit (motor) and tri-directional vibration measurement signals for the driven unit (compressor). Each recording was then analyzed at two sampling frequency levels to ensure a broad bandwidth of the vibration measurements was captured.



FIGURE 1: Breakdown of Machine Data

The transducers used to measure the vibration levels were positioned on the free end of the motor and on the free end of the compressor for the MID 115 type high-pressure air compressor. For the MID 524 type compressor the transducers were position on the coupling end of the motor and on the free end of the compressor. The transducers were oriented in the traditional axial, tangential, and radial directions that is common place in rotating machinery analysis. Unfortunately vibration data was not captured for individual cylinder actions as previously discussed in Chapter II. Figures 2 and 3 are the VTAGs for the MID 115 type compressor and MID 524 type compressor respectively. The VTAGs clearly show the different compressor and motor arrangements and the transducer placements for the two reciprocating machines.



FIGURE 2: Vibration Test and Analysis Guide, MID 115 page 1 of 2

-



"AIRCRAFT CARRIER MACHINERY VIBRATION TEST & ANALYSIS GUIDE" PERA (CV) PUB 1822-207

FIGURE 2: Vibration Test and Analysis Guide, MID 115 page 2 of 2



,

FIGURE 3: Vibration Test and Analysis Guide, MID 524 page 1 of 2


"AIRCRAFT CARRIER MACHINERY VIBRATION TEST & ANALYSIS GUIDE" PERA (CV) PUB 1822-207

FIGURE 3: Vibration Test and Analysis Guide, MID 524 page 2 of 2

B. DATA ACQUISITION AND PROCESSING

Each vibration measurement recording selected for the two compressors was first analyzed in the time domain and then in the frequency domain (spectrum) using a 486-50MHZ personal computer. EASYEST[™] LX software, developed by Keithley Asyst, was used to convert the analog data from the tape log to digital format. This PC-based data acquisition system digitized the analog signal, converted the units from voltage to velocity, and finally stored the velocity data sequences in ASCII form into the hard disk of the personal computer. The data was filed separately based on MID number, recording number, sampling frequency, machine component (motor or compressor), and sampling direction (tangential, axial, or radial). The digitized data was comprised of 2048 data points. Figures 4 and 5 depict how the vibration measurement data was broken down and stored into the various files. Although the figures show only one machine record for each compressor type, the same format was utilized for each recorded vibration measurement data set.



FIGURE 4: MID 115 Vibration Measurement Data Organization 25



FIGURE 5: MID 524 Vibration Measurement Data Organization 26

the Sampling frequencies selected based were on information provided in the VTAGs for each machine. In order to prevent aliasing, five times the analysis range for the machine frequencies was used as the sampling frequencies during the data acquisition process. For the MID 115 type compressor sampling frequencies of 750HZ (5 X 150HZ) for the low end and 7500HZ (5 X 1500HZ) for the high end were used. The MID 524 type compressor had a much lower analysis range. Thus frequencies of 400HZ (5 X 80HZ) and 3950HZ (5 X 790HZ) the low and high sampling frequencies were used for respectively.

The data was then loaded into the MATLAB[®] software environment to display the time domain information and to transform that information to display the frequency spectrum. Using the data obtained from the analog tape through EASYESTTM LX, time domain representations of the vibration signals were then plotted from the MATLAB[®] environment via a Hewlett-Packard Laserjet 4 printer. The Fast Fourier Transform (FFT) was calculated by using a program written using MATLAB[®] to obtain the frequency domain representation. The program code for the FFT can be found in the Appendix.

The Graphical representations for the time domain and the spectrum of the measured vibration signals were compared for each machine type to establish general machine trending. For example, two vibration records for the MID 115 type compressor were compared at both low and high sampling frequency in each

sampling direction against each other. Signal sampling directions (i.e. tangential, axial, and radial) were established in the tape log provided by PERA(CV). It was felt that by comparing time and frequency domain representations of the vibration measurements the transducer orientation and locations could be verified. As previously established, reciprocating machine vibration signals are time dependent thus no two signals were identical. However, signal trends could be mapped to correlate data between like machines for different sampling periods. After mapping like graphical displays, no conclusive evidence was found to discount the information provided in the tape log. The transducer pick-up directions were assumed to be correct and general vibration trends for the two types of compressor units were able to be established.

C. TIME DOMAIN AND FREQUENCY SPECTRUM REPRESENTATIONS

Figures 6 through 11 show the time domain and spectrum for a MID 115 type compressor taken on the compressor component of the unit at the established low sampling frequency. The figures are arranged in a sequence to allow the time domain be viewed first followed representation to by the corresponding frequency spectrum. The first pair of figures show the data collected in the tangential direction. The next pair of figures display the data in the axial direction with the data collected in the radial direction immediately Figures 12 through 17 show the same vibration following. measurement signals but at the established high sampling frequency. These figures are also presented in the same sequence as established above. Although the tape log provided a continuous record from the compressor and motor components of the high-pressure air compressor units during the period data was collected, the process to convert the vibration measurement signals from analog to digital format created discontinuities in the actual time periods displayed in the figures. A direct comparison between the time periods of the vibration measurement signals captured at different sampling frequencies cannot be made. The signals in this case have been shifted by a finite time differential between the low sampling frequency data and the high sampling frequency data. Figures 18 through 29 apply to a MID 524 type compressor.

Number of Sampling Data Points = 2048

Mean Value = -0.0122

Standard Deviation = 0.1108



REC17CT7.ASC







Number of Sampling Data Points = 2048

Mean Value = -0.0577

Standard Deviation = 0.1083











33[,]

Number of Sampling Data Points = 2048

Mean Value = -0.0420

Standard Deviation = 0.1641



FIGURE 10: MID 115 Compressor Component Sampled at 750 HZ Radial Direction





Number of Sampling Data Points = 2048

Mean Value = -0.0174

Standard Deviation = 0.1159



REC17CT8.ASC

FIGURE 12: MID 115 Compressor Component Sampled at 7500 HZ Tangential Direction





Number of Sampling Data Points = 2048

Mean Value = -0.0608

Standard Deviation = 0.1127



REC17CA8.ASC

FIGURE 14: MID 115 Compressor Component Sampled at 7500 HZ Axial Direction





Number of Sampling Data Points = 2048

Mean Value = -0.0445

Standard Deviation = 0.1653



FIGURE 16: MID 115 Compressor Component Sampled at 7500 HZ Radial Direction





41[.]

Number of Sampling Data Points = 2048

Mean Value = -0.0151

Standard Deviation = 0.0810



REC27CT7.ASC

FIGURE 18: MID 524 Compressor Component Sampled at 400 HZ Tangential Direction





Number of Sampling Data Points = 2048

Mean Value = -0.0125

Standard Deviation = 0.0753



REC27CA7.ASC

FIGURE 20: MID 524 Compressor Component Sampled at 400 HZ Axial Direction



Sampled at 400 HZ, Axial Direction

Number of Sampling Data Points = 2048

Mean Value = -0.0130

Standard Deviation = 0.0721



REC27CR7.ASC







Number of Sampling Data Points = 2048

Mean Value = -0.0171

Standard Deviation = 0.0811



REC27CT8.ASC

FIGURE 24: MID 524 Compressor Component Sampled at 3950 HZ Tangential Direction





Number of Sampling Data Points = 2048

Mean Value = -0.0102

Standard Deviation = 0.0696



REC27CA8.ASC

FIGURE 26: MID 524 Compressor Component Sampled at 3950 HZ Axial Direction





Number of Sampling Data Points = 2048

Mean Value = -0.0167

Standard Deviation = 0.0706



REC27CR8.ASC

FIGURE 28: MID 524 Compressor Component Sampled at 3950 HZ Radial Direction





To include the complete set of vibration measurement signals for all of the high-pressure air compressors considered in this study would be a tedious exercise. For clarity, only one set of vibration measurement signals for each machine type was chosen to be displayed in the body of the text. The vibration measurement signals for compressor units of the same MID number were all found to be similar in appearance. These similarities may be coincidental for the small sampling of data considered here, and may not be the general case for all compressor units. In addition, after reviewing all of the data collected and analyzed in the time domain and frequency spectrum, none of the compressor units displayed any alarming vibration patterns.

D. ARTIFICIAL FAULT SIMULATION

1. Impulse Disturbance

To create deformities in the basic waveform patterns of the vibration measurement signals an artificial fault signal was introduced. This signal was created in **MATLAB**[•] to correspond to the sampling size of the machine data and not to the major timing events of the compressor units. Due to the dynamic nature of the data processing using **EASYEST[™] LX**, the start and stop points of the waveform could not be adequately controlled for the infinitesimal portion of the overall signal that was acquired. In addition, because the vibration measurement data was captured using traditional rotating

machine analysis techniques, the major timing events and crank-angle position were never established. These shortcomings prevented an artificial fault signal that would represent poor operating conditions of a particular compressor mechanical component, such as a loose cylinder wrist pin, to be incorporated into the measured data. The fault signals that were introduced to the measured vibration data were made up of a series of instantaneous impulses (spikes) of constant amplitude at equidistant spacing along the time axis. These simple fault signals were created to correspond to the signal time span of the high sampling frequency data for the MID 115 type compressor unit. Figures 30 through 35 show the artificial fault signal added to the vibration measurement signals for a MID 115 type compressor component (time domain followed by the corresponding frequency spectrum in the tangential, axial, and radial directions). Both time domain and frequency spectrum are presented to display the semiarbitrary disruption to the vibration patterns of the compressor component. As can be seen in the appropriate figures, the fault signal appears as a spikes in the timedomain. In the frequency spectrum, the appearance of the fault signal is more readily noticed in the area of higher frequencies. As will be shown shortly, the true influence of the artificial fault signal will be more obvious when the manipulated vibration data is viewed in the time-frequency domain.

ARTIFICIAL FAULT SIMULATION

Number of Sampling Data Points = 2048

Mean Value = -0.0160

Standard Deviation = 0.1181



R17CT8F.ASC

FIGURE 30: Artificial Fault Simulation Tangential Direction





ARTIFICIAL FAULT SIMULATION

Number of Sampling Data Points = 2048

Mean Value = -0.0595

Standard Deviation = 0.1153



R17CA8F.ASC

FIGURE 32: Artificial Fault Simulation Axial Direction




ARTIFICIAL FAULT SIMULATION

Number of Sampling Data Points = 2048

Mean Value = -0.0431

Standard Deviation = 0.1677



FIGURE 34: Artificial Fault Simulation Radial Direction



FIGURE 35: Artificial Fault Simulation FFT Radial Direction

2. Transient Vibration Signals

addition to demonstrating the effects of In an simulated fault signal, transient signals were created and analyzed separately. A complete analysis of a reciprocating machine would not only produce time-dependent data, but in some cases the vibration data may also include transient vibration patterns. Vibration data collected around the cylinder frame of the compressor component would definitely display this type of transient signature. Unfortunately, the vibration measurement data analyzed in this study were absent the true effects of transient signals created by certain reciprocating components. Non-machine data was created in order to explore the transient phenomenon associated with reciprocating machines.

To create the transient signals, a thin aluminum plate, fully supported on one end and free hanging on the other, was struck with a sharp impacting motion. For the first data sample, a single impact event was imparted on the plate. The free vibration of the plate was recorded by using an accelerometer attached at the free end. A Hewlett-Packard 3562A Dynamic Signal Analyzer in conjunction with a personal computer captured, recorded, and converted the vibration signal to ASCII format. Once the signal was in ASCII form, the same analysis procedures used for the measured machine data was conducted. Figure 36 is the time domain

representation of a single impact event. Figure 37 is the corresponding frequency spectrum.

A second data sample was captured in similar fashion. However, for this data sample two impact events were conducted to demonstrate the effects of two nearly simultaneous transient events. Figures 38 and 39 display the time domain and frequency spectrum respectively.

TYPICAL TRANSIENT VIBRATION



FIGURE 36: Typical Transient Vibration Single Impact

•

,





TYPICAL TRANSIENT VIBRATION



DUAL IMPACT EVENT





IV. TIME-FREQUENCY DOMAIN REPRESENTATION

A. PSEUDO WIGNER-VILLE DISTRIBUTION (PWVD)

1. History of Pseudo Wigner-Ville Distribution

The primary advanced analysis technique considered in this study was the Pseudo Wigner-Ville Distribution (PWVD). PWVD is a three-dimensional (time, frequency, and amplitude) representation of an input signal and is particularly well suited for the analysis of transient and other non-stationary vibration signals. The capability of PWVD to evaluate the input data in three dimensions makes it a logical choice as an appropriate medium for the analysis of reciprocating machine vibration data. The application of PWVD analysis techniques for machinery condition monitoring and diagnostics is not a novel concept. The PWVD has been proposed in the past for use in machinery condition monitoring and diagnostics by Flandrin et. al. [Ref.7] and in gear fault detection by Forrester [Ref.8].

PWVD has a long history in its development for use in vibration signal analysis. Eugene Wigner [Ref.9] first introduced the Wigner distribution in 1932 to study the problem of statistical equilibrium in the area of quantum mechanics. His work was furthered in 1948 by J. Ville [Ref.10], who used the Wigner distribution in the area of harmonic signal analysis. Claasen and Mecklenbrauker [Refs.

11, 12, and 13] paved the way for many recent applications of the PWVD. Their three part paper is an all encompassing work that has served to highlight the capabilities of the Wigner Distribution (WD) and allow for greater knowledge of the subject with an emphasis on signal processing and analysis. Claasen and Mecklenbrauker described the application of a sliding window in the time domain while calculating the WD producing a smoothed version with respect to frequency. The WD obtained with a window function is called the pseudo WD. Transposing this terminology, PWVD is the application of a smoothing window to the results of a Wigner-Ville distribution [Ref.14]. The derivation of the PWVD equations and processes will not be presented in this paper. The development of the PWVD has been covered extensively in the sighted references. The purpose of this paper is to demonstrate what can be gained from a time-frequency domain analysis of reciprocating machines.

2. PWVD of Measured Vibration Data

To conduct the PWVD analysis of the reciprocating machine data presented in this study, a computer program developed by Jeon and Shin [Ref.14] was used to perform the required calculations. For each run of the PWVD program the option to remove the mean value was selected. The reduction size was selected as 128 by 128, and a square smoothing window of 26 by 26 was established to correspond to the number of

data points. The smoothed results were plotted using **CA**-**DISSPLA®**, release 11.0 by Computer Associates International, INC.

A 486-50MHZ personal computer in conjunction with a laser printer was used for all data processing. One of the main objectives of this study was to demonstrate that reciprocating machinery analysis can be conducted with minimal investment in any specialized analysis equipment beyond what is required to actually capture the vibration signals. Approximately twenty minutes of computation time was expended for each PWVD calculation for the digitized input signals comprised of 2048 data points. Another twenty minutes was required to output the PWVD results for both the threedimensional display and contour map. A total of eight hours were exhausted to calculate the PWVD and output a complete set of figures for the twelve data sets of each compressor unit. A Hewlett-Packard Series 700 workstation was used in the latter stages of this study to expedite calculations and graphic outputs.

After viewing all of the vibration measurement signals from the selected compressor units, two recordings for each compressor type were selected for PWVD analysis. Once again, only one set of data for each compressor type will be presented in the body of the text for clarity. Figures 40 through 51 apply to a MID 115 type compressor unit. The figures are presented in the same directional sequence

(tangential followed by axial then radial directions), and sampling frequencies (low sampling frequency followed by the high sampling frequency) as the time domain and spectrum representations in Chapter III. The figures are arranged in pairs to allow the PWVD results in three-dimensional; time, frequency, and amplitude orientation to be viewed first followed by the two-dimensional; time and frequency contour map. Figures 52 through 63 display the PWVD results for the input data taken from a MID 524 type compressor unit.







FIGURE 41: PWVD Contour Map, MID 115 Compressor Sampled at 750 HZ, Tangential Direction

Frequency (Hz)



FIGURE 42: PWVD Results, MID 115 Compressor Sampled at 750 HZ, Axial Direction



FIGURE 43: PWVD Contour Map, MID 115 Compressor Sampled at 750 HZ, Axial Direction

Frequency (Hz)



FIGURE 44: PWVD Results, MID 115 Compressor Sampled at 750 HZ, Radial Direction



FIGURE 45: PWVD Contour Map, MID 115 Compressor Sampled at 750 HZ, Radial Direction

Frequency (Hz)



FIGURE 46: PWVD Results, MID 115 Compressor Sampled at 7500 HZ, Tangential Direction





Frequency (Hz)



FIGURE 48: PWVD Results, MID 115 Compressor Sampled at 7500 HZ, Axial Direction







FIGURE 50: PWVD Results, MID 115 Compressor Sampled at 7500 HZ, Radial Direction







FIGURE 52: PWVD Results, MID 524 Compressor Sampled at 400 HZ, Tangential Direction















FIGURE 56: PWVD Results, MID 524 Compressor Sampled at 400 HZ, Radial Direction



FIGURE 57: PWVD Contour Map, MID 524 Compressor Sampled at 400 HZ, Radial Direction

Frequency (Hz)



FIGURE 58: PWVD Results, MID 524 Compressor Sampled at 3950 HZ, Tangential Direction







FIGURE 60: PWVD Results, MID 524 Compressor Sampled at 3950 HZ, Axial Direction



FIGURE 61: PWVD Contour Map, MID 524 Compressor Sampled at 3950 HZ, Axial Direction



FIGURE 62: PWVD Results, MID 524 Compressor Sampled at 3950 HZ, Radial Direction


FIGURE 63: PWVD Contour Map, MID 524 Compressor Sampled at 3950 HZ, Radial Direction

Analyzing the graphical output from the PWVD results, the particularities of each compressor unit is readily apparent. The PWVD results of the measured vibration data clearly display the harmonic nature of the compressor assemblies. The harmonics of the compressor assemblies are denoted by the narrow-band frequency levels lasting the duration of the signal time span. Although harmonic information can be detected in spectral analysis, the PWVD results include the additional information of signal duration. The time aspect of the signal is what clearly denotes it as a harmonic of the compressor unit. The dominant harmonic response common to all of the figures results from the baseline running speed frequency of the compressor unit. The second and higher harmonic responses result from different mechanical events and components.

Statistical analysis can be used to examine any distributions and peak amplitude levels of the harmonic Amplitude probability criterion method is a responses. sophisticated analysis tool which uses either peak-to-peak, peak, or RMS readings of displacement, velocity, or acceleration. This method is currently employed in some vibration analysis programs to decipher the vibration data under spectral analysis. However, in spectral analysis such characterization for reciprocating machinery is not completely satisfactory for two reasons. First, there may exist an abnormal situation for which no time or frequency signature is

clearly apparent. Secondly, if the abnormal situation is apparent, there is generally not enough information to pinpoint the cause and thus achieve diagnosis [Ref.7]. Since time events and frequency are simultaneously relevant, the three-dimensional display from the PWVD results is a natural choice. The severity of the fault would directly effect the amplitude level of the PWVD results. Of course, in order to discriminate between a normal situation and a defective one, baseline vibration data would be required. Alarm levels could then be established based on the mean of the signal plus a set standard deviation.

3. PWVD of Artificial Fault Simulation

PWVD analysis was also conducted on the manipulated data from a MID 115 type compressor component to display the effects of glitches in otherwise harmonic vibration patterns. Recall from Chapter III, a fault signal in the form of impulse disturbances was added to the measured vibration data. The fault signal was comprised of a series of instantaneous impulses of constant amplitude at equidistant spacing along the time axis. To correspond to the sampling size of the machine data, a total of seven spikes were added to the measured data. Figures 64 through 69 display the PWVD results. These figures are arranged in the same fashion at the previous PWVD results.

PSEUDO WIGNER-VILLE DISTRIBUTION



FIGURE 64: PWVD Results, Artificial Fault Simulation Tangential Direction



FIGURE 65: PWVD Contour Map, Artificial Fault Simulation Tangential Direction

PSEUDO WIGNER-VILLE DISTRIBUTION



FIGURE 66: PWVD Results, Artificial Fault Simulation Axial Direction





PSEUDO WIGNER-VILLE DISTRIBUTION



FIGURE 68: PWVD Results, Artificial Fault Simulation Radial Direction





These figures clearly depict the glitches appear as time-dependent disruptions, perpendicular to the harmonic vibration patterns of the measured data. The time component (location), and frequency range of each impulse is accurately established in the PWVD results. This trait is paramount in the assessment of machinery condition. By viewing time and frequency responses simultaneously provides diagnostic information not readily apparent in either the time-domain or frequency spectrum representations when viewed separately. In two-dimensional time-domain analysis the location of each impulse event may not be as easily detected. For example, the location of the impulse events were especially obscured when viewed in the tangential direction. In addition, actual machine faults may contain a wide range of frequencies. The glitches introduced into the machine data to simulate faulty conditions for this demonstration encompassed all frequency levels in the range of analysis. In the frequency spectrum representations the impulse events are almost elusive. As noted earlier, the disruptions to the normal patterns are only slightly visible in the higher frequency levels. From the PWVD results, the disruptions are clearly shown to span the entire frequency range considered in the analysis.

As mentioned in the previous chapter, the vibration data for the two compressor types was captured using traditional rotating analysis techniques. This limitation precluded the demonstration of transient vibration patterns in

actual reciprocating machine vibration data. To demonstrate the benefits of a time-frequency domain analysis, the transient vibration signals from the free vibration of the thin aluminum plate were inputted into the PWVD program. Figure 70 displays the PWVD results for the single impact event with Figure 71 being the corresponding contour map. Figures 72 and 73 display the PWVD results for the two almost simultaneous impacts. Comparing these figures to their respective time-domain and frequency spectrum representations, the benefits of the combined time-frequency analysis is evident. The PWVD results clearly display the time-dependency and major frequency components of the transient vibration signals.

PSEUDO WIGNER-VILLE DISTRIBUTION



FIGURE 70: PWVD Results, Typical Transient Vibration Single Impact





PSEUDO WIGNER-VILLE DISTRIBUTION



FIGURE 72: PWVD Results, Typical Transient Vibration Dual Impact





B. WAVELET ANALYSIS

1. History of Wavelet Analysis

Wavelet analysis was considered as a complimentary technique to the time-frequency domain analysis provide by PWVD. Wavelet transform is ideally suited for detecting small disturbances in wide-band transient or non-stationary vibration signals in the time-frequency domain. Although the disturbances in the harmonic waveforms created by the impulse events were visible in the PWVD results, it is proposed that further analysis of the disruptive events could be conducted with Wavelet analysis. It should be noted that a full explanation of wavelet transforms will not be presented here. The purpose of introducing Wavelet analysis in this study is to further develop the foundation for the application of timefrequency domain analysis for reciprocating machines. Wavelet analysis provides the possible expansion from analysis and condition monitoring to diagnostics.

When compared with PWVD analysis, the use of wavelet transform in vibration analysis is relatively new. Newland [Ref.15] investigated the properties and application of wavelet transform to vibration analysis. Wang and McFadden [Ref.16] demonstrated how wavelet transform may be applied to the analysis of the vibration signals produced by the meshing of a gear. The premise of this previous research was based on the ability of the wavelet transform to easily characterize the local regularity of a function. Simply by a change of the scale parameter (dilation) in the wavelet transform, many scales of local structure can be described by a distribution in the time-scale plane [Ref.17]. The simultaneous display of both large and small scale features enables the detection of both distributed and local faults.

2. Wavelet Analysis of Artificial Fault Simulation

To provide a brief demonstration on the effectiveness of Wavelet analysis, wavelet transform was conducted on the vibration data taken from a MID 115 type compressor component in the tangential direction with the added effects of the impulse disturbances. Figures 74 and 75 display the wavelet transform results in the three dimensional; time, frequency, amplitude orientation, and in the two dimensional; time and frequency contour map respectively. These figures demonstrate the effectiveness of wavelet transforms to characterize the local regularity of the vibration data as well as amplify the influence of the constructed fault signal. The impulse disturbances have a dramatic effect in the upper frequency range of the input data where the harmonic responses are not as dominant. This feature of wavelet transform provides a great advantage for analysis of vibration data containing small disturbances. Also, wavelet transform sweeps along the frequency line in octaves which makes it more effective for the analysis of an input signal with a lengthy time record A 1/1 octave sweep step was selected for the [Ref.17]. displayed wavelet transform results.



WAVELET TRANSFORMATION CONTOUR





V. CONCLUSIONS AND RECOMMENDATIONS

Pseudo Wigner-Ville Distribution and wavelet transform provide two advanced analysis techniques for condition monitoring of non-stationary and transient machines. The inadequacy of pure time domain analysis or spectral analysis to provide a total assessment of reciprocating type machinery demands that new analysis techniques be employed. The logical progression would be to view time and frequency responses simultaneously. Time-frequency domain distribution allows for the detection of fault location as well as severity level. The three dimensional results from PWVD and wavelet transforms are two opportunities to fill the gap resulting from rotating machinery programs, and provide for better condition monitoring and diagnostics of reciprocating type machines.

The use of a personal computer for the data reduction demonstrates the versatility of the PWVD technique. Although the time demands for a complete analysis using PWVD technique may be consuming, the PWVD results provide a complete representation of the harmonic nature of the compressor component. In addition, the simulated fault signal was clearly depicted in the graphical output. Alarm levels to indicate a change in the mechanical condition of the machine could be established by conducting PWVD analysis on a routine schedule.

The brief introduction of Wavelet analysis was present to demonstrate that even the smallest disturbances in the vibration patterns could be characterized in the timefrequency domain. Wavelet transform requires very short computation time, but it does not describe the magnitude of the main frequency components well. This was the primary reason why Wavelet analysis was presented as a complementary analysis method to the PWVD technique.

Based on the information presented in this study, the following recommendations are made:

a. Obtain vibration measurement data from reciprocating compressors around the cylinder frame to capture the nonstationary and transient vibration patterns of the reciprocating components. For other types of reciprocating machinery, the transducer should be moved around the reciprocating components of the machine to observe the highest response area(s).

b. Record crank-angle position along with vibration data to establish machine timing. Obtain crankshaft RPM and timing of mechanical events to establish a relationship between mechanical events and vibration patterns.

c. Obtain manufacturer data to conduct a thorough analysis of the operating condition of the machine. Establish optimal pressures, loading, horse-power, etc.

d. Based on time-frequency domain analysis, develop diagnostic methods and establish alarm levels.

APPENDIX: MATLAB PROGRAM CODE FOR FFT CALCULATION

```
function [Ya,fx] = fftcalc(y,t,nblock,itext)
℅
જ
   This function returns the averaged fft results and
જ
   plots the frequency spectrum
8
g
   INPUTS:
જ
                 : Acceleration vector (calibrated)
          У
8
                 : time vector
          t
웅
          nblock : number of data block
જ
8
   OUTPUTS:
8
          Ya
                 : average fft vector of y
ષ્ટ
          fx
                 : frequecy vector
8
જ
   Developed by: Liu, Chao-Shih 10/15/93
8
   Revised by: John Harding
                                  08/94
જ
   dt = t(2) - t(1); % establish time step
                % establish sampling frequency
  fs = 1/dt;
  gref = 1e-6; % establish scaling factor
ષ્ટ
% Standardized The Size of "y"
  y = y(:); t = t(:);
  ny = length(y);
  my = mean(y);
  stdy = std(y);
ક્ર
% Compute The Averaged FFT Data
  n = ny/nblock; % number of data points/block
  n2 = n/2;
  n1 = 1;
ዮ
  Y = zeros(n,nblock);
                         % establish matrix dimensions
  for nb = 1:nblock
     nh = nb*n;
     Y(1:n,nb) = abs(fft(w.*y(n1:nh)));
     n1 = nh + 1;
  end
z
  if nblock~=1
     Y = sqrt(sum((Y').^2));
  end
ષ્ટ
  Ya = Y*dt;
  Ya(1) = 0; % remove DC component
```

```
웅
   f = fs/2*(0:n2)/n2;
  Ya(n2+2:n) = [];
  fx = f(1:n2+1);
  df = fx(2) - fx(1);
8
  Ya = 20*log10(Ya/gref); % Gdb transformation:
8
% Plot Frequency Domain:
  figure(1); clf;
plot(fx,Ya,'r');
  upper = (ceil(max(Ya)/10)+1)*10;
  if upper < 60
      lower = 0;
   else
      lower = 20;
  end
8
  axis([0 max(fx) lower 120]);
  title(itext);
  xlabel('Frequency (Hz)')
ylabel('Acceleration in Gdb')
8
% Print FFT Results
  set(1, 'PaperPosition',[0.25 1 8 9.25]);
  print
```

LIST OF REFERENCES

- Marshall, B. R., "A Surface Navy Vibration Program Overview: Standardization and State-of-the-Art", Naval Engineers Journal, Vol. 100, May 1988, pp. 90-100.
- 2. Chapman, C. L., and Jolley, R., "Systems and Equipment Maintenance Monitoring for Surface Ships (SEMMSS) Program", Naval Engineers Journal, Vol. 99, November 1987, pp. 63-69.
- 3. Update International, Inc., "A Practical Approach to Reciprocating Machinery Analysis".
- Taylor, C. F., "The Internal-Combustion Engine in Theory and Practice, Volume II: Combustion, Fuels, Materials, Design, Revised Edition", The M.I.T. Press, 1985, Chapter 8.
- Compressed Air and Gas Institute, "Compressed Air and Gas Handbook, Fourth Edition", 1973, Chapter 2.
- Reciprocating Machinery Vibration Data, NAVSEA DET PERA(CV), January, 1994.

- 7. Flandrin, P., Garreau, D., and Puyal, C., "Improving Monitoring of PWR Electrical Power Plants 'In Core' Instrumentation with Time-Frequency Signal Analysis", IEEE International Conference on Acoustics, Speech, and Signal Processing, vol. 4, pp. 2246-2249, May 1989.
- Forrester, B., "Analysis of Gear Vibration in the Time-Frequency Domain", Proceedings of the 44th Meeting of the Mechanical Failures Prevention Group, pp. 225-234, Apr 1990.
- Wigner, E., "On the Quantum Correction for Thermodynamic Equilibrium", Physics Review, vol. 40, pp. 749-759, June 1932.
- Ville, J., "Theorie et Applications de la Notion de Signal Analytique", Cables et Transmission, Vol 2a, No. 1, pp. 61-74, 1948.
- 11. Classen, T. and Mecklenbrauker, W., "The Wigner Distribuition - A Tool for Time-Frequency Signal Analysis Part I: Continuous-Time Signals", Philips Journal of Reasearch, vol. 35, nos. 3, pp. 217-250, 1980.

- 12. Classen, T. and Mecklenbrauker, W., "The Wigner Distribuition - A Tool for Time-Frequency Signal Analysis Part II: Discrete-Time Signals, "Philips Journal of Reasearch, vol. 35, nos 4/5, pp. 276-300, 1980.
- 13. Classen, T. and Mecklenbrauker, W., "The Wigner Distribuition - A Tool for Time-Frequency Signal Analysis Part III: Relations with other Time-Frequency Signal Transformations", Philips Journal of Reasearch, vol. 35. nos. 6, pp. 372-389, 1980.
- 14. Shin, Y. and Jeon, J., "Pseudo Wigner-Ville Time-Frequency Distribution and Its Application to Machinery Condition Monitoring", Shock and Vibration, vol. 1, no. 1, pp. 65-76, 1993.
- 15. Newland, D., "Wavelet Analysis of Vibration", ASME PD-Vol. 52, Structural Dyanmics and Vibration - 1993, pp. 1-12, The 16th Annual Energy-Source Technology Conference, Houston, TX., 31 Jan. - 4 Feb., 1993.
- 16. Wang, W. and McFadden, P., "Application of the Wavelet Transform to Gearbox Vibration Analysis", ASME PD-Vol. 52, Structural Dyanmics and Vibration - 1993, pp. 13-20, The 16th Annual Energy-Source Technology Conference, Houston, TX., 31 Jan. - 4 Feb., 1993.

17. Shin, Y. and Jeon, J., "Wavelet Analysis of Nonstationary Acoustic and Vibration Signatures", Proceeding of inter-noise 94 Conference, Vol. III, pp. 1903-1906, Yokohama, Japan, 29-31 August, 1994.

INITIAL DISTRIBUTION LIST

1. Defense Technical Information CenterNo. of CopiesCameron Station2Alexandria, VA 22304-6145

1

2

- Dudley Knox Library, Code 52
 Naval Postgraduate School
 Monterey, CA 93943-5002
- 3. Department Chairman, Code ME Department of Mechanical Engineering Naval Postgraduate School Monterey, CA 93940
- 4. Naval/Mechanical Engineering Curricular Office 1 Code 34 Naval Postgraduate School Monterey, CA. 93940
- 5. Prof. Y. S. Shin, Code ME/Sg Department of Mechanical Engineering Naval Postgraduate School Monterey, CA 93940
- 6. Mr. Lynn Hampton, Program Manager Machinery Condition Analysis NAVSEADET PERA(CV) Code 1822 1305 Ironsides Bremerton, WA 98310-4924

- 7. Mr. Ken Jacobs, Deputy Director Surface Ship Maintenance Division Naval Sea Systems Command Code 915B Washington, D.C. 20362-5101
- 8. COMMANDANT (G-ENE-3C) United States Coast Guard 2100 Second Street, S.W. Washington, DC 20593-0001
- 9. LT J. E. Harding, USCG USCGC MIDGETT (WHEC 726) FPO AP, 96698-3915

2

1