



DMSTTIAC

*Defense Modeling, Simulation and Tactical Technology
Information Analysis Center*

DMSTTIAC SOAR 97-01

Head Mounted Displays Analyses of Current Technologies and Future Applications

Myles V. Saulibio
Research Engineer
IIT Research Institute
DMSTTIAC Orlando Operations

Published by:
DMSTTIAC
IIT Research Institute
7501 S. Memorial Parkway, Suite 104
Huntsville, AL 35802

Approved for Public Release;
Distribution is Unlimited

19970417 036

February 1997

NOTICES

State of the Art Review. This state-of-the-art review has been published by the Defense Modeling and Simulation Tactical Technology Information Analysis Center (DMSTTIAC) as a service to both defense and non-defense agencies, academia and industry. DMSTTIAC is a DoD Information Analysis Center administered by the Defense Technical Information Center and operated by IIT Research Institute under contract DAAH01-95-C-0310. DMSTTIAC is funded by the Defense Technical Information Center (DTIC) and the Defense Modeling and Simulation Office (DMSO). The Director of DMSTTIAC is Mr. Hunter Chockley. The Contracting Officer is Ms. Cheryl Montoney, Defense Supply Center, Columbus (DSCC), Columbus, Ohio. The Technical Monitor is Mr. Chalmer D. George, and the Alternate is Mr. Howard C. Race, AMC-Smart Weapon Management Office (SWMO), Attn: AMSMI-SW, Redstone Arsenal, Alabama 35898-5222.

Reproduction and Handling. Unlimited Distribution

REPORT DOCUMENTATION PAGE

Form Approved

OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information including suggestions for reducing the burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 1997		3. REPORT TYPE AND DATES COVERED State-of-the-Art-Review; February 1997	
4. TITLE AND SUBTITLE Head Mounted Displays - Analyses of Current Technologies and Future Applications				5. FUNDING NUMBERS DAAH01-95-C-0310	
6. AUTHOR(S) Myle V. Saulibio					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) IIT Research Institute/DMSTTIAC 7501 South Memorial Parkway, Suite 104 Huntsville, AL 35802				8. PERFORMING ORGANIZATION REPORT NUMBER DMSTTIAC SOAR 97-01	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Commander U.S. Army Missile Command ATTN: AMSMI-SW Redstone Arsenal, AL 35898-5222				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES This document is available only from DMSTTIAC, IIT Research Institute, 10 West 35th Street, Chicago, IL 60616-3799.					
12a. DISTRIBUTION/AVAILABILITY STATEMENT				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This document provides a top level analysis of Head Mounted Display (HMD) systems for new missions or functions. It provides a collection of data and objective assessment on HMD technology and analyzes evolving HMD technologies that may be incorporated into technology demonstrations. This report will aid DoD components in the assessment, evaluation and qualification of HMD technology as it may be applied to meet established or future requirements for force capabilities.					
14. SUBJECT TERMS Head Mounted Displays, Helmet Mounted Displays, Liquid Crystal Displays, Cathode Ray Tubes, Shutter Glasses, Spatial Awareness, Field-of-View, Resolution				15. NUMBER OF PAGES 18	
				16. PRICE CODE \$62.00	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT Unclassified		

Head Mounted Displays

Analyses of Current Technologies and Future Applications

Myles V. Saulibio

Research Engineer

IIT Research Institute

DMSTTIAC Orlando Operations

Orlando, Florida 32826

Published by:

DMSTTIAC

IIT Research Institute

7501 S. Memorial Parkway, Suite 104

Huntsville, AL 35802

Approved for Public Release

Distribution Unlimited

February 1997



DMSTTIAC

Defense Modeling Simulation and Tactical Technology Information Analysis Center

Transmittal Slip

Date: 14 April 1997

From: Gerri A Koclanis **Phone:** (312) 567-4587

To: Pat Mawby

RE: NEW DMSTTIAC PRODUCT SOAR 97-01

Remarks/Comments: Pat: I am enclosing a copy of the latest
DMSTTIAC SOAR 97-01.

Thank you,

Gerri

Table of Contents

1. HMD Overview.....	1
2. Definitions	2
3. HMD Applications in Virtual Environments	3
4. LCDs and CRTs: A Comparison Overview	4
5. Sample Achievements	5
6. Future Challenges	6
7. Human Factors	7
8. Current.On-Going Research Efforts	9
9. Bottom Line/Conclusion	11
10. HMD Manufacturer	12
11. References	15

1. HMD Overview

Head mounted displays have been used worldwide for almost 30 years in over 10,000 aircraft. Helmet-mounted displays exist in less than 500 aircraft, most of which are helicopters.

The use of HMD's for simulation and training purposes is an enigma. Researchers and developers over the years have battled with the technical and human factors issues that confront them constantly.

Currently, the most popular choice for displays are *liquid crystal displays or (LCD's)* . Some high end HMDs use *cathode ray tubes (CRT's)* for the display.

Purpose of this Report:

The use of advanced visuals technology such as HMDs is becoming increasingly important as soldiers are required to carry out far more complex mission-oriented tasks on the battlefield of the future.

SOAR Investigative Aims-

- To provide a broad yet simplistic overview of HMD systems using a survey of available data, examination of memos, and a series of market reports.

SOAR Parameters

This SOAR provides a top level analyses of HMD systems for new missions or functions. It is the intent of this SOAR to provide a collection and objective assessment of HMD technology and to carefully analyze evolving HMD technology that may be incorporated into technology demonstrations. The broad purpose of this SOAR is to aid DoD components in the assessment, evaluation, and qualification of HMD technology as it may be applied to meet established or future requirements for force capabilities or to assess the ability of individual systems or aggregations of system, people, and institutions to meet such requirements.

This report also focuses on the trade-off between control and display complexity and overall system integration, areas being addressed by emerging HMD technologies.

2. Definitions

- 1) *Head Coupled*: Displays or robotic actions that are activated by head motion through a head tracking device.
- 2) *Head Mounted Displays*: A set of goggles or a helmet with tiny monitors in front of each eye which generate 3 dimensional (3D) images. The HMD provides the primary visual input for the individual say, for a pilot. A variety of display types are being used. Some are full color, high resolution device with a wide field of view that tracks a pilot's head motions, providing a full viewing field and imbedded symbology for heads-up presentation of the operational and system information.
- 3) *Helmet Mounted Displays* is a technology that mounts various display hardware on a human head and projects images or information into one or both eyes of the user. HMDs are worn strapped or fitted to the user's head in the form of an enclosed helmet or eyeglasses. Images may be superimposed in the real world or the real world may be blocked allowing the user a fully immersed Virtual Reality world environment. In all designs, a head tracker is a necessity as an interface to the computer image generator that tracks and keeps up with the user's relative position, viewing angle and direction.
- 4) *Shutter glasses*: LCD screens or physically rotating shutters used to see stereoscopically when linked to the frame rate of a monitor.
- 5) *CRT (Cathode Ray Tubes)* - direct representation of scenes (as in TV), "blips" that represent objects (as in radar and aircraft-control-tower displays), graphic representations (as in various types of test and medical equipment), and generated alphanumeric and symbolic characters.

3. HMD Applications in Virtual Environments

Representative current HMD applications are:

- 1) Total Immersion of human subjects into the virtual environment, a la Virtual Reality
- 2) Necessary Hands-Free Operation
- 3) High Resolution Micro-displays
- 4) Combat Vehicle Crew (CVC) goggle with 1280 X 1024 active-matrix electroluminescent (AMEL) display for M1A2 tank commander.
- 5) Use of advanced sensor suites , ability to modify the visual scene presented.

4. LCDs and CRTs: A comparison overview

	LCDs	CRTs
RESOLUTION	(-) Poor 208 X 139 pixels	(+) Good 1200 - 1000 pixels
COLOR	(-) Poor	(+) Good
CONTRAST	(-) Low Ratios 5:1 to 20:1	(+) Good Ratios 100:1
Light (Weight)	(+)	(-)
Computer Update Rates	(-) Slow	(+)
Cheap/Wide Availability	(+)	(-)

5. Sample Achievements

Numerous research efforts conducted over the years suggest that the manner in which information is presented to the individual can radically improve or degrade the person's ability to understand and comprehend the significance of and act on the information. The benefits of this on-going research will be to improve understanding of the operational and training needs as well as display requirements for a variety of applications from aircrew operations to telepresence/telemedicine to dismounted soldier simulations. Here are a few highlighted programs.

- 1) Simulator Training Research Advanced Testbed for Aviation (STRATA), Ft Rucker, Alabama, May 1992 to Feb 1995. Experiment conducted using a pilot crew station and the stereoscopic fiber optic HMD in the simulation of the AH-64A helicopter. STRATA is a reconfigurable research testbed that can evaluate training subsystems for different aircraft types.
- 2) High Resolution Micro-displays
- 3) Combat Vehicle Crew (CVC) goggle with 1280 X 1024 active-matrix electroluminescent (AMEL) display for M1A2 tank commander.
- 4) Dismounted Soldier Simulation (DSS) , Veda Inc. and STRICOM Engineering Directorate.

6. Future Challenges

HMD systems are continually evolving and responding to current user demand including peripheral devices and software. Additional research is needed and there is a lack of established standards for viewing, dependent upon the user requirements. Research and development is required in the following areas to improve the utility of HMD systems and broaden the user base.

- 1) Higher level performance and lower power consumption for miniature display technologies for high-information-content capability.
- 2) Novel optics approaches for wide field-of-view displays in small, lightweight, form factors.
- 3) Reductions in display power consumption and electronics complexity in a wearable system.
- 4) Adapting new human interface techniques to the HMD information system.
- 5) Developing scaleable tools such as data compression techniques and image processors for matching information with the display.
- 6) Performing extreme integration of components and electronics.
- 7) HMDs used in Virtual Reality systems attempt to mimic the visual events of the real world, but they seem to come up short of expectations. These shortcomings can be the result of technological limitations that rotate, displace, differentially magnify, or differentially blur the images in the two eyes, or they can be the result of inviolate physical laws that cause the stereoscopic image to appear in a plane other than the plane of the LCD. These shortcomings adversely impact and overburden the human visual system, leading to information overload, fatigue, phobias, and simulation sickness.
- 8) Hardware and software issues arise depending upon the application. Design and use issues contribute to display weight, fit, cost, and dynamic cost and environment.
- 9) Hardware Issues: Selection of applicable display technology - CRT or Liquid Crystal. Field of View (FOV) matched to the task(s). CRTs have long been challenged by the problem of resolution, which is essentially the number of raster scan lines, or simply scan lines.
- 10) Stereoscopic disparities effects under dynamic viewing conditions; perceptual effects of shear and magnification (i.e., size) disparities under large-field stereoscopic viewing conditions.

7. Human Factors

- 1) Human performance in head mounted displays depends largely on the display's field of view (FOV). Light enters our eyes through an angular visual field that spans approximately 200 degrees horizontally and 150 degrees vertically, but this is not matched by typical head-mounted displays (HMD's).
- 2) Most of the surveyed HMDs have relatively narrow fields of view, ranging from roughly 30 to 70 degrees diagonally. Narrow FOV has been shown to degrade human performance on the following:
 - a). Navigation
 - b). Spatial Awareness
 - c). Manipulation
 - d). Target Tracking Tasks
 - e). Disruption of eye-and-head -movement coordination
 - f). Perception of size, space, and ego-center
 - g). Psychological effects
- 3) Wide FOV displays are not yet generally available and if so, are only available at high-cost. Choosing the widest FOV available may not be optimal for many intended applications. Researchers have indicated that a wide FOV will aggravate simulator sickness effects, and in particular those due to vector and visual-vestibular mismatch, and may not be necessary for a task that is confined to a small space.
- 4) The last few years have seen the HMD reach acceptable standards for installation in the cockpit of military helicopters and fighters.
- 5) Adapting new human interface techniques to the HMD information system.
- 6) Performing extreme integration of components and electronics.
- 7) The use of any visual display such as the HMD depends upon the visual capabilities of the subject HMD user. The visual skills people have-especially visual acuity (resolution) and color discrimination (deficiency in the ability of the cones to differentiate various wave lengths) - have a direct bearing upon the design of visual

displays, particularly on the ability to detect relevant stimuli and to discriminate between and among variations thereof. The meaningfulness of what the subject sees in any visual display depends in part upon their perceptual processes and the learning of relevant associations. Thus the appropriate HMD design must be predicated in part upon the perceptual and learning factors as well as upon the specific visual skills of the user.

- 8) No available HMD provides a combination wide FOV and high resolution that matches the FOV and half-arc minute resolution of the human eye.
- 9) Trade-offs in FOV and resolution are necessary. Wide FOV is critical to applications where full virtual immersion is required and for tasks requiring peripheral vision. Human factors issues include but are limited to HDM weight, head supported weight, luminance, cost, and environment (temperature, shock, and humidity).
- 10) Further issues include human performance efficiency in virtual worlds, task characteristics, user characteristics, design constraints imposed by human sensory and motor physiology (visual, auditory, tactile, haptic). Also, integration issues with multi-modal interaction, virtual environment design metaphors, health and safety issues, cyber-sickness, and social impact.
- 11) HMDs tend to produce large distortions in the optics and lack of interpupillary adjustments either in the hardware or software. Future technology will evolve to correct these defects. Meanwhile, the headaches and discomfort of modern headmounts limit usage to a few hours a day at most.

8. Current/On-Going Research Efforts

Current applications include dismounted soldier simulation, ground vehicles tactics, techniques, and procedures, and rotary/fixed wing aircraft. The focus of these efforts include developing higher resolution (e.g. 5arc min/line pair), wider FOV (120 degrees ++), and lighter weight systems (< 4 lbs). Other technical issues being addressed include cross-systems compatibility, light weight for longer exposure. Significant on-going or completed Department of Defense research efforts are presented below.

The Joint Helmet-Mounted Cueing System (JHMCS)	Aeronautical Systems Center, Wright- Patterson AFB, Ohio.
Integrated Helmet Audio-Visual System (IHAVS) 3-D aural cueing, HMD for imagery and aircraft state information	Joint Advanced Strike Technology (JAST)
RAH-22 Comanche Helmet Integrated Display/Sight Subsystem (HIDSS) Heads up , eyes out pilotage capability that reduces pilot workload.	PM-Comanche, St. Louis, MO.
Helmet Mounted Mission Rehearsal Simulation System (HMMRSS) and other related projects Transportable flight simulation testbed to train deployed aircrews on high cost weapons systems and mission rehearsal tasks.	NAWCTSD, Orlando, FL.
Crew Station Technology Lab On-going projects in the last 9 years	NAWCAD, Pautuxent River, Md.
AL/HRA On-going projects in the last 12 years Night Vision Goggle using miniature CRTs; developed 5 different HMDs,	Armstrong Lab, Mesa, Arizona.
Simulator Training Research Advanced Testbed for Aviation (STRATA) Fiber Optic HMD in a reconfigurable rotary wing simulator	Ft Rucker, Alabama
Aerospace Vision Lab (AVL) Human visual performance assessment and the development of design recommendations for wide FOV, etc.	Armstrong Laboratory Crew Systems Directorate, Wright Patterson AFB, OH

Visual Perception in Synthetic Environments Program Behavioral research on visual perception.	Armstrong Laboratory , AL/HRAU, Mesa, Arizona
ARL/HRED Continued research to quantify deficits in human performance related to displays.	Army Research Laboratory, Human Research and Engineering Directorate, Aberdeen Proving Ground, Maryland.
Advanced Flat Panel Head Mounted Display Program (AFP) Development of a sterilizable, orthostereoscopic system	Honeywell Technology Center (HTC)
Full Immersion Head Mounted Display System Development of a range of full-peripheral vision head mounted display systems that high resolution, low-cost, and light-weight, based upon the Kaiser Electro-Optics (KEO) Visual Immersion Module (VIM) optical technology.	Kaiser Electro- Optics, Inc.
Virtual Environment Testbed Continual human-factors psychology experiments to evaluate the potential of Virtual Environment technology for use in training.	Army Research Institute Environment Testbed and Institute for Simulation and Training (IST) University of Central Florida
Combat Vehicle Crew- CVC HMD Program First high resolution (1280X1024) flat panel HMD. Designed for use by a M1A2 Abrams Main Battle Tank Commander, it shows IVIS (Inter-vehicular information system) information and thermal imagery from the commander's ITV (Independent Thermal Viewer)	Honeywell Technology Center DARPA HMD Program
DARPA HMD Program Seeks to develop and demonstrate miniature high definition flat panel displays and supporting technologies to enable a wide-range of mission critical, man-portable, and head-or-helmet-mountable functions (for virtual, augmented, and hybrid reality applications).	US Army Natick Research, Development, and Engineering Center, Medford, MA.

9. Bottom Line/Conclusion

HMD displays present complex scene content configurations. In the development and use of such displays, the dominant guideline is that of simplicity. Obviously, the application of this principle needs to be within the constraints imposed by the operational requirements for "fidelity" of the configuration. The argument for simplicity arises from the fact that the perceptual processes of "searching" for relevant features take longer (and are subject to high error rates) if an image is cluttered up with what may be irrelevant material.

One fundamental principle in deciding the right HMD is evaluating the issue of resolution using two important factors:

1. The net resolution of the internal display system (LCD or CRT)
2. The horizontally covered field of view or FOV. FOV values vary greatly for different HMDs. This is a result of a lack of standards in the manner of how a manufacturer presents these values. For this report, FOV values should always represent a 100% stereoscopic overlap configuration. Note that a user requires at least 20 degrees overlap to satisfy the human visual system.

With most display design challenges, one should first ask (and answer) the following questions: What information does the user need? and, How can that information best be presented? Obviously, the simplification of complex configurations should be guided by the answers to these questions.

10. HMD Manufacturers

HMDs continue to experience modest growth on the commercial market. As with typical technology trends, lower costs over time with proportionate increases in resolution will occur. Currently commercially-available low resolution HMDs cost under \$10,000, with several baseline models under \$1,000. The Table 1.0 below lists the current manufactures of helmet mounted display systems.

The following table is only a sampling of the representative manufacturers of HMDs. When examined closely, it is assumed that the analysis will reveal useful information about the HMD manufacturer population as a whole. The purpose of the sampling is to select and study a simple random number of HMD manufacturers

Note: The table does not rank, recommend, or rate each manufacturer or their product line.

Manufacturer	Contact	Product
3D-MAX	sales@ThreeD-Max.udac.se Tel: 46 (0)18187777 Fax: 46 (0) 18516600	3D-MAX Display: LCD shutter glasses
Astounding Technologies, Inc.	950 Benecia Avenue Sunnyvale, CA. 94086 USA Tel: (408) 522-0300 Fax: (408) 522-0310	Video Visor Display: Active Matrix LCD Resolution: 428 X 244 pixels Field of View: 30 (H) X 22.5 (V) Overlap: 100% Weight: < 14 oz.
CAE Electronics Ltd	8585 Cote de Liesse C.P. 1800 Saint-Laurent Quebec, Canada H4L4X4 Tel: (514) 341-6780 Fax: (514) 341-7669	Fiber-Optic HMD, Telepresence Visual System Display: CRT Resolution: pixel size 6.6 background, 2.2 inset; pixel structure: 1.2 million pixels distributed between inset and background Field of View: 120 degrees (H) X 55 degrees (V) Overlap: 25 degrees Weight: 4.5 lbs.
Division LTD	The Courtyard, #10 431 West Franklin Street Chapel Hill, NC 27516 Tel: (919) 968-7795 Fax: (919) 968-7890 E-Mail: info@division.com	dVISOR Display: Active Matrix Color LCD Resolution: 345 X 259 pixels Field of View: 105 (H) X 41 (V) Overlap: 40 degrees Weight: 80 oz.
Fakespace, Inc.	4085 Campbell Avenue Menlo Park, CA. 94025 Tel: (415) 688-1940 Fax: (415) 688-1949 E-Mail: fakespace@well.sf.ca.us WWW: www.fakespace.com	BOOM3M (mono) Display: dual CRT Resolution: 1280 X 1024 pixels Field of View: 104(H) X 90(V) Tracking: 2DOF (pan and tilt), optomechanical

Forte Technologies, Inc.	1057 E. Henrietta Road Rochester, NY 14623 Tel: (716) 427-8595 Fax: (716) 292-6353 E-Mail: support@fortevr.com WWW: www.fortevr.com	VFX1 Display: Resolution: pixels Field of View: (H) X (V) Tracking: (pan and tilt), optomechanical
General Reality Company	124 Race Street San Jose, CA 95126 Tel: (408) 289-8340 Fax: (408) 289-8258 E-Mail: sales@genreality.com WWW: www.genereality.com	
General Reality Company	124 Race Street San Jose, CA 95126 Tel: (408) 289-8340 Fax: (408) 289-8258 E-Mail: sales@genreality.com WWW: www.genereality.com	CyberEye CE-200N, CyberEye CEP-100 Display: dual active matrix LCD Resolution: 789 X 230 pixels Field of View: 22.5 (H) X 16.8 (V) Overlap: 100 % Weight: 14 oz.
General Reality Company	124 Race Street San Jose, CA 95126 Tel: (408) 289-8340 Fax: (408) 289-8258 E-Mail: sales@genreality.com WWW: www.genereality.com	ClearVue Display: monochrome CRT with LC filters Resolution: 1280 X 1024 pixels Field of View: 80 (H) X 40 (V) Overlap: 30 degrees Weight: 3 lbs, 5 oz.
Hughes Training, Inc	Link Division P.O. Box 1237 Binghamton, NY 13902-1237 Tel: (607) 721-4356 Fax: (607) 721-5600	CyberFace 2 Display: Single large format LCD, divergent axis Resolution: 385 X 119 pixels Field of View: 140 (H) X 110 (V) Overlap: 30 degrees Weight: 32 oz.
LEEP Systems	241 Crescent Street Waltham, MA 02154-3425 Tel: (617) 647-1395 Fax: (617) 899-9602	CyberFace 3 Display: Single large format LCD, head-coupled Resolution: 480 X 120 pixels Field of View: 80 (H) X 60 (H)
LEEP Systems	241 Crescent Street Waltham, MA 02154-3425 Tel: (617) 647-1395 Fax: (617) 899-9602	CyberFace 4 Display: Single large format LCD, head-coupled Resolution: 640 X 480 pixels Field of View: 80 (H) X 60 (H)
LEEP Systems	241 Crescent Street Waltham, MA 02154-3425 Tel: (617) 647-1395 Fax: (617) 899-9602	CyberFace 5 Display: Quad LCD, triple acuity Resolution: 1170 X 202 pixels FOV : 140 (H) X 110 (V)
LEEP Systems	241 Crescent Street Waltham, MA 02154-3425 Tel: (617) 647-1395 Fax: (617) 899-9602	MRG2/Mirage LCD Technology FOV: >110 degrees Resolution 240 X720

Liquid Image Corporation	659 Century Street Winnipeg, Manitoba R3H 0L9 Canada Tel: (204) 775-2633 Fax: (204) 772-0239 WWW: www.liquidimage.ca/vr	STV-01, Eyephone NewHRX
Nissho Electronics Corp	Advanced Electronics Systems Division 70301 Tsukiji, Chuo-ku Tokyo 104 Japan Tel: 81-3-3544-8452 Fax: 81-3-3544-8284	Datavisor 9Ci and 10X Display: Dual CRT Resolution: 1280 X 1024 pixels Field of View: 50° (H) X 37° (V) Weight: 3.5 lbs.
Nvision Inc.	7915 Jones Branch Drive Suite 1B10 McLean, VA 22102 Ph: (703) 506-8808 Fax: (703) 903-0455	

11. References

<i>The Infrared and elector-optics system handbook: Vol. 3. Electro-optical components</i>	Biberman, L.M. & Tsou, B.H. (1993) Bellingham and WA: SPIE Optical Engineering Press. Synopsis: Image display technology and problems with emphasis on airborne systems.
<i>"Energy Management Displays for Air Combat"</i> ILEEE/AL4, A 11 th Digital Avionics Systems Conference. Paper No. 72, Oct 3-5 1992.	Clark, J.C.; Burley, J.R.
<i>"Displays for Air Combat"</i> High Alpha Workshop, NASA Ames Dryden Flight Research Facility, Apr 20-22, 1992	Clark, J.C.; Burley, J.R.
<i>"A Task Analysis of Air Combat in a Thrust-Vectored Aircraft"</i> Mid- Atlantic Human Factors Conference, Feb 25-26, 1993	Clark, J.W.; Fulop, A.C.; Burley, James R.
<i>"Pilot/Vehicle Display Development From Simulation to Flight"</i> ALAA Simulation Conference, Paper No. 92-4174, Aug 20-24, 1992.	Dare, A.R.; Burley, L.R.
<i>"A Target Detection Study for Detecting Virtual Objects at Varying Depths and Locations While Monitoring the Physical Environment"</i> Mid-Atlantic Human Factors Conference, Feb 25-26, 1993	Fulop, Ann C.; Williams, S.P.; Burley, James R.
<i>"Grating and Flicker Sensitivity in the Near and Far Periphery: Naso-Temporal Asymmetries and Binocular Summation"</i>	Vision Research, 34, 2841-2848
<i>"Visual processing and partial-overlap head-mounted displays"</i>	J. Society for Information Display, 2/2, 69-73
<i>"Human Factors Evaluation of Helmet Mounted Displays for Training Applications"</i> 17 th Interservice/Industry Training Systems and Education Conference (ITSEC 1995)	Christopher J. Whaley; Jeffery M. Gerth ;and Dennis J. Folds.
<i>"Evaluation of Conformal and Body-Axis Attitude Information for Spatial Awareness"</i> SPIE Helmet-Mounted Displays I (V Conference, Paper No. 1695-19, Apr 20-24, 1992.	Jones, D.J.; Abbott, T.S.; Burley, J.R.H.

<i>"System design considerations for a visually coupled system"</i> S.R. Robinson (Ed.), The Infrared and electro-optics system handbook: Vol. 8. <i>Emerging systems and technologies</i> (pp. 515-536)	Tsou, B.H. (1993) Bellingham, WA: SPIE Optical Engineering Press.
<i>"Predictive Nosepointing and Flightpath Displays for Air-to-Air Combat"</i> SPIE Helmet-Mounted Displays IV Conference, Paper No. 1695-20, Apr 20-24 1992	Vicken, S.A.; Burley, James R.
<i>"Perceptual and Motor Skills"</i> - restricting the field of view: perceptual and performance effects Vol. 70, No. 1, pp 35-45, 1990	Alfano, Patricia L. and George F. Michel
<i>"Spatial orientation in real and virtual worlds"</i> Proceedings of the 37 th Annual Meeting of the Human Factors Society. Pp 328-332, 1993	Arthur, E.J., P.A. Hancock, and S.T. Chrysler.
<i>"Visual Capabilities in the space environment"</i> New York: Pergamon Press, 1965	Baker, C.A. , editor.
<i>"Peripheral apparent motion as a function of location, contrast, and direction of stimulus motion"</i> Perceptual and Motor Skills Vol. 68, pp. 33-34, 1989	Barfield, W.,A. Pyrali, and C. Craft.
<i>"Visual Enhancements and geometric field of view as factors in the design of three-dimensional persepective display"</i> Proceedings of the 34 th Annual Meeting of the Human Factors Society 1990	Barfield, woodrow, Rafael Lim, and Craig Rosenberg.
<i>"The super cockpit and its human factors challenges"</i> Proceedings of the 10 th Annual Meeting of the Human Factors Society, pp. 48-32, 1986	Furness, Thomas A., III.
<i>"Visual Processing and partial-overlap head-mounted displays"</i> Journal of the Society for Information Display, Vol. 2, No. 2, pp. 69-74	Grigsby, Scott S. and Brian H. Tsou
<i>"Spatial Orientation in pictorial displays"</i> IEEE Transactions on systems, man, and cybernetics, Vol 18, pp 425-436, 1988	Grunwald, Arthur, Stephen R. Ellis, and Stephen Smith.

<p><i>"Visual Field Information in low-altitude visual flight by line-of-sight slaved helmet-mounted displays"</i> IEEE Transactions on systems, man and cybernetics, Vol. 24, No1, Pg 120, Jan 94</p>	<p>Grunwald, Arthur J. and Silvia Kohn.</p>
<p><i>"Evaluation of conformal and body-axis attitude information for spatial awareness"</i></p> <p>Proceedings of the SPIE: Helmet-Mounted Displays III, Vol. 1695, pp. 146-153, 1992</p>	<p>Jones, Denise R., Terence S. Abbott, and James R. Burley II</p>
<p><i>"Simulator Sickness in virtual environments"</i></p> <p>U.S. Army Research Institute Technical Report 1027, May 1995</p>	<p>Kolasinski, Eugenia M.</p>
<p><i>"Spatial orientation and dynamics in virtual reality systems, lessons from flight simulation"</i></p> <p>Proceedings of the 35th Annual Meeting of the Human Factors Society, pp 1348-1352, 1991</p>	<p>McCauley, Michael E., and Thomas J. Sharkey.</p>
<p><i>"Binocular vision in a virtual worlds: visual deficits following the wearing of a head-mounted display."</i></p> <p>Ophthalmic Physiol. Opt., Vol. 13, No. 4, pp387-391, Oct 1993.</p>	<p>Mon-Williams, M., J.P Wann, and S. Rushton</p>
<p><i>"The effect of field-of-view size on performance of a simulated air-to-ground attack."</i></p> <p>Proceeding of Helmet Mounted Displays and Night Vision Goggles, AGARD Conference Proceedings, No. 516, 1991</p>	<p>Osgood, R.K., and M.J. Wells</p>
<p><i>"A literature survey for virtual environments: Military flight simulator visual systems and simulator sickness."</i></p> <p>Presence, Vol. 1, No. 3, pp 344-363, Summer 1992.</p>	<p>Pausch, Randy, Thomas Crea, and Matthew Conway.</p>
<p><i>"A user study comparing head-mounted and stationary displays"</i></p> <p>Proceedings of the IEEE 1993 Symposium of Research Frontiers in Virtual Reality, pp. 41-43</p>	<p>Pausch, Randy, M. , Anne Shackelford, and Dennis Proffitt.</p>
<p><i>"Simulating peripheral vision in immersive virtual environments."</i> Computers & Graphics, Vol. 17, No.6, pp 643-653, November/December 1993</p>	<p>Slater, Mel and Martin Usoh.</p>

<p><i>"Spatial awareness with a helmet-mounted display."</i></p> <p>Proceedings of the 33rd Annual Meeting of the Human Factors Society , pp 1388-1391, 1989</p>	Venturino, M. and R.J. Kunze
<p><i>"A User study evaluating level of detail degradation in the periphery of head-mounted displays."</i></p> <p>Unpublished tech report presented in a SIGGRAPH 95 technical sketch session, 1995</p>	Watson, Benjamin, Neff Walker, and Larry F. Hodges.
<p><i>"Using target replacement performance to measure spatial awareness in a helmet-mounted simulator."</i>Proceedings of the 32rd Annual Scientific Meeting of the Human Factors Society, pp 1429-1433, 1988</p>	Wells, M.J. , Venturino, and R.K. Osgood
<p><i>"Effect of field-of-view size on performance at a simple simulated air-to-air mission."</i></p> <p>Helmet Mounted Displays, Proceedings of the SPIE, Vol. 1116, pp. 126-137, 1989</p>	Wells, Maxwell J., Michael Venturino, and R.K. Osgood.
<p><i>"Performance and head movements using a helmet-mounted display with different sized fields-of-view."</i></p> <p>Optical Engineering, Vol. 29, No. 8, pp 870-877, Aug 1990</p>	Wells, Maxwell J. and Michael Venturino