Pro (182)		
NACA TN 2531	NATIONAL ADVISORY COMMIT FOR AERONAUTICS	TEE
	TECHNICAL NOTE 2531	
	SIMPLIFIED METHOD FOR CALCULATION OF COMPI	RESSIBLE
	LAMINAR BOUNDARY LAYER WITH ARBITRAN	RY
	FREE-STREAM PRESSURE GRADIENT	ų
	By George M. Low	
•	Lewis Flight Propulsion Laboratory Cleveland, Ohio	
	Reproduced From Best Available Copy	200
	NACA	007
	Washington	2
	October 1951	
	DISTRIBUTION STATEMENT A Approved for Public Release Distribution Unlimited	08

AQM00-10-3241

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

1

TECHNICAL NOTE 2531

SIMPLIFIED METHOD FOR CALCULATION OF COMPRESSIBLE

LAMINAR BOUNDARY LAYER WITH ARBITRARY

FREE-STREAM PRESSURE GRADIENT

By George M. Low

SUMMARY

The Kármán-Pohlhausen integral method, as applied to compressible laminar boundary layers, was simplified by an analysis similar to the incompressible Holstein-Bohlen method. Although this simplification is helpful for many calculations, it is of greatest value when conditions at the edge of the boundary layer are known from experimental measurements. The analysis was conducted under the assumptions of a Prandtl number of 1, zero heat transfer, and a linear viscosity-temperature relation; velocity profiles are approximated by a fourth-degree polynomial.

Results are presented so that velocity and temperature profiles, momentum and displacement thicknesses, and wall shear stress can be calculated for flows over two-dimensional bodies with arbitrary freestream velocity distributions. The results are also applicable to flows over three-dimensional bodies with axial symmetry through the use of Mangler's transformation.

INTRODUCTION

Present-day theory of compressible laminar boundary layers permits the aerodynamicist to make satisfactory boundary-layer calculations for flows with zero pressure gradients. Exact solutions of the boundarylayer equations for flows with streamwise pressure gradients, however, exist only for several specific pressure distributions (reference 1). Solutions of the laminar-boundary-layer equations for flows with arbitrary pressure gradients are of ever increasing importance because it has been suggested that at sufficiently high altitudes and speeds laminar boundary layers can exist at very high Reynolds numbers (reference 2), and because the pressure gradients encountered over most wings and bodies are not approximated by any of the aforementioned exact solutions.

2285

The lack of exact solutions for flows with arbitrary streamwise pressure gradients necessitates the use of approximate solutions. The Kármán-Pohlhausen method has long been found to yield satisfactory solutions for incompressible flows, provided that the separation point is not approached. Howarth (reference 1) has recently applied this method to compressible flows.

The solution of the incompressible or compressible boundary-layer equations by the Kármán-Pohlhausen method is complex because it involves the numerical solution of a cumbersome differential equation, and because it involves second derivatives of the free-stream velocity, which cannot be determined with any accuracy if the free-stream velocity is known only from experimental measurements. For incompressible fluids, these difficulties have been overcome by the Holstein-Bohlen simplification (reference 3), which eliminates the second derivatives of the free-stream velocity and simplifies the differential equation.

In the present report of an analysis made at the NACA Lewis laboratory, the Holstein-Bohlen simplification is applied to the Kármán-Pohlhausen method for compressible fluids. The momentum-integral equation is derived using the transformation of Howarth (reference 1) together with a more general viscosity-temperature relation than that used in reference 1. The greater part of the analysis presented follows along the lines of reference 1, but the emphasis herein is placed on simplifying the final results of the analysis so that they can easily be applied to any practical problem.

Although the present analysis is carried out for two-dimensional flows, it can be applied to three-dimensional flows with axial symmetry by using the transformation of Mangler (see appendix A). Under this transformation, a three-dimensional body with a given pressure gradient is transformed to a related two-dimensional body. The results of the present study can be applied to this two-dimensional body.

SYMBOLS

The following symbols are used in this report:

a speed of sound

C	proport	lonalit	y f	actor	used	in	equation ((1))
---	---------	---------	-----	-------	------	----	------------	-----	---

c_p specific heat at constant pressure

 $f(M_1)$ function defined by equation (28)

- $f_1(\lambda)$ function defined by equation (28)
 - $f_2(\lambda)$ function defined by equation (28)
 - $f(\eta)$ function defined by equation (20)
 - h increment of length
 - i summation index
 - K arbitrary constant
 - k thermal conductivity
 - M Mach number
 - n transformation variable defined by equation (9)
 - Pr Prandtl number, $\mu c_{\rm p}/k$
 - p static pressure
 - r radial coordinate
 - S Sutherland's constant (216° F)
 - t static temperature
 - u, v velocity in x- and y-directions, respectively
 - x,y cartesian coordinates measured along body and perpendicular to body, respectively
 - Z function defined by equation (25)
 - γ ratio of specific heats
 - Δ boundary-layer thickness in x,n coordinate system
 - Δ^* function defined by equation (19)
 - δ boundary-layer thickness in x,y coordinate system
 - δ^* boundary-layer displacement thickness

η n/∆

Θ	function defined by equation (18)		#
θ.	boundary-layer momentum thickness		
λ	Pohlhausen parameter		
μ	absolute viscosity	, en	228
ν	kinematic viscosity		U
ρ	mass density		
τ	shear stress		
ø	transformed stream function	· · · . · · · · · · · ·	
¥	stream function		
Subscrij	pts:		
0	conditions at stagnation point		
l	conditions at outer edge of boundary]	layer	*
S	standard condition	$\Delta (c_1^{(1)}) = \frac{1}{2} \sum_{i=1}^{n-1} c_i (c_i^{(1)}) = \frac{1}{2} \sum_{i=1}^{n-1} c_i (c$	4
W	condition at solid boundary		

ASSUMPTIONS

4

The following assumptions are made in addition to the usual boundary-layer assumptions in order to make the problem amenable to solution:

(1) The Prandtl number of the fluid is equal to 1. It has been shown in reference 4 that this assumption has no appreciable effect on flat-plate skin-friction calculations if the fluid is air (for M < 5), but the assumption does limit the accuracy of heat-transfer calculations and temperature distributions.

(2) The heat transfer at the solid boundary is equal to zero. This assumption should be reasonable for many practical applications.

2285

(3) The viscosity and temperature are related linearly by the following expression:

$$\frac{\mu}{\mu_{\rm s}} = C \frac{t}{t_{\rm s}} \tag{1}$$

Chapman and Rubesin (reference 5) have shown that solutions of the boundary-layer equations based on equation (1) agree well with reality for flat-plate flows if the constant C is determined by matching equation (1) with Sutherland's relation at the solid boundary so that

$$C = \sqrt{\frac{t_w}{t_s}} \frac{(t_s + S)}{(t_w + S)}$$
(2)

This assumption should also be reasonable for the case of flows with streamwise pressure gradients because the wall temperature t_w is constant as a consequence of assumptions (1) and (2).

ANALYSIS

Compressible laminar-boundary-layer equations. - The momentum equation describing the flow in the boundary layer is

 $u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} = -\frac{1}{\rho} \frac{dp}{dx} + \frac{1}{\rho} \frac{\partial}{\partial y} \left(\mu \frac{\partial u}{\partial y} \right)$ (3)

The equation of continuity is

$$\frac{\partial}{\partial x} (\rho u) + \frac{\partial}{\partial y} (\rho v) = 0 \qquad (4)$$

The flow of heat is described by the energy equation, which is

$$\rho c_{p} \left(u \frac{\partial t}{\partial x} + v \frac{\partial t}{\partial y} \right) = u \frac{dp}{dx} + \frac{\partial}{\partial y} \left(k \frac{\partial t}{\partial y} \right) + \mu \left(\frac{\partial u}{\partial y} \right)^{2}$$
(5)

A particular solution of the energy equation can be obtained by multiplying equation (3) by ρu and adding the result to equation (5), and by letting the Prandtl number equal 1. This solution is

$$\frac{u^2}{2} + c_p t = constant$$
 (6)

and corresponds to the case where the heat transfer at the solid boundary is equal to zero.

The equation of state can be expressed as

$$\frac{\mathbf{p}}{\mathbf{p}_{s}} = \frac{\rho}{\rho_{s}} \frac{\mathbf{t}}{\mathbf{t}_{s}}$$
(7)

The Bernoulli equation, which applies at the outer edge of the boundary layer, is

$$\frac{dp}{dx} = -\rho_1 u_1 \frac{du_1}{dx}$$
(8)

<u>Transformation of Howarth.</u> - In reference 1 Howarth introduces a transformation which, when applied to equation (3), yields an equation similar to the incompressible momentum equation. In the present report the transformation is modified slightly to include the proportionality factor C in equation (1). The transformation variables are

$$x \equiv x$$

$$n \equiv \frac{1}{\sqrt{C}} \left(\frac{p}{p_{s}}\right)^{\frac{1}{2}} \int_{0}^{y} \frac{t_{s}}{t} dy$$
(9)

where n alters the scale in the direction normal to the surface. The derivatives are expressed as follows:

$$\frac{\partial}{\partial x}_{y} = \frac{\partial}{\partial x}_{n} + \frac{\partial n}{\partial x} \frac{\partial}{\partial n}$$

$$\frac{\partial}{\partial y} = \frac{1}{\sqrt{C}} \left(\frac{p}{p_{s}}\right)^{\frac{1}{2}} \frac{t_{s}}{t} \frac{\partial}{\partial n} \qquad (10)$$

Before transforming equation (3) it is convenient to introduce a stream function $\psi(\mathbf{x},\mathbf{y})$ which satisfies equation (4). This function is defined by

$$\rho u = \rho_{g} \frac{\partial \psi}{\partial y}$$

$$\rho v = -\rho_{g} \frac{\partial \psi}{\partial x}$$
(11)

2285

In terms of the transformed coordinate system, a function $\phi(x,n)$ can be defined as

$$\psi(\mathbf{x},\mathbf{y}) = \sqrt{C\left(\frac{p}{p_{s}}\right)^{\frac{1}{2}}} \phi(\mathbf{x},\mathbf{n})$$
 (12)

From equations (10), (11), and (12),

$$u = \frac{\partial \phi}{\partial n}$$

$$v = -\frac{\rho_{\rm s}}{\rho} \left[\sqrt{\frac{p_{\rm C}}{p_{\rm s}}} \left(\frac{\partial \phi}{\partial x} + \frac{\partial \phi}{\partial n} \frac{\partial n}{\partial x} \right) + \phi \frac{\partial}{\partial x} \left(\sqrt{\frac{p_{\rm C}}{p_{\rm s}}} \right) \right] \right\}$$
(13)

and, as shown in reference 1, from equations (1), (7), (8), (10), and (13), the momentum equation becomes

$$\frac{\partial \phi}{\partial n} \frac{\partial^2 \phi}{\partial x \partial n} - \frac{\partial \phi}{\partial x} \frac{\partial^2 \phi}{\partial n^2} - u_{\perp} \frac{du_{\perp}}{dx} \left(\frac{t}{t_{\perp}} - \frac{\gamma}{2a_{\perp}^2} \phi \frac{\partial^2 \phi}{\partial n^2} \right) = v_{\rm s} \frac{\partial^3 \phi}{\partial n^3} \qquad (14)$$

The temperature term in this equation can be expressed in the form

$$\frac{t}{t_1} = 1 + \frac{u_1^2 - u^2}{2c_p t_1} = 1 + \frac{\gamma - 1}{2} M_1^2 - \frac{\gamma - 1}{2a_1^2} \left(\frac{\partial \phi}{\partial n}\right)^2$$
(15)

from which

$$\frac{\partial \phi}{\partial n} \frac{\partial^2 \phi}{\partial n \partial x} - \frac{\partial \phi}{\partial x} \frac{\partial^2 \phi}{\partial n^2} - u_{\perp} \frac{du_{\perp}}{dx} \left[1 + \frac{\gamma - 1}{2} M_{\perp}^2 - \frac{\gamma - 1}{2a_{\perp}^2} \left(\frac{\partial \phi}{\partial n} \right)^2 - \frac{\gamma}{2a_{\perp}^2} \phi \frac{\partial^2 \phi}{\partial n^2} \right] = v_{\rm s} \frac{\partial^3 \phi}{\partial n^3}$$
(16)

With the exception of the term within the bracket, equation (16) is identical in form to the incompressible momentum equation.

<u>Momentum-integral equation</u>. - The momentum-integral equation is obtained by integrating each term of equation (16) from the solid boundary to the outer edge of the boundary layer (see reference 1):

$$u_{l}^{2} \frac{d\Theta}{dx} + u_{l} \frac{du_{l}}{dx} \left[\Theta \left(2 - \frac{M_{l}^{2}}{2} \right) + \Delta^{*} \left(1 + \frac{\gamma - 1}{2} M_{l}^{2} \right) \right] = v_{s} \left(\frac{\partial u}{\partial n} \right)_{w} \quad (17)$$

where

$$\Theta \equiv \int_{0}^{\Delta} \left(1 - \frac{u}{u_{l}}\right) \frac{u}{u_{l}} dn \qquad (18)$$

$$\Delta^* \equiv \int_0^{\Delta} \left(1 - \frac{u}{u_1}\right) dn \tag{19}$$

The auxiliary functions Θ and Δ^* are similar to the momentum thickness θ and the displacement thickness δ^* in the physical coordinate system.

<u>Modified Kármán-Pohlhausen solution</u>. - In order to solve equation (17) by the Kármán-Pohlhausen method it is necessary to introduce the variable $\eta \equiv n/\Delta$ and to assume that u/u_1 is a polynominal in η . As in the method of Pohlhausen, this polynomial is taken to be of the fourth degree. The coefficients of the polynomial are determined from the following boundary conditions:

n = 0:

$$u = 0$$

$$-u_{1} \frac{du_{1}}{dx} \left(1 + \frac{\gamma - 1}{2} M_{1}^{2} \right) = v_{s} \frac{\partial^{3} \phi}{\partial n^{3}} = v_{s} \frac{\partial^{2} u}{\partial n^{2}}$$
n = Δ :

$$u = u_{1}$$

$$\frac{\partial n}{\partial u} = \frac{\partial n^2}{\partial u^2} = 0$$

Thus the following form is obtained for the velocity profile:

$$\frac{u}{u_{\perp}} = f(\eta) = 2\eta - 2\eta^3 + \eta^4 + \lambda \left[\frac{1}{6}\eta (1-\eta)^3\right] \qquad (20)$$

where the parameter λ is defined as

$$\lambda \equiv \frac{\Delta^2}{\nu_{\rm s}} \frac{\mathrm{d}u_{\rm l}}{\mathrm{d}x} \left(1 + \frac{\Upsilon - 1}{2} M_{\rm l}^2 \right)$$
(21)

2

2285

Transformation to the n-coordinate and subsequent integration in equations (18) and (19) yield

$$\Theta = \frac{\Delta}{315} \left(37 - \frac{\lambda}{3} - \frac{5\lambda^2}{144} \right)$$
(22)

$$\Delta^* = \Delta \left(\frac{36 - \lambda}{120} \right) \tag{23}$$

and it is found that

$$\left(\frac{\partial u}{\partial n}\right)_{W} = \frac{u_{I}}{\Delta} \left(2 + \frac{\lambda}{6}\right)$$
(24)

Equations (22), (23), and (24) could be applied to equation (17) directly and the result would be a differential equation for λ (reference 1). A simpler solution can be obtained by applying the substitution of Holstein-Bohlen:

$$Z = \Theta^2 / \nu_s$$
 (25) or, from equations (22) and (21),

in a lin

$$Z = \frac{\lambda \left[\frac{1}{315} \left(37 - \frac{\lambda}{3} - \frac{5\lambda^2}{144}\right)\right]^2}{\frac{du_1}{dx} \left(1 + \frac{\gamma - 1}{2} M_1^2\right)}$$
(26)

Equation (17) is multiplied by Θ/u_1v_1 , and equations (25) and (26) are substituted in the resulting expression to yield

$$\frac{u_{1}}{2}\frac{dZ}{dx} + f_{1}(\lambda)\left[-f(M_{1}) + \frac{\Delta^{*}}{\Theta}\right] = \frac{\Theta}{u_{1}}\left(\frac{\partial u}{\partial n}\right)_{W}$$

Then, from equations (22), (23), and (24),

$$\frac{dZ}{dx} = \frac{2}{u_1} \left[f_1(\lambda) f(M_1) + f_2(\lambda) \right]$$
(27)

)

2285

where

$$f_{1}(\lambda) \equiv \lambda \left[\frac{1}{315} \left(37 - \frac{\lambda}{3} - \frac{5\lambda^{2}}{144} \right) \right]^{2}$$

$$f_{2}(\lambda) \equiv \frac{1}{315} \left(37 - \frac{\lambda}{3} - \frac{5\lambda^{2}}{144} \right) \left(2 - \frac{2\lambda}{15} + \frac{\lambda^{2}}{120} \right)$$

$$f(M_{1}) \equiv \frac{M_{1}^{2} - 4}{2 + (\gamma - 1) M_{1}^{2}}$$
(28)

and

$$Z = \frac{f_{1}(\lambda)}{\frac{du_{1}}{dx} \left(1 + \frac{\gamma - 1}{2} M_{1}^{2}\right)}$$
(29)

Equations (27) and (29) can now be integrated simultaneously, and λ can be obtained as a function of x by a method of numerical integration given in detail in appendix B. The functions $f_1(\lambda)$ and $f_2(\lambda)$ are graphically presented in figure 1 and are tabulated in table I; $f(M_1)$ is tabulated in table II. Boundary-layer variables are still in the transformed system of coordinates, however, and a transformation to the physical (x,y) coordinates is required.

Inverse transformation to physical coordinates. - The distance normal to the surface can be obtained from equation (9):

$$dy = \sqrt{\frac{p_s^C}{p}} \frac{t}{t_s} dn$$
$$= \Delta \sqrt{\frac{p_s^C}{p}} \frac{t}{t_s} d\eta$$

or

$$y = \Delta \sqrt{\frac{p_{\rm B} J}{p}} \frac{t_{\rm I}}{t_{\rm g}} \int_0^{\eta} \frac{t}{t_{\rm I}} \, d\eta$$

But, from equation (15),

$$\frac{t}{t_{1}} = 1 + \frac{\gamma - 1}{2} M_{1}^{2} \left[1 - \left(\frac{u}{u_{1}} \right)^{2} \right]$$
(30)

and, from equation (20),

$$\frac{t}{t_{1}} = 1 + \frac{\gamma - 1}{2} M_{1}^{2} \left(1 - \sum_{i=2}^{8} a_{i} \eta^{i} \right)$$
(31)

where

2285

$$a_{2} = \frac{\lambda^{2}}{36} + \frac{2}{3}\lambda + 4$$

$$a_{3} = -\frac{\lambda^{2}}{6} - 2\lambda$$

$$a_{4} = \frac{5\lambda^{2}}{12} + \frac{4\lambda}{3} - 8$$

$$a_{5} = -\frac{5\lambda^{2}}{9} + \frac{5\lambda}{3} + 4$$

$$a_{6} = \frac{5\lambda^{2}}{12} - 3\lambda + 4$$

$$a_{7} = -\frac{\lambda^{2}}{6} + \frac{5\lambda}{3} - 4$$

$$a_{8} = \frac{\lambda^{2}}{36} - \frac{\lambda}{3} + 1$$

(The functions a_i are tabulated in table I and presented graphically in fig. 2.)

from which

$$y = \Delta \sqrt{\frac{p_{s}^{C}}{p}} \frac{t_{1}}{t_{s}} \left[\eta \left(1 + \frac{\gamma - 1}{2} M_{1}^{2} \right) - \frac{\gamma - 1}{2} M_{1}^{2} \sum_{i=2}^{8} \frac{a_{i} \eta^{i+1}}{i+1} \right]$$
(32)

8

where Δ is obtained from equation (21). The boundary-layer thickness is determined by letting η equal 1:

$$\delta = \Delta \sqrt{\frac{p_s C}{p}} \frac{t_1}{t_s} \left[1 + \frac{\gamma - 1}{2} M_1^2 \left(-0.0001 \lambda^2 - 0.0094 \lambda + 0.4175 \right) \right]$$
(33)

The momentum thickness is defined as

$$\theta = \int_{0}^{\delta} \frac{\rho u}{\rho_{\perp} u_{\perp}} \left(1 - \frac{u}{u_{\perp}}\right) dy$$
$$= \frac{t_{\perp}}{t_{s}} \sqrt{\frac{p_{s}C}{p}} \int_{0}^{\Delta} \frac{u}{u_{\perp}} \left(1 - \frac{u}{u_{\perp}}\right) dn$$
$$= \frac{t_{\perp}}{t_{s}} \sqrt{\frac{p_{s}C}{p}} \Theta$$
(34)

and the displacement thickness is

$$\delta^{*} = \int_{0}^{\delta} \left(1 - \frac{\rho u}{\rho l u l}\right) dy = \frac{t_{l}}{t_{s}} \sqrt{\frac{p_{s} c}{p}} \left[\int_{0}^{\Delta} \left(1 - \frac{u}{u l}\right) dn + \int_{0}^{\Delta} \left(\frac{t_{l}}{t_{l}} - 1\right) dn \right]$$
$$= \frac{t_{l}}{t_{s}} \sqrt{\frac{p_{s} c}{p}} \left[\Delta^{*} + \Delta \left(\frac{\gamma - 1}{2}\right) M_{l}^{2} \left(-0.0001\lambda^{2} - 0.0094\lambda + 0.4175\right) \right] (35)$$

The wall shear stress τ_w is defined as

$$\tau_{W} = \mu \left(\frac{\partial u}{\partial y}\right)_{W}$$
$$= \mu_{S} \sqrt{\frac{pC}{p_{S}}} \left(\frac{\partial u}{\partial n}\right)_{W}$$
$$= \frac{u_{I} \mu_{S}}{\Delta} \sqrt{\frac{pC}{p_{S}}} \left(2 + \frac{\lambda}{6}\right)$$
(36)

The separation point is defined as the point where the shear stress vanishes, or, from equation (36), where $\lambda = -12$. It is emphasized, however, that the Kármán-Pohlhausen solution has been found to be quite inaccurate in the neighborhood of a separation point.

SUMMARY OF METHOD

The results of this study will be summarized in the order they are needed for the solution of a particular problem. It is assumed that all free-stream conditions $\left(u_{1}, \frac{du_{1}}{dx}, M_{1}, t_{1}, p_{1}\right)$ are known functions of x. The standard conditions (v_{s}, p_{s}, t_{s}) are selected as mean values of the free-stream conditions. Next λ is determined as a function of x by solving equations (27) and (29) numerically:

$$\frac{dZ}{dx} = \frac{2}{u_1} \left[f_1(\lambda) f(M_1) + f_2(\lambda) \right]$$
(27)

$$Z = \frac{f_{1}(\lambda)}{\frac{du_{1}}{dx} \left(1 + \frac{\gamma - 1}{2} M_{1}^{2}\right)}$$
(29)

where

2285

$$f_{1}(\lambda) \equiv \lambda \left[\frac{1}{315} \left(37 - \frac{\lambda}{3} - \frac{5\lambda^{2}}{144} \right) \right]^{2}$$

$$f_{2}(\lambda) \equiv \frac{1}{315} \left(37 - \frac{\lambda}{3} - \frac{5\lambda^{2}}{144} \right) \left(2 - \frac{2\lambda}{15} + \frac{\lambda^{2}}{120} \right)$$

$$f(M_{1}) \equiv \frac{M_{1}^{2} - 4}{2 + (\gamma - 1) M_{1}^{2}}$$
(28)

A suggested procedure for solving equation (27) is presented in appendix B. All functions of λ and M_{l} are tabulated in tables I and II.

Once λ is known as a function of x, the following functions can be found:

$$\Delta = \sqrt{\frac{\lambda v_{\rm s}}{\frac{\mathrm{d}u_{\rm l}}{\mathrm{d}x} \left(1 + \frac{\gamma - 1}{2} M_{\rm l}^2\right)}} \tag{21}$$

.

1

$$\Theta = \frac{\Delta}{315} \left(37 - \frac{\lambda}{3} - \frac{5\lambda^2}{144} \right)$$
(22)

$$\Delta^* = \Delta \left(\frac{36 - \lambda}{120} \right) \tag{23}$$

and

$$\delta = \Delta \sqrt{\frac{p_s C}{p}} \frac{t_1}{t_s} \left[1 + \frac{\gamma - 1}{2} M_1^2 (-0.0001 \lambda^2 - 0.0094 \lambda + 0.4175) \right]$$
(33)

$$\theta = \frac{t_1}{t_s} \sqrt{\frac{p_s C}{p}} \Theta$$
 (34)

$$\delta^{*} = \frac{t_{1}}{t_{s}} \sqrt{\frac{p_{s}C}{p}} \left[\Delta^{*} + \Delta \left(\frac{\gamma - 1}{2} \right) M_{1}^{2} \left(-0.0001 \lambda^{2} - 0.0094 \lambda + 0.4175 \right) \right] (35)$$

$$\tau_{\rm w} = \frac{u_{\rm l}\mu_{\rm s}}{\Delta} \sqrt{\frac{p_{\rm c}}{p_{\rm s}}} \left(2 + \frac{\lambda}{6}\right) \tag{36}$$

and, for assumed values of $0 \le \eta \le 1$,

$$\frac{u}{u_{1}} = 2\eta - 2\eta^{3} + \eta^{4} + \lambda \left[\frac{1}{6} \eta (1-\eta)^{3}\right]$$
(20)

$$\frac{t}{t_{l}} = 1 + \frac{\gamma - 1}{2} M_{l}^{2} \left[1 - \left(\frac{u}{u_{l}} \right)^{2} \right]$$
(30)

.

The velocity and temperature profiles can then be found in terms of the physical (x,y) coordinate system by the following relation:

$$y = \Delta \sqrt{\frac{p_{s}C}{p}} \frac{t_{1}}{t_{s}} \left[\eta \left(1 + \frac{\gamma - 1}{2} M_{1}^{2} \right) - \frac{\gamma - 1}{2} M_{1}^{2} \sum_{i=2}^{8} \frac{a_{i} \eta^{i+1}}{i+1} \right]$$
(32)

where

2285

$$a_{2} = \frac{\lambda^{2}}{36} + \frac{2}{3}\lambda + 4$$

$$a_{3} = -\frac{\lambda^{2}}{6} - 2\lambda$$

$$a_{4} = \frac{5\lambda^{2}}{12} + \frac{4\lambda}{3} - 8$$

$$a_{5} = -\frac{5\lambda^{2}}{9} + \frac{5\lambda}{3} + 4$$

$$a_{6} = \frac{5\lambda^{2}}{12} - 3\lambda + 4$$

$$a_{7} = -\frac{\lambda^{2}}{6} + \frac{5\lambda}{3} - 4$$

$$a_{8} = \frac{\lambda^{2}}{36} - \frac{\lambda}{3} + 1$$

SPECIAL CASES

Solution near a stagnation point. - In the immediate neighborhood of a stagnation point, u_1 is equal to zero and the incompressible solution must apply. This solution is (reference 3):

$$\lambda_{0} = 7.052$$

$$Z_{0} = \frac{0.077}{\mathrm{du}_{1}/\mathrm{dx}}$$

$$\left(\frac{\mathrm{d}Z}{\mathrm{dx}}\right)_{0} = -0.0652 \frac{\mathrm{d}^{2}\mathrm{u}_{1}/\mathrm{dx}^{2}}{\mathrm{du}_{1}/\mathrm{dx}}$$

$$(37)$$

<u>Flat-plate solution</u>. - In the case of the flat plate, $\lambda = 0$ and the conditions at the outer edge of the boundary layer are constant and equal to the standard condition(s). Equation (27) therefore becomes

$$\frac{dZ}{dx} = \frac{2}{u_1} \left[f_1(0) f(M_1) + f_2(0) \right]$$
$$= \frac{0.470}{u_1}$$

and

.

$$Z = \frac{0.470 \text{ x}}{2}$$
(38)

From equations (25) and (34), the momentum thickness is

$$\theta = 0.685 \sqrt{\frac{v_{\perp} \times C}{u_{\perp}}}$$
(39)

The boundary-layer thickness is found from equations (22), (34), and (33) to be

$$\delta = 5.836 \sqrt{\frac{\nu_{\perp} \times C}{u_{\perp}}} \left[1 + 0.417 M_{\perp}^2 \left(\frac{\gamma - 1}{2} \right) \right]$$
(40)

The displacement thickness, from equations (23) and (35), is

$$\delta^* = 1.75 \sqrt{\frac{\nu_{\perp} \times C}{u_{\perp}}} \left[1 + 1.392 \left(\frac{\gamma - 1}{2} \right) M_{\perp}^2 \right]$$
(41)

and, from equation (36), the wall shearing stress is found to be

$$\tau_{w} = \frac{u_{l}\mu_{l}}{2.918} \sqrt{\frac{u_{l}C}{\nu_{l}x}}$$
(42)

Velocity and temperature profiles can be found as functions of η by letting λ vanish in equations (20) and (30), respectively. The relation of η and y can then be obtained from equation (32). The error introduced in the flat-plate solution by assuming that the velocity profile is a fourth-degree polynomial can be deduced by comparing these results with the results of reference 5:

$$\theta = 0.664 \sqrt{\frac{\nu_1 \mathbf{x} \mathbf{C}}{u_1}}$$
(43)

3

2285

$$\delta^* = 1.73 \sqrt{\frac{\nu_{\perp} \times C}{u_{\perp}}} \left[1 + 1.372 \left(\frac{\gamma - 1}{2} \right) M_{\perp}^2 \right]$$
(44)

$$\boldsymbol{\tau}_{\mathbf{w}} = \frac{\boldsymbol{\mu}_{\perp} \boldsymbol{u}_{\perp}}{3.02} \sqrt{\frac{\boldsymbol{u}_{\perp} C}{\boldsymbol{\nu}_{\perp} \mathbf{x}}}$$
(45)

Equations (43) and (45) apply for any Frandtl number, whereas equation (44) applies for Pr = 1 only.

It can therefore be seen that the results of the present analysis are quite accurate for the case of zero pressure gradient. No definite conclusions for the nonzero pressure gradient case can be made, however.

Lewis Flight Propulsion Laboratory National Advisory Committee for Aeronautics Cleveland, Ohio, August 8, 1951

APPENDIX A

TRANSFORMATION OF MANGLER

The laminar-boundary-layer equations for three-dimensional flows with axial symmetry are

$$\overline{u} \frac{\partial \overline{u}}{\partial \overline{x}} + \overline{v} \frac{\partial \overline{u}}{\partial \overline{y}} = -\frac{1}{p} \frac{d\overline{p}}{d\overline{x}} + \frac{1}{p} \frac{\partial}{\partial \overline{y}} \left(\overline{\mu} \frac{\partial \overline{u}}{\partial \overline{y}} \right)$$
(A1)

$$\frac{\partial}{\partial \overline{x}} \left(\overline{p} r_0 \overline{u} \right) + \frac{\partial}{\overline{q} \overline{b}} \left(\overline{p} r_0 \overline{u} \right) = 0$$
 (A2)

$$\overline{\rho}c_{p}\left[\overline{u}\,\frac{\partial\overline{t}}{\partial\overline{x}} + \overline{v}\,\frac{\partial\overline{t}}{\partial\overline{y}}\right] = \overline{u}\,\frac{\partial\overline{p}}{\partial\overline{x}} + \frac{\partial}{\partial\overline{y}}\left(\overline{k}\,\frac{\partial\overline{t}}{\partial\overline{y}}\right) + \overline{\mu}\left(\frac{\partial\overline{u}}{\partial\overline{y}}\right)^{2}$$
(A3)

where the bar is used to differentiate the three-dimensional from the two-dimensional quantities, and $r_0(x)$ defines the radial coordinate of the body in a meridional plane. The continuity equation is satisfied by the following stream function:

$$r_{0} \overline{\rho} \overline{u} = \frac{\partial \overline{\psi}}{\partial \overline{y}}$$
(A4)
$$r_{0} \overline{\rho} \overline{v} = -\frac{\partial \overline{\psi}}{\partial \overline{x}}$$

The following transformation variables were introduced by Mangler (unavailable report):

$$x = K^{2} \int_{0}^{\overline{x}} r_{0}^{2}(\overline{x}) d\overline{x}$$

$$y = K r_{0}(\overline{x}) \overline{y}$$
(A5)

where K is an arbitrary constant. Thus

2285

$$\frac{\partial}{\partial \overline{x}} = Kr_0^2 \frac{\partial}{\partial y} + \frac{yr_0^*}{r_0} \frac{\partial}{\partial y}$$

where the prime indicates differentiation with respect to $\overline{\mathbf{x}}$.

It is further assumed that

$$\overline{p}(\overline{x},\overline{y}) = p(x,y)$$

$$\overline{t}(\overline{x},\overline{y}) = t(x,y)$$

$$\overline{\mu}(\overline{x},\overline{y}) = \mu(x,y)$$

$$\overline{\rho}(\overline{x},\overline{y}) = \rho(x,y)$$

$$\overline{\psi}(\overline{x},\overline{y}) = \frac{1}{K} \psi(x,y)$$

Equations (A1), (A2), and (A3) can then be transformed to the following form:

$$u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} = -\frac{1}{\rho} \frac{dp}{dx} + \frac{1}{\rho} \frac{\partial}{dy} \left(\mu \frac{\partial u}{dy} \right)$$
(A6)

$$\frac{\partial}{\partial x}(\rho u) + \frac{\partial}{\partial y}(\rho v) = 0$$
 (A7)

$$\rho c_{p} \left(u \frac{\partial t}{\partial x} + v \frac{\partial y}{\partial y} \right) = u \frac{\partial x}{\partial x} + \frac{\partial y}{\partial y} \left(k \frac{\partial y}{\partial y} \right) + \mu \left(\frac{\partial u}{\partial y} \right)^{2}$$
(A8)

where

$$u(\mathbf{x},\mathbf{y}) = \overline{u}(\overline{\mathbf{x}},\overline{\mathbf{y}})$$

$$v(\mathbf{x},\mathbf{y}) = \frac{1}{Kr_0} \left[\overline{v}(\overline{\mathbf{x}},\overline{\mathbf{y}}) - \frac{yr_0!}{Kr_0^2} \overline{u}(\overline{\mathbf{x}},\overline{\mathbf{y}}) \right]$$
(A9)

Equations (A6), (A7), and (A8) are now identical to equations (3), (4), and (5). The solution of these equations, as presented in the text of

19

. بر

(All)

this report, therefore applies to the three-dimensional problem, but the final results must be retransformed to the three-dimensional quantities. The boundary-layer thickness δ is not defined in a solution of the differential boundary-layer equations, but its definition is required for the solution of the integral equation. The transformation of δ can best be accomplished by examining the velocity profiles:

$$\frac{\underline{u}}{\underline{u}_{\perp}} = \frac{\underline{u}}{\underline{u}_{\perp}} \left(\frac{\underline{y}}{\underline{\delta}} \right)$$
$$\frac{\overline{\underline{u}}}{\overline{\underline{u}}_{\perp}} = \frac{\overline{\underline{u}}}{\overline{\underline{u}}_{\perp}} \left(\frac{\overline{\underline{y}}}{\underline{\delta}} \right)$$

.

From equation (A9), however,

$$\frac{u}{u_{1}} = \frac{\overline{u}}{\overline{u}_{1}}$$

It therefore follows that

$$\frac{y}{\delta} = \frac{\overline{y}}{\overline{\delta}}$$

whence, from equation (A5),

$$\delta = Kr_0(\overline{x}) \overline{\delta}$$
 (A10)

The momentum thickness is transformed as follows:

$$\overline{\theta}(\overline{\mathbf{x}}) = \int_{0}^{\overline{\delta}} \frac{\overline{u}}{\overline{u}_{1}} \left(1 - \frac{\overline{\rho} \cdot \overline{u}}{\overline{\rho}_{1} \overline{u}_{1}}\right) d\overline{\mathbf{y}}$$
$$= \frac{1}{\mathrm{Kr}_{0}} \int_{0}^{\overline{\delta}} \frac{u}{u_{1}} \left(1 - \frac{\rho \cdot u}{\rho_{1} u_{1}}\right) d\mathbf{y}$$
$$= \frac{1}{\mathrm{Kr}_{0}} \theta(\mathbf{x})$$

and similarly,

$$\overline{\delta}^{*}(\overline{\mathbf{x}}) = \frac{1}{\mathrm{Kr}_{\mathrm{O}}} \, \delta^{*}(\mathbf{x})$$

$$\overline{\tau}_{\mathrm{W}}(\overline{\mathbf{x}}) = \mathrm{Kr}_{\mathrm{O}} \, \tau_{\mathrm{W}}(\mathbf{x})$$

where the quantities without the bar (representing two-dimensional quantities) are given by equations (33) to (36).

Therefore, if it is desired to determine any of the boundary-layer characteristics at a distance \bar{x} from the nose of an axially symmetric body, the corresponding two-dimensional distance x is first found from equation (A5). The two-dimensional quantities (δ , δ^* , θ , τ_w , and so forth) are then found using equations (33) to (36), and are transformed to the three-dimensional quantities at \bar{x} through the use of equations (A10) to (A12). The transformation applies for flows with or without streamwise pressure gradients.

21

(A12)

APPENDIX B

SOLUTION OF DIFFERENTIAL EQUATION BY RUNGE-KUTTA METHOD

The Runge-Kutta method of finite differences (reference 6) has been found to be very satisfactory for solving equation (27). It is believed that a detailed discussion of the method, as applied to the present problem, will be of help to the reader.

	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)
	x	ul	$\frac{du_1}{dx}$	Ml	f(M _l)	$1 + \frac{\gamma - 1}{2} M_1^2$	Z	f _l (λ)	λ	$f_2(\lambda)$	k
1	0						Z _O				k1
2	h/2						$Z_0 + \frac{1}{2} k_1$				^k 2
3	h/2						$Z_0 + \frac{1}{2} k_2$				k3
4	h						$Z_0 + k_3$				k4
5	h						^z ב				к1
6	$h + \frac{h}{2}$						$Z_1 + \frac{1}{2} k_1$				^k 2
7	$h + \frac{h}{2}$						$Z_1 + \frac{1}{2} k_2$				k ₃
8	2h						$Z_1 + k_3$				k4

It is suggested that a table of the following form be used:

The distance along the body (x) is subdivided into a number of increments h, and the free-stream variables u_1 , du_1/dx , and M_1 at each point are tabulated in columns (2), (3), and (4). Column (5) follows from equation (28), and column (6) is easily tabulated. Columns (1) to (6) can be tabulated for all x, whereas for columns (7) to (11), each row must be calculated separately.

The value of $Z_0 = \Theta_0^2 / v_s$ (column (7), row 1) is given by equation (37) for stagnation-point flow, or is equal to zero if $\Theta_0 = 0$. The value of $f_1(\lambda)$ (column 8) is obtained from equation (29), or in column notation,

 $f_1(\lambda) = (7)(3)(6)$

2285

Columns (9) and (10) are obtained from figure (1). Column (11) lists the Runge-Kutta parameter k, which in column notation is

$$k = \frac{2}{(2)} (8)(5) + (10) h$$

Rows 1 to 4 can now be completed in this manner. At the completion of row 4 the total increment in Z can be computed using the following equation:

$$\Delta Z = \frac{1}{6} (k_1 + 2k_2 + 2k_3 + k_4)$$

The entire process is then repeated for rows 5 to 8. The value of Z_1 (column (7), row 5) is equal to $Z_0 + \Delta Z$. The procedure is carried out for all increments of x, and as a result λ is obtained as a function of x.

REFERENCES

- Howarth, L.: Concerning the Effect of Compressibility on Laminar Boundary Layers and Their Separation. Proc. Roy. Soc. (London), ser. A, vol. 194, no. A1036, July 28, 1948, pp. 16-42.
- 2. Lees, Lester: The Stability of the Laminar Boundary Layer in a Compressible Fluid. NACA Rep. 876, 1947. (Formerly NACA TN 1360.)
- 3. Schlichting, H.: Lecture Series "Boundary Layer Theory." Part I -Laminar Flows. NACA TM 1217, 1949, pp. 93-100.
- 4. Rubesin, M. W., and Johnson, H. A.: A Critical Review of Skin-Friction and Heat-Transfer Solutions of the Laminar Boundary Layer of a Flat Plate. Trans. A.S.M.E., vol. 71, no. 4, May 1949, pp. 383-388.
- 5. Chapman, Dean R., and Rubesin, Morris W.: Temperature and Velocity Profiles in the Compressible Laminar Boundary Layer with Arbitrary Distribution of Surface Temperature. Jour. Aero. Sci., vol. 16, no. 9, Sept. 1949, pp. 547-565.
- 6. Scarborough, James B.: Numerical Mathematical Analysis. Johns Hopkins Press (Baltimore), 1930, pp. 273-274.

1.0		-																									
2 + X /6	•	4.000	3.833	3.667	3.500	3.333	3.167	3,000	2.833	2.667	2.500	2.333	2.167	2.000	1. 833	1. 667	1. 500	1.1 33	1.1 67	1. 000	.833	.667	•500	.333	.167	0	NACA
Θ/Δ	-	0.0889	.0925	.0958	.0990	•101•	.1047	TUT.	.1094	.1115	.1133	.1149	.1163	.1175	.1184	.1191	.1197	.1199	.1200	.1198	.1195	.1189	.1181	0/11.	.1158	.1143	م مر
∆*/∆	•	0.2000	.2083	.2167	.2250	.2333	.2417	.2500	.2583	.2667	.2750	.2833	.2917	.3000	.3083	.3167	.3250	.3333	.3417	.3500	.3583	.3667	.3750	. 3833	.3917	•4000	- - - -
-0.0001λ ²	-0.0094) +0.4175	0.2888	.3008	.3125	.3240	.3353	.3463	.3572	.3678	.3782	• 3883	.3983	.4080	.4175	.4268	.4358	.4447	.4533	.4617	.4699	.4778	.4855	.4930	. 5003	.5074	.5142	
o B	0	1.000	.694	.445	.250	.111	.028	0	.028	.111	.250	.445	.694	1.000	1.361	1.778	2.250	2.778	3.361	4.000	4.694	5.445	6.250	7.111	8.028	9.000	
87 1	~	-8.000	-5.833	-4.000	-2.500	-1.333	500	0	.167	0	- 500	-1.333	-2.500	-4.000	-5.833	-8.000	-10.500	-13.333	-16.500	-20.000	-23.833	-28.000	-32.500	-37.333	-42.500	-48.000	
មិន	D	28.000	21.417	15.667	10.750	6.667	3.417	1.000	- 583	-1.333	-1.250	333	1.417	4.000	7.417	11.667	16.750	22.667	29.417	37.000	45.417	54.667	64.750	75.667	87.417	100.000	
ង	ი	-56.000	-44.889	-34.889	-26.000	-18.221	-11.556	-6.000	-1.555	1. 778	4.000	5.111	5.111	4.000	J. 778	-1.555	-6.000	-11.556	-18.221	-26.000	-34.889	-44.889	-56.000	-68.222	-81.556	-96.000	
8	4	68.000	57.084	47.000	37.750	29.334	21.750	15.000	9.084	4.000	250	-3.667	-6.250	-8.000	-8.917	-9.000	-8.250	-6.667	-4.250	-1.000	3.084	8.000	13. 750	20.333	27.750	36.000	
ង្ខ័	p	-48.000	-42.167	-36.667	-31.500	-26.667	-22.167	-18.000	-14.167	-I0.667	-7.500	-4.667	-2.167	0	1.833	3.333	4.500	5.333	5.833	6.000	5.833	5.333	4.500	3.333	I. 833	0	
св С	U	16.000	14.695	13.444	12.250	11.11	10.028	9.000	8.028	7.111	6.250	5.445	4.694	4.000	3.361	2.778	2.250	J.778	1.361	1.000	.695	•444	.250	.111	.028	0	
$f_{\alpha}(\lambda)$		0.1422	.1426	.1 438	.1461	.1495	.1544	.1608	.1687	.1784	.1898	.2030	.2181	.2350	.2536	.2742	.2963	.3200	.3450	.3717	.3992	.4279	.4576	.4874	•5181	.5486	
f. (V)	-	0.0948	.0941	.0920	.0882	.0831	.0767	.0689	.0599	.0497	.0385	.0264	.0135	0	0140	0284	0429	0575	0720	0862	0999	1130	1255	1369	1474	1567	
~		12	H	5	ດ	ω	7	9	Ω	4	Ю	N	Ч	ō	Ч Ч	21	δ. I	4	ĥ	0	- 1	8	ဂီ၊	-10	Ę	-12	

TABLE I - FUNCTIONS OF N

24

NACA TN 2531

2285

...

TABLE II - FUNCTIONS OF M1

Ml	$\frac{\gamma-1}{2} M_1^2$	$1 + \frac{\gamma - 1}{2} M_1^2$	f(M _l)	M _l	$\frac{\gamma-1}{2} M_1^2$	$1 + \frac{\gamma - 1}{2} M_1^2$	f(M _l)
0	0	1.000	-2.000	2.2	0.968	1.968	0.213
.2	.008	1.008	-1.974	2.4	1.152	2.152	.409
.4	.032	1.032	-1.861	2.6	1.352	2.352	.589
.6	.072	1.072	-1.698	2.8	1.568	2.568	.748
.8	.128	1.128	-1.489	3.0	1.800	2.800	.893
1.0	.200	1.200	-1.250	3.2	2.048	3.048	1.024
1.2	.288	1.288	994	3.4	2.312	3.312	1.141
1.4	.392	1.392	733	3.6	2.592	3.592	1.247
1.6	.512	1.512	476	3.8	2.880	3.880	1.343
1.8	.648	1.648	231	4.0	3.200	4.200	1.500
2.0	.800	1.800	0				

$$[\gamma = 1.40]$$

.

-





.



Figure 2. - Auxiliary functions used in equations (31) and (32).

.

٠

₩.



Figure 2. - Concluded. Auxiliary functions used in equations (31) and (32).

NACA TN 2531 National Advisory Committee for Aeronautics. SIMPLIFIED METHOD FOR CALCULATION OF COMPRESSIBLE LAMINAR BOUNDARY LAYER WITH ARBITRARY FREE-STREAM PRESSURE WITH ARBITRARY FREE-STREAM PRESSURE GRADIENT. George M. Low. October 1951. 28p. diagrs., 2 tabs. (NACA TN 2531)	 Flow, Compressible Flow, Laminar (1.1.2) Low, George M. NACA TN 2531 	NACA TN 2531 National Advisory Committee for Aeronautics. SIMPLIFIED METHOD FOR CALCULATION OF COMPRESSIBLE LAMINAR BOUNDARY LAYER WITH ARBITRARY FREE-STREAM PRESSURE GRADIENT. George M. Low. October 1951. 28p. diagrs., 2 tabs. (NACA TN 2531)	 Flow, Compressible Flow, Laminar (1.1.2) Flow, Laminar (1.1.3.1) Low, George M. NACA TN 2531
The Kármán-Polhausen method, as applied to com- pressible laminar boundary layers, is simplified by an analysis similar to the incompressible Holstein- Bohlen method. The analysis is carried out under the assumptions of a Prandtl number of 1, zero heat transfer, and a linear viscosity-temperature relation. Results are presented so that velocity and tempera- ture profiles, momentum and displacement thick- nesses, and wall shear stress can be calculated for flows over two-dimensional bodies with arbitrary free-stream velocity distributions. The results are also applicable to flows over three-dimensional(over) Copies obtainable from NACA, Washington	MACA	The Kármán-Polhausen method, as applied to com- pressible laminar boundary layers, is simplified by an analysis similar to the incompressible Holstein- Bohlen method. The analysis is carried out under the assumptions of a Prandtl number of 1, zero heat transfer, and a linear viscosity-temperature relation. Results are presented so that velocity and tempera- ture profiles, momentum and displacement thick- nesses, and wall shear stress can be calculated for flows over two-dimensional bodies with arbitrary free-stream velocity distributions. The results are also applicable to flows over three-dimensional(over) Copies obtainable from NACA, Washington	NACA
NACA TN 2531 National Advisory Committee for Aeronautics. SIMPLIFIED METHOD FOR CALCULATION OF COMPRESSIBLE LAMINAR BOUNDARY LAYER WITH ARBITRARY FREE-STREAM PRESSURE GRADIENT. George M. Low. October 1951. 28p. diagrs., 2 tabs. (NACA TN 2531)	 Flow, Compressible Flow, Laminar (1.1.2) Low, George M. NACA TN 2531 	NACA TN 2531 National Advisory Committee for Aeronautics. SIMPLIFIED METHOD FOR CALCULATION OF COMPRESSIBLE LAMINAR BOUNDARY LAYER WITH ARBITRARY FREE-STREAM PRESSURE WITH ARBITRARY FREE-STREAM PRESSURE GRADIENT. George M. Low. October 1951. 28p. diagrs., 2 tabs. (NACA TN 2531)	 Flow, Compressible Flow, Laminar (1.1.2) Low, George M. NACA TN 2531
The Kármán-Polhausen method, as applied to com- pressible laminar boundary layers, is simplified by an analysis similar to the incompressible Holstein- Bohlen method. The analysis is carried out under the assumptions of a Prandtl number of 1, zero heat transfer, and a linear viscosity-temperature relation. Results are presented so that velocity and tempera- ture profiles, momentum and displacement thick- nesses, and wall shear stress can be calculated for flows over two-dimensional bodies with arbitrary free-stream velocity distributions. The results are also applicable to flows over three-dimensional(over) Copies obtainable from NACA, Washington	NACA	The Kármán-Polhausen method, as applied to com- pressible laminar boundary layers, is simplified by an analysis similar to the incompressible Holstein- Bohlen method. The analysis is carried out under the assumptions of a Prandtl number of 1, zero heat transfer, and a linear viscosity-temperature relation. Results are presented so that velocity and tempera- ture profiles, momentum and displacement thick- nesses, and wall shear stress can be calculated for flows over two-dimensional bodies with arbitrary free-stream velocity distributions. The results are also applicable to flows over three-dimensional(over) Copies obtainable from NACA, Washington	NACA

bodies with axial symmetry through the use of Mangler's transformation.

NACA TN 2531

bodies with axial symmetry through the use of Mangler's transformation.

Copies obtainable from NACA, Washington

NACA TN 2531

bodies with axial symmetry through the use of Mangler's transformation.



Copies obtainable from NACA, Washington

NACA TN 2531

bodies with axial symmetry through the use of Mangler's transformation.







Copies obtainable from NACA, Washington

Copies obtainable from NACA, Washington

P