Data Data Number 10 and Description of Advances of Data Part Part of Data Part Part Part Part Part Part Part P	REPORT DOCUMENTATION PAGE					OMB No. 0704-0188	
REFORT DATE COLL. 94 - 2.5 Jal. 0         Store         TITLE AND SUBTILE         Hybrid Optical /Digital Imaging for Automatic Inspection         Automatic Inspection         Performing ORGANIZATION NAME(S) AND ADDRESS(ES)         Inspection Tole         Inspection Tole <t< th=""><th>The public reporting burden for thi pathering and maintaining the data of information, including suggesti 0704-01880, 1215 Jefferson Davi jubject to any penalty for failing to PLEASE DO NOT RETURN</th><th>s collection of information needed, and completing and ons for reducing the burd s Highway, Suite 1204, And comply with a collection of YOUR FORM TO TH</th><th>is estimated to average 1 hour d reviewing the collection of info en, to Department of Defense ington, VA 22202-4302. Resp information if it does not displa- IE ABOVE ADDRESS.</th><th>per response, inclu rmation. Send com b, Washington Hea ondents should be y a currently valid (</th><th>iding the tin mments regaind adquarters S aware that OMB control</th><th>In the for reviewing instructions, searching existing data sources raing this burden estimate or any other aspect of this collectio Services, Directorate for Information Operations and Report notwithstanding any other provision of law, no person shall b number.</th></t<>	The public reporting burden for thi pathering and maintaining the data of information, including suggesti 0704-01880, 1215 Jefferson Davi jubject to any penalty for failing to PLEASE DO NOT RETURN	s collection of information needed, and completing and ons for reducing the burd s Highway, Suite 1204, And comply with a collection of YOUR FORM TO TH	is estimated to average 1 hour d reviewing the collection of info en, to Department of Defense ington, VA 22202-4302. Resp information if it does not displa- IE ABOVE ADDRESS.	per response, inclu rmation. Send com b, Washington Hea ondents should be y a currently valid (	iding the tin mments regaind adquarters S aware that OMB control	In the for reviewing instructions, searching existing data sources raing this burden estimate or any other aspect of this collectio Services, Directorate for Information Operations and Report notwithstanding any other provision of law, no person shall b number.	
(6/00)       Final Report       ILC JULE 44 - 15 Jule of The Alto SubTITE         THE AND SUBTITE       Final Report       ILC JULE 44 - 15 Jule of The Alto SubTITE         Hybrid Optical/Digital Imaging for Automatics Inspection       Scottact # DAAD19-99-C-0043         Automatics Inspection       Scottact # DAAD19-99-C-0043         Scottact # DAAD19-99-C-0043       Scottact # DAAD19-99-C-0043         Scottact # DaaD19-90-Cottact # DAAD19-99-C-0043       Scottact # DAAD19-99-C-0043         Scottact # DaaD19-90-Cottact #	1. REPORT DATE (DD-MN	-YYYY) 2. REPO	RT TYPE			3. DATES COVERED (From - To)	
TITLE AND SUBTITE       I.G. CONTRACT (PADL9)-99-C-0043         Automatic Inspection       Contract # PADL9-99-C-0043         State of the section       Sc. GRANT NUMBER         Automatic Inspection       Sc. PROGRAM ELEMENT NUMBER         Automatic Inspection       Sc. PROGRAM ELEMENT NUMBER         Automatic Inspection       Sc. PROGRAM ELEMENT NUMBER         Automatic Inspection       Sc. PROJECT NUMBER         Automatic Inspection       Sc. PROJECT NUMBER         Sc. WORK UNIT NUMBER       Sc. TASK NUMBER         Sc. TASK NASCL-ROCALL AND ADDRESS(ES)       Sc. TASK NUMBER         Sc. Sc. Army Research	4/8/00	Final	Report		5- 00	1 26 JUL 74 - 25 JUL OC	
Ryprid Optical/Digital Imaging for Automatic Inspection       Contract # DADIS-99-C-0043         Automatic Inspection       50. GRANT NUMBER         AUTHORISI       50. GRANT NUMBER         Sdward. R. Dowski, Jr.       54. PROJECT NUMBER         St. WORK UNIT NUMBER       54. PROJECT NUMBER         Soldadr, Colorado 80303       50. GRANT VOMBER         Soldadr, Colorado 80303       50. SPONSORIMONTORIG AGENCY NAME(S) AND ADDRESS(ES)       10. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> . S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> 10. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> . O. Box 12211       11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> 10. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> . O. Box 12211       11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> 10. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> . O. Box 12211       11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> 11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> . O. Box 12211       11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> 11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> . SUPPLEMENTARY NOTES       11. SPONSOR/MONITOR'S ACRO	4. TITLE AND SUBTITLE						
AUTHOR(S)       56. PROGRAM ELEMENT NUMBER         Sdward. R. Dowski, Jr.       54. PROJECT NUMBER         Sdward. R. Dowski, Jr.       55. TASK NUMBER         St. WORK UNIT NUMBER       57. WORK UNIT NUMBER         DOI Discovery Drive Suite 300 Soulder, Colorado 80303       5. PERFORMING ORGANIZATION REPORT NUMBER         TYN. ANSEL.RO.RI (Sylvia Hall)       10. SPONSORIMONITOR'S ACRONYM(S)         . S. Army Research Office TYN: ANSEL.RO.RI (Sylvia Hall)       10. SPONSORIMONITOR'S ACRONYM(S)         . OS N 12211 Sesarch Triangle Park, NC       11. SPONSORIMONITOR'S REPORT NUMBER(S)         . DOYLOG for public release       11. SPONSORIMONITOR'S REPORT NUMBER(S)         . SUPPLEMENTARY NOTES       I. SUPPLEMENTARY NOTES         Report Developed under STTR contract for topic 'Army 99 T001'.       .         . ABSTRACT uning this project a revolutionary system for digital imaging was demonstrated. This system is ared on the asyl-developed andigital scholingly processing to Carding (WrC). WTC employee and for field and depth of focus. WTC can also simutaneously decrease the size, weight, and cost of a variety of digital imaging ythermalizer in spytem showed revolutionary increases in performance. Application MC sinceoper as also shown o passively athermalizer in agoing systems, har code scanners, and machine vision systems. WTC systems were also shown or passively athermalizer code scanners, and machine vision systems. For lutther normation see STTR Report.         SUBJECT TEMMS       11. LIMITION OF ASTRACT I UU       18. NAME OF RESPONSUELE PERSON Edward R. Dow	Hybrid Optical/I Automatic Inspec	igital imaging	LOL		5b. GRA	ANT NUMBER	
AUTHOR(S)       5d. PROJECT NUMBER         Sdward. R. Dowski, Jr.       5d. PROJECT NUMBER         Sdward. R. Dowski, Jr.       5d. PROJECT NUMBER         Status       5f. WORK UNIT NUMBER         Status       5f. WORK UNIT NUMBER         DOI Discovery Drive       5f. WORK UNIT NUMBER         Suite 390       3001der, Colorado 80303         SPONSORIKOMONTORIMA GENCY NAME(S) AND ADDRESS(ES)       10. SPONSOR/MONITOR'S ACRONYM(S)         V. S. Army Research Office       11. sponsor/monitor's acconvertice         TTN: AMSL-RO-RI (Sylvia Hall)       11. sponsor/monitor's acconvertice         .O. Box 12211       11. sponsor/monitor's acconvertice         LOSTRIBUTION/AVAILABILITY STATEMENT       Pproved for public release         I. SUPPLEMENTARY NOTES       10. SPONSOR/MONITOR'S acconvertice         Report Developed under STTR contract for topic "Army 99 T001".       Acc 40 2 3 0 . 1 - PH - ST 1         ASSTRACT       Army fight a project a revolutionary system for digital imaging was demonstrated. This system is ased in the asely-developed inging technology of Wavefront Coding (WFC). WFC employs ased and indigital imaging systems. A high-magnification WFC microscope was constructed indigital imaging systems. Dr further figure systems. WFC systems were also shown or passively athermalize IR imaging systems. A high-magnification WFC microscope was constructed intary systems, bar code scanners, and machine vision systems. For further figure intaging systems. A code scanners, and machine vision sys					5c. PRC	OGRAM ELEMENT NUMBER	
Edward. R. Dowski, Jr.       5. TASK NUMBER         FERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)       5. WORK UNIT NUMBER         DID Discovery Drive       5. PERFORMING ORGANIZATION         Suite 390       30ulder, Colorado 80303         SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)       10. SPONSOR/MONITOR'S ACRONYM(S)         ., S. Army Research Office       10. SPONSOR/MONITOR'S ACRONYM(S)         ., S. Army Research Office       10. SPONSOR/MONITOR'S ACRONYM(S)         ., S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S)         ., S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S)         ., S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S)         ., Supplementance       11. SPONSOR/MONITOR'S ACRONYM(S)         ., SUPPLEMENTARY NOTES       11. SPONSOR/MONITOR'S ACRONYMUS)         teport Developed under STTR contract for topic "Army 99 T001".       .         . ABSTRACT	5. AUTHOR(S)	<u></u>			5d. PRC	DJECT NUMBER	
Schward, K. Dowski, Gr.         Set TASK NUMBER         St. WORK UNIT NUMBER         DM Optics, Inc.         1010 Discovery Drive         Suite 390         Soulder, Colorado 80303         SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)         .S. ATRY Research Office         TTM: AMSRL-RO-RI (Sylvia Hall)         .O. Box 12211         .seearch Triangle Park, NC         7709-2211         DistRUTION/AVAILABILITY STATEMENT         pproved for public release         I. SUPPLEMENTARY NOTES         tegort Developed under STTR contract for topic "Army 99 T001".         ABSTRACT         uring this project a revolutionary system for digital imaging was demonstrated. This system is actively developed imaging technology of Wavefront Coding (WFC). WFC employs pecialized aspheric optics and digital signal processing to greatly increase the depth of field ind depth of focus. WFC can also simutaneously decrease the size, weight, and cost of a variety f digital imaging systems. During this effort new WFC single lens systems were designed and opasitory increases in performace. Applications of Mavefront coding of the systems were designed and or systems. For further information see STTR Report.         SUBJECT TERMS       11. LINITATION OF ABSTRACT or THEPAGE         Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging         SECURITY CLASSIFICATION OF:       11. LINITATION OF ABSTRACT or THEPAGE </td <td>-1 1 5 5</td> <td>-i T-n</td> <td></td> <td></td> <td></td> <td></td>	-1 1 5 5	-i T-n					
57. WORK UNIT NUMBER         PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)         DM Optics, Inc.         1001 Discovery Drive         Suite 390         3011der, Colorado 80303         SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)         , S. Army Research Office         TTN: AMSRL-RO-RI (Sylvia Hall)         .0. Box 12211         research Triangle Park, NC         7709-2211         DISTRIBUTION/AVAILABILITY STATEMENT         pproved for public release         I. SUPPLEMENTARY NOTES         teport Developed under STTR contract for topic "Army 99 T001".         ABSTRACT         uring this project a revolutionary system for digital imaging was demonstrated. This system is aged on the newly-developed imaging technology of Wavefront Ooding (MPC). WPC employs are designed and imulated that can perform as well as expensive multi-line systems. WFC systems were designed and imulated that can perform as well as expensive multi-lines systems. WFC systems were designed and materials microscopy, endoscopy, inexpensive difficultion were fully increase the depth of field mages from this system showed revolutionary increases in performance. Applications of Wavefront toding wavefront were designed and materials microscopy, endoscopy, inexpensive mitri-line systems. For further information see STTR Report.         SUBJECT TERMS       Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging         Digital imaging, Wavefront Coding, single-lens imaging, athermalizatio	Edward. R. Dows	1, Jr.			5e. TAS	SK NUMBER	
PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)       8. PERFORMING ORGANIZATION         DM Optics, Inc.       101 Discovery Drive         Suite 390       3011der, Colorado 80303         SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)       10. SPONSOR/MONITOR'S ACRONYM(S)         . S. Army Research Office       TTM: AMSRL-RO-RI (Sylvia Hall)         ?O. Box 12211       11. SPONSOR/MONITOR'S ACRONYM(S)         Lesearch Triangle Park, NC       7709-2211         . DISTRIBUTION/AVAILABILITY STATEMENT       Pproved for public release         Supplementary wortes       4.80 40230.1-PH-STI         LOSTRIBUTION/AVAILABILITY STATEMENT       ARO 40230.1-PH-STI         pporved for public release       5. SUPPLEMENTARY NOTES         Lesport Developed under STTR contract for topic "Army 99 T001".       .         ASSTRACT       uring this project a revolutionary system for digital imaging was demonstrated. This system is ased on the newly-developed imaging technology of Wavefront Coding (WFC). WFC employs ases from this systems. WFC can also simutaneously decrease the size, weight, and cost of a variety increase from this systems. During this effort new WC single lens systems. WerC sophematic network induce high magnification WFC mempleys onstructed.         ages from this system showed revolutionary increases in performance. Applications of Wavefront oding include high magnification WFC mempleys onstructed.         ages from this system, bar code scanners, and machine vision systems. For further nformation see STTR					5f. WO		
PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)       8. PERFORMING ORGANIZATION         DCM Optics, Inc.       1001 Discovery Drive         Suite 390       3001der, Colorado 80303         SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)       10. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> , S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S) <sup>-</sup> TTN: AMSRL-RO-RI (Sylvia Hall)       10. SPONSOR/MONITOR'S REPORT         .O. Box 12211       research Triangle Park, NC         ?709-2211       11. SPONSOR/MONITOR'S REPORT         DISTRIBUTION/AVAILABILITY STATEMENT       pporved for public release         Pporved for public release							
DD Optics, Inc.       REPORT NUMBER         1001 Discovery Drive       30         3001der, Colorado 80303       10. SPONSOR/MONITORING AGENCY NAME(S) AND ADDRESS(ES)       10. SPONSOR/MONITOR'S ACRONYM(S)         . S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S)         . TTY: AMSL-RO-RI (Sylvia Hall)	7. PERFORMING ORGANI	ZATION NAME(S) AN	D ADDRESS(ES)		L	8. PERFORMING ORGANIZATION	
Boulder, Colorado 80303         SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)        S. Army Research Office         TTN: AMSL-RO-RI (Sylvia Hall)         D.O. Box 12211         tessarch Triangle Park, NC         7709-2211         DISTRIBUTION/AVAILABILITY STATEMENT         pproved for public release         Supplementation of the newly-developed imaging technology of Wavefront Coding (WFC). WFC employs         pecialized aspheric optics and digital signal processing to greatly increase the depth of field         nd depth of focus. WFC can also simutaneously decrease the size, weight, and cost of a variety         f digital imaging systems. A high-magnification WFC systems were designed and         inituate imaging systems. A high-magnification WFC systems were also shown         o passively athermalize IR imaging systems. A high-magnification WFC microscope was constructed.         Mages from this system, show a code scanners, and materials microscopy, endoscoy, inexpensive         initature imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging         SUBJECT TERMS         Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging         SECURITY CLASSIFICATION OF:       17. LIMITATION OF       18. NUMBER OF       19. NAME OF RESPONSIBLE PERSON         B. REPORT       b. ABSTRACT       IT       IT       IT       It	CDM Optics, Inc. 4001 Discovery I Suite 390	Drive					
SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)       10. SPONSOR/MONITOR'S ACRONYM(S)         Y. S. Army Research Office       11. SPONSOR/MONITOR'S ACRONYM(S)         Y. S. Army Research Office       11. SPONSOR/MONITOR'S REPORT         Y. O. Box 12211       11. SPONSOR/MONITOR'S REPORT         Userarch Triangle Park, NC       7709-2211         DISTRIBUTION/AVAILABILITY STATEMENT       Pproved for public release         S. SUPPLEMENTARY NOTES       Image for digital imaging was demonstrated. This system is ased on the newly-developed imaging technology of Wavefront Coding (WFC). WFC employs pecialized aspheric optics and digital signal processing to greatly increase the depth of field nd depth of focus. WFC can also simutaneously decrease the size, weight, and cost of a variety of digital imaging systems. During this effort new WFC single lens systems were designed and imulated that can perform as well as expensive multi-lens systems. WFC systems were also shown o passively athermalize IR imaging systems. A high-magnification WFC microscope was constructed. Mayefront toding include high magnification biological and materials microscopy, endoscopy, inexpensive information see STTR Report.         S. SUBJECT TERMS       Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging         S. SECURITY CLASSIFICATION OF:       17. LIMITATION OF ABSTRACT C. THIS PAGE UU         T       T	Boulder, Colorad	lo 80303					
2. DISTRIBUTION/AVAILABILITY STATEMENT pproved for public release 3. SUPPLEMENTARY NOTES teport Developed under STTR contract for topic "Army 99 T001". 4. ABSTRACT uring this project a revolutionary system for digital imaging was demonstrated. This system is tased on the newly-developed imaging technology of Wavefront Coding (WFC). WFC employs pecialized aspheric optics and digital signal processing to greatly increase the depth of field and depth of focus. WFC can also simutaneously decrease the size, weight, and cost of a variety of digital imaging systems. During this effort new WFC single lens systems were designed and imulated that can perform as well as expensive multi-lens systems. WFC systems were also shown o passively athermalize IR imaging systems. A high-magnification WFC microscope was constructed indiature imaging systems, bar code scanners, and materials microscopy, endoscopy, inexpensive information see STTR Report. 5. SUBJECT TERMS Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging S. SECURITY CLASSIFICATION OF: T T T T T T T T T T T T T T T T T T T	U. S. Army Resea ATTN: AMSRL-RO-R P.O. Box 12211 Research Triangl 27709-2211	rch Office I (Sylvia Hal e Park, NC	1)			11. SPONSOR/MONITOR'S REPORT NUMBER(S) ARD 40230.1-PH-STI	
A. SUPPLEMENTARY NOTES Report Developed under STTR contract for topic "Army 99 T001".  A. ABSTRACT uring this project a revolutionary system for digital imaging was demonstrated. This system is based on the newly-developed imaging technology of Wavefront Coding (WFC). WFC employs pecialized aspheric optics and digital signal processing to greatly increase the depth of field and depth of focus. WFC can also simutaneously decrease the size, weight, and cost of a variety of digital imaging systems. During this effort new WFC single lens systems were designed and imulated that can perform as well as expensive multi-lens systems. WFC systems were also shown o passively athermalize IR imaging systems. A high-magnification WFC microscope was constructed mages from this system showed revolutionary increases in performance. Applications of Wavefront oding include high magnification biological and materials microscopy, inexpensive iniature imaging systems, bar code scanners, and machine vision systems. For further nformation see STTR Report.  S. SUBJECT TERMS Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging  A. REPORT b. ABSTRACT c. THIS PAGE UU UU 18. NUMBER 19a. NAME OF RESPONSIBLE PERSON Edward R. Dowski, Jr. PAGES UU UU 19. Total 19b. TELEPHONE NUMBER (include area code)	12. DISTRIBUTION/AVAIL Approved for pub	ABILITY STATEMEN lic release	Γ				
ABSTRACT wuring this project a revolutionary system for digital imaging was demonstrated. This system is ased on the newly-developed imaging technology of Wavefront Coding (WFC). WFC employs pecialized aspheric optics and digital signal processing to greatly increase the depth of field nd depth of focus. WFC can also simutaneously decrease the size, weight, and cost of a variety if digital imaging systems. During this effort new WFC single lens systems were designed and simulated that can perform as well as expensive multi-lens systems. WFC systems were also shown to passively athermalize IR imaging systems. A high-magnification WFC microscope was constructed images from this system showed revolutionary increases in performance. Applications of Wavefront oding include high magnification biological and materials microscopy, endoscopy, inexpensive uiniature imaging systems, bar code scanners, and machine vision systems. For further nformation see STTR Report. <b>3. SUBJECT TERMS</b> Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging <b>3. SECURITY CLASSIFICATION OF:</b> <b>17. LIMITATION OF</b> <b>18. NUMBER</b> <b>19a. NAME OF RESPONSIBLE PERSON</b> Edward R. Dowski, Jr. <b>19b. TELEPHONE NUMBER</b> (Include area code)	13. SUPPLEMENTARY NO	TES		<u></u>			
A. ABSTRACT Juring this project a revolutionary system for digital imaging was demonstrated. This system is based on the newly-developed imaging technology of Wavefront Coding (WFC). WFC employs pecialized aspheric optics and digital signal processing to greatly increase the depth of field ind depth of focus. WFC can also simutaneously decrease the size, weight, and cost of a variety of digital imaging sytems. During this effort new WFC single lens systems were designed and imulated that can perform as well as expensive multi-lens systems. WFC systems were also shown to passively athermalize IR imaging systems. A high-magnification WFC microscope was constructed images from this system showed revolutionary increases in performance. Applications of Wavefront coding include high magnification biological and materials microscopy, endoscopy, inexpensive uniature imaging systems, bar code scanners, and machine vision systems. For further information see STTR Report. <b>5. SUBJECT TERMS</b> Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging <b>8. SECURITY CLASSIFICATION OF:</b> <b>17. LIMITATION OF</b> <b>18. NUMBER</b> <b>19a. NAME OF RESPONSIBLE PERSON</b> Edward R. Dowski, Jr. <b>19b. TELEPHONE NUMBER</b> (Include area code)	Report Developed	l under STTR c	contract for top	oic "Army	99 TO	01".	
5. SUBJECT TERMS Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging 5. SECURITY CLASSIFICATION OF: a. REPORT b. ABSTRACT c. THIS PAGE UU UU 11 Edward R. Dowski, Jr. PAGES 11 Total 19b. TELEPHONE NUMBER (Include area code)	14. ABSTRACT During this project based on the newly specialized asphere and depth of focus of digital imaging simulated that can to passively ather Images from this a Coding include his miniature imaging information see S	t a revolution -developed ima -developed ima -developed ima -developed ima -developed image -developed image -dev	ary system for di ging technology of digital signal pr o simutaneously of ng this effort ne ill as expensive m ing systems. A hi evolutionary incr n biological and code scanners, and	gital imag of Wavefror occessing t lecrease th w WFC sing multi-lens .gh-magnifi ceases in p materials d machine v	ying wa nt Codi to grea he size gle len system Loation perform micros vision	as demonstrated. This system is ng (WFC). WFC employs atly increase the depth of field e, weight, and cost of a variety as systems were designed and as. WFC systems were also shown a WFC microscope was constructed. mance. Applications of Wavefront scopy, endoscopy, inexpensive systems. For further	
Digital imaging, Wavefront Coding, single-lens imaging, athermalization, IR imaging         5. SECURITY CLASSIFICATION OF:       17. LIMITATION OF         18. NUMBER       19a. NAME OF RESPONSIBLE PERSON         B. REPORT       b. ABSTRACT         U       UU         UU       11         Total       19b. TELEPHONE NUMBER (Include area code)	15. SUBJECT TERMS						
B. SECURITY CLASSIFICATION OF:       17. LIMITATION OF       18. NUMBER       19a. NAME OF RESPONSIBLE PERSON         B. REPORT       b. ABSTRACT       c. THIS PAGE       ABSTRACT       OF       Edward R. Dowski, Jr.         II       II       UU       11 Total       19b. TELEPHONE NUMBER (Include area code)	Digital imaging	, Wavefront Co	oding, single-l	ens imagi	ng, at	hermalization, IR imaging	
a. REPORT b. ABSTRACT C. THIS PAGE ABSTRACT UU 11 Total 19b. TELEPHONE NUMBER (Include area code)	16. SECURITY CLASSIFIC	ATION OF:	17. LIMITATION OF	18. NUMBER	19a. NA	ME OF RESPONSIBLE PERSON	
	a. REPORT b. ABSTR U U	ACT c. THIS PAGE	UU	PAGES 11 Total	195. TE	LG R. DOWSKI, JL. LEPHONE NUMBER (Include area code) 449-5593	
Standard Form 298 (Rev. 8/						Standard Form 298 (Bev. 8/9	

## <u>Hybrid Optical/Digital Imaging for Automatic Inspection</u> <u>Final Report</u>

There were four goals of the Phase I effort. These goals were centered on the refinement of CDM Optics' WFCDesign optical/digital design software, the testing of WFCDesign software tools on commercially important imaging applications, evaluation of Wavefront Coded (WFC) imaging examples, and the evaluation of real-time processing DSP hardware for processing Wavefront Coded imagery. Each of these goals were realized. The following describes the efforts taken towards each of the Phase I goals and the results achieved.

<u>Goal #1 Refinement of WFCDesign</u> WFCDesign is the name of CDM Optics' custom optical/digital design software. This software consists of Zemax commercial lens design software and custom software extensions to model the digital sampling and filtering aspects of Wavefront Coded imaging systems. While commercial optical design software is well suited to designing traditional optics that require no signal processing of the images, WFCDesign specifically allows the design of the system from the spherical and aspherical optics, through the digital detector, to the signal processing. Both the optics and signal processing can be jointly optimized in this manner. Since the optics influence the signal processing, and the type and form of the signal processing influences the optics, the ability to design both together leads to very powerful optical designs. A block diagram of WFCDesign is shown in figure 1.



Figure 1: WFCDesign block diagram. By designing the Wavefront Coded optics and signal processing *together*, system-wide optimization and tradeoffs can be made.

The main refinements made to WFCDesign during the Phase I effort were to speed the execution, develop new optical surface forms, and develop optical/digital design rules. A large number of computations are needed to simulate the sampled optical signals as well as perform the image filtering. The original version of WFCDesign used Matlab-based processing for calculations. Although easy to program, Matlab processing is slower then needed. In order to make WFCDesign practical, the time required to perform these types of calculations has to be short so that large numbers of optimization parameters can be automatically searched. We have reduced the computation time by using a combination of C++ programming and Pentium-based MMX calculations. A number of new Wavefront Coded optical surface forms have been developed. These include very general polynomial forms as well as spline forms. Design rules for generation of Wavefront Coded optics have been developed from using the systems. Much as with traditional optical design rules, Wavefront Coding design rules allow users to navigate the often complicated multi-dimensional design optimizations. Early Wavefront Coded imagery was formed with an optical element with a surface shape of a simple cubic. This is the only general optical part that is physically available today. During the Phase I effort more general surface forms were developed that can significantly improve the performance of the optical/digital system. One general form is:

$$S(x,y) = \sum a_i \operatorname{sign}(x) |x/r_n|^{b_i} + a_i \operatorname{sign}(y) |y/r_n|^{b_i}$$

where the sum is over the index *i*. Sign(x) = -1 for x < 0, +1 for  $x \ge 0$ . The parameter  $r_n$  is a normalized radius value. This Wavefront Coding surface form is rectangularly separable and allows for fast processing if ideally fabricated. In practice it is difficult to achieve the ideal speed allowed by such a form due to fabrication errors. Other forms of Wavefront Coding surfaces are non-separable, and the sum of rectangularly separable forms. A non-separable form is defined as:

$$S(\mathbf{r},\boldsymbol{\theta}) = \sum \mathbf{r}_{i}^{a} \cos(\mathbf{b}_{i} \,\boldsymbol{\theta} + \boldsymbol{\phi}_{i})$$

where the sum is again over the subscript *i*.

<u>Goal #2 Testing of WFCDesign on Commercially Important Imaging Applications</u> A number of optical designs were performed as part of the Phase I effort to test the WFCDesign software tools, to use as a test bed to develop design rules, and to highlight the power and simplicity of Wavefront Coding. These designs include a very fast and compact singlet that images with a large field of view and depth of field, a germanium/silicon triplet IR lens that is very insensitive to temperature-related effects, and a simple 10X microscope lens that uses two aspheric plastic optical elements and images well over a large field of view. Each is briefly described below.

• The fast and compact singlet system was designed to illustrate the power of Wavefront Coding applied to miniature imaging systems soon to be found in cell phones, personal digital assistants, and PC cameras. The primary constraints of these systems are to use a minimum number of optical elements, to have very short length, and to image with high quality over a very wide field of view. When using a single optical element, these constraints are impossible for traditional optics. With Wavefront Coded optics, all of the constraints can be met and very high quality imaging can be produced.

The lens drawing in figure 2 describes a version of the singlet lens designed. The first element is an aspheric Wavefront Coded optic made of acrylic. The two elements to the right represent the IR filter and detector cover glass. This lens has a speed of F/2.8 and a full field of view of 50 degrees. The focal length is 3.5mm The detector is a one-quarter inch Bayer color filter array detector. The system, after digital signal processing, images over nearly the entire field of view and stays in focus with objects from infinity to 30cm.



Figure 2: Lens drawing of fast and compact singlet that images with a wide field of view. The first element is an aspheric imaging optic made of acrylic. The two elements to the right are the IR filter and detector cover plate. This type of lens is meant for miniature optics of cell phones, personal digital assistants, and PC cameras. The lens has a focal length of 3.5mm, a speed of F/2.8, a full field of view of 50 degrees, and an overall length of 5.4mm.

• **Temperature corrected** germanium/silicon IR imaging system with *aluminum* mounting material was designed to show how Wavefront Coding can be used to reduce the effects of ambient temperature changes on passive optical/digital systems. Traditional IR imaging systems require active thermal compensations to perform well over even a 10 degree C temperature range. With Wavefront Coding, a specially designed system that uses only aluminum mounting material can operate with diffraction-limited performance over a 90 degree C temperature range.

Figure 3 represents the layout of this IR imaging system and the exit pupil of the system. The system is a germanium, silicon, germanium triplet design. The aperture stop is at the back surface of the third element. The system is fast, F/2, and has a focal length of 100mm. The design wavelength is 10 microns and the mounting material is purposely chosen to be aluminum which makes the design more difficult. IR imaging systems usually use much more thermally stable, and expensive, mounting materials, such as Invar.



Figure 3: IR imaging system with aluminum mounting material that operates over a 90 degree C temperature range without active compensation. Left drawing represents the three optical elements of germanium, silicon, and germanium. The aperture stop is at the back surface of the last element. The drawing on the right represents the exit pupil of the system.

The performance of this Wavefront Coded IR imaging system in terms of the modulation transfer function (MTF) is given in figure 4. The upper graph of figure 4 shows the MTF of the all-optical traditional IR system over a temperature range of -20 degrees C to +70 degrees C. At +20 degrees C the system is diffraction-limited. With a 10-20 degree change the system becomes badly misfocused. The lower graph of figure 4 shows the Wavefront Coded version of the system over the same

temperature range. The MTFs before digital filtering are seen to have very little variation with temperature. These MTFs are the MTFs of the intermediate image (before digital filtering) and therefore produce blurred imagery. After digital filtering the MTFs are nearly ideal. Since the Wavefront Coded MTFs are all related to sampled systems, each MTF for the Wavefront Coded system includes the pixel MTF response that was not included in the all-optical traditional system MTFs.



Figure 4: MTFs of traditional and Wavefront Coded IR imaging systems as a function of temperature. The top graph represents the all-optical traditional version of the IR imaging system of figure 3 without Wavefront Coding as the ambient temperature is varied between -20 degrees C and +70 degrees C. The system is seen to be badly out of focus as the temperature is varied. The bottom graph represents the MTFs of the IR imaging system with Wavefront Coding. Since the Wavefront Coded MTFs include sampling, they all include the pixel MTFs that are not included on the all-optical traditional MTFs. The MTFs before filtering over the same 90 degree temperature range show very little variation with temperature. The MTFs after filtering are also have little variation with temperature and are very close to the optimum diffraction-limited MTF.

• A Simple 10X microscope objective design that employs Wavefront Coding to reduce the optical complexity and fabrication cost was also designed as part of the Phase I effort. By reducing the optical complexity, the fabrication time and tolerances can also be reduced, thereby greatly decreasing the cost of the objectives. Since microscope objectives typically have a very narrow field of view, the main aberrations to be controlled are field curvature and chromatic aberration. Since both field curvature and chromatic aberration are "focus-like" aberrations, they can be ideally corrected with Wavefront Coding. A simple acrylic objective that images with high quality can allow very low cost objectives suitable for high volume applications such as industrial inspection, and student or children's microscopes, that are not possible with traditional optical designs.

Figure 5 shows the layout of a two-element Wavefront Coded 10X microscope objective. Both elements are acrylic and aspheric. The second is located at the aperture stop and contains a Wavefront Coded surface. The remote stop ensures a very low level of distortion over the field.



Figure 5: Layout of Wavefront Coded 10X microscope objective. Both elements are aspheric and acrylic. The second element is at the aperture stop of the system and contains a Wavefront Coded surface. This simple set of optics produces imagery, after digital processing, that has very low distortion and is very well corrected for chromatic aberration and field curvature.

Figure 6 shows the MTFs for this system both with and without Wavefront Coding. Both sets of MTFs include pixel MTFs. Without Wavefront Coding the system suffers from severe axial chromatic aberration and field curvature. Field curvature is the major problem for the traditional system. The top curve of figure 6 shows the MTFs as a function of field angle. On-axis the system is diffraction limited. For off-axis field points the MTF quickly degrades and produces a poor image.

The lower graph of figure 6 shows the MTFs for the objective with Wavefront Coding. The MTFs before digital filtering are seen to be have very little variation with field angle. After digital filtering the MTFs over the entire field very nearly follow the ideal diffraction-limited curves. The Wavefront Coding objective has ideal performance while using only two acrylic optical elements. This is a revolutionary design.



.

Figure 6: MTFs of simple 10X objective with and without Wavefront Coding. The top graph represents the MTFs without Wavefront Coding as a function of field angle. While the MTF is diffraction-limited for on-axis imaging, performance is severely degraded for off-axis imaging. The bottom graph represents the MTFs with Wavefront Coding. Before filtering the MTFs are seen to have little variation with field angle. After filtering the MTFs for all field angles are nearly identical to the ideal diffraction-limited MTF. Pixel MTFs are included in both graphs.

<u>Goal #3 Evaluation of Wavefront Coded Imaging with Real Systems</u> As part of the Phase I effort we modified a Zeiss biological research-grade microscope for Wavefront Coding and produced a series of measurements and images. The measured MTFs and PSFs as a function of misfocus clearly showed vast improvements in depth of field through Wavefront Coding. The images produced gave dramatic proof of the benefits of Wavefront Coding for extended depth of field microscopy applications.

We modified the Zeiss microscope by placing a cubic-phase Wavefront Coding optical element near the back of the microscope objective. The Zeiss microscope has a slot in the housing above the objective intended for differential interference contrast (DIC) optical elements. Using this slot for the Wavefront Coding optical element made the modifications of the microscope relatively simple and mechanically accurate.

Measurements of the MTFs of the system with a 40X, NA=1.3 oil immersion objective with a 2.5X eyepiece (for a total magnification of 100X) are shown in figure 7. Without wavefront coding the system has a depth of field of less then 1 micron. With Wavefront Coding the depth of field was increased to over 10 microns. From figure 7 the MTFs from the traditional system vary greatly with misfocus. (MTFs were taken in 2 micron stage increments) The Wavefront Coded MTFs before filtering show very little variation with misfocus, and after filtering produce MTFs that are very similar to the in-focus MTF from the traditional system.



Figure 7: MTFs from Zeiss 100X, NA=1.3 oil immersion microscope system with and without Wavefront Coding. The MTFs from the traditional system are seen to vary greatly with misfocus. MTFs are measured in 2 micron stage increments. The MTFs of the Wavefront Coding system are nearly constant over the same misfocus range. After filtering, the MTFs are again nearly constant and very similar to the in-focus MTF from the traditional imaging system.

Examples of imaging with the 100X system are shown in figures 8 and 9. In figure 8, the object is a leaf with water bubbles. The distance from the surface of the leaf to the top of some of the bubbles exceeds 20 microns. The traditional system image can only clearly image the surface of the leaf. The surface of the bubbles are all well beyond the depth of field of the traditional system. The Wavefront Coding image in

contrast clearly images the surface of the leaf and the entire bubbles. The depth of field is large enough that perspective can be seen in the Wavefront Coded image.



Figure 8: Example 100X, NA=1.3 Zeiss microscope with and without Wavefront Coding. The object is a leaf with bubbles. The distance from the surface of the leaf to the top of some of the bubbles exceeds 20 microns. The image on the left is from the traditional system. Only the surface of the leaf is clearly in focus. The image on the right is from the Wavefront Coded system. The surface of the leaf as well as all the bubbles are clearly imaged. The depth of field is so great that perspective is even seen.

In figure 9 the main objects are water conducting tubes (tracheids) of a leaf. The tracheids have a helical coil that surround the tube. The depth of the coils is large enough that they cannot be imaged clearly with the traditional system. The Wavefront Coded system can clearly image all the coils with resolution at least as high as the traditional, focused system.



Wavefront Coded Image



Figure 9: Example 100X, NA=1.3 Zeiss microscope with and without Wavefront Coding. The main object is a water conducting tubes (tracheids) of an ivy leaf. The image on the left is from the traditional system. The traditional system does not have a large enough depth of field to image the helical coils of these cells. The image on the right is from the Wavefront Coding system. This image is seen to clearly resolve the helical coils of the tracheids as well as sharply image nearly all objects in the scene.

<u>Goal #4 Evaluation of Real-Time Processing DSP for Wavefront Coding</u> Many Wavefront Coding systems require real-time processing. As part of the Phase I effort we considered the processing speed and complexity of DSP implementations for real-time Wavefront Coding processing. We specifically considered the Texas Instruments TMSC6X series of microprocessors. Early level programming and algorithm design was performed on a development TI board.

The TI C6X series of microprocessors has an advertised speed of 3 billion multiply and accumulates per second when operating on data stored in memory internal to the processor itself. For small images sizes and compact digital filters, this speed should be sufficient for real time processing. It was determined, however, that Wavefront Coding digital filtering requires external memory that would greatly degrade actual processing speeds. Realized processing speeds could degrade by a factor of 10. The amount of internal memory of the TI chip is low and so a processing algorithm design to minimize memory was required. For large image sizes or large filter sizes (greater then 32 1D taps) the algorithm requirements are such that real-time processing is not possible with the TI series 'C6x device.

## Feasibility of Phase II Based on Phase I Effort

Based on the Phase I effort, future work should include: 1) development of an general high magnification Wavefront Coded microscope working with a variety of objectives and illumination methods, 2) design of real-time Wavefront Coded processors for high-magnification for live-cell microscopy and high-speed manufacturing/inspection systems, and 3) the design of optical systems representative of next-generation microscope optics.

A microscope retrofit system for Wavefront Coding has been proven on a Zeiss biological microscope working at the limits of optical microscopy. This system has very high magnification (100X) and the largest spatial resolution available, with a numerical aperture (NA) of 1.3. Results from this system indicates that retrofits for other types of microscopes and objectives are feasible.

The first-generation optical phase elements for Wavefront Coding were proven to give a high degree of performance. New Wavefront Coded optical designs should further increase performance of the system by reducing the amount of computation required. Optical designs for simplified objectives done during Phase I also indicate that Wavefront Coding can also be used to greatly simplify the complexity of microscope objectives, thus lowering the overall cost for a number of applications.

Real-time Wavefront Coded (WFC) image production for large-format microscope applications requires over ten billion multiply-adds per second. The minimum data rate for modest sized microscope images is approximately 1k x 1k pixels per frame at 10 frames per second, or 10Meg pixels per second. In general, the maximum length of a PSF for a WFC biological system is 32 pixels in either spatial dimension. Such a system will require a large filter kernel that would contain 32 x 32 elements, or 1024 = 1k coefficients. This system requires 1k computations per pixel, with 10M pixels per second, or 10 billion multiply-adds (MACs) per second.

Some Wavefront Coded optical systems can be processed in a separable fashion, where the columns of the image are filtered independently of the rows. Such filtering is more efficient mathematically than twodimensional, or non-separable, spatial filtering. A rectangularly separable design similar to that described above would contain 32+32=64 coefficients and require 640 million MACs per second. Based on the results from the Phase I effort, both an FPGA-based solution and a DSP-based solution are proposed for implementing WFC processing. The processing must also be scalable, as future WFC microscope systems for biological and medical use can approach 4k x 4k sensors operating at 25 frames per second.

Real-time stand-alone Wavefront Coded processors for two-dimensional filtering can be produced efficiently using current state-of-the-art silicon-based processing hardware. Hardware processing for high-quality image rendering is practical due to the high parallelism offered in Field Programmable Gate Array (FPGA) devices currently available. The Virtex-E and Virtex-EM family of chips from Xilinx, Inc. are examples of capable FPGA devices. In contrast, the separable designs may be processed on cheaper digital signal processing (DSP) chips currently available today, provided the data throughput can be achieved (data throughput was the limiting case with the TI 'C6x investigated in Phase I). An important distinction is that DSPs are sequential machines, capable of doing one task at a time. Even though several data entries may be processed simultaneously on a DSP, the instructions are executed sequentially. FPGAs offer parallel instruction implementation with multiple data entries, a huge advantage for non-separable Wavefront Coded processors. The FPGA solution is considered a hardware solution for non-separable processing, and the DSP is a software solution for separable processing.

•

(