Navy Experimental Diving Unit 321 Bullfinch Rd. Panama City, FL 32407-7015 TA98-010 NEDUTR-5-01 February 2001



EVALUATION OF DUI "WING" BUOYANCY COMPENSATOR

C. J. ZANONI:

<Unlimited> <Distribution>

20010426 035

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS P	AGE						
	REPO	ORT DOCUMENTATION F	AGE				
1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RE	STRICTIV	E MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DIS	TRIBUTIO	N/AVAILABILITY	OF REPORT	
N/A			DISTRI releas	BUTION S e; distr	TATEMENT A: App ibution is unli	roved for pul mited	olic
2b. DECLASSIFICATION/DOWNGRADING AUTHORITY				o			
4. PERFORMING ORGANIZATION REPORT NUMBER(S) NEDU Technical Report No. 5-01			5. MON	ITORING	ORGANIZATION RE	PORT NUMBER (S)
6a. NAME OF PERFORMING ORGANIZATION Navy Experimental Diving Unit	6b. OFFICE (If Ap	SYMBOL pplicable) 031	7a. NA	ME OF MO	NITORING ORGANI	ZATION	
6c. ADDRESS (City, State, and ZIP Code) 321 Bullfinch Road, Panama City, FL 32407	-7015		7b. AL	DRESS (C	City, State, and	Zip Code)	
8a. NAME OF FUNDING SPONSORING ORGANIZATION Naval Sea Systems Command	8b. OFFICE (If Ap	SYMBOL oplicable) 00C	9. PRC	CUREMENI	INSTRUMENT IDE	NTIFICATION	NUMBER
8c. ADDRESS (City, State, and ZIP Code)	•		10. SC	URCE OF	FUNDING NUMBERS	3	
2531 Jefferson Davis Highway, Arlington,	VA 22242-516	50					NORK UNIT
			PROGRA	M NT NO.	PROJECT NO.	TASK NO. TA98-010	ACCESSION NO.
11. TITLE (Include Security Classification)					<u> </u>		
EVALUATION OF DUI "WING" BUOYANCY COMPENSATOR	(UNCLASSIF)	IED)					
12. PERSONAL AUTHOR(S)C. J. Zanoni							
13a. TYPE OF REPORT Technical Report	13b. TIME FROM	COVERED Dec 00 TO Jan 01	14. D/ Fe	ATE OF RI Boruary 3	EPORT (Year, Mor 2001	nth, Day)	15. PAGE COUNT 7
16. SUPPLEMENTARY NOTATION	<u> </u>						
17. COSATI CODES			18. SUBJI iden	ECT TERMS	S (Continue on a block number)BC	reverse if ne Testing	ecessary and
FIELD GROUF		SUB-GROUP					
19. ABSTRACT: NEDU was tasked to conduct a su determine which BC perform satisfactorily. E inspection of the buoyancy compensator, techn diver orientation, and Test Pool Evaluation (conducted. Phase II consisted of buoyancy / in the Gulf of Mozico to test diver buoyancy	irvey of com buoyancy com lical review BC surface lift capaci control and	mercially available pensator evaluation of the manufactur floating attitudes ty testing in the operational chara	buoyancy n was cond er supplie if used a Fest Pool cteristics	compens ucted in d docume s a Life at 15 fs	ators (BCs), and three phases. ntation (instrue Jacket). No fa w. Phase III co	d perform tes Phase I, rec ctions / repa ailure mode a onsisted of r	sting to seipt air manuals), analysis was manned dives
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT		• • • • • • • • • • • • • • • • • • •		21. ABS	STRACT SECURITY	CLASSIFICATI	ON
UNCLASSIFIED/UNLIMITED X SAME AS RPT.	DTIC	USERS			Unclassi	fied	
22a. NAME OF RESPONSIBLE INDIVIDUAL NEDU Librarian		22b. TELEPHONE (850-230-310	Include Ar	ea Code)	22c. OFF	ICE SYMBOL	
DD Form 1473							

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE

CONTENTS

<u>Page No.</u>

Page No.

Introduction	1
Methods	1
General	1
Experimental Design and Analysis	1
Equipment and Instrumentation	2
Procedures	2
Results	3
Conclusions.	4
Recommendations	4
References	7

TABLES

1	Buoyancy Compensator Pull Test Data Sheet5
2	Human factor evaluation data sheets
	for the DUI "Wing"6

<u>Table No.</u>

INTRODUCTION

Navy Experimental Diving Unit (NEDU) is tasked¹ to conduct surveys of commercially available buoyancy compensators (BCs), and perform testing to determine which BCs perform satisfactorily in accordance with references (2) and (3). All BCs that meet the above requirements will be candidates for recommendation to the Authorized for Navy Use (ANU) list. The purpose of this technical report is to determine if the DUI "Wing" BC meets those requirements.

METHODS

GENERAL

Each BC was tested and evaluated in three different environments Phase I (Bench Test), Phase II (Controlled Environment (Test Pool/Ocean Simulation Facility (OSF)), and Phase III (Open Ocean Diving). While bench testing, each BC was evaluated by two qualified U.S. Navy divers for completeness and adequacy of maintenance manuals and technical documentation, skill level required to perform routine repair and maintenance, operation of the integrated weight belt and the operation of all BC components. In a controlled environment, each BC was tested and evaluated for buoyancy and lift capability. While performing open water dives, each BC was used and evaluated by qualified U.S. Navy divers in a single SCUBA tank configuration to a minimum of 30 fsw (9.4 msw).

EXPERIMENTAL DESIGN AND ANALYSIS

All BCs tested were off the shelf items; the "Wing" BC is available in one adjustable "fits all" sizes. The Task Leader or assigned representative was present during the set-up and post-dive procedures on all BCs.

Phase I testing:

- Each model BC was evaluated by two qualified U.S. Navy divers for ease of operation and maintenance procedures.
- Average cost, from five different suppliers was acquired.

Specific comments from evaluators were compiled and documented.

Phase II testing:

• All BCs were tested to 15 fsw (4.7 msw) utilizing the Test Pool. Each BC was fully inflated and the average lift capacity recored.

Phase III testing:

Each BC was evaluated during open water dives. A series of evaluation dives were conducted to a minimum depth of 30 fsw. Divers completed a human factor questionnaire after each dive. A set of descriptive statistics of the responses and specific comments were complied.

EQUIPMENT AND INSTRUMENTATION

No special or proprietary tools were required to perform routine maintenance or repair on the BCs.

- a. <u>Phase I:</u> During bench testing, the following equipment was used:
 - (1) Fully charged SCUBA bottle and an approved regulator
 - (used to supply low-pressure air to perform equipment checks)
 - (2) Manufacturer's instructions and maintenance manual
 - (3) Miscellaneous hand tools and adapter fittings
 - (4) Weights (soft or molded)
- b. Phase II: During Test Pool testing the following equipment was used:
 - (1) Calibrated Viking spring scale model 895, 0 to 50 pounds (0 to 22.7 kg) manufactured by Hanson in Shubuta, Mississippi.
 - (2) Lanyards, spinnaker shackles, and weight as appropriate to anchor BCs to deck in test pool.
 - (3) Fully charged SCUBA bottle and an approved regulator (used to supply low-pressure air)
 - (4) Personnel as required
 - (5) Weights
- c. <u>Phase III:</u> During at sea testing, the following equipment was used:
 - (1) Fully charged SCUBA bottle, approved regulator and all other personnel diving equipment needed to perform a SCUBA dive
 - (2) Personnel as required
 - (3) At sea diving platform

PROCEDURES

BC evaluation was conducted in three phases: (1) receipt inspection and technical review of manufacturer supplied documentation, (2) Test Pool evaluation (buoyancy/lift capacity at 15 fsw), and (3) open water dives to test buoyancy control and operational characteristics.

- a. Phase I testing began with a review of the following:
 - (1) Completeness and adequacy of the maintenance manuals and technical documentation
 - (2) Requirements for special or proprietary tools
 - (3) Skill level required to perform routine repair and maintenance
 - (4) Operation of integrated weight system
 - (5) Operation and activation of all BC components
 - (6) Ease of assembly in single tank configuration
 - (7) Unit price

A technical documentation and operational function worksheet was completed by each qualified diver assigned, and returned to the Task Leader.

b. <u>Phase II Testing</u>: Buoyancy/lift capacity of the units was tested in the Test Pool at a depth of 15 fsw. All divers participating in the study were required to familiarize themselves with the contents of the user's manual, to include location of controls on the BC and donning procedures.

A calibrated Viking spring scale model 895 was attached to the deck via a 100lbs. clump in the Test Pool to measure buoyancy. Each BC tested was attached to the scale and tested in the Test Pool at 15 fsw. The buoyancy was measured and documented; at a minimum, each BC was required to provide 10 lbs. of positive lift as outlined in reference (2). The BC was also tested for leaks at depth.

c. <u>Phase III Testing</u>: Manned open water dives were conducted to a minimum depth of 30 fsw to determine each BC's swim characteristics. Results were documented using a diver's questionnaire.

RESULTS

PHASE I

The inspection of the manufacturers supplied documentation on the use, service, parts, technical aspects and exploded views/diagrams were excellent. Documentation fails to include a parts list or technical specifications within the supplied buoyancy compensator manual, but are available from the manufacturer upon request. There were no requirements for special or proprietary tools needed. Skill level required to perform routine maintenance should be at least a second class diver or above. The integrated weight system weights were secure and easy to operate the release mechanism. The operation and activation of all BC components were easy to operate. There were no problems assembling the single tank configuration, there was no twin tank configuration.

The average manufacturer's suggested price per unit is \$348.

PHASE II

The "Wing" BC in the single tank configuration averaged 48.6 pounds of positive lift (lbf) at 15 fsw (4.7 msw) (see Table 1). The measured buoyancy of the "Wing" BC was approximately 16.2% less than the 58 lbf quoted by the manufacturer. However, that difference might have been due to differing test conditions, procedures, or depth.

No twin tank configuration was tested. At time of testing, a twin tank configuration was not available from manufacturer.

PHASE III

During the manned evaluation of the DUI "Wing" BC, 11 divers tested the BC in a single tank configuration to depths ranging from 30 to 100 fsw. On a scale of 1 - 6 (4.0 being the minimum mark for an overall acceptable score), this BC scored a rating of 4.30 in the single tank configuration.

CONCLUSIONS

During testing, two major items of note were encountered. First, in accordance with manufacturer's technical manual and Maintenance Requirement Card (MRC) MIP 5921/023 R-1, the cylinder band strap must be wet prior to installation of the tank. If this was not done, the bottle had a tendency to slip down and out of the BC, which could lead to the loss of the diver's air supply. Second, approximately 30% of the divers reported there was not an attachment point for the low pressure (LP) inflation hose or octopus, making the LP inflation hose and octopus difficult to locate while diving.

RECOMMENDATIONS

Based on the testing and evaluation in accordance with reference (3) and reported in Tables (1) and (2), we recommend that the DUI Model name "Wing" (P/N: 290600) be authorized for Navy Use in single tank configuration. Prior to each diving day PMS MIP 5921/023 R-1 must be completed. No surface floating attitude testing was conducted as per manufacturer's supplied documentation on the use of the BC, therefore we do not recommend this BC be used as a life preserver.

Table 1. DUI "Wing" Buoyancy Compensator Pull Test Data Sheet

•

•

Vir	ig" Single Tank Configur	ation			
	NOMENCLATURE	BC #	BUOYANCY (LBF)	DEPTH	INFLATION METHOD
	DUI "WING"	1	48 LBF	15 FSW	LP WHIP FROM SCUBA BOTTLE
	DUI "WING"	2	49 LBF	15 FSW	LP WHIP FROM SCUBA BOTTLE
				valanti Sugar nya "Spern Sulati nya dia dia 12562	
	"DUI "WING"	3	49 LBF	15 FSW	LP WHIP FROM SCUBA BOTTLE
				And And States	
	Average Buoyancy		48.6 LBF		
] .	Each size BC was te	sted	to 15 fsw (4.7 msw) uti	lizing th	le Test Pool. Each BC was
t	od thron timos in tho	in of	a tank configuration re	undin.	the average lift connected

rully inflated three times in the single tank configuration, recording the average lift capacity.

Table 2. Human Factors Evaluationof the DUI "Wing" Buoyancy Compensator in Single Tank Configuration.

•

adequate, 6 = excellent).

REFERENCES

- 1. Commander, Naval Sea Systems Command, Task Assignment 98-10, Commercial Diving Equipment Test and Evaluation, Dec 97.
- 2. NAVSEA ltr Ser: OOC32/3265 dated 21 July 1989
- 3. R. W. Mazzone, *Procedure for the Evaluation of Commercially Available Buoyancy Compensator's (Unmanned/Manned),* NEDU TP98-01, Navy Experimental Diving Unit, January 1998.
- 4. Naval Sea Systems Command, *U.S. Navy Diving Manual, Vol. #5*, Rev. 4, NAVSEA SS521-AG-PRO-010, 20 Jan 99. Chapter 7-2.3.4, page 7-9.