### 10th International Command and Control Research and Technology Symposium

The Future of C2

### **Future Integrated Fire Control**

Bonnie W. Young Northrop Grumman 2611 Jefferson-Davis Highway Suite 8000 Arlington, VA 22202 (703) 407-4531ph bonnieworthyoung@hotmail.com

	Report Docume	entation Page		I OM	Form Approved IB No. 0704-0188
Public reporting burden for the col maintaining the data needed, and c including suggestions for reducing VA 22202-4302. Respondents sho does not display a currently valid (	lection of information is estimated t completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding an DMB control number.	o average 1 hour per response, inclu ion of information. Send comments arters Services, Directorate for Infor ny other provision of law, no person	ding the time for reviewing ins regarding this burden estimate mation Operations and Reports shall be subject to a penalty for	tructions, searching exis or any other aspect of th s, 1215 Jefferson Davis J failing to comply with	ting data sources, gathering and is collection of information, Highway, Suite 1204, Arlington a collection of information if it
1. REPORT DATE JUN 2005		2. REPORT TYPE		3. DATES COVE 00-00-2005	RED 5 to 00-00-2005
4. TITLE AND SUBTITLE				5a. CONTRACT	NUMBER
Future Integrated	Fire Control			5b. GRANT NUM	1BER
				5c. PROGRAM E	LEMENT NUMBER
6. AUTHOR(S)				5d. PROJECT NU	JMBER
				5e. TASK NUMB	ER
				5f. WORK UNIT	NUMBER
7. PERFORMING ORGANI Northrop Grumma 8000, Arlington, VA	ZATION NAME(S) AND AI an,2611 Jefferson-D .,22202	DDRESS(ES) avis highway Suite		8. PERFORMINC REPORT NUMB	GORGANIZATION ER
9. SPONSORING/MONITO	RING AGENCY NAME(S) A	AND ADDRESS(ES)		10. SPONSOR/M	ONITOR'S ACRONYM(S)
				11. SPONSOR/M NUMBER(S)	ONITOR'S REPORT
12. DISTRIBUTION/AVAII Approved for publ	LABILITY STATEMENT ic release; distribut	ion unlimited			
13. SUPPLEMENTARY NC The original docum	otes nent contains color i	images.			
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFIC	CATION OF:		17. LIMITATION OF	18. NUMBER	19a. NAME OF
a. REPORT <b>unclassified</b>	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ABSTRACT	65	RESPONSIBLE PERSON

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std Z39-18

### **Future Integrated Fire Control**

Bonnie W. Young Northrop Grumman 2611 Jefferson-Davis Highway Suite 8000 Arlington, VA 22202 (703) 407-4531ph bonnieworthyoung@hotmail.com

### <u>Abstract</u>

Future advances in fire control for air and missile defense depend largely on a networkfoundation that enables enabled the collaborative use of distributed warfare assets for time-critical operations. These advances enable major enhancements for tactical fire control. Selecting the best shooter from a set of geographically distributed firing units can improve the chances of intercepting targets and improve the economy of weapon Earlier launch decisions are resources. possible when sensors are intelligently tasked based on shared knowledge of the battlespace. No longer must collocated sensors and weapons be paired for engagements. Lifting such pairing constraints expands the effective kinematic range of weapons and enables additional operational capabilities such as forward pass and off-board engagement support for guidance relay and target illumination. For complex threat environments in which sophisticated or significant numbers of aerospace targets exist, automated collaborative fire control (or Integrated Fire Control (IFC)) may be a necessity for victory. This paper presents research in advanced data fusion and decision aid capabilities as a means of enabling and enhancing IFC. It addresses the importance of achieving distributed information superiority-shared, accurate, and timely situational awareness as the foundation of IFC capabilities. It discusses required IFC design and architecture guidelines. Finally, the paper proposes an IFC concept to meet the complex needs of future warfare.

### **1.0 Integrated Fire Control**

IFC refers to the participation and coordination of multiple non-collocated

warfare assets1 in tactical engagements of enemy targets. In other words, IFC is the ability of a weapon system to develop fire control solutions from information provided by one or more non-organic sensor sources: conduct engagements based on these fire control solutions; and either provide midcourse guidance (in-flight target updates) to the interceptors based on this externally provided information or in certain cases, have them provided by a warfare unit other than the launching unit. IFC enables expansion of a weapon's battlespace to the effective kinematic range of the missiles and can remove dependency on range limits of the organic/dedicated sensor.

IFC relies on the ability of participating sensors, weapons, and C2 nodes to share target information in real-time and eliminate correlation errors so the engaging weapon system can utilize the information as if it was produced by its organic sensor(s). An architectural solution that enables IFC is based on combining sensor and data networks to overcome individual system limitations and enable collaborative engagements; and providing automated engagement decision aids that use "common" algorithms and the shared data set to simultaneously produce identical engagement recommendations at each participating node, in accordance with established rules of engagement (ROE). The ability to direct distributed warfare resources in а collaborative manner enables major

<sup>&</sup>lt;sup>1</sup> Warfare assets (or warfare resources) are sensors, weapons, command and control (C2) systems, and warfare units (mobile platforms such as ships, aircraft, satellites, land-based units, etc.) Additional assets that support IFC are communication resources and computer/processing systems.

enhancements for tactical fire control as shown in Figure 1.

### Why Integrated Fire Control?

• Selection of the best shooter from a set of

- geographically distributed weapons
- Improved chance of interception (by selecting the
- optimal engagement geometry)
- Improved economy of weapon resources (by reducing redundant shots)
- Earlier launch decisions are possible (remote
- detection/precision tracking)
- Decoupling of local sensor/weapon pairing constraint
- Sharing engagement control forward pass
- Off-board engagement support for guidance relay and target illumination
- Enhanced defense against complex threat

environments (sophisticated or significant numbers of aerospace targets) – IFC may be a necessity for victory

Figure 1 – IFC Payoffs

### **1.1 Operational IFC Variants**

Collaboration among distributed warfare resources to perform integrated engagements takes many forms. Distributed collaboration can consist of simply receiving a threat cue from a remote source to the sophisticated integration required to pass engagement control to a remote unit. This section introduces the major types of IFC capabilities from an operational perspective.

### (1) Precision Cue

The Precision Cue is an IFC capability in which a cue (representing a possible threat) is received from a remote source (i.e., sensor, Intel source, tactical data link, remote operator). The cue is used to direct a local sensor (or sensors) to detect a specific target. The cue is comprised of target information such as a state (location) estimate, target track data, and/or an assessment of the target's identification (Combat ID).



Figure 2 – Precision Cue

Figure 2 illustrates the Precision Cue variant, showing how a remote unit detects a threat and transmits the target information to the "local" unit. The local unit then tasks a local sensor to detect and track the threat.

### (2) Launch on Remote

Launch on Remote (LoR) is an IFC capability in which remote sensor data is used to initiate a missile launch without holding the track locally.





Operationally, LoR relies on the ability of a local sensor to track (and provide fire control quality data for) the threat target after missile launch to acquire the data needed to support the in-flight guidance of the interceptor. A related variant of the LoR is "Launch on Composite" in which composite data (comprised of data from multiple sensors remote and/or local) is used to initiate the missile launch.

Figure 3 illustrates an example of the LoR variant. In this illustration, the remote sensor detects and tracks the threat and provides the data to the firing unit. The firing unit uses this threat data to make a launch decision. The firing unit requires its local sensor to track the threat after launch to support in-flight guidance.

### (3) Engage on Remote

Engage on Remote (EoR) is an IFC capability in which one or more remote sensors provide data upon which all (or portions) of an engagement is conducted. Variants of EoR include: using remote data to initiate launch as well as support in-flight guidance computations; using a remote sensor to relay in-flight guidance to the interceptor; and using a remote sensor to illuminate the threat during interceptor endgame. A related variant of EoR is "Engage on Composite" in which composite data is used to provide fire control quality data throughout the engagement to support guidance computations and engagement control.



Figure 4 – Engage on Remote

Figure 4 illustrates an example of the EoR variant. In this illustration, the remote unit provides fire control quality (FCQ) data of the threat to the firing unit throughout the engagement. The firing unit uses the remote data to make the launch decision as well as support the entire engagement.

### (4) Forward Pass

Forward Pass is an IFC capability in which control of the in-flight missile can be handed off (or forward passed) to another unit to complete the intercept. Forward Pass may be used to complete an engagement that otherwise may have been impossible due to constraints on the system that initiated the engagement. A remote system may be located strategically to better provide endgame control. Or perhaps multiple threats require a weapon system to rapidly launch multiple interceptors while handing off engagement control to remote systems.

Figure 5 illustrates an example of the FP variant. This example shows the remote unit taking control of the engagement after launch by tracking the threat and providing guidance directly to the interceptor.



Figure 5 – Forward Pass

### (5) Remote Fire

Remote fire is an IFC capability in which the launch decision is made by a remote unit (one that is not collocated with the weapon system). For "remote fire", engagement control can be performed by the remote unit or can be passed to the firing unit.



Figure 6 – Remote Fire

Figure 6 illustrates and example of the RF variant. In this example, the remote unit makes the decision that the firing unit should launch its interceptor. After launch, the remote unit takes control of the engagement; however engagement control could reside with the firing unit for the RF variant.

### (6) Preferred Shooter Determination

Preferred Shooter Determination is an IFC capability in which the optimum weapon (or weapons) from a group of warfare units (operating collaboratively) is (are) selected to intercept a threat target. The best shooter(s) (are) selected based on optimum is engagement geometry and engageability determination. This capability can be performed in conjunction with any of the This capability is, in other IFC variants. effect, Force-centric weapon-target pairing.



Figure 7 – Preferred Shooter Determination

Figure 7 illustrates the PSD variant. This illustration depicts five distributed warfare units sharing data over a network to determine the best engagement strategy (or weapon-target pairing) for the threat. In this example, one of the Destroyers is selected as having the best shot opportunity.

### **1.2 Fire Control Functions**

In order to intercept an aerospace threat, some basic functions must be performed. These fire control functions are "common" in the sense that they are necessary to support the various Joint weapon systems that comprise the aerospace warfare arsenal. The functions listed below are defined broadly enough to encompass basic functions that support fire and forget weapon systems to more complex functionality that supports more sophisticated weapon systems that require in-flight engagement support after launch. This section defines a generic set of fire control functions with the intent of easily aligning with the terminology used for the various Service's weapon systems.

(1) Object Observation – sensor(s) observes aerospace object and produces object measurements. (2) Object Tracking and Identification – sensor measurements (from one or more sensors) are used to estimate an object's location & kinematics (track); and an assessment of its identity & intent (i.e., friendly, hostile, neutral, etc.).

(3) Fire Control Quality Data Attainment – For air targets of interest, data is obtained with enough accuracy and update rate to support engagement (launch decision, guidance calculations, and engagement control). Obtaining data may require tasking sensor resources as well as communication resources (to dedicate a data path, allocate more bandwidth or increase the rate of throughput).

(4) Engagement Initiation or Launch Decision – decision to initiate defensive measures against an air target of interest (includes: threat evaluation, engageability determination, shooter selection or weapontarget pairing, and sensor support selection)

(5) Guidance Calculation – calculation is made of the interceptor guidance required to intercept target. (Note: this may require target discrimination as well)

(6) Engagement Control - engagement is controlled by managing warfare resources that are participating in the engagement (firing interceptor; tasking sensors & communication resources; ensuring resources committed; monitoring are resource performance; ensuring FCO data is available and validating quality of data; monitoring engagement support & ensuring it provided (guidance relay. target is illumination, etc.); and negating (terminating) engagement if necessary.

(7) Guidance Relay – sensor or communication data path provides guidance (in-flight target updates (IFTUs) or target object maps (TOMs)) to interceptor<sup>2</sup> while in flight.

**(8) Target Illumination** – sensor illuminates target to support interceptor<sup>3</sup> homing to target.

### **2.0 IFC Design Considerations**

Just as there are a variety of Operational IFC variants; there are a variety of system

<sup>&</sup>lt;sup>2</sup> For weapon systems that require in-flight guidance or a "map" of the target.

<sup>&</sup>lt;sup>3</sup> For weapon systems that require end game illumination of targets.

solutions or mechanisms that can be employed to enable these capabilities. IFC is based on the collaboration of distributed warfare resources. Such collaboration can be enabled manually or in an automated fashion; from a centralized decision-making C2 node or in a de-centralized fashion; using requests and handshakes, bidding processes, or common decision-aids for simultaneously generating identical task sets. To further complicate matters. the most suitable solution depends operational on the situation; and thus various solution configurations must be available to the Joint warfighter. Therefore, the solution must be designed to handle a variety of IFC processes from supporting the manual selection and control of warfare assets during an engagement to providing sophisticated automation to make optimum resource selection decisions in near-real-time to select the best shooter; predict which sensor or combination of sensors can best guarantee fire control quality data throughout an engagement; and/or determine which units are capable of accepting control of an engagement after launch to enable a forward pass.

The manner in which these fire control functions are performed determines the degree of integration achievable and the ability to perform fire control from a Forcecentric perspective. The key to achieving *integrated* fire control is the realization that these common fire control functions can be performed in a variety of manners:

- [1] Locally or remotely
- [2] From a Unit-centric or Force-centric perspective
- [3] By the weapon system or by common processing
- [4] Centralized or De-centralized control
- [5] Manually or in an Automated-fashion

### 2.1 Local vs. Remote

An examination of the various forms of IFC capabilities possible based on performing the basic fire control functions on one or more warfighting units is summarized in Table 1. The columns represent the different IFC variants. The rows list the fire control functions. "L" is used to describe a function performed by a warfare asset that is local (or

collocated with the system that fires the weapon). "R" describes a function performed remotely or on a unit that is non-collocated with the launching unit.

Table 1 – IFC Options

	FC	LoR	EoR	FP	RF	PSD
Object	R	R	R	L or	R	L or R
Observ.				R		
Object	L &	R	R	L or	R	L or R
Trking/ID	R			R		
FCQ Data	L	R& L	R	L or	R	L or R
Attain.				R		
Eng	L	L	L	L	R	Force
Initiation						Centric
Guidance	L	L	L	L or	L or	L or R
Calc				R	R	
Eng	L	L	L	L &	L or	L or R
Control				R	R	
Guidance	L	L	L or	L or	L or	L or R
Relay			R	R	R	
Target	L	L	L or	L or	L or	L or R
Illumin.			R	R	R	

A box in each mapping is shaded to indicate that the performance of this particular fire control function determines which IFC variant is taking place. For example, in the case of PC (Precision Cue), the aerospace object is observed by a remote unit. In the case of LoR, FCQ data is provided by a remote unit for making the launch decision; however, after launch the local sensor provides FCQ data.

### 2.2 Force-centric IFC



Figure 8 – Shifting to Force-centric Thinking

Figure 8 illustrates the expansion of the "effective engagement envelope" from a single unit using only local resources to multiple fully collaborative or integrated units using resources for the benefit of the group rather than the individual unit's needs. Such collaboration requires system designs that are developed with a "big picture" or forcecentric perspective in which distributed warfare resources are all considered part of a system of systems. Shifting to a Forcecentric perspective is key to enabling all IFC capabilities, since IFC involves the collaboration of distributed assets. For example, Force-centric thinking is necessary for selecting the preferred shooter from a group of distributed firing units.

### **2.3 Common Processing**

Another IFC challenge lies in the necessary paradigm shift of engagement functionality moving out of weapon systems and instead being performed by common processors across warfare units. This difficult, vet necessary, shift is key to enabling more advanced forms of IFC. When engagement functions (such as: pairing a shooter with a target: determining engageability; determining if sensor support is adequate; and making launch decisions) are performed by weapon systems, the focus is unit-centric. Each weapon system is focused on it's own engageability-whether it will intercept the target. The weapon system does not have a broader, force-centric, perspective. It cannot determine if it's the best shooter in the Force; and it will only consider local sensor support.



Figure 9 – Weapon System vs. Common Processing

In order to shift to a force-centric warfare paradigm, engagement functionality must be performed from a Force-level perspective. This requires access to information concerning all the relevant warfare resources (weapons and sensors, namely) within the In order to perform IFC in a Force. decentralized manner, the engagement functions need to be performed using common (identical) algorithms on each participating unit and be fed by a SIAP and common resource information. Figure 9 shows fire control functions historically performed by weapon systems (as illustrated in the upper circle) shifting out of the weapon system and into separate, but common, processing domains (in the lower circle).

In addition to making the decision to engage, additional fire control functions such as guidance computation and engagement control are best performed by common processes to support forward pass. Performing such functions in an identical manner on each unit will enable control of engagement to be passed between units.

Shifting fire control functions into common processors is also key to managing the various types of resources in a coordinated manner. Having separate resource managers for each resource type-such as a weapon manager. sensor manager. and link manager-focuses the use of these resources too narrowly. Each resource managed separately without considering the others only optimizes for that resource. The resources need to be managed by common consider processes that their interdependence and optimized with a "big picture" perspective.

### **2.4 Architecture Considerations**

IFC can be performed using a centralized decision node approach; however there are major advantages to adopting a decentralized approach. The biggest factor is the latency involved in centralized IFC. Aerospace warfare places high demands on rapid decision-making and responses, especially for intercepting hostile aircraft and missiles. Waiting for a launch decision to be made at a remote central decision node may not be an option. In addition, distributing command authority for interceptor launch decisions to the unit level is a long-standing tradition and has its obvious merits. The future vision for decentralized and distributed IFC upholds unit-level command authority. Equipping units with common algorithms to produce identical engagement recommendations at each participating distributed node enables a decentralized, yet Force-centric, approach to IFC.

Figure 10 illustrates centralized а architecture in the upper portion and a decentralized architecture in the lower half. In the upper half, a centralized BMC2 node receives all data, creates a master tactical picture. determines optimum resource tasking, and issues commands out to the distributed units. Thus, the distributed nodes are "dumb" nodes that simply pass data along and receive commands for managing their local resources.



Figure 10 - Architecture Comparison

In the lower half of Figure 10, a decentralized architecture is depicted. In this scene, "smart" nodes communicate and collaborate over a network. In this option, information is shared among the distributed units; each of which develop a shared picture of the battlespace. From the shared picture, each unit then determines the best use of the Force's resources and tasks their local resources accordingly.

### **2.5 Level of Automation**

Another IFC challenge lies in assimilating a great quantity of information with sufficient rapidity and accuracy to effect decisions that are well informed and that mitigate risk. This process of assimilation may be fully manual, fully automated, or rely on a hybrid of human-machine decision-making interactions. The IFC design will need to accommodate situations in which a human operator makes the shooter selection decisions and sensor taskings. The design must also contain sophisticated automated decision aids that will process information to determine and recommend optimized uses of warfare resources. Fully automated modes will be capable of directly tasking warfare resources; yet will allow operators to "command bv negation" (or override automated resource taskings) when the pace battle rhythm demands of the such capability.



Figure 11 – Levels of Automation

Figure 11 shows the human-machine interactions for the three major levels of

automation for IFC: manual, semiautomated, and fully automated.

### **2.6 Control Authority of Warfare Assets**

An important issue related to IFC is the control authority of warfare assets. Historically, the control of weapons and sensors has been the responsibility of the resident warfighter (Officer) in charge of the local platform (ship, aircraft, etc.). Maintaining this control authority is an important design consideration for IFC Each unit needs to implement solutions. decision aids that recommend tasking for all relevant warfare assets in the battle group. However, resident operators need to always have the ability to override resource taskings for local resources, and in many cases, approve resource taskings, such as launch decision, generated in an automated fashion.

### **2.7 IFC Design Principles**

The following design principles are key to achieving IFC for aerospace operations:

[1] Enable fire control functions to be performed locally or remotely

[2] Utilize warfare resources from a Forcecentric perspective

[3] Shift fire control functions from specific weapon system methods to common processes

[4] Design IFC into a decentralized architecture

[4] Enable fire control functions to be performed in an automated-fashion

[5] Perform IFC while enabling local Command Authority

### **3.0 Proposed IFC Concept**

This section proposes a vision or concept for a system solution to enable future IFC operations. The concept is based on the guidance provided by the design principles laid out in the previous section.

The concept is to:

[1] Implement an architecture that combines a network centric paradigm with automated intelligent management of sensors, weapons, and links to overcome individual system limitations and enable collaborative engagements; and

[2] Provide automated engagement decision aids that use "common" algorithms and shared tactical data to simultaneously produce identical engagement recommendations at each distributed unit.

The IFC concept is based on the following three fundamental system characteristics:

- Dynamically updateable doctrine;
- Decentralized architecture; and
- Synchronized information, doctrine, and decision aids

The approach enables each smart node to determine the optimum force-level resource management option and gain nodal agreement among distributed units prior to tasking local resources.

The envisioned concept for future IFC operations is based on a network-centric foundation achieved through implementing common processors on distributed units and enabling enhanced information sharing. Figure 12 provides a context diagram of the distributed units-each containing common processors. The common processors function collaboratively as a distributed system to produce a Single Integrated Air Picture (SIAP). One peer, or warfare unit hosting a common processor, is enlargened to show the processor's interfaces with the unit's resources.



Figure 12 – Distributed System

Each processor contains common processing—identical computational and algorithmic methods. This supports the "Common Processing" philosophy, illustrated in Figure 13, upon which the SIAP concept is based. The philosophy, simply stated, is that identical processors provided with identical sets of data/information input will produce identical tactical air pictures.

This premise is carried one step further in support of future IFC. Equipping each

processor with common decision-making algorithms, which when fed identical track pictures (or data sets), allows each unit to produce identical resource tasking recommendations and engagement orders.



Figure 13 – Common Processing Philosophy

As Figure 14 illustrates, each unit can use "common" algorithms to produce identical Force-level engagement recommendations at each participating node. Therefore, each unit concurrently arrives at the same conclusion that a particular weapon has the best shot and that a particular sensor (not necessarily collocated with the weapon) can best track and/or illuminate the target. This concept relies on incorporating common automated decision aids into each common processor and implementing an architecture that enables the sharing of common data sets and information among units.



Figure 14 – IFC Common Processing

Figure 15 shows a diagram of the automated functions to be performed by each unit to



Figure 15 - Functional IFC Concept

produce identical decision recommendations and management aids. The functions are loosely based on the data fusion construct developed by the Joint Directors of Laboratories (JDL). Figure 15 identifies functional areas that align with the JDL levels of data fusion. The figure shows entities external to the peers such as sensors, weapons, decision-makers, Intel/weather data sources, and the warfighting units to which peers are resident. Figure 15 shows functional domains for fusing data and information to develop a representation of the real operational situation. These functional domains include: Tracking and Combat ID, Object Context Assessment, Threat **Evaluation**, Warfighting Resource Assessment and Environmental Assessment.

The Wargaming domain uses the situation awareness data (or picture) to develop and analyze hypotheses of enemy behavior and the effect of friendly defensive or offensive measures. From wargaming, a determination of the best Course of Action (COA) can be made and a set of resource tasks can be The derived. Distributed Resource Management (DRM) domain then pairs resources with tasks using optimization methods. Finally, the C2 Assessment domain keeps track of plans, procedures, doctrine, and other governing rule sets that are used to make assessments and resource pairing decisions. The functions shown in Figure 15 will be discussed in more detail in the next Section on Key IFC Capabilities.

Table 2 lists decision recommendation products of the processes shown in Figure 15.

4	Table 2 – List of IFC Products
	Products of IFC AMA and Data Fusion Pr
	• Preferred shooter determination

- Weapon-Target Pairing
- Sensor Support for Engagements
- Engagement Control Strategy (i.e., forward pass)
- Engagement Preferences (intercept geometry)

In conclusion, a basic operational example of how this IFC concept would be realized is as follows. Each distributed unit uses "common" algorithms to produce identical Force-level engagement recommendations. Therefore, each unit arrives at the same conclusion that a particular weapon has the best shot; that a particular sensor (not necessarily collocated with the weapon) can best track and/or illuminate the target; and that a particular unit should assume engagement control after missile launch.

### **4.0 Key IFC Capabilities Required**

Based on the IFC introduction presented in section 1; the design principles for IFC established in section 2; and the vision for future IFC proposed in section 3; this section addresses the set of key capabilities required. In order to enable the IFC solution concept illustrated in Figure 15 and described in the previous section, the following capabilities are needed:

- Shared Situation Awareness
- Determination of Best Course of Action
- Distributed Resource Management
- Embedded IFC Planning

### **4.1 Shared Situation Awareness**

Shared Situation Awareness (SA) is key for IFC because each unit needs identical, complete, accurate, & timely awareness (knowledge) of the operational situation. Shared SA is the ability of distributed units to gain a common understanding of the totality of the tactical situation, including the threat, the defended assets, the readiness of warfighting resources, and command and control constraints within which the systems must operate. Figure 16 illustrates the various data sets or "pictures" comprising SA.



Figure 16 – SA Pictures

Each unit must create and maintain a "picture" of each of these aspects (shown in Figure 16) of the operational situation. The

ocess:

pictures are really sets of information, updated on a continuous basis, that are products of the data fusion process.

### Data Fusion Processes

Shared SA relies on common data processing and data fusion algorithms on each distributed unit to assess and develop a representation of the real situation. Table 3 describes each of the primary SA data fusion capabilities.

Table 3 – SA Data	Fusion Capabilities
SA	Description
Capabilities	
Tracking &	<ul> <li>Pixel/Signal-level</li> </ul>
Combat ID	association
	<ul> <li>Object kinematics</li> </ul>
	<ul> <li>Object characterization</li> </ul>
	<ul> <li>Object kinematics</li> </ul>
	prediction
Object	Object relations
Context	estimation
Assessment	• Refinement of object ID &
	typing based on group
	behavior
	<ul> <li>Provision of physical</li> </ul>
	context for track picture
	• Discrimination, kill
	assessment
	• Development &
	maintenance of defended
	assets picture
Warfighting	• Assessment of sensors,
Resource	weapons, & warfighting
Assessment	units
	• Health & status
	assessment
	<ul> <li>Configuration &amp; capability</li> </ul>
	maintenance
C2 Situation	<ul> <li>Assessment &amp; Adoption of</li> </ul>
Assessment	Blue Force C2 inputs
	<ul> <li>Promulgation of</li> </ul>
	commands within
	Community of Interest
	(COI)
	<ul> <li>Translation of C2 inputs</li> </ul>
	into system operating rules,
	constraints, & parameters
SA	Assessment of track
Certification	quality
	<ul> <li>Assessment of track ID</li> </ul>
	confidence
	• Certification of fire control
	quality SA

SA	Description
Capabilities	
Environment	• Development &
Assessment	maintenance of
	environmental picture
	(weather, mapping,
	jamming, etc.) for AOI
Processor	• Assessment of processor
Evaluation	performance (SIAP state)
	• Processor health & status
	assessment
Threat	• Threat identification,
Evaluation	evaluation, and
	prioritization
Force	• Fusion of assessments
Readiness	• Determination of overall
Assessment	readiness of warfighting
	forces

The set of functions that develop SA are data association. and assessment fusion. processes that develop a description or interpretation of the current relationships among aerospace objects, events, and the context of the operational environment. This process estimates the operational situation and assigns quantitative confidence values to the estimates. Effectively, the functions seek to develop as accurate a representation of the real world as possible. Quantitative values are computed to allow decision-makers to know with what confidence a particular object is a threat or what the probability that a particular weapon system will engage a threat, as examples. The payoff of situational automating the assessment capability is that the complex and timecritical nature of operational situations for aerospace warfare can involve the assimilation of large amounts of information in time periods that are too narrow for manual assessment to support rapid and effective decision-making. Performing such assessments on distributed warfighting units to support collaborative operations compounds the challenge. Embedding common situational assessment functions in a network of distributed units that can share data and information is key to enabling IFC.

### **Information Architecture**

Shared SA relies on an appropriate information architecture to enable data sharing among distributed units. While individual warfare units provide organic capabilities, the real force multiplier is when they are netted together in a mutually supportive role—providing a battle space awareness that is greater than the sum of their individual awarenesses. Distributed unit collaboration to achieve shared SA and IFC capabilities is achieved through the establishment, maintenance, and management of Peer-to-Peer (P2P) networks that enable an adequate data dissemination capability.

The reality of warfare operations is that at any given time, warfighting units may be collaborating on various levels based on their collaboration needs as well as their ability to collaborate. Their collaboration needs may range from autonomous operations (or the complete lack of collaboration); to the sharing of tactical information and development of a single integrated air picture; to highly integrated IFC operations involving the commitment of warfare assets to а collaborative warfighting operation involving multiple distributed units. The ability to adequate collaborate depends on communications and data paths between distributed units as well as embedded processor functionality that manage the necessary distribution of data/information that enables automated decision-making capabilities and collaborations to occur.

Objectives for information sharing in support of IFC are as follows:

[1] The information architecture must be based on Force-centric de-centralized architecture

[2] The network must allow warfare resources to be managed according to Force-level needs (rather than unit-centric needs)

[3] Network management must be flexible to enable special data distribution needs during engagements (higher data rate and/or throughput).

Required information dissemination functions are listed in Table 4. These functions need to be performed using common methods across warfare units.

<b>Table 4 – Information Dissemination Functions</b>
Information Dissemination Functions
• Determines needs of information-recipient

Information Dissemination Functions
users or decision nodes (data
advertisements/ subscriptions)
• Tracks data availability
• Establishes routing paths & maintains
connectivity
Optimizes bandwidth usage
<ul> <li>Determines feasibility of</li> </ul>
transmission/checks link status
<ul> <li>Sends and receives commands to/from</li> </ul>
remote link managers to control, manage, &
synchronize transmission
• Transmits data/information according to
local/remote synchronized commands

Table 5 contains types of information that need to be exchanged among distributed units to support the IFC concept. In particular, it is necessary for units to exchange information concerning warfare resources in addition to the sensor data that is the usual focus of tactical information exchange efforts.

### Table 5 - IFC Information Exchange Requirements

Information Exchange Required for IFC
<ul> <li>Associated Measurement Reports</li> </ul>
• Resource information: Health, Status,
Configuration, & Capabilities of Resources
• C2 Datasets (Doctrine, TTPs, plans, manual
commands)
Resource Tasking Requests
Resource Commitment "Handshakes"

Table 6 lists characteristics of the data exchange that are critical to supporting the IFC concept. In a bandwidth-limited environment, it may become necessary to intelligently manage communication resources to support critical aerospace operations such as collaborative engagements.

Table	6 -	Data	Exchange	Characteristics

Data Exchange Characteristics
• Supports real-time P2P exchange of sensor
measurement data
<ul> <li>Broadcast/Multicast/Point-to-Point</li> </ul>
<ul> <li>Non-real-time traffic for operations control</li> </ul>
<ul> <li>Link monitoring</li> </ul>
<ul> <li>Quality of Service delivery</li> </ul>
<ul> <li>Data integrity and confidentiality</li> </ul>
<ul> <li>Bandwidth allocation/monitoring</li> </ul>
• Data dissemination prioritization (for time-

Data Exchange Characteristics
sensitive data or bandwidth constraints)
• Ad hoc nodal topology (nodes can easily join
or leave network)
• Interfaces with Tactical Data Links (TDLs)

### 4.2 Determination of Best COA

Determination of the best Course of Action (COA) is key for determining that a threat requires defensive measures – taking into account possible ramifications. The ability to predict operational situations and hypothesize the effect of alternative COAs (Effects Based Operations), is a powerful aid in effective IFC decision-making. This section introduces the concept of automated wargaming in support of tactical aerospace operations.

The ability to predict enemy COAs provides great advantage to the warfighter. Assigning quantitative confidence values to potential COAs will support other advanced C2 capabilities such as collaborative planning and resource management. For example, based on the confidence level of a predicted enemy Theater Ballistic Missile (TBM) launch site, units may assign a priority level to the site as a possible future threat. This function then feeds the resource management capability by building a case for increased sensor surveillance of the region or a possible assigned strike mission. Examples of enemy COA attributes that can be predicted and assessed are described in Table 7.

|--|

Table 7 - Ellelly CC	A Attibutes
Enemy COA	Description
TBM Launch	Prediction of launch site
Site	locations and types based
	on launch point estimations
	of tracked TBMs.
TBM Launch	Prediction of future TBM
	launches (launch type,
	time, direction) based on
	known and estimated
	parameters and capabilities
	of the launcher (from
	previous launches, Intel, a
	priori knowledge, estimated
	time of mobility of the
	transport-launching
	container, etc.)
Enemy	Prediction that attributes a

Enemy COA	Description
Attribution	particular hostile event or
	object to a particular
	enemy. This is particularly
	important for terrorist
	activity—predicting which
	nation or terrorist group is
	responsible for a hostile
	action.
Enemy Intent	Determination of enemy
-	intention based on actions,
	communications, and
	enemy doctrine.
Enemy	Estimation of the size,
Capability	location, and capabilities of
	enemy forces
Threat	Identification of potential
Opportunities	opportunities for enemy
	threat based on prediction
	of enemy actions, operation
	readiness analysis, of
	friendly vulnerabilities, and
	analysis of environmental
	conditions.
Enemy	Develop a battlespace
Scenarios	visualization of the national
	guidance and assigned
	regional area of
	responsibility to create
	enemy scenarios & enemy
	COA. From this
	visualization, at the
	component-level, targeting
	analysis, SA, target
	development and selection,
	target nomination,
	weaponeering, and Battle
	Damage Assessment can be
	accomplished.

In addition to predicting enemy COAs, automated wargaming methods can provide the ability to identify, evaluate and prioritize blue force COAs based on analyzing historical trends and projecting the performance of sensors and weapons based on their known capabilities.

The future concept is to embed units with common wargaming functionality that enables them to identify and evaluate tactical options for near real-time defensive responses or offensive actions; as well as plan blue force COAs for longer projected time periods such as hours to weeks ahead. Thus, this future capability would bridge the gap between tactical operations and planning capabilities; enabling dynamic replanning and allowing warfighting resources to be used most effectively based on the most current knowledge of the operational situation.

Wargaming functionality includes multiperspective analysis, which analyzes current and predicted operational situations from both red and perspectives. blue Offensive/defensive analysis predicts the results of hypothesized enemy engagements considering rules of engagement (ROE), enemy doctrine, and weapon models. The wargaming would take into account estimated weapons effectiveness based on projected weapon resource capabilities. Wargaming functions calculate effectiveness measurements such as: probability of kill, probability of raid annihilation, probability of survivability, and probability of munitions effectiveness. These projected measures of effectiveness would support the estimate of projected force readiness. Wargaming could enable units to support Effects-Based Operations (EBO) in which the effects of blue force actions on the enemy would be analyzed and assessed to support decision-making. wargaming functionality The produces prioritized blue force COAs that support the generation of missions and tasks for use by the DRM process.

Some additional prediction capabilities that can be integrated into the wargaming to enhance the decision process are listed in Table 8. These include environmental effects on possible COAs; the projection of resource capabilities; and an overall prediction of force readiness.

Table	8 -	Addition	al Pr	ediction	Capabiliti	es
						_

Prediction	Description						
Capabilities							
Environment	Prediction of environmental						
Prediction	effects on hypothesized						
	COAs:						
	- Prediction of weather effects						
	on specific munitions and						
	sensor detection ranges						
	- Prediction of environmental						
	impacts from munitions						
	employment.						

Prediction	Description					
Capabilities						
Resource	Prediction of the capability					
Projection	and performance of sensors,					
	weapons, & units given					
	hypothesized COAs.					
Force	Prediction of Force Readiness					
Projection	- Prediction of overall force					
-	readiness & capabilities					

Once a blue force defensive or offensive action is determined as the optimum COA, a list of tasks for warfare resources can be derived. This set of tasks feeds the DRM process described in the next section.

### 4.3 Distributed Resource Management

Distributed Resource Management (DRM) is key to enabling and optimizing the use of distributed resources for collaborative and integrated fire control. DRM is effectively the culmination of the data fusion processes performed for SA and determining the best COA. DRM is the capability that allocates the prioritized tasks to the optimum sensor and weapon resources.

Input • Warfighting Resource Picture • Prioritized Threats • Prioritized Blue Force COA • Environment Picture • Defended Assets Picture • C2 Information-Rule-sets	A
Distributed Resource Management • Generate Tasks (translate COAs into tasks) • Identify available resources • Perform allocation optimization or task scheduling (allocate tasks to resources)	
Output • Allocated Tasks (task assignments per resource for entire Force)	

Figure 17 – DRM Input and Output

For input, the DRM capability requires results of situation assessment and situation prediction. The DRM must identify a running list (that is continually being updated as the operational situation changes) of specific tasks (or resource missions) based on the identified and prioritized threats, best estimated blue force COA, and operational situation (i.e., environment, defended assets Figure 17 shows DRM locations, etc.). functions and the input and output to this function set.

The DRM uses optimization techniques to schedule tasks or allocate them to the most suitable warfighting resources. Based on the availability and capability of resources at any given time, the DRM may have to modify the list of tasks and determine that some cannot be performed or may be performed in a different order. The advantage of the DRM capability is that it enables each distributed unit to determine the best use of each resource in the "force" (or within a set of collaborating peers) and to make this determination in а near-simultaneous manner. In this way, resources can be used for force needs rather than just for the needs of an individual unit.





The basic concept for implementing DRM is the development of a set of processing algorithms, containing automated methods for optimization and decision aids, that will be replicated on each participating warfighting unit to effectively produce the same decision results given that each instantiation will be fed with the common

information embedded in the SIAP. Figure 18 shows the major functions involved in DRM.

Table 9 contains IFC functions performed by the DRM fusion and optimization engine. The functions in Table 9 indicate the detailed decision-making that needs to be performed to "determine the prioritized list of resource tasks" and "generate allocation options and select optimum"; as these fusion engine functions are shown in Figure 18.

Table 9 - DRM Fusion Engine Functions
DRM Fusion Engine Functions for IFC
Launch determination
- Receive threat & COA determination
- Assess engageability of weapon options
- Determine intercept probability
- Decide to launch (or not)
Engagement support strategies
- Threat detection/cue
- FCQ data availability
- Sensor tasking/commitment
- Preferred sensor arrangement
Weapon-target pairing
- Preferred shooter determination
- Engageability of weapon options
Selective engagement
- Selection of best option if multiple
engagement options along the threat
trajectory exist
Engagement support strategy after launch
- Forward pass (preferred eng control option)
- Remote guidance relay (preferred sensor
arrangement)
- Remote target illumination (preferred sensor
support)

An additional capability for effective DRM is a synchronization process shares that allocation results to compare and correct for discrepancies. This step may be necessary to distributed units compute ensure that identical decision results; especially when the commitment of distributed resources is critical, as is the case for IFC.

A bonus feature of DRM is that it distributes command authority to individual units. Historically, the control of weapons and sensors has been the responsibility of the resident warfighter (Officer) in charge of the local unit (ship, aircraft, etc.). Maintaining this control authority is a feature of DRM. Each unit would use the DRM capability to

formulate sets of tasking for all relevant warfare assets (both resident and nonresident) in the battle group. However, resident operators always have the ability to override resource taskings for local resources generated in an automated fashion by the DRM. Thus, command authority is upheld.

### 4.4 Embedded IFC Planning

Embedded IFC planning is key to the automated orchestration of IFC operations. Prior to deploying warfare units into operation, planners can establish doctrine to guide the automated systems that perform decision-making capabilities. Table 10 lists examples of built-in planning that can be performed and embedded into the systems prior to operations.

#### Table 10 – IFC Planning

IFC Planning Functions
<ul> <li>Predicting operational situations that</li> </ul>
require collaborative fire control
<ul> <li>Establishing prioritization schemes for</li> </ul>
missions, threats, defended areas, tactics
• Establishing rule sets to guide resource
behavior for IFC operations
<ul> <li>Establishing parameters to control</li> </ul>
engageability calculations, target-weapon
pairing, target identification/threat
evaluation, & sensor tasking
Establishing decision logic

Planning that is predetermined or established prior to operations is called deliberate Planning. Two levels of deliberate planning exist: defense planning and defense design. Defense planning refers to macro-level planning—establishing plans from a larger perspective. Defense design is planning at the micro-level—assigning TTPs and rule sets to specific resources and establishing parameters for computational systems. Examples of each are shown in Table 11.

Table 11 -	Defense P	lanning	and Def	fense Desig	gn
Defense	Planning	or - "M	acro"	Planning	7

- Assigning resources to missions
- Allocating areas/zones within theater
- CINC priorities
- Identifying critical assets

### Defense Design – "Micro" Planning

- Specific TTPs & Rule sets
- Initialization parameters
- Correlation Track Quality Values

Dynamic Planning is the modification of plans during operations. This capability is also referred to as dynamic replanning. This capability is useful because the reality of operational situations can rarely unfold exactly as predicted in a plan. Implementing a plan that reflects reality by updating is based on up-to-the-moment data as it becomes available becomes a necessary capability for IFC and automated decision aids. Implementing dynamic planning allows the systems to take resource changes into account-sometimes resources break or become unavailable. It also supports faster Blue Force reaction times by taking into account unexpected enemy COAs and threats. Table 12 lists examples of dynamic planning functions.

Table 12 – Dynamic Planning Functions			
Dynamic Planning Functions			
• Replanning – dynamic creation of new plan			
• Refinement of plan			
Reassignment of resources			
Ad hoc operations			
<ul> <li>Alteration of rule sets</li> </ul>			
Reset of parameters			
<ul> <li>Reestablishing prioritization</li> </ul>			

### 5.0 IFC Development Strategy

This section presents a strategy for developing the key capabilities required to enable the proposed IFC concept.

There are three levels of IFC capabilities<sup>4</sup> that development efforts should aim towards as objectives:

[1] **Enhanced Air Picture**: cleaner/better/ more complete/more common

[2] AMA for weapon/target & sensor/target pairing: "best" weapon, "best" target, "best" kill location, "best" tactics

[3] **Full AMA/DRM**: IFC competes with other mission areas for resources

The first level provides enhanced data for firing units. This level can be considered the NCW foundation of shared information gained by a network-centric environment; and upon

<sup>&</sup>lt;sup>4</sup> Defined by Joint SIAP System Engineering Organization (JSSEO) Team; June 2004

which, advanced IFC capabilities can be built. Enhanced data shared among remote units provides enhancements for IFC. The second objective level includes the use of automated decision aids to recommend the best weapon and sensor pairings with targets. This level is effectively, the optimized management of distributed resources for fire control or engagement purposes. Finally, the third objective level broadens the scope of automated resource management to all applicable operational mission areas, of which fire control is one. Achieving this capability level allows resources to be optimally managed across mission areas. The development strategy presented in this paper addresses the achievement of the second level: managing resources within the IFC mission area.

The second strategy guiding the development approach is to build in increments or spirals that afford intermediate IFC capabilities. The rest of this section proposes development spirals based on grouping similar system capabilities into four spirals, with each consecutive spiral adding more functional sophistication.

The four spirals are identified as:

- [1] The NCW Foundation
- [2] Common & Request-Based IFC
- [3] Semi-Automated & Force-Centric IFC
- [4] Fully Automated & Optimized IFC



Figure 19 – Spiral Levels of Accomplishment

Figure 19 shows how each spiral provides increasing levels of IFC in terms of the IFC design principles. The green columns show that engagement functionality is performed by weapon systems in the first spiral, but shifts into a common process by the second spiral. The other three groups of colored columns show incremental increases in levels of automation, DRM complexity, and Forcecentricity (shifting from a unit perspective to a Force-level perspective).

### 5.1 Spiral 1 – NCW Foundation

The first IFC development spiral is the establishment of a NCW foundation—the ability to share high quality data for fire control. This spiral assumes a P2P network and the implementation of common processes across distributed units to generate a single integrated air picture. Spiral 1 IFC capabilities are focused on sharing Fire Control Quality (FCQ) data among distributed units and issuing automated requests to distributed sensors to provide additional data.

### System Capabilities Required:

### [1] Track Certification

The provision of a certification process, which determines track quality and certifies individual tracks for "engageability" due to the data quality, data latency, associated CID, and other appropriate criteria.

[2] Shared Associated Measurement Data

Enhanced networks for sharing measurement data with high rates and throughput

### [3] Sensor Tasking Requests

The ability to determine in an automated fashion that additional data is required for a particular track or sector; and the ability to broadcast a request within the COI.

### [4] Sensor Request Prioritization

The ability to prioritize received sensor tasking requests when multiple requests are received concurrently. Example prioritization schemes include: first come, first serve; request urgency labeling (example levels may include: desired, urgent, critical, etc.); and prioritization according to the request source (some requesting units may have precedence over others).

### [5] Engagement Notification

The ability to send weapon launch notifications to participating units within the COI. This capability places requirements on the network and network interfaces to handle the formatting and transmission of weapon launch notifications.

### **IFC Capabilities Achieved:**

• **Precision Cue** – receipt of a remote "cue" or alert of a potential threat target

• Engagement Notification – notification to COI when a weapon fired

• Request for Off-board Sensor Support request broadcast within COI for remote sensor data to provide precision cue (surveillance) or higher track accuracy.

• Positive Interceptor Identification – veru high confidence identification of aerospace object within track picture that represents interceptor

• Manual LoR - engagement is prosecuted on the available filtered track state. However, the weapon system performs engagement functions and the local sensor must be capable of supporting the engagement after launch as a back up if the composite track state is not sufficient.

• Manual EoR - use of remote FCQ data to support EoR; however, remote sensor support tasking and commitment requires Operator (or manual) in the loop.



Figure 20 - Spiral 1 Accomplishments

Figure 20 shows the level of integration or collaboration that is achieved according to some of the IFC design principles that guide the IFC concept and development. The graphs illustrates that: the engagement functions still reside in the weapon systems and are not performed by common processes; processes are mainly manual but some automation exists; that DRM is very basic; and that the fire control focus is unit-centric.

### 5.2 Spiral 2 - Common/Request-Based IFC

The second IFC development spiral is primarily focused on the shift of fire control (or engagement) functionality out of weapon systems and into common processors. Additionally, spiral 2 includes the ability to issue requests among distributed units to engage a threat.

### **System Capabilities Required:**

### [1] Sharing Resource Information

Enhanced networks for sharing sensor resource information among distributed units [2] Enhanced Sensor Scheduling

Enhanced scheduling/prioritization schemes for the optimal determination of sensor tasks.

### [3] Self-monitoring

The ability to monitor/assess picture quality and the functioning of the common processes & networks to determine incomplete picture, low quality or latent track data, or other possible error sources.

### [4] Weapon Tasking Requests

The ability to broadcast weapon task requests (requests that other units engage a particular threat) in an automated fashion within COI.

### [5] Intelligent Processing

The ability to optimally apply the use of data fusion algorithms and filter out data to fuse only the optimal data to produce the highest quality track picture.

### [6] Common Fire Control Functionality

Fire control functions performed by common processors (rather than by weapon systems).

### **IFC Capabilities Achieved:**

• Request-based EoR - request broadcast within COI for remote sensor to provide FCQ data on threat throughout duration of engagement

• Request-based Selection Shooter request broadcast within COI for remote weapons to intercept a particular threat

• Automated LoR (or composite) – launch decision computed for local weapon based on composite track picture or best available data & data fusion processes



Figure 21 - Spiral 2 Accomplishments

Figure 21 illustrates that in Spiral 2: engagement functionality has shifted our of weapon systems and into common

processors; the level of automation and DRM complexity has increased (enhanced sensor schedulers and automated request-based engagements); and that using request-based weapons management enables an advancement in the ability to operate from a Force perspective.

### 5.3 Spiral 3 – Semi-Automated & Force-Centric IFC

The third IFC development spiral focuses on increasing automated processes for managing resources and on a Force-level determination of the preferred shooter.

### System Capabilities Required:

[1] **Request-based DRM** – generation and transmission of requests for engagement support (by weapon or sensor) to specific unit based on limited awareness of that unit's resource capabilities. Ability to gain resource commitments in automated fashion.

[2] **Basic AMA** – basic ability to determine collaborative engagement strategies involving local and remote resources; as well as evaluating distributed shooter-target pairings to select optimum.

[3] **Basic Deliberate Planning** – basic embedded doctrine and rule sets to enable the automated evaluation of optimal engagement strategies and resource use.

### **IFC Capabilities Achieved:**

**Enhanced Request-Based IFC** - Requestbased IFC capabilities (such as EoR, selecting the best shooter, tasking sensors to enhance the picture) are enhanced because each distributed unit computes determinations of resource capabilities, instead of have to interact with the local and remote sensor and weapon systems. Thus, the determinations are enhanced and more rapidly made. Additionally, resources can be committed in an automated fashion.

• **Basic Preferred Shooter Determination** Distributed units simultaneously determine the optimum shooter for each threat based on their situation awareness of battlespace and weapon HSCC.

Figure 22 illustrates that in Spiral 3: levels of automation, DRM complexity, and Forcecentricity have risen. The addition of AMAs and embedded planning enable distributed resources to be managed with a more Forcelevel perspective.



Figure 22 - Spiral 3 Accomplishments

### 5.4 Spiral 4 – Fully Automated IFC

The fourth IFC development spiral achieves the vision set forth in this paper for a proposed IFC concept. Spiral 4's capabilities achieve the Level 2 IFC objectives of full automation for optimized DRM within the IFC mission area.

### System Capabilities Required:

### $\left[1\right]$ Advanced Data Fusion and SA

Advanced COA determination (effects based operations) – units use enhanced SA and AMAs to perform wargaming functions to determine best COA based on estimated enemy COAs and the threat picture. From the COAs, a detailed sets of tasks are defined that need to be performed by the distributed resources.

### [2] Fully Automated DRM

Participating PROCESSORs simultaneously compute the optimum use of the Force's distributed resources to perform defined sets of tasks (determined from COA determination) within the IFC mission area. Each unit then tasks its local sensors based on the Force-level determination of optimized missions.

### [3] Deliberate and Dynamic Planning

Embedded plans as well as dynamic planning capabilities provide rule sets and logic for AMAs to function and make decision recommendations in an automated fashion. Planning functions enable resources to be allocated to tasks according to planned rules.

### **IFC Capabilities Achieved:**

• **Automated IFC** – distributed units simultaneously determine the optimum distributed resource engagement strategies involving the best use of distributed sensors, weapons, and C2 resources; and then task local resources based on the Force-level determinations. Advanced IFC strategies achieved include:

- > Distributed sensor management
- > Preferred shooter determination
- > Automated EoR
- > Forward pass
- **Remote fire**



Figure 23 – Spiral 4 Accomplishments

Figure 23 illustrates that the IFC capabilities provided in Spiral 4 enable the design principles of common fire control functionality, full automation, envisioned DRM, and Force-level perspective are reached.

### **6.0 Conclusion**

In conclusion, this paper set forth to define the IFC problem space; explore design principles to govern IFC solutions; propose a grand vision for future IFC operations; introduce capabilities required to achieve the proposed IFC concept; and discuss an incremental development strategy for achieving the vision.

The following list of "take-aways" conclude this paper:

• Performing fire control using distributed resources in an integrated and collaborative manner takes advantage of network-centric advances and is the key to future aerospace warfare advances.

• Design principles guiding IFC solutions include a de-centralized architecture, automating processes, using common fire control functions across the Force, and using a force-wide perspective in managing resources. • The proposed IFC concept is based on automated engagement decision aids that use "common" algorithms and shared tactical data to simultaneously produce identical engagement recommendations at each distributed unit.

• Key capabilities required include: shared SA, determination of best COA, DRM, and embedded IFC planning.

• IFC development strategy is based on spiral builds that afford intermediate IFC capabilities while focused toward automated Force-centric IFC vision.

### **References**

[1] Alberts, David S., et al., *Network Centric Warfare, Developing and Leveraging Information Superiority*, 2/e CCRP Publication Series, 2000.

[2] Alberts, David S., et al., *Understanding Information Age Warfare*, CCRP Publication Series, August 2001.

[3] Antony, Richard T., *Principles of Data Fusion Automation*, Artech House, Inc., 1995.

[5] Capstone Requirements Document (CRD) for Theater Air and Missile Defense (TAMD) (S/NF) JROCM 056-01, 1 March 2001.

[5] Crowe, Doug, et al., Integrated Architecture Behavior Model (IABM) Configuration 05 Description Document Version x.xa (Working Copy), JSSEO, June 2004.

[6] Hall, David L., *Mathematical Techniques in Multisensor Data Fusion*, Boston: Artech House, Inc., 1992.

[7] Hall, David L. & McMullen Sonya A.H., Mathematical Techniques in Multisensor Data Fusion, 2<sup>nd</sup> ed., Artech House, Inc., 2004.

[8] Johnson, Bonnie & Green, John M., Naval Network-Centric Sensor Resource Management, Command & Control Research & Technology Symposium, 2002.

[9] Johnson, Bonnie, Green, John M., & Canfield W., *Gaining Naval Battle Space Through Automation*, National Fire Control Symposium, 2001.

[10] Schroeder, Jerry, et al., Single Integrated Air Picture (SIAP) Operational Concept Document, JSSEO, 2002.

[11] Schroeder, Jerry, White Paper on Integrated Fire Control (Advanced Engagement Concepts) for Joint Theater Air and Missile Defense, SIAP Program, 1999.

[12] Schroeder, Jerry, White Paper on Automated Battle Management Aids for Joint Theater Air and Missile Defense, SIAP Program, 1999.

[11] Smith, Edward A., *Effects Based Operations*, CCRP Publication Series, 2002.

[12] Steinberg, Alan N., Bowman, Christopher L., & White Franklin E., *Revisions to the JDL Data Fusion Model.* 

[13] Young, Bonnie W., A C2 System for Future Aerospace Warfare, Command and Control Research and Technology Symposium, 2004.





# Future Integrated Fire Control ICCRTS 2005

### June 2005

CYBERSPACE

SPACE

OUTER

0

A TRANU MOAN

Bonnie Young Senior System Architect Northrop Grumman Corporation Bonnie Young@ngc.com 703-407-4531 Future C2 Challenges:
Information Dominance
Most Effective Use of Joint/Coalition Assets & Forces
Dynamic Force & C2 Tailoring

> Remote Sensor

> > Elevated Coverage

Engage on Remote

> Remote Sensor

Engage on Remote Engage on Remote

-41

# **C2** Challenges for Future Warfare



• Non-interoperable pictures: air, ground, maritime

• Non-interoperable units: ships, aircraft, land assets, etc.

• Uncoordinated C2/Decisionmaking: use of weapons & sensors is "platform-centric"

• JEZ: achieve ability for aircraft & interceptors to share airspace

• IFC: achieve ability to utilize non-collocated weapons & sensors to perform fire control

• Enhance C2 decision-making to support time-critical Joint (& Coalition) operations



The role of C2 in warfare operations is to optimize the use of offensive and defensive resources to combat enemy threats.

Future advances in Joint C2 will rely on:

- Automated Decision-Making
- Advanced Data Fusion
- Enhanced Situational Awareness
- Distributed Resource Management
- Collaborative Time-Critical Missions
- Collaborative Planning & Dynamic Re-Planning
- Force-Wide Resource Optimization

### **Research Goal:**

To explore concepts and develop capabilities that achieve shared battlespace situational awareness among distributed forces and optimize the management of distributed warfare resources for Force-centric collaboration.

### **Sponsors:**

- Joint Single Integrated Air Picture (SIAP) System Engineering Org.
- Navy's Common Command and Decision (CC&D) System
- Johns Hopkins University Masters Program

### **Major Participants:**

- Mike Green, Naval Post Graduate School, Monterey, CA
- William Canfield, Lockheed Martin, Moorestown, NJ
- Ray Thornber, Galaxy Scientific, San Diego, CA
- Capt Jeff Wilson & JSSEO Staff, JSSEO, Arlington, VA

# Integrated Fire Control C2 Design Considerations Future C2 Concepts Key Capabilities Required Conclusion

Integrated Fire Control (IFC) refers to the participation and coordination of multiple noncollocated warfare assets in tactical engagements of enemy targets

• IFC is the ability to develop fire control solutions from information provided by remote sensors

• IFC expands the weapon's effective kinematic range by removing dependency on range limits of the local sensors

• Future advances in aerospace warfare depend largely on IFC – the collaborative use of distributed warfare assets for time-critical aerospace engagements.

# Why Integrated Fire Control?

# The ability to direct distributed warfare resources in a collaborative manner enables major enhancements for tactical fire control:

- Selection of the best shooter from a set of geographically distributed weapons
- Improved chance of interception (by selecting the optimal engagement geometry)
- Improved economy of weapon resources (by reducing redundant shots)
- Earlier launch decisions are possible (remote detection/precision tracking)
- Decoupling of local sensor/weapon pairing constraint
- Sharing engagement control forward pass
- Off-board engagement support for guidance relay and target illumination

• Enhanced defense against complex threat environments (sophisticated or significant numbers of aerospace targets) – IFC may be a necessity for victory

# **IFC Variants**



# **Fire Control Functions**

Fire Control Function	Function Description
<b>Object Observation</b>	Sensor(s) observes aerospace object.
Object Tracking & Identification	Object is tracked and identified – sensor measurements are used to estimate an object's location, kinematics, identity & intent
Fire Control Quality Data Attainment	Data is obtained with enough accuracy and update rate to support engagement (launch decision, guidance calculations, and engagement control). (May involve sensor tasking or managing data path (dedicated or increased bandwidth))
Engagement Initiation	Decision is made to initiate defensive measures against an air target of interest (includes: threat evaluation, engageability determination, shooter selection, sensor support selection).
Guidance Calculation	Calculation is made of the interceptor guidance required to intercept target.
Engagement Control	Warfare resources are managed during engagement: weapon control; tasking sensors & communication resources; ensuring resource commitment; monitoring resource performance; validating FCQ data; monitoring engagement support; and negating (terminating) engagement if necessary.
Guidance Relay	Sensor or communication data path provides guidance (in-flight target updates (IFTUs) or target object maps (TOMs)) to interceptor while in flight.
Target Illumination	Sensor illuminates target to support interceptor homing to target.

# Integrated Fire Control C2 Design Considerations Future C2 Concepts Key Capabilities Required Conclusion

# **Design Considerations**

The manner in which C2 functions are performed determines the degree of integration achievable and the ability to control Forces from a Forcecentric perspective.

The key to achieving *integrated* C2 or fire control is the realization that common command and decision functions can be performed in a variety of manners:

- [1] Locally or remotely
- [2] From a Unit-centric or Force-centric perspective
- [3] Using unique or common processing
- [4] Centralized or De-centralized control
- [5] Manually or in an Automated-fashion

# Local vs. Remote

	PC Precision Cue	LoR Launch on Remote	EoR Engage on Remote	FP Forward Pass	RF Remote Fire	<b>PSD</b> Preferred Shooter Determination
Object Observation	R	R	R	L or R	R	L or R
Object Tracking & Identification	L & R	R	R	L or R	R	L or R
Fire Control Quality Data Attainment	L	R & L	R	L or R	R	L or R
Engagement Initiation	L	L	L	L	R	Force Perspective
Guidance Calculation	L	L	L	L or R	L or R	L or R
Engagement Control	L	L	L	L & R	L or R	L or R
Guidance Relay	L	L	L or R	L or R	L or R	L or R
Target Illumination	L	L	L or R	L or R	L or R	L or R

= Key function that, when performed remotely, distinguishes an IFC variant

# **Shifting to Force Level Thinking**



# **Unique vs. Common Processing**

Another challenge lies in the necessary paradigm shift to performing C2 functions in an identical manner at each node. This difficult, yet necessary, shift is key to enabling more advanced forms of C2.



• The fire control focus is unit-centric

• Each weapon system is focused on it's own engageability—whether it's weapon will intercept the target

• Each weapon system cannot determine if it is the best shooter in the Force; and each will only consider local sensor support

• Forward Pass would be cumbersome if not impossible

- Fire control focus is Force-centric
- Requires access to information concerning all the relevant warfare resources within the Force
- Preferred shooter determination among Force's weapons is enabled
- Advanced forms of IFC requiring automation such as LoR and EoR are more effectively performed
- Performing fire control functions in an identical manner on each unit enables control of engagement to be more easily passed between units

# Centralized vs. De-centralized



## C2 can be performed using a centralized decision node approach; however there are major advantages to adopting a decentralized approach:

• The biggest factor is the latency involved in centralized C2. Aerospace warfare places high demands on rapid decision-making and responses - waiting for a launch decision to be made at a remote central decision node may not be an option.

• Distributing command authority for interceptor launch decisions to the unit level is a long-standing tradition and has its obvious merits.

• Equipping distributed units with common algorithms to produce identical engagement recommendations enables a decentralized, yet Force-centric approach and eliminates a single point of failure



# Manual vs. Automated

### Manual Decision-making

Process

С

0

N

т

R

0

L

Humans make distributed collaboration decisions
Humans communicate over voice communications or "intranet chat" to commit resources for IFC

### Semi-Automated Decision-making

-Humans make distributed collaboration decisions with aid of machine-fused & shared picture - Resource control, tasking, and commitment performed using automated feedback and control processes



### **Automated Decision-making**

- Machines perform decision-making capabilities as well as feedback processing, information display, and control.

- Machine-generated decision options are presented to human for monitoring and command by negation (overriding automated decisions).

# **Command Authority**

C2 must be designed to permit local control of warfare assets, thus maintaining organic command authority, while enabling Force-level optimized asset utilization, control, and collaboration across distributed warfighting units or hosts.

- Perform launch decision locally
- Use common decision aids that recommend resource usage (e.g., weapon-target pairing) with Force-wide perspective
- Ensure local operators always have ability to override local resource taskings generated in an automated fashion
- Maintain operator ability to manage resources manually

# **C2 Design Principles**

# The following design principles are key to advancing future C2 capabilities:

[1] Enable fire control functions to be performed locally or remotely

[2] Utilize warfare resources from a Force-centric perspective

[3] Shift common command and decision functions from unique methods to common processes

[4] Design C2 into a decentralized architecture

[4] Enable C2 decision-making to be performed in an automated-fashion

[5] Perform IFC while enabling local Command Authority

# Introduction to IFC IFC Design Considerations Future C2 Concepts Key Capabilities Required Conclusion

# **Future C2 Concepts**

[1] Implement an architecture that combines a network centric paradigm with automated intelligent management of sensors, weapons, and links to overcome individual system limitations and enable collaborative engagements; and
[2] Provide automated engagement decision aids that use
"common" algorithms and shared tactical data to simultaneously produce identical engagement recommendations at each distributed unit

### **Characteristics:**

- Dynamically updateable doctrine
- Decentralized architecture
- Synchronized information,
- doctrine, decision aids

Each smart node determines optimum force-level resource management option & gains nodal agreement prior to tasking resources

# **Distributed System of Peers**



- Each warfighting unit implements common processing algorithms to perform Joint tactical BMC2 functionality.
- A peer is defined as the common C2 processing integrated with a unit's warfare resources.
- A "system" of distributed peers interacts or collaborates by sharing information over a Peer-to-Peer (P2P) network.

# **Common Processing Philosophy**

The philosophy, simply stated, is that common processing algorithms provided with identical data & information input will produce identical picture, assessment, and decision results.

Peer Product: Tactical Picture



# **Common Processing for C2**





# **Common C2 Processing Products**

### **Products of AMA and Data Fusion Process:**

- Preferred shooter determination
- Weapon-Target Pairing
- Sensor Support for Engagements
- Engagement Control Strategy (i.e., forward pass)
- Engagement Preferences (intercept geometry)

**Example:** each distributed unit uses "common" algorithms to produce identical Force-level engagement recommendations. Therefore, each unit arrives at the same conclusion that a particular weapon has the best shot and that a particular sensor (not necessarily collocated with the weapon) can best track and/or illuminate the target.

# Integrated Fire Control C2 Design Considerations Future C2 Concepts Key Capabilities Required Conclusion

# **Key Capabilities Required**

### **Collaborating units need to determine:**

- Preferred shooter
- Weapon-Target Pairing
- Sensor Engagement Support Strategy
- Engagement Control Strategy (i.e., forward pass)
- Engagement Preferences (i.e., forward pass)

### What capabilities are needed?

- Shared Situation Awareness
- Determination of Best Course of Action
- Distributed Resource Management
- Embedded C2 Planning

# **Shared Situation Awareness...**

The price

# ... is key because each unit needs identical, complete, accurate, & timely awareness (knowledge) of the operational situation.

		<b>Track Picture</b> Fundamental track & CID data representation of aerospace objects.	<b>Defended Assets Picture</b> The location, status, & prioritization of all defended assets (ground, maritime, & aerospace; as well as Blue Force, Coalition, & Civilian)). Includes defended aerospace objects and zones as well as points or areas on the ground within			
	Objec Estim of aer	<b>Dbject Context Picture</b> Estimates of the group behavior of aerospace objects.		area of interest.	<b>C2 Situation Picture</b> Decision-maker commands, assigned missions of warfighting units	
		<b>Environmental Picture</b> Meteorological, electromo atmospheric information	e agnet conc	tic jamming, & cerning the	doctrine, Tactics Techniques Procedures (TTPs), location ar of IABMs, status of P2P netwo	and nd status ork.
reat Picture battle space area of inter		rest.	<sup>rest.</sup> Warfare Resources Picture			
identification, evaluation, and ritization of aerospace threat objects				The location, Health, Status, Configuration, and Capability (HSCC) information of each warfare resource		
				(sensors, weapons, and warfighting units).		

**Shared Situation Awareness (SA)** is the ability of distributed units to gain an understanding of the totality of the tactical situation, including the threat, the defended assets, the readiness of warfighting resources, and command and control constraints within which the systems must operate.

# **Data Processing & Fusion**

### Shared SA relies on:

Data processing and data fusion algorithms to assess and develop a representation of the real situation

### **Situation Assessment Capabilities**

### Tracking & Combat ID

- Pixel/Signal-level association
- Object kinematics
- Object characterization
- Object kinematics prediction

### **C2 Situation Assessment**

Assessment & Adoption of Blue Force C2 inputs

- Ensure peer promulgation of commands
- Translate C2 inputs into system operating rules, constraints, & parameters

### **SA Certification**

- Assessment of track quality
- Assessment of track ID confidence
- Certification of fire control quality SA

### **Object Context Assessment**

- Estimate object relations
- Refine object ID & typing based on group behavior
- Provide physical context for track picture
- Discrimination, kill assessment
- Maintain defended assets picture

### Warfighting Resource Assessment

Assessment of sensors, weapons, & warfighting units

• Health & status assessment

• Configuration & capability maintenance

### **Environment Assessment**

• Develop & maintain environmental picture (weather, mapping, jamming, etc.) for AOI

### **Peer Evaluation**

- Assessment of Peer processing performance
- Peer health & status
- assessment

### **Threat Evaluation**

• Identify, evaluate, & prioritize threats

### Force Readiness Assessment

Fusion of assessments

• Determination of overall readiness of warfighting forces

# **Information Architecture**

### Shared SA relies on:

An appropriate information architecture to enable data sharing among distributed units.

### <u>Peer-to-Peer (P2P) Network</u> <u>Capabilities</u>

### **Objectives for Information Sharing:**

Based on Force-centric de-centralized architecture

- Allows warfare resources to be managed according to
- Force-level needs (rather than unit-centric needs)
- Manages network to enable special data distribution needs during engagements. (higher data rate or throughput)

### Information Dissemination Capabilities:

- Determines needs of information-recipient users or decision nodes (data advertisements/ subscriptions)
- Tracks data availability
- Establishes routing paths & maintains connectivity
- Optimizes bandwidth usage
- Determines feasibility of transmission/checks link status
- Sends and receives commands to/from remote link managers to control, manage, & synchronize transmission
- Transmits data/information according to local/remote synchronized commands

### Information Exchange Required:

- Associated Measurement Reports
- Resource information: HSCC
- C2 Datasets (Doctrine, TTPs, plans, manual commands)
- Resource Tasking Requests
- Resource Commitment "Handshakes"

### Data Exchange Characteristics:

- Supports real-time P2P exchange of sensor measurement data
- Broadcast/Multicast/Point-to-Point
- Non-real-time traffic for operations control
- Link monitoring
- Quality of Service delivery
- Data integrity and confidentiality
- Bandwidth allocation/monitoring
- Data dissemination prioritization (for timesensitive data or bandwidth constraints)
- Ad hoc nodal topology (nodes can easily join or leave network)
- •Interfaces with Tactical Data Links (TDLs)

# **Determination of Best COA...**

### ... is key for determining that a threat requires defensive measures taking into account possible ramifications (Effects Based Operations)



- Projects the current situation into the future to estimate the enemy COA and potential impact of the blue force's planned actions.
- Develops and assesses alternative futures or hypotheses concerning the current situation and possible COAs.
- Assigns quantitative confidence values to potential COAs
- Enables collaborative planning, effective resource management, and dynamic replanning

# **Distributed Resource Management...**

# ... is key to enabling and optimizing the use of distributed resources for collaborative and integrated fire control

Distributed Resource Management	<ul> <li>Engagement support strategy after launch</li> <li>Forward pass (preferred eng control option)</li> <li>Remote guidance relay (preferred sensor arrangement)</li> <li>Remote target illumination (preferred sensor support)</li> </ul>			<b>Selective engagement</b> - Selection of best option if multiple engagement options along the threat trajectory exist
Launch determination			<b>Engagement support strategies</b>	Weapon-target pairing
- Receive threat & COA determination			- Threat detection/cue	- Preferred shooter
- Assess engageability of weapon options			- FCQ data availability	determination
- Determine intercept probability			- Sensor tasking/commitment	- Engageability of weapon
- Decide to launch (or not)			- Preferred sensor arrangement	options

• Based on the use of automated management (or decision) aids to determine and recommend optimum uses of warfare resources

- Using identical AMAs on distributed units enables decisions to be made in a timely manner to support time-critical engagement operations.
- Each distributed unit uses distributed resource management AMAs to determine tasks for all resources within the community of interest (COI)

• Resident operators always have ability to override resource tasking recommendations for local resources; thus command authority is upheld.

# **DRM Capability**



# **Embedded IFC Planning...**

### ... is key to the automated orchestration of IFC operations

### Built-in planning prior to operations is a key enabler of AMAs:

- Predicting operational situations that require collaborative fire control
- Establishing prioritization schemes for missions, threats, defended areas, weapons, tactics
- Establishing rule sets to guide resource behavior for IFC operations
- Establishing parameters to control engageability calculations, target-weapon pairing, target identification/threat evaluation, & sensor tasking
- Establishing decision logic

### Deliberate Planning is the predetermination

### of resource utilization.

### **Defense Planning - "Macro" Planning**

- Assigning resources to missions
- Allocating areas/zones within theater
- CINC priorities
- Identifying critical assets

### Defense Design - "Micro" Planning

- Specific TTPs
- Rule sets
- Initialization parameters
- Correlation Track Quality Values

### Dynamic Planning is the modification of plans during operations

### **Dynamic Planning Functions:**

- Replanning dynamic creation of new plan
- Refinement of plan
- Reassignment of resources
- Ad hoc operations
- Alteration of rule sets
- Reset of parameters
- Reestablishing prioritization

### Why Dynamic Planning is Useful:

- Plan implementation needs to reflect reality
- Resources change (things break, resources become unavailable)
- Enemy prediction never 100% accurate (unexpected events, enemy COAs, & threats)

# Integrated Fire Control C2 Design Considerations Future C2 Concepts Key Capabilities Required Conclusion

# Conclusion

• Using distributed resources in an integrated and collaborative manner takes advantage of network-centric advances and is the key to future air warfare and missile defense advances

• Design principles guiding advanced C2 solutions include a decentralized architecture, automating processes, using common fire control functions across the force, and using a force-wide perspective in managing resources

• The proposed strategy distributes C2 "power" to the edge: missile defense systems maintain self-contained command authority while also becoming full participants in force-centric family of systems

• Key capabilities required include: shared SA, determination of best COA, DRM, and embedded IFC planning.

# **BACK UP CHARTS**

# **Development Strategy**

### **Objective Capability Levels:**

[1] Enhanced Air Picture: cleaner/better/common

[2] AMA for weapon/target & sensor/target pairing ("best" weapon, "best" target, "best" kill location, "best" tactics)

[3] Full AMA/DRM: IFC competes with other mission areas for resources

### **Development Strategy:**

- > Develop system capabilities to reach at least level [2] objective
- > Build in increments or spirals that afford intermediate IFC capabilities

### Spirals:

[1] NCW Foundation: Sharing high quality data for fire control

[2] Request-based IFC & common engagement functionality

[3] Basic semi-automated & force-centric IFC

[4] Fully Automated & Optimized IFC



## 1<sup>st</sup> IFC Development Spiral

> NCW Foundation: Sharing high quality data for fire control

### **System Capabilities Required:**



- Track certification

- Enhanced networks for sharing measurement data with high rates and throughput

- Automated sensor task requests broadcast within COI
- Basic sensor request prioritization scheme (for when multiple requests are received)
- Engagement notification broadcast within COI

### IFC Capabilities Achieved:

- Precision Cue receipt of a remote "cue" or alert of a potential threat target
- Engagement Notification notification to COI when a weapon fired

- **Request for Off-board Sensor Support** – request broadcast within COI for remote sensor data to provide precision cue (surveillance) or higher track accuracy.

- **Positive Interceptor Identification** – absolute (100% confidence level) identification of aerospace object within track picture that represents interceptor

- **Basic Launch on Remote or Composite** - engagement is prosecuted on the available filtered track state. However, the weapon system performs engagement functions and the local sensor must be capable of supporting the engagement after launch as a back up if the composite track state is not sufficient.

- **Semi-automated EoR** - Use of remote FCQ data to support EoR; however, remote sensor support tasking and commitment requires Operator (or manual) in the loop

## **2<sup>nd</sup> IFC Development Spiral**

### Request-based IFC & common engagement functionality

### System Capabilities Required:

- Networks share sensor resource information (HSCC) among distributed units

Lvl of

DRM

**Complexity Centricity** 

Lvl of

Force-

Eng Fn

Shift to

IABM

Lvl Of

Auto-

mation

- Automated sensor resource scheduling/prioritization schemes
- Self-monitoring (to determine incomplete picture or low quality track data)
- Automated weapon task requests broadcast within COI
- Intelligent application of best data fusion algorithms and best available data to produce most accurate target track
- Launch decision (engageability) functionality shifts from weapon system to IABM

### **IFC Capabilities Achieved:**

- **Request-based EoR** – request broadcast within COI for remote sensor to provide FCQ data on threat throughout duration of engagement

- **Request-based Shooter Selection** - request broadcast within COI for remote weapons to intercept a particular threat

- Automated LoR (or composite) – IABM computes launch decision for local weapon based on composite track picture or best available data & data fusion processes

## **3<sup>rd</sup> IFC Development Spiral**

> Basic semi-automated & forcecentric IFC



### System Capabilities Required:

- Enhanced automated sensor scheduling techniques
- Request-based distributed resource management
- Basic automated management aids
- Basic deliberate planning

### **IFC Capabilities Achieved:**

- **Enhanced Request-Based IFC** - All request-based IFC capabilities (such as EoR, selecting the best shooter, tasking sensors to enhance the picture) are enhanced because each distributed unit manages local sensors and weapons using automated common IABM processes (rather than having to interact with Operators or local sensor/weapon systems).

- **Basic Preferred Shooter Determination** - Distributed units simultaneously determine the optimum shooter for each threat based on their situation awareness of battlespace and weapon HSCC.

## 4<sup>th</sup> IFC Development Spiral

### Fully Automated & Optimized IFC

### **System Capabilities Required:**

- Advanced data fusion and situation assessment
- Advanced COA determination (effects based operations)
- Fully automated DRM
- Deliberate and dynamic planning

### **IFC Capabilities Achieved:**

- **Automated IFC** – distributed units simultaneously determine the optimum distributed resource engagement strategies involving the best use of distributed sensors, weapons, and C2 resources; and then task local resources based on the Force-level determinations. Advanced IFC strategies achieved include:

- -Distributed sensor management
- -Preferred shooter determination
- -Automated EoR
- -Forward pass
- -Remote fire

