

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE APR 2008		2. REPORT TYPE		3. DATES COVERED 00-00-2008 to 00-00-2008	
4. TITLE AND SUBTITLE K-Band TWTA for the NASA Lunar Reconnaissance Orbiter				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NASA Glenn Research Center, Cleveland, OH, 44135				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM002087. Proceedings of the 2008 IEEE International Vacuum Electronic Conference (9th) (IVEC 2008) Held in Monterey, CA on April 22-24, 2008. U.S. Government or Federal Rights License					
14. ABSTRACT see report					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 2	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

11.4: K-Band TWTA for the NASA Lunar Reconnaissance Orbiter

**Dale A. Force,
Raine N. Simons,
Todd T. Peterson**

NASA Glenn Research Center,
Cleveland, OH 44135
Dale.A.Force@nasa.gov

**Adán Rodríguez-Arroyo,
Jirasak Visalsawat**

NASA Goddard Space Flight
Center, Greenbelt, MD 20771

**Paul C. Spitsen,
William L. Menninger,
Neal R. Robbins,
Daniel R. Dibb, Phillip C. Todd**

L-3 Communications Electron
Technologies, Inc., Torrance, CA
90509

Keywords: K-Band; traveling wave tube; Lunar Reconnaissance Orbiter, TWTA, EPC

Abstract: *This paper presents the K-Band traveling wave tube amplifier (TWTA) developed for the Lunar Reconnaissance Orbiter and discusses the new capabilities it provides.*

Introduction

The Lunar Reconnaissance Orbiter (LRO) is the first mission in NASA's Vision for Space Exploration, a plan to return to the moon and then to travel to Mars and beyond. LRO will launch in late 2008 with the objectives to finding safe landing sites, locate potential resources, characterize the radiation environment, and demonstrate new technology.

The spacecraft will be placed in low polar orbit (50 km) for a 1-year mission under NASA's Exploration Systems Mission Directorate. LRO will return global data, such as day-night temperature maps, a global geodetic grid, high-resolution color imaging and the moon's UV albedo. However, there is particular emphasis on the polar regions of the moon where continuous access to solar illumination may be possible and the prospect of water in the permanently shadowed regions at the poles may exist. After one year, the Orbiter will transition to a science phase under NASA's Science Mission Directorate [1]. The Orbiter Program Office is located at NASA Goddard Spaceflight Center.

The K-Band data link transmits at 25.65 GHz with left-handed circular polarization, with rate 1/2, K=7 convolutional and RS coding. The transmission rate is 228.7 Msps for normal operations (100Mbps before coding) with contingency rates of 114.3 Msps (50 Mbps) and 57.2 Msps (25 Mbps). LRO uses a 75 cm combined S-band/K-Band high gain antenna for the K-Band link, transmitting to an 18 m antenna at White Sands. Since the orbiter needs 40 W of RF power to provide adequate margin on the link, a TWTA was needed.

The LRO TWTA contract [2] is managed by NASA Glenn Research Center as a continuation of the 32 GHz high power TWT program with L-3 Communications,

Electron Technologies, Inc. (ETI), which produced a 180 W TWT [3].

TWTA Design

By basing the design of the LRO TWT on the 180 W TWT, we were able to provide a very robust TWT for the LRO mission very rapidly. The chief changes needed were to redesign the input and output couplers to connect to WR-34 instead of WR-28 waveguide, and to modify the helix design for the lower power and frequency.

The LRO TWT is a helix TWT with a four stage depressed collector, samarium cobalt periodic permanent magnetic focusing, and a tungsten/osmium cathode.

The EPC design is based on the L-3 Communications, ETI standard 2300Hx series, with the necessary modifications to meet the LRO specifications. The most significant change was to the input filter and magnetics to reduce greatly the Conducted Emissions of the EPC. The modifications reduced the Conducted Emissions by more than 20 dB, although the EPC is still short of the stringent MIL-STD-461C. The L-3 Communications ETI designation of the TWTA is Model 9835H.

The following tables compare the NASA specifications for the TWTA with the actual performance of the Flight Model (SN 201) and Protoflight Model (the spare, SN 202).

Except for the conducted emission, the Flight Model TWTA meets the NASA specifications. The Flight Model TWTA was delivered for integration into the Lunar Reconnaissance Orbiter communications subsystem in January 2008. The Protoflight Model TWTA meets the NASA Specifications except for the conducted emissions and for the worst case DC power consumption. The Protoflight Model TWTA was delivered in March 2008.

Future Missions

A third TWT was built under this program (SN 203). The third TWT is being considered for the Communication Navigation and Networking Reconfigurable Testbed (CoNNeCT). The LRO TWTA design also serves as the baseline for the Lunar Communications Terminal (LCT).




Figure 1
TWTs SN 201 and 202

Table I
TWTA K-Band TWTA Specifications

Parameter	NASA Specifications
Frequency Band	25.5-25.8 GHz
Output Power (CW)	40 W min.
Saturated Gain	46 dB min.
Sat. Gain Flatness	0.5 dB max.
AM-to-PM	4.5 deg/dB max.
VSWR	2.0:1 max.
TWT Efficiency	44 % min.
Mass	3.5 kg max.
DC Power	104 W max.
Overall Efficiency	38.5 % min.
Operating/Mission Life	14/26 months
Environment	Lunar orbit
Input/Output Ports	WR-34
EMI/EMC Specification	MIL-STD-461C

Table II
TWTA K-Band TWTA SN 201 Performance

Parameter	Performance
Frequency Band	25.5-25.8 GHz
Output Power (CW)	41.6 W min.
Saturated Gain	48.93 dB min.
Sat. Gain Flatness	0.3 dB
AM-to-PM	3.3 deg/dB max.
VSWR	1.7:1 max.
TWT Efficiency	49.5 % min.
Mass	2.95 kg
DC Power	94.6 W max.
Overall Efficiency	44.0 % min.

Table III
TWTA K-Band TWTA SN 202 Performance

Parameter	Performance
Frequency Band	25.5-25.8 GHz
Output Power (CW)	41.0 W min.
Saturated Gain	47.93 dB min.
Sat. Gain Flatness	0.1 dB
AM-to-PM	2.6 deg/dB max.
VSWR	1.81:1 max.
TWT Efficiency	44.6 % min.
Mass	2.95 kg
DC Power	107.8 W max.
Overall Efficiency	38.0 % min.

References

- [1] <http://lunar.gsfc.nasa.gov/mission.html>
- [2] NASA Glenn Research Center Contract Number NNC04CB13C
- [3] W. Menninger, N. Robbins, D. Dibb, and D. Lewis, "Power Flexible Ka-band Traveling Wave Tube Amplifiers of Up to 250-W RF for Space Communications," *IEEE Trans. Electron Devices*, vol. 54, no. 2, pp. 181-187, Feb. 2007.