PROPELLANT FORMULATION DEVELOPMENT FOR FUTURE ARMY WEAPONS SYSTEMS BY MEANS OF ADVANCED MODELING AND FLAME KINETICS RESEARCH

R. Sausa^{*}, M. Grams^a, C. Conner^a, and W. Anderson US Army Research Laboratory Aberdeen Proving Ground, MD 21005-5069

ABSTRACT

We apply our experimental and modeling results of a number of burner-stabilized flames relevant to the combustion of solid propellants to calculate the burning rates of tri-amino-guanidiniumazotetrazolate (TAGzT) with and without a nitrate ester-based propellant using our CYCLOPS combustion model that we developed at US Army Research Laboratory. The model employs a detailed, chemical reaction mechanism containing 59 species and 368 reactions. Our calculations show that TAGzT enhances the burning rate of the base propellant over a range of pressures used for rockets and guns; a factor of three at 10 MPa.

1. INTRODUCTION

Predictive modeling of a solid propellant's burn rate is essential to guiding and developing novel propellant formulations for Future Combat Systems and for providing a fundamental screening tool that can result in substantial cost savings compared to experimental formulation and missile and gun firings. As a result, much recent research centers on computer models with detailed chemical mechanisms to predict the burning rate of materials (Miller and Anderson, 2004, and references therein; Miller, 2005). Essential to these models is an accurate knowledge of the gas-phase processes and reaction kinetics. Burner-stabilized flames provide a convenient method to test these mechanisms for accuracy of their reaction's rate constants over a wide temperature range (Grams and Sausa, 2008, and reference therein). In this paper, we report our experimental and modeling results of various burner-stabilized flames, NH₃, H₂, HN₃/O₂, N₂O, NO₂, and apply these results to predict the burning rate of TAGzT and TAGzT with nitrocellulose (NC), nitrate ester (NE), and nitroglycerine (NG) with our two-phase, combustion model CYCLOPS. TAGzT is a very promising, new whose high-nitrogen compound combustion products are environmentally-safe and also help decrease gun barrel and rocket nozzle erosion, thus

increasing the life-time of those components (Leveritt et al., 2006).

2. EXPERIMENT AND MODEL

We describe the details of our experimental apparatus elsewhere (Grams and Sausa, 2008; Venizelos and Sausa, 2000s; Miller and Anderson, 2004). Figure 1 shows a photograph of burning propellant strand and a drawing depicting the complex molecular processes associated with the event. Briefly, we calculate the burning rates of TAGzT and 20% TAGzT with an 80% nitrate esterbased propellant (NC:NE:NG::60:25:15) over a broad pressure range using Cyclops, a burn-rate predictor developed at the US Army Research Laboratory. The CYCLOPS predictor employs a detailed chemical mechanism containing over 350 elementary chemical reactions involving about sixty species. We derive this mechanism from a critical

Caricature of Molecular Nature of Burning Propellant CAS-PHASE FLAME Elementary reactions Thermal conduction Convection Multi-component carisoptic Thermal diffusion Multi-COMPONENT CAS-PHASE FLAME Elementary reactions Multi-component carisoptic Thermal diffusion Multi-component carisoptic Thermal density changes Mixture properties Mixture propert

Fig. 1. Burning solid propellant (left) and associated molecular processes (right).

^a ARL Postdoctoral Research Associate

Report Documentation Page					Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.							
1. REPORT DATE DEC 2008				3. DATES COVERED -			
4. TITLE AND SUBTITLE					5a. CONTRACT NUMBER		
Propellant Formulation Development For Future Army Weapons					5b. GRANT NUMBER		
Systems By Means Of Advanced Modeling And Flame Kinetics Research					5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER			
					5e. TASK NUMBER		
					5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Research Laboratory Aberdeen Proving Ground, MD 21005-5069					8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)					10. SPONSOR/MONITOR'S ACRONYM(S)		
					11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited							
^{13. SUPPLEMENTARY NOTES} See also ADM002187. Proceedings of the Army Science Conference (26th) Held in Orlando, Florida on 1-4 December 2008, The original document contains color images.							
14. ABSTRACT							
15. SUBJECT TERMS							
16. SECURITY CLASSIFIC	CATION OF:	17. LIMITATION OF	18. NUMBER	19a. NAME OF			
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ABSTRACT UU	OF PAGES 5	RESPONSIBLE PERSON		

Standard Form 298 (Rev. 8-98	3
Prescribed by ANSI Std Z39-1	ŝ

literature review, and test its H-N-O component with our unique, burner flame apparatus that is equipped with advanced laser spectroscopic and molecular beam, mass-spectrometric diagnostics. We measure the temperature of a number of NH₃, H₂, HN₃/O₂, N₂O, NO₂ flames by thin-wire thermometry, and the stable and radical species concentrations by molecular beam-mass spectrometry, laser induced fluorescence, or both, as function of height above burner surface. We then compare the experimental species profiles to those we calculate with the Sandia PREMIX flame code containing the propellant's detailed chemical mechanism (Kee et al, 1991, 1994). Rate and sensitivity analyses reveal new chemical information relevant to H-O-N chemistry, which is unique to advanced, high-nitrogen, energetic ingredients such as TAGzT.

3. RESULTS AND DISCUSSION

PREMIX Overall, our flame calculations predict very well the stable species H_2 , HN_3 , N_2O , NH_3 , NO_2 , N_2 , NO, O_2 , and radical species OH and NH for a number of flames. We present representative data in figure 2. Figure 2a (top) shows both the NH LIF and modeled profiles of an H₂/O₂/HN₃ flame. The experimental profile is normalized to the modeled profiles near 6 mm for comparison purposes. Figure 2a reveals that the NH concentration decreases rapidly from the burner surface and is zero above 10 mm. The modeled profiles agree very well with the experimental profile at burner distances greater than 4 mm, but not as well near the burner surface. Sensitivity analysis reveals that the reactions $HN_3+OH=N_3+H_2O$ (R1) and $HN_3+NH=N_3+NH_2$ (R2) are important in determining the NH, HN₃, and NO concentrations throughout the flame. particularly near the burner surface, and that their rate constants are much higher than those reported in the literature (LeBras and Combourieu, 1973; Li et al., 2006). Our model does a better job predicting our experimental NH data near the burner surface when we decrease the rate expression of reactions R1 and R2 by a factor of four and three, respectively (see figure 2a, modelmodified).

The slopes of the NH profiles near the burner surface, 2 to 4 mm, are about two orders of magnitude more than the slope from 4 to 9 mm. This dramatic change in slope suggests that there are two or more reactions that are responsible for NH



Fig. 2. NH LIF and flame model data (top) and modeled NH rates.

production and consumption, and that their interplay determines the observed shape of the NH profile. A plot of the calculated NH rate as a function of burner distance, presented in figure 2b (bottom), shows that NH is produced by the reaction $N_3+H=NH+N_2$ and consumed by the reactions $HN_3+NH=NH_2+N_3$, $NH+NH=N_2+H+H$, and NH+OH=H+HNO near the burner surface, less than 2 mm. The reaction $NH_2+H=NH+H_2$ plays an important role in forming NH from 2 to 8 mm. The NH peak at 5 mm corresponds to the shoulder in the experimental NH profile near 5mm.

Figure 3 shows a chemical pathway diagram from our in-house, post processing program for the H₂/O₂/HN₃ flame. It reveals how HN₃, a four atom, high-nitrogen compound, decomposes to its intermediate and final products. HN₃ reacts predominantly with OH, H, and NH to form N₃, which mostly reacts with H and itself to form N₂. N₃ also reacts with H to form NH, which in turn forms additional N2. The attack of H and NH on HN₃ to form NH₂ is another channel for HN₃ decomposition. The resulting NH₂ reacts mostly with OH to form NH₃. NO is formed mainly from the reactants HNO+H, NO₂+H, and NH+O, directly or by means of the N intermediate which reacts with OH. Some of the NO converts to N₂ directly, by reacting with N, NH, or N3, or indirectly, by reacting with NH and N₃ to form N₂O, which subsequently reacts with H. We observe the major and most of the minor species experimentally, and their profiles agree with those we calculate with Sandia PREMIX flame code (Grams and Sausa, 2008).

Figure 4 shows the experimental and predicted burning rates of neat TAGzT over the 0.1 to 200 MPa range. The model predicts the experimental data very well at pressures less than 10 MPa (Tappan et al., 2006; Korobeinichev et al., 2006). Above 10 MPa, the burning rate curve plateaus. Unfortunately, we are not aware of any corresponding experimental data for comparison purposes. A plausible explanation in the rate's leveling off is the decrease in heat feedback to the burner surface at the higher pressures. Our sensitivity analyses reveal that many temperaturesensitive reactions associated with the gas-phase chemistry are both operable at 0.1 MPa and 300 MPa. Table 1 lists the reactions for 0.1 MPa. Many

Table 1. Temperature sensitive reactions near the propellant surface showing endothermic or exothermic character at 0.1 MPa for pure TAGzT

$NH + NH = N_2 + H + H$	Endothermic		
$2H + M = H_2 + M$	Exothermic		
$N + H_2 = NH + M$	Exothermic		
$HCN + H (+M) = H_2CN (+M)$	Exothermic		
$2H + H_2 = 2H_2$	Exothermic		
$H_2CN + N \Leftrightarrow N_2 + H (+M)$	Endothermic		
$NH_3 (+M) = NH_2 + H (+M)$	Exothermic		



Fig. 3. Pathway diagram of an $H_2/O_2/HN_3$ flame



Fig. 4. Modeled and experimental rates of TAGzT

of these reactions are exothermic and provide heat feedback to the surface to gasify the surface products, which in general increase the propellant's burning rate. Near 300 MPa and above, many of these reactions become endothermic and thus provide less heat feedback to the surface compared to the 0.1 MPa reactions. As a result, the propellant's burning rate is less than the expected rate for that pressure and its burning curve deviates from linearity.

Figure 5 shows the experimental and predicted burning rates of TAGzT with and without the base propellant. The model predicts very well the base propellant's burning rates over the pressure regions of 0.3 to 10 MPa (Miller, M., private communication) and 14 to 500 MP (Juhasz et al., 1999). Figure 5 also shows that TAGzT increases the burning rate of the base propellant over the 0.1 to 1000-MPa pressure range. This enhancement is as much as a factor of six at lower pressures, but becomes less significant at 100 MPa and is negligible above 200 MPa.

CONCLUSION

Advanced flame diagnostics and modeling capabilities provide the necessary tools for characterizing new, propellant formulations for Future Force weapons systems. Our CYCLOPS model predicts very well the burning rates of TAGzT over a wide rage of pressure, and reveals that TAGzT enhances the burning-rate of the selected nitrate ester propellant. The agreement between experiment and model is a testament to the high the extremely intricate auality of chemical mechanisms that we have developed. Interaction between the flame kinetic studies and propellant models is synergistic in that the flame studies provide mechanistic testing and refinements, while the propellant models highlight features needing further study in the flame experiments

ACKNOWLEDGMENTS

Drs. Grams and Conner are grateful to the National Research Council and Oak Ridge Associated Universities, respectively, for their postdoctoral research associateships. This work is supported by the EQT Program.

REFERENCES

Conner, C. and Anderson, W., 2007: Predicted Burning Rate Enhancement by TAGzT in



Fig. 5. Modeled and experimental rates of NC-NE-NG with and without TAGzT

The Combustion of Nitrate Ester Propellants, Proceedings, JANNAF 34th Propellant & Explosives Development and Characterization Subcommittee Reno, Nevada August 13 – 17, 2007.

Grams. M.P. and Sausa, R.C., 2008: The Combustion of a Simple, High-Nitrogen Compound: An Experimental and Modeling Study of a Low Pressure, Hydrazoic Acid-Doped Flame, Proceedings, JANNAF 42nd Combustion Meeting, Newton, MA, May 12-16.

Juhasz, A., Bullock, C., Homan, B. and Devynck, D., 1999: Micro Closed Bomb for Characterizing the Burning of Propellants at Gun Pressures," 36th JANNAF Combustion Subcommittee Meeting, CPIA Publ. 691, Vol. 1, Chemical Propulsion Information Agency, Columbia, MD, 175-187, 1999.

Kee, R.J., Grcar, J.F., Smooke, M.D. and Miller, J.A., 1985, 1991: A FORTRAN Program for Modeling Steady, Laminar, One-Dimensional Premixed Flames, Sandia national Laboratories Technical Report SAND 85-8240, December 1985; reprinted March 1991.

Kee, R.J., Rupley, F.M. and Miller, J.A., 1991, 1994: CHEMKIN-II: a FORTRAN Chemical Kinetics Package for the Analysis of Gas-Phase Chemical Kinetics, Sandia National Laboratories Report SAND89-8009, 1991; reprinted 1994.

Korobeinichev, O., Paletsky, A., Tereshchenko, G., Volkov, E. and Budachev, N., 2006: Combustion Chemistry of Double Base Propellants with Additives of High Energy Materials, Interim ARO Progress Report, Grant Number W911NF-05-1-0549, January 2006

LeBras G. and Combourieu, J., 1973: Reactions of atomic hydrogen and active nitrogen with hydrogen azide, *Int. J. Chem. Kinetics*, 5(4), 559-576.

Leveritt, C., Michienzi, C., Brant, A. and Knott, C., 2006: High-Energy Gun Propellants Containing High-Nitrogen Modifiers, Proceedings, 33rd JANNAF Propellant and Explosives Development and Characterization Subcommittee Meeting, Destin, Florida, March 2006, JSC CD-42.

Li, S., Zhang, Q. and Wang, W., 2006: *Ab initio* and variational transition state approach to atmospheric photooxidation: Mechanism and kinetics for the reaction of HN_3 with OH radical," *Chem. Phys. Let.*, 428(4-6), 262-267.

Miller, M.S., 2005: Burning-Rate Models and Their Successors, a Personal Perspective, in: Overviews of Recent Research on Energetic Materials, R.W. Shaw, T.B. Brill, and D.L. Thompson, Eds., Advanced Series in Physical Chemistry Vol. 16, World Scientific, London, chapter 13.

Miller, M.S. and Anderson, W.R., 2004: Burning-Rate Predictor for Multi-Ingredient Propellants: Nitrate-Ester Propellants," *Journal of Propulsion and Power*, 20(3) 440-454.

Tappan, B., Ali, A., Son, S. and Brill, T., 2006: Decomposition and Ignition of the High-Nitrogen Compounds Triaminoguanidinium Azotetrazolate (TAGzT), Propellants, Explosives, Pyrotechnics 31, 163.

Venizelos, D.T. and Sausa, R.C., 2000: Detailed Chemical Kinetics Studies of an $NH_3/N_2O/Ar$ Flame by Laser-Induced Fluorescence, Mass Spectrometry, and Modeling, Proceedings of the Combustion Institute, Volume 28, 2411–2418.