HARDENED AIRCRAFT SHELTER TEST PROGRAM

by

Michael M. Swisdak, Jr.

ABSTRACT

Operation DISTANT RUNNER produced data on the size and distribution of both airblast and debris produced by the detonation of 4500 kilograms of high explosive inside a Third Generation Hardened Aircraft Shelter. DISTANT RUNNER also produced data on the fragment/debris hazard ranges which are associated with detonations inside the shelter. After the full scale tests were completed, that event was modeled at two scales 1:10 and 1:4. These structures utilized detailed geometric modeling of both the rebar and the aggregate with which the reinforced structure was built. The concrete mixture, however, was modeled for the full-scale compressive strength. The 1:10 size model appeared to behave as if it were more like a 1:7 scale model. This appeared in the airblast, the size and distribution of the debris, and the hazard ranges produced by the debris. Because of this, testing at a larger scale was undertaken. This paper will present the results of breakup and debris throw for a guarter-scale shelter. Results obtained from all three scales will also be compared. For the structure modeled in these tests and with the decisions which were made about the details of the modeling utilized, the apparent scale factor (as determined from the breakup of the structure) differs from the design scale factor. As the scale size becomes larger (i.e., smaller models), the differences between design and apparent scale factor increases .

INTRODUCTION

During August through September 1981, Field Command, Defense Nuclear Agency (FC/DNA) conducted a five-event, high explosive test series at White Sands Missile Range, New Mexico. This test series, DISTANT RUNNER, was part of the Defense Nuclear Agency's Theatre Nuclear Forces Survivability, Security, and Safety Program. Event 4 of that series exposed one hardened aircraft shelter (HAS) to an internal pressure/fragmentation loading generated by the simultaneous detonation of 12 MK 82 General Purpose Bombs (Net Explosive Weight (NEW) 1040 kg (2292 pounds) of tritonal) inside the closed shelter. Event 5 exposed another shelter to an internal pressure/fragmentation loading generated by the simultaneous detonation of 48 MK 82 General Purpose Bombs (Net Explosive Weight (NEW) 4159 kg (9168 pounds) of tritonal) inside the closed shelter. A detailed description of the DISTANT RUNNER Program is found in References 1-5.

Because of the scope and completeness of the data generated during the DISTANT RUNNER Series, it was felt that this was an ideal opportunity to investigate/validate the use of affordable models for the breakup of reinforced concrete structures subjected to internal detonations. Five small-scale (1/10) replica models were built and tested. Event 5 of DISTANT RUNNER was the prototype for all of these 1/10-scale models. The data generated included structural breakup, debris distributions (mass and areal density), internal

Report Documentation Page				Form Approved OMB No. 0704-0188		
Public reporting burden for the col maintaining the data needed, and including suggestions for reducing VA 22202-4302. Respondents sho does not display a currently valid (llection of information is estimated t completing and reviewing the collect g this burden, to Washington Headqu uld be aware that notwithstanding au OMB control number.	o average 1 hour per response, inc ion of information. Send comment arters Services, Directorate for Inf ny other provision of law, no perso	luding the time for reviewing insi ts regarding this burden estimate formation Operations and Reports on shall be subject to a penalty for	ructions, searching exis or any other aspect of the s, 1215 Jefferson Davis failing to comply with	sting data sources, gathering and his collection of information, Highway, Suite 1204, Arlington a collection of information if it	
1. REPORT DATE 2. REPORT TYPE			3. DATES COVERED 00-00-1992 to 00-00-1992			
4. TITLE AND SUBTITLE	4. TITLE AND SUBTITLE 5a. CONTRACT NUMBER					
Hardened Aircraft	Shelter Test Progra	am		5b. GRANT NUN	MBER	
				5c. PROGRAM H	ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NU	JMBER	
				5e. TASK NUME	BER	
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANI Naval Surface Wai Hampshire Avenu	7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center, Indian Head Division, 10901 New Hampshire Avenue, Silver Spring, MD, 20903-5640					
9. SPONSORING/MONITO	RING AGENCY NAME(S)	AND ADDRESS(ES)		10. SPONSOR/M	IONITOR'S ACRONYM(S)	
				11. SPONSOR/M NUMBER(S)	IONITOR'S REPORT	
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT lic release; distribut	ion unlimited				
13. SUPPLEMENTARY NO See also ADA26093 CA on 18-20 Augu	ottes 85, Volume II. Minu st 1992.	ites of the Twenty-	Fifth Explosives Sa	afety Semina	r Held in Anaheim,	
14. ABSTRACT see report						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF					19a. NAME OF	
a. REPORTb. ABSTRACTc. THIS PAGEABSTRACTunclassifiedunclassifiedunclassifiedReport (SAR)				OF PAGES 20	KESPONSIBLE PERSON	

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std Z39-18 and external airblast, and full-scale debris hazard range. This effort is described in References 6-7.

Analysis of the 1/10-scale results (airblast and debris size) (reported in Reference 6) indicates that the structure behaved as if it were larger than it actually was. That is, the data indicate that it behaved more like a 1/6.586 scale rather than a 1/10 scale. Reference 6 postulated several possible reasons for this difference in breakup. These included: (1) concrete strength, (2) use of welded wire mesh instead of rebars, and (3) scaling of the surface energy of the concrete.

Because of the questions that grew out of the analysis of the 1/10-scale data, it was proposed that a further series of experiments at a larger scale (approaching 1/3 to 1/4) be undertaken. This program was to include developmental "slab" tests at various scales before **a** full model (at a scale to be determined) was built. Because of funding constraints, it was decided to jump directly to the larger model test, omitting the intermediate "slab" tests which were to be used to better describe the concrete breakup, shape, and mass distributions as a function of scale. After investigation, it was decided that the most economical scale (from the standpoint of the availability of materials) was 1/4-scale. In 1990, one 1/4-scale model aircraft shelter was constructed at the New Mexico Institute of Mining Technology (NMIMT), Socorro, New Mexico. Twenty-nine days after the final concrete pour (exhaust port), the model was tested. Reference 8 describes the NMIMT effort in model construction and data collection.

MODEL PHILOSOPHY

The 1/10-scale trials were designed to model both the external shots as well as Event 5 of DISTANT RUNNER. In addition, a mass model of an aircraft was included inside each shelter. Each MK 82 bomb and its location was also modeled. Internal and external airblast were measured on each shot. After this test series was completed, it was the consensus that the pre-conditioning shots (external airblast events) did not contribute to the strength (or weakness) of the model and could be eliminated from any further testing effort. Moreover, the mass model of the airplane did not seem to contribute to shelter response or to the external debris (only small amounts of material attributable to the airplane model was located outside the shelter). As a result, for the 1/4-scale test, no airplane model was included and airblast was not recorded.

1/4-SCALE MODEL DETAILS

The total NEW on DISTANT RUNNER Event 5 was 9,168 pounds--contained in 48 Tritonal-loaded MK 82 bombs. When the NEW is calculated for 1/4-scale, it is 143.25 pounds of tritonal. It was decided to substitute Composition C-4 for the tritonal. When the TNT equivalences are taken into account, approximately 130-140 pounds of C-4 are required, depending upon the TNT equivalence selected. Each bomb case was simulated by iron pipe with nominal outer diameter 2.625", inner diameter 2.386", and length 13.5 inches. A 0.375" end cap was welded on one end. The total explosive weight (including C-4 explosive and the C3 DETASHEET used to initiate it) was 137.08 pounds. All bomblets were initiated simultaneously, using identical lengths of NONEL and detonating cord. Figures 1 and 2 show the locations of each bomblet stack.

The shelter was constructed using one-quarter scale reinforcing bar which was welded into mats of the appropriate diameter (0.207" and 0.120") and spacing. The concrete mix used for the structure was scaled from the DISTANT RUNNER mix, with adjustments made for availability of materials and producibility. Test specimens of all concrete mixes were taken and compressive strengths as a function of cure time were determined. All were near or exceeded 4000 psi at the time of the test. The double-corrugated liner material was not readily available. A single manufacturer was located and the material was manufactured to the appropriate dimensions.

The blast deflector design was scaled up from the 1/10-scale models, rather than scaled down from the full scale. At the time of the 1/10-scale tests, it was decided that this simplification would not affect the quality of the results and would greatly simplify construction, thereby reducing costs.

The floor was joined to the walls of the structure in the same manner as was done on the 1/10-scale models. This has proven to be a point of concern. After discussions with the Department of Defense Explosives Safety Board (DDESB), it was decided that the 1/4-scale test should model the 1/10 scale tests, rather than the full scale event. Several different schemes have been used in prototype structures to join the walls of the shelter to the floor slab. One of these where the walls are lightly tied to the floor was modeled on both the 1/10-scale and the 1/4-scale tests.

RESULTS AND OBSERVATIONS

The test was conducted on September 5, 1990. A general impression of the observers present was that the model appeared to break-up into larger pieces than had been expected. In fact, what appeared to be the entire side wall of the structure could be seen flying through the air. It must be pointed out, however, that this same phenomena was observed on DISTANT RUNNER Event 4. On that event, the side wall appeared to fly, wing-like, over the fiberboard fragment recovery bundles, landing in front of one of the high speed cameras.

On DISTANT RUNNER, the massive blast deflector remained relatively intact. For the modeling effort, the construction details were simplified. These simplifications did not seem to alter the results. The blast deflector remained a monolithic structure and travelled a short distance.

Based on the final location of the pieces of the front door and an examination of the area surrounding their impact point, it can be concluded that the front door came off almost intact (two major pieces) and seemed to break up upon impact with the ground. It hit and stopped within the 5° recovery zone located out the front. (Note: the pieces were recovered within the 5° recovery sector.) If the door had been broken into more than a few large pieces before it was expelled from the shelter, the impact points would have shown a much greater dispersion.

After the event, the material located within the 5° recovery sectors was recovered, weighed, measured, and cataloged. In addition, over 160 pieces of large debris, located outside the 5° sectors, were also surveyed, recovered, and analyzed.

Figure 3 is a survey map of the large debris pleces which were located separately from the material in the 5° sectors. Over 160 large pleces of debris are included in this category. The front of the shelter is located at 0° (North), the recovery side of the shelter at 90° (East), and the rear at 180° (South). The 270° side faced a steeply up-sloping hill; thus, very little recovery effort was expended in this direction. If Figure 3 is compared with similar maps generated for both the 1/10-scale (such as Figure 4-1 of Reference 6) and full scale events (Figure 14 of Reference 3), no outstanding differences are apparent.

Prior to the event, displacement cubes were placed on and around the outside of the structure. The reason for installing these cubes was twofold: (1) to act as debris of known size to be tracked photographically, and (2) from their final locations and known initial starting points, to be able to back-calculate their launch velocity and angle.

There were two types of cubes used: (1) 2-inch aluminum cubes, weighing 0.75 pounds each (a total of ten were used) and (2) 6-inch wooden cubes, weighing approximately 4.1 pounds each (a total of five were used). Figure 4 is a sketch of the locations of each of the cubes.

Out of the fifteen cubes emplaced prior to the test, thirteen were recovered afterward. One of the wooden cubes had broken into two pieces, but both pieces were recovered. Two of the aluminum cubes were never located. Table 1 gives the final locations of each of the cubes. None of the cubes could be seen in any of the high speed photographic coverage. Using the information presented in Table 1 as well as the initial locations of the cubes, a series of trajectory calculations was performed to bracket the initial launch conditions required for the cubes to land where they were found. The computer program TRAJ⁹ was used for these calculations.

The sloping terrain present at the test site was included in the trajectory calculations. In addition, the ricochet option was enabled, with the soil being described as dry sand (Soil Constant = 2.00). For those cubes in direct contact with the side of the shelter, it was assumed that the launch angle was within ± 15 to 20° of the normal from the center of the shelter to the cube location. The results are shown in Table 2. Relatively low velocities were obtained, with consistent results being obtained from both types of cubes. It must be remembered that there is no unique combination of launch velocity and angle for a given final location--rather a range of angles and velocities.

With the exception of the cubes located on the very top of the structure, the velocities were all less than 200 ft/s. From the top of the structure, the velocities could be as high as 600 ft/s. However, based on information presented in Reference 6, an upper limit of 400 ft/s would seem to be more realistic.

Before any appreciable breakup or movement could be observed on the high speed photography, the entire scene is engulfed in flame and smoke. At very late times, approximately 100 milliseconds or more after detonation, the large debris pieces emerge from the cloud/dust and can be tracked. The velocities obtained are quite consistent with those obtained on the 1/10-scale model tests. It should be remembered that no velocity data was obtained on Event 5 of DISTANT RUNNER. On DISTANT RUNNER, the fireball obscured all useable data.

ANALYSIS

Over 35,000 separate pieces of debris are reported and cataloged. However, only those pieces weighing over 30 grains (1.9 grams) were considered in the following analyses. Calculations performed for the analysis of both the full-scale DISTANT RUNNER and the tenth-scale models showed that full-scale concrete debris must weigh at least 0.3 pounds to be hazardous. A 1.9 gram debris piece from a quarter scale model would correspond to 121.6 grams (0.26 pounds) full scale. Even after the lighter debris pieces were eliminated, there were approximately 19,000 debris pieces to be considered.

Samples of the concrete debris collected in the 5° recovery areas were evaluated as to shape factor. The shape factor relates the debris weight with a length dimension according the relationship:

$$M = B \star \rho_c \star L^3 \tag{1}$$

where

The shape factor represents the fraction of the volume of the box determined by the debris, when that box is filled by the debris of mass M with density ρ_c . Note that the dimensions (length, width, thickness) specify a box size within which the debris item can just fit. This is shown schematically in Figure 5.

Samples were selected from all three directions and statistically analyzed for shape factor and the effects of sieve size. For each direction, the average shape factor was 0.38. There was no apparent size effect. When the data are combined, an estimate of the shape factor for the 1/4-scale model can be established. This was 0.38 ± 0.06 , based on 4,478 samples. The average value obtained for DISTANT RUNNER was 0.44 ± 0.03 (based on 5,837 samples); that for the tenth-scale models was 0.47 ± 0.03 (based on a total of over 22,000 pieces for the five models).

The differences between the tenth-scale and the full-scale are statistically significant (at the 95% confidence level), as was pointed out in Reference 6. A similar, statistically significant, difference between the quarter-scale and the full scale results was also found. The effect of these differences is to contribute to the over-estimation of debris ranges based on the tenth- and quarter-scale results.

Porzel, in his development of the Technology Base for the Naval Explosives Safety Improvement Program¹⁰, postulated the following number distribution for the breakup of materials:

where

N(>L)	=	Number of debris pieces with length greater than L
No	=	Total number of debris pleces (determined by fit)
L		Debris Length
LBAR	=	Characteristic debris length, in same units as L (determined by fit)

This distribution has been applied to the fragmentation or breakup of a wide variety of items including primary fragments from bomb cases following a detonation, pieces of a broken dinnerware plate, and sizes/numbers of pieces of naturally occurring coal. In Reference 3, this distribution was applied to the data generated on Events 4 and 5 of DISTANT RUNNER. It was observed in this case that there appeared to be at least two characteristic sizes of the debris rather than one and the technique was not pursued further.

Figure 6 illustrates a typical example and the application of equation 2 to the data generated during this test. At least two break points are identified. Their location is chosen to maximize the correlation coefficient obtained fitting equation 2 to a portion of the data. One curve is fitted to the data below Break 1; a second equation is fitted to the data lying between the first and second break. The values of LBAR obtained in each portion as well as the location of the break points themselves can then be compared to determine appropriate values of scale factors. For example, let us assume (arbitrarily) that an LBAR of 1.65 inches was obtained for the full scale results and an LBAR of 0.50 inches for the nominal quarter scale. Then the apparent scale factor is simply 1.65/0.50 or 3.30. Similarly, let us assume that the first break point occurred at 7.5 inches full scale and 2.5 inches, quarter scale. In this instance, the apparent scale factor is 7.5/2.5 or 3.0. The location of the second break point could, theoretically, be used to determine an apparent scale factor. However, because of the smaller amount of data available in this portion of the distribution, the results may not be as accurate.

Figures 6, 7 and 8 present the debris-number distributions, based on debris length, obtained for the three scale sizes: full scale, tenth scale and quarter scale. The full-scale distribution, Figure 7, differs slightly from the one appearing in Reference 3. Additional data were added to the distribution, small errors were corrected, and the results recalculated for this report. Table 3 presents a summary of the apparent model scale factors based upon this method. For the tenth-scale model, the apparent scale factor varied between 7.405 and 9.5, with an average of 8.660. The quarter scale apparent scale factor varied between 3.00 and 4.01, with an average of 3.418.

HAZARD RANGES

The debris ranges obtained from the model results must be scaled to full scale before hazard ranges can be computed. Unfortunately, the scaling of debris ranges is not straightforward, since gravity was not scaled in the model experiments. A scaling algorithm was developed and reported in Reference 6. Essentially, given the location of each piece of debris in the model scale, estimates are made of the launch conditions required to place it at that location. The debris piece is then scaled to full scale, the previously-calculated launch conditions applied, and the "full-scale" debris trajectory is calculated. This is repeated for

(2)

each debris piece. As indicated above, the algorithm is detailed in Reference 6. As a check on the algorithm, the procedure was applied to the full scale DISTANT RUNNER results. If the procedure is working appropriately, the same debris locations as the input conditions should be returned when the algorithm is applied. This was, indeed, the case.

Certain assumptions and information are required before the algorithm can be applied. These include the densities and shape factors of the debris. In addition, a debris cut-off velocity must be specified. When a piece of debris impacts the ground and breaks up into smaller pieces, one result is an unrealistic estimate for the initial velocity of the intact piece. When the calculated initial debris velocity exceeds this specified value, that particular piece of debris is not considered further. A value of 400 ft/s has been utilized in all these debris analyses. This value is consistent with both the photographically-determined and the displacement cube-inferred velocities previously reported.

Since the debris analyses were performed and reported in References 3 to 7, additional work^{11,12} has been performed on the standardization of such analyses. One important difference is the calculation of a pseudo-trajectory normal (PTN) hazardous fragment density. These new techniques have been applied to the original DISTANT RUNNER Event 5 data as well as to the data from the five tenth-scale models. The results are shown in Table 4. The ranges were only slightly different using both the old and the newer, preferred technique.. The quarter-scale results are very similar to the full scale DISTANT RUNNER results out the side and the rear, but are significantly longer out the front. Out the front, the quarter-scale results more closely resemble the tenth-scale results.

On both the tenth-scale and quarter-scale models, the front door assembly hit within the recovery sector, bounced, and broke up. On the full scale event, the door landed outside the 5° recovery sector. This would help to explain why the hazard range in the direction to the front of all of the models was significantly greater than the DISTANT RUNNER range.

SUMMARY

Three distinct sizes of reinforced concrete structures have now been constructed and tested to destruction: (1) DISTANT RUNNER at full scale, (2) a series of five tenth-scale models, and (3) one quarter-scale model. In the most general terms, all three behaved in a similar manner.

One objective of the model testing is to determine if the hazard ranges can be inferred from the model results. DISTANT RUNNER showed that the explosives safety quantitydistance (ESQD) range for these third-generation hardened aircraft shelters was controlled by the debris/fragmentation rather than airblast. The series of tenth-scale model tests showed that the full-scale airblast results were, indeed, adequately predictable from these model data. Because of this and because the airblast did not drive the ESQD range, airblast was not measured on the quarter scale test.

The tenth-scale models overpredicted the debris hazard range in all three directions. The quarter-scale model agreed with the full-scale results off the side, slightly underpredicted them off the rear and overpredicted them out the front. One reason both the tenth- and quarter-scale models overpredicted the range out the front is because of the behavior of the front door. At full scale, the doors seemed to hold together and landed outside the recovery sectors, not influencing the debris density for the front recovery sector. On both model scales, the doors landed within the recovery sectors.

At the 95% confidence level, the shape of the recovered debris (as measured by the debris shape factor) for both the tenth- and quarter-scale results, was statistically different from the full-scale results.

The apparent scale factor, i.e., the scale factor inferred from experimental data, was less than the design scale factor for both model scales. At tenth-scale, the average apparent scale factor (as determined by the length distribution) was 8.66 rather than 10. At quarter-scale, the factor was 3.42.

Another objective of this program was to examine the relationship between the "designscale" of a model and its "apparent-scale", as determined from its breakup behavior. Figure 9 presents this relationship as determined for the reinforced concrete structures tested during this program. A caveat must be applied here. Only this one type of structure has been considered. The relationship shown in Figure 10 may not apply to another type of structure or to a similar structure if significant changes are made in the way in which the structure is modeled.

These series of tests have indicated that the breakup behavior of reinforced concrete structures can be inferred from model results. The gross breakup pattern is similar. The shape factors are nearly identical. The hazard ranges mirror the full scale numbers.

REFERENCES

- 1. LTC Flory, R. A., "DISTANT RUNNER," <u>Minutes of the 19th Explosives Safety Seminar.</u> <u>DoD Explosives Safety Board</u>, September 1980.
- 2. LTC Flory, R. A., "DISTANT RUNNER Results," <u>Minutes of the 20th Explosives Safety</u> <u>Seminar. DoD Explosives Safety Board</u>, August 1982.
- 3. Ward, J. M., "DISTANT RUNNER-Debris Recovery and Analysis Program for Events 4 and 5," <u>Minutes of the 20th Explosives Safety Seminar. DoD Explosives Safety Board</u>, August 1982.
- 4. Ward, J. M., "Debris Recovery And Analysis Program For DISTANT RUNNER Events 4, and 5,"<u>Proceedings of the DISTANT RUNNER SYMPOSIUM, 27-28 April 1982</u>, 2 September 1982.
- 5. Ward, J. M., <u>Debris Hazards From Internal Explosions in Hardened Aircraft Shelters</u>, NSWC TR 86-114, 16 April. 1986.
- 6. Ward, J. M., et. al., Modeling of Debris and Airblast Effects From Explosions Inside Scaled Hardened Aircraft Shelters, NSWC TR 85-470, 3 May 1986.
- 7. Swisdak, M. M., <u>Aircraft Shelter Model Test (ASMT) Follow-up Analyses</u>, NSWC TR 86-472, 30 September 1986.
- 8. Harvey, K. L., <u>One-Quarter Scale Third Generation Hardened Aircraft Shelter Test</u> <u>Results</u>, NMT/TERA No. T-91-1834-U, 19 June 1991.
- 9. Montanaro, Paul, "TRAJ--A Two Dimensional Trajectory Program For Personal Computers," <u>Minutes of the 24th Explosives Safety Seminar, DoD Explosives Safety</u> <u>Board</u>, August 1990.
- Porzel, F. B., "Technology Base of the Navy Explosives Safety Improvement Program," <u>Minutes of the 19th Explosives Safety Seminar, DoD Explosives Safety Board,</u> September 1980.
- Swisdak, M. M., "Analysis of the Debris Produced By A Processing Building Accident," <u>Minutes of the 23rd Explosives Safety Seminar</u>, DoD Explosives Safety Board, August 1988.
- 12. Swisdak, M. M., "Procedures For the Analysis Of The Debris Produced By Explosion Events," <u>Minutes of the 24th Explosives Safety Seminar. DoD Explosives Safety</u> <u>Board</u>, August 1990.



FIGURE 1. PLAN VIEW OF QUARTER SCALE SHELTER SHOWING BOMBLET LOCATIONS

536



FIGURE 2. FRONT VIEW OF QUARTER-SCALE MODEL SHOWING BOMBLET LOCATIONS

537





FIGURE 4. 1/4-SCALE SHELTER: DISPLACEMENT CUBE LOCATIONS



FIGURE 5. SHAPE FACTOR MEASUREMENTS

FIGURE 6. DEBRIS-NUMBER DISTRIBUTION: DISTANT RUNNER (full scale)









FIGURE 8. DEBRIS NUMBER DISTRIBUTION: QUARTER SCALE MODEL



FIGURE 9. DESIGN VERSUS APPARENT SCALE FACTOR



TABLE 1.	FINAL DISPL	ACEMENT	CUBE LO	DCATIONS
----------	--------------------	---------	---------	-----------------

-

]]	HORIZONTAL.	
CUBE NUMBER	MATERIAL	HORIZONTAL	VERTICAL	ANGLE
		(FEET)	(FEET)	(DEG.MIN.SEC)
AC-1	ALUMINUM	159.6	-10.03	107.55.44
AC-2	ALUMINUM	126.14	-6.29	100.42.03
AC-3	ALUMINUM	not located		
AC-4	ALUMINUM	277.61	-15.48	90.03.09
AC-5	ALUMINUM	241.59	-12.55	88.24.14
AC-6	ALUMINUM	229.2	-12.08	86.37.49
AC-7	ALUMINUM	220.73	-11.75	82.42.55
AC-8	ALUMINUM	not located		
AC-9	ALUMINUM	137.75	-10.05	123.35.46
AC-10	ALUMINUM	98.76	-1.59	179.14.11
W-1	WOOD	147.52		83.55.00
W-2	WOOD	199.5	-10.36	91.07.00
W-2A	WOOD	169.02	-8.88	85.08.40
W-3	WOOD	248.55	-13.01	82.27.43
W-4	WOOD	254.09	-12.96	87.31.55
W-5	WOOD	211.31	-11.41	82.33.00

NOTES:

- (1) Distances and angles are measured relative to the center of the shelter
- (2) 0° is out the front of the shelter

.

(3) Because of the sloping terrain, the vertical displacements are included

TABLE 2. INITIAL CONDITIONS DETERMINED FROM DISPLACEMENT CUBE LOCATIONS

MATERIAL	IDENTIFICATION	NITIAL HEIGHT	INITIAL ANGLE	FINAL RANGE	LAUNCH ANGLE	LAUNCH VELOCITY
	NUMBER					
		(feet)	(°)	(feet)	(°)	(ft/s)
Aluminum	5	0.2	0	242	510	130-160
Wood	5	0.2	0	211	19	130-160
Aluminum	4	2.5	15	278	0-14	130-160
Wood	4	2.5	15	254	1025	120-160
Aluminum	3	6.6	35	not found	not calculated	not calculated
Wood	3	6.6	35	249	30-40	90-120
					1020	130-150
Aluminum	2	7	50	126	30-70	60-80
Wood	2	7	50	broken	not calculated	not calculated
Aluminum	1	7.5	90	1 6 0	81-85	200-250
					85-87	250-400
					86-87	450-600
Wood	1	7.5	90	148	72-82	140-160
					78-84	180-200
					81-85	250-300
					83-88	300-500
Aluminum	6,7	2	15	229 & 221	1218	110-130
					10 to -6	130-150
Aluminum	8	7.5	90	not found	not calculated	not calculated
Aluminum	9	7.5	90	138	30-50	50-70
					72-78	90-110
					76-78	110-130
					78-84	130-150
					80-84	150-170
					82-85	170-190
					82-86	190-210
Aluminum	10	4	45	99	20-60	50-70
			[1020	70-90
L	1					

TABLE 3. AIRCRAFT SHELTER SCALE FACTOR DETERMINATION

EVENT					
	LBAR-1 (in)				
DISTANT RUNNER	1.6402	1.000	0.9856	1.000	
TENTH SCALE	0.1962	8.360	0.1331	7.405	
QUARTER SCALE	0.4845	3.385	0.2458	4.010	

EVENT	MEASUREMENT				
	BREAK 1 (in)	AVERAGE			
DISTANT RUNNER	7.5	1.000	9.5	1.000	
TENTH SCALE	0.8	9.375	1	9.500	8.660
QUARTER SCALE	2.5	3.000	2.9	3.276	3.418

TABLE 4. COMPARISON OF MODEL DATA WITH FULL SCALE HAZARD RANGES

EVENT	HAZARD RANGE (m/kg^1/3)				
	FRONT	SIDE	REAR		
DISTANT RUNNER (OLD)	19.6	24.5	15.3		
DISTANT RUNNER (PTN)	20.1	21.4	17.3		
TENTH SCALE-1 (OLD)	26.88	28.15	18.38		
TENTH SCALE-2 (OLD)	26.29	26.93	19.73		
TENTH SCALE-3 (OLD)	24.90	30.17	15.41		
TENTH SCALE-4 (OLD)	25.61	27.16	18.02		
TENTH SCALE-5 (OLD)	25.90	27.99	20.49		
TENTH SCALE-AVERAGE (OLD)	25.9	28.1	18.4		
TENTH SCALE-1 (PTN)	25.93	27.29	20.00		
TENTH SCALE-2 (PTN)	26.63	28.22	21.36		
TENTH SCALE-3 (PTN)	27.18	32.22	16.79		
TENTH SCALE-4 (PTN)	22.72	26.61	19.26		
TENTH SCALE-5 (PTN)	28.66	30.44	22.71		
TENTH SCALE-AVERAGE (PTN)	26.2	29.0	20.0		
QUARTER SCALE (PTN)	26.9	22.4	15.0		

NOTES:

- (1) PTN is Pseudo Trajectory Normal Density
- (2) OLD is the previous method of calculating debris density