Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 2. REPORT TYPE				3. DATES COVERED 00-00-2013 to 00-00-2013	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
Mechanical Energy Changes in Perfectly Inelastic Collisions				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Naval Academy, Physics Department, Annapolis, MD, 21401				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF: 17. LIMITATION OF				18. NUMBER	19a. NAME OF
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	2	RESI UNSIDLE FERSUN

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std Z39-18

## Mechanical Energy Changes in Perfectly Inelastic Collisions

Carl E. Mungan, U.S. Naval Academy, Annapolis, MD

Suppose a block of mass  $m_1$  traveling at speed  $v_1$  makes a one-dimensional perfectly inelastic collision with another block of mass  $m_2$ . What else does one need to know to calculate the fraction of the mechanical energy that is dissipated in the collision?

One needs to know the velocity  $v_2$  of the other block (defining its sign to be positive if it is in the same direction of travel as the first block, and negative otherwise). That makes sense because there is nothing special about the first block compared to the second one; the energy loss must be the same if we interchange subscripts 1 and 2. If the common final speed of the two blocks after the collision is V, then conservation of momentum implies

$$m_1 \upsilon_1 + m_2 \upsilon_2 = (m_1 + m_2) V. \tag{1}$$

The fraction f of the mechanical energy that is retained is

$$f = \frac{\frac{1}{2}(m_1 + m_2)V^2}{\frac{1}{2}m_1v_1^2 + \frac{1}{2}m_2v_2^2} = \frac{(m_1v_1 + m_2v_2)^2}{(m_1 + m_2)(m_1v_1^2 + m_2v_2^2)}$$
(2)

using Eq. (1). Equation (2) is plotted in Fig. 1 as a function of the velocity ratio  $r \equiv v_1/v_2$  for the two cases  $m_2 = m_1$  (in red) and  $m_2 = 3m_1$  (in blue). We see that *f* varies from 100% for  $v_1 = v_2$  (when a "collision" merely consists in linking the



Fig. 1. Plots of Eq. (2) as a function of the velocity ratio of two equal-mass blocks (in red) and of two unequal-mass blocks (in blue). The horizontal dashed lines are graphs of f = 0.5 (in red) and of f = 0.25 (in blue).

two blocks together) to 0% for  $m_1v_1 = -m_2v_2$  (when the blocks collide head-on with equal and opposite momenta to end up at rest). If one of the blocks has zero initial speed, then the fraction of the mechanical energy that is lost only depends on the ratio of the two masses, regardless of the initial speed of the other block. In particular, the curves in Fig. 1 asymptotically approach  $f = 1/(1 + m_2/m_1)$  as  $r = \pm \infty$ , which corresponds to  $v_2 = 0$  (as indicated by the two horizontal dashed lines).

Here are two applications of these ideas. Suppose that one is not satisfied with the maximum height h reached by a ballistic pendulum after a bullet (of mass m and speed v) is fired into it, and so one fires a second, identical bullet. It matters greatly when the second bullet strikes the swinging pendulum! We can inadvertently cancel out its entire motion if the second bullet impacts the hanging block (of mass M) when it is at its lowest point and swinging backward. If the second bullet hits when the block is at one of its turning points, we will double h, but we could have quadrupled h if the second bullet instead hit when the block is at its lowest point and swinging forward. This conclusion follows from the fact that h varies quadratically with the bullet's mass,<sup>1</sup>

$$h = \frac{m^2 v^2}{2gM^2} \tag{3}$$

in the limit that  $m \ll M$ . Maximizing the height requires phase matching between the period of the pendulum and the repetition period of the bullets, similar to intermittently pushing a child on a swing.

Another application, which is a model for collisions with continuous rather than discrete increments of mass, is the "inverse rocket" problem of rain falling vertically into a freely rolling railroad car. Suppose that at a given instant, the car (including the water it is carrying) has mass m and speed v. A bit of water of mass dm with zero horizontal speed lands in the car. Conservation of momentum requires that the car changes speed by dv such that

$$mv = (m + dm)(v + dv) \implies mdv = -vdm,$$
 (4)

neglecting the second-order term, implying that the car loses speed since dv < 0. One can express Eq. (4) as F = dP/dt, where the external horizontal force *F* on the system of car plus rain is zero, and *P* is the horizontal momentum of that entire system.<sup>2</sup> Using both equalities in Eq. (4), the fractional change in kinetic energy of the car is

$$\frac{dK}{K} = \frac{\frac{1}{2}(m+dm)(\nu+d\nu)^2 - \frac{1}{2}m\nu^2}{\frac{1}{2}m\nu^2}$$
(5)  
$$= \frac{\frac{1}{2}m\nu(\nu+d\nu) - \frac{1}{2}m\nu^2}{\frac{1}{2}m\nu^2} = \frac{d\nu}{\nu} = -\frac{dm}{m}.$$

Although the car gains mass, it loses kinetic energy because of its drop in speed. Integrating both sides of Eq. (5), if rain falls into it at constant rate R (in kg/s), then the car's kinetic energy decreases in time t according to

$$K(t) = K_0 / (1 + Rt/m_0), \qquad (6)$$

where  $K_0 = \frac{1}{2}m_0v_0^2$  is the initial kinetic energy. Defining a time constant  $\tau = m_0/R$ , the kinetic energy falls to a half in one time constant, to a third in two time constants, to a quarter in three time constants, and so on. Kinetic energy is not lost at a constant rate, even though water is falling into it at a constant rate; instead, the car loses more mechanical energy per second when it is moving fast than when it is moving slow.

## References

- J. W. Zwart, "A safe and inexpensive ballistic pendulum," *Phys. Teach.* 25, 447–448 (Oct. 1987).
- In a perfectly inelastic collision, *dP/dt* only reduces to *d(mv)/ dt* if the collected mass elements have zero initial momentum, which is equivalent to u = -v in J. Mallinckrodt, "F does *not* equal *d(mv)/dt*," letter to the editor, *Phys. Teach.* 48, 360 (Sept. 2010). For example, *F* = *d(mv)/dt* holds for a raindrop falling through stationary mist (because the mist has zero initial momentum) as in C. E. Mungan, "More about the falling raindrop," *Am. J. Phys.* 78, 1421 (Dec. 2010). In contrast, it does not hold for a horizontally moving funnel adding sand into a cart (because the sand is initially moving with the cart's velocity) as in W. Kunkel and R. Harrington, "Modeling the motion of an increasing mass system," *Phys. Teach.* 48, 243–245 (April 2010).

**Carl Mungan** is an associate professor of physics at the United States Naval Academy.

U.S. Naval Academy, Physics Department, Annapolis, MD 21401; mungan@usna.edu