UNCLASSIFIED

AD NUMBER

ADB000428

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies only; Test and Evaluation; NOV 1974. Other requests shall be referred to National Aeronautics and Space Administration, Hampton, VA 23365.

AUTHORITY

NASA ltr, 25 Apr 1975

THIS PAGE IS UNCLASSIFIED

AEDC-TR-74-125

cy.2

acata

SINE DELIKE STR

DEC 13 1974 AUG 1 1 1983

EVALUATION OF THE THIOKOL TE-M-640 SOLID-PROPELLANT ROCKET MOTOR UNDER THE COMBINED EFFECTS OF SIMULATED ALTITUDE AND ROTATIONAL SPIN

R. M. Brooksbank ARO, Inc.

ENGINE TEST FACILITY ARNOLD ENGINEERING DEVELOPMENT CENTER AIR FORCE SYSTEMS COMMAND ARNOLD AIR FORCE STATION, TENNESSEE 37899-0,5-15 1975 This document has been approved for public 7778 June This document has been approved for public 7778 June its distribution is unlimited.

November 1974

Final Report for Period July 11, 1973 to July 12, 1974

Distribution limited to U. S. Government agencies only; this report contains information on test and evaluation of military hardware; November 1974; other requests for this document must be referred to National Aeronautics and Space Administration, Scout Project Office, Langley Research Center, Hampton, Virginia 23365.

> Flogerly of U.S. Air Force AEDC LIBRARY F40600-75-C-0001

FILE COPY

Prepared for

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION HAMPTON, VIRGINIA 23365 TECHNICAL REPORTS

NOTICES

1 50

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

APPROVAL STATEMENT

This technical report has been reviewed and is approved.

Chauncey & smith, fe

CHAUNCEY D. SMITH, JR. Lt Colonel, USAF Chief Air Force Test Director, ETF Directorate of Test

Frank & Yassarello

FRANK J. PASSARELLO Colonel, USAF Director of Test

UNCLASSIFIED

REPORT DUCUMENTATION PAGEBEFORE COMPLETING FORM1. REPORT NUMBER2. GOVT ACCESSION NO.3. RECIPIENT'S CATALOG NUMBERAEDC-TR-74-1252. GOVT ACCESSION NO.3. RECIPIENT'S CATALOG NUMBER4. TITLE (and Sublifile)5. TYPE OF REPORT & PERIOD COVEREDEVALUATION OF THE THIOKOL TE-M-6405. TYPE OF REPORT & PERIOD COVEREDSOLID-PROPELLANT ROCKET MOTOR UNDER THE COMBINED EFFECTS OF SIMULATED ALTITUDE5. TYPE OF REPORT & PERIOD COVEREDAND ROTATIONAL SPIN6. PERFORMING ORG. REPORT NUMBER7. AUTHOR(*)8. CONTRACT OR GRANT NUMBER(*)8. M. Brooksbank - ARO, Inc.8. CONTRACT OR GRANT NUMBER(*)9. PERFORMING ORGANIZATION NAME AND ADORESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 3738910. PROGRAM ELEMENT. PROJECT. TASK AREA & WORK UNIT NUMBERS11. CONTROLLING OFFICE NAME AND ADORESS NASA, Scout Project Office,12. REPORT OATE NOVEmber 1974
1. REPORT NUMBER 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER AEDC-TR-74-125 2. GOVT ACCESSION NO. 3. RECIPIENT'S CATALOG NUMBER A. TITLE (and Sublifie) 5. TYPE OF REPORT & PERIOD COVERED EVALUATION OF THE THIOKOL TE-M-640 5. TYPE OF REPORT & PERIOD COVERED SOLID-PROPELLANT ROCKET MOTOR UNDER THE 5. TYPE OF REPORT & JUly 11, COMBINED EFFECTS OF SIMULATED ALTITUDE 6. PERFORMING ORG. REPORT NUMBER AND ROTATIONAL SPIN 9. CONTRACT OF GRANT NUMBER 7. AUTHOR(*) 8. CONTRACT OF GRANT NUMBER R. M. Brooksbank - ARO, Inc. 9. CONTRACT OF GRANT NUMBERS Arnold Engineering Development Center 10. PROGRAM ELEMENT, PROJECT, TASK Arnold Air Force Station Program Element 921E5 Tennessee 37389 12. REPORT OATE 11. CONTROLLING OFFICE NAME AND ADORESS 12. REPORT OATE NASA, Scout Project Office, 12. REPORT OATE
AEDC-TR-74-125 A. TITLE (and Sublifile) EVALUATION OF THE THIOKOL TE-M-640 SOLID-PROPELLANT ROCKET MOTOR UNDER THE COMBINED EFFECTS OF SIMULATED ALTITUDE AND ROTATIONAL SPIN 7. AUTHOR(s) R. M. Brooksbank - ARO, Inc. 9. PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 11. CONTROLLING OFFICE NAME AND ADORESS NASA, Scout Project Office,
4. TITLE (and Sublitte) EVALUATION OF THE THIOKOL TE-M-640 SOLID-PROPELLANT ROCKET MOTOR UNDER THE COMBINED EFFECTS OF SIMULATED ALTITUDE AND ROTATIONAL SPIN 7. AUTHOR(*) R. M. Brooksbank - ARO, Inc. 9 PERFORMING ORGANIZATION NAME ANO ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 11. CONTROLLING OFFICE NAME AND ADDRESS NASA, Scout Project Office, 12. REPORT OATE
EVALUATION OF THE THIOKOL TE-M-640 SOLID-PROPELLANT ROCKET MOTOR UNDER THE COMBINED EFFECTS OF SIMULATED ALTITUDE AND ROTATIONAL SPINFinal Report - July 11, 1973 to July 12, 19747. AUTHOR(*)6. PERFORMING ORG. REPORT NUMBER8. CONTRACT OR GRANT AND BER(*)8. CONTRACT OR GRANT NUMBER(*)9. PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 3738910. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS11. CONTROLLING OFFICE NAME AND ADDRESS NASA, Scout Project Office,12. REPORT OATE November 1974
SOLID-PROPELLANT ROCKET MOTOR UNDER THE COMBINED EFFECTS OF SIMULATED ALTITUDE1973 to July 12, 1974AND ROTATIONAL SPIN6. PERFORMING ORG. REPORT NUMBER7. AUTHOR(*)8. CONTRACT OR GRANT NUMBER(*)8. M. Brooksbank - ARO, Inc.8. CONTRACT OR GRANT NUMBER(*)9 PERFORMING ORGANIZATION NAME ANO ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 3738910. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Element 921E511. CONTROLLING OFFICE NAME ANO ADDRESS NASA, Scout Project Office,12. REPORT OATE November 1974
COMBINED EFFECTS OF SIMULATED ALTITUDE 6. PERFORMING ORG. REPORT NUMBER AND ROTATIONAL SPIN 6. PERFORMING ORG. REPORT NUMBER 7. AUTHOR(*) 8. CONTRACT OR GRANT NUMBER(*) R. M. Brooksbank - ARO, Inc. 8. CONTRACT OR GRANT NUMBER(*) 9 PERFORMING ORGANIZATION NAME AND ADDRESS 10. PROGRAM ELEMENT, PROJECT, TASK Arnold Engineering Development Center Arnold Air Force Station Program Element 921E5 11. CONTROLLING OFFICE NAME AND ADDRESS 12. REPORT DATE NASA, Scout Project Office, 12. REPORT DATE
AND ROTATIONAL SPIN 7. AUTHOR(*) R. M. Brooksbank - ARO, Inc. 9. PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 11. CONTROLLING OFFICE NAME AND ADDRESS 12. REPORT OATE NASA, Scout Project Office,
 AUTHOR(*) R. M. Brooksbank - ARO, Inc. PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 I. CONTROLLING OFFICE NAME AND ADDRESS NASA, Scout Project Office, CONTRACT OR GRANT NUMBER(*) CONTRACT OR GRANT NUMBER(*) CONTRACT OR GRANT NUMBER(*) CONTRACT OR GRANT NUMBER(*) PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Element 921E5 REPORT DATE NOVEmber 1974
R. M. Brooksbank - ARO, Inc. PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 I. CONTROLLING OFFICE NAME AND ADDRESS NASA, Scout Project Office, 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 11. CONTROLLING OFFICE NAME AND ADDRESS 12. REPORT DATE NOVEMBER 1974
R. M. Brooksbank - ARO, Inc. PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 11. CONTROLLING OFFICE NAME AND ADDRESS NASA, Scout Project Office, 12. REPORT DATE November 1974
 PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 Controlling office NAME AND ADDRESS Report Date NASA, Scout Project Office, 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Program Element 921E5 Report Date November 1974
 PERFORMING ORGANIZATION NAME AND ADDRESS Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 CONTROLLING OFFICE NAME AND ADDRESS NASA, Scout Project Office, November 1974
Arnold Engineering Development Center Arnold Air Force Station Tennessee 37389 11. CONTROLLING OFFICE NAME AND ADORESS NASA, Scout Project Office, 12. REPORT DATE November 1974
Arhold Air Force Station Program Element 921E5 Tennessee 37389 12. REPORT OATE NASA, Scout Project Office, November 1974
11. CONTROLLING OFFICE NAME AND ADDRESS 12. REPORT DATE NASA, Scout Project Office, November 1974
11. CONTROLLING OFFICE NAME AND ADORESS NASA, Scout Project Office, November 1974
NASA, Scout Project Office, November 1974
Langley Research Center 13. NUMBER OF PAGES 58
Hampton, Virginia 23365
14. MONITORING AGENCY NAME & ACORESS(If different from Controlling Office) 15. SECURITY CLASS. (of this report)
UNCLASSIFIED
154 DECLASSIFICATION/DOWNGRADING
SCHEOULE N/A
16 OISTRIBUTION-STATEMENT (at this Report)
Distribution limited to U.S. Government agenetes only; this
report contains information on test and evaluation of military
hardware; November 1974; other requests for this document must be
referred to National Aeronautics and Space Administration. Scout
Project Office, Langley Research Center, Hampton, Virginia 23365.
IT DISTRIBUTION STATEMENT (of the obstract entered in Black 20, if different from Report)
This document has been approved for public release 15-15
its distribution is unlimited Per 1410 of Culture
is distribution is distribution of a staff
18. SUPPLEMENTARY NOTES
Available in DDC.
19. KEY WOROS (Continue on reverse eide if necessary and identify by block number)
TE-M-640 ballistics
solid propellant thrust
nocket motors snin
altitude tests structural strength
altitude tests structural strength
altitude tests structural strength 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Three Thiokol Inc. TE-W-640 solid-propollart restore
altitude tests 20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Three Thickol, Inc., TE-M-640 solid-propellant rocket motors worse tosted at avonage prossure altitudes of 100,000 ft 111,000 ft
altitude tests 20. ABSTRACT (Continue on reverse elds if necessary and identify by block number) Three Thickol, Inc., TE-M-640 solid-propellant rocket motors were tested at average pressure altitudes of 100,000 ft, 111,000 ft, and 105 000 ft properties while crimping about their sol
altitude tests 20. ABSTRACT (Continue on reverse elds if necessary and identify by block number) Three Thickol, Inc., TE-M-640 solid-propellant rocket motors were tested at average pressure altitudes of 100,000 ft, 111,000 ft, and 105,000 ft, respectively, while spinning about their axial
altitude tests altitude tests ^{20.} ABSTRACT (Continue on reverse elds if necessary end identify by block number) Three Thiokol, Inc., TE-M-640 solid-propellant rocket motors were tested at average pressure altitudes of 100,000 ft, 111,000 ft, and 105,000 ft, respectively, while spinning about their axial centerlines at 180 rpm. Test objectives were to evaluate altitude ballistic proference and lateral (consult) for solid to the spin test objectives were to evaluate altitude
altitude tests altitude tests ^{20.} ABSTRACT (Continue on reverse elds if necessary end identify by block number) Three Thiokol, Inc., TE-M-640 solid-propellant rocket motors were tested at average pressure altitudes of 100,000 ft, 111,000 ft, and 105,000 ft, respectively, while spinning about their axial centerlines at 180 rpm. Test objectives were to evaluate altitude ballistic performance and lateral (nonaxial) force and to demon-
altitude tests altitude tests ^{20.} ABSTRACT (Continue on reverse elde il necessary end identily by block number) Three Thiokol, Inc., TE-M-640 solid-propellant rocket motors were tested at average pressure altitudes of 100,000 ft, 111,000 ft, and 105,000 ft, respectively, while spinning about their axial centerlines at 180 rpm. Test objectives were to evaluate altitude ballistic performance and lateral (nonaxial) force and to demon- strate structural integrity of the motor case and nozzle. The
altitude tests structural strength 20. ABSTRACT (Continue on reverse elde il necessary end identily by block number) Three Thiokol, Inc., TE-M-640 solid-propellant rocket motors were tested at average pressure altitudes of 100,000 ft, 111,000 ft, and 105,000 ft, respectively, while spinning about their axial centerlines at 180 rpm. Test objectives were to evaluate altitude ballistic performance and lateral (nonaxial) force and to demon- strate structural integrity of the motor case and nozzle. The first two motors failed 27 and 8 sec, respectively, after ignition.

DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

20. ABSTRACT (Continued)

third motor was tested and performed satisfactorily. Test results for the three motors are presented and discussed herein.

AFEC Arnold AFS Tenn .

.

PREFACE

The test program reported herein was conducted by the Arnold Engineering Development Center (AEDC), Air Force Systems Command (AFSC), at the request of the National Aeronautics and Space Administration, Hampton, Virginia, for Thiokol, Inc., under Program Element 921E5. The results of the test were obtained by ARO, Inc. (a subsidiary of Sverdrup & Parcel and Associates, Inc.), contract operator of AEDC, AFSC, Arnold Air Force Station, Tennessee. The work was done in Propulsion Development Test Cell (T-3) of the Engine Test Facility (ETF) under ARO Project No. RA307 (R41C-04A). Data reduction was completed on July 30, 1974, and the manuscript (ARO-ETF-TR-74-102) was submitted for publication on October 21, 1974.

N

•

CONTENTS

Page

1.0	INTRODUCTIO	Ν		•	•	•	•			•	 •		•		 •	•	•		•			•	•	•	5
2.0	APPARATUS		•••			•		 •	•	•	 			•	 •							•			6
3.0	PROCEDURE		• •			•	•				 •		•				•					•			9
4.0	RESULTS AND	DISCUSSI	ION		•		•			•	 •		•		 •	•	•	•		•	•				10
5.0	SUMMARY OF	RESULTS		•	•	-		 •		•	 •		•	•	 •	•	•	•	•	•			•		14
	REFERENCES		• •								 	•		•	 -		•								15

ILLUSTRATIONS

Figure

1. Thiokol, Inc., TE-M-640 Rocket Motor
a. Schematic
b. Photograph
c. Detail of Nozzle/Case Interface
2. TP-640 Pyrogen Igniter
3. Installation of TE-M-640 Motor and Spin Assembly in Propulsion
Development Test Cell (T-3)
a. Schematic
b. Photograph
4. Instrumentation Locations
a. Thermocouples
b. Linear Potentiometers
c. Photograph of Linear Potentiometers
5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure
5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. b. b
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 27
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 28
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 c. Motor S/N E11 c. Motor S/N E11 6. Variation of Thrust, Chamber Pressure, and Test Cell Pressure
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 during Testing of Motor S/N E02 c. Motor S/N E02
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 6. Variation of Thrust, Chamber Pressure, and Test Cell Pressure during Testing of Motor S/N E02 7. Comparison of Actual versus Predicted Chamber Pressure Variation
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 during Testing of Motor S/N E02 c. Motor S/N E02 c. Motor S/N E02 during Testing of Actual versus Predicted Chamber Pressure Variation with Time for TE-M-640 Motor S/N E02 during Testing Of Motor S/N E02
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 c. Motor S/N E11 c. Motor S/N E11 c. Motor S/N E11 c. Motor S/N E02 during Testing of Motor S/N E02 c. Motor S/N E02 during Testing of TE-M-640 Motor S/N E02 during Failure of
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 during Testing of Motor S/N E02 c. Motor S/N E02 c. Motor S/N E02 during Testing of Actual versus Predicted Chamber Pressure Variation with Time for TE-M-640 Motor S/N E02 8. Variation of Thrust and Chamber Pressure during Failure of Motor S/N E01 Motor S/N E01 31
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 6. Variation of Thrust, Chamber Pressure, and Test Cell Pressure during Testing of Motor S/N E02 7. Comparison of Actual versus Predicted Chamber Pressure Variation with Time for TE-M-640 Motor S/N E02 8. Variation of Thrust and Chamber Pressure during Failure of Motor S/N E01 9. Comparison of Actual versus Predicted Chamber Pressure Variation
 5. Variation of Thrust, Chamber Pressure; and Pyrogen Pressure during Ignition a. Motor S/N E02 b. Motor S/N E01 c. Motor S/N E11 6. Variation of Thrust, Chamber Pressure, and Test Cell Pressure during Testing of Motor S/N E02 7. Comparison of Actual versus Predicted Chamber Pressure Variation with Time for TE-M-640 Motor S/N E02 8. Variation of Thrust and Chamber Pressure during Failure of Motor S/N E01 9. Comparison of Actual versus Predicted Chamber Pressure Variation with Time for TE-M-640 Motor S/N E02

Figure

Page

.

•

10.	Variation of Thrust, Chamber Pressure, and Test Cell Pressure
	during Failure of Motor S/N E01
11.	Performance of Motor S/N E11
	a. Variation of Thrust, Chamber Pressure, and Test Cell Pressure
	during Testing of Motor S/N E11
	b. Chamber Pressure during Tailoff
12.	Definition of Vacuum Total and Action Impulse for Motor S/N E11 36
13.	Postfire Photograph of Motor S/N E02
14.	Aft Dome Temperature Variation with Time during Operation
	of Motor S/N E02
15.	Postfire Photograph of Motor S/N E01
16.	Axial Movement of Aft Dome Relative to Motor Aft Thrust Ring for
	Motor S/N E01
	a. Potentiometer L1
	b. Potentiometer L2
	c. Potentiometer L2
17.	Variation of Motor Temperature with Time for TE-M-640 Motor S/N E11
	a. Forward Dome (TC1, TC2, and TC3)
	b. Cylindrical Section Opposite Transverse Propellant
	Slot (TC4 and TC20)
	c. Cylindrical Section (TC5, TC6, TC7, and TC8)
	d. Aft Dome (TC9 and TC10)
	e. Pyrogen Case (TC15)
	f. Forward Dome (TC16, TC17, TC18, and TC19)
	g. Nozzle (TN11, TN12, TN13, and TN14)
18.	Postfire Photograph of Motor S/N E11 50
19.	Relative Circumferential Movement between Aft Thrust Ring and
	AEDC Mounting Adapter during Motor Operation (S/N E11)
20.	Variation of Nonaxial (Lateral) Force Vector with Time during
	Motor Operation
	a. Motor S/N E02
	b. Motor S/N E01
	c. Motor S/N E11

TABLES

1.	Instrument Summary and Measurement Uncertainty	55
2.	Summary of TE-M-640 Motor Performance	57
3.	Summary of TE-M-640 Motor Physical Dimensions	58

1.0 INTRODUCTION

The Thiokol, Inc., TE-M-640 rocket motor is designed for use as the propulsion unit for the fourth stage of the Scout launch vehicle (Ref. 1). The test program reported herein was conducted as a part of the qualification program for the TE-M-640 motor. The TE-M-640 motor is similar to the United Technology Center (UTC) FW-4S motor previously tested at the AEDC (Ref. 2). Both the UTC FW-4S and the Thiokol TE-M-640 motors carry the designation Altair III.

The initial scope of the TE-M-640 qualification program specified that a total of three motors be tested - one at the manufacturer's facility and two at the AEDC (Ref. 1).

Reported herein are the results of the three tests conducted at the AEDC, which include tests of two motors manufactured under initial processing procedures and the test of the third motor manufactured under revised processing procedures. The test objectives of this program were to evaluate the motor altitude ballistic performance and nonaxial (lateral) force and to demonstrate structural integrity of the TE-M-640 motor case and nozzle when fired while spinning about its axial centerline at 180 rpm.

The first test was successfully conducted at the manufacturer's facility in October 1972. The first two motors tested at the AEDC (S/N E02 fired on July 11, 1973, and S/N E01 fired on August 30, 1973) resulted in case failures in the aft dome. Investigation by representatives of Thiokol, LTV Aerospace Corp., and NASA/Langley Research Center (LRC), following the failure of motor S/N E02 in August 1973, revealed a possible failure mode resulting from mechanical failure of a repaired propellant void at the insulator-liner-propellant bondline in the nozzle port (Ref. 3). After the failure of the second motor at the AEDC (S/N E01), in August 1973, an extensive failure analysis review was conducted. Results from this investigation (Ref. 3) indicated the failure of both motors resulted from an anomaly in the aft insulator preparation and cure which contributed to a weak liner-to-propellant bond. Manufacturing processes were subsequently modified as follows: (1) thoroughly drying the insulated case assembly prior to liner application, (2) application of a liner wash coating to the insulation, and (3) increasing the thickness of the liner in the aft dome region from nominally 0.025 to 0.050 in.

Three motors were successfully tested after implementation of the revised processing procedures. Of these, two were tested at the manufacturer's facility, and one was tested at the Air Force Rocket Propulsion Laboratory. To complete the qualification program, it was required that one additional motor be tested at the AEDC (Ref. 4). Motor ignition characteristics, altitude ballistic performance, structural integrity of the motor case and nozzle, and nonaxial thrust data are presented and discussed for the three firings conducted at the AEDC. Ballistic data obtained are compared with the Model Specification Requirements (Ref. 5) where applicable.

2.0 APPARATUS

2.1 TEST ARTICLE

The Thiokol TE-M-640 solid-propellant rocket motor (Fig. 1) is 58.45 in. long and 19.67 in. in diameter. The 40.38-in.-long chamber is a filament-wound glass fiber and epoxy resin structure, nominally 0.08 in. thick with a 27-in.-long cylindrical-section and with ovaloid forward and aft domes which incorporate adapters of high strength aluminum. The domes terminate in aluminum polar bosses for igniter and nozzle installation. The chamber is filament-wound directly over a semi-destructible mandrel, which supports the silica-filled Buna-N[®] rubber insulator. The loaded motor weighs approximately 660 lbm, of which nominally 602 lbm is propellant. The composite propellant grain (TP-H-3062) is a case-bonded, transversely slotted, tube configuration (Fig. 1a). The liner thickness in the aft dome (Fig. 1c) was approximately 0.025 in. for the first two motors reported herein (S/N's E02 and E01) and 0.050 in. for the third motor (S/N E11). Nominal motor performance is: thrust 6000 lbf, chamber pressure, 750 psia, and action time, 29.8 sec.

The nozzle assembly (Fig. 1a) consists of a Graph-I-Tite[®] G-90 throat insert and a conical expansion cone structure of silica phenolic and graphite cloth phenolic, backed up with a stainless steel shell to provide structural rigidity. The graphite cloth is bonded to the silica phenolic over an area from the throat insert to an area ratio of 9:1. The nominal throat area is 4.3 in.^2 . The nominal area ratio is 50:1, and the expansion half-angle is 20 deg. The nozzle assembly is flanged and bolted to the motor aft polar boss.

Ignition was accomplished by a pyrogen igniter (Fig. 2), which contained 0.27 lbm of TP-3062M propellant. The igniter used one double-bridgewire SD60A-1, nominal 6-sec-delay squib to ignite a 5-gm BKNO₃ pellet charge, which initiated burning within the igniter. Two squib ports are available; however, only one squib was used. The second squib port was instrumented with a pyrogen pressure transducer; the igniter also contains two chamber pressure ports.

2.2 INSTALLATION

Each motor was cantilever mounted to the spindle face of a spin-fixture assembly in Propulsion Development Test Cell (T-3) (Ref. 6). The spin assembly was mounted on a thrust cradle, which was supported from the cradle support stand by three vertical and two horizontal double-flexure columns (Fig. 3). The spin fixture assembly consists of a 10-hp squirrel-cage-type drive motor, a thrust bearing assembly, a 46-in.-long spindle having a 36-in.-diam aft spindle face, and a 170-channel slip-ring assembly.

Each motor was rotated counterclockwise, looking upstream, during the firing. Electrical leads to and from the igniter, chamber pressure transducers, thermocouples, strain gages, and linear potentiometers were provided through the slip-ring assembly mounted between the forward and aft bearing assemblies on the spindle. Axial thrust was transmitted through the spindle-thrust bearing assembly to two load cells mounted just forward of the thrust bearing.

Preignition pressure altitude conditions were maintained in the test cell by a steam ejector operating in series with the ETF exhaust gas compressors. During the motor firing, the motor exhaust gases were used as the driving gas for the 32-in.-diam, ejector-diffuser system to maintain test cell pressure at an acceptable level.

2.3 INSTRUMENTATION

Instrumentation was provided to measure axial thrust, motor chamber pressure, motor pyrogen pressure, lateral force, aft dome strain, motor case axial (S/N E01) and circumferential (S/N E01, E11) movement, test cell pressure, motor case and nozzle temperatures, and motor rotational speed. Table 1 presents instrument ranges, recording methods, and an estimate of measurement uncertainty over the range of measurement for all reported parameters.

The axial thrust measuring system consisted of two double-bridge, strain-gage-type load cells mounted in series with the axial double-flexure column forward of the thrust bearing on the motor centerline. The lateral (nonaxial) force measuring system consisted of two double-bridge, strain-gage-type load cells installed forward and aft between the flexure-mounted cradle and the cradle support stand normal to the motor axial centerline and in the horizontal plane passing through the motor axial centerline (Fig. 3).

Bonded strain-gage-type transducers were used to measure motor chamber pressure (0 to 1000 and 0 to 15 psia) and pyrogen pressure (0 to 3000 psia). Chromel[®]-Alumel[®] (CA) thermocouples were used to measure motor chamber and nozzle temperatures during and after the motor burn time. The thermocouple locations are shown in Fig. 4a. Strain grids were bonded to the motor case on the aft dome to measure strain (deflection) during motor operation. Unbonded strain-gage-type transducers were used to measure test cell pressure. Motor rotational speed and angular orientation with time were determined from the output of a magnetic pickup. Linear potentiometers mounted to a support ring were attached to the aft surface of the motor to measure axial movement between aft dome and forward thrust ring (motor S/N E01, Figs. 4b and c); a single linear potentiometer was attached to the aft ring to measure relative "twist" (circumferential) between the aft thrust ring and the AEDC adapter (motor S/N's E01 and E11, Fig. 4b).

The output signal of each measuring device was recorded on independent instrumentation channels. Ballistic data were obtained from four axial thrust channels, three chamber pressure channels, two pyrogen pressure channels, and four test cell pressure channels. During the first two motor firings (S/N's E02 and E01), the signal from each instrument was indicated in totalized digital form on a visual readout of a millivolt-to-frequency converter. A magnetic tape system, recording in frequency form, stored the signal from the converter for reduction at a later time by an electronic digital computer. The computer provided a tabulation of average absolute values for each 0.10-sec time increment and total integrals over the cumulative time increments. During the test of the third motor (S/N E11), the output signal from each instrument was recorded on magnetic tape from a multi-input, analog-to-digital converter for reduction at a later time by an electronic digital computer. The latter method was also utilized to record output signals from the strain grids, linear potentiometers, nonaxial force, and motor thermocouples from all three motor firings. The ballistic parameters of motor (S/N E11) were recorded at 1248 samples per second. The strain grid, linear potentiometer, and motor thermocouple outputs were recorded for all three firings at 25 samples per second.

The output signal from the magnetic rotational speed pickup was recorded in the following manner: A frequency-to-analog converter was triggered by the pulse output from the magnetic pickup and in turn supplied a square wave of constant amplitude to the electronic counter and magnetic tape. The scan sequence of the electronic counter was adjusted so that it displayed directly the motor spin rate in revolutions per minute.

The millivolt outputs of the lateral force load cells were recorded on magnetic tape from a multi-input, analog-to-digital converter at a sampling rate of 2500 samples per second.

Selected channels of thrust and pressure were recorded on null-balance, potentiometer-type strip charts for analysis immediately after a motor firing. High-speed, motion-picture cameras provided a permanent visual record of the firings.

2.4 CALIBRATION

The thrust calibration weights, thrust load cells, and pressure transducers were laboratory calibrated prior to usage in this test. After installation of the measuring devices in the test cell, the systems were again calibrated at sea-level, nonspin, ambient conditions and again at simulated altitude conditions with the motor spinning at 180 rpm.

The pressure and lateral force recording systems were calibrated by an electrical, four-step calibration, using resistance in the transducer circuits to simulate selected pressure levels. The axial thrust instrumentation systems were calibrated by applying to the thrust cradle known forces, which were produced by deadweights acting through a bell crank. The calibrator is hydraulically actuated and remotely operated from the control room. Thermocouple recording instruments were calibrated by using known millivolt levels to simulate thermocouple outputs. The strain grids were calibrated by a one-step resistance calibration using resistance and gage factor data provided by the motor manufacturer. The linear potentiometers were in-place calibrated using gage blocks of a thickness approximating the expected operating range.

After the motor firing, with the test cell still at simulated altitude pressure, the recording systems were recalibrated to determine any shift.

3.0 **PROCEDURE**

The first two Thiokol TE-M-640 motors (S/N's E01 and E02) arrived at the AEDC on May 8, 1973; the third motor arrived on June 25, 1974 (S/N E11). Each motor was visually inspected for possible shipping damage and radiographically inspected for grain cracks, voids, or separations and found to meet criteria provided by the manufacturer. Each motor was temperature cycled three times between 30 and 110° F (48 hr at each temperature), S/N's E01 and E02 at the AEDC and S/N E11 at the manufacturer's facility. During storage in an area temperature conditioned at 75 ± 5°F, each motor was installed in the firing hardware. Before installation in the test cell, the motor assembly was temperature conditioned at 77 ± 5°F for a minimum of 40 hr.

After installation of each motor assembly in the test cell, the motor centerline was axially aligned with the spin axis by rotating the motor assembly and measuring the deflection of the nozzle throat flange and nozzle exit and making appropriate adjustments. Instrumentation connections were made, and each motor was balanced while spinning at 180 rpm. The initiator was installed in the igniter, and a continuity check of all electrical systems was performed. Prefire, sea-level calibrations were completed, and the test cell pressure was reduced to the desired altitude condition. Spinning of the motor was started, and after spinning had stabilized, a complete set of altitude calibrations was taken.

The final operation prior to firing was to adjust the circuit resistance and voltage to provide 10 amps to the igniter squib. The entire instrumentation measuring-recording complex was activated, and the motor was fired while spinning (under power) at 180 rpm. After motor tailoff for motor S/N E11, the spinning was maintained for 600 sec

while postfire temperature scans and altitude calibrations were accomplished (see Section 4.2 for discussion of motor operation for S/N's E01 and E02). Each motor was then decelerated slowly until rotation had stopped and each motor was inspected, photographed, and removed to the storage area. Postfire inspections consisted of measuring the nozzle throat and exit diameters (for motor S/N's E02 and E11), weighing each motor, and photographically recording the postfire condition of each motor.

4.0 RESULTS AND DISCUSSION

Three Thiokol, Inc., TE-M-640 solid-propellant rocket motors (S/N's E01, E02, and E11) were tested at simulated altitudes ranging from 100,000 to 111,000 ft while spinning about their axial centerlines at 180 rpm. The objectives of the qualification program were to determine motor altitude ballistic performance and the nonaxial (lateral) component of motor thrust and to demonstrate structural integrity of the motor when tested under the combined effects of rotational spin and near-vacuum environment at $77 \pm 5^{\circ}$ F. The first two motors tested at the AEDC (S/N's E02 and E01) resulted in case failures. An extensive failure analysis conducted by the test sponsor, user, and motor manufacturer revealed an anomaly in the aft insulator preparation and cure. Subsequent manufacturing modifications were made, and three successful tests were conducted prior to the third test at AEDC (S/N E11), which was also successful.

The resulting data are presented in both tabular and graphical form. Motor performance data are presented in Table 2, and motor physical dimensions are summarized in Table 3. Nonaxial thrust data are presented and discussed. Altitude ignition characteristics, ballistic performance, and structural integrity data are also presented. When multiple channels of equal accuracy instrumentation data were used to obtain values of a single parameter, the average values were used to calculate the data presented.

4.1 ALTITUDE IGNITION CHARACTERISTICS

The simulated altitude at ignition ranged from 119,000 to 123,000 ft. Ignition lag times (tg), the time interval from application of ignition voltage (t_o) to the first perceptible rise in chamber pressure (t_i), were 5.97, 5.91, and 5.77 sec for motor S/N's E02, E01, and E11, respectively. Ignition delay times (t_d), defined as the time interval from the first indication of pressure in the igniter until chamber pressure has risen to 90 percent of the maximum chamber pressure (P_{max}), were 0.150 sec (S/N E02), 0.137 sec (S/N E01), and 0.120 sec (S/N E11). These values are within the specified limits (Ref. 5) of from 0.071 to 0.165 sec. The variations of thrust, chamber pressure, and pyrogen pressure with time during ignition for each of the three firings are presented in Fig. 5.

AEDC-TR-74-125

4.2 BALLISTIC PERFORMANCE

4.2.1 Motor S/N E02

The first motor tested (S/N E02) experienced a case burnthrough at the aft dome approximately 27 sec into a predicted 32-sec burn time. The variations of thrust, chamber pressure, and test cell pressure during motor operation are shown in Fig. 6. Performance of the motor was normal for about the first 4 sec after ignition, after which the chamber pressure level increased approximately 20 percent higher than predicted, (Fig. 7) reaching a maximum of 919 psia at 12 sec after ignition. The chamber pressure rapidly decreased thereafter resulting in tailoff at 27 sec after ignition. Low-level burning (chuffing) continued from 27 until about 40 sec after ignition until all remaining propellant was consumed.

4.2.2 Motor S/N E01

The second motor tested (S/N E01) experienced an aft dome case failure about 8 sec into a predicted 32-sec burn time. The variations of thrust, chamber pressure, and test cell pressure during motor operation are shown in Fig. 8. The chamber pressure levels immediately after ignition were slightly higher than predicted and continued to increase above the predicted pressure (Fig. 9) until reaching a maximum level of 909 psia at 8 sec after ignition at which time burning abruptly terminated (see Fig. 10) leaving the remaining propellant intact. The nozzle assembly and motor aft dome were ejected from the motor at the time of the case failure.

4.2.3 Motor S/N E11

The third motor tested, which was manufactured utilizing a revised processing procedure, (see Section 1.0) performed satisfactorily.

The variations of thrust, chamber pressure, and test cell pressure with time are presented in Fig. 11.

Action time (t_a) , defined as the time interval between 10 percent of maximum chamber pressure during ignition and 10 percent of maximum chamber pressure during tailoff, was 29.81 sec, which falls within the specification limits (Ref. 5) of from 28.4 to 32.0 sec. Total burn time (t_s) , defined as the time interval between the first indication of chamber pressure during ignition and the time at which the ratio of chamber-to-cell pressure had decreased to 1.3 during tailoff, was approximately 32.9 sec. The time of nozzle flow breakdown (t_{bd}) , the time after ignition when exhaust diffuser flow breakdown occurs as indicated by an abrupt increase in cell pressure during tailoff, was 29.58 sec.

Since the nozzle does not operate fully expanded at the low chamber pressure encountered during tailoff, the measured total impulse data during the period cannot be corrected to vacuum conditions by adding the product of the test cell pressure integral and nozzle exit area. Therefore, total burn time and action time were segmented, and the method used to determine vacuum impulse is illustrated in Fig. 12. The exhaust nozzle flow breakdown was considered to have occurred simultaneously with the exhaust diffuser flow breakdown (as indicated by a rapid increase in cell pressure during tailoff). The flow at the nozzle throat was considered sonic until the ratio of chamber-to-cell pressure had decreased to a value of 1.3.

Vacuum total impulse (based on t_a) was 173,559 lbf-sec, which falls within the specification limits (Ref. 5) of from 171,600 to 174,020 lbf-sec. Vacuum total impulse (based on t_s) was 173,971 lbf-sec, and vacuum specific impulse (based on t_s and the manufacturer's stated propellant weight) was 288.94 lbf-sec/lbm.

4.3 STRUCTURAL INTEGRITY

4.3.1 Motor S/N E02

Postfire examination of the motor revealed a large burnthrough in the aft dome approximately 12 in. long and 5 in. wide (Fig. 13). Inspection revealed all propellant to have been consumed. Examination of temperature data for thermocouples located in the area of the failure (TC9 and TC10, Fig. 14) indicated no significant temperature increase prior to the time of the failure.

4.3.2 Motor S/N E01

Postfire examination of the motor revealed a complete case failure at the aft dome (Fig. 15). The aft dome and nozzle assembly was abruptly ejected from the motor at the time of the dome failure. Examination of the linear potentiometer data which measured the relative axial movement between the aft dome and the AEDC mounting adapter (Fig. 16) indicated an axial growth of 0.15 to 0.23 in. at the time of dome failure. As with motor S/N E02, the temperature data obtained from thermocouples located on the aft dome (TC9 and TC10) indicated no significant temperature increase prior to the failure. The exposed aft propellant surface remaining after the failure exhibited numerous depressions (Fig. 15) approximately 2 in. in diameter and 0.1 to 0.5 in. deep.

4.3.3 Motor S/N E11

Motor case and nozzle temperature variations with time are presented in Fig. 17. The Model Specification (Ref. 5) requires that the maximum case temperature not exceed 500°F between motor burnout and 200 sec after motor burnout. The maximum case temperature measured was 408°F, occurring at a position 17.4 in. aft from the forward adapter ring (TC6, Fig. 17c). The maximum measured nozzle temperature was 695°F, occurring 185 sec after ignition at a location 15.5 in. forward of the exit plane (TN12, Fig. 17g) at an area ratio of 7.

Postfire examination of the motor case and nozzle revealed structural integrity to be satisfactory. No case delaminations or discolorations were observed (Fig. 18).

Erosion of the nozzle during the firing produced a 14.3-percent increase in throat area and a 0.5-percent increase in exit area from the prefire measurements.

Examination of the circumferential linear potentiometer data (Fig. 19) indicates a relative "twist" between the motor aft thrust ring and AEDC mounting adapter to be about 0.005 to 0.006 in., measured counterclockwise, looking upstream.

4.4 NONAXIAL THRUST VECTOR MEASUREMENT

Measurement of the nonaxial (lateral) component of motor thrust was a primary objective of this test program. The recorded lateral thrust data were corrected for installation and/or electronic effects using the technique described in Ref. 7. The resulting data are presented in Fig. 20.

The maximum magnitude of nonaxial thrust recorded during the near steady-state portion of motor operation is listed below, together with the corresponding angular location and average values:

Motor S/N	E02	E01	E11
Maximum Magnitude	of		
Nonaxial Force, lbf	35	48	11
Angle at which Maxin	mum		
Force Occurred, deg	190	0	90
Average Magnitude of	2		
Nonaxial Force, lbf	22	40	5
Remarks	Motor failed 27 sec after ignition	Motor failed 8 sec after igni- tion	Successful Motor Operation

Based on pretest dynamic calibrations, the estimated uncertainty of the nonaxial force measurements during the near-steady state portion of motor S/N E11 operation is about ± 0.7 lbf.

5.0 SUMMARY OF RESULTS

Three Thiokol, Inc., TE-M-640 solid-propellant rocket motors were tested to determine motor altitude ballistic performance and the nonaxial thrust vector and to demonstrate the structural integrity of the motor case and nozzle under the combined effects of rotational spin and simulated altitude conditions while spinning about its axial centerline at 180 rpm. The results are summarized as follows:

- 1. The first two motors tested (S/N's E02 and E01) resulted in case failures in the aft dome. The third motor tested (S/N E11), manufactured using a revised process procedure, performed satisfactorily:
 - a. Motor S/N E02 experienced a burnthrough at the aft dome about 27 sec after ignition. Performance of the motor was normal for about the first 4 sec after ignition, after which the chamber pressure level increased approximately 20 percent higher than predicted, reaching a maximum of 919 psia at 12 sec after ignition. Low-level burning continued for about 13 sec following the failure until the remaining propellant was consumed.
 - b. Motor S/N E01 experienced a case failure at about 8 sec after ignition, resulting in detachment of the nozzle and aft dome. Abrupt termination of burning occurred, leaving approximately 433 lb of propellant remaining intact in the motor.
- 2. Postfire examination of motor S/N E11 revealed the motor case and nozzle structural integrity to be satisfactory.
- 3. The maximum motor case temperature measured at 200 sec following motor burnout was 408°F for motor S/N E11, which was below the specification maximum of 500°F.
- 4. The altitude ballistic performance of motor S/N E11 was within the specification limits:
 - a. Vacuum total impulse, based on t_a , was 173,559 lbf-sec, which was within the specification limits of from 171,600 to 174,020 lbf-sec. Vacuum total impulse based on t_s was 173,971 lbf-sec; there were no specified limits on this parameter.

t.

- b. Vacuum specific impulse, based on total burn time and the manufacturer's stated propellant weight, was 288.94 lbf-sec/lbm.
- c. Action time (t_a) , the time interval between 10 percent of maximum chamber pressure during ignition and 10 percent of maximum chamber pressure during tailoff, was 29.81 sec. This was within the specified limits of from 28.4 to 32.0 sec.
- d. Total burn time (t_s) , the interval between the first indication of chamber pressure during ignition and the time at which the ratio of chamber-to-cell pressure had decreased to 1.3 during tailoff, was 32.92 sec.
- 5. The maximum magnitude of nonaxial thrust recorded for motor S/N E11 during the near steady-state portion of motor operation was 11 lbf and occurred 2.5 sec after the first indication of chamber pressure. The average magnitude of the nonaxial thrust vector was about 5 lbf.
- 6. Ignition delay time, the time interval from first indication of chamber pressure until chamber pressure has risen to 90 percent of maximum, ranged from 0.120 to 0.150 sec for the three motors tested, which falls within the specified limits of from 0.71 to 0.165 sec.

REFERENCES

- 1. Test Plan 2360-198. "Qualification Tests for the TE-M-640 Altair III Rocket Motor." E13-73 - Rev. A, Thiokol, Inc., Elkton, Maryland, April 26, 1973.
- Merryman, H. L. "Performance of a UTC FW-4S Solid-Propellant Rocket Motor under the Combined Effects of Simulated Altitude and Rotational Spin." AEDC-TR-68-253 (AD844025), November 1968.
- 3. Interm Report Altair III Qualification Failure Analysis, Vol. II, Thiokol, Inc., Elkton, Maryland, October 3, 1973.
- 4. Test Plan Altair III Confirmation Test at the Arnold Engineering Development Center, LTV/VSD, Dallas, Texas, June 21, 1974.
- 5. Model Specification No. SC0104C Rocket Motor FW-4S, May 20, 1969.

.

- 6. <u>Test Facilities Handbook</u> (Tenth Edition). "Rocket Test Facility." Vol. 2, Arnold Engineering Development Center, May 1974.
- Nelius, M. A. and Harris, J. E. "Measurements of Nonaxial Forces Produced by Solid-Propellant Rocket Motors Using a Spin Technique." AEDC-TR-65-228 (AD474410), November, 1965.



a. Schematic Figure 1. Thiokol, Inc., TE-M-640 rocket motor.



b. Photograph Figure 1. Continued.



AEDC-TR-74-125



*Hercules Powder Company Part Number SD60A-1 Nominal 6-sec Delay Squib

Figure 2. TP-640 pyrogen igniter.



a. Schematic

Figure 3. Installation of TE-M-640 motor and spin assembly in Propulsion Development Test Cell (T-3).



b. Photograph Figure 3. Concluded.



a. Thermocouples Figure 4. Instrumentation locations.



b. Linear potentiometers Figure 4. Continued.





a. Motor S/N E02 Figure 5. Variation of thrust, chamber pressure, and pyrogen pressure during ignition.



b. Motor S/N E01 Figure 5. Continued.

•



c. Motor S/N E11 Figure 5. Concluded.



Figure 6. Variation of thrust, chamber pressure, and test cell pressure during testing of motor S/N E02.



Figure 7. Comparison of actual versus predicted chamber pressure variation with time for TE-M-640 motor S/N E02.

.

AEDC-TR-74-125



Figure 8. Variation of thrust and chamber pressure during failure of motor S/N E01.



Figure 9. Comparison of actual versus predicted chamber pressure variation with time for TE-M-640 motor S/N E01.

AEDC-TR-74-125



.

•

Figure 10. Variation of thrust, chamber pressure, and test cell pressure during failure of motor S/N E01.

. •

.



a. Variation of thrust, chamber pressure, and test cell pressure during testing of motor S/N E11 Figure 11. Performance of motor S/N E11.





established from data during the time interval from 24.5 to 25.5 sec after first indication of chamber pressure.

Figure 12. Definition of vacuum total and action impulse for motor S/N E11.



Figure 13. Postfire photograph of motor S/N E02.



Figure 14. Aft dome temperature variation with time during operation of motor S/N E02.





AEDC-TR-74-125



a. Potentiometer L1 Figure 16. Axial movement of aft dome relative to motor aft thrust ring for motor S/N E01.







c. Potentiometer L3 Figure 16. Concluded.





AEDC-TR-74-125

-



b. Cylindrical section opposite transverse propellant slot (TC4 and TC20) Figure 17. Continued.

.



,

45

. /





Figure 17. Continued.

46

.

~



.

e. Pyrogen case (TC15) Figure 17. Continued.



Figure 17. Continued.





Figure 18. Postfire photograph of motor S/N E11.



Figure 19. Relative circumferential movement between aft thrust ring and AEDC mounting adapter during motor operation (S/N E11).



Figure 20. Variation of nonaxial (lateral) force vector with time during motor operation.



.

.

b. Motor S/N E01 Figure 20. Continued.



c. Motor S/N E11 Figure 20. Concluded.

		STEAL	W-8	TATE ISTIN	TED MEASU	REMENT					
	Precision Index (8)			B1 (1	189 3)	Uncert ±(B +	tsinty tggS)				
Perimeter Designation	Perceot of Readiog	Unit of Measure- ment	Degree of Freedom	Percent of Reading	Usit of Memeure- Menure-	Percent of Rending	Unit of Xeesure-	Range	Type of Megeuring Device	iype or Recording Device	System Calibration
Axial Force, 1bf	±0.08		123	±0.03		±0,19		3000 to 7000 1bf	Bonded Strain-	Saquential Sampling, Millivolt-to-Digital Converter, and Mag-	In-Place Application of Deadweights Cali- brated in the
Total Impulse, lbf-sec	±0.07		31	±0.03		±0.17			Transducere	netic Tapé Storsge Dats Acquieition System	Standards Laboratory
Chamber Preceure, psia	±0.09		41	±0.07		±0.25		300 to 900 pais	Bonded Strein- Gage-Type Pres- sure Transducers		Recistance Shunt Based on the Standarde Lab- oratory Detarmination
Chamber Pressure, Integral, peis-nec	±0.08		31	±0.07		±0.23					of Transducer Applied Prenaure vernue Resis- tance Shunt Equivalant Pressure Blationship
Low-Range Chamber	±0.2		31	±0.5		±1 Note 1		0.5 to 15 peim			
Preenure, psia	±0.1		51	±0.2		±0.4 Note 2		15 to 50 peis	+	,	
Tent Cell Prsesure, pein	±0.2		39	±2,0		±2.4		0.05 to 0.8 peia	Unbonded Strain-		
Test Cell Prassure Intagral, peia-sec	±0.2		31	±2.0		±2.4			surs Transducers		↓ ↓
Relative Tangential Movement, in.		±0.002 in.	31		±0.001 in.		±0.005 in.	±0.05 in.	Rectilinesr Potentioneter	ł	In-Place Application of Multiple Gage Blocke Calibrated In the Standards Laboratory
Weight, 1bm		±0.015 1bm	31		±0.06 1bm		i0.1 1bm	800 to 1500 1bm	Beam-Bslance Scsles	Vieusl Readout	In-Pisce Application of Desdweights Calibrated in the Standardn Lab- oratory
Case Tempersture,"F		±0.25*7	100		±2.2°F		±2.7*F	70 to 450°7		Sequential Sampling, Willivolt-to-Digital	Millivolt Substitution Basnd on the NBS Tam-
Nozzie Temp. "F		10.25°F	100		±2.2*F		±2.7*F	70 to 530°F	Chromel-Alumsi Tempersture	Converter, and Mag- netic Tape Storage Data	peraturs versus Milli- volt Tablen
				±(0,25% +	0.9°F)	± (0.25% +	1.4°F)	530 to 700 F	Trangan al	UCANTALION DALAN	

Table 1. Instrument Summary and Measurement Uncertainty

*REFERENCE: CPIA No. 180. "ICRPG Handbook for Estimating the Uncertainty in Messeurementa made with Liquid Propellant Rocket Engine Systeme." (ADE55330), April 30, 1969. NOTES: 1. 15-psig full-scale transducer. 2. 50-psig full-scale transducer.

 \sim

Table 1. Concluded

		STEA	DY-ST	TATE ESTIM	ATED NEASU	REMENT*					
D	Precis	aion Index (S)		B: (1	Las B)	Uneer ±(B +	tainiy t95S)]		- 25 GH 1	
Parameter Designation	Percent of Resding	Unit of Masaure- ment	Degree of Freedom	Percent of Resding	Unit of Nessurs- ment	Percent of Reading	Unit of Measure- Ment	Range	Type of Measuring Deview	Type of Recording Device	Nethod of System Calibration
Pyrogen Pressura, psia -	±0.1		31	+0.2		±0.4		500 to 2000 pmin	Bonded Strain- Gage-Type Pressure Transducera	Sequential Sampling, Millivoli-io-Digiial Converier, and Magnaiie Tape Siorage	In-Place Application of Deadweights Cali- braied in the Standards Laboratory
Nozzle Strain µin./in.	±0,5		31	±9.		±10. Nots 3		1000 to 12,000 #in./in	Sirmin Grid	Data Acquigiiion Syaiem	Resiaiance Shuni Basec on the Manufacturer's Deiermination of Elongailon varsus Résisiance Changs
Lateral Thrust Vector Magnitude, lbf		±0.25 1bf	31		±0.2 151		±0.7 1bf	1.5 to 12 1bf	Bonded Strain- Gage-Type Force Transducare		In-Place Application of Multiple Force Levela Measured with Force Transducere in the Standards Laboratory

NOTES: 3. Uncertainty Estimates Based on Experience with Systems Similar io iboac Furnished by User.

.

.

•

Specification

				Limits ⁸
Test Number R41C-04A (RA30?)	01	02	03	
Motor Ssrial Number	E02	E01	E11	
Tsst Dats	7/11/73	8/30/73	7/12/74	
Averags Motor Case Temperature at Ignition, "F	93	85	76	
Ignition Lag Tims (tg) ¹ , sec	5.97	5.91	5, 72	
Ignition Delsy Time (t _d) ²	0, 150	0. 137	0, 120	0.071 to 0.165
Action Time (ta) ³ , sec	*	**	29, 81	28, 4 to 32, 0
Time of Nozzle Flow Breakdown (tbd) ⁴	*	**	29, 58	
Total Burn Time ⁵ , time interval that nozzle throat flow was sonic {t _g }, sec	*	**	32, 92	
Simulated Altitude at Ignition, ft	119,000	122,000	123,000	
Average Simulated Altitude during t _a , ft	٠	**	105,000	
Maximum Vacuum Thrust, 1bf	7529	7295	6889	
Maximum Chamber Pressure, psia	919	909	832	
Measured Total Impulss (based on t _{bd}), lbf-sec Avarage of Four Channels of Data Maximum (hannel Deutstion from Avarage	*	**	172, 372	
percent	-	-	0.01	
Chambar Pressurs Integral (based on t _{bd}), psia-ssc Average of Two Channels of Data Maximum Channel Devistion from Average,	•	**	20, 640	
percant	-	-	0.08	
Cell Pressure Integral (based on t _{bd}), psia-sec Average of Two Channels of Data Maximum Channel Deviation from Averags,	٠	**	3,890	
percent	-	-	0.11	
Chamber Pressure Integral, psia-sec from t _{bd} to t _s	•	**	86, 9	
Vacuum Total Impulse (based on ta), 1bf-sec		**	173, 559	171,600 to 174,020
Vacuum Total Impulse (based on tg), lbf-sec	*	**	173, 971	
Vacuum Specific Impulse (based on t _a), lbf-sec/lbm - Based on Manufacturar's Stated Propellant				
Wsight	*	**	288, 26	
Based on Expended Mass (AEDC)	*	**	286, 54	
Vacuum Specific Impulse (based on tg), lbf-sec/lbm Bassd on Manufacturer's Stated Propellant				
Weight Based on Expended Mass (AEDC)	*	**	288, 94	
Average Vacuum Thrust Coefficient. Cr	CA.			
Based on ta and Average Pre- and Postfire				
Throat Arcas	*	**	1.834	
Maximum Case Temperature, "F	*	**	408	<500°F (at 200 sec from motor burnout)

Table 2. Summary of TE-M-640 Motor Performance

¹Defined as the time interval from application of ignition voltage (t_0) to the first perceptible rise in chamber pressure (q). ²Defined as the time interval from the first indication of chamber pressure until chamber pressure has

risen to 90 percent of maximum.

³Defined as the time interval beginning when chamber pressure increases to 10 percent of maximum chamber pressure at ignition and ending when chamber pressure has fallen to 10 percent of maximum chamber pressure

during tailoff. ⁴Defined as the time after ignition where exhaust diffuser flow breakdown occurs, as indicated by an abrupt

increase in cell pressure during tailoff. ⁵Defined as the time interval between the first indication of chamber pressure at ignition and the time at which the ratio of chamber-to-cell pressure has discreased to 1.3 during tailoff, ⁶Model Specification No. SC0104C, May 20, 1969, Rocket Motor FW-4S.

*Motor case failure occurred 27 sec after ignition.

**Motor case failure occurred 8 sec after ignition.

Table 3. Summary of TE-M-640 Motor Physical Dimensions

Test Number	01	02	03
Motor Serial Number	E-02	E-01	E-11
Test Date	7/11/73	8/30/73	7/12/74
AEDC Prefire Motor Weight ¹ , 1bm	1419.37	1403.27	1486.66
AEDC Postfire Motor Weight ¹ , 1bm	806.04*	1233.27**	880.95
AEDC Expended Mass, 1bm	613.33*	170.00**	605.71
Manufacturer's Stated Propellant Weight, 1bm	601.9	603.7	602.1
Nozzle Throat Area, In. ² Prefire Postfire Percent Change from Prefire	4.272 4.721 +10.51	4.267 ** **	4.271 4.883 +14.3
Nozzle Exit Area, in. ² Prefire Postfire Percent Change from Prefire	215.02 215.50 +0.2	215.85 ** **	215.21 216.26 +0.5
Prefire Nozzle Area Ratio	50.33	50.59	50.39

¹Weight Includes 822.1 lbm for AEDC Firing Harness, Pressure Transducers, Instrumentation, etc.

*Motor case burnthrough resulted in loss of case material.

٩.,

**Motor case failure resulted in loss of nozzle assembly and aft dome.

.