

DEPARTMENT OF THE NAVY

NAVAL UNDERSEA WARFARE CENTER DIVISION 1176 HOWELL STREET NEWPORT RI 02841-1708

IN REPLY REFER TO:

Attorney Docket No. 82867 Date: 22 November 2004

The below identified patent application is available for licensing. Requests for information should be addressed to:

PATENT COUNSEL NAVAL UNDERSEA WARFARE CENTER 1176 HOWELL ST. CODE 00OC, BLDG. 112T NEWPORT, RI 02841

Serial Number 10/816,484

Filing Date 2 April 2004

Inventor Thomas J. Gieseke

If you have any questions please contact Michael P. Stanley, Patent Counsel, at 401-832-4736.

This Document Contains Missing Page/s That Are Unavailable In The Original Document DISTRIBUTION STATEMENT A Approved for Public Release Distribution Unlimited

20041221 227

Attorney Docket No. 82867 Customer No. 23523

INLET FREE TORPEDO LAUNCH SYSTEM

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT THOMAS J. GIESEKE, citizen of the United States of America, employee of the United States Government, resident of Newport, County of Newport, State of Rhode Island, has invented certain new and useful improvements entitled as set forth above of which the following is a specification:

MICHAEL P. STANLEY Reg. No. 47108 Naval Undersea Warfare Center Division, Newport Newport, RI 02841-1708 TEL: 401-832-4736 FAX: 401-832-1231

1	Attorney Docket No. 82876
2	
3	INLET FREE TORPEDO LAUNCH SYSTEM
4	
5	STATEMENT OF GOVERNMENT INTEREST
6	. The invention described herein may be manufactured and
7	used by or for the Government of the United States of America
8	for governmental purposes without the payment of any royalties
9	thereon or therefor.
10	
11	BACKGROUND OF THE INVENTION
12	(1) Field of the Invention
13	The invention generally relates to a launch system and
14	more particularly to a launcher which eliminates the need for
15	an inlet door for a supply of fluid for launch by using an
16	alternatively configured fluid flow.
17	(2) Description of the Prior Art
18	The current art for torpedo launch systems with a
19	pressurizing pump have a "U" configuration where one end of
20	the "U" is a flow intake, the bottom of the "U" contains the
21	pump, and the other end of the "U" is the torpedo tube. To
22	operate, the intake end of the launch system includes a large
23	and complex hydraulically actuated door.
24	A prior art turbine pump ejection system (TPES) 100 is
25	shown, by way of example, in FIG. 1 of the drawings. The
26	turbine pump ejection system 100 includes an inlet door 102
27	opening to an inlet recess 104. The inlet recess 104 supplies

seawater as the system fluid to an inlet cylinder 106 as a
 result of a turbine pump 108 drawing seawater into the inlet
 cylinder and pumping seawater into an impulse tank 110,
 through a slide valve 112, down a torpedo tube 114, through a
 shutterway recess 116, and out of the platform via a primary
 shutterway 118.

7 In operation, the inlet door 102, the slide valve 112,
8 the primary shutterway 118 and a secondary shutterway 120 are
9 opened to create an open flow path through the launch system
10 100.

Prior to launch, the pressure in the inlet recess 104 and the pressure in the shutterway recess 116 each independently increase to some fraction of the available dynamic head, as a result of forward motion of the system through the ocean. Any imbalance between the pressure in the inlet recess 112 and the shutterway recess 116 causes fluid in the launch system, and any device in the torpedo tube 114, to move.

18 When a launch is initiated, the turbine pump 108 begins to rotate and fluid is drawn though the inlet door 102, the 19 20 inlet recess 104, the inlet cylinder 106 and into the turbine pump 108. The turbine pump 108 pumps fluid into the impulse 21 22 tank 110, through the slide valve 112, down the torpedo tube 114 carrying the weapon in the torpedo tube through the 23 shutterway recess 116 and out of the system 100 via the 24 25 primary shutterway 118.

26 The following reference, for example, discloses an27 external fluid intake apart from the operating launch tube,

but does not disclose an internally circulating fluid path
 which eliminates an inlet door.

3 Wosak (U.S. Patent No. 2,837,971) discloses hydraulic ejection equipment for missiles. Specifically, the reference 4 5 discloses a system having a water-filled cylinder 6 communicating at one end with the sea and communicating at its 7 other end, through ports in its walls and a passageway or conduit, with the aft end of a missile ejector tube whose fore 8 or discharge end communicates with the sea. A piston is 9 10 mounted for reciprocating movement in the water cylinder with the piston is connected to a suitable driving mechanism for 11 12 moving the piston from its retracted position to force water 13 ahead of the piston through the ports in the forward end of the water cylinder though the conduit connecting those ports 14 15 with the aft end of the missile ejector tube thereby to charge the water into the ejector tube and behind the missile in the 16 tube and in a sufficient amount and with sufficient force to 17 expel the missile from the tube with a force and velocity. 18

19 It should be understood that the present invention would 20 in fact enhance the functionality of the launching systems by 21 providing a launcher design which eliminates the need for an 22 intake door.

- 23
- 24

SUMMARY OF THE INVENTION

Accordingly, it is a general purpose and primary object
of the present invention to provide a launcher system with a
fluid intake door eliminated as a component of the launcher.

It is a further object of the present invention to
 provide a launcher system which provides a common path for
 fluid intake and vehicle exit.

4 It is a still further object of the present invention to
5 provide a launcher which corrects reverse fluid flow in
6 existing systems.

7 In accordance with one aspect of the present invention, there is provided an inlet free launcher system including an 8 inlet recess in fluid communication with a shutterway recess. 9 10 A primary shutterway is provided both for ejection of a vehicle and for supplying fluid intake to the system. A pump 11 12 selectively circulates fluid from the inlet recess to the 13 shutterway recess, and a launch tube houses the vehicle, such as a weapon, within the system prior to launch thereof. A 14 15 slide valve and impulse tank combination are positioned 16 intermediate the pump and the launch tube, such that the slide valve controls a flow of fluid to the launch tube. A guide 17 18 can is positioned in the shutterway recess for guiding the 19 vehicle from the launch tube to an exterior of the launcher 20 and fluid within the system is continually moderated to enable selective launch of the vehicle with a fluid force. 21

- 22
- 23

BRIEF DESCRIPTION OF THE DRAWINGS

The appended claims particularly point out and distinctly
claim the subject matter of this invention. The various
objects, advantages and novel features of this invention will
be more fully apparent from a reading of the following

detailed description in conjunction with the accompanying 1 2 drawings in which like reference numerals refer to like parts, 3 and in which: 4 FIG. 1 is a schematic of a prior art turbine pump ejection system for launching a device; 5 6 FIG. 2 is a schematic of a launcher for an underwater 7 environment according to a preferred embodiment of the present 8 invention; 9 FIG. 3 is a schematic of Phases 1 and 2 of a launch 10 operation of the launcher of the present invention; 11 FIG. 4 is a schematic of Phase 3 of the launch operation 12 by the launcher of the present invention; 13 FIG. 5 is a schematic of Phase 4 of the launch operation 14 by the preferred embodiment of the present invention; FIG. 6 is a schematic of Phase 5 of the launch operation 15 16 by the preferred embodiment of the present invention; 17 FIG. 7 is a graph relating pump speed and flow rates in 18 support of the present invention; 19 FIG. 8 is a graph relating performance of pump head and 20 time in support of the present invention; 21 FIG. 9 is a graph showing parameters associated with a 22 launchable vehicle entering a guide can of the launcher of the 23 present invention; and 24 FIG. 10 is a graph depicting a comparison of base-line 25 system performance of the prior art and modified system 26 performance of the launcher of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

1

2	In general, the present invention eliminates the need for
3	a conventional intake door by utilizing a D-shaped launcher 10
4	as shown in FIG. 2. The launcher 10 is referred to;
5	hereinafter, as a shutterway intake launcher (SIL) because the
6	fluid intake and the exit for a torpedo or an unmanned vehicle
7	share the same communication path with the ambient underwater
8	environment.
9	In further description, the overall structure of the
10	shutterway intake launcher 10 includes an inlet recess 12
11	having recess communication holes 14 formed in a wall thereof.
12	The inlet recess 12 supplies fluid to an inlet cylinder 16
13	upon actuation of a pump 18. The pump 18 pumps the fluid into

an impulse tank 20, through a slide valve 22, down a launch
tube 24, through a shutterway recess 26 and through a primary
shutterway 28. A secondary shutterway is shown as component
30 in fluid communication with the other component of the
launcher 10.

The recess communication holes 14 penetrate a wall of the 19 20 inlet recess 12 which defines a corresponding wall 31 of the shutterway recess 26 such that the shutterway intake launcher 21 22 10 relies on the intake of fluid through either the primary shutterway 28 or the open secondary shutterway 30 due to the 23 absence of an inlet door in the inlet recess 12. In other 24 25 words and as will be described below, fluid collected in the shutterway recess 26 is supplied to the inlet recess 12 via 26 27 the recess communication holes 14.

By way of general understanding, the launch tube 24 is
 the back of the "D" and the loop of the "D" is a re circulating water path containing the pump 18. In effect, the
 fluid intake and vehicle or torpedo exit share the same
 communication path with the ambient environment.

Several aspects of the invention have been examined using
analytical and numerical techniques. Of primary interest is
the impact of added mass and loss to the existing flow system.
Based on the calculated results, it is estimated that there
will be minimal changes to the operation of the turbine pump
18 and the basic dynamics of torpedo launch will be unaffected
by the proposed system changes.

13 Continuing with the description, the shutterway intake 14 launcher 10 operates by the intake of fluid through either the 15 operating launch tube (primary shutterway 28) or the open 16 second shutterway 30 to compensate for the loss of fluid flow due to the absence of an inlet door. Furthermore, the 17 18 shutterway intake launcher 10 operates largely free from prelaunch reverse flow (the system can be pressure-balanced as 19 20 much as is possible without eliminating leakage flow), such 21 that the launcher does not require an inlet door.

The functioning and operation of the shutterway intake
launcher 10 is largely controlled by several performance
related phenomenon. These phenomenon include changes in
performance of the turbine pump 18 as a result of flow-path
changes; effectiveness of pressure balancing due to a closed
system operation; launch transient changes as a result of

flow-path changes; changes in launch dynamics as a result of
 launch jet elimination; and changes in flex hose cable
 dynamics as a result of flow path changes.

The first four of the above phenomena are addressed by 4 5 formulating a launch system performance model using first 6 principle hydrodynamics concepts. The governing equations for 7 such a model are: conservation of mass, applied at each location where flow streams converge; Newton's equation of 8 9 motion applied for each fluid mass; Darcy's equation for flow 10 loss applied across each flow restriction; Newton's equation 11 of motion applied for the motion of the vehicle; and an 12 experimental model for transient pump performance.

Although some simplifications are made regarding forces
during these transient launch phases, they serve as a primary
model for the shutterway intake launcher 10.

FIGS. 3 through 6 illustrate the phases of the launch process including positioning of a vehicle 32, such as a weapon, within the launch tube 24. The arrowheaded lines in the figures indicate a flow of fluid through the shutterway intake launcher 10, while the sequence bubbles correspond to the equations below.

Phases 1 and 2 are shown in FIG. 3. Phase 1 is the prelaunch phase of the operation of the shutterway intake launcher 10. During the pre-launch phase, the pump 18 is not actuated but the entire flow path is open. A dynamic head recovered in the shutterway recess 26 drives fluid through the launcher 10. Under these conditions, the pump 18 serves as a

flow restriction and is not a source of energy. Other than
 this slight deviation, the system operates identically as it
 does in Phase 2 (description to follow) until the weapon 32
 contacts the aft end of the torpedo tube or moves forward out
 of the launch tube 24.

6 Phase 2 is the initial acceleration of the vehicle 32. During this phase of the launch operation, the turbine pump 18 7 (see FIG. 2) begins to increase speed. The head developed by 8 9 the pump 18 is a function of the speed, the flow rate and the transient operating characteristics of the pump. FIGS. 7 and 8 10 show the performance of the pump 18 as compared to known 11 12 parameters. FIGS. 7 and 8 are reflective as a guide to the 13 head of the pump 18 versus speed input to the launch operation which determines the relationship between the pressure at 14 points of the inlet cylinder 16 and the impulse tank 20. 15 16 In Equation (1), two fluid paths are considered. One 17 path is directly from the launch tube 24 to the guide can 34 18 and one from the launch tube 24 to the shutterway recess 26 19 and then back to the launch tube 24.

20

 $\frac{dQ_{4,6}}{dt} + \frac{dQ_{5,6}}{dt} = \frac{dQ_{6,10}}{dt} + - \frac{d^2V_6}{dt^2}$

(1)

Conservation of mass is applied in the shutterway recess
26, and in the inlet recess 12. The rate of volume change
(dV) of the shutterway recess 26 is equal to the flow (Q) out
of the launch tube 24 and into the shutterway recess 26, less
the flow out of the shutterway recess 26 and into the inlet

recess 12 and the flow out of the shutterway recess 26 through
 the two open shutterways, i.e.:

3

5

18

 $Q_{4,5} = Q_{5,6} + Q_{5,1} + Q_{5,8} + Q_{5,9} - \frac{dV_5}{dt}$

(2)

4 or in differential form

$$\frac{dQ}{4,5} \Big|_{dt} = \frac{dQ_{5,6}}{dt} + \frac{dQ_{5,1}}{dt} + \frac{dQ_{5,8}}{dt} + \frac{dQ_{5,9}}{dt} - \frac{d^2 V_5}{dt^2}$$
(3)

6 The rate of volume change (dV) of the shutterway recess 26 is incorporated to account for motion of the vehicle 32 out 7 of the shutterway recess 26 and into a guide can 34. 8 The rate . 9 of volume change may also be used to incorporate accumulator effects in the cavity. Leakage to other non-pressure hull 10 11 regions in the forward end of the ship has been included. Conservation of mass must also be addressed in the guide can 12 13 34.

14 The flow at the intake of the pump 18 is equal to the sum 15 of the flow through the inlet recess 12 and from the 16 shutterway recess 26. In differential form this can be 17 expressed:

$$\frac{dQ_{1,2}}{dt} = \frac{dQ_{6,1}}{dt} + \frac{dQ_{5,1}}{dt} + \frac{dQ_{5,1}}{dt} - \frac{d^2V_1}{dt^2}$$
(4)

19 The differential form, Equations (1) and (4), is useful20 when relating the flow rates to flow accelerations.

Flow through each portion of the shutterway intake
launcher is controlled by the pressure (P) acting over that
portion, the mass in the respective portion, and the loss
through the portion. It can be shown that the flow rate (Q)

1 from a starting point (A) to an end point (B) can be expressed 2 as:

15

$$P_{A} - P_{B} - \frac{k_{A,B}\rho}{2A^{2}} Q_{A,B}^{2} \left[\frac{Q_{A,B}}{\left\| Q_{A,B} \right\|} \right] - \frac{l_{A,B}\rho}{A} \frac{dQ_{A,B}}{dt} = 0$$
(5)

(P) is the pressure with the third term in this 5 expression being the flow loss, which includes a loss 6 coefficient k, the flow area A and the fluid density ρ . The 7 fourth term is the flow acceleration, which includes the effective section length l, the flow area, and the fluid 8 9 density. If the pipe sections between points A and B contain 10 sections with different flow areas, effective loss and mass 11 terms can be incorporated into Equation (5). The effective 12 loss K_{A.B} is given by

13
$$K_{A,B} = \sum_{i=1,N} \frac{k_i \rho}{2A_i^2}$$
 (6)

(7)

14 and the effective mass L_{AB} is given by

$$L_{A,B} = \sum_{i=1,N} \frac{l_i \rho}{A_i}$$

16 Although Equations (6) and (7) are not standard 17 expressions for loss and effective mass, they are useful forms 18 for the current modeling effort. Equation (5) can be modified 19 to include the effects of hull curvature and pressure recovery 20[.] by adjusting the pressures as appropriate. The recovered pressure P_R and hull pressure distribution is included through 21 adjustment of the ambient pressures P_{∞} using 22 $P_{R} = P_{\infty} + \frac{1}{2} \rho U_{b}^{2} (C_{R} + C_{P} - C_{R} C_{P})$ 23 (8)

1 where U_b is the boat speed and where the pressure recovery 2 coefficient C_R and pressure coefficient C_p vary between the 3 inlet recess 12 and shutterway recess 26. For simplicity of 4 modeling, it is assumed that this pressure acts along the 5 surface of the submarine hull.

6 If the instantaneous flow rates are known, the seven flow 7 acceleration equations are generated using Equation (5), the three conservation of mass equations, Equations (1), (2) and 8 9 (4), and the pump performance functions (derived from FIGS. 7 10 and 8), form a set of equations which can be solved for the 11 five unknown pressures and five unknown flow accelerations at a specific time during the launch transient. With the flow 12 accelerations expressed in terms of the flow rates and 13 14 pressures, the equations can be numerically integrated to 15 develop a time history of internal pressures and flow rates 16 during a launch.

17 A matrix formulation of the problem, Ax = B, is as follows 18 on the successive pages:

3 Many of the loss coefficients and effective masses were4 derived using two design reports prepared by J. Schwemin of

NUWC in 1987. These reports are listed below and incorporated
 by reference.

Schwemin, J.A., "Comparison of Launcher System Flow Loss
Coefficients for NUSC Land Based Test Facility (Full Size
Impulse Tank) and SSN 21 Actual Ship Condition", Naval
Undersea Systems Center, July 1987; and

7 Schwemin, J.A., "Comparison of Launcher System Water
8 Masses for NUSC Land Based Test Facility (Full Size Impulse
9 Tank) and SSN 21 Actual Ship Condition", Naval Undersea
10 Systems Center, July 1987.

11 The losses which were not taken from this report were the losses from the shutterway recess 26 to the inlet recess 12, 12 13 the loss from the launch tube 24 to the shutterway recess 26, 14 the loss from the shutterway recess 26 to the guide can 34 with a vehicle 32 passing through an inlet of the guide can 15 16 34, the leakage resistance from the shutterway recess 26 to 17 ambient, and the loss from the inlet recess 12 to the ambient 18 when the inlet door was shut/removed. All losses were 19 referenced to a 21-inch diameter flow area.

20 One determination of the present invention is the 21 assessment of the sensitivity of the shutterway intake 22 launcher 10 to variations in the launcher loss coefficient. Consequently, the losses initially selected for the present 23 24 invention serve as a design point only. The sensitivity of the performance of the shutterway intake launcher 10 to 25 changes about the design point will drive further advances and 26 27 modifications to the invention.

Phase 3, as shown in FIG. 4, is the initial device exit
 from the launch tube 24.

As the vehicle 32 begins to exit the launch tube 24, the effective mass of the section from the point of the launch tube 24 to the point of the shutterway recess 26 (FIG. 2.) begins to increase. To correct for this dynamic change, the first element in the 7th row of the matrix in Equation (9) should be changed to read:

 $A_{7,1} = L_{4,5} + \rho \, \delta /_{A}$

(10)

10 where A is the area and L is the length and δ is the distance 11 which the vehicle protrudes from the launch tube 24.

12 The effective loss from the launch tube 24 to the 13 shutterway recess 26 drops significantly during Phase 3 of the 14 launch because there is no longer a sudden expansion of fluid. 15 The drag on the nose of the protruding vehicle 32 produces a 16 pressure drop of approximately one fourth of the sudden 17 expansion losses.

18 The conservation of mass equations remain unchanged as 19 the flow from the launch tube 24 is exactly matched by the 20 displacement of the emerging vehicle 32.

Phase 4 is the motion of the vehicle 32 into the guide can 34 and is shown in FIG. 5. As the nose of the vehicle 32 leaves the shutterway recess 26 and enters the guide-can 34, rapid changes in the flow of the fluid in the shutterway intake launcher 10 must be accounted for through the conservation of mass equations.

As in Phase 3 of the launch operation, the effective mass
 of fluid between the launch tube 24 and the shutterway recess
 26 continues to increase as the vehicle 32 travels through the
 launch tube 24. Equation 9 remains applicable during this
 phase of the launch operation.

6 The flow of fluid through the launch tube 24 to the shutterway recess 26 is now governed by the pressure 7 difference between the launch tube 24 and the guide can 34 and 8 the dynamic head produced by the motion of the vehicle 32. 9 10 The pressure at the guide can 34 includes the effects of ship 11 motion, shutterway pressure recovery, and transients of the 12 shutterway intake launcher 10. The loads which arise due to 13 motion of the vehicle 32 can be approximated using an effective drag coefficient of 0.25 and the internal flow rate 14 15 of the launcher 10 to determine the vehicle speed.

16 The flow of fluid through the primary shutterway 28 is
17 still driven by the pressure drop across that opening.
18 However, the loss through that opening is increased
19 substantially as a result of the presence of the exiting
20 vehicle 32 as is the effective mass of the fluid in that
21 region.

FIG. 9 shows the measurable geometry of the launch operation as the vehicle 32 enters the primary shutterway 28. Initially, the loss coefficient varies with the square of the effective annular area $(A_0 - A(s))$. As the vehicle 32 moves further into the guide can 34, an added loss proportional to the penetration depth of the vehicle (s) must be added.

The conservation of mass equations for the shutterway 28 1 2 are modified to account for the motion of the vehicle 32. As 3 the vehicle 32 approaches and begins to enter the guide can 34, fluid is displaced from the primary shutterway 28. 4 The fluid is either displaced into the shutterway recess 26 5 6 directly or flows along a path external to the ship and then 7 enters the shutterway recess 26 via the secondary shutterway 28 as a leakage path or another leakage path. This fluid 8 9 displacement or external flow takes place in a very short time 10 and can result in unwanted acceleration of the vehicle 32. 11 Equation 3 can be modified through the second derivative of the volume term to account for this acceleration. 12

13

The volume flux into the recesses can be described using

(11)

(12)

14

15 and

16 $\mathring{V}_{5} = (A_{i} - A(s))\frac{ds}{dt}$

 $\mathring{V}_6 = A(s)\frac{ds}{dt}$

17 The derivative of the rate of the volume flux is related18 to the velocity of the vehicle 32 by

19
$$-\frac{d^2 V_5}{dt^2} + A_t \frac{d^2 s}{dt^2} = \frac{d^2 V_6}{dt^2} = \frac{ds}{dt} \frac{dA(s)}{dt} + A(s) \frac{d^2 s}{dt^2}$$
(13)

20 where ds/dt is the velocity. Because the acceleration of the
21 vehicle 32 is coupled to the pressures and flow rates of the
22 shutterway intake launcher 10, (Equation 13) must be
23 incorporated in the matrix solution (Equation 9). Suitably
24 formulated equations are

3

$$\frac{d^2 V_6}{dt^2} = \frac{A(s)}{A_{12}} \frac{dQ_{12}}{dt} + \frac{Q_{12}^2}{A_{12}^2} \frac{dA}{ds}$$

$$\frac{d^2 V_5}{dt^2} = \frac{\left(A_t - A(s)\right)}{A_{12}} \frac{dQ_{1,2}}{dt} - \frac{Q_{1,2}^2}{A_{1,2}^2} \frac{dA}{ds}$$
(15)

For this preliminary analysis, a 90 degree cone was
assumed for the vehicle nose shape (to simplify calculation of
A(s)).

7 Phase 5 is the motion of the vehicle 32 out of the guide 8 can 34 and is shown in FIG. 6. Once the vehicle 32 has cleared the end of the launch tube 24, the dynamics of the 9 launcher 10 revert to the dynamics of Phase 2 between the 10 11 launch tube 24 and the shutterway recess 26. At this point, 12 the motion dynamics of the vehicle 32 is no longer directly 13 coupled with the internal flow of the launch system 10. The vehicle 32 decelerates based on the pressure difference 14 between the external flow and the shutterway recess 26. 15 Phase 6 is the weapon clear and is not illustrated. 16 As the vehicle 32 navigates the guide can 34 and the primary 17 shutterway 28, additional transients are expected. However, 18 due to the large areas and volumes at the exit of the primary 19 20 shutterway 28, these transients will be ignored. The motion 21 of the vehicle 32 is assumed to be uncoupled from the dynamics of the shutterway intake launcher 10 during this phase of the 22 23 launching operation.

FIG. 10 depicts a comparison of the predicted transientlaunch velocities for both the base-line configuration based

18

(14)

on the prior art of FIG. 1 and for the modified configuration
 of the shutterway intake launcher 10 shown in FIG. 2. The
 most significant system performance change is the transients
 generated as the vehicle 32 exits the tube. These transients
 are the result of the assumed behavior of the jet of fluid
 which precedes the vehicle 32.

7 Preliminary calculations regarding the shutterway intake 8 launcher 10 indicate a similar tube exit velocity for both the 9 baseline and modified systems. Added flow losses associated 10 with the operation of the shutterway intake launcher 10 are 11 small.

During operation of the shutterway intake launcher 10, the effective mass of the system is less than the effective mass of the system during an open loop operation. The waterhammer effect as the vehicle 32 enters the shutterway 28 can produce large accelerations and pressure transients in the shutterway intake launcher 10.

Because of the transient effects as the vehicle 32 enters the shutterway 28, either a means to reduce the added mass of the guide can 34 must be found or a depth independent accumulator system must be added to the shutterway intake launcher 10.

The added mass associated with the shutterway 28 can be reduced by either increasing the area of the inlet recess 12 or by shortening the path from the external flow to the shutterway recess 26. The path can be reduced by machining holes somewhere in the boundary between the shutterway recess

26 and the external flow. Holes already incorporated into the
 shutterways to reduce pressure recovery may provide the mass
 reduction needed.

4 The advantages of the shutterway intake launch system 10
5 include a solution to the reverse-flow problem, and the
6 provision of a pressure-balanced system.

7 Alternatives to the concept presented herein include: An 8 inlet door as a part of a launcher system with the lowest tubes in the submarine torpedo banks isolated from the upper 9 10 tubes and also connected to the inlet chamber. As such the 11 upper tubes can operate in a standard fashion (drawing water 12 through the inlet door) and the lower tubes can be operated as 13 the shutterway intake launcher concept. Further, an accumulator can be added to the system to eliminate any water 14 15 hammer effects.

16 This invention has been disclosed in terms of certain 17 embodiments. It will be apparent that many modifications can 18 be made to the disclosed apparatus without departing from the 19 invention. Therefore, it is the intent of the appended claims 20 to cover all such variations and modifications as come within 21 the true spirit and scope of this invention.

1	Attorney Docket No. 82867
2	
3	INLET FREE TORPEDO LAUNCH SYSTEM
4	
5	ABSTRACT OF THE DISCLOSURE
6	A launcher for torpedoes and underwater vehicles includes
7	an inlet recess in fluid communication with a shutterway
. 8	recess. A primary shutterway is provided both for ejection of
9	the vehicle and for supplying fluid intake to the launcher. A
10	pump circulates fluid from the inlet recess to the shutterway
11	recess, and a launch tube houses a vehicle such as a weapon,
12	within the launcher prior to launch thereof. A slide valve
13	and impulse tank combination are positioned intermediate the
14	pump and the launch tube, such that the slide valve controls a
15	flow of fluid to the launch tube. A guide can is positioned
16	at the shutterway recess for guiding the vehicle from the
17	launch tube to an exterior of the launcher and fluid within
18	the launcher is continually moderated to enable selective
19	launch of the vehicle with a fluid force.







FIG. 3



FIG. 4



FIG. 5







